

RF EXPOSURE REPORT

for

Shenzhen Chaoyue Technology Development Co.,Ltd.

Model Number: M500

FCC ID: 2ATKM-M500

Prepared for : Shenzhen Chaoyue Technology Development Co.,Ltd.
Building C, Zhiyun Industrial Park, No.13 Huaxing Tongsheng
Address : Community, Dalang Street, Longhua District, Shenzhen,China

Prepared by : MAXLAB Testing Co.,Ltd.
1/F, Building B, Xinshidai GR Park,Shiyan Street, Bao'an District,
Address : Shenzhen,Guangdong, 518052, People' s Republic of China

1. RF EXPOSURE EVALUATION

Test Result of RF Exposure Evaluation

According to the KDB-447498 D01 V06, FCC 47CFR § 2.1093 the following RF exposure evaluation shall to demonstrate RF exposure compliance.

$$\left[\frac{\text{(max. power of channel, including tune-up tolerance, mW)}}{\text{(min. test separation distance, mm)}} \right]$$

$$* [\sqrt{f(\text{GHz})}]$$

2.4G WIFI

Frequency (MHz)	Antenna port	Target power W/ tolerance (dBm)	Max tune up power tolerance (dBm)	Maximum Conducted Output Power (mW)	Separation distance mm	RF exposure
2462	ANT1	8.518±1.0	9.518	8.949525	5	2.808497

The Max RF exposure is 2.808497.

Threshold at which no SAR required is ≤ 3.0 for 1-g SAR, Separation distance is 5mm.