

FCC RF Exposure

Applicant : SOUNDLAB TECHNOLOGY CO.,LTD
Address : No. 6-2, Shangxia Middle Road, Shangxia Area, Dongjiang
Science Park, Zhongkai High-tech Zone, Huizhou
Product Name : Soundbar
Brand Mark : nxtechnologies
Model : NXBAR2.1
Series model : SL200
FCC ID : 2ATKO-SL200A
Report Number : BLA-EMC-202512-A1902
Date of Receipt : Dec. 03, 2025
Date of Test : Dec. 03, 2025 to Dec. 31, 2025
47 CFR Part 15, Part1.1307
Test Standard : 47 CFR Part 15, Part2.1091
KDB447498D04 General RF Exposure Guidance v01
Test Result : Pass

Compiled by: Mark Chen

Review by: Xavier

Approved by:

Issued Date: Jul. 27, 2026



BlueAsia Technical Services(Shenzhen) Co.,Ltd.

Address: No.41, South of Beihuan Road, Shangwu Community, Shiyan Subdistrict, Bao'an District, Shenzhen, Guangdong, China



The test report is effective only with both signature and specialized stamp and The result(s) shown in this report refer only to the sample(s) tested. Without written approval of BlueAsia, this report can't be reproduced except in full. The results described in this report do not represent the quality or characteristics of the sampled batch, nor do they represent any similar or identical products that are not explicitly stated.

Table of Contents

1 General information	4
1.1 General information	4
1.2 General description of EUT	4
2 RF Exposure Compliance Requirement	5
2.1 Standard Requirement	5
2.2 Limits	5
2.3 Result	6

Revise Record

Version No.	Date	Description
01	Jul. 27, 2026	Original

1 General information

1.1 General information

Applicant	SOUNDLAB TECHNOLOGY CO.,LTD
Address	No. 6-2, Shangxia Middle Road, Shangxia Area, Dongjiang Science Park, Zhongkai High-tech Zone, Huizhou
Manufacturer	SOUNDLAB TECHNOLOGY CO.,LTD
Address	No. 6-2, Shangxia Middle Road, Shangxia Area, Dongjiang Science Park, Zhongkai High-tech Zone, Huizhou
Factory	SOUNDLAB TECHNOLOGY CO.,LTD
Address	No. 6-2, Shangxia Middle Road, Shangxia Area, Dongjiang Science Park, Zhongkai High-tech Zone, Huizhou

1.2 General description of EUT

Product name	Soundbar
Model no.	NXBAR2.1
Series model no.	SL200
Differences of Series model	Their electrical circuit design layout, components used and internal wiring are identical, Only the model name are different.
Operation Frequency	2402MHz-2480MHz
Modulation Type	GFSK, $\pi/4$ -DQPSK, 8DPSK
Number of Channels	79
Antenna Type	PCB Antenna
Antenna Gain	1.51dBi (Provided by customer)
Power supply	100-240V, 50/60Hz 1.8A MAX
Test Voltage	AC 120V
Hardware Version	N/A
Software Version	N/A

2 RF Exposure Compliance Requirement

2.1 Standard Requirement

According to 447498 D04 Interim General RF Exposure Guidance v01

Standalone SAR test exclusion considerations

Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Exclusion Threshold condition, listed below, is satisfied.

2.2 Limits

$$P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}} (d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases} \quad (\text{B. 2})$$

where

$$x = -\log_{10} \left(\frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right)$$

and f is in GHz, d is the separation distance (cm), and $ERP_{20 \text{ cm}}$ is per Formula (B.1).

Example values shown in Table B.2 are for illustration only.

Table B.2—Example Power Thresholds (mW)

Frequency (MHz)	Distance (mm)										
		5	10	15	20	25	30	35	40	45	50
	300	39	65	88	110	129	148	166	184	201	217
	450	22	44	67	89	112	135	158	180	203	226
	835	9	25	44	66	90	116	145	175	207	240
	1900	3	12	26	44	66	92	122	157	195	236
	2450	3	10	22	38	59	83	111	143	179	219
	3600	2	8	18	32	49	71	96	125	158	195
	5800	1	6	14	25	40	58	80	106	136	169

$$P_{th} \text{ (mW)} = ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases} \quad (\text{B. 1})$$

2.3 Result

$$\text{EIRP} = \text{pt} \times \text{gt} = (\text{E} \times \text{d})^{2/30}$$

Where:

pt = transmitter output power in watts,

gt = numeric gain of the transmitting antenna (unitless),

E = electric field strength in V/m,

d = measurement distance in meters (m)

$$\text{Spot} = (\text{E} \times \text{d})^{2/30} \times \text{gt}$$

Separation distance= 20cm

Ant gain = 1.51dBi

For BT Classic(8DPSK):

Max Output power = 3.017dBm @ 2402MHz

$$\text{EIRP} = 3.017\text{dBm} + 1.51\text{dBi} = 4.527\text{dBm},$$

$$\text{So, ERP} = 4.527\text{dBm} - 2.15 = 2.377\text{dBm} = 1.729\text{mW} < 3060 \text{ mW}$$

Comply with RF exposure exemption limit.

----END OF REPORT----

The test report is effective only with both signature and specialized stamp, the result(s) shown in this report refer only to the sample(s) tested. Without written approval of BlueAsia, this report can't be reproduced except in full.