7. Radio Frequency Exposure

7.1 Applicable Standards

The measurements shown in this test report were made in accordance with the procedures given in FCC Part 2 (Section 2.1091)

KDB 447498
IEEE C95.1:2005

7.2 EUT Specification

Frequency band (Operating)	902MHz ~ 928MHz
Device category	☐ Portable (<20cm separation) ☒ Mobile (>20cm separation)
Exposure classification	☐ Occupational/Controlled exposure ☒ General Population/Uncontrolled exposure
Antenna diversity	☒ Single antenna ☐ Multiple antennas ☐ Tx diversity ☐ Rx diversity ☐ Tx/Rx diversity
Evaluation applied	☒ MPE Evaluation* ☐ SAR Evaluation ☐ N/A

Remark:

1. *The maximum Fundamental Emission is 107dBuV/m at 915MHz (with 3dbi antenna gain.)*
2. *DTS device is not subject to routine RF evaluation; MPE estimate is used to justify the compliance.*
3. *For mobile or fixed location transmitters, no SAR consideration applied. The maximum power density is 1.0 mW/cm^2 even if the calculation indicates that the power density would be larger.*

7.3 Test Results

No non-compliance noted.

7.4 Calculation

Given $E = \frac{\sqrt{30 \times P \times G}}{d}$ & $S = \frac{E^2}{3770}$

Where *E = Field strength in Volts / meter*

P = Power in Watts
G = Numeric antenna gain

d = Distance in meters

S = Power density in milliwatts / square centimeter

Combining equations and re-arranging the terms to express the distance as a function of the remaining variables yields:

$$S = \frac{30 \times P \times G}{3770 d^2}$$

Changing to units of mW and cm, using:

P (mW) = P (W) / 1000 and
d (cm) = d(m) / 100

Yields

$$S = \frac{30 \times (P/1000) \times G}{3770 \times (d/100)^2} = 0.0796 \times \frac{P \times G}{d^2}$$

Where *d = Distance in cm*
P = Power in mW
G = Numeric antenna gain
S = Power density in mW / cm^2

7.5 Maximum Permissible Exposure

Antenna Gain (dBi)	Antenna Gain (linear)	distance (m)	Fundamental Emission (dBuV/m)	Fundamental Emission (V/m)	Fundamental Emission (W)	Fundamental Emission (dBm)
3	1.9952	3	107	0.223872	0.03	14.77

Fundamental Emission (dBm)	Antenna Gain(dBi)	Distance (cm)	Power Density (mW/cm^2)	Limit (mW/cm^2)
14.77	3	20	0.01191	0.6013