13. Radio Frequency Exposure

13.1 Applicable Standards

The measurements shown in this test report were made in accordance with the procedures given in FCC Part 2 (Section 2.1093)

LIMIT

KDB 447498 D01 § 4.3(a)
For 100 MHz to 6 GHz and test separation distances ≤ 50 mm, the 1-g and 10-g SAR test exclusion thresholds are determined by the following:
[(max. power of channel, including tune-up tolerance, mW) / (min. test separation distance, mm)] · [√f(GHz)] ≤ 3.0 for 1-g SAR, and ≤ 7.5 for 10-g extremity SAR, where

*f(GHz) is the RF channel transmit frequency in GHz
* Power and distance are rounded to the nearest mW and mm before calculation
*The result is rounded to one decimal place for comparison
*The values 3.0 and 7.5 are referred to as numeric thresholds in step b) below

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm, and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm according to 4.1 f) is applied to determine SAR test exclusion

13.2 EUT Specification

Frequency band (Operating)	902MHz~928MHz
Device category	☒ Portable (<20cm separation) ☐ Mobile (>20cm separation)
Exposure classification	☐ Occupational/Controlled exposure ☒ General Population/Uncontrolled exposure
Antenna diversity	☒ Single antenna ☐ Multiple antennas ☐ Tx diversity ☐ Rx diversity ☐ Tx/Rx diversity
Evaluation applied	☐ MPE Evaluation* ☒ SAR Evaluation ☐ N/A
Remark: *1. The maximum conducted output power is 9.76dBm (9.462mW) at 926.76MHz (with 4dBi antenna gain.)* *2. DTS device is not subject to routine RF evaluation; MPE estimate is used to justify the compliance.* *3. For mobile or fixed location transmitters, no SAR consideration applied.*	

**Note: Simultaneous transmission is not applicable for this EUT.*

13.3 Test Results

According to the KDB447498:

The SAR test exclusion thresholds Level:

[(max. power of channel, including tune-up tolerance, mW) /(min. test separation distance, mm)] * sqrt (freq. in GHz) < 3

Calculation

Channel Frequency (MHz)	Max. Conducted output power(dBm)	Max. Tune up power (dBm)	Max. Tune up power (mW)	Distance (mm)	SAR test exclusion thresholds (mW)
903.24	7.37	9.37	8.65	5	16.00
914.76	8.63	10.63	11.56	5	16.00
926.76	9.76	11.76	15.00	5	16.00

Since the source-based time-averaging conducted output power is well below the SAR low threshold level, so the EUT is considered to comply with SAR requirement without testing

----------THE END OF REPORT----------