

TEST REPORT

Product Name : Bluetooth Module

Model Number : JK21M1

FCC ID : 2ATOGJK21M1

Prepared for : GUANGDONG ICECO ENTERPRISE CO., LTD.
Address : 23 Health Rd., National Health Technology Park, Torch
Development Zone, Zhongshan, Guangdong, China

Prepared by : EMTEK (SHENZHEN) CO., LTD.
Address : Building 69, Majialong Industry Zone, Nanshan District,
Shenzhen, Guangdong, China

TEL:(0755) 26954280

FAX:(0755) 26954282

Report Number : ENS2509170213W00202R
Date of sample receipt : Nov 29, 2024
Date(s) of Tests : Nov 29, 2024 to Apr 07, 2025
Date of issue : Apr 08, 2025

Table of Contents

1. TEST RESULT CERTIFICATION	3
2. EUT SPECIFICATION	5
3. TEST REQUIREMENT	6
4. MEASUREMENT RESULT	7



1. TEST RESULT CERTIFICATION

Applicant : GUANGDONG ICECO ENTERPRISE CO., LTD.
Address : 23 Health Rd., National Health Technology Park, Torch Development Zone, Zhongshan, Guangdong, China
Manufacturer : GUANGDONG ICECO ENTERPRISE CO., LTD.
Address : 23 Health Rd., National Health Technology Park, Torch Development Zone, Zhongshan, Guangdong, China
Factory : GUANGDONG ICECO ENTERPRISE CO., LTD.
Address : 23 Health Rd., National Health Technology Park, Torch Development Zone, Zhongshan, Guangdong, China
EUT : Bluetooth Module
Model Name : JK21M1
Trademark : ICECO, SetPower

Measurement Procedure Used:

APPLICABLE STANDARDS	
STANDARD	TEST RESULT
§ 15.247(i), § 2.1093	PASS

The above equipment was tested by EMTEK (SHENZHEN) CO., LTD. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.10 (2013) and the energy emitted by the sample EUT tested as described in this report is in compliance with the requirements of FCC Rules FCC § 15.247(i), § 2.1093.

The test results of this report relate only to the tested sample identified in this report

Date of Test : Nov 29, 2024 to Apr 07, 2025

Prepared by : 
Una Yu /Editor

Reviewer : 
Joe Xia/Supervisor

Approve & Authorized Signer : 
Lisa Wang/Manager



Modified History

Version	Report No.	Revision Date	Summary
	ENS2509170213W00202R	/	Original Report



2. EUT Specification

Characteristics	Description
Product:	Bluetooth Module
Model Number:	JK21M1
Sample:	1#
Data Rate:	1Mbps for GFSK modulation 2Mbps for GFSK modulation
Modulation:	GFSK(1M) GFSK(2M)
Operating Frequency Range(s) :	2402-2480MHz
Number of Channels:	40 channels
Transmit Power Max:	-0.75 dBm(0.000841 W)
Antenna Gain:	2.338 dBi
Power supply:	DC 3.3V
Evaluation applied:	☐ MPE Evaluation ☒ SAR Evaluation

3. Test Requirement

SAR Evaluation

According to 447498 D01 V06, systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at *test separation distances* ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot$

$[\sqrt{f_{(\text{GHz})}}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR,²⁴ where

- $f_{(\text{GHz})}$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation²⁵
- The result is rounded to one decimal place for comparison
- 3.0 and 7.5 are referred to as the numeric thresholds in the step 2 below

The test exclusions are applicable only when the minimum *test separation distance* is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum *test separation distance* is < 5 mm, a distance of 5 mm according to 5) in section 4.1 is applied to determine SAR test exclusion.

Routine SAR evaluation refers to that specifically required by § 2.1093, using measurements or computer simulation. When routine SAR evaluation is not required, portable transmitters with output power greater than the applicable low threshold require SAR evaluation to qualify for TCB approval. One antenna is available for the EUT. The minimum separation distance is 5mm.

4. Measurement Result

Antenna gain: 2.338 dBi

Transmit Frequency (MHz)	Mode	Measured Power (dBm)	EIRP (dBm)	Tune upPower (dBm)	Max tune up power (dBm)	Calculation Result	1-g SAR
2402	GFSK (1M)	-1.31	1.028	1±1	2	0.4913	3
2440	GFSK (1M)	-1.29	1.048	1±1	2	0.4951	3
2480	GFSK (1M)	-0.97	1.368	1±1	2	0.4992	3
2402	GFSK (2M)	-1.13	1.208	1±1	2	0.4913	3
2440	GFSK (2M)	-1.19	1.148	1±1	2	0.4951	3
2480	GFSK (2M)	-0.75	1.588	1±1	2	0.4992	3

According to KDB 447498 D01 V06, no stand-alone required for BT antenna, and no simultaneous SAR measurement is required.

*** End of Report ***