



RF Exposure Evaluation

FOR

34ED LLC

Centegix Integration Gateway

Test Model: CE-INT-04

Prepared for : 34ED LLC
Address : 2500 Cumberland Parkway, Ste 300, Atlanta, GA 30339, United States

Prepared by : Shenzhen LCS Compliance Testing Laboratory Ltd.
Address : 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China
Tel : (+86)755-82591330
Fax : (+86)755-82591332
Web : www.LCS-cert.com
Mail : webmaster@LCS-cert.com

Date of receipt of test sample : March 09, 2026
Number of tested samples : 2
Sample No. : A260303056-1, A260303056-2
Serial number : Prototype
Date of Test : March 09, 2026 ~ April 02, 2026
Date of Report : April 03, 2026



**RF Exposure Evaluation****Report Reference No. : LCSA03046085EF**

Date of Issue..... : April 03, 2026

Testing Laboratory Name : Shenzhen LCS Compliance Testing Laboratory Ltd.Address..... : 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei,
Shajing Street, Baoan District, Shenzhen, 518000, ChinaTesting Location/ Procedure : Full application of Harmonised standards ■
Partial application of Harmonised standards □
Other standard testing method □**Applicant's Name : 34ED LLC**

Address..... : 2500 Cumberland Parkway, Ste 300, Atlanta, GA 30339, United States

Test SpecificationStandard : FCC KDB publication 447498 D01 General RF Exposure Guidance v06
FCC CFR 47 part1 1.1310
FCC CFR 47 part2 2.1091

Test Report Form No..... : TRF-4-E-214 A/0

TRF Originator : Shenzhen LCS Compliance Testing Laboratory Ltd.

Master TRF : Dated 2011-03

Shenzhen LCS Compliance Testing Laboratory Ltd. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen LCS Compliance Testing Laboratory Ltd. is acknowledged as copyright owner and source of the material. Shenzhen LCS Compliance Testing Laboratory Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

Test Item Description..... : Centegix Integration Gateway

Trade Mark : Centegix

Test Model : CE-INT-04

Ratings..... : Please Refer to Page 6

Result : Pass**Compiled by:**

Vera Deng/ Administrator

Supervised by:

Kevin Huang/ RF Manager

Approved by:

Gavin Liang/ Manager



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



RF Exposure Evaluation

Test Report No. : LCSA03046085EF	<u>April 03, 2026</u> Date of issue
---	--

Test Model.....	: CE-INT-04
EUT.....	: Centegix Integration Gateway
Applicant.....	: 34ED LLC
Address.....	: 2500 Cumberland Parkway, Ste 300, Atlanta, GA 30339, United States
Telephone.....	: /
Fax.....	: /
Manufacturer.....	: Shenzhen jinhaichuang Electronics Co., Ltd
Address.....	: A808, SoJIA Science Park complex building, No. 7, hanghang Road, Hangcheng street, Bao'an District, Shenzhen, Guangdong Province
Telephone.....	: /
Fax.....	: /
Factory.....	: Shenzhen jinhaichuang Electronics Co., Ltd
Address.....	: A808, SoJIA Science Park complex building, No. 7, hanghang Road, Hangcheng street, Bao'an District, Shenzhen, Guangdong Province
Telephone.....	: /
Fax.....	: /

Test Result	Pass
--------------------	-------------

The test report merely corresponds to the test sample.

It is not permitted to copy extracts of these test result without the written permission of the test laboratory.





Revision History

Report Version	Issue Date	Revision Content	Revised By
000	April 03, 2026	Initial Issue	---





TABLE OF CONTENTS

Description	Page
1. Product Information.....	6
2. Evaluation Method	8
3. Limit	8
4. MPE Calculation Method	9
5. Conducted Power.....	9
6. Manufacturing Tolerance	10
7. Measurement Results	14
8. Conclusion.....	15
9. Description of Test Facility.....	15
10.Measurement Uncertainty.....	16





1. Product Information

EUT	: Centegix Integration Gateway
Test Model	: CE-INT-04
Ratings	: Input: DC 12V, 3A
Hardware Version	: /
Software Version	: /
Bluetooth	:
Frequency Range	: 2402MHz~2480MHz
Channel Number	: 79 channels for Bluetooth V5.0 (DSS) 40 channels for Bluetooth V5.0 (DTS)
Channel Spacing	: 1MHz for Bluetooth V5.0 (DSS) 2MHz for Bluetooth V5.0 (DTS)
Modulation Type	: GFSK, $\pi/4$ -DQPSK, 8-DPSK for Bluetooth V5.0 (DSS) GFSK for Bluetooth V5.0 (DTS)
Bluetooth Version	: V5.0
Antenna Description	: External Antenna, 3.23dBi(Max.)
WIFI(2.4G Band)	:
Frequency Range	: 2412MHz~2462MHz
Channel Spacing	: 5MHz
Channel Number	: 11 Channels for 20MHz bandwidth (2412~2462MHz) 7 Channels for 40MHz bandwidth (2422~2452MHz)
Modulation Type	: IEEE 802.11b: DSSS (CCK, DQPSK, DBPSK) IEEE 802.11g: OFDM (64QAM, 16QAM, QPSK, BPSK) IEEE 802.11n: OFDM (64QAM, 16QAM, QPSK, BPSK)
Antenna Description	: External Antenna, 3.23dBi(Max.)
WIFI(5.2G Band)	:
Frequency Range	: 5180MHz~5240MHz
Channel Number	: 4 Channels for 20MHz bandwidth(5180MHz~5240MHz) 2 channels for 40MHz bandwidth(5190MHz~5230MHz) 1 channels for 80MHz bandwidth(5210MHz)
Modulation Type	: IEEE 802.11a: OFDM (64QAM, 16QAM, QPSK, BPSK) IEEE 802.11n: OFDM (64QAM, 16QAM, QPSK, BPSK) IEEE 802.11ac: OFDM (256QAM, 64QAM, 16QAM, QPSK, BPSK)
Antenna Description	: External Antenna, 2.31dBi(Max.)
WIFI(5.8G Band)	:
Frequency Range	: 5745MHz~5825MHz
Channel Number	: 5 channels for 20MHz bandwidth(5745MHz~5825MHz) 2 channels for 40MHz bandwidth(5755MHz~5795MHz) 1 channels for 80MHz bandwidth(5775MHz)
Modulation Type	: IEEE 802.11a: OFDM (64QAM, 16QAM, QPSK, BPSK) IEEE 802.11n: OFDM (64QAM, 16QAM, QPSK, BPSK) IEEE 802.11ac: OFDM (256QAM, 64QAM, 16QAM, QPSK, BPSK)
Antenna Description	: External Antenna, 2.31dBi(Max.)
2G	:
Support Band	: ☒ GSM 850 (U.S.-Band)





☒ PCS 1900
Type Of Modulation : GMSK for GSM/GPRS; GMSK/8PSK for EGPRS
Antenna Description : External Antenna
1.8dBi (max.) For GSM 850
2.5dBi (max.) For PCS 1900

3G :
Support Band : ☒ WCDMA Band II
☒ WCDMA Band IV
☒ WCDMA Band V

Type Of Modulation : BPSK, QPSK, 16QAM
Antenna Description : External Antenna
2.5dBi (max.) For WCDMA Band II
2.5dBi (max.) For WCDMA Band IV
1.8dBi (max.) For WCDMA Band V

LTE :
Support Band : ☒ E-UTRA Band 2
☒ E-UTRA Band 4
☒ E-UTRA Band 5
☒ E-UTRA Band 7
☒ E-UTRA Band 12
☒ E-UTRA Band 13
☒ E-UTRA Band 17
☒ E-UTRA Band 25
☒ E-UTRA Band 26
☒ E-UTRA Band 41
☒ E-UTRA Band 66

Type Of Modulation : QPSK/16QAM
Antenna Description : External Antenna
2.5dBi(max.) For E-UTRA Band 2
2.5dBi(max.) For E-UTRA Band 4
1.8dBi(max.) For E-UTRA Band 5
3.9dBi(max.) For E-UTRA Band 7
1.8dBi(max.) For E-UTRA Band 12
1.8dBi(max.) For E-UTRA Band 13
1.8dBi(max.) For E-UTRA Band 17
2.5dBi(max.) For E-UTRA Band 25
1.8dBi(max.) For E-UTRA Band 26
3.9dBi(max.) For E-UTRA Band 41
2.5dBi(max.) For E-UTRA Band 66

EUT Type : Production Unit

Device Type : Mobile Device

Note: For a more detailed antenna description, please refer to the antenna specifications or the antenna report provided by the customer.





2. Evaluation Method

Systems operating under the provisions of FCC 47 CFR section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as mobile device whereby a distance of 0.2m normally can be maintained between the user and the device, and below RF Permissible Exposure limit shall comply with.

In accordance with KDB447498D01 for Simultaneous transmission MPE test exclusion applies when the sum of the MPE ratios for all simultaneous transmitting antennas incorporated in a host device, based on the calculated/estimated, numerically modelled or measured field strengths or power density, is ≤ 1.0 . The MPE ratio of each antenna is determined at the minimum test separation distance required by the operating configurations and exposure conditions of the host device, according to the ratio of field strengths or power density to MPE limit, at the test frequency. Either the maximum peak or spatially averaged results from measurements or numerical simulations may be used to determine the MPE ratios. Spatial averaging does not apply when MPE is estimated using simple calculations based on far-field plane-wave equivalent conditions. The antenna installation and operating requirements for the host device must meet the minimum test separation distances required by all antennas, in both standalone and simultaneous transmission operations, to satisfy compliance.

3. Limit

3.1 Refer Evaluation Method

[ANSI C95.1-2019](#): IEEE Standard for Safety Levels with Respect to Human Exposure to Electric, Magnetic, and Electromagnetic Fields, 0 Hz to 300 GHz

[FCC KDB publication 447498 D01 General 1 RF Exposure Guidance v06](#): Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies.

[FCC CFR 47 part1 1.1310](#): Radiofrequency radiation exposure limits.

[FCC CFR 47 part2 2.1091](#): Radiofrequency radiation exposure evaluation: mobile devices.

3.2 Limit

Limits for Maximum Permissible Exposure (MPE)/Controlled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm ²)	Averaging Time (minute)
Limits for Occupational/Controlled Exposure				
0.3 – 3.0	614	1.63	(100) *	6
3.0 – 30	1842/f	4.89/f	(900/f ²)*	6
30 – 300	61.4	0.163	1.0	6
300 – 1500	/	/	f/300	6
1500 – 100,000	/	/	5	6

Limits for Maximum Permissible Exposure (MPE)/Uncontrolled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm ²)	Averaging Time (minute)
Limits for Occupational/Uncontrolled Exposure				
0.3 – 3.0	614	1.63	(100) *	30
3.0 – 30	824/f	2.19/f	(180/f ²)*	30
30 – 300	27.5	0.073	0.2	30
300 – 1500	/	/	f/1500	30
1500 – 100,000	/	/	1.0	30

F=frequency in MHz

*=Plane-wave equivalent power density



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



4. MPE Calculation Method

Predication of MPE limit at a given distance

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = PG / 4\pi R^2$$

Where: S=power density

P=power input to antenna

G=power gain of the antenna in the direction of interest relative to an isotropic radiator

R=distance to the center of radiation of the antenna

5. Conducted Power

[BT]

Mode	Channel	Frequency (MHz)	Peak Conducted Output Power (dBm)
GFSK	0	2402	-1.35
	39	2441	1.37
	79	2480	0.16
$\pi/4$ -DQPSK	0	2402	0.39
	39	2441	2.88
	79	2480	1.79
8-DPSK	0	2402	0.83
	39	2441	3.25
	79	2480	2.12

[BLE]

Mode	Channel	Frequency (MHz)	Peak Conducted Output Power (dBm)
BLE 1M	0	2402	3.05
	19	2440	5.47
	39	2480	4.41

[2.4G WIFI]

Mode	Channel	Frequency (MHz)	Conducted Output Power (dBm)
11B	1	2412	13.99
	6	2437	13.77
	11	2462	13.21
11G	1	2412	13.29
	6	2437	13.2
	11	2462	12.69
11N20 SISO	1	2412	10.95
	6	2437	10.36
	11	2462	10.17
11N40 SISO	3	2412	13.82
	6	2437	10.52
	9	2462	11.24



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



[5.2G WIFI]

Mode	Channel	Frequency (MHz)	Max Conducted Power(dBm)
11A	36	5180	11.23
	40	5200	11.26
	48	5240	12.06
11N20 SISO	36	5180	10.82
	40	5200	10.91
	48	5240	11.62
11N40 SISO	38	5190	10.89
	46	5230	11.4
11AC20 SISO	36	5180	10.81
	40	5200	10.82
	48	5240	11.6
11AC40 SISO	38	5190	10.8
	46	5230	11.37
11AC80 SISO	42	5210	10.44

[5.8G WIFI]

Mode	Channel	Frequency (MHz)	Max Conducted Power(dBm)
11A	149	5745	13.27
	157	5785	13.75
	165	5825	13.91
11N20 SISO	149	5745	13.76
	157	5785	14.26
	165	5825	14.22
11N40 SISO	151	5755	13.85
	159	5795	14.22
11AC20 SISO	149	5745	13.56
	157	5785	14.14
	165	5825	14.24
11AC40 SISO	151	5755	13.86
	159	5795	14.64
11AC80 SISO	155	5775	14.64

6. Manufacturing Tolerance

[BT]

GFSK (Peak)			
Channel	Channel 0	Channel 39	Channel 78
Target (dBm)	-1.0	1.0	0
Tolerance ±(dB)	1.0	1.0	1.0
π/4DQPSK (Peak)			
Channel	Channel 0	Channel 39	Channel 78
Target (dBm)	0	2.0	1.0
Tolerance ±(dB)	1.0	1.0	1.0
8DPSK (Peak)			
Channel	Channel 0	Channel 19	Channel 39
Target (dBm)	0	3.0	2.0
Tolerance ±(dB)	1.0	1.0	1.0





[BLE]

GFSK (Peak)			
Channel	Channel 0	Channel 19	Channel 39
Target (dBm)	3.0	5.0	4.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0

[2.4G WIFI]

11B (Average)			
Channel	Channel 1	Channel 6	Channel 11
Target (dBm)	13.0	13.0	13.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11G (Average)			
Channel	Channel 1	Channel 6	Channel 11
Target (dBm)	13.0	13.0	12.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11N20 (Average)			
Channel	Channel 1	Channel 6	Channel 11
Target (dBm)	10.0	10.0	10.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11N40 (Average)			
Channel	Channel 3	Channel 6	Channel 9
Target (dBm)	13.0	10.0	11.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0

[5.2G WIFI]

11A (Average)			
Channel	Channel 36	Channel 40	Channel 48
Target (dBm)	11.0	11.0	12.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11N20 (Average)			
Channel	Channel 36	Channel 40	Channel 48
Target (dBm)	10.0	10.0	11.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11N40 (Average)			
Channel	Channel 38	Channel 46	
Target (dBm)	10.0	11.0	
Tolerance $\pm$ (dB)	1.0	1.0	
11AC20 (Average)			
Channel	Channel 36	Channel 40	Channel 48
Target (dBm)	10.0	10.0	11.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11AC40 (Average)			
Channel	Channel 38	Channel 46	
Target (dBm)	10.0	11.0	
Tolerance $\pm$ (dB)	1.0	1.0	
11AC80 (Average)			



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



Channel	Channel 42
Target (dBm)	10.0
Tolerance $\pm$ (dB)	1.0

[5.8G WIFI]

11A (Average)			
Channel	Channel 149	Channel 157	Channel 165
Target (dBm)	13.0	13.0	13.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11N20 (Average)			
Channel	Channel 149	Channel 157	Channel 165
Target (dBm)	13.0	14.0	14.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11N40 (Average)			
Channel	Channel 151	Channel 159	
Target (dBm)	13.0	14.0	
Tolerance $\pm$ (dB)	1.0	1.0	
11AC20 (Average)			
Channel	Channel 149	Channel 157	Channel 165
Target (dBm)	13.0	14.0	14.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11AC40 (Average)			
Channel	Channel 151	Channel 159	
Target (dBm)	13.0	14.0	
Tolerance $\pm$ (dB)	1.0	1.0	
11AC80 (Average)			
Channel	Channel 155		
Target (dBm)	14.0		
Tolerance $\pm$ (dB)	1.0		



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity

[GSM/WCDMA/LTE]

Band	Maximum Tune up	
	(dBm)	(mW)
GSM850	24.97	314.051
GSM1900	22.99	199.067
WCDMA band II	24.50	281.838
WCDMA band IV	24.50	281.838
WCDMA band V	24.50	281.838
LTE band 2	24.50	281.838
LTE band 4	24.50	281.838
LTE band 5	24.50	281.838
LTE band 7	24.50	281.838
LTE Band 12	24.50	281.838
LTE Band 13	24.50	281.838
LTE Band 17	24.50	281.838
LTE Band 25	24.50	281.838
LTE Band 26	24.50	281.838
LTE Band 41	24.50	281.838
LTE Band 66	24.50	281.838



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



7. Measurement Results

7.1 Standalone MPE Evaluation

As declared by the Applicant, the EUT is a wireless device used in a fix application, at least 20 cm from any body part of the user or nearby persons; from the maximum EUT RF output power, the minimum separation distance, $r = 20\text{cm}$, as well as the gain of the used antenna refer to antenna information, the RF power density can be obtained.

[BT]

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm ²)	MPE Limits (mW/cm ²)	MPE ratios1
	dBm	mW					
GFSK	2.0	1.5849	3.23	2.1038	0.0007	1.0000	0.0007
$\pi/4$ -DQPSK	3.0	1.9953	3.23	2.1038	0.0008	1.0000	0.0008
8-DPSK	4.0	2.5119	3.23	2.1038	0.0011	1.0000	0.0011

[BT LE]

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm ²)	MPE Limits (mW/cm ²)	MPE ratios1
	dBm	mW					
BT LE	6.0	3.9811	3.23	2.1038	0.0017	1.0000	0.0017

[2.4G WIFI]

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm ²)	MPE Limits (mW/cm ²)	MPE ratios2
	dBm	mW					
IEEE 802.11b	14.0	25.1189	3.23	2.1038	0.0105	1.0000	0.0105
IEEE 802.11g	14.0	25.1189	3.23	2.1038	0.0105	1.0000	0.0105
IEEE 802.11n HT20	11.0	12.5893	3.23	2.1038	0.0053	1.0000	0.0053
IEEE 802.11n HT40	14.0	25.1189	3.23	2.1038	0.0105	1.0000	0.0105

[5.2G WIFI]

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm ²)	MPE Limits (mW/cm ²)	MPE ratios2
	dBm	mW					
IEEE 802.11a	13.0	19.9526	2.31	1.7022	0.0068	1.0000	0.0068
IEEE 802.11n HT20	12.0	15.8489	2.31	1.7022	0.0054	1.0000	0.0054
IEEE 802.11n HT40	12.0	15.8489	2.31	1.7022	0.0054	1.0000	0.0054
IEEE 802.11ac VHT20	12.0	15.8489	2.31	1.7022	0.0054	1.0000	0.0054
IEEE 802.11ac VHT40	12.0	15.8489	2.31	1.7022	0.0054	1.0000	0.0054
IEEE 802.11ac VHT80	11.0	12.5893	2.31	1.7022	0.0043	1.0000	0.0043

[5.8G WIFI]

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm ²)	MPE Limits (mW/cm ²)	MPE ratios2
	dBm	mW					
IEEE 802.11a	14.0	25.1189	2.31	1.7022	0.0085	1.0000	0.0085
IEEE 802.11n HT20	15.0	31.6228	2.31	1.7022	0.0107	1.0000	0.0107
IEEE 802.11n HT40	15.0	31.6228	2.31	1.7022	0.0107	1.0000	0.0107
IEEE 802.11ac VHT20	15.0	31.6228	2.31	1.7022	0.0107	1.0000	0.0107
IEEE 802.11ac VHT40	15.0	31.6228	2.31	1.7022	0.0107	1.0000	0.0107
IEEE 802.11ac VHT80	15.0	31.6228	2.31	1.7022	0.0107	1.0000	0.0107





<According to LTE modular power (FCC ID: 2APJ4-SLM750V) >

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm2)	MPE Limits (mW/cm2)	MPE ratios3
	dBm	mW					
GSM850	24.97	314.051	1.8	1.5136	0.0946	0.549	0.1723
GSM1900	22.99	199.067	2.5	1.7783	0.0704	1.000	0.0704
WCDMA band II	24.50	281.838	2.5	1.7783	0.0997	1.000	0.0997
WCDMA band IV	24.50	281.838	2.5	1.7783	0.0997	1.000	0.0997
WCDMA band V	24.50	281.838	1.8	1.5136	0.0849	0.549	0.1546
LTE band 2	24.50	281.838	2.5	1.7783	0.0997	1.000	0.0997
LTE band 4	24.50	281.838	2.5	1.7783	0.0997	1.000	0.0997
LTE band 5	24.50	281.838	1.8	1.5136	0.0849	0.549	0.1546
LTE band 7	24.50	281.838	3.9	2.4547	0.1376	1.000	0.1376
LTE Band 12	24.50	281.838	1.8	1.5136	0.0849	0.466	0.1822
LTE Band 13	24.50	281.838	1.8	1.5136	0.0849	0.518	0.1639
LTE Band 17	24.50	281.838	1.8	1.5136	0.0849	0.469	0.1810
LTE Band 25	24.50	281.838	2.5	1.7783	0.0997	1.000	0.0997
LTE Band 26	24.50	281.838	1.8	1.5136	0.0849	0.543	0.1564
LTE Band 41	24.50	281.838	3.9	2.4547	0.1376	1.000	0.1376
LTE Band 66	24.50	281.838	2.5	1.7783	0.0997	1.000	0.0997

Remark:

1. Output power including tune-up tolerance;
2. Output power was adjust to duty cycle at 100% if measured duty cycle less than 98%;
3. MPE evaluate distance is 20cm from user manual provide by manufacturer.

7.2 Simultaneous Transmission MPE Evaluation

The sample support one BT&BLE and one 2.4GWLAN&5.2G WLAN5.8G WLAN, another one LTE, so need consider simultaneous transmission;

Simultaneous transmission MPE

According to KDB447498 for Transmitters used in mobile exposure conditions for simultaneous transmission operations;

$\sum$ of MPE ratios ≤ 1.0

<the worst simultaneous transmission operations result >

Mode	BT MAX MPE ratios	WIFI MAX MPE ratios	LTE MAX MPE ratios	$\sum$ MPE ratios	Limit	Results
BT+WIFI+LTE	0.0017	0.0105	0.1822	0.1944	1.0	Pass

Remark:

1. Output power including tune-up tolerance;
2. BT/BLE/2.4G WIFI output power is burst peak power;
3. 5G WIFI output power is burst average power;
4. MPE evaluate distance is 20cm from user manual provide by manufacturer;
5. MPE values = $PG/4\pi R^2$

8. Conclusion

The measurement results comply with the FCC Limit per 47 CFR 2.1091 for the uncontrolled RF Exposure of mobile device.

9. Description of Test Facility

NVLAP Accreditation Code is 600167-0.

FCC Designation Number is CN5024.

CAB identifier is CN0071.

CNAS Registration Number is L4595.

Test Firm Registration Number: 254912.



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



10.Measurement Uncertainty

BT/BLE/2.4GWLAN&5.2GWLAN&5.8GWLAN:

Test Item		Frequency Range	Uncertainty	Note
Output power	:	1GHz-40GHz	±0.57dB	(1)

(1). This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

-----THE END OF REPORT-----

