



FCC TEST REPORT

FCC ID: 2ATQZ-GE100

On Behalf of

Shenzhen Mooer Audio Co., Ltd

Intelligent Multi Effects

Model No.: GE100 Pro Li, GE100 Pro

Prepared for : Shenzhen Mooer Audio Co., Ltd
Address : 6F, Unit D, Jinghang Building, Liuxian 3rd Road, Baoan 71 District,
Shenzhen, China.

Prepared By : Shenzhen PSI Testing Co., Ltd.
Address : 1-2/F., Building 5, Yudafu Industrial Park, No.10, Xingye West Road,
Shajing Subdistrict, Bao'an District, Shenzhen, Guangdong, China

Report Number : psi2512052-C02-R05
Date of Receipt : January 9, 2026
Date of Test : January 9, 2026 – March 23, 2026
Date of Report : March 24, 2026
Version Number : V0

TABLE OF CONTENTS

Description	Page
1. Summary Of Standards And Results	6
1.1. Description of Standards and Results.....	6
2. General Information	7
2.1. Description of Device (EUT)	7
2.2. Accessories of Device (EUT)	8
2.3. Tested Supporting System Details.....	8
2.4. Block Diagram of Connection Between EUT and Simulators	8
2.5. Test Mode Description.....	9
2.6. Software test version and power setting information	9
2.7. Test Conditions.....	10
2.8. Test Facility.....	10
2.9. Measurement Uncertainty	10
2.10. Test Equipment List	11
3. Spurious Emission	12
3.1. Test Limits	12
3.2. Block Diagram of Test setup	13
3.3. Test Procedure	14
3.4. Test Results	15
4. Power Line Conducted Emission	27
4.1. Test Limits	27
4.2. Test Procedure	27
4.3. Test Setup	27
4.4. Test Results	28
5. Out-of-band Emissions	31
5.1. Test Limits	31
5.2. Test Procedure	31
5.3. Test Setup	31
5.4. Test Results	31
6. Conducted Maximum Output Power	42
6.1. Test limits	42
6.2. Test Procedure	42
6.3. Test Setup	42
6.4. Test Results	42
7. Peak Power Spectral Density	46
7.1. Test limits	46
7.2. Test Procedure	46
7.3. Test Setup	46
7.4. Test Results	46
8. Occupied Bandwidth	50
8.1. Test limits	50
8.2. Test Procedure	50
8.3. Test Setup	50
8.4. Test Results	50

9. Band Edge Test	57
9.1. Test Limit	57
9.2. Block Diagram of Test Setup	57
9.3. Test Procedure	57
9.4. Test Results	58
10. Antenna Requirement	62
10.1. Standard Requirement	62
10.2. Test Results	62
11. Photos of test setup	63
12. Photos of EUT	63

TEST REPORT DECLARATION

Applicant : Shenzhen Mooer Audio Co., Ltd
Address : 6F, Unit D, Jinghang Building, Liuxian 3rd Road, Baoan 71 District, Shenzhen, China.
Manufacturer : Shenzhen Mooer Audio Co., Ltd
Address : 6F, Unit D, Jinghang Building, Liuxian 3rd Road, Baoan 71 District, Shenzhen, China.
EUT Description : Intelligent Multi Effects
(A) Model No. : GE100 Pro Li, GE100 Pro
(B) Trademark : **MOOER**

Measurement Standard Used:

FCC Rules and Regulations Part 15 Subpart C Section 15.247

ANSI C63.10-2020+COR.1-2023

Test Result: PASS

The device described above is tested by Shenzhen PSI Testing Co., Ltd. to determine the maximum emission levels emanating from the device and the severe levels of the device can endure and its performance criterion. The test results are contained in this test report and Shenzhen PSI Testing Co., Ltd. is assumed full responsibility for the accuracy and completeness of test. Also, this report shows that the EUT is technically compliant with the FCC Part 15C requirements.

This report applies to above tested sample only. This report shall not be reproduced in parts without written approval of Shenzhen PSI Testing Co., Ltd.

Tested by (name + signature).....:	Jensen Wang Test Engineer	
Approved by (name + signature).....:	Simple Guan Project Manager	
Date of issue.....:	March 24, 2026	

Revision History

Revision	Issue Date	Revisions	Revised By
V0	March 24, 2026	Initial released Issue	Jensen Wang

1. Summary Of Standards And Results

1.1. Description of Standards and Results

The EUT have been tested according to the applicable standards as referenced below:

Test Item	Standards Paragraph	Result
Conducted Emission	FCC Part 15: 15.207, ANSI C63.10	P
6dB Bandwidth	FCC PART 15:15.247(a)(2), ANSI C63.10	P
Output Power	FCC Part 15: 15.247(b)(3), ANSI C63.10	P
Radiated Spurious Emission	FCC Part 15: 15.209 FCC Part 15: 15.247(d), ANSI C63.10	P
Conducted Spurious & Band Edge Emission	FCC Part 15: 15.247(d), ANSI C63.10	P
Power Spectral Density	FCC PART 15:15.247(e), ANSI C63.10	P
Radiated Band Edge Emission	FCC Part 15: 15.247(d), ANSI C63.10	P
Antenna Requirement	FCC Part 15: 15.203	P
Note: 1. P is an abbreviation for Pass. 2. F is an abbreviation for Fail. 3. N/A is an abbreviation for Not Applicable. 4. Conclusion determination rules of this report: Unless there are clear provisions on measurement uncertainty in the standard or customer requirements, decision by actual test data without considering measurement uncertainty. 5. Measurement method usage KDB 558074 D01 15.247 Meas Guidance v05r02.		

2. General Information

2.1. Description of Device (EUT)

Product Name : Intelligent Multi Effects

Model : GE100 Pro Li, GE100 Pro

Diff : There is no difference except the name of the model and battery. The voltage to RF IC of both models are the same, there is no effect to RF parameter. So all conducted tests are made with the GE100 Pro Li model, only additional radiation spurious emissions and band edges need to be made with GE100 Pro model.

Test Voltage : DC 7.4V from battery, DC 5V from Adapter

Radio Technology	: Bluetooth V5.2 LE
Operation frequency	: 2402-2480MHz
Channel No.	: 40 channels
Channel Separation	: 2MHz
Rate	: 1Mbps
Modulation	: GFSK
Antenna Type	: Internal Antenna, max gain 1.5dBi EUT has two RF antennas, one of them is PCB Antenna, max. gain -0.58dBi, the other one is chip antenna, max. gain 1.5dBi, The product has shielded the PCB antenna end through software. So this report evaluates the largest antenna gain.
Software version	: N/A
Hardware version/FVIN	: N/A
Note	: Antenna information is provided by applicant. Testing lab is not responsible for the accuracy of the information.


2.2. Accessories of Device (EUT)

Accessories 1 : N/A
 Manufacturer : N/A
 Model : N/A
 Rating : N/A

2.3. Tested Supporting System Details

No.	Description	Manufacturer	Model	Serial Number
1	Adapter	Baseus	CCXFK65CC	N/A

2.4. Block Diagram of Connection Between EUT and Simulators



RF Conducted Test

For RF conducted test, the path loss from EUT to SPA already set into SPA offset, offset=Cable loss+Internal path loss.

2.5. Test Mode Description

Keeping TX			
Mode	Data rate (Mbps)	Channel	Frequency(MHz)
GFSK Tx Mode	1	CH0	2402
	1	CH19	2440
	1	CH39	2480
GFSK Tx Mode	2	CH0	2402
	2	CH19	2440
	2	CH39	2480
Note: According exploratory test, EUT will have maximum output power in those data rate. So those data rate were used for all test.			

Channel list:					
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
CH0	2402	CH14	2430	CH28	2458
CH1	2404	CH15	2432	CH29	2460
CH2	2406	CH16	2434	CH30	2462
CH3	2408	CH17	2436	CH31	2464
CH4	2410	CH18	2438	CH32	2466
CH5	2412	CH19	2440	CH33	2468
CH6	2414	CH20	2442	CH34	2470
CH7	2416	CH21	2444	CH35	2472
CH8	2418	CH22	2446	CH36	2474
CH9	2420	CH23	2448	CH37	2476
CH10	2422	CH24	2450	CH38	2478
CH11	2424	CH25	2452	CH39	2480
CH12	2426	CH26	2454	--	--
CH13	2428	CH27	2456	--	--

2.6. Software test version and power setting information

Software testing version	FCC_assist.exe		
Mode	The client 's preset testing software is used to control the operation of EUT in continuous transmission mode and select the testing channel, wireless mode:		
Power level setup by client			
Mode	Channel	Frequency (MHz)	Soft Set
GFSK Tx Mode 1Mbps/2Mbps	CH0	2402	TX level is set as defaults value.
	CH39	2441	TX level is set as defaults value.
	CH78	2480	TX level is set as defaults value.

2.7. Test Conditions

Items	Required	Actual
Temperature range:	15-35℃	26℃
Humidity range:	25-75%	54%
Pressure range:	86-106kPa	101kPa

2.8. Test Facility

Shenzhen PSI Testing Co., Ltd.

1-2/F., Building 5, Yudafu Industrial Park, No.10, Xingye West Road, Shajing Subdistrict, Bao'an District, Shenzhen, Guangdong, China

September 13, 2023 File on Federal Communication Commission

Registration Number: 916281

2.9. Measurement Uncertainty

(95% confidence levels, k=2)

Item	Uncertainty
Power Line Conducted Emissions Test	2.13dB
Radiation Emission test in 3m chamber(Below 30MHz)	4.07dB
Radiation Emission test in 3m chamber(30MHz to 1GHz)	4.51dB
Radiation Emission test in 3m chamber(1GHz to 18GHz)	5.07dB
Radiation Emission test in 3m chamber(18GHz to 40GHz)	5.21dB
Radio Frequency	48.24KHz
Conducted RF Power	0.41dB
Power Spectral Density	0.39 dB
Occupied-Bandwidth	968Hz
Duty Cycle	1%
Conducted-Spurious Emission	1.26dB

2.10.Test Equipment List

Item	Equipment	Manufacturer	Model No.	Serial No.	Firmware Version	Last Cal.	Cal. Interval
1.	9*6*6 anechoic chamber	SKET	9*6*6	N/A	/	2025.12.18	3 Year
2.	Test Receiver	Rohde&Schwarz	ESCI 7	101032/003	4.42 SP3	2025.12.18	1 Year
3.	L.I.S.N.#1	Rohde&Schwarz	ENV216	102282	/	2025.12.18	1 Year
4.	L.I.S.N.#2	RFT	NNB111	13835240	/	2025.12.18	1 Year
5.	Loop Antenna	Schwarz beck	FMZB 1519B	00128	/	2025.01.02	2 Year
6.	Bilog Antenna	Schwarz beck	VULB 9168	01448	/	2025.01.02	2 Year
7.	Spectrum Analyzer	Rohde&Schwarz	FSV-40N	101648	3.70	2025.12.18	1 Year
8.	Horn Antenna	Schwarz beck	BBHA 9120 D	02706	/	2025.01.02	2 Year
9.	Amplifier	SKET	LAPA_01G1 8G-45dB	SK20220329 01	/	2025.12.18	1 Year
10.	Horn Antenna	Schwarz beck	BBHA 9170	00946	/	2024.12.31	2 Year
11.	Amplifier	SKET	LNPA_0118 G-45	SK20200108 01	/	2025.12.18	1 Year
12.	RF Power Probe	Rohde&Schwarz	NRP-Z11	1138.3004.0 2-1111533-F Z	/	2025.12.18	1 Year
13.	RF Sensor Unit	Tachoy	TR1029-2	20220428P0 08	/	2025.12.18	1 Year
14.	Spectrum Analyzer	Agilent	N9020A	MY51281067	A.14.03	2025.12.18	1 Year
15.	Temp. & Humid Chamber	Auchno	9606	/	/	2025.12.18	1 Year
16.	Regulated DC Power Supply	Xinouhua	ADC120V10 A	2022112516 38	/	2025.12.18	1 Year
17.	Cable	SKET	Cable-RE-1	#02/#03	/	2025.12.18	1 Year
18.	Cable	SKET	Cable-RE-2	#01	/	2025.12.18	1 Year
19.	Cable	SKET	Cable-RE-3	#04	/	2025.12.18	1 Year
20.	Cable	SKET	Cable-CE-1	A-E-24	/	2025.12.18	1 Year
21.	6dB Attenuator	Schwarzbeck	DGA 9552N 6dB	CK4186	/	2025.12.18	1 Year
22.	Power meter	Agilent	E4419B	GB40202121	/	2025.12.18	1 Year
23.	Comprehensive Test Instrument	Rohde&Schwarz	CMW 500	145266	/	2025.12.18	1 Year
For Test Software Information							
Item	Software Name	Manufacturer		Version			
RE	EZ EMC	Farad		PSI-3A1			
CE	EZ EMC	Farad		PSI-3A1			
RF	RTS	TACHOY		V1.0.0			

3. Spurious Emission

3.1. Test Limits

Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100 **	3
88-216	150 **	3
216-960	200 **	3
Above 960	500	3

Note: The peak limit is 20 dB higher than the average limit


All the emissions appearing within 15.205 restricted frequency bands shall not exceed the limits shown in 15.209, all the other emissions shall be at least 20dB below the fundamental emissions, or comply with 15.209 limits.

15.205 Restricted frequency band


MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
¹ 0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 - 156.52525	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.7 - 156.9	2690 - 2900	22.01 - 23.12
8.41425 - 8.41475	162.0125 - 167.17	3260 - 3267	23.6 - 24.0
12.29 - 12.293	167.72 - 173.2	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	240 - 285	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	322 - 335.4	3600 - 4400	(²)

3.2. Block Diagram of Test setup


a. In 3m Anechoic Chamber Test Setup Diagram for below 30MHz



b. In 3m Anechoic Chamber Test Setup Diagram for below 1GHz



c. In 3m Anechoic Chamber Test Setup Diagram for frequency above 1GHz



3.3. Test Procedure

(1) Test Setup for below 1GHz: EUT was placed on a non-metallic table, 80 cm above the ground plane inside a semi-anechoic chamber.

Test Setup for frequency above 1GHz: EUT was placed on a non-metallic table, 150 cm above the ground plane inside a semi-anechoic chamber.

(2) Setup EUT and simulator

(3) Test antenna was located 3m from the EUT on an adjustable mast. Below pre-scan procedure was first performed in order to find prominent radiated emissions.

(a) Change work frequency or channel of device if practicable.

(b) Change modulation type of device if practicable.

(c) Rotated EUT though three orthogonal axes to determine the attitude of EUT arrangement produces highest emissions

(4) Spectrum frequency from 9KHz to 25GHz (tenth harmonic of fundamental frequency) was investigated

(5) For final emissions measurements at each frequency of interest, the EUT were rotated and the antenna height was varied between 1m and 4m in order to maximize the emission. Measurements in both horizontal and vertical polarities were made and the data was recorded. In order to find the maximum emission, the relative positions of equipments and all of the interface cables were changed according to ANSI C63.10 on Radiated Emission test.

(6) For emissions above 1GHz, both Peak and Average level were measured with Spectrum Analyzer, and the RBW is set at 1MHz, VBW is set at 3MHz for Peak measure; RBW is set at 1MHz, VBW is set at 10Hz for Average measure.

Test setup information:


9KHz~150KHz	RBW 200Hz	VBW 1KHz
150KHz~30MHz	RBW 9KHz	VBW 30KHz
30MHz~1GHz	RBW 120KHz	VBW 300KHz
Above1GHz	RBW 1MHz	VBW 3MHz

3.4. Test Results

We have scanned from 9kHz to the 10th harmonic of the EUT's highest frequency.
Detailed information please see the following page.


From 9KHz to 30MHz:	
Test Date : 2026.1.14	Temperature : 26℃
Test Engineer : Jensen Wang	Humidity : 54%
Test Mode : GFSK mode	
Test Results : PASS	
Note:	The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

From 30MHz to 1000MHz:	
Test Date : 2026.1.14	Temperature : 26℃
Test Engineer : Jensen Wang	Humidity : 54%
Test Mode : GFSK mode	
Model : GE100 Pro Li	
Test voltage : DC 7.4V from Battery	
Test Results : PASS	
Note:	1. The test results are listed in next pages. 2. If the limits for the measurement with the average detector are met when using a receiver with a peak detector, the test unit shall be deemed to meet both limits and the measurement with the average detector and quasi-peak detector need not be carried out. 3. All modes have been tested, and only worst data of 1Mbps GFSK 2402MHz mode was listed in this report.

Polarization: Horizontal

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	38.0782	13.45	14.48	27.93	40.00	-12.07	QP
2	52.6674	12.65	13.99	26.64	40.00	-13.36	QP
3	121.8686	16.10	13.56	29.66	43.50	-13.84	QP
4	150.4056	12.85	15.12	27.97	43.50	-15.53	QP
5	254.8400	18.26	13.31	31.57	46.00	-14.43	QP
6 *	491.6057	17.28	19.49	36.77	46.00	-9.23	QP

Level = Reading + Factor Margin = Level - Limit

Polarization: Vertical

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	39.2301	13.22	14.54	27.76	40.00	-12.24	QP
2	60.6777	14.04	13.21	27.25	40.00	-12.75	QP
3 *	121.1230	20.47	13.52	33.99	43.50	-9.51	QP
4	156.0466	14.75	15.02	29.77	43.50	-13.73	QP
5	289.0020	16.20	14.48	30.68	46.00	-15.32	QP
6	440.3892	17.34	18.61	35.95	46.00	-10.05	QP

Level = Reading + Factor Margin = Level - Limit

From 1GHz to 25GHz:	
Test Date : 2026.1.14	Temperature : 26℃
Test Engineer : Jensen Wang	Humidity : 54%
Test Mode : GFSK mode	
Model : GE100 Pro Li	
Test voltage : DC 7.4V from Battery	
Test Results : PASS	
Note:	1. The test results are listed in next pages. 2. If the limits for the measurement with the average detector are met when using a receiver with a peak detector, the test unit shall be deemed to meet both limits and the measurement with the average detector and quasi-peak detector need not be carried out. 3. If the limits for the measurement with the average detector are met when using a receiver with a quasi-peak detector, the test unit shall be deemed to meet both limits and the measurement with the average detector need not be carried out.


1Mbps:

Test Mode : GFSK TX Low								
No.	Freq MHz	Polarity	Reading (dBuV/m)	Correct Factor	Result (dBuV/m)	Limit (dBuV/m)	Margin	Remark
1	4804	V	58.42	-13.25	45.17	74.00	-28.83	Peak
2	4804	V	48.52	-13.25	35.27	54.00	-18.73	Avg
3	7206	--	--	--	--	--	--	--
4	9608	--	--	--	--	--	--	--
5	4804	H	56.01	-13.25	42.76	74.00	-31.24	Peak
6	4804	H	44.99	-13.25	31.74	54.00	-22.26	Avg
7	7206	--	--	--	--	--	--	--
8	9608	--	--	--	--	--	--	--
Test Mode : GFSK TX Mid								
1	4880	V	59.65	-12.98	46.67	74.00	-27.33	Peak
2	4880	V	48.02	-12.98	35.04	54.00	-18.96	Avg
3	7320	--	--	--	--	--	--	--
4	9760	--	--	--	--	--	--	--
5	4880	H	56.88	-12.98	43.90	74.00	-30.10	Peak
6	4880	H	46.56	-12.98	33.58	54.00	-20.42	Avg
7	7320	--	--	--	--	--	--	--
8	9760	--	--	--	--	--	--	--
Test Mode : GFSK TX High								
1	4960	V	58.71	-12.70	46.01	74.00	-27.99	Peak
2	4960	V	47.43	-12.70	34.73	54.00	-19.27	Avg
3	7440	--	--	--	--	--	--	--
4	9920	--	--	--	--	--	--	--
5	4960	H	55.56	-12.70	42.86	74.00	-31.14	Peak
6	4960	H	44.92	-12.70	32.22	54.00	-21.78	Avg
7	7440	--	--	--	--	--	--	--
8	9920	--	--	--	--	--	--	--
Note: 1. Means other frequency and mode comply with standard requirements and at least have 20dB margin. 2. Correct Factor=Cable Loss+ Antenna Factor-Amplifier Gain. Result=Reading + Correct Factor. Margin= Result-Limit.								


2Mbps:

Test Mode : GFSK TX Low								
No.	Freq MHz	Polarity	Reading (dBuV/m)	Correct Factor	Result (dBuV/m)	Limit (dBuV/m)	Margin	Remark
1	4804	V	57.92	-13.25	44.67	74.00	-29.33	Peak
2	4804	V	47.81	-13.25	34.56	54.00	-19.44	Avg
3	7206	--	--	--	--	--	--	--
4	9608	--	--	--	--	--	--	--
5	4804	H	57.53	-13.25	44.28	74.00	-29.72	Peak
6	4804	H	45.20	-13.25	31.95	54.00	-22.05	Avg
7	7206	--	--	--	--	--	--	--
8	9608	--	--	--	--	--	--	--
Test Mode : GFSK TX Mid								
1	4880	V	56.76	-12.98	43.78	74.00	-30.22	Peak
2	4880	V	47.90	-12.98	34.92	54.00	-19.08	Avg
3	7320	--	--	--	--	--	--	--
4	9760	--	--	--	--	--	--	--
5	4880	H	55.56	-12.98	42.58	74.00	-31.42	Peak
6	4880	H	45.24	-12.98	32.26	54.00	-21.74	Avg
7	7320	--	--	--	--	--	--	--
8	9760	--	--	--	--	--	--	--
Test Mode : GFSK TX High								
1	4960	V	59.40	-12.70	46.70	74.00	-27.30	Peak
2	4960	V	50.02	-12.70	37.32	54.00	-16.68	Avg
3	7440	--	--	--	--	--	--	--
4	9920	--	--	--	--	--	--	--
5	4960	H	54.81	-12.70	42.11	74.00	-31.89	Peak
6	4960	H	47.00	-12.70	34.30	54.00	-19.70	Avg
7	7440	--	--	--	--	--	--	--
8	9920	--	--	--	--	--	--	--
Note: 1. Means other frequency and mode comply with standard requirements and at least have 20dB margin. 2. Correct Factor=Cable Loss+ Antenna Factor-Amplifier Gain. Result=Reading + Correct Factor. Margin= Result-Limit.								

From 30MHz to 1000MHz:	
Test Date : 2026.4.24	Temperature : 26℃
Test Engineer : Jensen Wang	Humidity : 54%
Test Mode : GFSK mode	
Model : GE100 Pro	
Test voltage : AC 120V/60Hz	
Test Results : PASS	
Note:	1. The test results are listed in next pages. 2. If the limits for the measurement with the average detector are met when using a receiver with a peak detector, the test unit shall be deemed to meet both limits and the measurement with the average detector and quasi-peak detector need not be carried out. 3. All modes have been tested, and only worst data of 1Mbps GFSK 2402MHz mode was listed in this report.



Level = Reading + Factor Margin = Level - Limit

Polarization: Vertical

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1 *	36.8791	17.27	14.43	31.70	40.00	-8.30	QP
2	53.0613	14.60	13.95	28.55	40.00	-11.45	QP
3	121.1230	19.47	13.52	32.99	43.50	-10.51	QP
4	156.0466	14.75	15.02	29.77	43.50	-13.73	QP
5	289.0020	16.20	14.48	30.68	46.00	-15.32	QP
6	432.9250	13.98	18.43	32.41	46.00	-13.59	QP

Level = Reading + Factor Margin = Level - Limit

From 1GHz to 25GHz:	
Test Date : 2026.4.24	Temperature : 26℃
Test Engineer : Jensen Wang	Humidity : 54%
Test Mode : GFSK mode	
Model : GE100 Pro	
Test voltage : AC 120V/60Hz	
Test Results : PASS	
Note:	1. The test results are listed in next pages. 2. If the limits for the measurement with the average detector are met when using a receiver with a peak detector, the test unit shall be deemed to meet both limits and the measurement with the average detector and quasi-peak detector need not be carried out. 3. If the limits for the measurement with the average detector are met when using a receiver with a quasi-peak detector, the test unit shall be deemed to meet both limits and the measurement with the average detector need not be carried out.

1Mbps:

Test Mode : GFSK TX Low								
No.	Freq MHz	Polarity	Reading (dBuV/m)	Correct Factor	Result (dBuV/m)	Limit (dBuV/m)	Margin	Remark
1	4804	V	57.92	-13.25	44.67	74.00	-29.33	Peak
2	4804	V	47.60	-13.25	34.35	54.00	-19.65	Avg
3	7206	--	--	--	--	--	--	--
4	9608	--	--	--	--	--	--	--
5	4804	H	55.46	-13.25	42.21	74.00	-31.79	Peak
6	4804	H	45.65	-13.25	32.40	54.00	-21.60	Avg
7	7206	--	--	--	--	--	--	--
8	9608	--	--	--	--	--	--	--
Test Mode : GFSK TX Mid								
1	4880	V	56.81	-12.98	43.83	74.00	-30.17	Peak
2	4880	V	50.38	-12.98	37.40	54.00	-16.60	Avg
3	7320	--	--	--	--	--	--	--
4	9760	--	--	--	--	--	--	--
5	4880	H	56.63	-12.98	43.65	74.00	-30.35	Peak
6	4880	H	47.07	-12.98	34.09	54.00	-19.91	Avg
7	7320	--	--	--	--	--	--	--
8	9760	--	--	--	--	--	--	--
Test Mode : GFSK TX High								
1	4960	V	59.18	-12.70	46.48	74.00	-27.52	Peak
2	4960	V	47.52	-12.70	34.82	54.00	-19.18	Avg
3	7440	--	--	--	--	--	--	--
4	9920	--	--	--	--	--	--	--
5	4960	H	56.48	-12.70	43.78	74.00	-30.22	Peak
6	4960	H	46.56	-12.70	33.86	54.00	-20.14	Avg
7	7440	--	--	--	--	--	--	--
8	9920	--	--	--	--	--	--	--
Note: 1. Means other frequency and mode comply with standard requirements and at least have 20dB margin. 2. Correct Factor=Cable Loss+ Antenna Factor-Amplifier Gain. Result=Reading + Correct Factor. Margin= Result-Limit.								

2Mbps:

Test Mode : GFSK TX Low								
No.	Freq MHz	Polarity	Reading (dBuV/m)	Correct Factor	Result (dBuV/m)	Limit (dBuV/m)	Margin	Remark
1	4804	V	59.18	-13.25	45.93	74.00	-28.07	Peak
2	4804	V	50.01	-13.25	36.76	54.00	-17.24	Avg
3	7206	--	--	--	--	--	--	--
4	9608	--	--	--	--	--	--	--
5	4804	H	56.07	-13.25	42.82	74.00	-31.18	Peak
6	4804	H	45.55	-13.25	32.30	54.00	-21.70	Avg
7	7206	--	--	--	--	--	--	--
8	9608	--	--	--	--	--	--	--
Test Mode : GFSK TX Mid								
1	4880	V	56.75	-12.98	43.77	74.00	-30.23	Peak
2	4880	V	47.84	-12.98	34.86	54.00	-19.14	Avg
3	7320	--	--	--	--	--	--	--
4	9760	--	--	--	--	--	--	--
5	4880	H	55.96	-12.98	42.98	74.00	-31.02	Peak
6	4880	H	46.76	-12.98	33.78	54.00	-20.22	Avg
7	7320	--	--	--	--	--	--	--
8	9760	--	--	--	--	--	--	--
Test Mode : GFSK TX High								
1	4960	V	59.41	-12.70	46.71	74.00	-27.29	Peak
2	4960	V	47.34	-12.70	34.64	54.00	-19.36	Avg
3	7440	--	--	--	--	--	--	--
4	9920	--	--	--	--	--	--	--
5	4960	H	55.67	-12.70	42.97	74.00	-31.03	Peak
6	4960	H	47.37	-12.70	34.67	54.00	-19.33	Avg
7	7440	--	--	--	--	--	--	--
8	9920	--	--	--	--	--	--	--
Note: 1. Means other frequency and mode comply with standard requirements and at least have 20dB margin. 2. Correct Factor=Cable Loss+ Antenna Factor-Amplifier Gain. Result=Reading + Correct Factor. Margin= Result-Limit.								

4. Power Line Conducted Emission

4.1. Test Limits

Frequency (MHz)	Limits dB(μ V)	
	Quasi-peak Level	Average Level
0.15 -0.50	66 -56*	56 - 46*
0.50 -5.00	56	46
5.00 -30.00	60	50

Notes: 1. *Decreasing linearly with logarithm of frequency.

2. The lower limit shall apply at the transition frequencies.


3. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

4.2. Test Procedure

The EUT is put on the plane 0.8m high above the ground by insulating support and is connected to the power mains through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm coupling impedance for the EUT system. Please refer the block diagram of the test setup and photographs. Both sides of AC lines are checked to find out the maximum conducted emission. In order to find the maximum emission levels, the relative positions of equipment and all of the interface cables shall be changed according to ANSI C63.10 on Conducted Emission Measurement.

The bandwidth of test receiver is set at 9 kHz.

4.3. Test Setup



4.4. Test Results

Test Date	: 2026.1.14	Temperature	: 26℃
Test Engineer	: Jensen Wang	Humidity	: 54%
Test Mode	: GFSK mode		
Test Results	: PASS		


Note: 1. The test results are listed in next pages.

2. If the limits for the measurement with the average detector are met when using a receiver with a peak detector, the test unit shall be deemed to meet both limits and the measurement with the average detector and quasi-peak detector need not be carried out.

3. If the limits for the measurement with the average detector are met when using a receiver with a quasi-peak detector, the test unit shall be deemed to meet both limits and the measurement with the average detector need not be carried out.

4. All modes have been tested, and only worst data of GFSK mode, Channel 2402MHz (AC 120V/ 60Hz) was listed in this report.


Polarization: L



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.1740	32.81	9.94	42.75	64.77	-22.02	QP
2	0.1740	21.25	9.94	31.19	54.77	-23.58	AVG
3	0.4540	29.99	9.78	39.77	56.80	-17.03	QP
4	0.4540	18.77	9.78	28.55	46.80	-18.25	AVG
5 *	0.8660	30.84	9.42	40.26	56.00	-15.74	QP
6	0.8660	18.54	9.42	27.96	46.00	-18.04	AVG
7	1.2420	29.93	9.41	39.34	56.00	-16.66	QP
8	1.2420	18.54	9.41	27.95	46.00	-18.05	AVG
9	1.3900	28.46	9.40	37.86	56.00	-18.14	QP
10	1.3900	18.00	9.40	27.40	46.00	-18.60	AVG
11	28.8220	25.83	10.31	36.14	60.00	-23.86	QP
12	28.8220	13.99	10.31	24.30	50.00	-25.70	AVG

Note: Level = Reading + Factor Margin = Level - Limit

Polarization: N



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.2180	31.01	10.00	41.01	62.89	-21.88	QP
2	0.2180	20.73	10.00	30.73	52.89	-22.16	AVG
3	0.3100	30.81	9.76	40.57	59.97	-19.40	QP
4	0.3100	20.34	9.76	30.10	49.97	-19.87	AVG
5	0.6300	29.77	9.78	39.55	56.00	-16.45	QP
6	0.6300	18.27	9.78	28.05	46.00	-17.95	AVG
7	0.7780	30.02	9.71	39.73	56.00	-16.27	QP
8 *	0.7780	21.74	9.71	31.45	46.00	-14.55	AVG
9	1.0620	29.84	9.49	39.33	56.00	-16.67	QP
10	1.0620	18.78	9.49	28.27	46.00	-17.73	AVG
11	29.8340	26.95	10.30	37.25	60.00	-22.75	QP
12	29.8340	14.79	10.30	25.09	50.00	-24.91	AVG

Note: Level = Reading + Factor Margin = Level - Limit

5. Out-of-band Emissions

5.1. Test Limits


In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in § 15.209(a) is not required.

5.2. Test Procedure

ANSI C63.10 Section 11.11.1, Section 11.11.2, Section 11.11.3

Connect the transmitter output to spectrum analyzer using a low loss RF cable, and set the spectrum analyzer to RBW=100 kHz, VBW= 300 kHz, peak detector, and max hold. Measurements utilizing these settings are made of the in-band reference level, band edge and out-of-band emissions.

5.3. Test Setup





5.4. Test Results

PASS.

The test results are listed in next pages.

Band Edge: Pass


Condition	Antenna	Modulation	TX_Frequency (MHz)	Max. Mark_freq(MHz)	Ref_level(dBm)	Spurious level(dBm)	limit(dBm)	Result
NVNT	ANT1	1Mbps	2402.00	2399.965	0.473	-52.065	-19.527	Pass
NVNT	ANT1	1Mbps	2480.00	2496.325	1.408	-53.735	-18.592	Pass
NVNT	ANT1	2Mbps	2402.00	2399.965	-0.154	-33.437	-20.154	Pass
NVNT	ANT1	2Mbps	2480.00	2485.325	0.625	-49.192	-19.375	Pass

**1 Reference_Level_NVNT_ANT1_1Mbps_2480**




1_Reference_Level_NVNT_ANT1_2Mbps_2402







Spurious Emission: Pass

Condition	Antenna	Modulation	TX_Frequency (MHz)	Ref_level(dBm)	Spurious level(dBm)	limit(dBm)	Result
NVNT	ANT1	1Mbps	2402.00	0.473	-47.543	-19.527	Pass
NVNT	ANT1	1Mbps	2440.00	1.127	-44.940	-18.873	Pass
NVNT	ANT1	1Mbps	2480.00	1.408	-44.147	-18.592	Pass
NVNT	ANT1	2Mbps	2402.00	-0.154	-45.589	-20.154	Pass
NVNT	ANT1	2Mbps	2440.00	0.458	-45.068	-19.542	Pass
NVNT	ANT1	2Mbps	2480.00	0.625	-44.391	-19.375	Pass


1 Reference Level NVNT ANT1 1Mbps 2402**2 Spurious Emission NVNT ANT1 1Mbps 2402****1 Reference Level NVNT ANT1 1Mbps 2440**




1_Reference_Level_NVNT_ANT1_1Mbps_2480



1_Reference_Level_NVNT_ANT1_2Mbps_2402



1_Reference_Level_NVNT_ANT1_2Mbps_2440



1_Reference_Level_NVNT_ANT1_2Mbps_2480



6. Conducted Maximum Output Power

6.1. Test limits

Please refer FCC PART 15.247.

Regulation 15.247(b) The limit of Maximum Peak Output Power Measurement is 1 W(30dBm)


6.2. Test Procedure

ANSI C63.10:2020, section 11.9.1 Maximum peak conducted output power.

The following procedure shall be used when an instrument with a resolution bandwidth that is greater than the DTS bandwidth is available to perform the measurement:



- Set the RBW $\geq$ DTS bandwidth.
- Set VBW $\geq [3 \times \text{RBW}]$.
- Set span $\geq [3 \times \text{RBW}]$.
- Sweep time = auto couple.
- Detector = peak.
- Trace mode = max hold.
- Allow trace to fully stabilize.
- Use peak marker function to determine the peak amplitude level.

6.3. Test Setup





6.4. Test Results



Condition	Antenna	Rate	Frequency (MHz)	Max. Conducted Power(dBm)	Max. Conducted Power(mW)	Limit(mW)	Result
NVNT	ANT1	1Mbps	2402.00	0.60	1.15	1000	Pass
NVNT	ANT1	1Mbps	2440.00	1.26	1.34	1000	Pass
NVNT	ANT1	1Mbps	2480.00	1.50	1.41	1000	Pass
NVNT	ANT1	2Mbps	2402.00	0.68	1.17	1000	Pass
NVNT	ANT1	2Mbps	2440.00	1.32	1.36	1000	Pass
NVNT	ANT1	2Mbps	2480.00	1.50	1.41	1000	Pass



Peak Output Power_NVNT_ANT1_1Mbps_2480



Peak Output Power NVNT_ANT1_2Mbps_2440



7. Peak Power Spectral Density

7.1. Test limits


For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

7.2. Test Procedure

Details see the KDB558074 D01 Meas Guidance v05r02




1. Place the EUT on the table and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
3. Set the spectrum analyzer as RBW = 30kHz(Set the RBW to: $3\text{ kHz} \leq \text{RBW} \leq 100\text{ kHz}$), VBW = 300kHz(Set the VBW $\geq 3 \times \text{RBW}$), span $\geq 1.5 \times \text{DTS bandwidth}$., detail see the test plot.
4. Record the max reading.
5. Repeat the above procedure until the measurements for all frequencies are completed.



7.3. Test Setup





7.4. Test Results

Condition	Antenna	Rate	Frequency (MHz)	Power Spectral Density(dBm/3kHz)	Limit(dBm/3kHz)	Result
NVNT	ANT1	1Mbps	2402.00	-19.00	8	Pass
NVNT	ANT1	1Mbps	2440.00	-18.39	8	Pass
NVNT	ANT1	1Mbps	2480.00	-18.43	8	Pass
NVNT	ANT1	2Mbps	2402.00	-21.88	8	Pass
NVNT	ANT1	2Mbps	2440.00	-21.27	8	Pass
NVNT	ANT1	2Mbps	2480.00	-21.06	8	Pass





Power Spectral Density NVNT_ANT1_2Mbps_2440



8. Occupied Bandwidth

8.1. Test limits

Systems using digital modulation techniques may operate in the 902-928 MHz, and 2400-2483.5 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz

8.2. Test Procedure


Details see the KDB558074 D01 Meas Guidance v05r02 and C63.10 section 6.9.3

a) The bandwidth is measured at an amplitude level reduced 6dB from the reference level. The reference level is the level of the highest amplitude signal observed from the transmitter at the fundamental frequency. Once the reference level is established, the equipment is conditioned with typical modulating signal to produce the worst-case (i.e. the widest) bandwidth.

b) The test receiver set RBW = 100kHz, VBW $\geq$ 3*RBW =300kHz, Peak Detector, Sweep time set auto, detail see the test plot.


c) The test receiver set RBW =1-5%BW, VBW>3*RBW, Sweep time set auto, detail see the test plot for 99%Bandwidth.


8.3. Test Setup





8.4. Test Results

Condition	Antenna	Rate	Frequency (MHz)	-6dB BW(kHz)	limit(kHz)	Result
NVNT	ANT1	1Mbps	2402.00	505.92	500	Pass
NVNT	ANT1	1Mbps	2440.00	504.79	500	Pass
NVNT	ANT1	1Mbps	2480.00	500.96	500	Pass
NVNT	ANT1	2Mbps	2402.00	870.19	500	Pass
NVNT	ANT1	2Mbps	2440.00	870.38	500	Pass
NVNT	ANT1	2Mbps	2480.00	866.43	500	Pass





-6dB Bandwidth NVNT ANT1 2Mbps 2440



Condition	Antenna	Rate	Frequency (MHz)	99%OBW(MHz)
NVNT	ANT1	1Mbps	2402.00	1.027
NVNT	ANT1	1Mbps	2440.00	1.028
NVNT	ANT1	1Mbps	2480.00	1.030
NVNT	ANT1	2Mbps	2402.00	2.037
NVNT	ANT1	2Mbps	2440.00	2.037
NVNT	ANT1	2Mbps	2480.00	2.038


99% Occupied Bandwidth NVNT ANT1 1Mbps 2402





99% Occupied Bandwidth NVNT ANT1 1Mbps 2440



99% Occupied Bandwidth NVNT ANT1 1Mbps 2480



99% Occupied Bandwidth NVNT_ANT1_2Mbps_2440



9. Band Edge Test


9.1. Test Limit

In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a)(see § 15.205(c)).`

Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100 **	3
88-216	150 **	3
216-960	200 **	3
Above 960	500	3

** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g., §§ 15.231 and 15.241

9.2. Block Diagram of Test Setup



9.3. Test Procedure

ANSI C63.10 section 6.10.5.2

All restriction band and non- restriction band have been tested, only worse case is reported.

Details see the KDB558074 D01 Meas Guidance v05r02

1. Put the EUT on a 1.5m high table, power on the EUT. Emissions were scanned and measured rotating the EUT to 360 degrees, Find the maximum Emission
2. Check the spurious emissions out of band.
3. RBW 1MHz, VBW 3MHz, peak detector for peak value, RBW 1MHz, VBW 10Hz, RMS detector for AV value.

9.4. Test Results

Test Date : 2026.1.14					Temperature : 26℃			
Test Engineer : Jensen Wang					Humidity : 54%			
Model : GE100 Pro Li								
Test voltage : DC 7.4V from Battery								
Test Results : PASS								
Frequency Range : 2310MHz~2410MHz								
Test Mode : 1Mbps: GFSK TX 2402MHz								
No.	Freq MHz	Polarity	Reading (dBuV/m)	Correct Factor	Result (dBuV/m)	Limit (dBuV/m)	Margin	Remark
1	2390	H	59.77	-20.45	39.32	74.00	-34.68	Peak
2	2390	H	--	-20.45	--	54.00	--	Avg
3	2400	H	62.68	-20.41	42.27	74.00	-31.73	Peak
4	2400	H	--	-20.41	--	54.00	--	Avg
1	2390	V	63.13	-20.45	42.68	74.00	-31.32	Peak
2	2390	V	--	-20.45	--	54.00	--	Avg
3	2400	V	63.25	-20.41	42.84	74.00	-31.16	Peak
4	2400	V	--	-20.41	--	54.00	--	Avg
Frequency Range : 2450MHz~2550MHz								
Test Mode : 1Mbps: GFSK TX 2480MHz								
1	2483.5	H	63.12	-20.15	42.97	74.00	-31.03	Peak
2	2483.5	H	--	-20.15	--	54.00	--	Avg
1	2483.5	V	66.83	-20.15	46.68	74.00	-27.32	Peak
2	2483.5	V	--	-20.15	--	54.00	--	Avg
Note:	1. Means other frequency and mode comply with standard requirements and at least have 20dB margin. 2. Correct Factor=Cable Loss+ Antenna Factor-Amplifier Gain. Result=Reading + Correct Factor. Margin= Result-Limit. 3. If the limits for the measurement with the average detector are met when using a receiver with a peak detector, the test unit shall be deemed to meet both limits and the measurement with the average detector need not be carried out.							

Frequency Range : 2310MHz~2410MHz								
Test Mode : 2Mbps: GFSK TX 2402MHz								
No.	Freq MHz	Polarity	Reading (dBuV/m)	Correct Factor	Result (dBuV/m)	Limit (dBuV/m)	Margin	Remark
1	2390	H	59.49	-20.45	39.04	74.00	-34.96	Peak
2	2390	H	--	-20.45	--	54.00	--	Avg
3	2400	H	63.60	-20.41	43.19	74.00	-30.81	Peak
4	2400	H	--	-20.41	--	54.00	--	Avg
1	2390	V	61.85	-20.45	41.40	74.00	-32.60	Peak
2	2390	V	--	-20.45	--	54.00	--	Avg
3	2400	V	64.11	-20.41	43.70	74.00	-30.30	Peak
4	2400	V	--	-20.41	--	54.00	--	Avg
Frequency Range : 2450MHz~2550MHz								
Test Mode : 1Mbps: GFSK TX 2480MHz								
1	2483.5	H	61.15	-20.15	41.00	74.00	-33.00	Peak
2	2483.5	H	--	-20.15	--	54.00	--	Avg
1	2483.5	V	66.65	-20.15	46.50	74.00	-27.50	Peak
2	2483.5	V	--	-20.15	--	54.00	--	Avg
Note: 1. Means other frequency and mode comply with standard requirements and at least have 20dB margin. 2. Correct Factor=Cable Loss+ Antenna Factor-Amplifier Gain. Result=Reading + Correct Factor. Margin= Result-Limit. 3. If the limits for the measurement with the average detector are met when using a receiver with a peak detector, the test unit shall be deemed to meet both limits and the measurement with the average detector need not be carried out.								

Test Date					: 2026.4.24				Temperature				: 26℃				
Test Engineer					: Jensen Wang				Humidity				: 54%				
Model					: GE100 Pro												
Test voltage					: AC 120V/60Hz												
Test Results					: PASS												
Frequency Range					: 2310MHz~2410MHz												
Test Mode					: 1Mbps: GFSK TX 2402MHz												
No.		Freq MHz		Polarity		Reading (dBuV/m)		Correct Factor		Result (dBuV/m)		Limit (dBuV/m)		Margin		Remark	
1		2390		H		60.93		-20.45		40.48		74.00		-33.52		Peak	
2		2390		H		--		-20.45		--		54.00		--		Avg	
3		2400		H		62.79		-20.41		42.38		74.00		-31.62		Peak	
4		2400		H		--		-20.41		--		54.00		--		Avg	
1		2390		V		61.43		-20.45		40.98		74.00		-33.02		Peak	
2		2390		V		--		-20.45		--		54.00		--		Avg	
3		2400		V		63.93		-20.41		43.52		74.00		-30.48		Peak	
4		2400		V		--		-20.41		--		54.00		--		Avg	
Frequency Range					: 2450MHz~2550MHz												
Test Mode					: 1Mbps: GFSK TX 2480MHz												
1		2483.5		H		62.02		-20.15		41.87		74.00		-32.13		Peak	
2		2483.5		H		--		-20.15		--		54.00		--		Avg	
1		2483.5		V		63.91		-20.15		43.76		74.00		-30.24		Peak	
2		2483.5		V		--		-20.15		--		54.00		--		Avg	
Note:																	
1. Means other frequency and mode comply with standard requirements and at least have 20dB margin.																	
2. Correct Factor=Cable Loss+ Antenna Factor-Amplifier Gain.																	
Result=Reading + Correct Factor. Margin= Result-Limit.																	
3. If the limits for the measurement with the average detector are met when using a receiver with a peak detector, the test unit shall be deemed to meet both limits and the measurement with the average detector need not be carried out.																	

Frequency Range : 2310MHz~2410MHz								
Test Mode : 2Mbps: GFSK TX 2402MHz								
No.	Freq MHz	Polarity	Reading (dBuV/m)	Correct Factor	Result (dBuV/m)	Limit (dBuV/m)	Margin	Remark
1	2390	H	58.36	-20.45	37.91	74.00	-36.09	Peak
2	2390	H	--	-20.45	--	54.00	--	Avg
3	2400	H	62.27	-20.41	41.86	74.00	-32.14	Peak
4	2400	H	--	-20.41	--	54.00	--	Avg
1	2390	V	61.67	-20.45	41.22	74.00	-32.78	Peak
2	2390	V	--	-20.45	--	54.00	--	Avg
3	2400	V	64.86	-20.41	44.45	74.00	-29.55	Peak
4	2400	V	--	-20.41	--	54.00	--	Avg
Frequency Range : 2450MHz~2550MHz								
Test Mode : 1Mbps: GFSK TX 2480MHz								
1	2483.5	H	61.03	-20.15	40.88	74.00	-33.12	Peak
2	2483.5	H	--	-20.15	--	54.00	--	Avg
1	2483.5	V	63.87	-20.15	43.72	74.00	-30.28	Peak
2	2483.5	V	--	-20.15	--	54.00	--	Avg
Note: 1. Means other frequency and mode comply with standard requirements and at least have 20dB margin. 2. Correct Factor=Cable Loss+ Antenna Factor-Amplifier Gain. Result=Reading + Correct Factor. Margin= Result-Limit. 3. If the limits for the measurement with the average detector are met when using a receiver with a peak detector, the test unit shall be deemed to meet both limits and the measurement with the average detector need not be carried out.								

10. Antenna Requirement

10.1. Standard Requirement

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

10.2. Test Results

The EUT antenna is internal antenna. It complies with the standard requirement.

11. Photos of test setup

Reference to the **appendix I Test Setup Photo** for details.

12. Photos of EUT

Reference to the **appendix II external photos** and **appendix III internal photos** for details.

----- END OF REPORT-----