FCC Part 15C Test Report

FCC ID: 2ATTK-CYTT22

Product Name:	WIFI smart led light strip suit
Trademark:	N/A
Model Name :	CYTT-22
Prepared For : Address :	Shenzhen ChuangYi Tong Technology Co., Ltd 3rd Floor, 4th Building, Hehe Tech Park, Guanlan Street, Longhua District, Shenzhen, China
Prepared By : Address :	Shenzhen BCTC Testing Co., Ltd. BCTC Building & 1-2F, East of B Building, Pengzhou Industrial, Fuyuan 1st Road, Qiaotou Community, Fuyong Street, Bao'an District, Shenzhen, China
Test Date:	Jul. 30, 2019 –Aug. 07, 2019
Date of Report :	Aug. 07, 2019
Report No.:	BCTC-FY190704480E

TEST RESULT CERTIFICATION

Applicant's name ..... :	Shenzhen ChuangYi Tong Technology Co., Ltd
Address ..... :	3rd Floor, 4th Building, Hehe Tech Park, Guanlan Street, Longhua District, Shenzhen, China
Manufacture's Name ..... :	Shenzhen ChuangYi Tong Technology Co., Ltd
Address ..... :	3rd Floor, 4th Building, Hehe Tech Park, Guanlan Street, Longhua District, Shenzhen, China
Product description	
Product name..... :	WIFI smart led light strip suit
Trademark ..... :	N/A
Model and/or type reference :	CYTT-22
Standards ..... :	FCC Part15.247 ANSI C63.10:2013

This device described above has been tested by BCTC, and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of BCTC, this document may be altered or revised by BCTC, personal only, and shall be noted in the revision of the document.

Prepared by(Engineer):	Cai Fang Zhong	Cai Fang Zhong
Reviewer(Supervisor):	Eric Yang	Eric Yang
Approved(Manager):	Zero Zhou	Zero Zhou

倍测检测 BCTC APPROVED SHENZHEN BCTC TESTING CO., LTD

Table of Contents **Page**

1 . SUMMARY OF TEST RESULTS 6
1.1 TEST FACILITY 7
1.2 MEASUREMENT UNCERTAINTY 7
2 . GENERAL INFORMATION 8
2.1 GENERAL DESCRIPTION OF EUT 8
2.2 DESCRIPTION OF TEST MODES 9
2.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED 10
2.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE) 10
2.5 EQUIPMENTS LIST FOR ALL TEST ITEMS 11
3 . EMC EMISSION TEST 12
3.1 CONDUCTED EMISSION MEASUREMENT 12
3.1.1 POWER LINE CONDUCTED EMISSION LIMITS 12
3.1.2 TEST PROCEDURE 12
3.1.3 DEVIATION FROM TEST STANDARD 12
3.1.4 TEST SETUP 13
3.1.5 EUT OPERATING CONDITIONS 13
3.1.6 TEST RESULTS 14
3.2 RADIATED EMISSION MEASUREMENT 18
3.2.1 RADIATED EMISSION LIMITS 18
3.2.2 TEST PROCEDURE 18
3.2.3 DEVIATION FROM TEST STANDARD 19
3.2.4 TEST SETUP 19
3.2.5 EUT OPERATING CONDITIONS 20
3.2.6 TEST RESULTS (BETWEEN 9KHZ – 30 MHZ) 21
3.2.7 TEST RESULTS (BETWEEN 30MHZ – 1GHZ) 22
3.2.8 TEST RESULTS (1GHZ~25GHZ) 26
3.3 RADIATED BAND EMISSION MEASUREMENT 29
3.3.1 TEST REQUIREMENT: 29
3.3.2 TEST PROCEDURE 29
3.3.3 DEVIATION FROM TEST STANDARD 30
3.3.4 TEST SETUP 30
3.3.5 EUT OPERATING CONDITIONS 30
4 . POWER SPECTRAL DENSITY TEST 32
4.1 APPLIED PROCEDURES / LIMIT 32

Table of Contents **Page**

4.1.1 TEST PROCEDURE 32
4.1.2 DEVIATION FROM STANDARD 32
4.1.3 TEST SETUP 32
4.1.4 EUT OPERATION CONDITIONS 32
4.1.5 TEST RESULTS 33

5 . BANDWIDTH TEST 39

5.1 APPLIED PROCEDURES / LIMIT 39
5.1.1 TEST PROCEDURE 39
5.1.2 DEVIATION FROM STANDARD 39
5.1.3 TEST SETUP 39
5.1.4 EUT OPERATION CONDITIONS 39
5.1.5 TEST RESULTS 40

6 . PEAK OUTPUT POWER TEST 46

6.1 APPLIED PROCEDURES/LIMIT 46

6.1.1 TEST PROCEDURE 46
6.1.2 DEVIATION FROM STANDARD 46
6.1.3 TEST SETUP 46
6.1.4 EUT OPERATION CONDITIONS 46
6.1.5 TEST RESULTS 47

7 . 100 KHZ BANDWIDTH OF FREQUENCY BAND EDGE 48
7.1 APPLICABLE STANDARD 48
7.2 TEST PROCEDURE 48
7.3 DEVIATION FROM STANDARD 48
7.4 TEST SETUP 48
7.5 EUT OPERATION CONDITIONS 48
7.1 TEST RESULTS 48

8 . DUTY CYCLE OF TEST SIGNAL 55

8.1 STANDARD REQUIREMENT 55

8.2 FORMULA: 55

9 . ANTENNA REQUIREMENT 57

9.1 STANDARD REQUIREMENT 57

9.2 EUT ANTENNA 57

10 . EUT TEST PHOTO 58

Table of Contents **Page**

11 . EUT PHOTO **60**
APPENDIX-PHOTOGRAPHS OF EUT CONSTRUCTIONAL DETAILS

1. SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:

FCC Part15 (15.247) , Subpart C			
Standard Section	Test Item	Judgment	Remark
15.207	Conducted Emission	PASS	
15.247 (a)(2)	6dB Bandwidth	PASS	
15.247 (b)	Peak Output Power	PASS	
15.247 (d)	Radiated Spurious Emission	PASS	
15.247 (e)	Power Spectral Density	PASS	
15.205	Restricted Band of Operation	PASS	
15.247 (d)	Band Edge (Out of Band Emissions)	PASS	
15.203	Antenna Requirement	PASS	

NOTE:

(1)" N/A" denotes test is not applicable in this Test Report

1.1 TEST FACILITY

Shenzhen BCTC Testing Co., Ltd.
Add. : BCTC Building & 1-2F, East of B Building, Pengzhou Industrial, Fuyuan 1st Road, Qiaotou Community, Fuyong Street, Bao'an District, Shenzhen, China
FCC Test Firm Registration Number: 712850
Test site MRA number: CN1212
IC Registered No.: 23583

1.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement **y** ± **U** , where expended uncertainty **U** is based on a standard uncertainty multiplied by a coverage factor of **k=2** , providing a level of confidence of approximately **95** %。

No.	Item	Uncertainty
1	3m camber Radiated spurious emission(30MHz-1GHz)	U=4.3dB
2	3m chamber Radiated spurious emission(1GHz-18GHz)	U=4.5dB
3	3m chamber Radiated spurious emission(18GHz-40GHz)	U=3.34dB
4	Conducted Adjacent channel power	U=1.38dB
5	Conducted output power uncertainty Above 1G	U=1.576dB
6	Conducted output power uncertainty below 1G	U=1.28dB
7	humidity uncertainty	U=5.3%
8	Temperature uncertainty	U=0.59 ℃

2. GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF EUT

<table>
<tr><td>Equipment</td><td>WIFI smart led light strip suit</td></tr>
<tr><td>Trade Name</td><td>N/A</td></tr>
<tr><td>Model Name</td><td>CYTT-22</td></tr>
<tr><td>Model Difference</td><td>N/A</td></tr>
<tr><td>Product Description</td><td>
<table>
<tr><td>Operation Frequency:</td><td>802.11b/g/n20MHz:2412~2462 MHz</td></tr>
<tr><td>Modulation Type:</td><td>WIFI: OFDM/DSSS</td></tr>
<tr><td>Bit Rate of Transmitter</td><td>802.11b:11/5.5/2/1 Mbps
802.11g:54/48/36/24/18/12/9/6Mbps
802.11n Up to 75Mbps</td></tr>
<tr><td>Number Of Channel</td><td>802.11b/g/n20MHz:11 CH</td></tr>
<tr><td>Antenna Designation:</td><td>Please see Note 3.</td></tr>
</table>
Based on the application, features, or specification exhibited in User's Manual, the EUT is considered as an ITE/Computing Device. More details of EUT technical specification, please refer to the User's Manual.
</td></tr>
<tr><td>Channel List</td><td>Please refer to the Note 2.</td></tr>
<tr><td>Adapter</td><td>Adapter1:
MODEL:QX36T120300VL
INPUT: 100-240V~50/60Hz 1A
OUTPUT: 12V 3A
Adapter2:
MODEL:YNQX18T120150VL
INPUT: 100-240V~50/60Hz 1A
OUTPUT: 12V 1.5A</td></tr>
<tr><td>Connecting I/O Port(s)</td><td>Please refer to the User's Manual</td></tr>
</table>

Note:

1. For a more detailed features description, please refer to the manufacturer’s specifications or the User's Manual.

2.

Channel List for 802.11b/g/n(20)							
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
01	2412	04	2427	07	2442	10	2457
02	2417	05	2432	08	2447	11	2462
03	2422	06	2437	09	2452		

3.

Table for Filed Antenna

Ant.	Brand	Model Name	Antenna Type	Gain (dBi)	NOTE
1	N/A	N/A	PCB Antenna	1	

2.2 DESCRIPTION OF TEST MODES

Pretest Mode	Description
Mode 1	802.11b CH1/ CH6/ CH11
Mode 2	802.11g CH1/ CH6/ CH11
Mode 3	802.11n20 CH1/ CH6/ CH11
Mode 4	Link Mode

Conducted Emission	
Final Test Mode	Description
Mode 4	Link Mode

For Radiated Emission	
Final Test Mode	Description
Mode 1	802.11b CH1/ CH6/ CH11
Mode 2	802.11g CH1/ CH6/ CH11
Mode 3	802.11n20 CH1/ CH6/ CH11

Note:

(1) The measurements are performed at all Bit Rate of Transmitter, the worst data was reported.

2.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED

Conducted Emission Test



Spurious emissions



2.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	Series No.	Note
E-1	WIFI smart led light strip suit	N/A	CYTT-22	N/A	EUT
E-2	Adapter	N/A	QX36T120300VL	N/A	EUT
E-2	Adapter	N/A	YNQX18T120150VL	N/A	EUT

Item	Shielded Type	Ferrite Core	Length	Note
C-1	NO	NO	1.2M	AC cable unshielded

Note:

(1) The support equipment was authorized by Declaration of Confirmation.

(2) For detachable type I/O cable should be specified the length in cm in 『Length』 column.

2.5 EQUIPMENTS LIST FOR ALL TEST ITEMS

Radiation Test equipment

Item	Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
1	Spectrum Analyzer (9kHz-26.5GHz)	Agilent	E4407B	MY45109572	Jun. 13, 2019	Jun. 12, 2020
2	Test Receiver (9kHz-7GHz)	R&S	ESRP	101154	Jun. 13, 2019	Jun. 12, 2020
3	Bilog Antenna (30MHz-3GHz)	SCHWARZBECK	VULB9163	VULB9163-942	Jun. 22, 2019	Jun. 21, 2020
4	Horn Antenna (1GHz-18GHz)	SCHWARZBECK	BBHA9120D	1541	Jun. 22, 2019	Jun. 21, 2020
5	Horn Antenna (18GHz-40GHz)	SCHWARZBECK	BBHA9170	822	Jun. 22, 2019	Jun. 21, 2020
6	Amplifier (9KHz-6GHz)	SCHWARZBECK	BBV9744	9744-0037	Jun. 25, 2019	Jun. 24, 2020
7	Amplifier (0.5GHz-18GHz)	SCHWARZBECK	BBV9718	9718-309	Jun. 25, 2019	Jun. 24, 2020
8	Amplifier (18GHz-40GHz)	MITEQ	TTA1840-35-HG	2034381	Jun. 17, 2019	Jun. 16, 2020
9	Loop Antenna (9KHz-30MHz)	SCHWARZBECK	FMZB1519B	014	Jul. 02, 2019	Jul. 01, 2020
10	RF cables1 (9kHz-30MHz)	Huber+Suhnar	9kHz-30MHz	B1702988-0008	Jun. 25, 2019	Jun. 24, 2020
11	RF cables2 (30MHz-1GHz)	Huber+Suhnar	30MHz-1GHz	1486150	Jun. 25, 2019	Jun. 24, 2020
12	RF cables3 (1GHz-40GHz)	Huber+Suhnar	1GHz-40GHz	1607106	Jun. 25, 2019	Jun. 24, 2020
13	Power Metter	Keysight	E4419	\	Jun. 17, 2019	Jun. 16, 2020
14	Power Sensor (AV)	Keysight	E9 300A	\	Jun. 17, 2019	Jun. 16, 2020
15	Signal Analyzer 20kHz-26.5GHz	KEYSIGHT	N9020A	MY49100060	Jun. 13, 2019	Jun. 12, 2020
16	Test Receiver 9kHz-40GHz	R&S	FSP40	100550	Jun. 13, 2019	Jun. 12, 2020
17	D.C. Power Supply	LongWei	TPR-6405D	\	\	\
18	Software	Frad	EZ-EMC	FA-03A2 RE	\	\

Conduction Test equipment

Item	Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
1	Test Receiver	R&S	ESR3	102075	Jun. 13, 2019	Jun. 12, 2020
2	LISN	SCHWARZBECK	NSLK8127	8127739	Jun. 13, 2019	Jun. 12, 2020
3	LISN	R&S	ENV216	101375	Jun. 13, 2019	Jun. 12, 2020
4	RF cables	Huber+Suhnar	9kHz-30MHz	B1702988-0008	Jun. 25, 2019	Jun. 24, 2020
5	Software	Frad	EZ-EMC	EMC-CON 3A1	\	\

3. EMC EMISSION TEST

3.1 CONDUCTED EMISSION MEASUREMENT

3.1.1 POWER LINE CONDUCTED EMISSION Limits (Frequency Range 150KHz-30MHz)

FREQUENCY (MHz)	Limit (dBuV)		Standard
	Quasi-peak	Average	
0.15 -0.5	66 - 56 *	56 - 46 *	FCC
0.50 -5.0	56.00	46.00	FCC
5.0 -30.0	60.00	50.00	FCC

Note:

(1) The tighter limit applies at the band edges.

(2) The limit of " * " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.

The following table is the setting of the receiver

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz

3.1.2 TEST PROCEDURE

a. The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.

b. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.

c. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.

d. LISN at least 80 cm from nearest part of EUT chassis.

e. For the actual test configuration, please refer to the related Item –EUT Test Photos.

3.1.3 DEVIATION FROM TEST STANDARD

No deviation

3.1.4 TEST SETUP



Note: 1.Support units were connected to second LISN.
2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

3.1.5 EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.

We pretest AC 120V and AC 240V, the worst voltage was AC 120V and the data recording in the report.

3.1.6 TEST RESULTS

Temperature :	26 ℃	Relative Humidity :	54%
Pressure :	101kPa	Phase :	L
Test Voltage :	AC 120V/60Hz(Adapter1)	Test Mode :	Mode 4



Remark:
1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV		dBuV	dBuV	dB	Detector	Comment
1		0.1600	46.24	9.51	55.75	65.46	-9.71	QP	
2		0.1600	16.34	9.51	25.85	55.46	-29.61	AVG	
3		0.1990	42.59	9.46	52.05	63.65	-11.60	QP	
4		0.1990	12.77	9.46	22.23	53.65	-31.42	AVG	
5	*	0.3180	44.91	9.57	54.48	59.76	-5.28	QP	
6		0.3180	18.04	9.57	27.61	49.76	-22.15	AVG	
7		0.5260	39.83	9.70	49.53	56.00	-6.47	QP	
8		0.5260	21.38	9.70	31.08	46.00	-14.92	AVG	
9		3.1780	34.61	9.67	44.28	56.00	-11.72	QP	
10		3.1780	18.83	9.67	28.50	46.00	-17.50	AVG	
11		11.7540	31.63	9.69	41.32	60.00	-18.68	QP	
12		11.7540	15.67	9.69	25.36	50.00	-24.64	AVG	

Temperature :	26 ℃	Relative Humidity :	54%
Pressure :	101kPa	Phase :	N
Test Voltage :	AC 120V/60Hz(Adapter1)	Test Mode :	Mode 4



Remark:
1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV		dBuV	dBuV	dB	Detector	Comment
1		0.1560	49.12	9.51	58.63	65.67	-7.04	QP	
2		0.1560	19.02	9.51	28.53	55.67	-27.14	AVG	
3		0.1960	45.06	9.46	54.52	63.78	-9.26	QP	
4		0.1960	14.33	9.46	23.79	53.78	-29.99	AVG	
5	*	0.3660	45.63	9.53	55.16	58.59	-3.43	QP	
6		0.3660	17.74	9.53	27.27	48.59	-21.32	AVG	
7		0.6900	32.36	9.68	42.04	56.00	-13.96	QP	
8		0.6900	9.78	9.68	19.46	46.00	-26.54	AVG	
9		4.8140	29.74	9.79	39.53	56.00	-16.47	QP	
10		4.8140	14.80	9.79	24.59	46.00	-21.41	AVG	
11		11.9660	23.48	9.69	33.17	60.00	-26.83	QP	
12		11.9660	12.04	9.69	21.73	50.00	-28.27	AVG	

Temperature :	26 ℃	Relative Humidity :	54%
Pressure :	101kPa	Phase :	L
Test Voltage :	AC 120V/60Hz(Adapter2)	Test Mode :	Mode 4



Remark:
1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV		dBuV	dBuV	dB	Detector	Comment
1		0.1900	38.71	9.47	48.18	64.04	-15.86	QP	
2		0.1900	20.02	9.47	29.49	54.04	-24.55	AVG	
3		0.5340	23.85	9.73	33.58	46.00	-12.42	AVG	
4	*	0.6020	38.19	9.99	48.18	56.00	-7.82	QP	
5		1.7260	36.18	9.58	45.76	56.00	-10.24	QP	
6		2.1580	19.29	9.60	28.89	46.00	-17.11	AVG	
7		4.6140	37.25	9.77	47.02	56.00	-8.98	QP	
8		4.6140	21.05	9.77	30.82	46.00	-15.18	AVG	
9		9.0460	37.07	9.70	46.77	60.00	-13.23	QP	
10		9.1740	20.55	9.70	30.25	50.00	-19.75	AVG	
11		14.3580	16.67	9.70	26.37	50.00	-23.63	AVG	
12		14.6660	32.76	9.70	42.46	60.00	-17.54	QP	

Temperature :	26 ℃	Relative Humidity :	54%
Pressure :	101kPa	Phase :	N
Test Voltage :	AC 120V/60Hz(Adapter2)	Test Mode :	Mode 4



Remark:
1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV		dBuV	dBuV	dB	Detector	Comment
1		0.1580	52.95	9.51	62.46	65.57	-3.11	QP	
2		0.1580	29.16	9.51	38.67	55.57	-16.90	AVG	
3	*	0.5860	45.33	9.94	55.27	56.00	-0.73	QP	
4		0.5860	28.06	9.94	38.00	46.00	-8.00	AVG	
5		0.9460	41.86	9.59	51.45	56.00	-4.55	QP	
6		0.9460	24.02	9.59	33.61	46.00	-12.39	AVG	
7		3.4420	41.34	9.69	51.03	56.00	-4.97	QP	
8		3.4420	22.94	9.69	32.63	46.00	-13.37	AVG	
9		6.6060	38.72	9.74	48.46	60.00	-11.54	QP	
10		6.6060	22.16	9.74	31.90	50.00	-18.10	AVG	
11		10.1980	36.61	9.69	46.30	60.00	-13.70	QP	
12		10.1980	21.71	9.69	31.40	50.00	-18.60	AVG	

3.2 RADIATED EMISSION MEASUREMENT

3.2.1 RADIATED EMISSION LIMITS (Frequency Range 9kHz-1000MHz)

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

FREQUENCY (MHz)	Limit (dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

Notes:

(1) The limit for radiated test was performed according to FCC PART 15C.
(2) The tighter limit applies at the band edges.
(3) Emission level (dBuV/m)=20log Emission level (uV/m).

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	25GHz
RB / VB (emission in restricted band)	1 MHz / 1 MHz for Peak, 1 MHz / *10Hz* for Average

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

3.2.2 TEST PROCEDURE

Below 1GHz test procedure as below:

a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic camber. The table was rotated 360 degrees to determine the position of the highest radiation.
b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

Above 1GHz test procedure as below:

g. Different between above is the test site, change from Semi- Anechoic Chamber to fully Anechoic Chamber and change form table 0.8 metre to 1.5 metre(Above 18GHz the distance is 1 meter and table is 1.5 metre).
h. Test the EUT in the lowest channel ,the middle channel ,the Highest channel

Note:

Both horizontal and vertical antenna polarities were tested
and performed pretest to three orthogonal axis. The worst case emissions were reported

3.2.3 DEVIATION FROM TEST STANDARD

No deviation

3.2.4 TEST SETUP

（A）Radiated Emission Test-Up Frequency Below 30MHz



（B）Radiated Emission Test-Up Frequency 30MHz~1GHz



（C）Radiated Emission Test-Up Frequency Above 1GHz



3.2.5 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

3.2.6 TEST RESULTS (BETWEEN 9KHZ – 30 MHZ)

Temperature:	26℃	Relative Humidtity:	54%
Pressure:	101kPa	Test Voltage :	AC 120V/60Hz
Test Mode :	Mode 4	Polarization :	--

Freq.	Reading	Limit	Margin	State
(MHz)	(dBuV/m)	(dBuV/m)	(dB)	P/F
--	--	--	--	PASS
--	--	--	--	PASS

NOTE:

The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.
Distance extrapolation factor =40 log (specific distance/test distance)(dB);
Limit line = specific limits(dBuv) + distance extrapolation factor.
Test all the modes and only worst case was reported.

3.2.7 TEST RESULTS (BETWEEN 30MHZ – 1GHZ)

Temperature :	26℃	Relative Humidity :	54%
Pressure :	101 kPa	Polarization :	Horizontal
Test Voltage :	AC 120V/60Hz(Adapter1)		
Test Mode :	Mode 4		



Remark:
Factor = Antenna Factor + Cable Loss – Pre-amplifier.

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dB/m	dB	Detector
1		46.9948	35.54	-15.02	20.52	40.00	-19.48	QP
2		99.1797	43.84	-16.43	27.41	43.50	-16.09	QP
3	*	200.6881	56.11	-16.28	39.83	43.50	-3.67	QP
4		304.6099	49.34	-13.47	35.87	46.00	-10.13	QP
5		408.9460	42.24	-10.89	31.35	46.00	-14.65	QP
6	!	827.4934	43.54	-3.02	40.52	46.00	-5.48	QP

Temperature :	26℃	Relative Humidity :	54%
Pressure :	101kPa	Polarization :	Vertical
Test Voltage :	AC 120V/60Hz(Adapter1)		
Test Mode :	Mode 4		



Remark:
Factor = Antenna Factor + Cable Loss – Pre-amplifier.

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dB/m	dB	Detector
1	*	43.8119	49.41	-15.20	34.21	40.00	-5.79	QP
2		97.4560	53.77	-16.74	37.03	43.50	-6.47	QP
3		159.7844	49.66	-18.87	30.79	43.50	-12.71	QP
4		200.6881	48.63	-16.28	32.35	43.50	-11.15	QP
5		303.5437	49.10	-13.50	35.60	46.00	-10.40	QP
6	!	827.4934	43.17	-3.02	40.15	46.00	-5.85	QP

Remark:
Test all the modes and only worst case was reported.

Temperature :	26℃	Relative Humidity :	54%
Pressure :	101 kPa	Polarization :	Horizontal
Test Voltage :	AC 120V/60Hz(Adapter2)		
Test Mode :	Mode 4		



Remark:
Factor = Antenna Factor + Cable Loss – Pre-amplifier.

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dB/m	dB	Detector
1		46.9947	38.04	-15.02	23.02	40.00	-16.98	QP
2		99.1795	43.34	-16.43	26.91	43.50	-16.59	QP
3		160.9088	47.44	-18.80	28.64	43.50	-14.86	QP
4		200.6879	53.11	-16.28	36.83	43.50	-6.67	QP
5		304.6099	48.84	-13.47	35.37	46.00	-10.63	QP
6	*	827.4932	43.54	-3.02	40.52	46.00	-5.48	QP

Temperature :	26℃	Relative Humidity :	54%
Pressure :	101kPa	Polarization :	Vertical
Test Voltage :	AC 120V/60Hz(Adapter2)		
Test Mode :	Mode 4		



Remark:
Factor = Antenna Factor + Cable Loss – Pre-amplifier.

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dB/m	dB	Detector
1		43.8119	46.41	-15.20	31.21	40.00	-8.79	QP
2	*	97.4560	51.77	-16.74	35.03	43.50	-8.47	QP
3		200.6879	47.13	-16.28	30.85	43.50	-12.65	QP
4		303.5437	47.60	-13.50	34.10	46.00	-11.90	QP
5		468.8761	40.61	-9.58	31.03	46.00	-14.97	QP
6		827.4932	40.17	-3.02	37.15	46.00	-8.85	QP

Remark:
Test all the modes and only worst case was reported.

3.2.8 TEST RESULTS (1GHZ~25GHZ)

802.11b

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
Low Channel:2412MHz									
V	4824.00	66.53	39.55	7.85	25.66	60.49	74.00	-13.51	PK
V	4824.00	51.27	39.55	7.85	25.66	45.23	54.00	-8.77	AV
V	7236.00	67.05	38.33	7.52	24.55	60.79	74.00	-13.21	PK
V	7236.00	49.32	38.33	7.52	24.55	43.06	54.00	-10.94	AV
V	15450.00	52.11	35.23	6.75	26.59	50.22	74.00	-23.78	PK
H	4824.00	66.52	39.55	7.85	25.66	60.48	74.00	-13.52	PK
H	4824.00	51.00	39.55	7.85	25.66	44.96	54.00	-9.04	AV
H	7236.00	66.92	38.33	7.52	23.55	59.66	74.00	-14.34	PK
H	7236.00	50.02	38.33	7.52	23.22	42.43	54.00	-11.57	AV
H	15450.00	53.37	35.45	6.75	27.88	52.55	74.00	-21.45	PK

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
Middle Channel:2437MHz									
V	4874.00	66.34	38.89	7.57	25.45	60.47	74.00	-13.53	Pk
V	4874.00	50.32	38.89	7.57	25.45	44.45	54.00	-9.55	AV
V	7311.00	65.91	38.78	7.35	24.78	59.26	74.00	-14.74	Pk
V	7311.00	49.67	38.78	7.35	24.78	43.02	54.00	-10.98	AV
V	15450.00	53.14	35.89	6.42	26.47	50.14	74.00	-23.86	Pk
H	4874.00	66.68	38.89	7.57	25.45	60.81	74.00	-13.19	Pk
H	4874.00	51.47	38.89	7.57	25.45	45.60	54.00	-8.40	AV
H	7311.00	66.35	38.78	7.35	24.78	59.70	74.00	-14.30	Pk
H	7311.00	49.10	38.78	7.35	24.78	42.45	54.00	-11.55	AV
H	15450.00	52.86	36.68	6.42	26.65	49.25	74.00	-24.75	Pk

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
High Channel: 2462MHz									
V	4924.00	67.70	38.75	7.46	25.45	61.86	74.00	-12.14	PK
V	4924.00	50.19	38.75	7.46	25.45	44.35	54.00	-9.65	AV
V	7386.00	64.82	38.65	7.22	24.78	58.17	74.00	-15.83	PK
V	7386.00	48.96	38.65	7.22	24.78	42.31	54.00	-11.69	AV
V	15450.00	53.88	35.58	6.35	26.47	51.12	74.00	-22.88	PK
H	4924.00	67.47	38.75	7.46	25.45	61.63	74.00	-12.37	PK
H	4924.00	52.62	38.75	7.46	25.45	46.78	54.00	-7.22	AV
H	7386.00	66.43	38.65	7.22	24.78	59.78	74.00	-14.22	PK
H	7386.00	50.56	38.65	7.22	24.78	43.91	54.00	-10.09	AV
H	15450.00	53.28	36.42	6.32	26.65	49.83	74.00	-24.17	PK

Remark:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,

Margin= Emission Level - Limit

2. If peak below the average limit, the average emission was no test.

3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

802.11g

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
Low Channel:2412MHz									
V	4824.00	67.96	39.55	7.85	25.66	61.92	74.00	-12.08	PK
V	4824.00	49.85	39.55	7.85	25.66	43.81	54.00	-10.19	AV
V	7236.00	64.49	38.33	7.52	24.55	58.23	74.00	-15.77	PK
V	7236.00	49.53	38.33	7.52	24.55	43.27	54.00	-10.73	AV
V	15450.00	53.15	35.23	6.75	26.59	51.26	74.00	-22.74	PK
H	4824.00	66.37	39.55	7.85	25.66	60.33	74.00	-13.67	PK
H	4824.00	53.66	39.55	7.85	25.66	47.62	54.00	-6.38	AV
H	7236.00	65.42	38.33	7.52	23.55	58.16	74.00	-15.84	PK
H	7236.00	50.31	38.33	7.52	23.22	42.72	54.00	-11.28	AV
H	15450.00	53.58	35.45	6.75	27.88	52.76	74.00	-21.24	PK

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
Middle Channel:2437MHz									
V	4874.00	66.72	38.89	7.57	25.45	60.85	74.00	-13.15	PK
V	4874.00	49.13	38.89	7.57	25.45	43.26	54.00	-10.74	AV
V	7311.00	63.82	38.78	7.35	24.78	57.17	74.00	-16.83	PK
V	7311.00	50.54	38.78	7.35	24.78	43.89	54.00	-10.11	AV
V	15450.00	54.06	35.89	6.42	26.47	51.06	74.00	-22.94	PK
H	4874.00	65.71	38.89	7.57	25.45	59.84	74.00	-14.16	PK
H	4874.00	53.39	38.89	7.57	25.45	47.52	54.00	-6.48	AV
H	7311.00	64.84	38.78	7.35	24.78	58.19	74.00	-15.81	PK
H	7311.00	51.50	38.78	7.35	24.78	44.85	54.00	-9.15	AV
H	15450.00	53.77	36.68	6.42	26.65	50.16	74.00	-23.84	PK

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
High Channel: 2462MHz									
V	4924.00	67.95	38.75	7.46	25.45	62.11	74.00	-11.89	PK
V	4924.00	47.92	38.75	7.46	25.45	42.08	54.00	-11.92	AV
V	7386.00	64.85	38.65	7.22	24.78	58.20	74.00	-15.80	PK
V	7386.00	51.40	38.65	7.22	24.78	44.75	54.00	-9.25	AV
V	15450.00	54.48	35.58	6.35	26.47	51.72	74.00	-22.28	PK
H	4924.00	64.70	38.75	7.46	25.45	58.86	74.00	-15.14	PK
H	4924.00	54.09	38.75	7.46	25.45	48.25	54.00	-5.75	AV
H	7386.00	64.60	38.65	7.22	24.78	57.95	74.00	-16.05	PK
H	7386.00	53.03	38.65	7.22	24.78	46.38	54.00	-7.62	AV
H	15450.00	52.79	36.42	6.32	26.65	49.34	74.00	-24.66	PK

Remark:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,

Margin= Emission Level - Limit

2. If peak below the average limit, the average emission was no test.

3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

802.11n(20MHz)

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
Low Channel:2412MHz									
V	4824.00	69.09	39.55	7.85	25.66	63.05	74.00	-10.95	PK
V	4824.00	47.34	39.55	7.85	25.66	41.30	54.00	-12.70	AV
V	7236.00	66.01	38.33	7.52	24.55	59.75	74.00	-14.25	PK
V	7236.00	50.06	38.33	7.52	24.55	43.80	54.00	-10.20	AV
V	15450.00	55.72	35.23	6.75	26.59	53.83	74.00	-20.17	PK
H	4824.00	64.95	39.55	7.85	25.66	58.91	74.00	-15.09	PK
H	4824.00	54.05	39.55	7.85	25.66	48.01	54.00	-5.99	AV
H	7236.00	63.69	38.33	7.52	23.55	56.43	74.00	-17.57	PK
H	7236.00	52.26	38.33	7.52	23.22	44.67	54.00	-9.33	AV
H	15450.00	54.02	35.45	6.75	27.88	53.20	74.00	-20.80	PK

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
Middle Channel:2437MHz									
V	4874.00	68.36	38.89	7.57	25.45	62.49	74.00	-11.51	PK
V	4874.00	47.92	38.89	7.57	25.45	42.05	54.00	-11.95	AV
V	7311.00	66.07	38.78	7.35	24.78	59.42	74.00	-14.58	PK
V	7311.00	51.20	38.78	7.35	24.78	44.55	54.00	-9.45	AV
V	15450.00	54.60	35.89	6.42	26.47	51.60	74.00	-22.40	PK
H	4874.00	65.52	38.89	7.57	25.45	59.65	74.00	-14.35	PK
H	4874.00	53.39	38.89	7.57	25.45	47.52	54.00	-6.48	AV
H	7311.00	62.60	38.78	7.35	24.78	55.95	74.00	-18.05	PK
H	7311.00	52.16	38.78	7.35	24.78	45.51	54.00	-8.49	AV
H	15450.00	54.20	36.68	6.42	26.65	50.59	74.00	-23.41	PK

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
High Channel: 2462MHz									
V	4924.00	69.46	38.75	7.46	25.45	63.62	74.00	-10.38	PK
V	4924.00	48.03	38.75	7.46	25.45	42.19	54.00	-11.81	AV
V	7386.00	67.54	38.65	7.22	24.78	60.89	74.00	-13.11	PK
V	7386.00	51.62	38.65	7.22	24.78	44.97	54.00	-9.03	AV
V	15450.00	53.76	35.58	6.35	26.47	51.00	74.00	-23.00	PK
H	4924.00	66.84	38.75	7.46	25.45	61.00	74.00	-13.00	PK
H	4924.00	54.43	38.75	7.46	25.45	48.59	54.00	-5.41	AV
H	7386.00	63.01	38.65	7.22	24.78	56.36	74.00	-17.64	PK
H	7386.00	53.01	38.65	7.22	24.78	46.36	54.00	-7.64	AV
H	15450.00	53.06	36.42	6.32	26.65	49.61	74.00	-24.39	PK

Remark:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,

Margin= Emission Level - Limit

2. If peak below the average limit, the average emission was no test.

3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

3.3 RADIATED BAND EMISSION MEASUREMENT

3.3.1 TEST REQUIREMENT:

FCC Part15 C Section 15.209 and 15.205

LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

FREQUENCY (MHz)	Class B (dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

Notes:

(1) The limit for radiated test was performed according to FCC PART 15C.

(2) The tighter limit applies at the band edges.

(3) Emission level (dBuV/m)=20log Emission level (uV/m).

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	2300MHz
Stop Frequency	2520
RB / VB (emission in restricted band)	1 MHz / 1 MHz for Peak, 1 MHz / 10Hz for Average

3.3.2 TEST PROCEDURE

Above 1GHz test procedure as below:

a. 1. The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation.

b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.

c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.

d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading.

e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.

f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

g. Test the EUT in the lowest channel,the Highest channel

Note:

Both horizontal and vertical antenna polarities were tested
and performed pretest to three orthogonal axis. The worst case emissions were reported

3.3.3 DEVIATION FROM TEST STANDARD

No deviation

3.3.4 TEST SETUP

Radiated Emission Test-Up Frequency Above 1GHz



3.3.5 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.

3.3.6 TEST RESULT

	Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB/m)	Emission evel (dBuV/m)	Limits (dBuV/m)		Result
							PK	PK	AV	
802.11b	**Low Channel 2412MHz**									
	H	2390.00	60.20	38.06	7.42	20.15	49.71	74.00	54.00	PASS
	H	2400.00	53.62	38.06	7.42	20.15	43.13	74.00	54.00	PASS
	V	2390.00	62.34	38.06	7.42	20.15	51.85	74.00	54.00	PASS
	V	2400.00	53.13	38.06	7.42	20.15	42.64	74.00	54.00	PASS
	High Channel 2462MHz									
	H	2483.50	58.95	38.17	7.45	20.54	48.77	74.00	54.00	PASS
	H	2485.50	51.52	38.17	7.45	20.54	41.34	74.00	54.00	PASS
	V	2483.50	62.22	38.2	7.45	20.54	52.01	74.00	54.00	PASS
	V	2485.50	54.50	38.2	7.45	20.54	44.29	74.00	54.00	PASS
802.11g	**Low Channel 2412MHz**									
	H	2390.00	59.33	38.06	7.42	20.15	48.84	74.00	54.00	PASS
	H	2400.00	53.02	38.06	7.42	20.15	42.53	74.00	54.00	PASS
	V	2390.00	61.88	38.06	7.42	20.15	51.39	74.00	54.00	PASS
	V	2400.00	53.97	38.06	7.42	20.15	43.48	74.00	54.00	PASS
	High Channel 2462MHz									
	H	2483.50	59.44	38.17	7.45	20.54	49.26	74.00	54.00	PASS
	H	2485.50	55.22	38.17	7.45	20.54	45.04	74.00	54.00	PASS
	V	2483.50	63.17	38.2	7.45	20.54	52.96	74.00	54.00	PASS
	V	2485.50	53.29	38.2	7.45	20.54	43.08	74.00	54.00	PASS
802.11n20	**Low Channel 2412MHz**									
	H	2390.00	59.43	38.06	7.42	20.15	48.94	74.00	54.00	PASS
	H	2400.00	53.20	38.06	7.42	20.15	42.71	74.00	54.00	PASS
	V	2390.00	61.88	38.06	7.42	20.15	51.39	74.00	54.00	PASS
	V	2400.00	53.21	38.06	7.42	20.15	42.72	74.00	54.00	PASS
	High Channel 2462MHz									
	H	2483.50	61.38	38.17	7.45	20.54	51.20	74.00	54.00	PASS
	H	2485.50	55.10	38.17	7.45	20.54	44.92	74.00	54.00	PASS
	V	2483.50	59.65	38.2	7.45	20.54	49.44	74.00	54.00	PASS
	V	2485.50	55.05	38.2	7.45	20.54	44.84	74.00	54.00	PASS

Remark:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier, Margin= Emission Level - Limit
2. If the PK measured levels comply with average limit, then the average level were deemed to comply with average limit.

4. POWER SPECTRAL DENSITY TEST

4.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247	Power Spectral Density	8 dBm (in any 3KHz)	2400-2483.5	PASS

4.1.1 TEST PROCEDURE

1. Set analyzer center frequency to DTS channel center frequency.
2. Set the span to 1.5 times the DTS bandwidth.
3. Set the RBW to: 3 kHz ≤ RBW ≤ 100 kHz.
4. Set the VBW ≥ 3 x RBW.
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum amplitude level within the RBW.
10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

4.1.2 DEVIATION FROM STANDARD

No deviation.

4.1.3 TEST SETUP

4.1.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.1 Unless otherwise a special operating condition is specified in the follows during the testing.
Note: Power Spectral Density(dBm)=Reading+Cable Loss

4.1.5 TEST RESULTS

Temperature :	26℃	Relative Humidity :	54%
Pressure :	101kPa	Test Voltage :	AC 120V/60Hz
Test Mode :	TX b Mode		

Frequency	Power Spectral Density(dBm)	Limit (dBm)	Result
2412 MHz	-18.355	8	PASS
2437 MHz	-17.941	8	PASS
2462 MHz	-18.179	8	PASS

TX CH01

TX CH06

TX CH11

Temperature :	26℃	Relative Humidity :	54%
Pressure :	101kPa	Test Voltage :	AC 120V/60Hz
Test Mode :	TX g Mode		

Frequency	Power Spectral Density(dBm)	Limit (dBm)	Result
2412 MHz	-20.294	8	PASS
2437 MHz	-19.765	8	PASS
2462 MHz	-20.802	8	PASS

TX CH01



TX CH06



TX CH11



Temperature :	26℃	Relative Humidity :	54%
Pressure :	101kPa	Test Voltage :	AC 120V/60Hz
Test Mode :	TX n Mode(20M)		

Frequency	Power Spectral Density(dBm)	Limit (dBm)	Result
2412 MHz	-21.929	8	PASS
2437 MHz	-21.913	8	PASS
2462 MHz	-22.000	8	PASS

TX CH01



TX CH06



TX CH11



5. BANDWIDTH TEST

5.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(a)(2)	Bandwidth	>= 500KHz (6dB bandwidth)	2400-2483.5	PASS

5.1.1 TEST PROCEDURE

1. Set RBW = 100 kHz.
2. Set the video bandwidth (VBW) ≥ 3 x RBW.
3. Detector = Peak.
4. Trace mode = max hold.
5. Sweep = auto couple.
6. Allow the trace to stabilize.
7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

5.1.2 DEVIATION FROM STANDARD

No deviation.

5.1.3 TEST SETUP



5.1.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

5.1.5 TEST RESULTS

Temperature :	26℃	Relative Humidity :	54%
Pressure :	101kPa	Test Voltage :	AC 120V/60Hz
Test Mode :	TX b Mode		

Frequency (MHz)	6dB bandwidth (MHz)	Limit (kHz)	Result
2412	10.06	500	Pass
2437	10.04	500	Pass
2462	10.05	500	Pass

TX CH 01



TX CH 06



TX CH 11



Temperature :	26℃	Relative Humidity :	54%
Pressure :	101kPa	Test Voltage :	AC 120V/60Hz
Test Mode :	TX g Mode		

Frequency (MHz)	6dB bandwidth (MHz)	Limit (kHz)	Result
2412	16.41	500	Pass
2437	16.42	500	Pass
2462	16.43	500	Pass

TX CH 01



TX CH 06



TX CH 11



Temperature :	26℃	Relative Humidity :	54%
Pressure :	101kPa	Test Voltage :	AC 120V/60Hz
Test Mode :	TX n Mode(20M)		

Frequency (MHz)	6dB bandwidth (MHz)	Limit (kHz)	Result
2412	17.57	500	Pass
2437	17.56	500	Pass
2462	17.57	500	Pass

TX CH 01



TX CH 06



TX CH 11



6. PEAK OUTPUT POWER TEST

6.1 APPLIED PROCEDURES/LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(b)(3)	Peak Output Power	1 watt or 30dBm	2400-2483.5	PASS

6.1.1 TEST PROCEDURE

a. The EUT was directly connected to the Power meter

6.1.2 DEVIATION FROM STANDARD

No deviation.

6.1.3 TEST SETUP



6.1.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

6.1.5 TEST RESULTS

Temperature :	26℃	Relative Humidity :	54%
Pressure :	101kPa	Test Voltage :	AC 120V/60Hz

	Frequency	Maximum Conducted Output Power(PK)	LIMIT
	(MHz)	(dBm)	dBm
802.11b	2412	9.50	30
	2437	9.46	30
	2462	9.36	30
802.11g	2412	8.06	30
	2437	8.71	30
	2462	8.67	30
802.11n20	2412	7.89	30
	2437	7.45	30
	2462	7.86	30

7. 100 KHZ BANDWIDTH OF FREQUENCY BAND EDGE

7.1 APPLICABLE STANDARD

in any 100 kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator in operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, In addition, radiated emissions which fall in the restricted bands, as defined in§15.205(a), must also comply with the radiated emission limits specified in15.209(a).

7.2 TEST PROCEDURE

Using the following spectrum analyzer setting:

a) Set the RBW = 100KHz.
b) Set the VBW = 300KHz.
c) Sweep time = auto couple.
d) Detector function = peak.
e) Trace mode = max hold.
f) Allow trace to fully stabilize.

7.3 DEVIATION FROM STANDARD

No deviation.

7.4 TEST SETUP



7.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

7.1 TEST RESULTS

802.11b: Band Edge, Left Side



802.11b: Band Edge, Right Side

802.11g: Band Edge, Left Side



802.11g: Band Edge, Right Side



802.11n-HT20: Band Edge, Left Side



802.11n-HT20: Band Edge, Right Side

CONDUCTED EMISSION MEASUREMENT

802.11b

Low Channel 2412MHz

Middle Channel 2437MHz

High Channel 2462MHz

802.11g

Low Channel 2412MHz

Middle Channel 2437MHz

High Channel 2462MHz

802.11n20

Low Channel 2412MHz

Middle Channel 2437MHz



High Channel 2462MHz

8. DUTY CYCLE OF TEST SIGNAL

8.1 STANDARD REQUIREMENT

Pre-analysis Check: While conducting average power measurement, duty cycle of each mode shall be checked to ensure its duty cycle in order to compensate for the loss due to insufficient ratio of duty cycle.

All duty cycle is pre-scanned, and result as obtained below shows only the most representative ones where duty cycle is conducted as the given transmission with given virtual operation that expresses the percentage.

8.2 FORMULA:

Duty Cycle = Ton / (Ton+Toff)

Measurement Procedure:

1. Set span = Zero
2. RBW = 8MHz
3. VBW = 8MHz,
4. Detector = Peak

Duty Cycle:

	Duty Cycle	Duty Fator (dB)
802.11b	1	0
802.11g	1	0
802.11n(HT20)	1	0

802.11b



802.11g



802.11n(HT20)



9. ANTENNA REQUIREMENT

9.1 STANDARD REQUIREMENT

15.203 requirement: For intentional device, according to 15.203: an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

9.2 EUT ANTENNA

The EUT antenna is PCB Antenna, It comply with the standard requirement.

10. EUT TEST PHOTO

Conducted Measurement Photos

Radiated Measurement Photos



11. EUT PHOTO



※※※※※ END OF REPORT ※※※※※