

Prüfbericht-Nr.: Test report no.:	IN25EGGI 001	Auftrags-Nr.: Order no.:	147013404 070	Seite 1 von 36 Page 1 of 36
Kunden-Referenz-Nr.: Client reference no.:	2009322	Auftragsdatum: Order date:	2025-01-24	
Auftraggeber: Client:	ABMRC, LLC 860 Blue Gentian Road, Suite 200, Eagan, Minnesota-55121, USA			
Prüfgegenstand: Test item:	BiWaze Cough			
Bezeichnung / Typ-Nr.: Identification / Type no.:	2037351818-20113	Serien -Nr.: Serial no.:	CNS25C772	
Auftrags-Inhalt: Order content:	Testing and issue of Test Report with Grant Certificate			
Prüfgrundlage: Test specification:	FCC Part15 SubpartC 15.247; 15.205; 15.207; 15.209 RSS 247 Issue 4; RSS Gen Issue 5			
Wareneingangsdatum: Date of sample receipt:	2025-09-05			
Prüfmuster-Nr.: Test sample no.:	A004085214-002			
Prüfzeitraum: Testing period:	2025-09-05 - 2025-09-12			
Ort der Prüfung: Place of testing:	Wireless laboratory, Bangalore			
Prüflaboratorium: Testing laboratory:	TÜV Rheinland (India) Pvt.Ltd., 27/B, 2nd Cross, Electronic City Phase1 Bangalore -560 100, India FCC Test site registration number: 496599 ISED Test site registration number: 27711			
Prüfergebnis*: Test result*:	Pass			
geprüft von: tested by:			genehmigt von: authorized by:	
Datum: Date: 2025-11-20	Signed by: Naveen Kumar Muthyalapati Venkata		Ausstellungsdatum: Issue date: 2025-11-20	Signed by: Madhu Nagaraju
Stellung / Position:	M.V.Naveen Kumar Senior Engineer	Stellung / Position:	Madhu K.N Assistant Manager	
Sonstiges / Other:	FCC ID: 2ATX9-1395A IC: 33185-1890A HVIN: 2037351818-1890			
Zustand des Prüfgegenstandes bei Anlieferung: Condition of the test item at delivery:	Prüfmuster vollständig und unbeschädigt Test item complete and undamaged			
* Legende:	P(ass) = entspricht o.g. Prüfgrundlage(n) F(ail) = entspricht nicht o.g. Prüfgrundlage(n) N/A = nicht anwendbar N/T = nicht getestet			
* Legend:	P(ass) = passed a.m. test specification(s) F(ail) = failed a.m. test specification(s) N/A = not applicable N/T = not tested			
Dieser Prüfbericht bezieht sich nur auf das o.g. Prüfmuster und darf ohne Genehmigung der Prüfstelle nicht auszugsweise vervielfältigt werden. Dieser Bericht berechtigt nicht zur Verwendung eines Prüfzeichens. <i>This test report only relates to the above mentioned test sample. Without permission of the test center this test report is not permitted to be duplicated in extracts. This test report does not entitle to carry any test mark.</i>				

Prüfbericht - Nr.:

Test Report No.:

IN25EGGI 001

Seite 2 von 36

Page 2 of 36

- | | |
|---|--|
| 1 | <p>Alle eingesetzten Prüfmittel waren zum angegebenen Prüfzeitraum gemäß eines festgelegten Kalibrierungsprogramms unseres Prüfhauses kalibriert. Sie entsprechen den in den Prüfprogrammen hinterlegten Anforderungen. Die Rückverfolgbarkeit der eingesetzten Prüfmittel ist durch die Einhaltung der Regelungen unseres Managementsystems gegeben.</p> <p>Detaillierte Informationen bezüglich Prüfkonditionen, Prüfequipment und Messunsicherheiten sind im Prüflabor vorhanden und können auf Wunsch bereitgestellt werden.</p> <p><i>The equipment used during the specified testing period was calibrated according to our test laboratory calibration program. The equipment fulfils the requirements included in the relevant standards. The traceability of the test equipment used is ensured by compliance with the regulations of our management system. Detailed information regarding test conditions, equipment and measurement uncertainty is available in the test laboratory and could be provided on request.</i></p> |
| 2 | <p>Wie vertraglich vereinbart, wurde dieses Dokument nur digital unterzeichnet. Der TÜV Rheinland hat nicht überprüft, welche rechtlichen oder sonstigen diesbezüglichen Anforderungen für dieses Dokument gelten. Diese Überprüfung liegt in der Verantwortung des Benutzers dieses Dokuments. Auf Verlangen des Kunden kann der TÜV Rheinland die Gültigkeit der digitalen Signatur durch ein gesondertes Dokument bestätigen. Diese Anfrage ist an unseren Vertrieb zu richten. Eine Umweltgebühr für einen solchen zusätzlichen Service wird erhoben. Informationen zur Verifizierung der Authentizität unserer Dokumente erhalten Sie auf folgender Webseite: go.tuv.com/digital-signature</p> <p><i>As contractually agreed, this document has been signed digitally only. TUV Rheinland has not verified and unable to verify which legal or other pertaining requirements are applicable for this document. Such verification is within the responsibility of the user of this document. Upon request by its client, TUV Rheinland can confirm the validity of the digital signature by a separate document. Such request shall be addressed to our Sales department. An environmental fee for such additional service will be charged. For information on verifying the authenticity of our documents, please visit the following website: go.tuv.com/digital-signature</i></p> |
| 3 | <p>Prüfklausel mit der Note * wurden an qualifizierte Unterauftragnehmer vergeben und sind unter der jeweiligen Prüfklausel des Berichts beschrieben.</p> <p>Abweichungen von Prüfspezifikation(en) oder Kundenanforderungen sind in der jeweiligen Prüfklausel im Bericht aufgeführt.</p> <p><i>Test clauses with remark of * are subcontracted to qualified subcontractors and described under the respective test clause in the report.</i></p> <p><i>Deviations of testing specification(s) or customer requirements are listed in specific test clause in the report.</i></p> |
| 4 | <p>Die Entscheidungsregel für Konformitätserklärungen basierend auf numerischen Messergebnissen in diesem Prüfbericht basiert auf der "Null-Grenzwert-Regel" und der "Einfachen Akzeptanz" gemäß ILAC G8:2019 und IEC Guide 115:2023, es sei denn, in der auf Seite 1 dieses Berichts genannten angewandten Norm ist etwas anderes festgelegt oder vom Kunden gewünscht. Dies bedeutet, dass die Messunsicherheit nicht berücksichtigt wird und daher auch nicht im Prüfbericht angegeben wird. Zu weiteren Informationen bezüglich des Risikos durch diese Entscheidungsregel siehe ILAC G8:2019.</p> <p><i>The decision rule for statements of conformity, based on numerical measurement results, in this test report is based on the "Zero Guard Band Rule" and "Simple Acceptance" in accordance with ILAC G8:2019 and IEC Guide 115:2023, unless otherwise specified in the applied standard mentioned on Page 1 of this report or requested by the customer. This means that measurement uncertainty is not taken in account and hence also not declared in the test report. For additional information to the resulting risk based of this decision rule please refer to ILAC G8:2019.</i></p> |

Prüfbericht - Nr.:
Test Report No.:

IN25EGGI 001

Seite 3 von 36
Page 3 of 36

TEST SUMMARY

Test Item	Applicable Standard		Result
	FCC	ISED	
Maximum conducted (Peak) output power	FCC 15.247(b)(1)	RSS 247 Issue 4, Section 6.2.3.2 (a)	Pass
Maximum Power Spectral Density	FCC 15.247(e)	-	NA
20dB Bandwidth	FCC 15.247(a)(1)(iii)	RSS 247 Issue 4, Section 6.2.2.1 (a)	N/T
Channel Frequency Separation	15.247(a)(1)	RSS 247 Issue 4, Section 6.2.3.1 (a)	N/T
Number of Hopping Channels	15.247(a)(1)(iii)	RSS 247 Issue 4, Section 6.2.3.1 (b)	N/T
Time of Occupancy(Dwell Time)	15.247(a)(1)(iii)	RSS 247 Issue 4, Section 6.2.3.1 (b)	N/T
Emissions in non-restricted frequency bands	FCC 15.247(d)	RSS 247 Issue 4, Section 6.6	N/T
Spurious Radiated Emissions and Restricted Bands of Operation	FCC 15.209 / FCC 15.205	RSS-Gen Issue 5, Section 8.9 /8.10	Pass
AC Power lines Conducted emission	FCC 15.207	RSS-Gen Issue 5, Section 8.9 /8.10	Pass
Antenna Requirement	FCC 15.203	-	-

N/T: Not Tested – These test cases have not been executed, as the product incorporates the certified RF module: **WLAN Module of AP6212SD** from Ampak Technology Inc. This module has been tested at **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, under **FCC ID: ZQ6-AP6212SD & IC: 11956A-AP6212SD**. Therefore, the mentioned test cases are excluded, and relevant details can be found in the module's test reports of FCC: RF150626C12-1 & IC: IC150626C12-1, corresponding to the respective FCC ID & IC.

FCC Grant Date	IC Grant Date
28/11/2016	20/03/2017

Product Category: Electronics Testing

Test Discipline: EMC Test Facility

Prüfbericht - Nr.:

Test Report No.:

IN25EGGI 001

Seite 4 von 36

Page 4 of 36

REVISION HISTORY OF THIS REPORT

Report Number	Version	Description	Issue date
IN25EGGI 001	01	Initial issue of report	2025-11-20

Table of Contents

1	GENERAL REMARKS	6
1.1	Attachments	6
2	TEST SITES	7
2.1	Testing Facilities	7
2.2	List of Test and Measurement Instruments.....	7
3	GENERAL PRODUCT INFORMATION.....	8
3.1	Product Function and Intended Use	8
3.2	Ratings and System Details of Equipment under Test	8
3.3	Measurement Uncertainty:	9
4	TEST SET-UP AND OPERATION MODE.....	10
4.1	Principle of Configuration Selection	10
4.2	Test Operation and Test Software	10
4.3	Special Accessories and Auxiliary Equipment	10
4.4	Countermeasures to achieve EMC Compliance	10
4.5	List of frequencies	11
4.6	TUV Sample Identification.....	11
5	Operational Description	12
6	TEST METHODOLOGY	13
6.1	AC Power lines Conducted emission	13
6.1.1	Test Setup Configuration.....	13
6.2	Radiated Emission Test	14
6.2.1	Test Setup Configuration.....	14
7	TEST RESULTS	16
7.1	Maximum Peak Conducted Output Power	16
7.2	Spurious Radiated Emissions & Restricted Bands of Operation	18
7.3	AC Power lines Conducted Emission	33
8	LIST OF TABLES.....	36
9	List of Figures	36

Prüfbericht - Nr.:

Test Report No.:

IN25EGGI 001

Seite 6 von 36

Page 6 of 36

1 GENERAL REMARKS

1.1 Attachments

All attachments are part of this test report and are issued in separate document

1. Test Setup photos
2. EUT External Photos
3. EUT Internal Photos
4. FCC Label and Label Location
5. Block Diagram
6. Specification of EUT
7. Schematic Diagrams
8. Bill of Material
9. User Manual
10. Maximum Permissible Exposure Information

Prüfbericht - Nr.:
Test Report No.:

IN25EGGI 001

Seite 7 von 36
Page 7 of 36

2 TEST SITES

2.1 Testing Facilities

1. TÜV Rheinland (India) Pvt.Ltd.,
27/B, 2nd Cross,
ElectronicCityPhase1
Bangalore – 560 100,
India
2. TUV Rheinland (India) Pvt.Ltd.,
108, Beside ISBR Business School,
Electronic city Phase I
Bangalore - 560 100,
India

2.2 List of Test and Measurement Instruments

Table 1: List of test and measurement instruments

Equipment	Manufacturer	Model Name	Serial Number	Firmware Versions	Calibration Due Date	Periodicity	Test Facility
EMI Receiver	Rohde & Schwarz	ESW 44	103384	3.20SP2	24.06.2026	Yearly	Radiated Spurious Emission
Active loop antenna	Frankonia	LAX-10	LAX-10-800	-	16.04.2026	Yearly	
Balun & Biconical Antenna	Schwarzbeck mess-elektronik	BBA 9106+VH BB 9124	9124-1117	-	27.05.2026	Yearly	
Log-Periodic Antenna	Schwarzbeck mess-elektronik	VUSLP 9111B	9111B-324	-	26.05.2026	Yearly	
Horn Antenna	Schwarzbeck	BBHA 9120 D	9120D-01944	-	12.11.2025	Yearly	
Horn Antenna	Schwarzbeck	BBHA 9170	BBHA 9170-0904	-	14.02.2026	Yearly	
EMI Test Receiver	Rohde & Schwarz	ESW44	101773	1.72.SP1	26.01.2026	Yearly	
Semi Anechoic Chamber	Frankonia	-	-	-	-	-	
Fully Anechoic Chamber	Albatross	-	-	-	-	-	
Spectrum Analyzer	Agilent	E4407B	US411927 72	A.14.07	16.01.2026	Yearly	Conducted Test Parameters
10 dB RF Attenuator (DUT-1)	Rohde & Schwarz	-	-	-	15.10.2025	Yearly	
EMI Receiver	Rohde & Schwarz	ESR7	101133	3.48 SP3	20.05.2026	Yearly	Conducted AC Power line Test
Two Line LISN	Scientific	SMLIN6 3-2	161101	-	06.03.2026	Yearly	
Pulse limiter [0 - 30 MHz]	Rohde & Schwarz	ESH3-Z2	100811	-	26.06.2026	Yearly	

Table 2: Instrument application Software versions

SL. No.	Test Type	Application software	Version
1	Radiated spurious emission measurement in FAC	EMC 32	10.60.20
2	Radiated spurious emission measurement in 10mtr SAC	BAT EMC	3.20.0.17

3 GENERAL PRODUCT INFORMATION

3.1 Product Function and Intended Use

This product is used for assisting patients to clear retained bronchopulmonary secretions by gradually applying positive pressure to the airway, then rapidly shifting to a negative pressure. This rapid shift in pressure, via a facemask, mouthpiece or an endotracheal or tracheostomy tube produces a high expiratory flow rate from the lungs, simulating a cough.

This device is designed for use on patients unable to cough or clear secretions effectively due to reduced peak cough expiratory flow, resulting from high spinal cord injuries, neuromuscular deficits or severe fatigue associated with intrinsic lung disease. This device is intended for use in hospital, institutional setting or in home on adult patients and pediatric patients 3 years old and above.

3.2 Ratings and System Details of Equipment under Test

Table 3: Ratings and System Details as declared by Client*

Radio Protocol		Bluetooth
Operating Frequency Range		2402MHz to 2480MHz
No. of Channels		79
Channel Spacing		1MHz
Transmitter Power level(dBm)		8dBm
Measured Power (dBm)		2.91dBm@1Mbps_Ch-2480MHz
Modulation		GFSK, pi/4-DQPSK,8-DPSK
Data Rates		1Mbps,2Mbps,3Mbps
Number of antennas		1
Antenna Gain		1.05dBi(Max gain)
Antenna Type		PIFA Antenna
Supply Voltage to Product		100-230VAC 50Hz/60Hz through mains 25.9VDC through internal Battery (Refer the Data sheet)
Environmental conditions	Storage(°C)	Temperature: -25 °C to 70°C Relative Humidity: 15 to 95% (non-condensing) Atmospheric Pressure: 105 kPa to 65 kPa
	Operating(°C)	Temperature: 5 °C to 35 °C Relative Humidity: 15 to 95% (noncondensing) Atmospheric Pressure: 101 kPa to 77 kPa
EUT Dimension(L x W x H) in inches		27.5 cm L x 23.5 cm W x 9.0 cm H

***Disclaimer:** The information/data is supplied by the client and the same is considered to arrive at the final value. Any changes made apart from the specified specification, can directly impact on the tests results. Refer the products user manual for more details.

3.3 Measurement Uncertainty:

Reported uncertainties represent expanded uncertainties expressed at approximately the 95% confidence level using a coverage factor of $k = 2$

Table 4: Measurement Uncertainty

Parameter	Uncertainty
RF output power, conducted	± 0.67 dB
Power Spectral Density, conducted	± 0.85 dB
Unwanted Emissions, conducted	± 2.58 dB
All emissions, radiated	± 3.67 dB

4 TEST SET-UP AND OPERATION MODE

4.1 Principle of Configuration Selection

Transmission was enabled with highest possible duty cycle transmission on low, mid and high channel.

4.2 Test Operation and Test Software

Hardware Name: 2037351818-1395

UI Software Version: 1.24.0

Firmware Version: 1.19.0

4.3 DUT Configuration

Power Supply: 110VAC /60 Hz AC Mains & Internal Battery

Therapy Configuration: Auto Mode

Pause Pressure: 15cmH₂O for 5 seconds,

Inspiratory Pressure: 70cmH₂O for 5 seconds,

Expiratory Pressure: -70cm H₂O for 5 seconds,

Oscillation: On Condition

4.4 Special Accessories and Auxiliary Equipment

Sl. No	Equipment Name	Make	Model No.	Serial No
1	BiWaze Cough Dual Lumen Circuit with Face Mask	ABMRC	BC23412	--
2	Footswitch	Suns	FSR-21-10W-2-22/4S-PH3.5	--

4.5 Countermeasures to achieve EMC Compliance

- None

4.6 List of frequencies

Frequency Band (MHz)	Channel No.	Channel Frequency (MHz)
2402 – 2480 BT(BDR+EDR)	0	2402
	1	2403
	2	2404
	3	2405
	:	:
	:	:
	:	:
	37	2439
	38	2440
	39	2441
	40	2442
	:	:
	:	:
	:	:
	74	2476
	75	2477
	:	:
	:	:
	78	2480

Table 5: List of BT Centre frequencies

Channel used for BT testing.

Channel low: 2402MHz

Channel mid: 2441MHz

Channel high : 2480MHz

4.7 TUV Sample Identification

1. TUV Sample Identification number: A004085214-002 -- Conducted test Sample.& Radiated test sample

Prüfbericht - Nr.:

Test Report No.:

IN25EGGI 001

Seite 12 von 36

Page 12 of 36

5 Operational Description

BiWaze Cough is used for assisting patients to clear retained bronchopulmonary secretions by gradually applying positive pressure to the airway, then rapidly shifting to a negative pressure. This rapid shift in pressure, via a facemask, mouthpiece or an endotracheal or tracheostomy tube produces a high expiratory flow rate from the lungs, simulating a cough.


6 TEST METHODOLOGY

6.1 AC Power lines Conducted emission

Measured levels of ac powerline conducted emission across the 50Ω LISN port (to which the EUT is connected). All emission voltage and current measurements shall be made on each current-carrying conductor at the plug end of the EUT power cord by the use of mating plugs and receptacles on the LISN, if used. Equipment shall be tested with power cords that are normally supplied or recommended by the manufacturer and that have electrical and shielding characteristics that are the same as those cords normally supplied or recommended by the manufacturer.

The device is placed on the test table, raised 80cm above the reference ground plane. The vertical conducting plane is located 40cm to the rear of the device. AC Conducted emission measurement is made over frequency range from 150 kHz to 30MHz, this measurement was performed an AC adaptor 110V AC 60Hz supply

6.1.1 Test Setup Configuration



6.2 Radiated Emission Test

The radiated emission measurement was performed according to the procedures in ANSI C63.10-2020. The equipment under test (EUT) was placed at the middle of the 80 cm high turntable for below 1 GHz & 1.5 m height for above 1 GHz measurement, and the EUT is 3 meters far from the measuring antenna. The turntable was rotated 360° for obtaining the maximum emission. The height of the measuring antennas was scanned between 1 m and 4 m, and the antenna rotated to repeat the measurements for both the horizontal and vertical antenna polarizations. Repeat the measurement steps until the maximum emissions were obtained. The measurement above 1000 MHz was performed by horn antenna, the measurement below 30 MHz was performed by loop antenna, Measurement from 30 MHz to 200 MHz was performed by Balloon and Biconical Antenna, and measurement from 200 MHz to 1 GHz was performed by Log-Periodic Antenna.

The EUT was rotated around the X-, Y-, and Z-Axis and the results from worst case axis are recorded

6.2.1 Test Setup Configuration




Figure 1: Frequency Range 9 kHz- 30 MHz




Figure 2: Frequency Range 30 MHz – 200 MHz




Figure 3: Frequency Range 200 MHz - 1GHz




Figure 4: Frequency Range above 1 GHz

Prüfbericht - Nr.:
Test Report No.:

IN25EGGI 001

Seite 16 von 36
Page 16 of 36

7 TEST RESULTS

7.1 Maximum Conducted Output Power

Result

Pass

Test Specification	FCC part 15 Subpart C 15.247 (b)(3)/ RSS 247 Issue 4 Section 6.2.3.2 (a)
Test Method	Subclause 11.9.2.3.2 of ANSI C63.10-2020
Detector	Gated RMS
Port of testing	Conducted mode
Requirement	Power ≤ 1 W (30 dBm) & e.i.r.p ≤ 4 W (36dBm)

Test Condition

Normal Test Condition:

Temperature (Norm) = +21.8°C Voltage = 110VAC through AC mains Relative humidity: 55%

KDB Guidelines applied:

Measurements were made as per section 8.3.1.1 in KDB 558074 D01 15.247 Measurement Guidance v05r02.

Prüfbericht - Nr.:

Test Report No.:

IN25EGGI 001

Seite 17 von 36

Page 17 of 36

Test results:

Note:

1. All the losses are included during measurement and final values are mentioned in the test report
2. Total Peak Output power (dBm) = Measured Peak power (dBm) + Cable loss (1dB)
3. This product do not support additional beamforming gain / directional gain, it uses single antenna and hence Directional gain of the single antenna is 1.05 dBi

Data rate	Channel Frequency (MHz)	Measured Gated RMS power (dBm)	Measured e.i.r.p (dBm)	FCC Limit (dBm)	ISED Limit (dBm)
1 Mbps	2402	2.17	3.22	30.00	36.00
	2441	2.38	3.43	30.00	36.00
	2480	2.91	3.96	30.00	36.00
2 Mbps	2402	1.65	2.70	30.00	36.00
	2441	1.74	2.79	30.00	36.00
	2480	1.76	2.81	30.00	36.00
3 Mbps	2402	1.61	2.66	30.00	36.00
	2441	1.69	2.74	30.00	36.00
	2480	1.73	2.78	30.00	36.00

Prüfbericht - Nr.:
Test Report No.:

IN25EGGI 001

Seite 18 von 36
Page 18 of 36

7.2 Spurious Radiated Emissions & Restricted Bands of Operation

Result

Pass

Test Specification	FCC part 15 Subpart C 15.247 (d) / (15.209 & 15.205)/ RSS-Gen Issue 5, Section 8.9 /8.10
Test Method	ANSI C63.10-2020
Measurement Location	Semi Anechoic Chamber 9kHz - 1 GHz Fully Anechoic Chamber 1 GHz - 26GHz
Measurement Bandwidth	100 kHz for frequency range < 1GHz 1 MHz for Frequency range >1GHz
Detector	Refer remarks below
Measuring Distance	3 m
Requirement	As per the limits mentioned in the below table
Test setup	Refer TEST METHODOLOGY

Table 6: Transmitter limits for Radiated emission

Frequency (MHz)	Field strength (μV/m)	Field strength (dBμV/m)	Distance of Measurement (m)
0.009 – 0.490	2400/F(kHz)	48.50 – 13.80	300*
0.490 – 1.705	24000/F(kHz)	33.80 – 23.00	30*
1.705 -30	30	29.54	30*
30-88	100	40.0	3
88-216	150	43.5	3
216-960	200	46.0	3
Above 960	500	54.0	3

Remark: * The limit shows in the table above of frequency range 0.009 – 0.490, 0.490 – 1.705 MHz and 1.705-30MHz is at 300 meter, 30 meter and 30 meter range respectively, which corresponds to 128.51 – 93.80, 73.80 – 62.96 and 69.54 dBμV/m at 3m range by extrapolation calculation and the measurement of loop antenna.

The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9–90 kHz, 110–490 kHz and above 1000 MHz Radiated emission limits in these three bands are based on measurements employing an average detector.

Test Conditions:

Temperature (Norm) = +23.4°C Voltage = 110VAC/60Hz Through AC Mains/Internal Battery

Relative humidity: 58%

Prüfbericht - Nr.:

Test Report No.:

IN25EGGI 001

Seite 19 von 36

Page 19 of 36

Test results:

Note: All the losses are included during measurement and final values are mentioned in the test report. Refer TEST METHODOLOGY for more details

Test results for frequency range 9kHz – 30MHz

No emissions found in frequency range 9 kHz to 30 MHz, and measured levels are below 20dB from the limit line, hence not reported.

Table 7: Test results for frequency range 30MHz – 1GHz

Operating Mode	Antenna Polarization	Measured Frequency (MHz)	Measured emission (dBµV/m)	Limit (dBµV/m)	Margin (dB)
Charging Mode	Vertical	30.01	39.52	40.00	-0.48
		31.07	36.06	40.00	-3.94
		33.56	36.99	40.00	-3.01
		33.78	37.06	40.00	-2.94
		46.93	28.33	40.00	-11.67
		80.00	30.83	40.00	-9.17
		107.93	29.60	43.50	-13.90
		207.89	35.71	43.50	-7.79
		234.47	37.58	46.00	-8.42
		326.69	35.04	46.00	-10.96
		445.49	36.73	46.00	-9.27
	Horizontal	79.99	33.70	40.00	-6.30
		90.03	32.18	43.50	-11.32
		99.99	38.88	43.50	-4.62
		107.75	33.32	43.50	-10.18
		139.82	31.28	43.50	-12.22
		146.07	27.87	43.50	-15.64
		206.90	35.85	43.50	-7.65
		220.13	36.76	46.00	-9.24
		233.97	35.60	46.00	-10.40
		236.03	41.72	46.00	-4.28
		300.02	35.96	46.00	-10.04

Prüfbericht - Nr.:

Test Report No.:

IN25EGGI 001

Seite 20 von 36


Page 20 of 36

Table 8: Test results for frequency range 30MHz – 1GHz

Operating Mode	Antenna Polarization	Measured Frequency (MHz)	Measured emission (dBµV/m)	Limit (dBµV/m)	Margin (dB)
Battery Mode	Vertical	80.01	33.00	40.00	-7.00
		99.99	36.14	43.50	-7.36
		108.27	38.82	43.50	-4.68
		210.44	36.18	43.50	-7.32
		326.69	31.40	46.00	-14.60
		445.49	34.69	46.00	-11.31
	Horizontal	80.02	32.20	40.00	-7.80
		90.01	33.36	43.50	-10.14
		99.98	39.62	43.50	-3.88
		108.01	35.28	43.50	-8.22
		139.96	33.90	43.50	-9.60
		182.68	32.40	43.50	-11.10
		205.12	35.58	43.50	-7.92
		215.85	37.26	43.50	-6.24
		232.36	34.30	46.00	-11.70
		326.69	36.94	46.00	-9.06


Test Plots:

Mode: Charging Mode




Channel Frequency 30MHz – 200MHz

Polarization Vertical




Channel Frequency 30MHz – 200MHz

Polarization Horizontal



Channel Frequency 200MHz – 1GHz


Polarization Vertical



Channel Frequency 200MHz – 1GHz


Polarization Horizontal

Mode: Battery mode




Channel Frequency 30MHz – 200MHz

Polarization Vertical




Channel Frequency 30MHz – 200MHz

Polarization Horizontal



Channel Frequency 200MHz – 1GHz

Polarization Vertical



Channel Frequency 200MHz – 1GHz

Polarization Horizontal

Prüfbericht - Nr.:

Test Report No.:

IN25EGGI 001

Seite 24 von 36

Page 24 of 36

Table 9: Test results for the frequencies above 1GHz:

Data Rate: 1Mbps

Channel Frequency (MHz)	Measured Frequency (MHz)	Antenna Polarization	Measured Emission (dBμV/m)	Limit (dBμV/m)	Margin (dB)
2402	2402(Pk)	Vertical	90.09	-	-
	2402(Av)		87.59	-	-
	2390(Pk)		39.19	74.00*	-34.81
	2390(Av)		26.01	54.00*	-27.99
	4804(Pk)		43.29	74.00	-30.71
	4804(Av)		32.47	54.00	-21.53
	7206(Pk)		48.09	74.00	-25.91
	7206(Av)		35.63	54.00	-18.37
	2402(Pk)	Horizontal	83.99	-	-
	2402(Av)		81.48	-	-
	2390(Pk)		39.11	74.00*	-34.89
	2390(Av)		26.05	54.00*	-27.95
	4804(Pk)		42.55	74.00	-31.45
	4804(Av)		31.32	54.00	-22.68
	7206(Pk)		47.36	74.00	-26.64
	7206(Av)		35.36	54.00	-18.64
2441	2441(Pk)	Vertical	89.79	-	-
	2441(Av)		87.16	-	-
	4882(Pk)		42.39	74.00	-31.61
	4882(Av)		30.81	54.00	-23.19
	7323(Pk)		47.37	74.00	-26.63
	7323(Av)		35.52	54.00	-18.48
	2441(Pk)	Horizontal	85.27	-	-
	2441(Av)		82.30	-	-
	4882(Pk)		42.48	74.00	-31.52
	4882(Av)		30.89	54.00	-23.11
	7323(Pk)		47.57	74.00	-26.43
	7323(Av)		35.29	54.00	-18.71
2480	2480(Pk)	Vertical	91.31	-	-
	2480(Av)		88.84	-	-
	2483.5(Pk)		41.01	74.00*	-32.99
	2483.5(Av)		28.52	54.00*	-25.48
	4960(Pk)		42.25	74.00	-31.75
	4960(Av)		30.26	54.00	-23.74
	7440(Pk)		47.65	74.00	-26.35
	7440(Av)		35.38	54.00	-18.62
	2480(Pk)	Horizontal	85.03	-	-
	2480(Av)		82.57	-	-
	2483.5(Pk)		39.16	74.00*	-34.84
	2483.5(Av)		26.52	54.00*	-27.48
	4960(Pk)		42.24	74.00	-31.76
	4960(Av)		30.11	54.00	-23.89
	7440(Pk)		47.45	74.00	-26.55
	7440(Av)		35.39	54.00	-18.61

_ → Fundamental Frequency

*→ Restricted Band edges

Pk: Peak Detector;

Av: Average Detector

Prüfbericht - Nr.:
Test Report No.:

IN25EGGI 001

Seite 25 von 36
Page 25 of 36

Data Rate: 2Mbps

Channel Frequency (MHz)	Measured Frequency (MHz)	Antenna Polarization	Measured Emission (dBµV/m)	Limit (dBµV/m)	Margin (dB)
2402	2402(Pk)	Vertical	92.32	-	-
	2402(Av)		79.51	-	-
	2390(Pk)		38.82	74.00*	-35.18
	2390(Av)		26.10	54.00*	-27.90
	4804(Pk)		42.30	74.00	-31.70
	4804(Av)		30.08	54.00	-23.92
	7206(Pk)		47.69	74.00	-26.31
	7206(Av)		35.61	54.00	-18.39
	2402(Pk)	Horizontal	85.25	-	-
	2402(Av)		72.56	-	-
	2390(Pk)		39.29	74.00*	-34.71
	2390(Av)		26.06	54.00*	-27.94
	4804(Pk)		41.81	74.00	-32.19
	4804(Av)		29.75	54.00	-24.25
	7206(Pk)		47.28	74.00	-26.72
	7206(Av)		35.38	54.00	-18.62
2441	2441(Pk)	Vertical	91.36	-	-
	2441(Av)		78.58	-	-
	4882(Pk)		41.76	74.00	-32.24
	4882(Av)		30.13	54.00	-23.87
	7323(Pk)		47.81	74.00	-26.19
	7323(Av)		35.47	54.00	-18.53
	2441(Pk)	Horizontal	85.87	-	-
	2441(Av)		73.09	-	-
	4882(Pk)		42.11	74.00	-31.89
	4882(Av)		29.89	54.00	-24.11
	7323(Pk)		47.41	74.00	-26.59
	7323(Av)		35.30	54.00	-18.70
2480	2480(Pk)	Vertical	91.66	-	-
	2480(Av)		78.82	-	-
	2483.5(Pk)		43.44	74.00*	-30.56
	2483.5(Av)		26.80	54.00*	-27.20
	4960(Pk)		42.02	74.00	-31.98
	4960(Av)		29.80	54.00	-24.20
	7440(Pk)		47.30	74.00	-26.70
	7440(Av)		35.43	54.00	-18.57
	2480(Pk)	Horizontal	85.75	-	-
	2480(Av)		72.92	-	-
	2483.5(Pk)		40.00	74.00*	-34.00
	2483.5(Av)		25.94	54.00*	-28.06
	4960(Pk)		42.16	74.00	-31.84
	4960(Av)		29.62	54.00	-24.38
	7440(Pk)		47.93	74.00	-26.07
	7440(Av)		35.38	54.00	-18.62

_ → Fundamental Frequency

*→ Restricted Band edges

Pk: Peak Detector;

Av: Average Detector

Prüfbericht - Nr.:

Test Report No.:

IN25EGGI 001

Seite 26 von 36

Page 26 of 36

Data Rate: 3Mbps

Channel Frequency (MHz)	Measured Frequency (MHz)	Antenna Polarization	Measured Emission (dBμV/m)	Limit (dBμV/m)	Margin (dB)
2402	2402(Pk)	Vertical	92.25	-	-
	2402(Av)		86.86	-	-
	2390(Pk)		39.28	74.00*	-34.72
	2390(Av)		26.16	54.00*	-27.84
	4804(Pk)		43.85	74.00	-30.15
	4804(Av)		31.33	54.00	-22.67
	7206(Pk)		47.44	74.00	-26.56
	7206(Av)		35.66	54.00	-18.34
	2402(Pk)	Horizontal	85.35	-	-
	2402(Av)		79.92	-	-
	2390(Pk)		38.96	74.00*	-35.04
	2390(Av)		26.09	54.00*	-27.91
	4804(Pk)		42.33	74.00	-31.67
	4804(Av)		31.35	54.00	-22.65
	7206(Pk)		47.06	74.00	-26.94
	7206(Av)		35.36	54.00	-18.64
2441	2441(Pk)	Vertical	91.59	-	-
	2441(Av)		86.12	-	-
	4882(Pk)		42.48	74.00	-31.52
	4882(Av)		30.64	54.00	-23.36
	7323(Pk)		48.15	74.00	-25.85
	7323(Av)		35.53	54.00	-18.47
	2441(Pk)	Horizontal	86.13	-	-
	2441(Av)		80.66	-	-
	4882(Pk)		42.40	74.00	-31.60
	4882(Av)		30.12	54.00	-23.88
	7323(Pk)		47.77	74.00	-26.23
	7323(Av)		35.33	54.00	-18.67
2480	2480(Pk)	Vertical	91.93	-	-
	2480(Av)		86.08	-	-
	2483.5(Pk)		43.44	74.00*	-30.56
	2483.5(Av)		28.08	54.00*	-25.92
	4960(Pk)		42.11	74.00	-31.89
	4960(Av)		30.14	54.00	-23.86
	7440(Pk)		47.11	74.00	-26.89
	7440(Av)		35.47	54.00	-18.53
	2480(Pk)	Horizontal	85.90	-	-
	2480(Av)		80.10	-	-
	2483.5(Pk)		39.18	74.00*	-34.82
	2483.5(Av)		26.39	54.00*	-27.61
	4960(Pk)		42.37	74.00	-31.63
	4960(Av)		29.90	54.00	-24.10
	7440(Pk)		47.55	74.00	-26.45
	7440(Av)		35.49	54.00	-18.51

_ → Fundamental Frequency

*→ Restricted Band edges

Pk: Peak Detector;

Av: Average Detector

Prüfbericht - Nr.:

Test Report No.:

IN25EGGI 001

Seite 27 von 36


Page 27 of 36

Test Plots:


Restricted Bands of Operation

Data Rate: 1Mbps

Channel Frequency: 2402MHz




Polarization: Vertical




Polarization: Horizontal

Channel Frequency: 2441MHz




Polarization: Vertical




Polarization: Horizontal

Channel Frequency: 2480MHz



Polarization: Vertical



Polarization: Horizontal


Prüfbericht - Nr.:
Test Report No.:

IN25EGGI 001


Seite 28 von 36
Page 28 of 36

Data Rate: 2Mbps

Channel Frequency: 2402MHz




Polarization: Vertical




Polarization: Horizontal

Channel Frequency: 2441MHz




Polarization: Vertical




Polarization: Horizontal

Channel Frequency: 2480MHz




Polarization: Vertical




Polarization: Horizontal

Data Rate: 3Mbps

Channel Frequency: 2402MHz




Polarization: Vertical




Polarization: Horizontal

Channel Frequency: 2441MHz




Polarization: Vertical




Polarization: Horizontal

Channel Frequency: 2480MHz



Polarization: Vertical




Polarization: Horizontal

Spurious Radiated emission:


Data Rate: 1Mbps

Frequency Range from 1GHz to 18GHz

Channel Frequency: 2402MHz




Polarization: Vertical




Polarization: Horizontal

Channel Frequency: 2441MHz




Polarization: Vertical




Polarization: Horizontal

Channel Frequency: 2480MHz



Polarization: Vertical



Polarization: Horizontal

Prüfbericht - Nr.:
Test Report No.:


IN25EGGI 001

Seite 31 von 36
Page 31 of 36


Data Rate: 2Mbps

Frequency Range from 1GHz to 18GHz

Channel Frequency: 2402MHz




Polarization: Vertical




Polarization: Horizontal

Channel Frequency: 2441MHz




Polarization: Vertical




Polarization: Horizontal

Channel Frequency: 2480MHz



Polarization: Vertical



Polarization: Horizontal

Prüfbericht - Nr.:
Test Report No.:


IN25EGGI 001

Seite 32 von 36
Page 32 of 36


Data Rate: 3Mbps

Frequency Range from 1GHz to 18GHz

Channel Frequency: 2402MHz




Polarization: Vertical




Polarization: Horizontal

Channel Frequency: 2441MHz




Polarization: Vertical




Polarization: Horizontal

Channel Frequency: 2480MHz



Polarization: Vertical



Polarization: Horizontal

Prüfbericht - Nr.:
Test Report No.:

IN25EGGI 001

Seite 33 von 36
Page 33 of 36

7.3 AC Power lines Conducted Emission

Result

Pass

Test Specification : FCC Part 15 Section 15.207/RSS Gen Issue 5 Section 8.8
Test Method : ANSI C 63.10-2020
ANSI C63.10-2020/Cor1-2023
Testing Location : Screened room
Measurement Bandwidth : 9kHz
Frequency Range : 150kHz – 30MHz
Supply Voltage : 110VAC,60Hz
Test Method : Refer TEST METHODOLOGY

Table 10: Limits for Conducted power line emission

Frequency of emission (MHz)	QP Limit (dBμV)	AV Limit (dBμV)
0.15 – 0.5	66 – 56*	56 – 46*
0.5 – 5	56	46
5 – 30	60	50

* Decreases with the logarithm of the frequency

Prüfbericht - Nr.:

Test Report No.:

IN25EGGI 001

Seite 34 von 36


Page 34 of 36

Test Conditions:

Temperature (Norm) = +22.3°C Voltage = 110VAC/60Hz through mains Relative humidity: 57%

Test results:

110VAC-60Hz-Line



Trace	Frequency	Level (dBμV)	Phase	Detector	Delta Limit/dB
2	642.000000000 kHz	42.66		Average	-3.34
2	386.000000000 kHz	44.69		Average	-3.46
2	1.410000000 MHz	41.35		Average	-4.65
2	1.410000000 MHz	41.33		Average	-4.67
2	10.110000000 MHz	45.23		Average	-4.77
2	9.602000000 MHz	45.14		Average	-4.86
2	9.346000000 MHz	45.10		Average	-4.90
2	9.858000000 MHz	45.07		Average	-4.93
2	9.090000000 MHz	45.06		Average	-4.94
1	642.000000000 kHz	46.20		Quasi Peak	-9.80
1	386.000000000 kHz	46.09		Quasi Peak	-12.06
1	894.000000000 kHz	43.70		Quasi Peak	-12.30
1	9.598000000 MHz	46.62		Quasi Peak	-13.38
1	8.578000000 MHz	46.36		Quasi Peak	-13.64
1	322.000000000 kHz	44.91		Quasi Peak	-14.75
1	162.000000000 kHz	47.01		Quasi Peak	-18.35

Prüfbericht - Nr.:


Test Report No.:

IN25EGGI 001

Seite 35 von 36

Page 35 of 36

110VAC-60Hz-Neutral:



Trace	Frequency	Level (dBμV)	Phase	Detector	Delta Limit/dB
2	386.000000000 kHz	44.86		Average	-3.29
2	9.598000000 MHz	43.74		Average	-6.26
2	9.342000000 MHz	43.71		Average	-6.29
2	9.086000000 MHz	43.68		Average	-6.32
2	9.854000000 MHz	43.62		Average	-6.38
2	898.000000000 kHz	39.28		Average	-6.72
2	1.154000000 MHz	38.92		Average	-7.08
1	642.000000000 kHz	44.82		Quasi Peak	-11.18
1	386.000000000 kHz	46.24		Quasi Peak	-11.91
1	506.000000000 kHz	43.70		Quasi Peak	-12.30
1	334.000000000 kHz	44.93		Quasi Peak	-14.42
1	9.598000000 MHz	44.64		Quasi Peak	-15.36
1	9.342000000 MHz	44.26		Quasi Peak	-15.74
1	166.000000000 kHz	47.34		Quasi Peak	-17.82
1	154.000000000 kHz	47.31		Quasi Peak	-18.47

8 LIST OF TABLES

Table 1: List of test and measurement instruments	7
Table 2: Instrument application Software versions	7
Table 3: Ratings and System Details as declared by Client*	8
Table 4: Measurement Uncertainty	9
Table 5: List of BT Centre frequencies	11
Table 6: Transmitter limits for Radiated emission	18
Table 7: Test results for frequency range 30MHz – 1GHz	19
Table 8: Test results for frequency range 30MHz – 1GHz	20
Table 9: Test results for the frequencies above 1GHz:	24
Table 10: Limits for Conducted power line emission	33

9 List of Figures

Figure 1: Frequency Range 9 kHz- 30 MHz	14
Figure 2: Frequency Range 30 MHz – 200 MHz	14
Figure 3: Frequency Range 200 MHz - 1GHz	15
Figure 4: Frequency Range above 1 GHz	15

End of test report