TEST REPORT

FCC Rules Part 15.247

Report Reference No. ..... :	**MTEB23060092-R**	
FCC ID.. ..... :	**2ATYP-HK5910**	
Compiled by (position+printed name+signature):	File administrators Alisa Luo	Alisa Luo
Supervised by (position+printed name+signature):	Test Engineer Sunny Deng	Sunny Deng
Approved by (position+printed name+signature):	Manager Yvette Zhou	Yvette
Date of issue..... :	**Jun.09,2023**	
Representative Laboratory Name ..... :	**Shenzhen Most Technology Service Co., Ltd.**	
Address ..... :	No.5, 2nd Langshan Road, North District, Hi-tech Industrial Park, Nanshan, Shenzhen, Guangdong, China.	
Applicant' s name ..... :	**Shiji (US) Inc.**	
Address ..... :	730 Peachtree Street NE, Suite 375, Atlanta, Georgia, 30319, United States	
Test specification/ Standard ..... **:**	**FCC Rules Part 15.247**	
TRF Originator..... :	Shenzhen Most Technology Service Co., Ltd.	

Shenzhen Most Technology Service Co., Ltd. All rights reserved.
This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen Most Technology Service Co., Ltd. is acknowledged as copyright owner and source of the material. Shenzhen Most Technology Service Co., Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

Test item description..... :	POS COMPUTER
Trade Mark .....:	Shiji
Model/Type reference.....:	HK5910
Listed Models .....:	HK578
Modulation Type .....:	GFSK, π/4DQPSK, 8DPSK
Operation Frequency.....:	From 2402MHz to 2480MHz
Hardware Version.....	HS-J6412
Software Version	MEHL0401
Rating .....:	DC 24V (by Adapter)
Result .....:	PASS

TEST REPORT

Equipment under Test	:	POS COMPUTER
Model /Type	:	HK5910
Listed Models	:	HK578
Remark	:	Only the model name is different, the others are the same.
Applicant	:	**Shiji (US) Inc.**
Address	:	730 Peachtree Street NE, Suite 375, Atlanta, Georgia, 30319, United States
Manufacturer	:	**Shiji (US) Inc.**
Address	:	730 Peachtree Street NE, Suite 375, Atlanta, Georgia, 30319, United States

Test Result:	**PASS**

The test report merely corresponds to the test sample.
It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

Contents

1 REVISION HISTORY 4

2 TEST STANDARDS 5

3 SUMMARY 6

3.1 General Remarks 6
3.2 Product Description 6
3.3 Equipment Under Test 6
3.4 Short description of the Equipment under Test (EUT) 6
3.5 EUT operation mode 7
3.6 Block Diagram of Test Setup 7
3.7 Test Item (Equipment Under Test) Description* 7
3.8 Auxiliary Equipment (AE) Description 7
3.9 Antenna Information* 7
3.10 Related Submittal(s) / Grant (s) 8
3.11 EUT configuration 8
3.12 Modifications 8

4 TEST ENVIRONMENT 9

4.1 Address of the test laboratory 9
4.2 Environmental conditions 9
4.3 Summary of measurement results 10
4.4 Statement of the measurement uncertainty 10
4.5 Equipments Used during the Test 11

5 TEST CONDITIONS AND RESULTS 12

5.1 AC Power Conducted Emission 12
5.2 Radiated Emission 19
5.3 Maximum Peak Output Power 30
5.4 20dB Bandwidth 31
5.5 Frequency Separation 32
5.6 Number of hopping frequency 33
5.7 Time of Occupancy (Dwell Time) 34
5.8 Spurious RF Conducted Emission 35
5.9 Pseudorandom Frequency Hopping Sequence 36
5.10 Antenna Requirement 37

6 TEST SETUP PHOTOS OF THE EUT 38

7 PHOTOS OF THE EUT 41

APPENDIX I.Conducted Peak Output Power 42
APPENDIX II.20dB Bandwidth 43
APPENDIX III.Carrier Frequencies Separation 45
APPENDIX IV.Conducted Out Of Band Emission 47
APPENDIX V.Dwell Time 52
APPENDIX VI.Number Of Hopping Channel 56

1 Revision History

Revision	Issue Date	Revisions	Revised By
00	2023-06-09	Initial Issue	Alisa Luo

2 TEST STANDARDS

The tests were performed according to following standards:

FCC Rules Part 15.247: Frequency Hopping, Direct Spread Spectrum and Hybrid Systems that are in operation within the bands of 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz.
ANSI C63.10-2013: American National Standard for Testing Unlicensed Wireless Devices

3 SUMMARY

3.1 General Remarks

Date of receipt of test sample	:	2023.06.02
Testing commenced on	:	2023.06.05
Testing concluded on	:	2023.06.09

3.2 Product Description

Product Name:	POS COMPUTER
Model/Type reference:	HK5910
Power Supply：	DC 24V (by Adapter)
Testing sample ID：	MTYP01607-1609
Bluetooth :	
Supported Type:	Bluetooth BR/EDR
Modulation:	GFSK, π/4DQPSK, 8DPSK
Operation frequency:	2402MHz~2480MHz
Channel number:	79
Channel separation:	1MHz
Antenna type:	Intergral Antenna
Antenna gain:	5.6dBi

3.3 Equipment Under Test

Power supply system utilised

Power supply voltage	:	○	230V / 50 Hz	○	120V / 60Hz
		○	12 V DC	○	24 V DC
		●	Other (specified in blank below)		

DC 24V (by Adapter)

3.4 Short description of the Equipment under Test (EUT)

This is a BT SPEAKER For more details, refer to the user's manual of the EUT.

3.5 EUT operation mode

The Applicant provides communication tools software(Engineer mode) to control the EUT for staying in continuous transmitting (Duty Cycle more than 98%) and receiving mode for testing .There are 79 channels provided to the EUT and Channel 00/39/78 were selected to test.

Operation Frequency:

Channel	Frequency (MHz)
00	2402
01	2403
⋮	⋮
38	2440
39	2441
40	2442
⋮	⋮
77	2479
78	2480

3.6 Block Diagram of Test Setup



3.7 Test Item (Equipment Under Test) Description*

Short designation	EUT Name	EUT Description	Serial number	Hardware status	Software status
EUT A	Adapter	GM60-240250-F			
EUT B	Adapter	FSP060-DAAN3			
EUT C	Adapter	FSP120-AAAN3			

*: declared by the applicant. According to customers information EUTs A and B are the same devices.

3.8 Auxiliary Equipment (AE) Description

AE short designation	EUT Name (if available)	EUT Description	Serial number (if available)	Software (if used)
AE 1				
AE 2				

3.9 Antenna Information*

Short designation	Antenna Name	Antenna Type	Frequency Range	Serial number	Antenna Peak Gain
Antenna 1	---	Intergral Antenna	2.4 – 2.5 GHz	---	5.6dBi
Antenna 2					

*: declared by the applicant.

3.10 Related Submittal(s) / Grant (s)

This submittal(s) (test report) is intended for the device filing to comply with Section 15.247 of the FCC Part 15, Subpart C Rules.

3.11 EUT configuration

The following peripheral devices and interface cables were connected during the measurement:

● - supplied by the manufacturer

○ - Supplied by the lab

●	ADAPTER 1	M/N:	GM60-240250-F
		Manufacturer:	Foshan Shunde GUANYUDA Power Supply Co., Ltd.
●	ADAPTER 2	M/N:	FSP060-DAAN3
		Manufacturer:	FSP Group Inc.
●	ADAPTER 3	M/N:	FSP120-AAAN3
		Manufacturer:	FSP Group Inc.

3.12 Modifications

No modifications were implemented to meet testing criteria.

4 TEST ENVIRONMENT

4.1 Address of the test laboratory

Shenzhen Most Technology Service Co., Ltd.
No.5, 2nd Langshan Road, North District, Hi-tech Industrial Park, Nanshan, Shenzhen, Guangdong, China.
The 3m-Semi anechoic test site fulfils CISPR 16-1-4 according to ANSI C63.4:2014 and CISPR 16-1-4:2010 SVSWR requirement for radiated emission above 1GHz.

Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

FCC-Registration No.: 0031192610

Shenzhen Most Technology Service Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files.

A2LA-Lab Cert. No.: 6343.01

Shenzhen Most Technology Service Co., Ltd. EMC Laboratory has been accredited by A2LA for technical competence in the field of electrical testing, and proved to be in compliance with ISO/IEC 17025: 2005 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing.

4.2 Environmental conditions

During the measurement the environmental conditions were within the listed ranges:

Radiated Emission:

Temperature:	23 ° C
Humidity:	48 %
Atmospheric pressure:	950-1050mbar

AC Main Conducted testing：

Temperature:	24 ° C
Humidity:	45 %
Atmospheric pressure:	950-1050mbar

Conducted testing：

Temperature:	24 ° C
Humidity:	45 %
Atmospheric pressure:	950-1050mbar

4.3 Summary of measurement results

Test Specification clause	Test case	Test Mode	Test Channel	Recorded In Report		Test result
§15.247(a)(1)	Carrier Frequency separation	GFSK Π/4DQPSK 8DPSK	☒ Lowest ☒ Middle ☒ Highest	GFSK Π/4DQPSK 8DPSK	☒ Middle	Compliant
§15.247(a)(1)	Number of Hopping channels	GFSK Π/4DQPSK 8DPSK	☒ Full	GFSK 8DPSK	☒ Full	Compliant
§15.247(a)(1)	Time of Occupancy (dwell time)	GFSK Π/4DQPSK 8DPSK	☒ Lowest ☒ Middle ☒ Highest	GFSK Π/4DQPSK 8DPSK	☒ Middle	Compliant
§15.247(a)(1)	Spectrumbandwidth of aFHSS system20dB bandwidth	GFSK Π/4DQPSK 8DPSK	☒ Lowest ☒ Middle ☒ Highest	GFSK Π/4DQPSK 8DPSK	☒ Lowest ☒ Middle ☒ Highest	Compliant
§15.247(b)(1)	Maximum outputpower	GFSK Π/4DQPSK 8DPSK	☒ Lowest ☒ Middle ☒ Highest	GFSK Π/4DQPSK 8DPSK	☒ Lowest ☒ Middle ☒ Highest	Compliant
§15.247(d)	Band edgecompliance conducted	GFSK Π/4DQPSK 8DPSK	☒ Lowest ☒ Highest	GFSK Π/4DQPSK 8DPSK	☒ Lowest ☒ Highest	Compliant
§15.205	Band edgecompliance radiated	GFSK Π/4DQPSK 8DPSK	☒ Lowest ☒ Highest	GFSK Π/4DQPSK 8DPSK	☒ Lowest ☒ Highest	Compliant
§15.247(d)	TX spuriousemissions conducted	GFSK Π/4DQPSK 8DPSK	☒ Lowest ☒ Middle ☒ Highest	GFSK Π/4DQPSK 8DPSK	☒ Lowest ☒ Middle ☒ Highest	Compliant
§15.247(d)	TX spuriousemissions radiated	GFSK Π/4DQPSK 8DPSK	☒ Lowest ☒ Middle ☒ Highest	GFSK	☒ Lowest ☒ Middle ☒ Highest	Compliant
§15.209(a)	TX spurious Emissions radiated Below 1GHz	GFSK Π/4DQPSK 8DPSK	☒ Lowest ☒ Middle ☒ Highest	GFSK	☒ Middle	Compliant
§15.107(a) §15.207	Conducted Emissions 9KHz-30 MHz	GFSK Π/4DQPSK 8DPSK	☒ Lowest ☒ Middle ☒ Highest	GFSK	☒ Middle	N/A

Remark:
1. The measurement uncertainty is not included in the test result.
2. We tested all test mode and recorded worst case in report

4.4 Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. to CISPR 16 - 4 „Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC Measurements“ and is documented in the Shenzhen Most Technology Service Co., Ltd. quality system acc. to DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Hereafter the best measurement capability for Shenzhen Most Technology Service Co., Ltd. is reported:

Test	Range	Measurement Uncertainty	Notes
Radiated Emission	30~1000MHz	4.10 dB	(1)
Radiated Emission	1~18GHz	4.32 dB	(1)
Radiated Emission	18-40GHz	5.54 dB	(1)
Conducted Disturbance	0.15~30MHz	3.12 dB	(1)

(1) This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

4.5 Equipments Used during the Test

Item	Equipment	Manufacturer	Model No.	Serial No.	Firmware versions	Last Cal.	Cal. Interval
1.	L.I.S.N.	R&S	ENV216	100093	/	2023/03/17	1 Year
2	Three-phase artificial power network	Schwarzback Mess	NNLK8129	8129178	/	2023/03/17	1 Year
3.	Receiver	R&S	ESCI	100492	V3.0-10-2	2023/03/17	1 Year
4	Receiver	R&S	ESPI	101202	V3.0-10-2	2023/03/17	1 Year
5	Spectrum analyzer	Agilent	9020A	MT-E306	A14.16	2023/03/17	1 Year
6	Bilong Antenna	Sunol Sciences	JB3	A121206	/	2023/03/17	1 Year
7	Horn antenna	HF Antenna	HF Antenna	MT-E158	/	2023/03/17	1 Year
8	Loop antenna	Beijing Daze	ZN30900B	/	/	2023/03/17	1 Year
9	Horn antenna	R&S	OBH100400	26999002	/	2023/03/17	1 Year
10	Wireless Communication Test Set	R&S	CMW500	/	CMW-BASE-3.7.21	2023/03/17	1 Year
11	Spectrum analyzer	R&S	FSP	100019	V4.40 SP2	2023/03/17	1 Year
12	High gain antenna	Schwarzbeck	LB-180400KF	MT-E389	/	2023/03/17	1 Year
13	Preamplifier	Schwarzbeck	BBV 9743	MT-E390	/	2023/03/17	1 Year
14	Pre-amplifier	EMCI	EMC051845SE	MT-E391	/	2023/03/17	1 Year
15	Pre-amplifier	Agilent	83051A	MT-E392	/	2023/03/17	1 Year
16	High pass filter unit	Tonscend	JS0806-F	MT-E393	/	2023/03/17	1 Year
17	RF Cable(below1GHz)	Times	9kHz-1GHz	MT-E394	/	2023/03/17	1 Year
18	RF Cable(above 1GHz)	Times	1-40G	MT-E395	/	2023/03/17	1 Year
19	RF Cable (9KHz-40GHz)	Tonscend	170660	N/A	/	2023/03/17	1 Year

Note: The Cal.Interval was one year.

5 TEST CONDITIONS AND RESULTS

5.1 AC Power Conducted Emission

TEST CONFIGURATION



TEST PROCEDURE

1 The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. The EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.10-2013.
2 Support equipment, if needed, was placed as per ANSI C63.10-2013
3 All I/O cables were positioned to simulate typical actual usage as per ANSI C63.10-2013
4 The EUT received DC 12V power from adapter, the adapter received AC120V/60Hz and AC 240V/60Hz power through a Line Impedance Stabilization Network (LISN) which supplied power source and was grounded to the ground plane.
5 All support equipments received AC power from a second LISN, if any.
6 The EUT test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT.The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
7 Analyzer / Receiver scanned from 150 KHz to 30MHz for emissions in each of the test modes.
8 During the above scans, the emissions were maximized by cable manipulation.

AC Power Conducted Emission Limit

For intentional device, according to § 15.207(a) AC Power Conducted Emission Limits is as following：

Frequency range (MHz)	Limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50
* Decreases with the logarithm of the frequency.		

TEST RESULTS

Remark:

1. All modes were test at Low, Middle, and High channel; only the worst result of Middle Channel was reported as below:
2. Remark: Result=Reading value+Factor,and Margin=Limit- Result
3. GM60-240250-F, FSP060-DAAN3, FSP120-AAAN3 three adapters have been tested, and only the worst adapter(GM60-240250-F) test data is shown

Power supply:	DC 24V (by Adapter)	Polarization	L
M/N:	HK5910(second display: 10.4 inch)		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV	dBuV	dB	Detector	Comment
1		0.1607	33.28	9.61	42.89	55.43	-12.54	AVG	
2	*	0.1700	46.39	9.61	56.00	64.96	-8.96	QP	
3		0.2060	30.78	9.60	40.38	53.37	-12.99	AVG	
4		0.2180	43.48	9.60	53.08	62.89	-9.81	QP	
5		0.4540	36.31	9.59	45.90	56.80	-10.90	QP	
6		0.4660	27.08	9.59	36.67	46.58	-9.91	AVG	
7		0.7460	19.35	9.60	28.95	46.00	-17.05	AVG	
8		0.7500	29.63	9.60	39.23	56.00	-16.77	QP	
9		1.1660	27.80	9.60	37.40	56.00	-18.60	QP	
10		1.1820	17.67	9.60	27.27	46.00	-18.73	AVG	
11		2.0380	15.02	9.60	24.62	46.00	-21.38	AVG	
12		2.1340	26.77	9.60	36.37	56.00	-19.63	QP	

*:Maximum data x:Over limit !:over margin

Power supply:	DC 24V (by Adapter)	Polarization	N
M/N:	HK5910(second display: 10.4 inch)		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV	dBuV	dB	Detector	Comment
1	*	0.1540	50.55	9.60	60.15	65.78	-5.63	QP	
2		0.1540	35.05	9.60	44.65	55.78	-11.13	AVG	
3		0.2128	28.29	9.60	37.89	53.10	-15.21	AVG	
4		0.2140	43.32	9.60	52.92	63.05	-10.13	QP	
5		0.2980	37.37	9.59	46.96	60.30	-13.34	QP	
6		0.3020	26.36	9.59	35.95	50.19	-14.24	AVG	
7		0.4620	36.83	9.59	46.42	56.66	-10.24	QP	
8		0.4620	27.72	9.59	37.31	46.66	-9.35	AVG	
9		0.7780	20.13	9.60	29.73	46.00	-16.27	AVG	
10		0.7900	31.02	9.60	40.62	56.00	-15.38	QP	
11		1.6580	20.06	9.60	29.66	46.00	-16.34	AVG	
12		1.7060	31.61	9.60	41.21	56.00	-14.79	QP	

*:Maximum data x:Over limit !:over margin

Power supply:	DC 24V (by Adapter)	Polarization	L
M/N:	HK5910(second display: 15 inch)		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV	dBuV	dB	Detector	Comment
1	*	0.1806	43.28	9.61	52.89	64.46	-11.57	QP	
2		0.1806	27.95	9.61	37.56	54.46	-16.90	AVG	
3		0.4180	25.74	9.59	35.33	47.49	-12.16	AVG	
4		0.4660	34.38	9.59	43.97	56.58	-12.61	QP	
5		0.8660	27.57	9.60	37.17	56.00	-18.83	QP	
6		0.8740	17.92	9.60	27.52	46.00	-18.48	AVG	
7		1.5020	26.68	9.60	36.28	56.00	-19.72	QP	
8		1.5020	16.08	9.60	25.68	46.00	-20.32	AVG	
9		2.8220	26.07	9.61	35.68	56.00	-20.32	QP	
10		2.8220	11.08	9.61	20.69	46.00	-25.31	AVG	
11		4.6180	22.36	9.63	31.99	56.00	-24.01	QP	
12		4.8100	12.68	9.63	22.31	46.00	-23.69	AVG	

*:Maximum data x:Over limit !:over margin

Power supply:	DC 24V (by Adapter)	Polarization	N
M/N:	HK5910(second display: 15 inch)		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV	dBuV	dB	Detector	Comment
1	*	0.1500	49.73	9.60	59.33	66.00	-6.67	QP	
2		0.1540	32.73	9.60	42.33	55.78	-13.45	AVG	
3		0.2500	27.70	9.60	37.30	51.76	-14.46	AVG	
4		0.2580	39.60	9.60	49.20	61.50	-12.30	QP	
5		0.4540	26.88	9.59	36.47	46.80	-10.33	AVG	
6		0.4820	35.72	9.59	45.31	56.30	-10.99	QP	
7		0.8860	28.43	9.60	38.03	56.00	-17.97	QP	
8		0.8860	18.85	9.60	28.45	46.00	-17.55	AVG	
9		1.4980	27.31	9.60	36.91	56.00	-19.09	QP	
10		1.5100	17.09	9.60	26.69	46.00	-19.31	AVG	
11		2.2980	13.51	9.61	23.12	46.00	-22.88	AVG	
12		2.4700	24.68	9.61	34.29	56.00	-21.71	QP	

*:Maximum data x:Over limit !:over margin

Power supply:	DC 24V (by Adapter)	Polarization	L
M/N:	HK5910(second display: VFD)		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV	dBuV	dB	Detector	Comment
1	*	0.1540	50.24	9.60	59.84	65.78	-5.94	QP	
2		0.1540	34.14	9.60	43.74	55.78	-12.04	AVG	
3		0.2780	35.97	9.59	45.56	60.88	-15.32	QP	
4		0.2780	27.35	9.59	36.94	50.88	-13.94	AVG	
5		0.6540	37.06	9.60	46.66	56.00	-9.34	QP	
6		0.6540	28.03	9.60	37.63	46.00	-8.37	AVG	
7		1.2620	28.13	9.60	37.73	56.00	-18.27	QP	
8		1.2660	18.62	9.60	28.22	46.00	-17.78	AVG	
9		2.4420	29.99	9.61	39.60	56.00	-16.40	QP	
10		2.6340	15.58	9.61	25.19	46.00	-20.81	AVG	
11		3.9900	30.29	9.62	39.91	56.00	-16.09	QP	
12		4.0500	15.72	9.62	25.34	46.00	-20.66	AVG	

*:Maximum data x:Over limit !:over margin

Power supply:	DC 24V (by Adapter)	Polarization	N
M/N:	HK5910(second display: VFD)		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV	dBuV	dB	Detector	Comment
1	*	0.1540	51.07	9.60	60.67	65.78	-5.11	QP	
2		0.1660	35.41	9.61	45.02	55.16	-10.14	AVG	
3		0.2780	37.89	9.59	47.48	60.88	-13.40	QP	
4		0.2780	28.55	9.59	38.14	50.88	-12.74	AVG	
5		0.6620	37.02	9.60	46.62	56.00	-9.38	QP	
6		0.6660	28.74	9.60	38.34	46.00	-7.66	AVG	
7		1.3660	29.00	9.60	38.60	56.00	-17.40	QP	
8		1.4140	18.22	9.60	27.82	46.00	-18.18	AVG	
9		2.0820	30.05	9.60	39.65	56.00	-16.35	QP	
10		2.1580	16.31	9.60	25.91	46.00	-20.09	AVG	
11		4.6100	29.13	9.63	38.76	56.00	-17.24	QP	
12		4.8060	15.14	9.63	24.77	46.00	-21.23	AVG	

*:Maximum data x:Over limit !:over margin

5.2 Radiated Emission

TEST CONFIGURATION

Frequency range 9 KHz – 30MHz



Frequency range 30MHz – 1000MHz



Frequency range above 1GHz-25GHz



TEST PROCEDURE

1. The EUT was placed on a turn table which is 0.8m above ground plane when testing frequency range 9 KHz –1GHz;the EUT was placed on a turn table which is 1.5m above ground plane when testing frequency range 1GHz – 25GHz.
2. Maximum procedure was performed by raising the receiving antenna from 1m to 4m and rotating the turn table from 0° to 360° to acquire the highest emissions from EUT.
3. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
4. Repeat above procedures until all frequency measurements have been completed.
5. Radiated emission test frequency band from 9KHz to 25GHz.
6. The distance between test antenna and EUT as following table states:

Test Frequency range	Test Antenna Type	Test Distance
9KHz-30MHz	Active Loop Antenna	3
30MHz-1GHz	Ultra-Broadband Antenna	3
1GHz-18GHz	Double Ridged Horn Antenna	3
18GHz-25GHz	Horn Anternna	1

7. Setting test receiver/spectrum as following table states:

Test Frequency range	Test Receiver/Spectrum Setting	Detector
9KHz-150KHz	RBW=200Hz/VBW=3KHz,Sweep time=Auto	QP
150KHz-30MHz	RBW=9KHz/VBW=100KHz,Sweep time=Auto	QP
30MHz-1GHz	RBW=120KHz/VBW=1000KHz,Sweep time=Auto	QP
1GHz-40GHz	Peak Value: RBW=1MHz/VBW=3MHz, Sweep time=Auto Average Value: RBW=1MHz/VBW=10Hz, Sweep time=Auto	Peak

Field Strength Calculation

The field strength is calculated by adding the Antenna Factor and Cable Factor and subtracting the Amplifier Gain and Duty Cycle Correction Factor(if any) from the measured reading. The basic equation with a sample calculation is as follows:

FS = RA + AF + CL - AG

Where FS = Field Strength	CL = Cable Attenuation Factor (Cable Loss)
RA = Reading Amplitude	AG = Amplifier Gain
AF = Antenna Factor	

Transd=AF +CL-AG

RADIATION LIMIT

For intentional device, according to § 15.209(a), the general requirement of field strength of radiated emission from intentional radiators at a distance of 3 meters shall not exceed the following table. According to § 15.247(d), in any 100kHz bandwidth outside the frequency band in which the EUT is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the100kHz bandwidth within the band that contains the highest level of desired power.

The pre-test have done for the EUT in three axes and found the worst emission at position shown in test setup photos.

Frequency (MHz)	Distance (Meters)	Radiated (dBμV/m)	Radiated (μV/m)
0.009-0.49	3	20log(2400/F(KHz))+40log(300/3)	2400/F(KHz)
0.49-1.705	3	20log(24000/F(KHz))+ 40log(30/3)	24000/F(KHz)
1.705-30	3	20log(30)+ 40log(30/3)	30
30-88	3	40.0	100
88-216	3	43.5	150

216-960	3	46.0	200
Above 960	3	54.0	500

TEST RESULTS

Remark:

1. This test was performed with EUT in X, Y, Z position and the worse case was found when EUT in X position.
2. We measured Radiated Emission at GFSK, π/4 DQPSK and 8DPSK mode from 9 KHz to 25GHz and recorded worst case at 8DPSK 3DH5 mode.
3. For below 1GHz testing recorded worst at 8DPSK 3DH5 middle channel.
4. Radiated emission test from 9 KHz to 10th harmonic of fundamental was verified, and no emission found except system noise floor in 9 KHz to 30MHz and not recorded in this report.
5. Remark: Result=Reading value+Factor
6. GM60-240250-F, FSP060-DAAN3, FSP120-AAAN3 three adapters have been tested, and only the worst adapter(GM60-240250-F) test data is shown

For 30MHz-1GHz

Horizontal

HK5910(second display: 10.4 inch)



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1		31.2892	3.71	20.02	23.73	40.00	-16.27	QP	200	18	
2		68.1514	15.71	9.17	24.88	40.00	-15.12	QP	200	99	
3		167.8242	15.21	17.04	32.25	43.50	-11.25	QP	200	135	
4		280.0237	11.23	14.82	26.05	46.00	-19.95	QP	200	186	
5		668.1422	12.35	24.69	37.04	46.00	-8.96	QP	200	235	
6	*	896.9965	9.50	28.97	38.47	46.00	-7.53	QP	200	299	

*:Maximum data x:Over limit !:over margin

Vertical

HK5910(second display: 10.4 inch)



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1		41.1320	11.10	13.05	24.15	40.00	-15.85	QP	100	24	
2		79.5208	16.93	10.06	26.99	40.00	-13.01	QP	100	87	
3		167.8242	13.61	17.04	30.65	43.50	-12.85	QP	100	126	
4		333.6867	8.76	16.14	24.90	46.00	-21.10	QP	100	186	
5		533.8321	11.88	23.07	34.95	46.00	-11.05	QP	100	243	
6	*	839.1818	7.77	28.33	36.10	46.00	-9.90	QP	100	305	

*:Maximum data x:Over limit !:over margin

Horizontal

HK5910(second display: 15 inch)



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1		30.8535	5.14	20.32	25.46	40.00	-14.54	QP	200	24	
2		59.4405	7.35	8.57	15.92	40.00	-24.08	QP	200	103	
3		104.1701	21.41	14.06	35.47	43.50	-8.03	QP	200	187	
4		167.8243	14.56	17.04	31.60	43.50	-11.90	QP	200	236	
5		482.2156	10.70	21.76	32.46	46.00	-13.54	QP	200	288	
6	*	665.8035	14.98	24.66	39.64	46.00	-6.36	QP	200	334	

*:Maximum data x:Over limit !:over margin

Vertical

HK5910(second display: 15 inch)



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1		33.5624	10.08	18.48	28.56	40.00	-11.44	QP	100	35	
2		72.0843	17.23	9.47	26.70	40.00	-13.30	QP	100	99	
3		104.1701	20.27	14.06	34.33	43.50	-9.17	QP	100	135	
4	*	166.0680	17.54	17.10	34.64	43.50	-8.86	QP	100	196	
5		332.5187	15.80	16.12	31.92	46.00	-14.08	QP	100	253	
6		584.7894	10.67	23.63	34.30	46.00	-11.70	QP	100	303	

*:Maximum data x:Over limit !:over margin

Horizontal

HK5910(second display: VFD)



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1		68.3908	10.53	9.19	19.72	40.00	-20.28	QP	200	34	
2		133.6188	12.03	16.23	28.26	43.50	-15.24	QP	200	70	
3		195.1365	13.96	15.05	29.01	43.50	-14.49	QP	200	106	
4		307.8313	6.03	15.65	21.68	46.00	-24.32	QP	200	188	
5	*	668.1423	14.70	24.69	39.39	46.00	-6.61	QP	200	235	
6		948.7610	4.43	29.49	33.92	46.00	-12.08	QP	200	306	

*:Maximum data x:Over limit !:over margin

Vertical

HK5910(second display: VFD)



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1		43.8119	18.98	11.28	30.26	40.00	-9.74	QP	100	26	
2		83.5221	15.72	10.03	25.75	40.00	-14.25	QP	100	84	
3		168.4137	16.78	17.02	33.80	43.50	-9.70	QP	100	134	
4		279.0436	12.82	14.79	27.61	46.00	-18.39	QP	100	188	
5		531.9634	10.82	23.05	33.87	46.00	-12.13	QP	100	206	
6	*	839.1818	8.03	28.33	36.36	46.00	-9.64	QP	100	304	

*:Maximum data x:Over limit !:over margin

For 1GHz to 25GHz

Note: GFSK, Pi/4 DQPSK and 8DPSK all have been tested, only worse case 8DPSK *is reported.*

8DPSK (above 1GHz)

Frequency(MHz):			**2402**		**Polarity:**		**HORIZONTAL**		
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
4804	56.62	PK	74	17.38	54.72	31.42	6.98	36.5	1.9
4804	44.8	AV	54	9.2	42.9	31.42	6.98	36.5	1.9
7206	50.7	PK	74	23.3	40.1	37.03	8.87	35.3	10.6
7206	43.15	AV	54	10.85	32.55	37.03	8.87	35.3	10.6

Frequency(MHz):			**2402**		**Polarity:**		**VERTICAL**		
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
4804	54.56	PK	74	19.44	52.66	31.42	6.98	36.5	1.9
4804	43.02	AV	54	10.98	41.12	31.42	6.98	36.5	1.9
7206	52.8	PK	74	21.2	42.2	37.03	8.87	35.3	10.6
7206	42.76	AV	54	11.24	32.16	37.03	8.87	35.3	10.6

Frequency(MHz):			**2441**		**Polarity:**		**HORIZONTAL**		
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
4882	57.33	PK	74	16.67	55.27	30.98	7.58	36.5	2.06
4882	47.06	AV	54	6.94	45	30.98	7.58	36.5	2.06
7323	53.32	PK	74	20.68	42.4	37.66	8.56	35.3	10.92
7323	41.28	AV	54	12.72	30.36	37.66	8.56	35.3	10.92

Frequency(MHz):			**2441**		**Polarity:**		**VERTICAL**		
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
4882	53.86	PK	74	20.14	51.8	30.98	7.58	36.5	2.06
4882	43.49	AV	54	10.51	41.43	30.98	7.58	36.5	2.06
7323	55.29	PK	74	18.71	44.37	37.66	8.56	35.3	10.92
7323	43.75	AV	54	10.25	32.83	37.66	8.56	35.3	10.92

Frequency(MHz):			**2480**		**Polarity:**		**HORIZONTAL**		
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
4960	54.57	PK	74	19.43	51.5	31.47	7.8	36.2	3.07
4960	45.66	AV	54	8.34	42.59	31.47	7.8	36.2	3.07
7440	54.54	PK	74	19.46	42.8	38.32	8.72	35.3	11.74
7440	44.25	PK	54	9.75	32.51	38.32	8.72	35.3	11.74

Frequency(MHz):			**2480**		**Polarity:**		**VERTICAL**		
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
4960	56.59	PK	74	17.41	53.52	31.47	7.8	36.2	3.07
4960	47.33	AV	54	6.67	44.26	31.47	7.8	36.2	3.07
7440	55.95	PK	74	18.05	44.21	38.32	8.72	35.3	11.74
7440	42.03	PK	54	11.97	30.29	38.32	8.72	35.3	11.74

REMARKS:

1. Emission level (dBuV/m) =Raw Value (dBuV)+Correction Factor (dB/m)
2. Correction Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)- Pre-amplifier
3. Margin value = Limit value- Emission level.
4. -- Mean the PK detector measured value is below average limit.
5. The other emission levels were very low against the limit.

Results of Band Edges Test (Radiated)

Note: GFSK, Pi/4 DQPSK and 8DPSK all have been tested, only worse case 8DPSK is reported.

8DPSK

Frequency(MHz):			**2402**		**Polarity:**		**HORIZONTAL**		
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
2390	57.1	PK	74	16.9	62.51	27.49	3.32	36.22	-5.41
2390	41.13	AV	54	12.87	46.54	27.49	3.32	36.22	-5.41
Frequency(MHz):			**2402**		**Polarity:**		**VERTICAL**		
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
2390	58.85	PK	74	15.15	64.26	27.49	3.32	36.22	-5.41
2390	41.62	AV	54	12.38	47.03	27.49	3.32	36.22	-5.41
Frequency(MHz):			**2480**		**Polarity:**		**HORIZONTAL**		
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
2483.5	58.57	PK	74	15.43	64.08	27.45	3.38	36.34	-5.51
2483.5	42.1	AV	54	11.9	47.61	27.45	3.38	36.34	-5.51
Frequency(MHz):			**2480**		**Polarity:**		**VERTICAL**		
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
2483.5	55	PK	74	19	60.51	27.45	3.38	36.34	-5.51
2483.5	39.08	AV	54	14.92	44.59	27.45	3.38	36.34	-5.51

REMARKS:

1. Emission level (dBuV/m) =Raw Value (dBuV)+Correction Factor (dB/m)
2. Correction Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)- Pre-amplifier
3. Margin value = Limit value- Emission level.
4. -- Mean the PK detector measured value is below average limit.

5.3 Maximum Peak Output Power

Limit

The Maximum Peak Output Power Measurement is 125mW (20.97).

Test Procedure

Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the powersensor.

Test Configuration



Test Results

See Appendix I

5.4 20dB Bandwidth

Limit

For frequency hopping systems operating in the 2400MHz-2483.5MHz no limit for 20dB bandwidth.

Test Procedure

The transmitter output was connected to the spectrum analyzer through an attenuator. The bandwidth of the fundamental frequency was measured by spectrum analyzer with 30 KHz RBW and 100 KHz VBW.

The 20dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 20dB.

Test Configuration



Test Results

See Appendix II

5.5 Frequency Separation

LIMIT

According to 15.247(a)(1),frequency hopping systems shall have hopping channel carrier frequencies separated by minimum of 25KHz or the 2/3*20dB bandwidth of the hopping channel, whichever is greater.

TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer through an attenuator. The bandwidth of the fundamental frequency was measured by spectrum analyzer with100 KHz RBW and 300 KHz VBW.

TEST CONFIGURATION



TEST RESULTS

See Appendix III

5.6 Number of hopping frequency

Limit

Frequency hopping systems in the 2400–2483.5 MHz band shall use at least 15 channels.

Test Procedure

The transmitter output was connected to the spectrum analyzer through an attenuator. Set spectrum analyzer start 2400MHz to 2483.5MHz with 100 KHz RBW and 300 KHz VBW.

Test Configuration



Test Results

See Appendix VI

5.7 Time of Occupancy (Dwell Time)

Limit

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

Test Procedure

The transmitter output was connected to the spectrum analyzer through an attenuator. Set center frequency of spectrum analyzer=operating frequency with 1MHz RBW and 1MHz VBW, Span 0Hz.

Test Configuration



Test Results

See Appendix V

5.8 Spurious RF Conducted Emission

TEST CONFIGURATION



TEST PROCEDURE

The Spurious RF conducted emissions compliance of RF radiated emission should be measured by following the guidance in ANSI C63.10-2013 with respect to maximizing the emission by rotating the EUT, measuring the emission while the EUT is situated in three orthogonal planes (if appropriate), adjusting the measurement antenna height and polarization etc. Set RBW=100kHz and VBW= 300KHz to measure the peak field strength , and mwasure frequeny range from 9KHz to 25GHz.

LIMIT

1. Below -20dB of the highest emission level in operating band.
2. Fall in the restricted bands listed in section 15.205. The maximum permitted average field strength is listed in section 15.209.

Test Results

See Appendix IV

5.9 Pseudorandom Frequency Hopping Sequence

TEST APPLICABLE

For 47 CFR Part 15C section 15.247 (a) (1) requirement:

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hop-ping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400–2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW. The system shall hop to channel frequencies that are selected at the system hopping rate from a pseudo randomly ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hop-ping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

EUT Pseudorandom Frequency Hopping Sequence Requirement

The pseudorandom frequency hopping sequence may be generated in a nice-stage shift register whose 5th and 9th stage outputs are added in a modulo-two addition stage. And the result is fed back to the input of the first stage. The sequence begins with the first one of 9 consecutive ones, for example: the shift register is initialized with nine ones.

- Number of shift register stages:9
- Length of pseudo-random sequence:29-1=511 bits
- Longest sequence of zeros:8(non-inverted signal)



Linear Feedback Shift Register for Generation of the PRBS sequence

An example of pseudorandom frequency hopping sequence as follows:



Each frequency used equally one the average by each transmitter.

The system receiver have input bandwidths that match the hopping channel bandwidths of their corresponding transmitter and shift frequencies in synchronization with the transmitted signals.

5.10 Antenna Requirement

Standard Applicable

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

And according to FCC 47 CFR Section 15.247 (c), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

Refer to statement below for compliance

The manufacturer may design the unit so that the user can replace a broken antenna, but the use of a standard antenna jack or electrical connector is prohibited. Further, this requirement does not apply to intentional radiators that must be professionally installed.

Antenna Connected Construction

The directional gains of antenna used for transmitting is5.6dBi, and the antenna is a Intergral Antenna connect to PCB board and no consideration of replacement. Please see EUT photo for details.

Results: Compliance.

6 Test Setup Photos of the EUT

(HK5910(second display: 10.4 inch))





(HK5910(second display: 15 inch))







(HK5910(second display: VFD))



7 Photos of the EUT

See photo report

APPENDIX I.Conducted Peak Output Power

Test Result

Modulation	Packet Type	Channel	Peak Output Power (dBm)	Peak Output Power (mW)	Max. Avg. Power (dBm)	Limit (dBm)	Result
GFSK	DH5	0	0.829	1.210	None	30	PASS
		39	1.308	1.351	None		PASS
		78	2.350	1.718	None		PASS
π/4DQPSK	2-DH5	0	1.580	1.439	None	20.97	PASS
		39	2.124	1.631	None		PASS
		78	3.047	2.017	None		PASS
8DPSK	3-DH5	0	2.014	1.590	None		PASS
		39	2.483	1.771	None		PASS
		78	3.403	2.189	None		PASS

Modulation	Packet Type	Channel	Peak Output Power (dBm)	Peak Power Limit (dBm)	ISED EIRP (dBm)	ISED EIRP Limit (dBm)	Max. Avg. Power (dBm)	Result
GFSK	DH5	0	0.829	30	0.829	36.02	None	PASS
		39	1.308	30	1.308	36.02	None	PASS
		78	2.350	30	2.350	36.02	None	PASS
π/4DQPSK	2-DH5	0	1.580	20.97	1.580	36.02	None	PASS
		39	2.124	20.97	2.124	36.02	None	PASS
		78	3.047	20.97	3.047	36.02	None	PASS
8DPSK	3-DH5	0	2.014	20.97	2.014	36.02	None	PASS
		39	2.483	20.97	2.483	36.02	None	PASS
		78	3.403	20.97	3.403	36.02	None	PASS

APPENDIX II.20dB Bandwidth

Test Result

Modulation	Channel	Center Frequency (MHz)	20 dB Bandwidth (MHz)
GFSK	0	2402 MHz	0.9533
	39	2441 MHz	0.9538
	78	2480 MHz	0.9510
π/4DQPSK	0	2402 MHz	1.303
	39	2441 MHz	1.311
	78	2480 MHz	1.315
8DPSK	0	2402 MHz	1.299
	39	2441 MHz	1.295
	78	2480 MHz	1.294

Test Graphs



GFSK_DH5_Channel 0



GFSK_DH5_Channel 39



GFSK_DH5_Channel 78



π/4DQPSK_2-DH5_Channel 0



π/4DQPSK_2-DH5_Channel 39



π/4DQPSK_2-DH5_Channel 78



8DPSK_3-DH5_Channel 0



8DPSK_3-DH5_Channel 39



8DPSK_3-DH5_Channel 78

Void

APPENDIX III.Carrier Frequencies Separation

Test Result

Modulation	Packet	Left Center frequency (MHz)	Right Center frequency (MHz)	Hopping Frequency Separation (MHz)	Limit (MHz)	Result
GFSK	DH5	2440.0972	2440.9385	0.8413	0.636	PASS
GFSK	DH5	2439.9274	2440.9229	0.9955	0.636	PASS
GFSK	DH5	2440.1527	2441.0948	0.9421	0.634	PASS
π/4DQPSK	2-DH5	2439.9412	2440.9679	1.0267	0.869	PASS
π/4DQPSK	2-DH5	2440.1461	2441.2379	1.0918	0.874	PASS
π/4DQPSK	2-DH5	2440.2193	2441.2685	1.0492	0.877	PASS
8DPSK	3-DH5	2439.8944	2440.9886	1.0942	0.866	PASS
8DPSK	3-DH5	2440.2601	2441.2562	0.9961	0.863	PASS
8DPSK	3-DH5	2440.2676	2441.0726	0.8050	0.863	PASS

Test Graphs

GFSK

GFSK

GFSK



π/4DQPSK

π/4DQPSK

π/4DQPSK

8DPSK

8DPSK

8DPSK

Void

APPENDIX IV.Conducted Out Of Band Emission

Test Result

Non-Hopping

Modulation	Packet	Channel	OOB Emission Frequency (MHz)	OOB Emission Level (dBm)	Limit (dBm)	Over Limit (dB)	Result
GFSK	DH5	0	2400.00	-49.390	-19.25	-30.140	PASS
			2398.96	-35.764	-19.25	-16.514	PASS
			2396.60	-45.133	-19.25	-25.883	PASS
		39	2537.05	-46.248	-18.98	-27.268	PASS
		78	2483.50	-37.547	-17.74	-20	PASS
			2575.76	-45.277	-17.74	-27.537	PASS
π/4DQPSK	2-DH5	0	2400.00	-48.872	-19.35	-29.522	PASS
			2398.95	-35.946	-19.35	-16.596	PASS
			24938.8	-46.791	-19.35	-27.441	PASS
		39	24941.9	-46.957	-18.8	-28.157	PASS
		78	2483.50	-38.096	-17.75	-20	PASS
			24898.2	-46.862	-17.75	-29.112	PASS
8DPSK	3-DH5	0	2400.00	-48.453	-19.29	-29.163	PASS
			2398.95	-35.772	-19.29	-16.482	PASS
			2396.60	-44.924	-19.29	-25.634	PASS
		39	24956.9	-48.073	-18.84	-29.233	PASS
		78	2483.50	-38.858	-17.71	-21	PASS
			9914.62	-47.026	-17.71	-29.316	PASS

Hopping

Modulation	Packet	Channel	OOB Emission Frequency (MHz)	OOB Emission Level (dBm)	Limit (dBm)	Over Limit (dB)	Result
GFSK	DH5	Hopping	2400.00	-36.330	-19.45	-16.880	PASS
			2483.50	-38.870	-17.68	-21.190	PASS
π/4DQPSK	2-DH5		2398.94	-35.954	-19.23	-16.724	PASS
			2400.00	-38.550	-19.23	-19.320	PASS
			2483.50	-40.247	-17.81	-22.437	PASS
8DPSK	3-DH5		2400.00	-39.896	-19.94	-19.956	PASS
			2483.50	-40.129	-17.7	-22.429	PASS

Test Graphs



Out Of Band Emission
GFSK_DH5_Channel 0



Out Of Band Emission
π/4DQPSK_2-DH5_Channel 0



Spurious Emission
GFSK_DH5_Channel 0



Spurious Emission
π/4DQPSK_2-DH5_Channel 0



Out Of Band Emission
GFSK_DH5_Channel 39



Out Of Band Emission
π/4DQPSK_2-DH5_Channel 39



Spurious Emissions
GFSK_DH5_Channel 39



Spurious Emissions
π/4DQPSK_2-DH5_Channel 39

Out Of Band Emission
GFSK_DH5_Channel 78

Out Of Band Emission
π/4DQPSK_2-DH5_Channel 78



Spurious Emission
GFSK_DH5_Channel 78



Spurious Emission
π/4DQPSK_2-DH5_Channel 78



Out Of Band Emission
8DPSK_3-DH5_Channel 0



Spurious Emission
8DPSK_3-DH5_Channel 0



Out Of Band Emission
8DPSK_3-DH5_Channel 39



Spurious Emissions
8DPSK_3-DH5_Channel 39



Out Of Band Emission
8DPSK_3-DH5_Channel 78



Spurious Emission
8DPSK_3-DH5_Channel 78



Out Of Band Emission(Left)
GFSK_DH5_Channel Hopping

Out Of Band Emission(Left)
π/4DQPSK_2-DH5_Channel Hopping



Out Of Band Emission(Right)
GFSK_DH5_Channel Hopping

Out Of Band Emission(Right)
π/4DQPSK_2-DH5_Channel Hopping

Out Of Band Emission(Left)
8DPSK_3-DH5_Channel Hopping

Out Of Band Emission(Right)
8DPSK_3-DH5_Channel Hopping

APPENDIX V.Dwell Time

Test Result

Modulation	Packet	Channel	Pulse Width (ms)	Number of Pulses in 31.6 seconds	Dwell Time (ms)	Limit (ms)	Result
GFSK	DH1	CH39 (2441MHz)	0.3744	317	118.68	< 400	PASS
	DH3		1.632	154	251.33		PASS
	DH5		2.880	110	316.8		PASS
π/4DQPSK	2-DH1		0.3840	312	119.81		PASS
	2-DH3		1.656	157	259.99		PASS
	2-DH5		2.880	106	305.28		PASS
8DPSK	3-DH1		0.3852	313	120.57		PASS
	3-DH3		1.632	159	259.49		PASS
	3-DH5		2.880	100	288.0		PASS

Test Graphs



Pulse Width
GFSK_DH1



Number of Pulses in 31.6 seconds
GFSK_DH1



Pulse Width
GFSK_DH3



Number of Pulses in 31.6 seconds
GFSK_DH3



Pulse Width
GFSK_DH5



Number of Pulses in 31.6 seconds
GFSK_DH5



Pulse Width
π/4DQPSK_2-DH1



Number of Pulses in 31.6 seconds
π/4DQPSK_2-DH1



Pulse Width
π/4DQPSK_2-DH3



Number of Pulses in 31.6 seconds
π/4DQPSK_2-DH3



Pulse Width
π/4DQPSK_2-DH5



Number of Pulses in 31.6 seconds
π/4DQPSK_2-DH5



Pulse Width
8DPSK_3-DH1



Number of Pulses in 31.6 seconds
8DPSK_3-DH1



Pulse Width
8DPSK_3-DH3



Number of Pulses in 31.6 seconds
8DPSK_3-DH3



Pulse Width
8DPSK_3-DH5



Number of Pulses in 31.6 seconds
8DPSK_3-DH5

APPENDIX VI.Number Of Hopping Channel

Test Result

Modulation	Packet	Number of Hopping Channel	Result
GFSK	DH5	79	PASS
π/4DQPSK	2-DH5	79	PASS
8DPSK	3-DH5	79	PASS

Test Graphs



Hopping Plot
GFSK



Hopping Plot
π/4DQPSK



Hopping Plot
8DPSK

Void

********** End of Report **********