



SAR TEST REPORT

Product Name: Smart Phone

Model Number: CPA2660

FCC ID: 2ATZ4-26Q1

Issued For : Shenzhen Youmi Intelligent Technology Co., Ltd.
406-407 Jinqi Zhigu Building, 4/F, 1 Tangling Road, Nanshan District, Shenzhen City, China

Issued By : Shenzhen LGT Test Service Co., Ltd.
Room 205, Building 13, Zone B, Zhenxiong Industrial Park, No.177, Renmin West Road, Jinsha, Kengzi Street, Pingshan District, Shenzhen, Guangdong, China

Report Number: LGT25L547HA03

Sample Received Date: Dec. 31, 2025

Date of Test Dec. 31, 2025 ~Feb. 03, 2026

Date of Issue Feb. 03, 2026

Head: 1.040 W/kg(1g)

Max. SAR Body: 1.025 W/kg(1g)

Limbs: 0.569 W/kg(10g)

The test report is effective only with both signature and specialized stamp. This report shall not be reproduced except in full without the written approval of the Laboratory. The results in this report only apply to the tested sample.



Table of Contents

1. General Information	5
1.1 EUT Description	5
1.2 Test Environment	7
1.3 Test Factory	7
2. Test Standards and Limits	8
3. SAR Measurement System	9
3.1 Definition of Specific Absorption Rate (SAR)	9
3.2 SAR System	9
4. Tissue Simulating Liquids	12
4.1 Simulating Liquids Parameter Check	12
5. SAR System Validation	16
5.1 Validation System	16
5.2 Validation Result	17
6. SAR Evaluation Procedures	18
7. EUT Antenna Location Sketch	19
7.1 SAR test exclusion consider table	20
8. EUT Test Position	26
8.1 Define Two Imaginary Lines on the Handset	26
8.2 Hotspot mode exposure position condition	27
9. Uncertainty	28
9.1 Measurement Uncertainty	28
9.2 System validation Uncertainty	29
10. Conducted Power Measurement	30
10.1 Test Result	30
11. EUT and Test Setup Photo	67
11.1 EUT Photos	67
11.2 Setup Photos	70
12. SAR Result Summary	76
12.1 Head SAR	76
12.2 Body-worn and Hotspot SAR	81
12.3 Limbs SAR	87
12.4 Repeated SAR	93
12.5 Repeated SAR measurement	94
12.6 Simultaneous Multi-band Transmission Evaluation	95
13. Equipment List	98



Appendix A. System Validation Plots	99
Appendix B. SAR Test Plots	125
Appendix C. Probe Calibration and Dipole Calibration Report	171

Revision History

Rev.	Issue Date	Contents
00	Feb. 03, 2026	Initial Issue



TEST REPORT CERTIFICATION

Applicant Shenzhen Youmi Intelligent Technology Co., Ltd.
Address 406-407 Jinqi Zhigu Building, 4/F, 1 Tangling Road, Nanshan District, Shenzhen City, China
Manufacture Shenzhen Youmi Intelligent Technology Co., Ltd.
Address 406-407 Jinqi Zhigu Building, 4/F, 1 Tangling Road, Nanshan District, Shenzhen City, China
Product Name Smart Phone
Trademark UMDIGI
Model Number CPA2660
Sample number LGT2601028

APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
ANSI/IEEE Std. C95.1-2019 FCC 47 CFR Part 2 (2.1093) IEEE 1528: 2013	PASS

Prepared by:

Deng Deng

Deng Deng
Engineer

Approved by:

Vita Li

Vita Li
Manager





1. General Information

Environmental evaluation measurements of specific absorption rate (SAR) distributions in emulated human head and body tissues exposed to radio frequency (RF) radiation from wireless portable devices for compliance with the rules and regulations of the U.S. Federal Communications Commission (FCC).

1.1 EUT Description

Product Name	Smart Phone			
Test Model Number	CPA2660			
Series Number	N/A			
Model Difference	N/A			
Device Category	Portable			
Product stage	Production unit			
RF Exposure Environment	General Population / Uncontrolled			
Hardware Version	G200			
Software Version	UMIDIGI A7			
Frequency Range	GSM 850: 824 ~ 849 MHz PCS 1900: 1850 ~ 1910 MHz WCDMA Band II: 1850 ~ 1910 MHz WCDMA Band IV: 1710 ~ 1755 MHz WCDMA Band V: 824 ~ 849 MHz LTE Band 2: 1850 ~ 1910 MHz LTE Band 4: 1710 ~ 1755 MHz LTE Band 5: 824 ~ 849 MHz LTE Band 7: 2500 ~ 2570 MHz LTE Band 12: 699 ~ 716 MHz LTE Band 13: 777 ~ 787 MHz LTE Band 17: 704 ~ 716 MHz LTE Band 25: 1850 ~ 1915 MHz LTE Band 26: 814 ~ 824 MHz / 824 ~ 849 MHz LTE Band 38: 2570 ~ 2620 MHz LTE Band 40: 2305 ~ 2315 MHz / 2350 ~ 2360 MHz LTE Band 41: 2500 ~ 2690 MHz LTE Band 66: 1710 ~ 1780 MHz WLAN 802.11b/g/n20: 2412 MHz ~ 2462 MHz WLAN 802.11n40: 2422 MHz ~ 2452 MHz WLAN 802.11a/n20/n40/ac20/ac40/ac80: 5150 ~ 5250 MHz WLAN 802.11a/n20/n40/ac20/ac40/ac80: 5250 ~ 5350 MHz WLAN 802.11a/n20/n40/ac20/ac40/ac80: 5470 ~ 5725 MHz WLAN 802.11a/n20/n40/ac20/ac40/ac80: 5725 ~ 5850 MHz Bluetooth: 2402 ~ 2480 MHz			
Max. Reported SAR: Test distance: Body: 0mm Limbs: 0mm	Mode	Head (W/kg) (1g)	Body Worn and Hotspot (W/kg) (1g)	Limbs (W/kg) (10g)
	GSM 850	0.513	0.665	0.293
	PCS 1900	1.007	0.722	0.393
	WCDMA Band II	0.848	1.025	0.569
	WCDMA Band IV	1.040	0.830	0.469
	WCDMA Band V	0.389	0.375	0.278
	LTE Band 2	0.866	0.861	0.465
	LTE Band 4	0.840	0.993	0.445
	LTE Band 5	0.473	0.843	0.538
	LTE Band 7	0.605	0.706	0.336



	LTE Band 12	0.411	0.767	0.520
	LTE Band 13	0.446	0.542	0.228
	LTE Band 17	0.416	0.782	0.553
	LTE Band 25	0.609	0.998	0.544
	LTE Band 26	0.486	0.352	0.217
	LTE Band 38	0.181	0.608	0.282
	LTE Band 40	0.228	0.371	0.197
	LTE Band 41	0.188	0.712	0.342
	LTE Band 66	0.738	0.658	0.352
	2.4G WLAN	0.297	0.338	0.102
	5.2G WLAN	0.390	0.488	0.207
	5.3G WLAN	0.464	0.433	0.199
	5.6G WLAN	0.529	0.443	0.189
	5.8G WLAN	0.434	0.528	0.200
	Bluetooth ^{Note}	0.059	0.059	0.235
Sum SAR		1.569	1.553	0.804
Limit		1.6		4
Battery	Rated Voltage:3.87V Capacity: 6600mAh			
Description test modes	SIM 1 and SIM 2 is a chipset unit and tested as single chipset, SIM 1 is used to tested			
Operating Mode:	GSM: GSM Voice; GPRS/EGPRS Class 12 WCDMA: RMC, HSDPA, HSUPA Release 6 LTE: QPSK, 16QAM 2.4G WLAN: 802.11b(DSSS): CCK, DQPSK, DBPSK 802.11g(OFDM): BPSK, QPSK,16-QAM,64-QAM 802.11n(OFDM): BPSK, QPSK,16-QAM,64-QAM 5G WLAN: 802.11a(OFDM): BPSK, QPSK,16-QAM,64-QAM 802.11n(OFDM): BPSK, QPSK,16-QAM,64-QAM 802.11ac (OFDM): BPSK, QPSK,16-QAM,64-QAM,256-QAM Bluetooth: GFSK + π /4DQPSK+8DPSK BLE: GFSK			
Antenna Specification	GSM/WCDMA/LTE: PIFA Antenna Bluetooth: FPC Antenna WLAN: FPC Antenna			
Operating Mode	Maximum continuous output			
SIM Card	Support dual-SIM, dual standby, the multiple SIM card with two lines cannot trans mitting at the same time			
Hotspot Mode	Support			
DTM Mode	Not Support			
Note 1: The BT value was Estimated.				



1.2 Test Environment

Ambient conditions in the SAR laboratory:

Items	Required
Temperature (°C)	18-25
Humidity (%RH)	30-70

1.3 Test Factory

Company Name:	Shenzhen LGT Test Service Co., Ltd.
Address:	Room 205, Building 13, Zone B, Zhenxiong Industrial Park, No.177, Renmin West Road, Jinsha, Kengzi Street, Pingshan District, Shenzhen, Guangdong, China
Accreditation Certificate	FCC Registration No.: 746540
	CAB ID: CN0136



2. Test Standards and Limits

No.	Identity	Document Title
1	47 CFR Part 2	Frequency Allocations and Radio Treaty Matters; General Rules and Regulations
2	ANSI/IEEE Std. C95.1-2019	IEEE Standard for Safety Levels with Respect to Human Exposure to Electric, Magnetic, and Electromagnetic Fields, 0 Hz to 300 GHz
3	IEEE Std. 1528-2013	Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques
4	FCC KDB 447498 D01 v06	Mobile and Portable Device RF Exposure Procedures and Equipment Authorization Policies
5	FCC KDB 865664 D01 v01r04	SAR Measurement 100 MHz to 6 GHz
6	FCC KDB 865664 D02 v01r02	RF Exposure Reporting
7	FCC KDB 941225 D01 v03r01	SAR Measurement Procedures for 3G Devices
8	FCC KDB 941225 D05 v02r05	SAR for LTE Devices
9	FCC KDB 941225 D06 v02r01	Hotspot Mode SAR
10	FCC KDB 648474 D04 v01r03	SAR Evaluation Considerations for Wireless Handsets
11	FCC KDB 248227 D01 Wi-Fi SAR v02r02	SAR Considerations for 802.11 Devices

(A). Limits for Occupational/Controlled Exposure (W/kg)

<u>Whole-Body</u>	<u>Partial-Body</u>	<u>Hands, Wrists, Feet and Ankles</u>
0.4	8.0	20.0

(B). Limits for General Population/Uncontrolled Exposure (W/kg)

<u>Whole-Body</u>	<u>Partial-Body</u>	<u>Hands, Wrists, Feet and Ankles</u>
0.08	1.6	4.0

NOTE: Whole-Body SAR is averaged over the entire body, partial-body SAR is averaged over any 1 gram of tissue defined as a tissue volume in the shape of a cube. SAR for hands, wrists, feet and ankles is averaged over any 10 grams of tissue defined as a tissue volume in the shape of a cube.

Population/Uncontrolled Environments:

Are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure.

Occupational/Controlled Environments:

Are defined as locations where there is exposure that may be incurred by people who are aware of the potential for exposure, (i.e. as a result of employment or occupation).

NOTE GENERAL POPULATION/UNCONTROLLED EXPOSURE PARTIAL BODY LIMIT 1.6 W/kg



3. SAR Measurement System

3.1 Definition of Specific Absorption Rate (SAR)

SAR is related to the rate at which energy is absorbed per unit mass in an object exposed to a radio field. The SAR distribution in a biological body is complicated and is usually carried out by experimental techniques or numerical modeling. The standard recommends limits for two tiers of groups, occupational/controlled and general population/uncontrolled, based on a person's awareness and ability to exercise control over his or her exposure. In general, occupational/controlled exposure limits are higher than the limits for general population/uncontrolled.

The SAR definition is the time derivative (rate) of the incremental energy (dW) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dv) of a given density (ρ). The equation description is as below:

$$SAR = \frac{d}{dt} \left(\frac{dW}{dm} \right) = \frac{d}{dt} \left(\frac{dW}{\rho dv} \right)$$

SAR is expressed in units of Watts per kilogram (W/kg) SAR measurement can be related to the electrical field in the tissue by


$$SAR = \frac{\sigma E^2}{\rho}$$

Where: σ is the conductivity of the tissue;

ρ is the mass density of the tissue and E is the RMS electrical field strength.

3.2 SAR System

MVG SAR System Diagram:



COMOSAR is a system that is able to determine the SAR distribution inside a phantom of human being according to different standards. The COMOSAR system consists of the following items:

- Main computer to control all the system
- 6 axis robot
- Data acquisition system
- Miniature E-field probe
- Phone holder
- Head simulating tissue

The following figure shows the system.



The EUT under test operating at the maximum power level is placed in the phone holder, under the phantom, which is filled with head simulating liquid. The E-Field probe measures the electric field inside the phantom. The OpenSAR software computes the results to give a SAR value in a 1g or 1g mass.

3.2.1 Probe

For the measurements the Specific Dosimetric E-Field Probe 2225-EPGO-450 with following specifications is used

- Probe Length: 330 mm
- Length of Individual Dipoles: 2mm
- Maximum external diameter: 8 mm
- Probe Tip External Diameter: 2.5 mm
- Distance between dipole/probe extremity: 1 mm
- Dynamic range: 0.01-100 W/kg
- Probe linearity: 3%
- Axial Isotropy: < 0.10 dB
- Spherical Isotropy: < 0.10 dB
- Calibration range: 0.15 GHz to 7.5 GHz for head simulating liquid.
- Angle between probe axis (evaluation axis) and surface normal line: less than 30°



Figure 1-MVG COMOSAR Dosimetric E field Probe



3.2.2 Phantom

For the measurements the Specific Anthropomorphic Mannequin (SAM) defined by the IEEE SCC-34/SC2 group is used. The phantom is a polyurethane shell integrated in a wooden table. The thickness of the phantom amounts to 2mm +/- 0.2mm. It enables the dosimetric evaluation of left and right phone usage and includes an additional flat phantom part for the simplified performance check. The phantom set-up includes a cover, which prevents the evaporation of the liquid.




Figure-SN 06/22 SAM 148



Figure-SN 06/22 ELLI 51

3.2.3 Device Holder



The SAR in the phantom is approximately inversely proportional to the square of the distance between the source and the liquid surface. For a source at 5 mm distance, a positioning uncertainty of ± 0.5 mm would produce a SAR uncertainty of ± 20 %. Accurate device positioning is therefore crucial for accurate and repeatable measurements. The positions in which the devices must be measured are defined by the standards.



4. Tissue Simulating Liquids

4.1 Simulating Liquids Parameter Check

The simulating liquids should be checked at the beginning of a series of SAR measurements to determine if the dielectric parameters are within the tolerances of the specified target values

The uncertainty due to the liquid conductivity and permittivity arises from two different sources. The first source of error is the deviation of the liquid conductivity from its target value (max _ 5 %) and the second source of error arises from the measurement procedures used to assess conductivity. The uncertainty shall be assessed using a rectangular probability For 1 g averaging, the maximum weighting coefficient for SAR is 0,5.

IEEE SCC-34/SC-2 RECOMMENDED TISSUE DIELECTRIC PARAMETERS

The head and body tissue dielectric parameters recommended by the IEEE SCC-34/SC-2 have been incorporated in the following table.

Frequency	ϵ_r	σ 10g S/m
300	45.3	0.87
450	43.5	0.87
750	41.9	0.89
835	41.5	0.90
900	41.5	0.97
1450	40.5	1.20
1800 to 2000	40.0	1.40
2100	39.8	1.49
2450	39.2	1.80
2600	39.0	1.96
3000	38.5	2.40
3500	37.9	2.91
4000	37.4	3.43
4500	36.8	3.94
5000	36.2	4.45
5200	36.0	4.66
5400	35.8	4.86
5600	35.5	5.07
5800	35.3	5.27



LIQUID MEASUREMENT RESULTS

Date	Ambient		Simulating Liquid		Parameters	Target	Measured	Deviation %	Limited %
	Temp. [°C]	Humidity %	Frequency (MHz)	Temp. [°C]					
2026-01-15	22.8	46	750	22.5	Permittivity	41.90	41.78	-0.29	±5
					Conductivity	0.89	0.87	-2.25	±5
2026-01-15	22.9	46	704	22.6	Permittivity	42.15	42.40	0.59	±5
					Conductivity	0.89	0.86	-3.37	±5
2026-01-15	22.9	46	710	22.6	Permittivity	42.11	41.52	-1.40	±5
					Conductivity	0.89	0.92	3.37	±5
2026-01-15	22.9	47	782	22.6	Permittivity	41.73	42.15	1.01	±5
					Conductivity	0.89	0.85	-4.49	±5
2026-01-06	22.9	47	835	22.6	Permittivity	41.50	42.29	1.90	±5
					Conductivity	0.90	0.94	4.44	±5
2026-01-06	23	47	826.4	22.7	Permittivity	41.50	41.74	0.58	±5
					Conductivity	0.89	0.88	-1.12	±5
2026-01-06	23	47	829	22.7	Permittivity	41.50	41.60	0.24	±5
					Conductivity	0.89	0.90	1.12	±5
2026-01-06	23	47	836.5	22.7	Permittivity	41.50	41.60	0.24	±5
					Conductivity	0.90	0.88	-2.22	±5
2026-01-06	23.1	48	841.5	22.8	Permittivity	41.50	41.68	0.43	±5
					Conductivity	0.91	0.95	4.40	±5
2026-01-06	23.1	47	844	22.8	Permittivity	41.50	42.21	1.71	±5
					Conductivity	0.91	0.89	-2.20	±5
2026-01-06	23.2	48	848.8	22.9	Permittivity	41.50	41.63	0.31	±5
					Conductivity	0.91	0.95	4.40	±5
2026-01-17	23.5	59	1800	23.3	Permittivity	40.00	40.86	2.15	±5
					Conductivity	1.40	1.39	-0.71	±5
2026-01-17	23.6	59	1712.6	23.3	Permittivity	40.12	41.20	2.69	±5
					Conductivity	1.35	1.38	2.22	±5
2026-01-17	23.7	59	1720	23.4	Permittivity	40.11	40.45	0.85	±5
					Conductivity	1.35	1.37	1.48	±5
2026-01-17	23.7	60	1732.5	23.4	Permittivity	40.10	40.83	1.82	±5
					Conductivity	1.36	1.37	0.74	±5
2026-01-17	23.7	60	1740	23.3	Permittivity	40.09	40.99	2.24	±5
					Conductivity	1.37	1.36	-0.73	±5
2026-01-17	23.7	60	1752.4	23.4	Permittivity	40.07	40.71	1.60	±5
					Conductivity	1.37	1.32	-3.65	±5
2026-01-19	23.3	52	1800	23	Permittivity	40.00	40.95	2.38	±5
					Conductivity	1.40	1.43	2.14	±5
2026-01-19	23.4	52	1745	23.1	Permittivity	40.08	40.81	1.82	±5
					Conductivity	1.37	1.38	0.73	±5
2026-01-16	20.9	56	1900	20.6	Permittivity	40.00	40.56	1.40	±5
					Conductivity	1.40	1.35	-3.57	±5
2026-01-16	20.9	56	1850.2	20.6	Permittivity	40.00	41.18	2.95	±5
					Conductivity	1.40	1.39	-0.71	±5



2026-01-16	21	56	1852.4	20.7	Permittivity	40.00	40.27	0.68	±5
					Conductivity	1.40	1.42	1.43	±5
2026-01-16	21	57	1860	20.7	Permittivity	40.00	41.26	3.15	±5
					Conductivity	1.40	1.42	1.43	±5
2026-01-16	21	57	1880	20.7	Permittivity	40.00	40.83	2.08	±5
					Conductivity	1.40	1.36	-2.86	±5
2026-01-16	21.1	57	1882.5	20.8	Permittivity	40.00	41.14	2.85	±5
					Conductivity	1.40	1.37	-2.14	±5
2026-01-20	22.6	43	1900	22.3	Permittivity	40.00	40.10	0.25	±5
					Conductivity	1.40	1.38	-1.43	±5
2026-01-20	22.7	43	1905	22.4	Permittivity	40.00	40.47	1.18	±5
					Conductivity	1.40	1.42	1.43	±5
2026-01-20	22.7	44	1907.6	22.4	Permittivity	40.00	41.18	2.95	±5
					Conductivity	1.40	1.44	2.86	±5
2026-01-20	22.8	44	1909.8	22.5	Permittivity	40.00	40.22	0.55	±5
					Conductivity	1.40	1.44	2.86	±5
2026-01-19	23.3	52	2300	23	Permittivity	39.47	40.64	2.96	±5
					Conductivity	1.67	1.66	-0.60	±5
2026-01-19	23.4	52	2310	23.1	Permittivity	39.45	40.74	3.27	±5
					Conductivity	1.68	1.69	0.60	±5
2026-01-17	23.5	59	2450	23.2	Permittivity	39.20	39.89	1.76	±5
					Conductivity	1.80	1.87	3.89	±5
2026-01-17	23.5	60	2462	23.2	Permittivity	39.18	39.82	1.63	±5
					Conductivity	1.81	1.84	1.66	±5
2026-01-18	20.5	56	2600	20.1	Permittivity	39.00	40.21	3.10	±5
					Conductivity	1.96	1.94	-1.02	±5
2026-01-18	20.6	56	2506	20.3	Permittivity	39.12	40.20	2.76	±5
					Conductivity	1.86	1.84	-1.08	±5
2026-01-18	20.6	56	2510	20.2	Permittivity	39.11	39.50	1.00	±5
					Conductivity	1.86	1.81	-2.69	±5
2026-01-18	20.6	57	2595	20.3	Permittivity	39.01	39.12	0.28	±5
					Conductivity	1.95	2.01	3.08	±5
2026-01-18	20.5	56	2610	20.3	Permittivity	38.99	39.72	1.87	±5
					Conductivity	1.97	1.99	1.02	±5
2026-01-18	20.6	57	2680	20.2	Permittivity	38.90	39.94	2.67	±5
					Conductivity	2.05	2.04	-0.49	±5
2026-01-11	20.1	56	5200	19.8	Permittivity	36.00	35.94	-0.17	±5
					Conductivity	4.66	4.62	-0.86	±5
2026-01-11	20.1	56	5180	19.8	Permittivity	36.02	36.28	0.72	±5
					Conductivity	4.64	4.65	0.22	±5
2026-01-11	20.1	56	5400	19.8	Permittivity	35.80	36.48	1.90	±5
					Conductivity	4.86	4.84	-0.41	±5
2026-01-11	20.1	56	5260	19.8	Permittivity	35.94	36.43	1.36	±5
					Conductivity	4.72	4.68	-0.85	±5
2026-01-12	22.8	55	5600	22.5	Permittivity	35.55	35.70	0.42	±5
					Conductivity	5.07	5.17	1.97	±5
2026-01-12	22.8	55	5500	22.5	Permittivity	35.68	35.66	-0.06	±5
					Conductivity	4.96	4.98	0.40	±5



2026-01-12	22.9	55	5800	22.6	Permittivity	35.30	36.44	3.23	±5
					Conductivity	5.27	5.32	0.95	±5
2026-01-12	23	56	5745	22.7	Permittivity	35.36	35.83	1.33	±5
					Conductivity	5.21	5.26	0.96	±5




5. SAR System Validation

5.1 Validation System

Each MVG system is equipped with one or more system validation kits. These units, together with the predefined measurement procedures within the MVG software, enable the user to conduct the system performance check and system validation. System kit includes a dipole, and dipole device holder.

The system check verifies that the system operates within its specifications. It's performed daily or before every SAR measurement. The system check uses normal SAR measurement in the flat section of the phantom with a matched dipole at a specified distance. The system validation setup is shown as below.





5.2 Validation Result

Comparing to the original SAR value provided by MVG, the validation data should be within its specification of $\pm 10\%$.

Date	Freq.	Power	Tested Value	Normalized SAR	Target SAR	Tolerance	Limit
	(MHz)	(mW)	(W/Kg)	(W/kg)	1g(W/kg)	(%)	(%)
2026-01-15	750	100	0.856	8.56	8.51	0.59	10
2026-01-06	835	100	0.979	9.79	9.63	1.66	10
2026-01-17	1800	100	3.681	36.81	36.60	0.57	10
2026-01-19	1800	100	3.678	36.78	36.60	0.49	10
2026-01-16	1900	100	3.989	39.89	40.20	-0.77	10
2026-01-20	1900	100	4.026	40.26	40.20	0.15	10
2026-01-19	2300	100	4.902	49.02	49.29	-0.55	10
2026-01-17	2450	100	5.305	53.05	52.98	0.13	10
2026-01-18	2600	100	5.715	57.15	56.15	1.78	10
2026-01-11	5200	100	7.790	77.90	77.84	0.08	10
2026-01-11	5400	100	7.677	76.77	76.82	-0.07	10
2026-01-12	5600	100	8.186	81.86	82.15	-0.35	10
2026-01-12	5800	100	8.227	82.27	80.51	2.19	10

Note:

1. The tolerance limit of System validation $\pm 10\%$.
2. The dipole input power (forward power) was 100 mW.
3. The results are normalized to 1 W input power.



6. SAR Evaluation Procedures

The procedure for assessing the average SAR value consists of the following steps:

The following steps are used for each test position

- Establish a call with the maximum output power with a base station simulator. The connection between the mobile and the base station simulator is established via air interface
- Measurement of the local E-field value at a fixed location. This value serves as a reference value for calculating a possible power drift.
- Measurement of the SAR distribution with a grid of 8 to 16mm * 8 to 16 mm and a constant distance to the inner surface of the phantom. Since the sensors cannot directly measure at the inner phantom surface, the values between the sensors and the inner phantom surface are extrapolated. With these values the area of the maximum SAR is calculated by an interpolation scheme.
- Around this point, a cube of 30 * 30 * 30 mm or 32 * 32 * 32 mm is assessed by measuring 5 or 8 * 5 or 8*4 or 5 mm. With these data, the peak spatial-average SAR value can be calculated.

➤ Area Scan & Zoom Scan

First Area Scan is used to locate the approximate location(s) of the local peak SAR value(s). The measurement grid within an Area Scan is defined by the grid extent, grid step size and grid offset. Next, in order to determine the EM field distribution in a three-dimensional spatial extension, Zoom Scan is required. The Zoom Scan is performed around the highest E-field value to determine the averaged SAR-distribution over 10 g. Area scan and zoom scan resolution setting follows KDB 865664 D01 quoted below.


When the 1-g SAR of the highest peak is within 2 dB of the SAR limit, additional zoom scans are required for other peaks within 2 dB of the highest peak that have not been included in any zoom scan to ensure there is no increase in SAR.



7. EUT Antenna Location Sketch

It is a Smart Phone, support GSM/WCDMA/LTE/WLAN/BT mode.

Top side



Bottom side
(Back view)

Antenna Separation Distance(mm)						
ANT	Back Side	Front Side	Left Side	Right Side	Top Side	Bottom Side
WLAN/BT	≤5	≤5	53	≤5	≤5	148
WWAN MHB	≤5	≤5	≤5	52	≤5	155
WWAN LB	≤5	≤5	≤5	≤5	153	≤5

Note 1: The antenna information refer the manufacturer provide report, applicable only to the tested sample identified in the report.



7.1 SAR test exclusion consider table

The WWAN/WLAN/BT SAR evaluation of Maximum power (dBm) summing tolerance.

Exposure Position	Wireless Interface	GSM850	PCS1900	WCDMA II	WCDMA IV	WCDMA V
	Calculated Frequency (MHz)	848.8	1880	1907.6	1712.6	826.4
	Maximum Turn-up power (dBm)	34	30.5	23.7	23.5	24.3
	Maximum rated power(mW)	2511.89	1122.02	234.42	223.87	269.15
Back Side	Separation distance (mm)	5	5	5	5	5
	exclusion threshold(mW)	16.28	10.94	10.86	11.46	16.50
	Testing required?	YES	YES	YES	YES	YES
Front Side	Separation distance (mm)	5	5	5	5	5
	exclusion threshold(mW)	16.28	10.94	10.86	11.46	16.50
	Testing required?	YES	YES	YES	YES	YES
Left Edge	Separation distance (mm)	5	5	5	5	5
	exclusion threshold(mW)	16.28	10.94	10.86	11.46	16.50
	Testing required?	YES	YES	YES	YES	YES
Right Edge	Separation distance (mm)	5	52	52	52	5
	exclusion threshold(mW)	212.13	129.40	128.60	134.62	212.13
	Testing required?	YES	YES	YES	YES	YES
Top Edge	Separation distance (mm)	153	5	5	5	153
	exclusion threshold(mW)	745.66	10.94	10.86	11.46	732.47
	Testing required?	YES	YES	YES	YES	NO
Bottom Edge	Separation distance (mm)	5	155	155	155	5
	exclusion threshold(mW)	16.28	1159.40	1158.60	1164.62	16.50
	Testing required?	YES	NO	NO	NO	YES



Exposure Position	Wireless Interface	LTE Band 2	LTE Band 4	LTE Band 5	LTE Band 7	LTE Band 12
	Calculated Frequency (MHz)	1880	1720	844	2510	704
	Maximum Turn-up power (dBm)	25.1	25.2	16.5	23.7	25.1
	Maximum rated power(mW)	323.59	331.13	44.67	234.42	323.59
Back Side	Separation distance (mm)	5	5	5	5	5
	exclusion threshold(mW)	10.94	11.44	16.33	9.47	17.88
	Testing required?	YES	YES	YES	YES	YES
Front Side	Separation distance (mm)	5	5	5	5	5
	exclusion threshold(mW)	10.94	11.44	16.33	9.47	17.88
	Testing required?	YES	YES	YES	YES	YES
Left Edge	Separation distance (mm)	5	5	5	5	5
	exclusion threshold(mW)	10.94	11.44	16.33	9.47	17.88
	Testing required?	YES	YES	YES	YES	YES
Right Edge	Separation distance (mm)	52	52	5	52	5
	exclusion threshold(mW)	129.40	134.37	212.13	114.68	212.13
	Testing required?	YES	YES	NO	YES	YES
Top Edge	Separation distance (mm)	5	5	153	5	153
	exclusion threshold(mW)	10.94	11.44	742.82	9.47	662.19
	Testing required?	YES	YES	NO	YES	NO
Bottom Edge	Separation distance (mm)	155	155	5	155	5
	exclusion threshold(mW)	1159.40	1164.37	16.33	1144.68	17.88
	Testing required?	NO	NO	YES	NO	YES



Exposure Position	Wireless Interface	LTE Band 13	LTE Band 17	LTE Band 25	LTE Band 26	LTE Band 38
	Calculated Frequency (MHz)	782	710	1882.5	841.5	2595
	Maximum Turn-up power (dBm)	25.4	24.7	25.5	23.5	25.2
	Maximum rated power(mW)	346.74	295.12	354.81	223.87	331.13
Back Side	Separation distance (mm)	5	5	5	5	5
	exclusion threshold(mW)	16.96	17.80	10.93	16.35	9.31
	Testing required?	YES	YES	YES	YES	YES
Front Side	Separation distance (mm)	5	5	5	5	5
	exclusion threshold(mW)	16.96	17.80	10.93	16.35	9.31
	Testing required?	YES	YES	YES	YES	YES
Left Edge	Separation distance (mm)	5	5	5	5	5
	exclusion threshold(mW)	16.96	17.80	10.93	16.35	9.31
	Testing required?	YES	YES	YES	YES	YES
Right Edge	Separation distance (mm)	5	5	52	5	52
	exclusion threshold(mW)	212.13	212.13	129.33	212.13	113.12
	Testing required?	YES	YES	YES	YES	YES
Top Edge	Separation distance (mm)	153	153	5	153	5
	exclusion threshold(mW)	706.60	665.55	10.93	741.35	9.31
	Testing required?	NO	NO	YES	NO	YES
Bottom Edge	Separation distance (mm)	5	5	155	5	155
	exclusion threshold(mW)	16.96	17.80	1159.33	16.35	1143.12
	Testing required?	YES	YES	NO	YES	NO



Exposure Position	Wireless Interface	LTE Band 40	LTE Band 41	LTE Band 66	BT	2.4G WLAN
	Calculated Frequency (MHz)	2310	2680	1745	2441	2462
	Maximum Turn-up power (dBm)	15.7	25.2	24.8	1.5	16.5
	Maximum rated power(mW)	37.15	331.13	302.00	1.41	44.67
Back Side	Separation distance (mm)	5	5	5	5	5
	exclusion threshold(mW)	9.87	9.16	11.36	9.60	9.56
	Testing required?	YES	YES	YES	NO	YES
Front Side	Separation distance (mm)	5	5	5	5	5
	exclusion threshold(mW)	9.87	9.16	11.36	9.60	9.56
	Testing required?	YES	YES	YES	NO	YES
Left Edge	Separation distance (mm)	5	5	5	53	53
	exclusion threshold(mW)	9.87	9.16	11.36	126.01	125.60
	Testing required?	YES	YES	YES	NO	NO
Right Edge	Separation distance (mm)	52	52	52	5	5
	exclusion threshold(mW)	118.69	111.63	133.55	9.60	9.56
	Testing required?	NO	YES	YES	NO	YES
Top Edge	Separation distance (mm)	5	5	5	5	5
	exclusion threshold(mW)	9.87	9.16	11.36	9.60	9.56
	Testing required?	YES	YES	YES	NO	YES
Bottom Edge	Separation distance (mm)	155	155	155	148	148
	exclusion threshold(mW)	1148.69	1141.63	1163.55	1076.01	1075.60
	Testing required?	NO	NO	NO	NO	NO



Exposure Position	Wireless Interface	5.2G WLAN	5.3G WLAN	5.6G WLAN	5.8G WLAN
	Calculated Frequency (MHz)	5180	5260	5500	5745
	Maximum Turn-up power (dBm)	14.5	14.5	14.3	14.5
	Maximum rated power(mW)	28.18	28.18	26.92	28.18
Back Side	Separation distance (mm)	5	5	5	5
	exclusion threshold(mW)	6.59	6.54	6.40	6.26
	Testing required?	YES	YES	YES	YES
Front Side	Separation distance (mm)	5	5	5	5
	exclusion threshold(mW)	6.59	6.54	6.40	6.26
	Testing required?	YES	YES	YES	YES
Left Edge	Separation distance (mm)	53	53	53	53
	exclusion threshold(mW)	95.91	95.40	93.96	92.58
	Testing required?	NO	NO	NO	NO
Right Edge	Separation distance (mm)	5	5	5	5
	exclusion threshold(mW)	6.59	6.54	6.40	6.26
	Testing required?	YES	YES	YES	YES
Top Edge	Separation distance (mm)	5	5	5	5
	exclusion threshold(mW)	6.59	6.54	6.40	6.26
	Testing required?	YES	YES	YES	YES
Bottom Edge	Separation distance (mm)	148	148	148	148
	exclusion threshold(mW)	1045.91	1045.40	1043.96	1042.58
	Testing required?	NO	NO	NO	NO

Note:

1. maximum power is the source-based time-average power and represents the maximum RF output power among production units.
2. per KDB 447498 D01, for larger devices, the test separation distance of adjacent edge configuration is determined by the closest separation between the antenna and the user.
3. per KDB 447498 D01, standalone SAR test exclusion threshold is applied; if the distance of the antenna to the user is <25mm, 25mm is user to determine SAR exclusion threshold
4. per KDB 447498 D01, the 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distance $\leq 50\text{mm}$ are determined by:

$$\frac{[(\text{max.power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance,}]}{}$$



mm)]*[$\sqrt{f(\text{GHz})}$] ≤ 3.0 for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, $f(\text{GHz})$ is the RF channel transmit frequency in GHz. Power and distance are rounded to the nearest mW and mm before calculation.

The result is rounded to one decimal place for comparison

For <50mm distance, we just calculate mW of the exclusion threshold value(3.0)to do compare

5. per KDB 447498 D01, at 100 MHz to 6GHz and for test separation distances >50mm, the SAR test exclusion threshold is determined according to the following
 - a)[threshold at 50mm in step 1]+(test separation distance -50mm)*($f(\text{MHz})/150$)]mW, at 100 MHz to 1500 MHz
 - b) [threshold at 50mm in step1]+(test separation distance -50mm) *10]mW at > 1500MHz and $\leq 6\text{GHz}$
6. Per KDB 248227 D01, choose the highest output power channel to test SAR and determine further SAR exclusion 8.for each frequency band ,testing at higher data rates and higher order modulations is not required when the maximum average output power for each of each of these configurations is less than 1/4db higher than those measured at the lower data rate than 11b mode ,thus the SAR can be excluded.




8. EUT Test Position

This EUT was tested in Right Cheek, Right Titled, Left Cheek, Left Titled, Front Face and Rear Face.


8.1 Define Two Imaginary Lines on the Handset

- (1) The vertical centerline passes through two points on the front side of the handset the midpoint of the width w_t of the handset at the level of the acoustic output, and the midpoint of the width w_b of the handset.
- (2) The horizontal line is perpendicular to the vertical centerline and passes through the center of the acoustic output. The horizontal line is also tangential to the face of the handset at point A.
- (3) The two lines intersect at point A. Note that for many handsets, point A coincides with the center of the acoustic output; however, the acoustic output may be located elsewhere on the horizontal line. Also note that the vertical centerline is not necessarily to the front face of the handset, especially for clamshell handsets, handsets with flip covers, and other irregularly shaped handsets.



Cheek Position

- 1) To position the device with the vertical center line of the body of the device and the horizontal line crossing the center piece in a plane parallel to the sagittal plane of the phantom. While maintaining the device in this plane, align the vertical center line with the reference plane containing the ear and mouth reference point (M: Mouth, RE: Right Ear, and LE: Left Ear) and align the center of the ear piece with the line RE-LE.
- 2) To move the device towards the phantom with the ear piece aligned with the line LE-RE until the phone touched the ear. While maintaining the device in the reference plane and maintaining the phone contact with ear, move the bottom of the phone until any point on the front side is in contact with the cheek of the phantom or until contact with the ear is lost






Title Position

- (1) To position the device in the “cheek” position described above.
- (2) While maintaining the device in the reference plane described above and pivoting against the ear, moves it outward away from the mouth by an angle of 15 degrees or until with the ear is lost.




Body-worn Position Conditions:

Body-worn accessory exposure is typically related to voice mode operations when handsets are carried in body-worn accessories. The body-worn accessory procedures in KDB Publication 447498 D01 should be used to test for body-worn accessory SAR compliance, without a headset connected to it. When the same wireless transmission configuration is used for testing body-worn accessory and hotspot mode SAR, respectively, in voice and data mode, SAR results for the most conservative *test separation distance* configuration may be used to support both SAR conditions. When the *reported* SAR for a body-worn accessory, measured without a headset connected to the handset, is $> 1.2 \text{ W/kg}$, the highest *reported* SAR configuration for that wireless mode and frequency band should be repeated for the body-worn accessory with a headset attached to the handset.



8.2 Hotspot mode exposure position condition

For handsets that support hotspot mode operations, with wireless router capabilities and various web browsing function, the relevant hand and body exposure condition are tested according to the hotspot SAR procedures in KDB 941225. A test separation distance of 10 mm is required between the phantom and all surface and edges with a transmitting antenna located within 25 mm from that surface or edge. When form factor of a handset is smaller than 9cm x 5cm, a test separation distance of 5mm (instead of 10mm) is required for testing hotspot mode. When the separate distance required for body-worn accessory testing is larger than or equal to that tested for hotspot mode, in the same wireless mode and for the same surface of the phone, the hotspot mode SAR data may be used to support body-worn accessory SAR compliance for that particular configuration (surface).





9. Uncertainty

9.1 Measurement Uncertainty

The following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in IEEE 1528: 2013. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.

Uncertainty Component	Tol (+/- %)	Prob. Dist.	Div.	Ci (1g)	Ci (10g)	1g Ui (+/-%)	10g Ui (+/-%)	vi
Measurement System								
Probe calibration	5.8	N	1	1	1	5.8	5.8	∞
Axial Isotropy	3.5	R	$\sqrt{3}$	$\sqrt{0.5}$	$\sqrt{0.5}$	1.43	1.43	∞
Hemispherical Isotropy	5.9	R	$\sqrt{3}$	$\sqrt{0.5}$	$\sqrt{0.5}$	2.41	2.41	∞
Boundary effect	1	R	$\sqrt{3}$	1	1	0.58	0.58	∞
Linearity	4.7	R	$\sqrt{3}$	1	1	2.71	2.71	∞
System detection limits	1	R	$\sqrt{3}$	1	1	0.58	0.58	∞
Modulation response	3	R	$\sqrt{3}$	1	1	1.73	1.73	∞
Readout Electronics	0.5	N	1	1	1	0.50	0.50	∞
Response Time	0	R	$\sqrt{3}$	1	1	0.00	0.00	∞
Integration Time	1.4	R	$\sqrt{3}$	1	1	1.81	1.81	∞
RF ambient conditions-Noise	3	R	$\sqrt{3}$	1	1	1.73	1.73	∞
RF ambient conditions-reflections	3	R	$\sqrt{3}$	1	1	1.73	1.73	∞
Probe positioner mechanical tolerance	1.4	R	$\sqrt{3}$	1	1	0.81	0.81	∞
Probe positioning with respect to phantom shell	1.4	R	$\sqrt{3}$	1	1	0.81	0.81	∞
Extrapolation, Interpolation and Integration Algorithms for Max, SAR	2.3	R	$\sqrt{3}$	1	1	1.33	1.33	∞
Test sample Related								
Test sample positioning	2.6	N	1	1	1	2.60	2.60	11
Device holder uncertainty	3	N	1	1	1	3.00	3.00	7
Output Power Variation - SAR Drift Measurement	5	R	$\sqrt{3}$	1	1	2.89	2.89	∞
SAR scaling	2	R	$\sqrt{3}$	1	1	1.15	1.15	∞
Phantom and tissue parameters								
Phantom uncertainty (shape and thickness uncertainty)	4	R	$\sqrt{3}$	1	1	2.31	2.31	∞
Uncertainty in SAR correction for deviations in permittivity and conductivity	2	N	1	1	0.84	2.00	1.68	∞
Liquid Conductivity - Measurement Uncertainty)	4	N	1	0.78	0.71	3.12	2.84	5
Liquid Permittivity - Measurement Uncertainty	5	N	1	0.23	0.26	1.15	1.30	5
Liquid Conductivity (Temperature Uncertainty)	2.5	R	$\sqrt{3}$	0.78	0.71	1.13	1.02	∞
Liquid Permittivity (Temperature Uncertainty)	2.5	R	$\sqrt{3}$	0.23	0.26	0.33	0.38	∞
Combined Standard Uncertainty		RSS				10.47	10.34	
Expanded Uncertainty (95% Confidence interval)		K				20.95	20.69	



9.2 System validation Uncertainty

Uncertainty Component	Tol (+-%)	Prob. Dist.	Div.	Ci (1g)	Ci (10g)	1g Ui (+-%)	10g Ui (+-%)	vi
Measurement System								
Probe calibration	5.8	N	1	1	1	5.8	5.8	∞
Axial Isotropy	3.5	R	$\sqrt{3}$	1	1	2.02	2.02	∞
Hemispherical Isotropy	5.9	R	$\sqrt{3}$	0	0	0.00	0.00	∞
Boundary effect	1	R	$\sqrt{3}$	1	1	0.58	0.58	∞
Linearity	4.7	R	$\sqrt{3}$	1	1	0.71	0.71	∞
System detection limits	1	R	$\sqrt{3}$	1	1	0.58	0.58	∞
Modulation response	0	N	$\sqrt{3}$	0	0	0.00	0.00	∞
Readout Electronics	0.5	N	1	1	1	0.50	0.50	∞
Response Time	0	R	$\sqrt{3}$	0	0	0.00	0.00	∞
Integration Time	1.4	R	$\sqrt{3}$	0	0	0.00	0.00	∞
RF ambient conditions-Noise	3	R	$\sqrt{3}$	1	1	1.73	1.73	∞
RF ambient conditions- reflections	3	R	$\sqrt{3}$	1	1	1.73	1.73	∞
Probe positioner mechanical tolerance	1.4	R	$\sqrt{3}$	1	1	0.81	0.81	∞
Probe positioning with respect to phantom shell	1.4	R	$\sqrt{3}$	1	1	0.81	0.81	∞
Extrapolation, Interpolation and Integration Algorithms for Max, SAR	2.3	R	$\sqrt{3}$	1	1	1.33	1.33	∞
Dipole								
Deviation of Experimental Source from Numerical Source	5	N	1	1	1	5.00	5.00	∞
Input Power and SAR Drift Measurement	0.5	R	$\sqrt{3}$	1	1	0.29	0.29	∞
Dipole Axis to Liquid Distance	2	R	$\sqrt{3}$	1	1	1.15	1.15	∞
Phantom and Tissue Parameters								
Phantom uncertainty (shape and thickness uncertainty)	4	R	$\sqrt{3}$	1	1	2.31	2.31	∞
Uncertainty in SAR correction for deviations in permittivity and conductivity	2	N	1	1	0.84	2.00	1.68	∞
Liquid Conductivity - Measurement Uncertainty)	4	N	1	0.78	0.71	3.12	2.84	5
Liquid Permittivity - Measurement Uncertainty	5	N	1	0.23	0.26	1.15	1.30	5
Liquid Conductivity (Temperature Uncertainty)	2.5	R	$\sqrt{3}$	0.78	0.71	1.13	1.02	∞
Liquid Permittivity (Temperature Uncertainty)	2.5	R	$\sqrt{3}$	0.23	0.26	0.33	0.38	∞
Combined Standard Uncertainty		RSS				10.16	10.03	
Expanded Uncertainty (95% Confidence interval)		K				20.32	20.06	



10. Conducted Power Measurement

10.1 Test Result

Burst Average Power (dBm)						
Band	GSM 850			PCS 1900		
Channel	128	190	251	512	661	810
Frequency (MHz)	824.2	836.6	848.8	1850.2	1880.0	1909.8
GSM (GMSK, 1-Slot)	33.10	33.38	33.71	29.88	30.38	30.27
GPRS (GMSK, 1-Slot)	33.09	33.36	33.69	29.88	30.39	30.29
GPRS (GMSK, 2-Slot)	31.20	31.24	31.59	27.69	28.28	28.37
GPRS (GMSK, 3-Slot)	29.39	29.40	29.78	26.17	26.80	26.88
GPRS (GMSK, 4-Slot)	27.37	27.35	27.78	24.22	24.82	24.96
EGPRS (8PSK, 1-Slot)	26.07	26.61	26.26	26.68	26.96	26.97
EGPRS (8PSK, 2-Slot)	25.19	25.08	25.56	25.74	25.16	25.65
EGPRS (8PSK, 3-Slot)	23.28	23.25	23.65	23.26	23.51	23.08
EGPRS (8PSK, 4-Slot)	21.03	21.03	21.26	20.33	20.86	21.46
Remark: GPRS, CS4 coding scheme. EGPRS, MCS5 coding scheme. Multi-Slot Class 8, Support Max 4 downlink, 1 uplink, 5 working link Multi-Slot Class 10, Support Max 4 downlink, 2 uplink, 5 working link Multi-Slot Class 12, Support Max 4 downlink, 4 uplink, 5 working link						

Frame- Average Power(dBm)						
Band	GSM 850			PCS 1900		
Channel	128	190	251	512	661	810
Frequency (MHz)	824.2	836.6	848.8	1850.2	1880.0	1909.8
GSM (GMSK, 1-Slot)	24.07	24.35	24.68	20.85	21.35	21.24
GPRS (GMSK, 1-Slot)	24.06	24.33	24.66	20.85	21.36	21.26
GPRS (GMSK, 2-Slot)	25.18	25.22	25.57	21.67	22.26	22.35
GPRS (GMSK, 3-Slot)	25.13	25.14	25.52	21.91	22.54	22.62
GPRS (GMSK, 4-Slot)	24.36	24.34	24.77	21.21	21.81	21.95
EGPRS (8PSK, 1-Slot)	17.04	17.58	17.23	17.65	17.93	17.94
EGPRS (8PSK, 2-Slot)	19.17	19.06	19.54	19.72	19.14	19.63
EGPRS (8PSK, 3-Slot)	19.02	18.99	19.39	19.00	19.25	18.82
EGPRS (8PSK, 4-Slot)	18.02	18.02	18.25	17.32	17.85	18.45
Remark: 1. SAR testing was performed on the maximum frame-averaged power mode. 2. The frame-averaged power is linearly proportion to the slot number configured and it is linearly scaled the maximum Burst - averaged power based on time slots. The calculated method is shown as below: Frame-averaged power = Burst averaged power (1 TX Slot) – 9.03 dB Frame-averaged power = Burst averaged power (2 TX Slots) – 6.02 dB Frame-averaged power = Burst averaged power (3 TX Slots) - 4.26 dB Frame-averaged power = Burst averaged power (4 TX Slots) – 3.01 dB						



WCDMA

Band	WCDMA Band 2			WCDMA Band 4			WCDMA Band 5		
Channel	9262	9400	9538	1312	1450	1513	4132	4182	4233
Frequency (MHz)	1852.4	1880	1907.6	1712.6	1740	1752.4	826.4	836.4	846.6
RMC 12.2Kbps	23.06	23.39	23.54	23.27	23.15	23.21	24.16	23.97	23.6
HSDPA Subtest-1	22.68	22.4	21.98	22.45	22.18	22.4	22.63	22.52	22.75
HSDPA Subtest-2	22.78	22.31	22.18	22.52	22.31	22.2	22.45	22.33	22.84
HSDPA Subtest-3	22.65	22.45	22.1	22.45	22.19	22.39	22.75	22.57	22.73
HSDPA Subtest-4	22.5	22.45	22.1	22.19	21.93	22.13	22.68	22.61	22.47
HSUPA Subtest-1	23.35	23	22.45	23.05	22.75	22.85	23.4	23.14	23.14
HSUPA Subtest-2	23.3	23.14	22.6	23.21	22.79	22.84	23.36	23.12	23.34
HSUPA Subtest-3	23.02	22.98	22.24	23.01	22.51	22.38	23.11	22.8	23.03
HSUPA Subtest-4	23.23	22.97	22.51	23.02	22.79	22.85	23.29	23.12	23.32
HSUPA Subtest-5	23.03	23.01	22.26	22.97	22.58	22.6	23.06	23.06	23.1

According to 3GPP 25.101 sub-clause 6.2.2, the maximum output power is allowed to be reduced by following the table.

Table 6.1A: UE maximum output power with HS-DPCCH and E-DCH

UE Transmit Channel Configuration	CM (db)	MPR (db)
For all combinations of ,DPDCH,DPCCH HS-DPDCH,E-DPDCH and E-DPCCH	$0 \leq CM \leq 3.5$	$MAX(CM-1,0)$
Note: $CM=1$ for $\beta_c/\beta_d=12/15$, $\beta_{hs}/\beta_c=24/15$. For all other combinations of DPDCH, DPCCH, HS-DPCCH, E-DPDCH and E-DPCCH the MPR is based on the relative CM difference.		

The device supports MPR to solve linearity issues (ACLR or SEM) due to the higher peak-to average ratios (PAR) of the HSUPA signal. This prevents saturating the full range of the TX DAC inside of device and provides a reduced power output to the RF transceiver chip according to the Cubic Metric (a function of the combinations of DPDCH, DPCCH, HS-DPCCH, E-DPDCH and E-DPCCH).

When E-DPDCH channels are present the beta gains on those channels are reduced firsts to try to get the power under the allowed limit. If the beta gains are lowered as far as possible, then a hard limiting is applied at the maximum allowed level.

The SW currently recalculates the cubic metric every time the beta gains on the E-DPDCH are reduced. The cubic metric will likely get lower each time this is done .However, there is no reported reduction of maximum output power in the HSUPA mode since the device also provides a compensation for the power back-off by increasing the gain of TX_AGC in the transceiver (PA) device.

The end effect is that the DUT output power is identical to the case where there is no MPR in the device.



BT				
Mode	Channel Number	Frequency (MHz)	Average Power (dBm)	Output Power (mW)
GFSK(1Mbps)	0	2402	-1.44	0.72
	39	2441	-1.32	0.74
	78	2480	-1.44	0.72
$\pi/4$ -QPSK(2Mbps)	0	2402	0.27	1.06
	39	2441	0.42	1.10
	78	2480	0.43	1.10
8DPSK(3Mbps)	0	2402	0.87	1.22
	39	2441	1.13	1.30
	78	2480	1.03	1.27

BLE				
Mode	Channel Number	Frequency (MHz)	Average Power (dBm)	Output Power (mW)
GFSK(1Mbps)	0	2402	-1.37	0.73
	19	2440	-1.24	0.75
	39	2480	-1.34	0.73
GFSK(2Mbps)	0	2402	-1.35	0.73
	19	2440	-1.22	0.76
	39	2480	-1.35	0.73

2.4GWIFI				
Mode	Channel Number	Frequency (MHz)	Average Power (dBm)	Output Power (mW)
802.11b	1	2412	16.18	41.50
	7	2437	16.27	42.36
	11	2462	16.4	43.65
802.11g	1	2412	15.58	36.14
	7	2437	15.66	36.81
	11	2462	15.72	37.33
802.11n-HT20	1	2412	15.59	36.22
	7	2437	15.69	37.07
	11	2462	15.73	37.41
802.11n-HT40	3	2422	14.96	31.33
	6	2437	15.09	32.28
	9	2452	15.14	32.66



5.2G WLAN				
Mode	Channel Number	Frequency (MHz)	Output Power (dBm)	Output Power (mW)
802.11a20	36	5180	14.36	27.29
	40	5200	14.14	25.94
	48	5240	13.85	24.27
802.11n-HT20	36	5180	13.17	20.75
	40	5200	12.93	19.63
	48	5240	12.67	18.49
802.11n-HT40	38	5190	12.96	19.77
	46	5230	12.72	18.71
802.11ac-VHT20	36	5180	13.09	20.37
	40	5200	13	19.95
	48	5240	12.76	18.88
802.11ac-VHT40	38	5190	12.96	19.77
	46	5230	12.66	18.45
802.11ac-VHT80	42	5210	12.17	16.48

5.3G WLAN				
Mode	Channel Number	Frequency (MHz)	Output Power (dBm)	Output Power (mW)
802.11a20	52	5260	14.23	26.49
	60	5300	14.08	25.59
	64	5320	14	25.12
802.11n-HT20	52	5260	13.05	20.18
	60	5300	12.92	19.59
	64	5320	12.64	18.37
802.11n-HT40	54	5270	13.16	20.70
	62	5310	12.69	18.58
802.11ac-VHT20	52	5260	13.06	20.23
	60	5300	12.91	19.54
	64	5320	12.69	18.58
802.11ac-VHT40	54	5270	13.15	20.65
	62	5310	12.67	18.49
802.11ac-VHT80	58	5290	12.01	15.89



5.6G WLAN				
Mode	Channel Number	Frequency (MHz)	Output Power (dBm)	Output Power (mW)
802.11a20	100	5500	14.06	25.47
	116	5580	13.9	24.55
	140	5700	13.33	21.53
802.11n-HT20	100	5500	12.9	19.50
	116	5580	12.59	18.16
	140	5700	11.99	15.81
802.11n-HT40	102	5510	13.13	20.56
	110	5550	12.9	19.50
	134	5670	12.26	16.83
802.11ac-VHT20	100	5500	12.85	19.28
	116	5580	12.64	18.37
	140	5700	11.98	15.78
802.11ac-VHT40	102	5510	13.17	20.75
	110	5550	12.92	19.59
	134	5670	12.09	16.18
802.11ac-VHT80	106	5530	12.15	16.41
	122	5610	11.66	14.66

5.8G WLAN				
Mode	Channel Number	Frequency (MHz)	Output Power (dBm)	Output Power (mW)
802.11a20	149	5745	14.23	26.49
	157	5785	14.17	26.12
	165	5825	13.76	23.77
802.11n-HT20	149	5745	12.98	19.86
	157	5785	12.76	18.88
	165	5825	12.59	18.16
802.11n-HT40	151	5755	13.54	22.59
	159	5795	13.39	21.83
802.11ac-VHT20	149	5745	12.91	19.54
	157	5785	12.97	19.82
	165	5825	12.53	17.91
802.11ac-VHT40	151	5755	13.62	23.01
	159	5795	13.42	21.98
802.11ac-VHT80	155	5775	12.64	18.37



LTE Conducted Power

General Note:

1. CMW500 base station simulator was used to setup the connection with EUT; the frequency band, channel bandwidth, RB allocation configuration, modulation type are set in the base station simulator to configure EUT transmitting at maximum power and at different configurations which are requested to be reported to FCC, for conducted power measurement and SAR testing.
2. Per KDB 941225 D05, when a properly configured base station simulator is used for the SAR and power measurements, spectrum plots for each RB allocation and offset configuration is not required.
3. Per KDB 941225 D05, start with the largest channel bandwidth and measure SAR for QPSK with 1 RB allocation, using the RB offset and required test channel combination with the highest maximum output power for RB offsets at the upper edge, middle and lower edge of each required test channel.
4. Per KDB 941225 D05, 50% RB allocation for QPSK SAR testing follows 1RB QPSK allocation procedure.
5. Per KDB 941225 D05, For QPSK with 100% RB allocation, SAR is not required when the highest maximum output power for 100 % RB allocation is less than the highest maximum output power in 50% and 1 RB allocations and the highest reported SAR for 1 RB and 50% RB allocation are ≤ 0.8 W/kg. Otherwise, SAR is measured for the highest output power channel; and if the reported SAR is > 1.45 W/kg, the remaining required test channels must also be tested.
6. Per KDB 941225 D05, 16QAM output power for each RB allocation configuration is $>$ not $\frac{1}{2}$ dB higher than the same configuration in QPSK and the reported SAR for the QPSK configuration is ≤ 1.45 W/kg; Per KDB 941225 D05, 16QAM SAR testing is not required.
7. Per KDB 941225 D05, Smaller bandwidth output power for each RB allocation configuration is $>$ not $\frac{1}{2}$ dB higher than the same configuration in the largest supported bandwidth, and the reported SAR for the largest supported bandwidth is ≤ 1.45 W/kg; Per KDB 941225 D05, smaller bandwidth SAR testing is not required.



LTE Band 2 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
1.4	1	0	QPSK	24.23	24.59	24.76
1.4	1	2		24.20	24.56	24.73
1.4	1	5		24.13	24.56	24.78
1.4	3	0		23.94	24.68	24.70
1.4	3	1		24.07	24.64	24.82
1.4	3	2		24.07	24.65	24.68
1.4	6	0		23.10	23.60	23.66
1.4	1	0	16-QAM	24.19	23.19	23.83
1.4	1	2		24.28	23.21	23.85
1.4	1	5		24.24	23.17	23.89
1.4	3	0		23.42	23.58	23.83
1.4	3	1		23.48	23.63	23.82
1.4	3	2		23.48	23.58	23.87
1.4	6	0		22.41	22.95	22.94
3	1	0	QPSK	24.10	24.64	24.78
3	1	7		24.09	24.60	24.82
3	1	14		24.13	24.57	24.76
3	8	0		23.20	23.65	23.68
3	8	4		23.07	23.67	23.76
3	8	7		23.11	23.61	23.78
3	15	0		23.06	23.64	23.70
3	1	0	16-QAM	24.33	23.15	23.82
3	1	7		24.37	23.09	23.81
3	1	14		24.35	23.06	23.90
3	8	0		22.10	22.71	22.92
3	8	4		22.16	22.72	22.83
3	8	7		22.17	22.66	22.85
3	15	0		22.28	22.67	22.96



LTE Band 2 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
5	1	0	QPSK	24.10	24.64	24.78
5	1	12		24.09	24.60	24.82
5	1	24		24.13	24.57	24.76
5	12	0		23.20	23.65	23.68
5	12	6		23.07	23.67	23.76
5	12	11		23.11	23.61	23.78
5	25	0		23.06	23.64	23.70
5	1	0	16-QAM	24.33	23.15	23.82
5	1	12		24.37	23.09	23.81
5	1	24		24.35	23.06	23.90
5	12	0		22.10	22.71	22.92
5	12	6		22.16	22.72	22.83
5	12	11		22.17	22.66	22.85
5	25	0		22.28	22.67	22.96
10	1	0	QPSK	24.03	24.52	24.50
10	1	24		24.14	24.58	24.68
10	1	49		24.30	24.44	24.81
10	25	0		23.17	23.73	23.60
10	25	12		23.17	23.61	23.68
10	25	24		23.21	23.56	23.76
10	50	0		23.26	23.54	23.75
10	1	0	16-QAM	24.34	24.40	24.05
10	1	24		24.47	24.39	24.08
10	1	49		24.60	24.29	24.16
10	25	0		22.25	22.82	22.80
10	25	12		22.33	22.80	22.85
10	25	24		22.47	22.73	22.92
10	50	0		22.37	22.75	22.79



LTE Band 2 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
15	1	0	QPSK	24.04	24.61	24.37
15	1	37		24.20	24.54	24.46
15	1	74		24.40	24.49	24.65
15	36	0		23.33	23.59	23.58
15	36	18		23.30	23.61	23.60
15	36	39		23.39	23.52	23.80
15	75	0		23.34	23.66	23.66
15	1	0	16-QAM	24.31	24.46	24.37
15	1	38		24.53	24.42	24.55
15	1	75		24.78	24.34	24.67
15	36	0		22.40	22.88	22.60
15	36	18		22.49	22.88	22.70
15	36	39		22.52	22.82	22.79
15	75	0		22.52	22.73	22.74
20	1	0	QPSK	24.13	24.90	24.45
20	1	49		24.42	24.80	24.59
20	1	99		24.72	24.72	24.78
20	50	0		23.30	23.77	23.51
20	50	24		23.46	23.69	23.50
20	50	49		23.56	23.43	23.74
20	100	0		23.49	23.59	23.56
20	1	0	16-QAM	23.28	23.46	23.84
20	1	49		23.51	23.31	23.99
20	1	99		23.84	23.30	24.19
20	50	0		22.50	22.82	22.69
20	50	24		22.67	22.81	22.74
20	50	49		22.79	22.68	22.79
20	100	0		22.62	22.76	22.63



LTE Band 4 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
1.4	1	0	QPSK	24.88	24.57	24.87
1.4	1	2		24.91	24.53	24.79
1.4	1	5		24.90	24.60	24.85
1.4	3	0		24.70	24.41	24.64
1.4	3	1		24.79	24.48	24.69
1.4	3	2		24.81	24.44	24.63
1.4	6	0		23.80	23.49	23.68
1.4	1	0	16-QAM	24.93	23.61	23.46
1.4	1	2		24.85	23.62	23.41
1.4	1	5		24.91	23.64	23.39
1.4	3	0		24.13	23.49	23.73
1.4	3	1		24.08	23.55	23.67
1.4	3	2		24.09	23.52	23.67
1.4	6	0		23.02	22.77	22.80
3	1	0	QPSK	24.79	24.59	24.94
3	1	7		24.73	24.55	24.79
3	1	14		24.62	24.60	24.86
3	8	0		23.81	23.42	23.66
3	8	4		23.80	23.54	23.72
3	8	7		23.69	23.41	23.68
3	15	0		23.81	23.51	23.69
3	1	0	16-QAM	24.90	24.73	24.61
3	1	7		24.58	24.81	24.74
3	1	14		24.58	24.92	24.70
3	8	0		23.64	23.44	23.63
3	8	4		23.55	23.47	23.77
3	8	7		23.40	23.57	23.64
3	15	0		23.56	23.55	23.77



LTE Band 4 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
5	1	0	QPSK	24.74	24.59	24.48
5	1	12		24.57	24.60	24.42
5	1	24		24.55	24.64	24.48
5	12	0		23.90	23.49	23.70
5	12	6		23.61	23.55	23.62
5	12	11		23.67	23.57	23.69
5	25	0		23.67	23.53	23.72
5	1	0	16-QAM	23.88	23.60	24.27
5	1	12		23.82	23.66	24.25
5	1	24		23.74	23.64	24.28
5	12	0		22.88	22.39	22.81
5	12	6		22.75	22.43	22.78
5	12	11		22.68	22.42	22.79
5	25	0		22.95	22.68	22.90
10	1	0	QPSK	24.75	24.36	24.73
10	1	24		24.58	24.44	24.73
10	1	49		24.48	24.52	24.73
10	25	0		23.67	23.40	23.82
10	25	12		23.65	23.43	23.65
10	25	24		23.54	23.42	23.77
10	50	0		23.67	23.60	23.69
10	1	0	16-QAM	24.95	24.25	24.65
10	1	24		24.87	24.24	24.59
10	1	49		24.72	24.32	24.60
10	25	0		22.78	22.56	22.86
10	25	12		22.78	22.65	22.90
10	25	24		22.71	22.70	22.85
10	50	0		22.79	22.62	22.75



LTE Band 4 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
15	1	0	QPSK	24.68	24.43	24.58
15	1	37		24.44	24.41	24.65
15	1	74		24.36	24.48	24.64
15	36	0		23.68	23.48	23.75
15	36	18		23.51	23.52	23.79
15	36	39		23.50	23.54	23.71
15	75	0		23.52	23.51	23.77
15	1	0	16-QAM	25.01	24.25	24.73
15	1	38		24.76	24.21	24.76
15	1	75		24.67	24.39	24.76
15	36	0		22.88	22.68	22.76
15	36	18		22.76	22.71	22.75
15	36	39		22.71	22.77	22.78
15	75	0		22.69	22.63	22.90
20	1	0	QPSK	25.09	23.59	23.40
20	1	49		24.99	23.63	23.38
20	1	99		24.90	23.62	23.36
20	50	0		22.78	22.67	22.89
20	50	24		22.82	22.66	22.89
20	50	49		22.79	22.70	22.89
20	100	0		22.92	22.59	22.85
20	1	0	16-QAM	23.93	23.71	24.17
20	1	49		23.65	23.63	24.26
20	1	99		23.65	23.88	24.26
20	50	0		22.87	22.58	22.90
20	50	24		22.66	22.70	22.89
20	50	49		22.68	22.68	22.94
20	100	0		22.61	22.62	22.87



LTE Band 5 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
1.4	1	0	QPSK	15.83	15.78	15.92
1.4	1	2		16.05	16.00	16.10
1.4	1	5		15.83	15.74	15.83
1.4	3	0		15.81	15.89	15.97
1.4	3	1		15.89	15.97	16.03
1.4	3	2		15.83	15.87	15.92
1.4	6	0		14.78	14.73	14.76
1.4	1	0	16-QAM	14.85	14.81	14.50
1.4	1	2		15.05	15.04	14.67
1.4	1	5		14.85	14.82	14.44
1.4	3	0		14.97	15.00	14.89
1.4	3	1		15.04	15.08	14.94
1.4	3	2		14.97	15.00	14.87
1.4	6	0		14.12	13.96	14.09
3	1	0	QPSK	15.71	15.84	16.00
3	1	7		15.92	16.02	16.16
3	1	14		15.81	15.68	15.90
3	8	0		14.81	14.79	14.85
3	8	4		14.86	14.83	14.86
3	8	7		14.85	14.76	14.80
3	15	0		14.82	14.78	14.85
3	1	0	16-QAM	15.09	14.87	14.62
3	1	7		15.27	15.06	14.71
3	1	14		15.15	14.76	14.48
3	8	0		14.00	13.86	14.02
3	8	4		14.05	13.89	14.04
3	8	7		14.04	13.81	13.97
3	15	0		14.03	13.78	14.08



LTE Band 5 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
5	1	0	QPSK	15.39	15.46	15.72
5	1	12		16.01	16.00	16.11
5	1	24		15.63	15.35	15.50
5	12	0		14.75	14.70	14.86
5	12	6		14.94	14.85	14.95
5	12	11		14.88	14.64	14.76
5	25	0		14.81	14.69	14.82
5	1	0	16-QAM	14.92	14.66	14.92
5	1	12		15.49	15.22	15.21
5	1	24		15.10	14.63	14.62
5	12	0		13.89	13.71	14.05
5	12	6		14.10	13.85	14.14
5	12	11		14.04	13.65	13.93
5	25	0		13.94	13.74	13.94
10	1	0	QPSK	15.20	15.43	16.43
10	1	24		15.79	16.00	16.28
10	1	49		16.26	15.95	16.22
10	25	0		14.68	14.72	15.33
10	25	12		14.90	14.88	15.17
10	25	24		15.18	14.95	15.06
10	50	0		14.93	14.84	15.19
10	1	0	16-QAM	14.74	14.44	15.10
10	1	24		15.22	15.04	14.98
10	1	49		15.68	15.03	14.72
10	25	0		13.80	13.79	14.46
10	25	12		14.03	13.93	14.30
10	25	24		14.31	14.01	14.19
10	50	0		14.03	13.92	14.32



LTE Band 7 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
5	1	0	QPSK	23.35	22.93	23.04
5	1	12		23.76	23.26	23.46
5	1	24		23.34	22.94	23.03
5	12	0		22.38	22.07	22.07
5	12	6		22.40	22.09	22.17
5	12	11		22.39	22.02	22.09
5	25	0		22.42	22.10	22.12
5	1	0	16-QAM	22.55	22.24	22.51
5	1	12		23.00	22.71	22.91
5	1	24		22.59	22.27	22.45
5	12	0		21.28	21.07	21.03
5	12	6		21.36	21.07	21.13
5	12	11		21.33	21.03	21.07
5	25	0		21.36	21.05	21.05
10	1	0	QPSK	23.38	22.99	23.11
10	1	24		23.63	23.20	23.28
10	1	49		23.47	23.05	23.07
10	25	0		22.40	22.13	22.15
10	25	12		22.46	22.06	22.16
10	25	24		22.55	22.09	22.21
10	50	0		22.48	22.06	22.18
10	1	0	16-QAM	22.18	22.34	22.23
10	1	24		22.33	22.55	22.43
10	1	49		22.23	22.43	22.18
10	25	0		21.33	21.08	21.10
10	25	12		21.40	21.05	21.12
10	25	24		21.48	21.01	21.13
10	50	0		21.40	21.05	21.17



LTE Band 7 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
15	1	0	QPSK	23.26	22.92	23.05
15	1	37		23.80	23.23	23.54
15	1	74		23.31	22.99	23.03
15	36	0		22.34	22.08	22.12
15	36	18		22.43	22.08	22.16
15	36	39		22.51	22.06	22.20
15	75	0		22.45	22.07	22.14
15	1	0	16-QAM	22.58	22.03	22.05
15	1	38		23.01	22.46	22.42
15	1	75		22.68	22.13	22.01
15	36	0		21.35	21.12	21.05
15	36	18		21.44	21.13	21.12
15	36	39		21.52	21.07	21.11
15	75	0		21.39	21.05	21.11
20	1	0	QPSK	23.11	22.71	22.86
20	1	49		23.52	23.19	23.25
20	1	99		23.17	22.91	22.87
20	50	0		22.23	22.08	22.01
20	50	24		22.41	22.05	22.12
20	50	49		22.61	21.95	22.16
20	100	0		22.37	21.99	22.10
20	1	0	16-QAM	22.25	21.97	21.96
20	1	49		22.73	22.48	22.43
20	1	99		22.33	22.12	22.02
20	50	0		21.22	21.09	20.95
20	50	24		21.41	21.07	21.06
20	50	49		21.64	20.92	21.12
20	100	0		21.38	21.01	21.05



LTE Band 12 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
1.4	1	0	QPSK	24.64	24.61	24.47
1.4	1	2		24.68	24.67	24.39
1.4	1	5		24.62	24.63	24.41
1.4	3	0		24.67	24.48	24.47
1.4	3	1		24.69	24.54	24.35
1.4	3	2		24.69	24.63	24.28
1.4	6	0		23.65	23.61	23.43
1.4	1	0	16-QAM	24.58	24.62	24.47
1.4	1	2		24.54	24.62	24.34
1.4	1	5		24.50	24.49	24.30
1.4	3	0		23.69	23.54	23.43
1.4	3	1		23.61	23.46	23.45
1.4	3	2		23.57	23.51	23.30
1.4	6	0		23.68	23.65	23.32
3	1	0	QPSK	24.52	24.81	24.57
3	1	7		24.53	24.65	24.45
3	1	14		24.67	24.59	24.36
3	8	0		23.52	23.59	23.39
3	8	4		23.61	23.67	23.31
3	8	7		23.64	23.68	23.37
3	15	0		23.62	23.64	23.28
3	1	0	16-QAM	24.64	23.62	23.46
3	1	7		24.61	23.54	23.45
3	1	14		24.67	23.57	23.48
3	8	0		22.51	22.57	22.43
3	8	4		22.42	22.62	22.37
3	8	7		22.56	22.50	22.43
3	15	0		22.76	22.59	22.35



LTE Band 12 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
5	1	0	QPSK	24.54	24.55	24.28
5	1	12		24.57	24.49	24.21
5	1	24		24.50	24.44	24.02
5	12	0		23.66	23.61	23.40
5	12	6		23.74	23.48	23.47
5	12	11		23.56	23.54	23.34
5	25	0		23.63	23.59	23.44
5	1	0	16-QAM	23.71	23.33	24.06
5	1	12		23.71	23.34	23.91
5	1	24		23.78	23.22	23.79
5	12	0		22.55	22.52	22.38
5	12	6		22.54	22.46	22.30
5	12	11		22.51	22.39	22.28
5	25	0		22.83	22.61	22.50
10	1	0	QPSK	24.95	23.58	23.36
10	1	24		24.89	23.63	23.39
10	1	49		24.92	23.58	23.43
10	25	0		23.99	23.59	23.25
10	25	12		23.97	23.68	23.24
10	25	24		23.96	23.63	23.30
10	50	0		22.83	22.71	22.41
10	1	0	16-QAM	24.53	24.37	24.07
10	1	24		24.56	24.32	23.93
10	1	49		24.44	24.10	23.76
10	25	0		22.63	22.64	22.49
10	25	12		22.75	22.55	22.48
10	25	24		22.54	22.54	22.46
10	50	0		22.65	22.65	22.34



LTE Band 13 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
5	1	0	QPSK	25.15	25.03	25.10
5	1	12		25.25	25.04	25.18
5	1	24		25.24	25.07	25.15
5	12	0		24.12	24.27	24.25
5	12	6		24.22	24.26	24.16
5	12	11		24.11	24.21	24.26
5	25	0		24.31	24.31	24.28
5	1	0	16-QAM	23.81	24.76	24.38
5	1	12		23.93	24.75	24.46
5	1	24		24.01	24.85	24.35
5	12	0		23.02	23.20	23.17
5	12	6		23.12	23.29	23.22
5	12	11		23.13	23.34	23.12
5	25	0		23.27	23.43	23.38
10	1	0	QPSK	/	25.11	/
10	1	24		/	25.24	/
10	1	49		/	25.27	/
10	25	0		/	24.21	/
10	25	12		/	24.16	/
10	25	24		/	24.29	/
10	50	0		/	24.25	/
10	1	0	16-QAM	/	25.13	/
10	1	24		/	25.24	/
10	1	49		/	25.23	/
10	25	0		/	23.25	/
10	25	12		/	23.33	/
10	25	24		/	23.31	/
10	50	0		/	23.29	/



LTE Band 17 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
5	1	0	QPSK	24.53	24.38	24.34
5	1	12		24.55	24.19	24.34
5	1	24		24.50	24.21	24.10
5	12	0		23.69	23.40	23.40
5	12	6		23.55	23.41	23.50
5	12	11		23.51	23.47	23.33
5	25	0		23.55	23.45	23.45
5	1	0	16-QAM	23.33	24.03	23.53
5	1	12		23.26	23.95	23.51
5	1	24		23.21	23.92	23.35
5	12	0		22.55	22.39	22.22
5	12	6		22.44	22.40	22.29
5	12	11		22.39	22.33	22.19
5	25	0		22.69	22.54	22.40
10	1	0	QPSK	24.47	24.59	24.57
10	1	24		24.43	24.41	24.31
10	1	49		24.39	24.34	24.26
10	25	0		23.50	23.62	23.44
10	25	12		23.46	23.46	23.46
10	25	24		23.42	23.42	23.35
10	50	0		23.60	23.47	23.47
10	1	0	16-QAM	24.51	24.36	24.12
10	1	24		24.41	24.24	23.92
10	1	49		24.30	24.00	23.79
10	25	0		22.60	22.52	22.54
10	25	12		22.40	22.51	22.53
10	25	24		22.39	22.43	22.39
10	50	0		22.55	22.45	22.38



LTE Band 25 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
1.4	1	0	QPSK	24.55	24.85	25.29
1.4	1	2		24.55	24.88	25.28
1.4	1	5		24.63	24.87	25.22
1.4	3	0		24.45	25.00	25.26
1.4	3	1		24.51	24.94	25.14
1.4	3	2		24.50	24.94	25.21
1.4	6	0		23.48	23.92	24.22
1.4	1	0	16-QAM	24.61	23.42	24.31
1.4	1	2		24.65	23.46	24.35
1.4	1	5		24.61	23.51	24.35
1.4	3	0		23.82	23.89	24.24
1.4	3	1		23.85	23.92	24.28
1.4	3	2		23.85	23.90	24.27
1.4	6	0		22.86	23.27	23.39
3	1	0	QPSK	24.49	24.97	25.22
3	1	7		24.51	24.88	25.30
3	1	14		24.53	24.84	25.27
3	8	0		23.55	24.03	24.21
3	8	4		23.49	24.05	24.22
3	8	7		23.51	23.98	24.16
3	15	0		23.55	24.01	24.18
3	1	0	16-QAM	24.72	23.49	24.34
3	1	7		24.78	23.43	24.30
3	1	14		24.85	23.38	24.32
3	8	0		22.60	23.05	23.34
3	8	4		22.60	23.05	23.35
3	8	7		22.60	23.09	23.32
3	15	0		22.69	23.06	23.51



LTE Band 25 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
5	1	0	QPSK	24.48	25.01	24.97
5	1	12		24.50	24.98	24.99
5	1	24		24.54	24.99	25.03
5	12	0		23.57	24.01	24.19
5	12	6		23.63	23.90	24.18
5	12	11		23.69	23.91	24.25
5	25	0		23.57	23.98	24.28
5	1	0	16-QAM	23.64	24.17	24.86
5	1	12		23.78	24.12	24.82
5	1	24		23.85	24.13	24.83
5	12	0		22.68	22.87	23.25
5	12	6		22.65	22.92	23.32
5	12	11		22.71	22.90	23.32
5	25	0		22.89	23.16	23.47
10	1	0	QPSK	24.45	25.03	25.07
10	1	24		24.55	24.89	25.09
10	1	49		24.74	24.88	25.28
10	25	0		23.65	23.98	24.08
10	25	12		23.63	23.97	24.23
10	25	24		23.67	23.90	24.24
10	50	0		23.77	23.96	24.19
10	1	0	16-QAM	24.73	24.89	24.48
10	1	24		24.95	24.81	24.60
10	1	49		25.01	24.74	24.64
10	25	0		22.77	23.13	23.32
10	25	12		22.85	23.12	23.32
10	25	24		22.89	23.10	23.38
10	50	0		22.84	23.10	23.24



LTE Band 25 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
15	1	0	QPSK	24.47	24.99	24.93
15	1	37		24.66	24.94	25.03
15	1	74		24.87	24.82	25.13
15	36	0		23.73	23.99	24.10
15	36	18		23.77	24.01	24.20
15	36	39		23.87	23.90	24.24
15	75	0		23.67	23.98	24.04
15	1	0	16-QAM	24.73	24.91	24.94
15	1	38		24.89	24.80	25.07
15	1	75		25.17	24.69	25.18
15	36	0		22.89	23.30	23.13
15	36	18		22.93	23.24	23.21
15	36	39		23.00	23.15	23.24
15	75	0		22.95	23.09	23.24
20	1	0	QPSK	24.58	25.38	24.92
20	1	49		24.89	25.25	25.13
20	1	99		25.14	25.14	25.32
20	50	0		23.74	23.96	23.99
20	50	24		23.84	23.99	24.14
20	50	49		23.92	24.02	24.20
20	100	0		23.85	24.00	24.17
20	1	0	16-QAM	23.70	23.84	24.34
20	1	49		23.96	23.64	24.49
20	1	99		24.24	23.66	24.64
20	50	0		22.98	23.20	23.22
20	50	24		23.11	23.16	23.23
20	50	49		23.22	23.08	23.29
20	100	0		23.03	23.09	23.16



LTE Band 26 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
1.4	1	0	QPSK	22.87	22.90	23.00
1.4	1	2		23.01	23.08	23.12
1.4	1	5		22.89	22.89	23.00
1.4	3	0		22.91	23.00	23.03
1.4	3	1		22.89	22.97	23.00
1.4	3	2		22.89	22.98	23.00
1.4	6	0		21.79	21.90	21.94
1.4	1	0	16-QAM	22.10	22.12	21.91
1.4	1	2		22.15	22.25	22.00
1.4	1	5		22.04	22.12	21.87
1.4	3	0		22.15	22.25	22.20
1.4	3	1		22.11	22.28	22.20
1.4	3	2		22.07	22.27	22.22
1.4	6	0		21.00	21.07	21.12
3	1	0	QPSK	22.88	22.95	22.93
3	1	7		23.16	23.21	23.20
3	1	14		22.85	22.99	22.90
3	8	0		21.81	21.83	21.91
3	8	4		21.81	21.88	21.93
3	8	7		21.85	21.85	21.92
3	15	0		21.80	21.90	21.90
3	1	0	16-QAM	22.12	21.86	22.43
3	1	7		22.42	22.16	22.46
3	1	14		22.10	21.82	22.39
3	8	0		20.80	20.83	20.91
3	8	4		20.84	20.87	20.97
3	8	7		20.84	20.87	20.90
3	15	0		20.75	20.94	20.91



LTE Band 26 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
5	1	0	QPSK	22.68	22.76	22.85
5	1	12		23.18	23.26	23.30
5	1	24		22.78	22.83	22.86
5	12	0		21.70	21.80	21.88
5	12	6		21.84	21.89	21.95
5	12	11		21.86	21.85	21.84
5	25	0		21.87	21.91	21.96
5	1	0	16-QAM	22.12	22.35	22.21
5	1	12		22.41	22.85	22.68
5	1	24		22.20	22.41	22.23
5	12	0		20.76	20.83	20.88
5	12	6		20.93	20.99	20.94
5	12	11		20.94	20.93	20.81
5	25	0		20.79	20.87	20.95
10	1	0	QPSK	/	23.11	/
10	1	24		/	23.33	/
10	1	49		/	23.21	/
10	25	0		/	21.81	/
10	25	12		/	21.97	/
10	25	24		/	21.96	/
10	50	0		/	21.93	/
10	1	0	16-QAM	/	22.25	/
10	1	24		/	22.52	/
10	1	49		/	22.38	/
10	25	0		/	20.87	/
10	25	12		/	20.94	/
10	25	24		/	21.05	/
10	50	0		/	20.92	/



LTE Band 26 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
1.4	1	0	QPSK	22.99	23.14	23.00
1.4	1	2		23.14	23.31	23.18
1.4	1	5		22.99	23.13	22.97
1.4	3	0		23.02	23.09	23.06
1.4	3	1		23.02	23.09	23.04
1.4	3	2		23.05	23.11	23.03
1.4	6	0		21.93	22.04	21.94
1.4	1	0	16-QAM	21.85	22.28	22.19
1.4	1	2		22.01	22.44	22.30
1.4	1	5		21.84	22.27	22.27
1.4	3	0		22.19	22.34	22.32
1.4	3	1		22.25	22.34	22.37
1.4	3	2		22.25	22.35	22.32
1.4	6	0		21.12	21.28	21.13
3	1	0	QPSK	22.89	22.95	22.96
3	1	7		23.35	23.36	23.26
3	1	14		23.01	23.01	22.85
3	8	0		21.90	22.07	22.03
3	8	4		21.96	22.10	22.03
3	8	7		21.96	22.11	22.01
3	15	0		21.89	22.10	22.06
3	1	0	16-QAM	22.40	22.32	22.02
3	1	7		22.83	22.63	22.28
3	1	14		22.40	22.30	21.92
3	8	0		20.94	21.08	21.01
3	8	4		20.96	21.09	21.01
3	8	7		20.99	21.06	20.99
3	15	0		20.93	21.06	21.06



LTE Band 26 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
5	1	0	QPSK	22.85	22.94	22.95
5	1	12		23.34	23.40	23.36
5	1	24		22.90	22.93	22.90
5	12	0		21.99	22.10	22.08
5	12	6		22.01	22.15	22.08
5	12	11		21.95	22.01	21.95
5	25	0		21.98	22.16	22.06
5	1	0	16-QAM	22.25	22.36	22.54
5	1	12		22.59	22.79	22.94
5	1	24		22.30	22.35	22.54
5	12	0		20.91	21.19	21.14
5	12	6		21.01	21.21	21.10
5	12	11		20.95	21.07	20.99
5	25	0		21.00	21.09	21.07
10	1	0	QPSK	22.98	23.04	23.05
10	1	24		23.22	23.18	23.15
10	1	49		23.12	23.04	23.01
10	25	0		22.07	22.21	22.16
10	25	12		22.02	22.17	22.04
10	25	24		22.10	22.10	21.92
10	50	0		22.10	22.21	22.06
10	1	0	16-QAM	21.83	22.52	22.26
10	1	24		22.04	22.72	22.33
10	1	49		21.92	22.58	22.21
10	25	0		21.02	21.25	21.13
10	25	12		21.06	21.21	21.11
10	25	24		21.11	21.13	20.95
10	50	0		21.06	21.20	21.08



LTE Band 26 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
15	1	0	QPSK	22.94	23.09	23.08
15	1	37		23.11	23.35	23.44
15	1	74		22.92	23.07	23.11
15	36	0		22.00	22.04	22.14
15	36	18		22.07	22.09	22.07
15	36	39		22.02	22.04	21.92
15	75	0		22.01	22.06	22.12
15	1	0	16-QAM	22.01	22.08	22.37
15	1	38		22.57	22.50	22.76
15	1	75		22.20	22.02	22.37
15	36	0		21.05	21.10	21.20
15	36	18		21.14	21.08	21.14
15	36	39		21.12	21.07	21.00
15	75	0		21.00	21.08	21.03



LTE Band 38 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
5	1	0	QPSK	23.88	24.62	24.63
5	1	12		23.81	24.52	24.58
5	1	24		23.89	24.53	24.59
5	12	0		22.88	23.69	23.77
5	12	6		22.83	23.67	23.71
5	12	11		22.81	23.64	23.68
5	25	0		22.84	23.68	23.73
5	1	0	16-QAM	22.81	23.53	24.07
5	1	12		22.84	23.66	24.04
5	1	24		22.88	23.65	24.10
5	12	0		22.06	22.70	22.73
5	12	6		21.98	22.55	22.69
5	12	11		22.01	22.54	22.74
5	25	0		22.00	22.89	22.92
10	1	0	QPSK	24.29	24.44	24.93
10	1	24		24.29	24.56	24.82
10	1	49		24.51	24.61	24.73
10	25	0		23.34	23.68	23.86
10	25	12		23.23	23.73	23.74
10	25	24		23.45	23.77	23.73
10	50	0		23.37	23.73	23.83
10	1	0	16-QAM	23.56	23.98	24.25
10	1	24		23.72	23.90	24.04
10	1	49		23.91	23.99	24.09
10	25	0		22.25	22.92	22.89
10	25	12		22.26	22.95	22.91
10	25	24		22.27	22.94	22.89
10	50	0		22.44	22.89	22.84



LTE Band 38 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
15	1	0	QPSK	24.36	24.93	24.99
15	1	37		24.53	24.95	24.77
15	1	74		24.43	24.97	24.73
15	36	0		23.25	23.81	23.76
15	36	18		23.22	23.64	23.83
15	36	39		23.34	23.72	23.73
15	75	0		23.20	23.75	23.82
15	1	0	16-QAM	23.89	23.91	23.96
15	1	38		24.05	24.02	23.84
15	1	75		24.01	23.94	23.75
15	36	0		22.31	22.82	22.91
15	36	18		22.37	22.78	22.86
15	36	39		22.40	22.84	22.73
15	75	0		22.42	22.81	22.87
20	1	0	QPSK	24.31	24.98	24.87
20	1	49		24.41	24.90	24.75
20	1	99		24.44	24.99	24.66
20	50	0		23.20	23.61	23.85
20	50	24		23.23	23.63	23.74
20	50	49		23.22	23.79	23.80
20	100	0		23.31	23.69	23.76
20	1	0	16-QAM	23.32	23.87	23.64
20	1	49		23.36	23.80	23.34
20	1	99		23.48	24.29	23.56
20	50	0		22.58	22.71	22.97
20	50	24		22.58	22.67	22.81
20	50	49		22.62	22.66	22.89
20	100	0		22.43	22.73	22.81



LTE Band 40 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
5	1	0	QPSK	14.52	12.82	12.97
5	1	12		14.52	12.82	13.03
5	1	24		14.51	12.81	13.01
5	12	0		14.51	12.81	13.00
5	12	6		14.50	12.81	13.00
5	12	11		14.50	12.81	13.04
5	25	0		14.50	12.81	13.05
5	1	0	16-QAM	14.49	12.81	13.03
5	1	12		14.49	12.81	13.09
5	1	24		14.49	12.82	13.06
5	12	0		14.48	12.81	13.10
5	12	6		14.48	12.86	13.10
5	12	11		14.48	12.87	13.12
5	25	0		14.48	12.84	13.12
10	1	0	QPSK	/	14.77	/
10	1	24		/	15.25	/
10	1	49		/	15.57	/
10	25	0		/	14.08	/
10	25	12		/	14.24	/
10	25	24		/	14.46	/
10	50	0		/	14.27	/
10	1	0	16-QAM	/	14.28	/
10	1	24		/	14.71	/
10	1	49		/	14.98	/
10	25	0		/	13.09	/
10	25	12		/	13.27	/
10	25	24		/	13.46	/
10	50	0		/	13.24	/



LTE Band 40 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
5	1	0	QPSK	14.56	14.68	14.81
5	1	12		15.10	15.15	15.28
5	1	24		14.53	14.59	14.75
5	12	0		13.97	14.10	14.15
5	12	6		14.11	14.18	14.31
5	12	11		13.93	14.00	14.09
5	25	0		13.94	14.05	14.12
5	1	0	16-QAM	14.23	14.03	14.18
5	1	12		14.77	14.53	14.68
5	1	24		14.19	13.96	14.02
5	12	0		13.01	13.08	13.24
5	12	6		13.16	13.22	13.33
5	12	11		12.99	13.02	13.14
5	25	0		12.96	13.13	13.14
10	1	0	QPSK	/	14.8	/
10	1	24		/	15.13	/
10	1	49		/	15.34	/
10	25	0		/	14.32	/
10	25	12		/	14.39	/
10	25	24		/	14.4	/
10	50	0		/	14.35	/
10	1	0	16-QAM	/	14.44	/
10	1	24		/	14.81	/
10	1	49		/	14.76	/
10	25	0		/	13.34	/
10	25	12		/	13.48	/
10	25	24		/	13.47	/
10	50	0		/	13.38	/



LTE Band 41 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
5	1	0	QPSK	24.40	24.60	24.27
5	1	12		24.34	24.51	24.40
5	1	24		24.33	24.53	24.34
5	12	0		23.33	23.51	23.43
5	12	6		23.27	23.53	23.51
5	12	11		23.32	23.48	23.47
5	25	0		23.25	23.52	23.53
5	1	0	16-QAM	23.28	23.16	23.74
5	1	12		23.24	23.21	23.76
5	1	24		23.18	23.22	23.74
5	12	0		22.54	22.51	22.41
5	12	6		22.43	22.47	22.45
5	12	11		22.51	22.30	22.37
5	25	0		22.60	22.72	22.68
10	1	0	QPSK	24.71	24.59	24.48
10	1	24		24.71	24.73	24.46
10	1	49		24.76	24.76	24.46
10	25	0		23.52	23.47	23.49
10	25	12		23.55	23.51	23.48
10	25	24		23.68	23.57	23.55
10	50	0		23.58	23.47	23.51
10	1	0	16-QAM	24.12	23.26	23.81
10	1	24		24.12	23.26	23.79
10	1	49		24.29	23.30	23.86
10	25	0		22.65	22.62	22.52
10	25	12		22.65	22.67	22.62
10	25	24		22.75	22.61	22.57
10	50	0		22.86	22.71	22.54



LTE Band 41 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
15	1	0	QPSK	24.68	24.52	24.88
15	1	37		24.73	24.67	24.60
15	1	74		24.81	24.67	24.68
15	36	0		23.63	23.56	23.75
15	36	18		23.72	23.44	23.73
15	36	39		23.72	23.58	23.68
15	75	0		23.60	23.61	23.72
15	1	0	16-QAM	24.11	23.22	23.92
15	1	38		24.37	23.32	23.76
15	1	75		24.25	23.28	23.77
15	36	0		22.79	22.60	22.76
15	36	18		22.87	22.64	22.49
15	36	39		22.86	22.65	22.64
15	75	0		22.69	22.62	22.71
20	1	0	QPSK	24.58	24.55	25.05
20	1	49		24.74	24.54	24.78
20	1	99		24.89	24.71	24.80
20	50	0		23.59	23.57	23.78
20	50	24		23.71	23.49	23.77
20	50	49		23.81	23.61	23.74
20	100	0		23.68	23.58	23.71
20	1	0	16-QAM	23.34	23.11	23.50
20	1	49		23.41	23.16	22.90
20	1	99		23.41	23.26	22.77
20	50	0		22.87	22.45	23.07
20	50	24		22.86	22.65	22.86
20	50	49		22.93	22.57	22.81
20	100	0		22.77	22.65	22.75



LTE Band 66 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
1.4	1	0	QPSK	24.39	24.23	24.35
1.4	1	2		24.40	24.26	24.35
1.4	1	5		24.29	24.24	24.35
1.4	3	0		24.22	24.22	24.36
1.4	3	1		24.31	24.26	24.39
1.4	3	2		24.23	24.17	24.31
1.4	6	0		23.30	23.35	23.43
1.4	1	0	16-QAM	24.38	23.39	23.44
1.4	1	2		24.35	23.39	23.46
1.4	1	5		24.38	23.43	23.48
1.4	3	0		23.60	23.10	23.46
1.4	3	1		23.64	23.16	23.42
1.4	3	2		23.63	23.14	23.42
1.4	6	0		22.60	22.54	22.54
3	1	0	QPSK	24.23	24.22	24.36
3	1	7		24.24	24.24	24.43
3	1	14		24.19	24.25	24.37
3	8	0		23.24	23.23	23.34
3	8	4		23.26	23.23	23.32
3	8	7		23.28	23.25	23.41
3	15	0		23.28	23.31	23.38
3	1	0	16-QAM	24.57	23.36	23.42
3	1	7		24.49	23.35	23.40
3	1	14		24.46	23.41	23.43
3	8	0		22.34	22.47	22.40
3	8	4		22.35	22.46	22.51
3	8	7		22.25	22.48	22.46
3	15	0		22.43	22.39	22.61



LTE Band 66 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
5	1	0	QPSK	24.24	24.37	24.10
5	1	12		24.16	24.39	24.09
5	1	24		24.16	24.41	24.12
5	12	0		23.36	23.38	23.33
5	12	6		23.27	23.36	23.31
5	12	11		23.23	23.25	23.31
5	25	0		23.33	23.36	23.29
5	1	0	16-QAM	23.41	23.46	23.97
5	1	12		23.34	23.44	23.94
5	1	24		23.36	23.44	23.95
5	12	0		22.34	22.22	22.42
5	12	6		22.29	22.21	22.40
5	12	11		22.25	22.21	22.40
5	25	0		22.55	22.36	22.55
10	1	0	QPSK	24.23	24.26	24.26
10	1	24		24.07	24.27	24.29
10	1	49		23.96	24.37	24.38
10	25	0		23.28	23.23	23.36
10	25	12		23.29	23.31	23.34
10	25	24		23.14	23.35	23.35
10	50	0		23.22	23.35	23.28
10	1	0	16-QAM	24.46	23.89	23.67
10	1	24		24.44	23.97	23.64
10	1	49		24.35	23.99	23.87
10	25	0		22.44	22.44	22.48
10	25	12		22.35	22.44	22.48
10	25	24		22.24	22.46	22.51
10	50	0		22.38	22.49	22.41



LTE Band 66 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
15	1	0	QPSK	24.18	24.25	24.08
15	1	37		24.03	24.33	24.13
15	1	74		24.07	24.32	24.24
15	36	0		23.26	23.20	23.37
15	36	18		23.08	23.39	23.25
15	36	39		23.18	23.31	23.32
15	75	0		23.08	23.23	23.32
15	1	0	16-QAM	24.53	23.25	24.15
15	1	38		24.33	23.32	24.21
15	1	75		24.31	23.24	24.28
15	36	0		22.44	22.40	22.34
15	36	18		22.28	22.56	22.33
15	36	39		22.27	22.50	22.42
15	75	0		22.32	22.35	22.38
20	1	0	QPSK	24.35	24.46	24.24
20	1	49		24.18	24.60	24.30
20	1	99		24.22	24.55	24.39
20	50	0		23.19	23.32	23.27
20	50	24		23.03	23.31	23.27
20	50	49		23.21	23.32	23.29
20	100	0		23.10	23.31	23.30
20	1	0	16-QAM	23.45	22.76	23.52
20	1	49		23.26	22.87	23.66
20	1	99		23.26	22.89	23.75
20	50	0		22.44	22.36	22.41
20	50	24		22.32	22.41	22.44
20	50	49		22.42	22.43	22.44
20	100	0		22.33	22.34	22.38

11. EUT and Test Setup Photo

11.1 EUT Photos

Front side




Back side





Right Edge



Left Edge





Top Edge




Bottom Edge



11.2 Setup Photos


Right Touch




Right Tilt



Left Touch




Left Tilt






Body and Limbs Front side (separation distance is 0mm)




Body and Limbs Back side (separation distance is 0mm)






Body and Limbs Left side (separation distance is 0mm)




Body and Limbs Right side (separation distance is 0mm)






Body and Limbs Top side (separation distance is 0mm)




Body and Limbs Bottom side (separation distance is 0mm)





Liquid depth (15 cm)





12. SAR Result Summary

12.1 Head SAR

Band	Model	Test Position	Freq.	SAR (1g) (W/kg)	Power Drift (%)	Max. Turn-up Power (dBm)	Meas. Output Power (dBm)	Scaling Factor	Scaled SAR (W/Kg)	Meas. No.
GSM850	GSM	Right Cheek	848.8	0.480	-3.96	34.00	33.71	1.069	0.513	1
		Right Tilt	848.8	0.385	-0.19	34.00	33.71	1.069	0.412	/
		Left Cheek	848.8	0.417	1.11	34.00	33.71	1.069	0.446	/
		Left Tilt	848.8	0.333	1.38	34.00	33.71	1.069	0.356	/
PCS 1900	GSM	Right Cheek	1850.2	0.843	-1.58	30.00	29.88	1.028	0.867	/
		Right Cheek	1880	0.980	-0.49	30.50	30.38	1.028	1.007	3
		Right Cheek	1909.8	0.917	3.59	30.50	30.27	1.054	0.967	/
		Right Tilt	1850.2	0.701	3.57	30.00	29.88	1.028	0.721	/
		Right Tilt	1880	0.787	3.36	30.50	30.38	1.028	0.809	/
		Right Tilt	1909.8	0.734	2.42	30.50	30.27	1.054	0.774	/
		Left Cheek	1850.2	0.765	-2.19	30.00	29.88	1.028	0.786	/
		Left Cheek	1880	0.844	2.17	30.50	30.38	1.028	0.868	/
		Left Cheek	1909.8	0.796	3.66	30.50	30.27	1.054	0.839	/
		Left Tilt	1880	0.676	-2.48	30.50	30.38	1.028	0.695	/
WCDMA Band II	RMC	Right Cheek	1852.4	0.712	-3.49	23.30	23.06	1.057	0.752	/
		Right Cheek	1880	0.768	0.72	23.50	23.39	1.026	0.788	/
		Right Cheek	1907.6	0.817	3.33	23.70	23.54	1.038	0.848	5
		Right Tilt	1907.6	0.654	3.77	23.70	23.54	1.038	0.679	/
		Left Cheek	1907.6	0.706	-1.24	23.70	23.54	1.038	0.732	/
		Left Tilt	1907.6	0.566	-1.00	23.70	23.54	1.038	0.587	/
WCDMA Band IV	RMC	Right Cheek	1712.6	0.986	-0.71	23.50	23.27	1.054	1.040	7
		Right Cheek	1740	0.867	0.39	23.30	23.15	1.035	0.897	/
		Right Cheek	1752.4	0.923	3.62	23.50	23.21	1.069	0.987	/
		Right Tilt	1712.6	0.787	-1.06	23.50	23.27	1.054	0.830	/
		Right Tilt	1740	0.763	-1.76	23.30	23.15	1.035	0.790	/
		Right Tilt	1752.4	0.802	-1.47	23.50	23.21	1.069	0.857	/
		Left Cheek	1712.6	0.848	-2.63	23.50	23.27	1.054	0.894	/
		Left Cheek	1740	0.785	2.44	23.30	23.15	1.035	0.813	/
		Left Cheek	1752.4	0.803	-0.17	23.50	23.21	1.069	0.858	/
		Left Tilt	1712.6	0.680	-1.34	23.50	23.27	1.054	0.717	/
WCDMA Band V	RMC	Right Cheek	826.4	0.377	2.45	24.30	24.16	1.033	0.389	9
		Right Tilt	826.4	0.303	1.99	24.30	24.16	1.033	0.313	/
		Left Cheek	826.4	0.248	-2.07	24.30	24.16	1.033	0.256	/
		Left Tilt	826.4	0.198	-0.28	24.30	24.16	1.033	0.204	/
2.4G WLAN	802.11b	Right Cheek	2462	0.200	-0.90	16.50	16.40	1.023	0.205	/
		Right Tilt	2462	0.163	1.23	16.50	16.40	1.023	0.167	/
		Left Cheek	2462	0.290	0.50	16.50	16.40	1.023	0.297	11
		Left Tilt	2462	0.236	-0.40	16.50	16.40	1.023	0.241	/
5.2G WLAN	802.11a	Right Cheek	5180	0.329	1.97	14.50	14.36	1.033	0.340	/
		Right Tilt	5180	0.265	-2.27	14.50	14.36	1.033	0.274	/
		Left Cheek	5180	0.378	0.64	14.50	14.36	1.033	0.390	13
		Left Tilt	5180	0.306	-0.37	14.50	14.36	1.033	0.316	/



5.3G WLAN	802.11a	Right Cheek	5260	0.375	1.24	14.50	14.23	1.064	0.399	/
		Right Tilt	5260	0.304	1.15	14.50	14.23	1.064	0.323	/
		Left Cheek	5260	0.436	3.40	14.50	14.23	1.064	0.464	15
		Left Tilt	5260	0.353	1.47	14.50	14.23	1.064	0.376	/
5.6G WLAN	802.11a	Right Cheek	5500	0.501	2.18	14.30	14.06	1.057	0.529	17
		Right Tilt	5500	0.404	-1.93	14.30	14.06	1.057	0.427	/
		Left Cheek	5500	0.480	-1.43	14.30	14.06	1.057	0.507	/
		Left Tilt	5500	0.467	3.54	14.30	14.06	1.057	0.494	/
5.8G WLAN	802.11a	Right Cheek	5745	0.352	4.00	14.50	14.23	1.064	0.375	/
		Right Tilt	5745	0.283	-0.92	14.50	14.23	1.064	0.301	/
		Left Cheek	5745	0.408	-0.46	14.50	14.23	1.064	0.434	19
		Left Tilt	5745	0.325	2.04	14.50	14.23	1.064	0.346	/



Band	BW (MHz)	Mod.	RB Size	RB offset	Test Position	Freq.	Result 1g (W/Kg)	Power Drift (%)	Max. Turn-up Power (dBm)	Meas. Output Power (dBm)	Scaling Factor	Scaled SAR (W/Kg)	Meas. No.
LTE Band 2	20M	QPSK	1	0	Right Cheek	1860	0.711	3.65	24.30	24.13	1.040	0.739	/
			1	0	Right Cheek	1880	0.827	3.76	25.10	24.90	1.047	0.866	21
			1	0	Right Cheek	1900	0.785	-0.13	24.50	24.45	1.012	0.794	/
			50	0	Right Cheek	1880	0.649	0.00	24.00	23.77	1.054	0.684	/
			1	0	Right Tilt	1880	0.662	-1.51	25.10	24.90	1.047	0.693	/
			50	0	Right Tilt	1880	0.518	0.95	24.00	23.77	1.054	0.546	/
			1	0	Left Cheek	1880	0.714	-3.19	25.10	24.90	1.047	0.748	/
			50	0	Left Cheek	1880	0.559	1.09	24.00	23.77	1.054	0.589	/
			1	0	Left Tilt	1880	0.571	-3.18	25.10	24.90	1.047	0.598	/
			50	0	Left Tilt	1880	0.448	0.08	24.00	23.77	1.054	0.472	/
LTE Band 4	20M	QPSK	1	0	Right Cheek	1720	0.819	-3.50	25.20	25.09	1.026	0.840	23
			1	0	Right Cheek	1732.5	0.635	-3.27	23.70	23.59	1.026	0.651	/
			1	0	Right Cheek	1745	0.610	3.40	23.50	23.40	1.023	0.624	/
			50	0	Right Cheek	1745	0.594	-2.06	23.00	22.89	1.026	0.609	/
			1	0	Right Tilt	1720	0.656	3.19	25.20	25.09	1.026	0.673	/
			50	0	Right Tilt	1745	0.476	1.69	23.00	22.89	1.026	0.488	/
			1	0	Left Cheek	1720	0.707	3.70	25.20	25.09	1.026	0.725	/
			50	0	Left Cheek	1745	0.513	2.05	23.00	22.89	1.026	0.526	/
			1	0	Left Tilt	1720	0.564	-0.56	25.20	25.09	1.026	0.578	/
			50	0	Left Tilt	1745	0.406	2.47	23.00	22.89	1.026	0.416	/
LTE Band 5	10M	QPSK	1	0	Right Cheek	844	0.465	-1.36	16.50	16.43	1.016	0.473	25
			25	0	Right Cheek	844	0.403	-2.37	15.50	15.33	1.040	0.419	/
			1	0	Right Tilt	844	0.373	3.45	16.50	16.43	1.016	0.379	/
			25	0	Right Tilt	844	0.325	3.56	15.50	15.33	1.040	0.338	/
			1	0	Left Cheek	844	0.401	3.44	16.50	16.43	1.016	0.408	/
			25	0	Left Cheek	844	0.346	-1.69	15.50	15.33	1.040	0.360	/
			1	0	Left Tilt	844	0.321	2.98	16.50	16.43	1.016	0.326	/
			25	0	Left Tilt	844	0.277	1.69	15.50	15.33	1.040	0.288	/
LTE Band 7	20M	QPSK	1	49	Right Cheek	2510	0.580	0.73	23.70	23.52	1.042	0.605	27
			50	49	Right Cheek	2510	0.501	3.74	22.80	22.61	1.045	0.523	/
			1	49	Right Tilt	2510	0.464	2.32	23.70	23.52	1.042	0.484	/
			50	49	Right Tilt	2510	0.402	-3.30	22.80	22.61	1.045	0.420	/
			1	49	Left Cheek	2510	0.502	0.36	23.70	23.52	1.042	0.523	/
			50	49	Left Cheek	2510	0.433	1.75	22.80	22.61	1.045	0.452	/
			1	49	Left Tilt	2510	0.403	-3.91	23.70	23.52	1.042	0.420	/
			50	49	Left Tilt	2510	0.35	-1.22	22.80	22.61	1.045	0.366	/
LTE Band 12	10M	QPSK	1	0	Right Cheek	704	0.397	-0.05	25.10	24.95	1.035	0.411	29
			25	0	Right Cheek	704	0.345	-3.11	24.10	23.99	1.026	0.354	/
			1	0	Right Tilt	704	0.32	-2.15	25.10	24.95	1.035	0.331	/
			25	0	Right Tilt	704	0.275	-2.22	24.10	23.99	1.026	0.282	/



			1	0	Left Cheek	704	0.345	-2.62	25.10	24.95	1.035	0.357	/
			25	0	Left Cheek	704	0.297	-0.37	24.10	23.99	1.026	0.305	/
			1	0	Left Tilt	704	0.28	-0.07	25.10	24.95	1.035	0.290	/
			25	0	Left Tilt	704	0.243	0.95	24.10	23.99	1.026	0.249	/
LTE Band 13	10M	QPSK	1	49	Right Cheek	782	0.433	-0.92	25.40	25.27	1.030	0.446	31
			25	24	Right Cheek	782	0.356	1.52	24.40	24.29	1.026	0.365	/
			1	49	Right Tilt	782	0.348	-2.87	25.40	25.27	1.030	0.359	/
			25	24	Right Tilt	782	0.286	3.73	24.40	24.29	1.026	0.293	/
			1	49	Left Cheek	782	0.373	3.58	25.40	25.27	1.030	0.384	/
			25	24	Left Cheek	782	0.306	-1.92	24.40	24.29	1.026	0.314	/
			1	49	Left Tilt	782	0.298	-3.87	25.40	25.27	1.030	0.307	/
			25	24	Left Tilt	782	0.245	2.09	24.40	24.29	1.026	0.251	/
LTE Band 17	10M	QPSK	1	0	Right Cheek	710	0.406	0.57	24.70	24.59	1.026	0.416	33
			25	0	Right Cheek	710	0.336	0.90	23.80	23.62	1.042	0.350	/
			1	0	Right Tilt	710	0.325	-2.88	24.70	24.59	1.026	0.333	/
			25	0	Right Tilt	710	0.266	-3.21	23.80	23.62	1.042	0.277	/
			1	0	Left Cheek	710	0.351	1.80	24.70	24.59	1.026	0.360	/
			25	0	Left Cheek	710	0.29	3.11	23.80	23.62	1.042	0.302	/
			1	0	Left Tilt	710	0.282	-0.55	24.70	24.59	1.026	0.289	/
			25	0	Left Tilt	710	0.232	0.40	23.80	23.62	1.042	0.242	/
LTE Band 25	20M	QPSK	1	0	Right Cheek	1882.5	0.592	-1.38	25.50	25.38	1.028	0.609	35
			50	49	Right Cheek	1905	0.488	-0.16	24.30	24.20	1.023	0.499	/
			1	0	Right Tilt	1882.5	0.475	1.24	25.50	25.38	1.028	0.488	/
			50	49	Right Tilt	1905	0.392	3.96	24.30	24.20	1.023	0.401	/
			1	0	Left Cheek	1882.5	0.51	-3.39	25.50	25.38	1.028	0.524	/
			50	49	Left Cheek	1905	0.42	-1.09	24.30	24.20	1.023	0.430	/
			1	0	Left Tilt	1882.5	0.409	-0.97	25.50	25.38	1.028	0.420	/
			50	49	Left Tilt	1905	0.336	3.24	24.30	24.20	1.023	0.344	/
LTE Band 26	15M	QPSK	1	37	Right Cheek	841.5	0.479	-3.89	23.50	23.44	1.014	0.486	37
			36	0	Right Cheek	841.5	0.395	-1.21	22.30	22.14	1.038	0.410	/
			1	37	Right Tilt	841.5	0.384	-1.41	23.50	23.44	1.014	0.389	/
			36	0	Right Tilt	841.5	0.319	1.52	22.30	22.14	1.038	0.331	/
			1	37	Left Cheek	841.5	0.416	2.66	23.50	23.44	1.014	0.422	/
			36	0	Left Cheek	841.5	0.343	0.92	22.30	22.14	1.038	0.356	/
			1	37	Left Tilt	841.5	0.331	2.95	23.50	23.44	1.014	0.336	/
			36	0	Left Tilt	841.5	0.272	-2.18	22.30	22.14	1.038	0.282	/
LTE Band 38	20M	QPSK	1	99	Right Cheek	2595	0.172	-1.58	25.20	24.99	1.050	0.181	39
			50	0	Right Cheek	2610	0.145	1.60	24.00	23.85	1.035	0.150	/
			1	99	Right Tilt	2595	0.14	1.82	25.20	24.99	1.050	0.147	/
			50	0	Right Tilt	2610	0.116	1.09	24.00	23.85	1.035	0.120	/
			1	99	Left Cheek	2595	0.15	0.84	25.20	24.99	1.050	0.157	/
			50	0	Left Cheek	2610	0.126	-2.95	24.00	23.85	1.035	0.130	/
			1	99	Left Tilt	2595	0.121	-1.43	25.20	24.99	1.050	0.127	/



			50	0	Left Tilt	2610	0.099	-2.25	24.00	23.85	1.035	0.102	/
LTE Band 40	10M	QPSK	1	49	Right Cheek	2310	0.221	2.17	15.70	15.57	1.030	0.228	41
			50	24	Right Cheek	2310	0.194	-3.75	14.60	14.46	1.033	0.200	/
			1	49	Right Tilt	2310	0.175	1.03	15.70	15.57	1.030	0.180	/
			50	24	Right Tilt	2310	0.154	-2.00	14.60	14.46	1.033	0.159	/
			1	49	Left Cheek	2310	0.192	1.76	15.70	15.57	1.030	0.198	/
			50	24	Left Cheek	2310	0.167	1.65	14.60	14.46	1.033	0.172	/
			1	49	Left Tilt	2310	0.154	-2.21	15.70	15.57	1.030	0.159	/
			50	24	Left Tilt	2310	0.137	2.83	14.60	14.46	1.033	0.141	/
LTE Band 41	20M	QPSK	1	0	Right Cheek	2680	0.182	-0.83	25.20	25.05	1.035	0.188	43
			50	49	Right Cheek	2506	0.142	1.21	24.00	23.81	1.045	0.148	/
			1	0	Right Tilt	2680	0.146	1.95	25.20	25.05	1.035	0.151	/
			50	49	Right Tilt	2506	0.114	-1.23	24.00	23.81	1.045	0.119	/
			1	0	Left Cheek	2680	0.158	3.66	25.20	25.05	1.035	0.164	/
			50	49	Left Cheek	2506	0.121	3.90	24.00	23.81	1.045	0.126	/
			1	0	Left Tilt	2680	0.129	-1.63	25.20	25.05	1.035	0.134	/
			50	49	Left Tilt	2506	0.101	3.41	24.00	23.81	1.045	0.106	/
LTE Band 66	20M	QPSK	1	49	Right Cheek	1745	0.705	-2.76	24.80	24.60	1.047	0.738	45
			50	0	Right Cheek	1745	0.552	1.67	23.50	23.32	1.042	0.575	/
			1	49	Right Tilt	1745	0.567	-3.11	24.80	24.60	1.047	0.594	/
			50	0	Right Tilt	1745	0.447	3.53	23.50	23.32	1.042	0.466	/
			1	49	Left Cheek	1745	0.606	0.54	24.80	24.60	1.047	0.635	/
			50	0	Left Cheek	1745	0.475	-2.56	23.50	23.32	1.042	0.495	/
			1	49	Left Tilt	1745	0.488	0.02	24.80	24.60	1.047	0.511	/
			50	0	Left Tilt	1745	0.385	1.16	23.50	23.32	1.042	0.401	/



12.2 Body-worn and Hotspot SAR

Band	Model	Test Position	Freq.	SAR (1g) (W/kg)	Power Drift (%)	Max. Turn-up Power (dBm)	Meas. Output Power (dBm)	Scaling Factor	Scaled SAR (W/Kg)	Meas. No.
GSM850	GPRS Data-2 Slot	Front Side	848.8	0.391	-3.23	31.70	31.59	1.026	0.401	/
		Back Side	848.8	0.648	3.12	31.70	31.59	1.026	0.665	2
		Left Side	848.8	0.143	3.79	31.70	31.59	1.026	0.147	/
		Right Side	848.8	0.176	-0.63	31.70	31.59	1.026	0.181	/
		Top Side	848.8	0.049	-1.64	31.70	31.59	1.026	0.050	/
		Bottom Side	848.8	0.054	1.40	31.70	31.59	1.026	0.055	/
PCS 1900	GPRS Data-3 Slot	Front Side	1909.8	0.423	-3.20	27.00	26.88	1.028	0.435	/
		Back Side	1909.8	0.702	3.92	27.00	26.88	1.028	0.722	4
		Left Side	1909.8	0.277	1.29	27.00	26.88	1.028	0.285	/
		Right Side	1909.8	0.150	-1.14	27.00	26.88	1.028	0.154	/
		Top Side	1909.8	0.189	-3.23	27.00	26.88	1.028	0.194	/
		Bottom Side	1909.8	0.060	-2.85	27.00	26.88	1.028	0.062	/
WCDMA Band II	RMC	Front Side	1907.6	0.251	-1.78	23.70	23.54	1.038	0.260	/
		Back Side	1852.4	0.886	0.25	23.30	23.06	1.057	0.936	/
		Back Side	1880	0.927	3.40	23.50	23.39	1.026	0.951	/
		Back Side	1907.6	0.988	-1.78	23.70	23.54	1.038	1.025	6
		Left Side	1907.6	0.386	-0.90	23.70	23.54	1.038	0.400	/
		Top Side	1907.6	0.267	-1.51	23.70	23.54	1.038	0.277	/
WCDMA Band IV	RMC	Front Side	1712.6	0.143	-0.83	23.50	23.27	1.054	0.151	/
		Back Side	1712.6	0.787	0.16	23.50	23.27	1.054	0.830	8
		Back Side	1740	0.710	-2.58	23.30	23.15	1.035	0.735	/
		Back Side	1752.4	0.734	2.47	23.50	23.21	1.069	0.785	/
		Left Side	1712.6	0.310	-0.56	23.50	23.27	1.054	0.327	/
		Top Side	1712.6	0.215	3.81	23.50	23.27	1.054	0.227	/
WCDMA Band V	RMC	Front Side	826.4	0.271	-1.78	24.30	24.16	1.033	0.280	/
		Back Side	826.4	0.363	-1.26	24.30	24.16	1.033	0.375	10
		Left Side	826.4	0.081	-1.26	24.30	24.16	1.033	0.084	/
		Right Side	826.4	0.099	-3.32	24.30	24.16	1.033	0.102	/
		Bottom Side	826.4	0.028	-2.12	24.30	24.16	1.033	0.029	/
2.4GHz WLAN	802.11b	Front Side	2462	0.330	-0.12	16.50	16.40	1.023	0.338	12
		Back Side	2462	0.298	-2.58	16.50	16.40	1.023	0.305	/
		Right Side	2462	0.116	-3.11	16.50	16.40	1.023	0.119	/
		Top Side	2462	0.266	-2.34	16.50	16.40	1.023	0.272	/
5.2GHz WLAN	802.11a	Front Side	5180	0.310	0.43	14.50	14.36	1.033	0.320	/
		Back Side	5180	0.425	3.33	14.50	14.36	1.033	0.439	/
		Right Side	5180	0.167	0.40	14.50	14.36	1.033	0.172	/
		Top Side	5180	0.473	0.39	14.50	14.36	1.033	0.488	14
5.3GHz WLAN	802.11a	Front Side	5260	0.281	-0.43	14.30	14.23	1.016	0.286	/
		Back Side	5260	0.385	-0.29	14.30	14.23	1.016	0.391	/
		Right Side	5260	0.152	2.83	14.30	14.23	1.016	0.154	/
		Top Side	5260	0.426	-0.48	14.30	14.23	1.016	0.433	16
5.6GHz WLAN	802.11a	Front Side	5500	0.263	-2.46	14.50	14.06	1.107	0.291	/
		Back Side	5500	0.363	-0.41	14.50	14.06	1.107	0.402	/
		Right Side	5500	0.139	-3.34	14.50	14.06	1.107	0.154	/
		Top Side	5500	0.400	1.28	14.50	14.06	1.107	0.443	18
5.8GHz WLAN	802.11a	Front Side	5745	0.324	-3.61	14.50	14.23	1.064	0.345	/
		Back Side	5745	0.448	-2.08	14.50	14.23	1.064	0.477	/
		Right Side	5745	0.177	-3.06	14.50	14.23	1.064	0.188	/
		Top Side	5745	0.496	2.20	14.50	14.23	1.064	0.528	20



Band	BW (MHz)	Mod.	RB Size	RB offset	Test Position	Freq.	Result 1g (W/Kg)	Power Drift (%)	Max. Turn-up Power (dBm)	Meas. Output Power (dBm)	Scaling Factor	Scaled SAR (W/Kg)	Meas. No.
LTE Band 2	20M	QPSK	1	0	Front side	1880	0.496	-2.02	25.10	24.90	1.047	0.519	/
			50	0	Front side	1880	0.388	0.65	24.00	23.77	1.054	0.409	/
			1	0	Back Side	1860	0.720	1.84	24.30	24.13	1.040	0.749	/
			1	0	Back Side	1880	0.822	-0.28	25.10	24.90	1.047	0.861	22
			1	0	Back Side	1900	0.768	-2.59	24.50	24.45	1.012	0.777	/
			50	0	Back Side	1880	0.644	-1.50	24.00	23.77	1.054	0.679	/
			1	0	Left Side	1880	0.324	2.79	25.10	24.90	1.047	0.339	/
			50	0	Left Side	1880	0.253	-1.89	24.00	23.77	1.054	0.267	/
			1	0	Right Side	1880	0.175	1.93	25.10	24.90	1.047	0.183	/
			50	0	Right Side	1880	0.138	0.75	24.00	23.77	1.054	0.146	/
			1	0	Top Side	1880	0.223	-3.84	25.10	24.90	1.047	0.234	/
			50	0	Top Side	1880	0.174	1.15	24.00	23.77	1.054	0.183	/
			1	0	Bottom Side	1880	0.066	0.17	25.10	24.90	1.047	0.069	/
			50	0	Bottom Side	1880	0.054	-3.95	24.00	23.77	1.054	0.057	/
LTE Band 4	20M	QPSK	1	0	Front side	1720	0.582	-1.04	25.20	25.09	1.026	0.597	/
			50	0	Front side	1745	0.421	-1.38	23.00	22.89	1.026	0.432	/
			1	0	Back Side	1720	0.968	0.06	25.20	25.09	1.026	0.993	24
			1	0	Back Side	1732.5	0.763	2.66	23.70	23.59	1.026	0.783	/
			1	0	Back Side	1745	0.728	-1.61	23.50	23.40	1.023	0.745	/
			50	0	Back Side	1745	0.700	-3.27	23.00	22.89	1.026	0.718	/
			1	0	Left Side	1720	0.381	-2.17	25.20	25.09	1.026	0.391	/
			50	0	Left Side	1745	0.275	-3.18	23.00	22.89	1.026	0.282	/
			1	0	Right Side	1720	0.204	-3.82	25.20	25.09	1.026	0.209	/
			50	0	Right Side	1745	0.148	1.25	23.00	22.89	1.026	0.152	/
			1	0	Top Side	1720	0.263	-2.77	25.20	25.09	1.026	0.270	/
			50	0	Top Side	1745	0.191	0.18	23.00	22.89	1.026	0.196	/
			1	0	Bottom Side	1720	0.079	1.32	25.20	25.09	1.026	0.081	/
			50	0	Bottom Side	1745	0.057	-0.60	23.00	22.89	1.026	0.058	/
LTE Band 5	10M	QPSK	1	0	Front side	844	0.502	-1.75	16.50	16.43	1.016	0.510	/
			25	0	Front side	844	0.435	3.80	15.50	15.33	1.040	0.452	/
			1	0	Back Side	829	0.718	-0.15	15.30	15.20	1.023	0.735	/



			1	0	Back Side	836.5	0.752	3.37	15.50	15.43	1.016	0.764	/
			1	0	Back Side	844	0.830	-3.46	16.50	16.43	1.016	0.843	26
			25	0	Back Side	844	0.716	3.39	15.50	15.33	1.040	0.745	/
			1	0	Left Side	844	0.186	-0.88	16.50	16.43	1.016	0.189	/
			25	0	Left Side	844	0.164	3.68	15.50	15.33	1.040	0.171	/
			1	0	Right Side	844	0.225	2.27	16.50	16.43	1.016	0.229	/
			25	0	Right Side	844	0.193	-3.33	15.50	15.33	1.040	0.201	/
			1	0	Bottom Side	844	0.066	-2.67	16.50	16.43	1.016	0.067	/
			25	0	Bottom Side	844	0.061	-3.20	15.50	15.33	1.040	0.063	/
LTE Band 7	20M	QPSK	1	49	Front side	2510	0.410	-0.70	23.70	23.52	1.042	0.427	/
			50	49	Front side	2510	0.353	-0.19	22.80	22.61	1.045	0.369	/
			1	49	Back Side	2510	0.677	-0.03	23.70	23.52	1.042	0.706	28
			50	49	Back Side	2510	0.583	1.41	22.80	22.61	1.045	0.609	/
			1	49	Left Side	2510	0.264	-3.63	23.70	23.52	1.042	0.275	/
			50	49	Left Side	2510	0.228	-0.40	22.80	22.61	1.045	0.238	/
			1	49	Top Side	2510	0.184	1.56	23.70	23.52	1.042	0.192	/
			50	49	Top Side	2510	0.161	2.34	22.80	22.61	1.045	0.168	/
LTE Band 12	10M	QPSK	1	0	Front side	704	0.447	-1.83	25.10	24.95	1.035	0.463	/
			25	0	Front side	704	0.386	-0.32	24.10	23.99	1.026	0.396	/
			1	0	Back Side	704	0.741	1.81	25.10	24.95	1.035	0.767	30
			25	0	Back Side	704	0.639	3.50	24.10	23.99	1.026	0.655	/
			1	0	Left Side	704	0.164	-3.07	25.10	24.95	1.035	0.170	/
			25	0	Left Side	704	0.143	0.13	24.10	23.99	1.026	0.147	/
			1	0	Right Side	704	0.199	-3.46	25.10	24.95	1.035	0.206	/
			25	0	Right Side	704	0.173	1.87	24.10	23.99	1.026	0.177	/
			1	0	Top Side	704	0.056	-2.55	25.10	24.95	1.035	0.058	/
			25	0	Top Side	704	0.048	3.36	24.10	23.99	1.026	0.049	/
			1	0	Bottom Side	704	0.061	-3.05	25.10	24.95	1.035	0.063	/
			25	0	Bottom Side	704	0.057	-2.40	24.10	23.99	1.026	0.058	/
LTE Band 13	10M	QPSK	1	49	Front side	782	0.317	2.02	25.40	25.27	1.030	0.327	/
			25	24	Front side	782	0.260	-0.90	24.40	24.29	1.026	0.267	/
			1	49	Back Side	782	0.526	-3.06	25.40	25.27	1.030	0.542	32
			25	24	Back Side	782	0.432	-1.12	24.40	24.29	1.026	0.443	/



			1	49	Left Side	782	0.117	-3.93	25.40	25.27	1.030	0.121	/
			25	24	Left Side	782	0.096	-2.68	24.40	24.29	1.026	0.098	/
			1	49	Right Side	782	0.144	-0.41	25.40	25.27	1.030	0.148	/
			25	24	Right Side	782	0.120	-0.01	24.40	24.29	1.026	0.123	/
			1	49	Top Side	782	0.038	3.62	25.40	25.27	1.030	0.039	/
			25	24	Top Side	782	0.031	3.64	24.40	24.29	1.026	0.032	/
			1	49	Bottom Side	782	0.042	-0.78	25.40	25.27	1.030	0.043	/
			25	24	Bottom Side	782	0.038	-0.50	24.40	24.29	1.026	0.039	/
LTE Band 17	10M	QPSK	1	0	Front side	710	0.461	-1.88	24.70	24.59	1.026	0.473	/
			25	0	Front side	710	0.382	-1.04	23.80	23.62	1.042	0.398	/
			1	0	Back Side	710	0.762	-1.01	24.70	24.59	1.026	0.782	34
			25	0	Back Side	710	0.629	1.26	23.80	23.62	1.042	0.656	/
			1	0	Left Side	710	0.169	-1.82	24.70	24.59	1.026	0.173	/
			25	0	Left Side	710	0.141	1.07	23.80	23.62	1.042	0.147	/
			1	0	Right Side	710	0.205	2.23	24.70	24.59	1.026	0.210	/
			25	0	Right Side	710	0.168	-0.75	23.80	23.62	1.042	0.175	/
			1	0	Bottom Side	710	0.062	1.02	24.70	24.59	1.026	0.064	/
			25	0	Bottom Side	710	0.050	0.76	23.80	23.62	1.042	0.052	/
LTE Band 25	20M	QPSK	1	0	Front side	1882.5	0.582	0.07	25.50	25.38	1.028	0.598	/
			50	49	Front side	1905	0.478	0.69	24.30	24.20	1.023	0.489	/
			1	0	Back Side	1860	0.813	3.50	24.70	24.58	1.028	0.836	/
			1	0	Back Side	1882.5	0.971	2.22	25.50	25.38	1.028	0.998	36
			1	0	Back Side	1905	0.869	2.91	25.00	24.92	1.019	0.885	/
			50	49	Back Side	1860	0.712	1.43	24.00	23.92	1.019	0.725	/
			50	49	Back Side	1882.5	0.753	-2.12	24.10	24.02	1.019	0.767	/
			50	49	Back Side	1905	0.797	-1.05	24.30	24.20	1.023	0.816	/
			1	0	Left Side	1882.5	0.379	3.31	25.50	25.38	1.028	0.390	/
			50	49	Left Side	1905	0.312	-3.18	24.30	24.20	1.023	0.319	/
			1	0	Right Side	1882.5	0.206	-1.83	25.50	25.38	1.028	0.212	/
			50	49	Right Side	1905	0.172	0.90	24.30	24.20	1.023	0.176	/
			1	0	Top Side	1882.5	0.265	2.22	25.50	25.38	1.028	0.272	/
			50	49	Top Side	1905	0.221	-2.38	24.30	24.20	1.023	0.226	/
			1	0	Bottom Side	1882.5	0.081	-0.40	25.50	25.38	1.028	0.083	/



			50	49	Bottom Side	1905	0.068	-2.13	24.30	24.20	1.023	0.070	/
LTE Band 26	15M	QPSK	1	37	Front side	841.5	0.209	-0.55	23.50	23.44	1.014	0.212	/
			36	0	Front side	841.5	0.173	1.03	22.30	22.14	1.038	0.179	/
			1	37	Back Side	841.5	0.347	-1.70	23.50	23.44	1.014	0.352	38
			36	0	Back Side	841.5	0.287	-0.03	22.30	22.14	1.038	0.298	/
			1	37	Left Side	841.5	0.077	-3.31	23.50	23.44	1.014	0.078	/
			36	0	Left Side	841.5	0.064	-2.58	22.30	22.14	1.038	0.066	/
			1	37	Right Side	841.5	0.098	0.01	23.50	23.44	1.014	0.099	/
			36	0	Right Side	841.5	0.083	-3.28	22.30	22.14	1.038	0.086	/
			1	37	Bottom Side	841.5	0.027	-3.88	23.50	23.44	1.014	0.027	/
			36	0	Bottom Side	841.5	0.025	-2.73	22.30	22.14	1.038	0.026	/
LTE Band 38	20M	QPSK	1	99	Front side	2595	0.349	-1.40	25.20	24.99	1.050	0.366	/
			50	0	Front side	2610	0.288	3.90	24.00	23.85	1.035	0.298	/
			1	99	Back Side	2595	0.579	3.93	25.20	24.99	1.050	0.608	40
			50	0	Back Side	2610	0.477	1.26	24.00	23.85	1.035	0.494	/
			1	99	Left Side	2595	0.229	0.94	25.20	24.99	1.050	0.240	/
			50	0	Left Side	2610	0.190	-1.75	24.00	23.85	1.035	0.197	/
			1	99	Right Side	2595	0.121	3.01	25.20	24.99	1.050	0.127	/
			50	0	Right Side	2610	0.101	-1.00	24.00	23.85	1.035	0.105	/
			1	99	Top Side	2595	0.158	-3.55	25.20	24.99	1.050	0.166	/
			50	0	Top Side	2610	0.133	0.48	24.00	23.85	1.035	0.138	/
			1	99	Bottom Side	2595	0.046	0.44	25.20	24.99	1.050	0.048	/
			50	0	Bottom Side	2610	0.041	-1.37	24.00	23.85	1.035	0.042	/
LTE Band 40	10M	QPSK	1	49	Front side	2310	0.216	0.87	15.70	15.57	1.030	0.223	/
			50	24	Front side	2310	0.186	2.24	14.60	14.46	1.033	0.192	/
			1	49	Back Side	2310	0.360	-3.55	15.70	15.57	1.030	0.371	42
			50	24	Back Side	2310	0.314	1.13	14.60	14.46	1.033	0.324	/
			1	49	Left Side	2310	0.140	-1.02	15.70	15.57	1.030	0.144	/
			50	24	Left Side	2310	0.122	-2.57	14.60	14.46	1.033	0.126	/
			1	49	Top Side	2310	0.097	-0.32	15.70	15.57	1.030	0.100	/
			50	24	Top Side	2310	0.086	-3.40	14.60	14.46	1.033	0.089	/
LTE Band 41	20M	QPSK	1	0	Front side	2680	0.416	3.90	25.20	25.05	1.035	0.431	/
			50	49	Front side	2506	0.316	-3.63	24.00	23.81	1.045	0.330	/