

Project No.: TM-2509000187P
Report No.: TMWK2509003910KS FCC ID: 2AU3U-NXB4

Page 1 / 20
Rev.: 00

RF Exposure Evaluation Report

FCC 47 CFR § 2.1091

for
beam4K

Model Name.: NXBM4-1.0

Prepared for:

NEXAR LTD
58 Harakevet St., 22nd floor, Tel Aviv 6777016, ISRAEL

Prepared by

Compliance Certification Services Inc.
Wugu Laboratory
No.11, Wugong 6th Rd., Wugu Dist.,
New Taipei City, Taiwan.
Issue Date: June 26, 2026

Note: This document may be altered or revised by Compliance Certification Services Inc. personnel only, and shall be noted in the revision section of the document. The client should not use it to claim product endorsement by TAF, NIST or any government agencies. The test results in the report only apply to the tested sample.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com.tw/Terms-and-Conditions> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com.tw/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of client's instruction, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced, except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.



Project No.: TM-2509000187P
Report No.: TMWK2509003910KS

Page 2 / 20
Rev.: 00

Revision History

Rev.	Issue Date	Revisions	Effect Page	Revised By
00	June 26, 2026	Initial Issue	ALL	Peggy Tsai

Table of Contents

1	ATTESTATION OF TEST RESULTS	4
2	TEST SPECIFICATION, METHODS AND PROCEDURES	5
3	DEVICE UNDER TEST (DUT) INFORMATION	6
3.1	DUT DESCRIPTION	6
3.2	WIRELESS TECHNOLOGIES	7
4	MEASUREMENT UNCERTAINTY.....	12
5	MAXIMUM PERMISSIBLE EXPOSURE.....	13
5.1	LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)	13
5.2	MPE CALCULATION METHOD.....	14
5.3	MPE EXEMPTION	15
5.4	MULTIPLE RF SOURCES	16
6	MPE EXEMPTION OPTION B	17
7	SIMULTANEOUS TRANSMISSION ANALYSIS	19
7.1	SUM OF THE WWAN + BLUETOOTH	19
7.2	SUM OF THE WWAN + WIFI 2.4GHZ	19
7.3	SUM OF THE WWAN + WIFI 5GHZ + BLUETOOTH.....	19
8	FACILITIES	20

Project No.: TM-2509000187P
Report No.: TMWK2509003910KS

Page 4 / 20
Rev.: 00

1 Attestation of Test Results

Applicant Name	NEXAR LTD
Model Name	NXBM4-1.0
Applicable Standards	FCC 47 CFR § 2.1091 FCC 47 CFR § 1.1310 Published RF exposure KDB procedures
Receive EUT Date:	September 22, 2025
Date of Test:	March 9, 2026
Compliance Certification Services Inc. , tested the above equipment in accordance with the requirements set forth in the above standards. Determination of compliance is based on the results of the compliance measurement,not taking into account measurement instrumentation uncertainty.All indications of Pass/Fail in this report are opinions expressed by Compliance Certification Services Inc, based on interpretations and/or observations of test results. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.	
Approved & Released By: 	Tested by: 
Sky Zhou Asst. Section Manager Compliance Certification Services Inc.	KW Huang Engineer Compliance Certification Services Inc.



Project No.: TM-2509000187P
Report No.: TMWK2509003910KS

Page 5 / 20
Rev.: 00

2 Test Specification, Methods and Procedures

The tests documented in this report were performed in accordance with FCC 47 CFR § 2.1091, the following FCC Published RF exposure [KDB](#) procedures:

- 447498 D04 Interim General RF Exposure Guidance v01
- 865664 D02 RF Exposure Reporting v01r02



Project No.: TM-2509000187P
Report No.: TMWK2509003910KS

Page 6 / 20
Rev.: 00

3 Device Under Test (DUT) Information

3.1 DUT Description

Product	beam4K
Trade Name	nexar
Model No.	NXBM4-1.0
Model Discrepancy	N/A
Hardware Version	Main board 001AH2225L-E01
Software Version	SOC_ver : 0253
Sample Stage	Identical prototype

3.2 Wireless Technologies

Frequency bands	☒ Bluetooth: 2402MHz-2480MHz ☒ 802.11b/g/n HT20: 2412MHz ~ 2462 MHz ☐ 802.11n HT40: 2422MHz ~ 2452 MHz ☒ 802.11a/n HT20: 5180MHz ~ 5240MHz / 5260 ~ 5320MHz / 5500 ~ 5700MHz / 5745MHz ~ 5825MHz ☒ 802.11n HT40: 5190 MHz ~ 5230 MHz / 5270 MHz ~ 5310 MHz / 5510 MHz ~ 5670 MHz / 5755 MHz ~ 5795MHz ☒ 802.11ac VHT20: 5180MHz ~ 5240MHz / 5260 ~ 5320MHz / 5500 ~ 5700MHz / 5745MHz ~ 5825MHz ☒ 802.11ac VHT40: 5190 MHz ~ 5230 MHz / 5270 MHz ~ 5310 MHz / 5510 MHz ~ 5670 MHz / 5755 MHz ~ 5795MHz ☒ 802.11ac VHT80: 5210 MHz / 5290 MHz / 5530 MHz / 5775 MHz ☐ 802.11ax HE20: 5180MHz ~ 5240MHz / 5260 ~ 5320MHz / 5500 ~ 5700MHz / 5745MHz ~ 5825MHz ☐ 802.11ax HE40: 5190 MHz ~ 5230 MHz / 5270 MHz ~ 5310 MHz / 5510 MHz ~ 5670 MHz / 5755 MHz ~ 5795MHz ☐ 802.11ax HE80: 5210 MHz / 5290 MHz / 5530 MHz / 5775 MHz ☒ WCDMA Band II: 1850 ~ 1910 MHz ☒ WCDMA Band IV: 1710 ~ 1755 MHz ☒ WCDMA Band V: 824 ~ 849 MHz ☒ LTE Band 2: 1850 ~ 1910 MHz ☒ LTE Band 4: 1710 ~ 1755 MHz ☒ LTE Band 5: 824 ~ 849 MHz ☒ LTE Band 7: 2500 ~ 2570 MHz ☒ LTE Band 12: 699 ~ 716 MHz ☒ LTE Band 13: 777 ~ 787 MHz ☒ LTE Band 25: 1850 ~ 1915 MHz ☒ LTE Band 26: 814 ~ 849 MHz ☒ LTE Band 38: 2570 ~ 2620 MHz ☒ LTE Band 41: 2496 ~ 2690 MHz ☒ LTE Band 66: 1710 ~ 1780 MHz ☐ Others:
Exposure classification	☐ Occupational/Controlled exposure ☒ General Population/Uncontrolled exposure



Antenna Specification	Type: PIFA Antenna BLE & WIFI 2.4GHz: Gain: 2.81 dBi WIFI 5GHz: Band 1: Gain: 1.72 dBi Band 2: Gain: 2.13 dBi Band 3: Gain: 1.39 dBi Band 4: Gain: -0.13 dBi WWAN Band II: Gain: -0.24 dBi Band IV: Gain: 0.20 dBi Band V: Gain: -1.13 dBi LTE: Band 2: Gain: -0.24 dBi Band 4: Gain: 0.20 dBi Band 5: Gain: -1.13 dBi Band 7: Gain: -1.10 dBi Band 12: Gain: -1.29 dBi Band 13: Gain: -1.19 dBi Band 25: Gain: -0.24 dBi Band 26: Gain: -1.13 dBi Band 38: Gain: 2.27 dBi Band 41: Gain: 2.83 dBi Band 66: Gain: 0.20 dBi
---	--

Antenna Specification	BLE	Gain :	2.81 dBi	(Numeric gain: 1.91)	Worst
	2.4GHz:	Gain :	2.81 dBi	(Numeric gain: 1.91)	Worst
	5GHz:				
	Band 1	Gain :	1.72 dBi	(Numeric gain: 1.49)	Worst
	Band 2	Gain :	2.13 dBi	(Numeric gain: 1.63)	Worst
	Band 3	Gain :	1.39 dBi	(Numeric gain: 1.38)	Worst
	Band 4	Gain :	-0.13 dBi	(Numeric gain: 0.97)	Worst
	WWAN:				
	Band II	Gain :	0.49 dBi	(Numeric gain: 1.12)	Worst
	Band IV	Gain :	-0.26 dBi	(Numeric gain: 0.94)	Worst
	Band V	Gain :	-1.44 dBi	(Numeric gain: 0.72)	Worst
	LTE				
	Band 2	Gain :	-0.24 dBi	(Numeric gain: 0.95)	Worst
	Band 4	Gain :	0.20 dBi	(Numeric gain: 1.05)	Worst
	Band 5	Gain :	-1.13 dBi	(Numeric gain: 0.77)	Worst
	Band 7	Gain :	-1.10 dBi	(Numeric gain: 0.78)	Worst
	Band 12	Gain :	-1.29 dBi	(Numeric gain: 0.74)	Worst
	Band 13	Gain :	-1.19 dBi	(Numeric gain: 0.76)	Worst
	Band 25	Gain :	-0.24 dBi	(Numeric gain: 0.95)	Worst
	Band 26	Gain :	-1.13 dBi	(Numeric gain: 0.77)	Worst
	Band 38	Gain :	2.27 dBi	(Numeric gain: 1.69)	Worst
	Band 41	Gain :	2.83 dBi	(Numeric gain: 1.92)	Worst
	Band 66	Gain :	0.20 dBi	(Numeric gain: 1.05)	Worst

**Maximum
tune up
power**

BLE	6.50 dBm	(4.467 mW)
WIFI 2.4GHz		
IEEE 802.11b Mode:	18.00 dBm	(63.096 mW)
IEEE 802.11g Mode:	19.00 dBm	(79.433 mW)
IEEE 802.11n HT 20 Mode:	19.00 dBm	(79.433 mW)
WIFI 5GHz (Band 1)		
IEEE 802.11a Mode:	18.00 dBm	(63.096 mW)
IEEE 802.11n HT 20 Mode:	18.00 dBm	(63.096 mW)
IEEE 802.11n HT 40 Mode:	18.00 dBm	(63.096 mW)
IEEE 802.11ac VHT 20 Mode:	18.00 dBm	(63.096 mW)
IEEE 802.11ac VHT 40 Mode:	18.00 dBm	(63.096 mW)
IEEE 802.11ac VHT 80 Mode:	12.50 dBm	(17.783 mW)
WIFI 5GHz (Band 2)		
IEEE 802.11a Mode:	17.50 dBm	(56.234 mW)
IEEE 802.11n HT 20 Mode:	18.00 dBm	(63.096 mW)
IEEE 802.11n HT 40 Mode:	18.00 dBm	(63.096 mW)
IEEE 802.11ac VHT 20 Mode:	18.00 dBm	(63.096 mW)
IEEE 802.11ac VHT 40 Mode:	18.00 dBm	(63.096 mW)
IEEE 802.11ac VHT 80 Mode:	12.50 dBm	(17.783 mW)
WIFI 5GHz (Band 3)		
IEEE 802.11a Mode:	17.50 dBm	(56.234 mW)
IEEE 802.11n HT 20 Mode:	18.00 dBm	(63.096 mW)
IEEE 802.11n HT 40 Mode:	17.50 dBm	(56.234 mW)
IEEE 802.11ac VHT 20 Mode:	18.00 dBm	(63.096 mW)
IEEE 802.11ac VHT 40 Mode:	17.50 dBm	(56.234 mW)
IEEE 802.11ac VHT 80 Mode:	18.50 dBm	(70.795 mW)
WIFI 5GHz (Band 4)		
IEEE 802.11a Mode:	18.00 dBm	(63.096 mW)
IEEE 802.11n HT 20 Mode:	18.00 dBm	(63.096 mW)
IEEE 802.11n HT 40 Mode:	18.50 dBm	(70.795 mW)
IEEE 802.11ac VHT 20 Mode:	18.00 dBm	(63.096 mW)
IEEE 802.11ac VHT 40 Mode:	18.50 dBm	(70.795 mW)
IEEE 802.11ac VHT 80 Mode:	18.50 dBm	(70.795 mW)

Maximum tune up power	WWAN		
	WCDMA Band II	25.00 dBm	(316.228 mW)
	WCDMA Band IV	25.00 dBm	(316.228 mW)
	WCDMA Band V	25.00 dBm	(316.228 mW)
	LTE		
	LTE Band 2	25.00 dBm	(316.228 mW)
	LTE Band 4	25.00 dBm	(316.228 mW)
	LTE Band 5	25.00 dBm	(316.228 mW)
	LTE Band 7	25.00 dBm	(316.228 mW)
	LTE Band 12	25.00 dBm	(316.228 mW)
	LTE Band 13	25.00 dBm	(316.228 mW)
	LTE Band 25	25.00 dBm	(316.228 mW)
	LTE Band 26	25.00 dBm	(316.228 mW)
	LTE Band 38	25.00 dBm	(316.228 mW)
	LTE Band 41	25.00 dBm	(316.228 mW)
	LTE Band 66	25.00 dBm	(316.228 mW)

Notes:

1. For more details, please refer to the User's manual of the EUT.
2. Disclaimer: Antenna information is provided by the applicant, test results of this report are applicable to the sample EUT received.
3. The tune up power referred the AVG power of the test report TMWK2509003904KR, TMWK2509003905KR and TMWK2509003906KR for RF Exposure assessment purpose.



Project No.: TM-2509000187P
Report No.: TMWK2509003910KS

Page 12 / 20
Rev.: 00

4 Measurement Uncertainty

BLE & WIFI 2.4G

PARAMETER	UNCERTAINTY
AC Powerline Conducted Emission	± 2.37dB
Channel Bandwidth	± 2.85dB
RF output power (Spectrum)	± 2.74dB
RF output power (Power Meter + Power sensor)	± 0.27dB
Power Spectral density	± 2.74dB
Conducted Bandedge	± 2.74dB
Conducted Spurious Emission	± 2.74dB
Radiated Emission_9kHz-30MHz	± 2.750 dB
Radiated Emission_30MHz-200MHz	± 3.874 dB
Radiated Emission_200MHz-1GHz	± 4.065 dB
Radiated Emission_1GHz-6GHz	± 5.594 dB
Radiated Emission_6GHz-18GHz	± 5.556 dB
Radiated Emission_18GHz-26GHz	± 3.165 dB
Radiated Emission_26GHz-40GHz	± 3.216 dB

WIFI 5G

PARAMETER	UNCERTAINTY
AC Powerline Conducted Emission	± 2.37dB
Channel Bandwidth	± 2.85dB
RF output power (Spectrum)	± 2.74dB
RF output power (Power Meter + Power sensor)	± 0.27dB
Power Spectral density	± 2.74dB
Radiated Emission_9kHz-30MHz	± 2.750 dB
Radiated Emission_30MHz-200MHz	± 3.874 dB
Radiated Emission_200MHz-1GHz	± 4.065 dB
Radiated Emission_1GHz-6GHz	± 5.594 dB
Radiated Emission_6GHz-18GHz	± 5.556 dB
Radiated Emission_18GHz-26GHz	± 3.165 dB
Radiated Emission_26GHz-40GHz	± 3.216 dB

5 Maximum Permissible Exposure

5.1 Limits for Maximum Permissible Exposure (MPE)

Table 1 - Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposure				
0.3-3.0	614	1.63	* 100	6
3.0-30	1842/f	4.89/f	* 900/f ²	6
30-300	61.4	0.163	1.0	6
300-1,500			f/300	6
1,500-100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	* 100	30
1.34-30	824/f	2.19/f	* 180/f ²	30
30-300	27.5	0.073	0.2	30
300-1,500			f/1500	30
<u>1,500-100,000</u>			1.0	30

5.2 MPE Calculation Method

Calculation

Given $E = \frac{\sqrt{30 \times P \times G}}{d}$ & $S = \frac{E^2}{377}$

Where E = Field strength in Volts / meter

P = Power in Watts

G = Numeric antenna gain

d = Distance in meters

S = Power density in milliwatts / square centimeter

Combining equations and re-arranging the terms to express the distance as a function of the remaining variables yields:

$$S = \frac{30 \times P \times G}{377 d^2}$$

Changing to units of mW and cm, using:

$$P \text{ (mW)} = P \text{ (W)} / 1000 \text{ and}$$

$$d \text{ (cm)} = d \text{ (m)} / 100$$

Yields

$$S = \frac{30 \times (P/1000) \times G}{377 \times (d/100)^2} = 0.0796 \times \frac{P \times G}{d^2} \text{ Equation 1}$$

Where d = Distance in cm

P = Power in mW

G = Numeric antenna gain

S = Power density in mW / cm²

If, Substituting the MPE safe distance using d = 20 cm into Equation 1:

$$S = 0.000199 \times P \times G$$

5.3 MPE EXEMPTION

- (A) The available maximum time-averaged power is no more than 1 mW
- (B) The available maximum time-averaged power or effective radiated power (ERP), whichever is greater, is less than or equal to the threshold P_{th} (mW) described in the following formula. This method shall only be used at separation distances (cm) from 0.5 centimeters to 40 centimeters and at frequencies from 0.3 GHz to 6 GHz (inclusive). P_{th} is given by:

$$P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}} (d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases}$$

Where

$$x = -\log_{10} \left(\frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right) \text{ and } f \text{ is in GHz;}$$

and

$$ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases}$$

d = the separation distance (cm);

- (C) Using Table 1 and the minimum separation distance (R in meters) from the body of a nearby person for the frequency (f in MHz) at which the source operates, the ERP (watts) is no more than the calculated value prescribed for that frequency. For the exemption in Table 1 to apply, R must be at least $\lambda/2\pi$, where λ is the free-space operating wavelength in meters. If the ERP of a single RF source is not easily obtained, then the available maximum time-averaged power may be used in lieu of ERP if the physical dimensions of the radiating structure(s) do not exceed the electrical length of $\lambda/4$ or if the antenna gain is less than that of a half-wave dipole (1.64 linear value).

Single RF Sources Subject to Routine Environmental Evaluation	
RF Source frequency (MHz)	Threshold ERP (watts)
0.3-1.34	$1,920 R^2$.
1.34-30	$3,450 R^2/f^2$.
30-300	$3.83 R^2$.
300-1,500	$0.0128 R^2 f$.
1,500-100,000	$19.2 R^2$.
Note: R is in meters, f is in MHz.	

5.4 Multiple RF sources

In the case of fixed RF sources operating in the same time-averaging period, or of multiple mobile or portable RF sources within a device operating in the same time averaging period, if the sum of the fractional contributions to the applicable thresholds is less than or equal to 1 as indicated in the following equation),

$$\sum_{i=1}^a \frac{P_i}{P_{th,i}} + \sum_{j=1}^b \frac{ERP_j}{ERP_{th,j}} + \sum_{k=1}^c \frac{Evaluated_k}{Exposure Limit_k} \leq 1$$



Project No.: TM-2509000187P
Report No.: TMWK2509003910KS

Page 17 / 20
Rev.: 00

6 MPE Exemption Option B

Bluetooth

Mode	Frequency (MHz)	R(m)	Max Tune-up power (dBm)	G(dBi)	Max Tune-up EIRP (dBm)	Max Tune-up ERP (dBm)	Max Tune-up ERP (mW)	ERP Threshold (mW)	MPE Exemption
BLE	2402	0.2	6.5	2.81	9.31	7.16	5.200	3060	Complies

WIFI 2.4GHz (DTS)

Mode	Frequency (MHz)	R(m)	Max Tune-up power (dBm)	G(dBi)	Max Tune-up EIRP (dBm)	Max Tune-up ERP (dBm)	Max Tune-up ERP (mW)	ERP Threshold (mW)	MPE Exemption
IEEE 802.11b	2412	0.2	18.0	2.81	20.81	18.66	73.451	3060	Complies
IEEE 802.11g	2437	0.2	19.0	2.81	21.81	19.66	92.470	3060	Complies
IEEE 802.11n HT 20	2437	0.2	19.0	2.81	21.81	19.66	92.470	3060	Complies

WIFI 5.2GHz (U-NII 1)

Mode	Frequency (MHz)	R(m)	Max Tune-up power (dBm)	G(dBi)	Max Tune-up EIRP (dBm)	Max Tune-up ERP (dBm)	Max Tune-up ERP (mW)	ERP Threshold (mW)	MPE Exemption
IEEE 802.11a	5220	0.2	18.0	1.72	19.72	17.57	57.148	3060	Complies
IEEE 802.11n HT 20	5220	0.2	18.0	1.72	19.72	17.57	57.148	3060	Complies
IEEE 802.11n HT 40	5230	0.2	18.0	1.72	19.72	17.57	57.148	3060	Complies
IEEE 802.11ac VHT 20	5220	0.2	18.0	1.72	19.72	17.57	57.148	3060	Complies
IEEE 802.11ac VHT 40	5230	0.2	18.0	1.72	19.72	17.57	57.148	3060	Complies
IEEE 802.11ac VHT 80	5210	0.2	12.5	1.72	14.22	12.07	16.106	3060	Complies

WIFI 5.3GHz (U-NII 2A)

Mode	Frequency (MHz)	R(m)	Max Tune-up power (dBm)	G(dBi)	Max Tune-up EIRP (dBm)	Max Tune-up ERP (dBm)	Max Tune-up ERP (mW)	ERP Threshold (mW)	MPE Exemption
IEEE 802.11a	5260	0.2	17.5	2.13	19.63	17.48	55.976	3060	Complies
IEEE 802.11n HT 20	5260	0.2	18.0	2.13	20.13	17.98	62.806	3060	Complies
IEEE 802.11n HT 40	5270	0.2	18.0	2.13	20.13	17.98	62.806	3060	Complies
IEEE 802.11ac VHT 20	5260	0.2	18.0	2.13	20.13	17.98	62.806	3060	Complies
IEEE 802.11ac VHT 40	5270	0.2	18.0	2.13	20.13	17.98	62.806	3060	Complies
IEEE 802.11ac VHT 80	5290	0.2	12.5	2.13	14.63	12.48	17.701	3060	Complies

WIFI 5.5GHz (U-NII 2C)

Mode	Frequency (MHz)	R(m)	Max Tune-up power (dBm)	G(dBi)	Max Tune-up EIRP (dBm)	Max Tune-up ERP (dBm)	Max Tune-up ERP (mW)	ERP Threshold (mW)	MPE Exemption
IEEE 802.11a	5500	0.2	17.5	1.39	18.89	16.74	47.206	3060	Complies
IEEE 802.11n HT 20	5600	0.2	18.0	1.39	19.39	17.24	52.966	3060	Complies
IEEE 802.11n HT 40	5510	0.2	17.5	1.39	18.89	16.74	47.206	3060	Complies
IEEE 802.11ac VHT 20	5600	0.2	18.0	1.39	19.39	17.24	52.966	3060	Complies
IEEE 802.11ac VHT 40	5510	0.2	17.5	1.39	18.89	16.74	47.206	3060	Complies
IEEE 802.11ac VHT 80	5610	0.2	18.5	1.39	19.89	17.74	59.429	3060	Complies

WIFI 5.8GHz (U-NII 3)

Mode	Frequency (MHz)	R(m)	Max Tune-up power (dBm)	G(dBi)	Max Tune-up EIRP (dBm)	Max Tune-up ERP (dBm)	Max Tune-up ERP (mW)	ERP Threshold (mW)	MPE Exemption
IEEE 802.11a	5745	0.2	18.0	-0.13	17.87	15.72	37.325	3060	Complies
IEEE 802.11n HT 20	5745	0.2	18.0	-0.13	17.87	15.72	37.325	3060	Complies
IEEE 802.11n HT 40	5755	0.2	18.5	-0.13	18.37	16.22	41.879	3060	Complies
IEEE 802.11ac VHT 20	5745	0.2	18.0	-0.13	17.87	15.72	37.325	3060	Complies
IEEE 802.11ac VHT 40	5755	0.2	18.5	-0.13	18.37	16.22	41.879	3060	Complies
IEEE 802.11ac VHT 80	5775	0.2	18.5	-0.13	18.37	16.22	41.879	3060	Complies



Project No.: TM-2509000187P
Report No.: TMWK2509003910KS

Page 18 / 20
Rev.: 00

WWAN

Mode	Frequency (MHz)	R(m)	Max Tune-up power (dBm)	G(dBi)	Max Tune-up EIRP (dBm)	Max Tune-up ERP (dBm)	Max Tune-up ERP (mW)	ERP Threshold (mW)	MPE Exemption
WCDMA Band II	1850	0.2	25.0	-0.24	24.76	22.61	182.390	3060	Complies
WCDMA Band IV	1710	0.2	25.0	0.20	25.20	23.05	201.837	3060	Complies
WCDMA Band V	824	0.2	25.0	-1.13	23.87	21.72	148.594	1661	Complies
LTE Band 2	1850	0.2	25.0	-0.24	24.76	22.61	182.390	3060	Complies
LTE Band 4	1710	0.2	25.0	0.20	25.20	23.05	201.837	3060	Complies
LTE Band 5	824	0.2	25.0	-1.13	23.87	21.72	148.594	1661	Complies
LTE Band 7	2500	0.2	25.0	-1.10	23.90	21.75	149.624	3060	Complies
LTE Band 12	699	0.2	25.0	-1.29	23.71	21.56	143.219	1426	Complies
LTE Band 13	777	0.2	25.0	-1.19	23.81	21.66	146.555	1585	Complies
LTE Band 25	1850	0.2	25.0	-0.24	24.76	22.61	182.390	3060	Complies
LTE Band 26	814	0.2	25.0	-1.13	23.87	21.72	148.594	1661	Complies
LTE Band 38	2570	0.2	25.0	2.27	27.27	25.12	325.087	3060	Complies
LTE Band 41	2496	0.2	25.0	2.83	27.83	25.68	369.828	3060	Complies
LTE Band 66	1710	0.2	25.0	0.20	25.20	23.05	201.837	3060	Complies

7 Simultaneous Transmission Analysis

In the case of fixed RF sources operating in the same time-averaging period, or of multiple mobile or portable RF sources within a device operating in the same time averaging period, if the sum of the fractional contributions to the applicable thresholds is less than or equal to 1 as indicated in the following equation),

$$\sum_{i=1}^a \frac{P_i}{P_{th,i}} + \sum_{j=1}^b \frac{ERP_j}{ERP_{th,j}} + \sum_{k=1}^c \frac{Evaluated_k}{Exposure Limit_k} \leq 1$$

7.1 Sum of the WWAN + Bluetooth

Mode	Max Tune-up ERP(mW)	ERP Threshold(mW)	simultaneous Transmission	simultaneous Transmission Limit
WWAN	369.828	3060	0.123	≤ 1
Bluetooth	5.200	3060		

7.2 Sum of the WWAN + WIFI 2.4GHz

Mode	Max Tune-up ERP(mW)	ERP Threshold(mW)	simultaneous Transmission	simultaneous Transmission Limit
WWAN	369.828	3060	0.151	≤ 1
WiFi 2.4GHz	92.470	3060		

7.3 Sum of the WWAN + WIFI 5GHz + Bluetooth

Mode	Max Tune-up ERP(mW)	ERP Threshold(mW)	simultaneous Transmission	simultaneous Transmission Limit
WWAN	369.828	3060	0.143	≤ 1
WiFi 5GHz	62.806	3060		
Bluetooth	5.200	3060		

Project No.: TM-2509000187P
Report No.: TMWK2509003910KS

Page 20 / 20
Rev.: 00

8 Facilities

All measurement facilities used to collect the measurement data are located at

☒ No.11, Wugong 6th Rd., Wugu Dist., New Taipei City, Taiwan.

END OF REPORT