

Maximum Permissible Exposure Report

1. Product Information

FCC ID : 2AU3Z-VWP
 EUT : Vivi Wireless Presentation
 Test Model : VWP-200-16
 Power Supply : USB1: DC 5V/1.3A; USB2: DC 5V/780mA;
 USB3: DC 5V/780mA ; USB4: DC 5V/780mA
 Hardware Version : V12
 Software Version : Android 9.0

Bluetooth

Frequency Range : 2402MHz ~ 2480MHz
 Chanel Number : 79 channels for Bluetooth V4.1 (BDR/EDR)
 40 channels for Bluetooth V4.1 (BT LE)
 Chanel Spacing : 1MHz for Bluetooth V4.1 (BDR/EDR)
 2MHz for Bluetooth V4.1 (BT LE)
 Modulation Type : GFSK, $\pi/4$ -DQPSK, 8-DPSK for Bluetooth V4.1(BDR/EDR)
 GFSK for Bluetooth V4.1 (BT LE)
 Bluetooth Version : V4.1

WIFI(2.4G Band)

Frequency Range : 2412MHz-2462MHz
 Channel Spacing : 5MHz
 Channel Number : 11 channels for 20MHz bandwidth(2412MHz~2462MHz)
 7 channels for 40MHz bandwidth(2422MHz~2452MHz)
 Modulation Type : 802.11b: DSSS(CCK,DQPSK,DBPSK);
 802.11g/n: OFDM(64QAM, 16QAM, QPSK, BPSK)

WIFI(5.2G Band)

Frequency Range : 5180MHz-5240MHz
 Channel Number : 4 channels for 20MHz bandwidth(5180MHz-5240MHz)
 2 channels for 40MHz bandwidth(5190MHz~5230MHz)
 1 channels for 80MHz bandwidth(5210MHz)
 Modulation Type : 802.11a/n/ac: OFDM(64QAM, 16QAM, QPSK, BPSK)

WIFI(5.8G Band)

Frequency Range : 5745MHz-5825MHz
 Channel Number : 5 channels for 20MHz bandwidth(5745MHz-5825MHz)
 2 channels for 40MHz bandwidth(5755MHz~5795MHz)
 1 channels for 80MHz bandwidth(5775MHz)
 Modulation Type : 802.11a/n/ac: OFDM(64QAM, 16QAM, QPSK, BPSK)

Antenna Description

External Antenna, 3dBi(Max.) for The BT and WIFI shares the same antenna0 ,
 3dBi(Max.) for WIFI antenna1
 Exposure category : General population/uncontrolled environment
 EUT Type : Production Unit
 Device Type : Mobile Device

2. Evaluation Method

Systems operating under the provisions of FCC 47 CFR section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as mobile device whereby a distance of 0.2m normally can be maintained between the user and the device, and below RF Permissible Exposure limit shall comply with.

In accordance with KDB447498 D01 General RF Exposure Guidance v06 for Simultaneous transmission MPE test exclusion applies when the sum of the MPE ratios for all simultaneous transmitting antennas incorporated in a host device, based on the calculated/estimated, numerically modelled or measured field strengths or power density, is ≤ 1.0 . The MPE ratio of each antenna is determined at the minimum test separation distance required by the operating configurations and exposure conditions of the host device, according to the ratio of field strengths or power density to MPE limit, at the test frequency. Either the maximum peak or spatially averaged results from measurements or numerical simulations may be used to determine the MPE ratios. Spatial averaging does not apply when MPE is estimated using simple calculations based on far-field plane-wave equivalent conditions. The antenna installation and operating requirements for the host device must meet the minimum test separation distances required by all antennas, in both standalone and simultaneous transmission operations, to satisfy compliance.

3. Limit

3.1 Refer evaluation method

[ANSI C95.1-1999](#): IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz.

[FCC KDB publication 447498 D01 General RF Exposure Guidance v06](#): Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies.

[FCC CFR 47 part1 1.1310](#): Radiofrequency radiation exposure limits.

[FCC CFR 47 part2 2.1091](#): Radiofrequency radiation exposure evaluation: mobile devices.

3.2 Limit

Limits for Maximum Permissible Exposure (MPE)/Controlled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm ²)	Averaging Time (minute)
Limits for Occupational/Controlled Exposure				
0.3 – 3.0	614	1.63	(100) *	6
3.0 – 30	1842/f	4.89/f	(900/f ²)*	6
30 – 300	61.4	0.163	1.0	6
300 – 1500	/	/	f/300	6
1500 – 100,000	/	/	5	6

Limits for Maximum Permissible Exposure (MPE)/Uncontrolled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm ²)	Averaging Time (minute)
Limits for Occupational/Controlled Exposure				
0.3 – 3.0	614	1.63	(100) *	30
3.0 – 30	824/f	2.19/f	(180/f ²)*	30
30 – 300	27.5	0.073	0.2	30
300 – 1500	/	/	f/1500	30
1500 – 100,000	/	/	1.0	30

F=frequency in MHz

*=Plane-wave equivalent power density

4. MPE Calculation Method

Predication of MPE limit at a given distance
Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = PG / 4\pi R^2$$

Where: S=power density

P=power input to antenna

G=power gain of the antenna in the direction of interest relative to an isotropic radiator

R=distance to the center of radiation of the antenna

5. Antenna Information

Netbox Duo can only use antennas certificated as follows provided by manufacturer;

Internal Identification	Antenna Identification in Internal photos	Antenna type and antenna number	Operate frequency band	Maximum antenna gain
Ant_0	WIFI and BT	External Antenna	2402MHz ~ 2480MHz; 2412MHz-2462MHz; 5180MHz-5240MHz; 5745MHz-5825MHz	3.0dBi(Max.)
Ant_1	WIFI	External Antenna	2412MHz-2462MHz; 5180MHz-5240MHz; 5745MHz-5825MHz	3.0dBi(Max.)

6. Measurement Results

6.1 Standalone MPE

As declared by the Applicant, the EUT is a wireless device used in a fix application, at least 20 cm from any body part of the user or nearby persons; from the maximum EUT RF output power, the minimum separation distance, $r = 20\text{cm}$, as well as the gain of the used antenna refer to antenna information, the RF power density can be obtained.

2.4GHz WLAN

Ant_0

Modulation Type	Max. Tune Up Output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm ²)	MPE Limits (mW/cm ²)
	dBm	mW				
GFSK	3.00	1.9953	3.0000	1.9953	0.0008	1.0000
$\pi/4$ -DQPSK	3.00	1.9953	3.0000	1.9953	0.0008	1.0000
8-DPSK	3.00	1.9953	3.0000	1.9953	0.0008	1.0000
BT LE	3.00	1.9953	3.0000	1.9953	0.0008	1.0000
2.4GWIFI (IEEE 802.11b)	16.00	39.8107	3.0000	1.9953	0.0158	1.0000
2.4GWIFI (IEEE 802.11g)	16.00	39.8107	3.0000	1.9953	0.0158	1.0000
2.4GWIFI (IEEE 802.11n HT20)	15.00	31.6228	3.0000	1.9953	0.0126	1.0000
2.4GWIFI (IEEE 802.11n HT40)	15.00	31.6228	3.0000	1.9953	0.0126	1.0000
5.2GWIFI (IEEE 802.11a)	9.00	7.9433	3.0000	1.9953	0.0032	1.0000
5.2GWIFI (IEEE 802.11n HT20)	9.00	7.9433	3.0000	1.9953	0.0032	1.0000
5.2GWIFI (IEEE 802.11ac VHT20)	9.00	7.9433	3.0000	1.9953	0.0032	1.0000
5.2GWIFI (IEEE 802.11n HT40)	9.00	7.9433	3.0000	1.9953	0.0032	1.0000
5.2GWIFI (IEEE 802.11ac VHT40)	8.00	6.3096	3.0000	1.9953	0.0025	1.0000

5.2GWIFI (IEEE 802.11ac VHT80)	9.00	7.9433	3.0000	1.9953	0.0032	1.0000
5.8GWIFI (IEEE 802.11a)	11.00	12.5893	3.0000	1.9953	0.0050	1.0000
5.8GWIFI (IEEE 802.11n HT20)	10.00	10.0000	3.0000	1.9953	0.0040	1.0000
5.8GWIFI (IEEE 802.11ac VHT20)	9.00	7.9433	3.0000	1.9953	0.0032	1.0000
5.8GWIFI (IEEE 802.11n HT40)	11.00	12.5893	3.0000	1.9953	0.0050	1.0000
5.8GWIFI (IEEE 802.11ac VHT40)	8.00	6.3096	3.0000	1.9953	0.0025	1.0000
5.8GWIFI (IEEE 802.11ac VHT80)	8.00	6.3096	3.0000	1.9953	0.0025	1.0000

Ant_1

Modulation Type	Max. Tune Up Output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm ²)	MPE Limits (mW/cm ²)
	dBm	mW				
2.4GWIFI (IEEE 802.11b)	9.00	7.9433	3.0000	1.9953	0.0032	1.0000
2.4GWIFI (IEEE 802.11g)	11.00	12.5893	3.0000	1.9953	0.0050	1.0000
2.4GWIFI (IEEE 802.11n HT20)	11.00	12.5893	3.0000	1.9953	0.0050	1.0000
2.4GWIFI (IEEE 802.11n HT40)	12.00	15.8489	3.0000	1.9953	0.0063	1.0000
5.2GWIFI (IEEE 802.11a)	10.00	10.0000	3.0000	1.9953	0.0040	1.0000
5.2GWIFI (IEEE 802.11n HT20)	10.00	10.0000	3.0000	1.9953	0.0040	1.0000
5.2GWIFI (IEEE 802.11ac VHT20)	11.00	12.5893	3.0000	1.9953	0.0050	1.0000
5.2GWIFI (IEEE 802.11n HT40)	10.00	10.0000	3.0000	1.9953	0.0040	1.0000
5.2GWIFI (IEEE 802.11ac VHT40)	10.00	10.0000	3.0000	1.9953	0.0040	1.0000
5.2GWIFI (IEEE 802.11ac VHT80)	6.00	3.9811	3.0000	1.9953	0.0016	1.0000
5.8GWIFI (IEEE 802.11a)	9.00	7.9433	3.0000	1.9953	0.0032	1.0000
5.8GWIFI (IEEE 802.11n HT20)	9.00	7.9433	3.0000	1.9953	0.0032	1.0000
5.8GWIFI (IEEE 802.11ac VHT20)	11.00	12.5893	3.0000	1.9953	0.0050	1.0000
5.8GWIFI (IEEE 802.11n HT40)	9.00	7.9433	3.0000	1.9953	0.0032	1.0000
5.8GWIFI (IEEE 802.11ac VHT40)	10.00	10.0000	3.0000	1.9953	0.0040	1.0000
5.8GWIFI (IEEE 802.11ac VHT80)	6.00	3.9811	3.0000	1.9953	0.0016	1.0000

Remark:

1. Output power (Average) including turn-up tolerance;
2. Output power was adjust to duty cycle at 100% if measured duty cycle less than 98%;
3. MPE evaluate distance is 20cm from user manual provide by manufacturer.

6.2 Simultaneous Transmission MPE

The sample supports 1 antennas for WLAN and BT and 1 antennas for WLAN. The *Ant_0* and *Ant_1* can transmit simultaneous.

According to KDB447498 D01 General RF Exposure Guidance v06 for Transmitters used in mobile exposure conditions for simultaneous transmission operations;

Σ of MPE ratios ≤ 1.0

Ant_0 and Ant_1 for Simultaneous Transmission Results

Modulation Type	MPE _{Ant_1} (mW/cm ²)	MPE _{Ant_2} (mW/cm ²)	Σ MPE ratios	Limit	Results
2.4GWIFI (IEEE 802.11n HT20)	0.0126	0.005	0.0176	1.0	PASS
2.4GWIFI (IEEE 802.11n HT40)	0.0126	0.0063	0.0189	1.0	PASS
5.2GWIFI (IEEE 802.11n HT20)	0.0032	0.004	0.0072	1.0	PASS
5.2GWIFI (IEEE 802.11ac VHT20)	0.0032	0.005	0.0082	1.0	PASS
5.2GWIFI (IEEE 802.11n HT40)	0.0032	0.004	0.0072	1.0	PASS
5.2GWIFI (IEEE 802.11ac VHT40)	0.0025	0.004	0.0065	1.0	PASS
5.2GWIFI (IEEE 802.11ac VHT80)	0.0032	0.0016	0.0048	1.0	PASS
5.8GWIFI (IEEE 802.11n HT20)	0.004	0.0032	0.0072	1.0	PASS
5.8GWIFI (IEEE 802.11ac VHT20)	0.0032	0.005	0.0082	1.0	PASS
5.8GWIFI (IEEE 802.11n HT40)	0.005	0.0032	0.0082	1.0	PASS
5.8GWIFI (IEEE 802.11ac VHT40)	0.0025	0.0040	0.0065	1.0	PASS
5.8GWIFI (IEEE 802.11ac VHT80)	0.0025	0.0016	0.0041	1.0	PASS

7. Conclusion

The measurement results comply with the FCC Limit per 47 CFR 2.1091 for the uncontrolled RF Exposure of mobile device.

-----THE END OF REPORT-----