

FCC Part 1.1310
RF Exposure Evaluation REPORT

For

Renesas Design Korea Inc.

FCC ID : 2AU49-RRQ61001009

Model : RRQ61001-009

Report Type : Original Report

Product Name : RRQ61001 Module

Report Number : RLK250801003RF07

Report Date : 2025-12-11

Prepared By : Bay Area Compliance Laboratories Corp.

(Linkou Laboratory)

No. 6, Wende 2Rd., Guishan Dist.,

Taoyuan City 33382, Taiwan (R.O.C.).

Tel: +886 (3) 3961072

Fax: +886 (3) 3961027

www.baclcorp.com.tw

**Facilities : The test site used by Bay Area Compliance Laboratories Corp. (Linkou Laboratory)
to collect test data is located on No. 6, Wende 2Rd., Guishan Dist,
Taoyuan City 33382, Taiwan (R.O.C.).**

Satement of Compliance

Applicant (Certification Holder)	Renesas Design Korea Inc.
	7th SiliconPark, 35 Pangyo-ro 255 beon-gil Bundang-gu, Seongnam-si, Gyeonggi-do, 13486
Brand (Trade) Name	Renesas
Product (Equipment) Name	RRQ61001 Module
Model Name	RRQ61001-009

Measurement Procedures and Standards Used:

- ☒ FCC Part 2.1091
- ☒ FCC Part 1.1310

1. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Linkou Laboratory).
2. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.
3. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested.
4. The determination of the test results does not require consideration of the uncertainty of the measurement, unless the assessment is required by customer agreement, regulation or standard document specification.
5. Bay Area Compliance Laboratories Corp. (Linkou Laboratory) is not responsible for the authenticity of the information provided by the applicant that affects the test results.

Report Issued Date : 2025-12-11

Reviewed By : Rory Cheng



Revision History

Revision	No.	Report Number	Issue Date	Description	Author/ Revised by
0.0	RLK250801003	RLK250801003RF07	2025-12-11	Original Report	Cedric Xu

TABLE OF CONTENTS

1. General Information..... 5
Product Description for Equipment under Test (EUT)5
2. FCC §1.1310 - RF Exposure..... 6
Applicable Standard.....6
3. RF Exposure Evaluation Result..... 8

1. General Information

Product Description for Equipment under Test (EUT)

Product Name	RRQ61001 Module
Main Model Name	RRQ61001-009
Series Model Name	RRQ61001-010
Model Discrepancy	Different antenna interfaces
Frequency Range	IEEE 802.11b/g/n HT20/ax HE20 Mode: 2412 ~ 2462 MHz IEEE 802.11a/n HT20/ac VHT20/ax HE20 Mode:5150 ~ 5250 MHz IEEE 802.11a/n HT20/ac VHT20/ax HE20 Mode:5250 ~ 5350 MHz IEEE 802.11a/n HT20/ac VHT20/ax HE20 Mode:5470 ~ 5725 MHz IEEE 802.11a/n HT20/ac VHT20/ax HE20 Mode:5725 ~ 5850 MHz
Modulation Technique	IEEE 802.11a Mode: OFDM IEEE 802.11b Mode: DSSS IEEE 802.11g Mode: OFDM IEEE 802.11n HT20 Mode: OFDM IEEE 802.11ac VHT20 Mode: OFDM IEEE 802.11ax HE20 Mode: OFDMA
Antenna Specification	Dipole Antenna 2.4G Gain : 3.3 dBi 5G Gain : 4.4 dBi

**All measurement and test data in this report was gathered from production sample serial number: RLK250801003-01 (Assigned by BACL (Linkou Laboratory)).*

****802.11ax mode only support full RU**

*****This device cannot run both WIFI 2.4G and WIFI 5G simultaneously.**

2. FCC §1.1310 - RF Exposure

Applicable Standard

According to subpart §1.1310 (a) Specific absorption rate (SAR) shall be used to evaluate the environmental impact of human exposure to radiofrequency (RF) radiation as specified in [§ 1.1307\(b\) of this part](#) within the frequency range of 100 kHz to 6 GHz (inclusive).

§1.1310 (d)(2) For operations within the frequency range of 300 kHz and 6 GHz (inclusive), the limits for maximum permissible exposure (MPE), derived from whole-body SAR limits and listed in Table 1 in [paragraph \(c\)\(1\)](#) of this section, may be used instead of whole-body SAR limits as set forth in [paragraphs \(a\)](#) through [\(c\)](#) of this section to evaluate the environmental impact of human exposure to RF radiation as specified in [§ 1.1307\(b\) of this part](#), except for portable devices as defined in [§ 2.1093 of this chapter](#) as these evaluations shall be performed according to the SAR provisions in [§ 2.1093](#).

§1.1310 (d)(3) At operating frequencies above 6 GHz, the MPE limits listed in Table 1 in [paragraph \(c\)\(1\)](#) of this section shall be used in all cases to evaluate the environmental impact of human exposure to RF radiation as specified in [§ 1.1307\(b\) of this part](#).

For single RF sources (*i.e.*, any single fixed RF source, mobile device, or portable device, as defined in paragraph (b)(2) of this section): A single RF source is exempt if:

(A) The available maximum time-averaged power is no more than 1 mW, regardless of separation distance. This exemption may not be used in conjunction with other exemption criteria other than those in paragraph (b)(3)(ii)(A) of this section.

Medical implant devices may only use this exemption and that in paragraph (b)(3)(ii)(A);

(B) Or the available maximum time-averaged power or effective radiated power (ERP), whichever is greater, is less than or equal to the threshold P_{th} (mW) described in the following formula. This method shall only be used at separation distances (cm) from 0.5 centimeters to 40 centimeters and at frequencies from 0.3 GHz to 6 GHz (inclusive). P_{th} is given by:

$$P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}} (d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases}$$

Where

$$x = -\log_{10} \left(\frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right) \text{ and } f \text{ is in GHz;}$$

and

$$ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases}$$

(C) Or using Table 1 and the minimum separation distance (R in meters) from the body of a nearby person for the frequency (f in MHz) at which the source operates, the ERP (watts) is no more than the calculated value prescribed for that frequency. For the exemption in Table 1 to apply, R must be at least $\lambda/2\pi$, where λ is the free-space operating wavelength in meters. If the ERP of a single RF source is not easily obtained, then the available maximum time-averaged power may be

used in lieu of ERP if the physical dimensions of the radiating structure(s) do not exceed the electrical length of $\lambda/4$ or if the antenna gain is less than that of a half-wave dipole (1.64 linear value).

Table 1 to § 1.1307(b)(3)(i)(C) - Single RF Sources Subject to Routine Environmental Evaluation

RF Source frequency (MHz)	Threshold ERP (watts)
0.3-1.34	$1,920 R^2$.
1.34-30	$3,450 R^2/f^2$.
30-300	$3.83 R^2$.
300-1,500	$0.0128 R^2 f$.
1,500-100,000	$19.2 R^2$.

3. RF Exposure Evaluation Result

§ 1.1307(b)(3)(i)(C) PASS

Mode	Freq. (MHz)	Tune-Up Power (dBm)	Antenna Gain (dBi)	Tune-Up Power (mW)	Tune-Up ERP (dBm)	Tune-Up ERP (mW)
2.4G Wi-Fi	2412-2462	19.00	3.3	79.43	20.15	103.51
UNII-1	5180-5240	13.50	4.4	22.39	15.75	37.58
UNII-2A	5260-5320	16.00	4.4	39.81	18.25	66.83
UNII-2C	5500-5700	15.50	4.4	35.48	17.75	59.57
UNII-3	5745-5825	13.00	4.4	19.95	15.25	33.50

Note : The tune up power was declared by applicant..

Mode	Freq.(MHz)	$\lambda/2\pi$ (mm)	Distance (mm)	Distance applies	ERP Limit (mW)	Result
2.4G Wi-Fi	2412-2462	9.22	200	apply	768.00	exempt
5G UNII-1	5180-5240	9.01	200	apply	768.00	exempt
5G UNII-2A	5260-5320	8.56	200	apply	768.00	exempt
5G UNII-2C	5500-5700	8.25	200	apply	768.00	exempt
5G UNII-3	5745-5825	9.22	200	apply	768.00	exempt

The minimum separation distance (R in meters) from the body of a nearby person for the frequency (f in MHz) at which the source operates

ERP (watts) is no more than the calculated value prescribed for that frequency

R must be at least $\lambda / 2\pi$

λ is the free-space operating wavelength in meters

This product does not have any form of simultaneous transmission capability.

Result: Compliance.

******* END OF REPORT *******