

FCC Part 15.407

TEST REPORT

For

Renesas Design Korea Inc.

7th SiliconPark, 35 Pangyo-ro 255 beon-gil Bundang-gu, Seongnam-si, Gyeonggi-do,
13486

FCC ID: 2AU49-RRQ61051008

Report Type:
Original Report

Product Type:
RRQ61051 Module

Report Producer : Charlie Li

Report Number : RLK250801004RF06

Report Date : 2025-12-31

Reviewed By: Rory Cheng



Prepared By: Bay Area Compliance Laboratories Corp.

(Linkou Laboratory)

No. 6, Wende 2Rd., Guishan Dist.,

Taoyuan City 33382, Taiwan (R.O.C.).

Tel: +886 (3) 3961072

Fax: +886 (3) 3961027

www.baclcorp.com.tw

Revision History

Revision	No.	Report Number	Issue Date	Description	Author/ Revised by
0.0	RLK250801004	RLK250801004RF06	2025-12-31	Original Report	Charlie Li

TABLE OF CONTENTS

1	General Information	4
1.1	Product Description for Equipment under Test (EUT).....	4
1.2	Objective.....	5
1.3	Test Methodology	5
1.4	Statement of Compliance.....	5
1.5	Measurement Uncertainty.....	6
1.6	Environmental Conditions	6
1.7	Test Facility	6
2	System Test Configuration	7
2.1	Description of Test Configuration	7
2.2	Equipment Modifications	7
2.3	Support Equipment List and Details.....	7
2.4	External Cable List and Details	7
3	Summary of Test Results.....	8
4	Test Equipment List and Details	9
5	Applicable Standard	10
5.1	DFS Requirement	10
5.2	DFS Measurement System	13
5.3	System Block Diagram.....	13
5.4	Test Procedure	13
6	Test Results.....	14
6.1	Description of EUT.....	14
6.2	Channel Loading.....	14
6.3	Conducted Test Setup Configuration.....	14
6.4	Radar Waveform Calibration.....	15
7	Channel Move Time and Channel Closing Transmission Time	16
7.1	Test Procedure	16
7.2	Test Result	16
8	Non-Occupancy Period.....	21
8.1	Test Procedure	21
8.2	Test Results.....	21

1 General Information

1.1 Product Description for Equipment under Test (EUT)

Applicant	Renesas Design Korea Inc.
	7th SiliconPark, 35 Pangyo-ro 255 beon-gil Bundang-gu, Seongnam-si, Gyeonggi-do, 13486
Brand(Trade) Name	Renesas
Product (Equipment)	RRQ61051 Module
Main Model Name	RRQ61051-008
Series Model Name	N/A
Model Discrepancy	N/A
Frequency Range	IEEE 802.11a/n HT20/ac VHT20/ax HE20 Mode:5250 ~ 5350 MHz IEEE 802.11a/n HT20/ac VHT20/ax HE20 Mode:5470 ~ 5725 MHz
Modulation Technique	IEEE 802.11a Mode: OFDM IEEE 802.11n HT20 Mode: OFDM IEEE 802.11ac VHT20 Mode: OFDM IEEE 802.11ax HE20 Mode: OFDMA
Maximum Conducted Average Output Powe	5250-5350 MHz: 15.68 dBm 5470-5725 MHz: 17.18 dBm
Antenna Specification	Manufacturer: Renesas Model : RRQ610x1-008 Antenna Type: PCB Antenna Band 2 Gain: 3.4 dBi Band 3 Gain: 3.4 dBi
Power Operation (Voltage Range)	☐ AC 120V/60Hz ☐ Adapter ☐ By AC Power Cord ☐ PoE
	☐ DC Type ☐ Battery ☐ DC Power Supply ☐ External from USB Cable ☐ External DC Adapter
	☒ 3.3Vdc
Received Date	Aug 01, 2025
Date of Test	Oct. 15, 2025

Note:*All measurement and test data in this report was gathered from production sample serial number: RLK250801004-01(Assigned by BACL, Linkou Laboratory).

**802.11ax mode only support full RU

1.2 Objective

This report is made pursuant to Part 15 Subpart E, of the Federal Communications Commission Rules.

The tests were performed in order to determine compliance with FCC Part 15.407(h) Radar Detection Function of Dynamic Frequency Selection (DFS).

1.3 Test Methodology

FCC CFR 47 Part15.407 (h)

FCC KDB 905462 D02 UNII DFS Compliance Procedures New Rules v02

1.4 Statement of Compliance

Decision Rule: No, (The test results do not include MU judgment)

1. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Linkou Laboratory).
2. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.
3. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested.
4. The determination of the test results does not require consideration of the uncertainty of the measurement, unless the assessment is required by customer agreement, regulation or standard document specification.
5. Bay Area Compliance Laboratories Corp. (Linkou Laboratory) is not responsible for the authenticity of the information provided by the applicant that affects the test results.

1.5 Measurement Uncertainty

Parameter	Uncertainty
DFS	± 3.73 dB
Time Domain	± 0.21 ms
Temperature	± 0.78 °C
Humidity	± 0.04 %
DFS_Level	± 1.85 dBm
DFS_Time	± 0.211 ms

Note: The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval. Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty.

1.6 Environmental Conditions

Test Site	Test Date	Temperature (°C)	Relative Humidity (%)	Test Engineer
DFS	2025/10/15	23.6	53	Cedric Xu

1.7 Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Linkou Laboratory) to collect test data is located on

☒ No.6, Wende 2Rd., Guishan Dist., Taoyuan City 33382, Taiwan (R.O.C.).

Bay Area Compliance Laboratories Corp. (Linkou Laboratory) is accredited to ISO 17025 by Taiwan Accreditation Foundation (TAF code: 3546) and the FCC designation No.TW3546 under the Mutual Recognition Agreement (MRA) in FCC Test.

2 System Test Configuration

2.1 Description of Test Configuration

The EUT was configured for testing in a normal mode which was provided by the Applicant.

2.2 Equipment Modifications

The EUT was configured for testing in a normal mode which was provided by the Applicant.

2.3 Support Equipment List and Details

No.	Description	Manufacturer	Model	FCC ID
1	Notebook (Lab provided)	DELL	E6410	N/A
2	Notebook (Lab provided)	Acer	N16Q1	N/A
3	Test Development Board (Customer provided)	RENESAS	EK-RQ61 565-11-C-0001 Ver 3.1	N/A
4	GWN 802.11ax Tri-Band Wi-Fi 6E Access Point (Lab provided)	GRANDSTREAM	GWN7665	YZZGWN7665
5	DaughterBoard (Customer provided)	RENESAS	RRQ610x1 565-16-B	N/A

2.4 External Cable List and Details

No.	Description	Manufacturer	Model
1	USB-A to Type-C cable (Customer provided)	VENTION	COZ

3 Summary of Test Results

Items	Description of Test	Results
Detection Bandwidth	UNII Detection Bandwidth	Not applicable
Performance Requirements Check	Initial Channel Availability Check Time (CAC)	Not applicable
	Radar Burst at the Beginning of the CAC	Not applicable
	Radar Burst at the End of the CAC	Not applicable
In-Service Monitoring	Channel Move Time	Compliance
	Channel Closing Transmission Time	Compliance
	Non-Occupancy Period	Compliance
Radar Detection	Statistical Performance Check	Not applicable

Note:

Not applicable: the EUT is a client unit without radar detection.

4 Test Equipment List and Details

Description	Manufacturer	Model	Serial Number	Calibration Date	Calibration Due Date
Conducted Room					
MXG Vector Signal Generator	AGILENT	N5182B	MY53050038	2025/08/21	2026/08/21
Signal Analyzer 40GHz	Rohde & Schwarz	FSV40-N	102248	2025/09/12	2026/09/12
Microflex Cable	EMCI	EMC102-KM-KM-1000	180520	2025/04/07	2026/04/07
Microflex Cable	EMCI	EMC102-KM-KM-1000	180521	2025/04/07	2026/04/07
Microflex Cable	MTJ Cooperation	SFL402-105FLEX	1	2025/04/07	2026/04/07
Microflex Cable	EMCI	SS402	5	2025/04/07	2026/04/07
4 Way Power Divider	MTJ Cooperation	MTJ7284-M	180301-3-2	2025/04/07	2026/04/07
2 Way Power Divider	MTJ Cooperation	MTJ7282-M	180301-3-3	2025/04/07	2026/04/07
2 Way Power Divider	MTJ Cooperation	MTJ7282-M	180301-3-4	2025/04/07	2026/04/07
(-30dB) Attenuator	MTJ Cooperation	MVE2211	SN 001	2025/04/07	2026/04/07
(-10dB) Attenuator	MTJ Cooperation	MTJ604-10	4	2025/04/07	2026/04/07
(-10dB) Attenuator	MTJ Cooperation	MTJ604-10	7	2025/04/07	2026/04/07
GWN 802.11ax Tri-Band Wi-Fi 6E Access Point	GRANDSTRE AM	GWN7665	33902627	N.C.R	N.C.R

***Statement of Traceability:** BACL Corp. attests that all of the calibrations on the equipment items listed above were traceable to the SI System of Units via the R.O.C. Center for Measurement Standards of the Electronics Testing Center, Taiwan (ETC) or to another internationally recognized National Metrology Institute (NMI), and were compliant with the current Taiwan Accreditation Foundation (TAF) requirements

5 Applicable Standard

5.1 DFS Requirement

CFR §47 Part 15.407(h),

FCC KDB 905462 D02 UNII DFS Compliance Procedures New Rules v02

Table 1: Applicability of DFS Requirements Prior to Use of a Channel

Requirement	Operational Mode		
	Master	Client Without Radar Detection	Client With Radar Detection
<i>Non-Occupancy Period</i>	Yes	Not required	Yes
<i>DFS Detection Threshold</i>	Yes	Not required	Yes
<i>Channel Availability Check Time</i>	Yes	Not required	Not required
<i>U-NII Detection Bandwidth</i>	Yes	Not required	Yes

Table 2: Applicability of DFS requirements during normal operation

Requirement	Operational Mode	
	Master Device or Client with Radar Detection	Client Without Radar Detection
<i>DFS Detection Threshold</i>	Yes	Not required
<i>Channel Closing Transmission Time</i>	Yes	Yes
<i>Channel Move Time</i>	Yes	Yes
<i>U-NII Detection Bandwidth</i>	Yes	Not required

Additional requirements for devices with multiple bandwidth modes	Master Device or Client with Radar Detection	Client Without Radar Detection
<i>U-NII Detection Bandwidth and Statistical Performance Check</i>	All BW modes must be tested	Not required
<i>Channel Move Time and Channel Closing Transmission Time</i>	Test using widest BW mode available	Test using the widest BW mode available for the link
<i>All other tests</i>	Any single BW mode	Not required
Note: Frequencies selected for statistical performance check (Section 7.8.4) should include several frequencies within the radar detection bandwidth and frequencies near the edge of the radar detection bandwidth. For 802.11 devices it is suggested to select frequencies in each of the bonded 20 MHz channels and the channel center frequency.		

Table 3: DFS Detection Thresholds for Master Devices and Client Devices with Radar Detection

Maximum Transmit Power	Value (See Notes 1, 2, and 3)
EIRP $\geq$ 200 milliwatt	-64 dBm
EIRP < 200 milliwatt and power spectral density < 10 dBm/MHz	-62 dBm
EIRP < 200 milliwatt that do not meet the power spectral density requirement	-64 dBm
Note 1: This is the level at the input of the receiver assuming a 0 dBi receive antenna. Note 2: Throughout these test procedures an additional 1 dB has been added to the amplitude of the test transmission waveforms to account for variations in measurement equipment. This will ensure that the test signal is at or above the detection threshold level to trigger a DFS response. Note3: EIRP is based on the highest antenna gain. For MIMO devices refer to KDB Publication 662911 D01.	

Table 4: DFS Response Requirement Values

Parameter	Value
<i>Non-occupancy period</i>	Minimum 30 minutes
<i>Channel Availability Check Time</i>	60 seconds
<i>Channel Move Time</i>	10 seconds See Note 1.
<i>Channel Closing Transmission Time</i>	200 milliseconds + an aggregate of 60 milliseconds over remaining 10 second period. See Notes 1 and 2.
<i>U-NII Detection Bandwidth</i>	Minimum 100% of the U-NII 99% transmission power bandwidth. See Note 3.
Note 1: <i>Channel Move Time</i> and the <i>Channel Closing Transmission Time</i> should be performed with Radar Type 0. The measurement timing begins at the end of the Radar Type 0 burst. Note 2: The <i>Channel Closing Transmission Time</i> is comprised of 200 milliseconds starting at the beginning of the <i>Channel Move Time</i> plus any additional intermittent control signals required to facilitate a <i>Channel</i> move (an aggregate of 60 milliseconds) during the remainder of the 10 second period. The aggregate duration of control signals will not count quiet periods in between transmissions. Note 3: During the <i>U-NII Detection Bandwidth</i> detection test, radar type 0 should be used. For each frequency step the minimum percentage of detection is 90 percent. Measurements are performed with no data traffic.	

Table 5 – Short Pulse Radar Test Waveforms

Radar Type	Pulse Width (μsec)	PRI (μsec)	Number of Pulses	Minimum Percentage of Successful Detection	Minimum Number of Trials
0	1	1428	18	See Note 1	See Note 1
1	1	Test A: 15 unique PRI values randomly selected from the list of 23 PRI values in Table 5a Test B: 15 unique PRI values randomly selected within the range of 518-3066 μsec, with a minimum increment of 1 μsec, excluding PRI values selected in Test A	Roundup $\left\{ \left(\frac{1}{360} \right) \cdot \left(\frac{19 \cdot 10^6}{\text{PRI}_{\mu\text{sec}}} \right) \right\}$	60%	30
2	1-5	150-230	23-29	60%	30
3	6-10	200-500	16-18	60%	30
4	11-20	200-500	12-16	60%	30
Aggregate (Radar Types 1-4)				80%	120
Note 1: Short Pulse Radar Type 0 should be used for the detection bandwidth test, channel move time, and channel closing time tests.					

Table 6 – Long Pulse Radar Test Waveform

Radar Type	Pulse Width (μsec)	Chirp Width (MHz)	PRI (μsec)	Number of Pulses per Burst	Number of Bursts	Minimum Percentage of Successful Detection	Minimum Number of Trials
5	50-100	5-20	1000-2000	1-3	8-20	80%	30


Table 7 – Frequency Hopping Radar Test Waveform

Radar Type	Pulse Width (μsec)	PRI (μsec)	Pulses per Hop	Hopping Rate (kHz)	Hopping Sequence Length (msec)	Minimum Percentage of Successful Detection	Minimum Number of Trials
6	1	333	9	0.333	300	70%	30

5.2 DFS Measurement System

BACL DFS measurement system consists of two subsystems: (1) The radar signal generating subsystem and (2) the traffic monitoring subsystem.

5.3 System Block Diagram



5.4 Test Procedure

A spectrum analyzer is used as a monitor verifies that the EUT status including Channel Closing Transmission Time and Channel Move Time, and does not transmit on a Channel during the Non-Occupancy Period after the diction and Channel move. It is also used to monitor EUT transmissions during the Channel Availability Check Time.

6 Test Results

6.1 Description of EUT


The calibrated radiated DFS detection threshold level is set to -62dBm.

6.2 Channel Loading

WLAN traffic is generated by software “Lan Test20”, software is used by IP and Frame based systems for loading the test channel during the In service compliance testing of the U-NII device.

Data package streamed from the Access Point to the Client using the software “Lan Test20”.


6.3 Conducted Test Setup Configuration




6.4 Radar Waveform Calibration

Radar Type 0

5320 MHz



5500 MHz



7 Channel Move Time and Channel Closing Transmission Time

7.1 Test Procedure

Perform type 0 short pulse radar waveform. The aggregate channel closing transmission time is calculated as follows:

$$\text{Aggregate Transmission Time} = N * \text{Dwell Time}$$

N is the number of spectrum analyzer bins showing a device transmission Dwell Time is the dwell time per bin (i.e. $\text{Dwell Time} = S/B$, S is the sweep time and B is the number of bin, i.e. 10000)

7.2 Test Result


Frequency (MHz)	Bandwidth (MHz)	Radar Type	Results
5320	20	Type 0	Compliant
5500	20	Type 0	Compliant

Please refer to the following tables and plots.

5320 MHz

Type 0 radar channel move time result:


Item	Time (s)	Limit (s)
Channel move time	0.493	10



Date: 15.OCT.2025 11:28:07

Type0 radar channel closing transmission time result:


Item	Aggregate Transmission Time After 200ms Delay (ms)	Limit (ms)
Closing Transmission Time	7.50	60



5500 MHz

Type 0 radar channel move time result:


Item	Time (s)	Limit (s)
Channel move time	0.476	10



Date: 15.OCT.2025 12:39:23

Type0 radar channel closing transmission time result:

Item	Aggregate Transmission Time After 200ms Delay (ms)	Limit (ms)
Closing Transmission Time	7.50	60



8 Non-Occupancy Period

8.1 Test Procedure


Measure the EUT for more than 30 minutes following the channel close/move time to verify that the EUT does not resume any transmissions on this channel. Provide one plot to demonstrate no transmission on the channel for the non-occupancy period (30 minutes observation time)

8.2 Test Results


Frequency(MHz)	Bandwidth (MHz)	Spectrum Analyzer Display
5320	20	No transmission within 30 minutes
5500	20	No transmission within 30 minutes

Please refer to the following plots.

5320 MHz



5500 MHz



***** END OF REPORT *****