

TEST REPORT

Product Name : Thermometer Hygrometer
Model Number : STH0C
FCC ID : 2AU4DDCV

Prepared for : X-Sense Innovations Co., Ltd.
Address : Room 1701, Block 3, Shenzhen International Innovation Valley, Dashi 1st Road, Xili Community, Xili Subdistrict, Nanshan District, Shenzhen.

Prepared by : EMTEK (DONGGUAN) CO, LTD.
Address : Room 111&112, Building 8, -1&2/F., Office Building2, Zone A, Zhongda Marine Biotechnology Research and Development Base, No.9, Xincheng Avenue, Songshan Lake High-Tech Industrial Development Zone, Dongguan, Guangdong, China

Tel : +86-0769-22807078
Fax : +86-0769-22807079

Report Number : EDG2603300045E00503R
Date of sample receipt : March 30, 2026
Date(s) of Tests : March 30, 2026 to April 08, 2026
Date of issue : April 08, 2026

Table of Contents

1. TEST RESULT CERTIFICATION	3
2. EUT SPECIFICATION	5
3. TEST REQUIREMENT	6
4. MEASUREMENT RESULT	7



1. TEST RESULT CERTIFICATION

Applicant : X-Sense Innovations Co., Ltd.
 Address : Room 1701, Block 3, Shenzhen International Innovation Valley, Dashi 1st Road, Xili Community, Xili Subdistrict, Nanshan District, Shenzhen.
 Manufacturer : X-Sense Electronics Co., Ltd.
 Address : Room 402, Building 4, No. 9, Jinshagang 1st Road, Shixia Village, Dalang Town, Dongguan City, 523750 Guangdong, P.R. CHINA
 Factory : X-Sense Electronics Co., Ltd.
 Address : Room 402, Building 4, No. 9, Jinshagang 1st Road, Shixia Village, Dalang Town, Dongguan City, 523750 Guangdong, P.R. CHINA
 EUT : Thermometer Hygrometer
 Model Name : STH0C
 Trademark : X-SENSE


Measurement Procedure Used:

APPLICABLE STANDARDS	
STANDARD	TEST RESULT
§ 15.247(i), § 2.1093	PASS

The above equipment was tested by EMTEK(DONGGUAN) CO., LTD. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.10 (2020) and the energy emitted by the sample EUT tested as described in this report is in compliance with the requirements of FCC Rules FCC § 15.247(i), § 2.1093.

The test results of this report relate only to the tested sample identified in this report

Date of Test : March 30, 2026 to April 08, 2026

Prepared by : 
 Jessica Zhang /Editor

Reviewer : 
 Warren Deng /Supervisor

Approve & Authorized Signer :  
 Sam Lv / Manager

Modified History

Version	Report No.	Revision Date	Summary
	ENS2511120038W01502R	/	Original Report



2. EUT Specification

Characteristics	Description
Product:	Thermometer Hygrometer
Model Number:	STH0C
Sample:	1#
Data Rate:	BLE: 1Mbps for GFSK modulation BT: 1Mbps for GFSK modulation 2Mbps for $\pi/4$ -DQPSK modulation 3Mbps for 8DPSK modulation 2.4G WIFI: 802.11b 802.11g 802.11n(20MHz channel bandwidth)
Modulation:	BLE: GFSK BT: GFSK, $\pi/4$ -DQPSK, 8DPSK 2.4G WIFI: DSSS with DBPSK/DQPSK/CCK for 802.11b; OFDM with BPSK/QPSK/16QAM/64QAM for 802.11g/n;
Operating Frequency Range(s) :	2402-2480MHz for BLE; 2402-2480MHz for BT; 2412-2462MHz for 2.4G WIFI
Number of Channels:	40 channels for BLE; 79 channels for BT; 11 channels for 2.4G WIFI
Transmit Power Max:	14.75 dBm(0.029854 W) for WiFi 2.4G; -1.61 dBm(0.000690 W) for BLE;
Antenna Gain:	2.08 dBi
Power supply:	Battery type: DC 4.5V
Evaluation applied:	☒ MPE Evaluation ☐ SAR Evaluation

3. Test Requirement

RF EXPOSURE EVALUATION

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency(RF) Radiation as specified in §1.1307(b)

Limits for Maximum Permissible Exposure (MPE)

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density(mW/cm ²)	Average Time
(A) Limits for Occupational/Control Exposures				
300-1500	--	--	F/300	6
1500-100000	--	--	5	6
(B) Limits for General Population/Uncontrol Exposures				
300-1500	--	--	F/1500	6
1500-100000	--	--	1	30

Friis transmission formula: $P_d = (P_{out} \cdot G) / (4 \cdot \pi \cdot R^2)$

Where

P_d = Power density in mW/cm²

P_{out} =output power to antenna in mW

G = Numeric gain of the antenna relative to isotropic antenna

π =3.1416

R = distance between observation point and center of the radiator in cm

P_d the limit of MPE, 1mW/cm². If we know the maximum gain of the antenna and total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

4. Measurement Result

gain:	2.08	FCC MPE						
Mode	Frequency (MHz)	Output Power(dBm)	E.I.R.P(dBm)	Target Power W/tolerance (dBm)	Max tune up power(dBm) tolerance	Max tuneup power(mW) tolerance	Power Density at R=20cm (mW/cm2)	Limit (mW/cm2)
BLE GFSK	2402	-1.61	0.47	0±1	1	1.26	0.000404	1
	2441	-3.25	-1.17	-2±1	-1	0.79	0.000255	1
	2480	-3.29	-1.21	-2±1	-1	0.79	0.000255	1

gain:	2.08	FCC MPE						
Mode	Frequency (MHz)	Output Power(dBm)	E.I.R.P(dBm)	Target Power W/tolerance (dBm)	Max tune up power(dBm) tolerance	Max tuneup power(mW) tolerance	Power Density at R=20cm (mW/cm2)	Limit (mW/cm2)
802.11b	2412	14.66	16.74	16±1	17	50.12	0.016096	1
	2437	13.6	15.68	15±1	16	39.81	0.012786	1
	2462	13.14	15.22	15±1	16	39.81	0.012786	1
802.11g	2412	14.75	16.83	16±1	17	50.12	0.016096	1
	2437	12.91	14.99	14±1	15	31.62	0.010156	1
	2462	13.03	15.11	15±1	16	39.81	0.012786	1
802.11n20	2412	14.56	16.64	16±1	17	50.12	0.016096	1
	2437	13.12	15.2	15±1	16	39.81	0.012786	1
	2462	12.87	14.95	14±1	15	31.62	0.010156	1
802.11n40	2422	14.66	16.74	16±1	17	50.12	0.016096	1
	2437	13.6	15.68	15±1	16	39.81	0.012786	1
	2452	13.14	15.22	15±1	16	39.81	0.012786	1

According to KDB 447498, no stand-alone required for BT antenna, and no simultaneous SAR measurement

*** End of Report ***