


5.47-5.725GHz_802.11a_Nss1,(6Mbps)_4TX

5580MHz_TX




EUT Y_4TX
Setting 23
05-M-A-4

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)			
PK	11.16756G	65.93	74.00	-8.07	49.64	3	Vertical	127	1.74	-	38.90	10.70	33.31			
AV	11.16633G	52.97	54.00	-1.03	36.68	3	Vertical	127	1.74	-	38.90	10.70	33.31			
PK	16.73568G	67.92	68.20	-0.28	50.25	3	Vertical	91	2.32	-	37.86	12.77	32.96			

5.47-5.725GHz_802.11a_Nss1,(6Mbps)_4TX

5580MHz_TX




EUT Y_4TX
Setting 23
05-M-A-4

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)			
PK	11.15607G	68.84	74.00	-5.16	52.56	3	Horizontal	136	1.80	-	38.90	10.70	33.32			
AV	11.15397G	53.34	54.00	-0.66	37.06	3	Horizontal	136	1.80	-	38.90	10.70	33.32			
PK	16.74483G	67.64	68.20	-0.56	49.99	3	Horizontal	125	1.24	-	37.82	12.78	32.95			

5.47-5.725GHz_802.11a_Nss1,(6Mbps)_4TX

5700MHz_TX




EUT Y_4TX
Setting 20
06-D-G-4-10

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)			
PK	5.7007G	122.77	Inf	-Inf	115.13	3	Vertical	119	1.36	-	31.90	7.31	31.57			
AV	5.7009G	113.25	Inf	-Inf	105.60	3	Vertical	119	1.36	-	31.91	7.31	31.57			
PK	5.7253G	67.95	68.20	-0.25	60.15	3	Vertical	119	1.36	-	32.05	7.33	31.58			

5.47-5.725GHz_802.11a_Nss1,(6Mbps)_4TX

5700MHz_TX




EUT Y_4TX
Setting 20
06-D-G-4-10

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)			
PK	5.6954G	118.29	Inf	-Inf	110.68	3	Horizontal	90	1.55	-	31.88	7.30	31.57			
AV	5.6946G	108.68	Inf	-Inf	101.07	3	Horizontal	90	1.55	-	31.88	7.30	31.57			
PK	5.725G	64.65	68.20	-3.55	56.85	3	Horizontal	90	1.55	-	32.05	7.33	31.58			

5.47-5.725GHz_802.11a_Nss1,(6Mbps)_4TX

5700MHz_TX




EUT Y_4TX
Setting 20
06-D-J-8

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)			
PK	11.39685G	58.15	74.00	-15.85	40.38	3	Vertical	222	1.64	-	39.99	10.52	32.74			
AV	11.40135G	45.29	54.00	-8.71	27.50	3	Vertical	222	1.64	-	40.00	10.53	32.74			
PK	17.08521G	59.58	68.20	-8.62	39.66	3	Vertical	185	1.64	-	40.26	13.16	33.50			

5.47-5.725GHz_802.11a_Nss1,(6Mbps)_4TX

5700MHz_TX




EUT Y_4TX
Setting 20
06-D-J-8

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)			
PK	11.41164G	57.77	74.00	-16.23	39.99	3	Horizontal	41	2.20	-	40.00	10.53	32.75			
AV	11.40186G	45.13	54.00	-8.87	27.35	3	Horizontal	41	2.20	-	40.00	10.53	32.75			
PK	17.08782G	60.49	68.20	-7.71	40.57	3	Horizontal	244	1.29	-	40.25	13.16	33.49			

5.47-5.725GHz_802.11a_Nss1,(6Mbps)_4TX

5720MHz Straddle 5.47-5.725GHz_TX




EUT Y_4TX
Setting 24.5
06-D-G-4-10

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)			
PK	5.7212G	126.51	Inf	-Inf	118.74	3	Vertical	128	2.16	-	32.03	7.32	31.58			
AV	5.7208G	117.25	Inf	-Inf	109.49	3	Vertical	128	2.16	-	32.02	7.32	31.58			
PK	5.8544G	67.33	68.20	-0.87	59.19	3	Vertical	128	2.16	-	32.32	7.41	31.59			

5.47-5.725GHz_802.11a_Nss1,(6Mbps)_4TX

5720MHz Straddle 5.47-5.725GHz_TX




EUT Y_4TX
Setting 24.5
06-D-G-4-10

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)			
PK	5.7148G	124.14	Inf	-Inf	116.41	3	Horizontal	90	1.50	-	31.99	7.32	31.58			
AV	5.7152G	112.96	Inf	-Inf	105.23	3	Horizontal	90	1.50	-	31.99	7.32	31.58			
PK	5.8672G	60.29	68.20	-7.91	52.09	3	Horizontal	90	1.50	-	32.37	7.42	31.59			

5.47-5.725GHz_802.11a_Nss1,(6Mbps)_4TX

5720MHz Straddle 5.47-5.725GHz_TX




EUT Y_4TX
Setting 22.5
05-M-J-8

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)			
PK	11.43682G	67.93	74.00	-6.07	51.25	3	Vertical	123	1.36	-	38.93	10.82	33.07			
AV	11.43568G	53.90	54.00	-0.10	37.22	3	Vertical	123	1.36	-	38.93	10.82	33.07			
PK	17.16078G	65.79	68.20	-2.41	47.31	3	Vertical	343	1.54	-	38.42	12.97	32.91			

5.47-5.725GHz_802.11a_Nss1,(6Mbps)_4TX

5720MHz Straddle 5.47-5.725GHz_TX




EUT Y_4TX
Setting 22.5
05-M-J-8

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)			
PK	11.44042G	63.60	74.00	-10.40	46.92	3	Horizontal	244	1.80	-	38.92	10.82	33.06			
AV	11.44147G	50.53	54.00	-3.47	33.85	3	Horizontal	244	1.80	-	38.92	10.82	33.06			
PK	17.16132G	67.98	68.20	-0.22	49.50	3	Horizontal	213	1.80	-	38.42	12.97	32.91			

5.725-5.85GHz_802.11a_Nss1,(6Mbps)_4TX

5745MHz_TX




EUT Y_4TX
Setting 24
06-D-G-4-10

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)			
PK	5.64G	67.80	68.20	-0.40	60.40	3	Vertical	118	1.45	-	31.72	7.25	31.57			
PK	5.7465G	126.78	Inf	-Inf	118.84	3	Vertical	118	1.45	-	32.18	7.34	31.58			
AV	5.746G	116.76	Inf	-Inf	108.82	3	Vertical	118	1.45	-	32.18	7.34	31.58			
PK	5.9365G	62.34	68.20	-5.86	53.93	3	Vertical	118	1.45	-	32.57	7.44	31.60			

5.725-5.85GHz_802.11a_Nss1,(6Mbps)_4TX

5745MHz_TX




EUT Y_4TX
Setting 24
06-D-G-4-10

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)			
PK	5.5375G	59.11	68.20	-9.09	51.58	3	Horizontal	91	1.40	-	31.90	7.18	31.55			
PK	5.7395G	123.41	Inf	-Inf	115.51	3	Horizontal	91	1.40	-	32.14	7.34	31.58			
AV	5.7405G	113.25	Inf	-Inf	105.35	3	Horizontal	91	1.40	-	32.14	7.34	31.58			
PK	5.977G	59.21	68.20	-8.99	50.81	3	Horizontal	91	1.40	-	32.55	7.46	31.61			

5.725-5.85GHz_802.11a_Nss1,(6Mbps)_4TX

5745MHz_TX




EUT_Y_4TX
Setting 19
05-M-J-8

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)			
PK	11.48695G	67.84	74.00	-6.16	50.97	3	Vertical	125	1.24	-	39.05	10.84	33.02			
AV	11.48755G	53.58	54.00	-0.42	36.71	3	Vertical	125	1.24	-	39.05	10.84	33.02			
PK	17.226G	60.87	68.20	-7.33	42.25	3	Vertical	267	2.76	-	38.60	13.00	32.98			

5.725-5.85GHz_802.11a_Nss1,(6Mbps)_4TX

5745MHz_TX




EUT Y_4TX
Setting 19
05-M-J-8

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)			
PK	11.4926G	64.50	74.00	-9.50	47.60	3	Horizontal	246	1.80	-	39.07	10.85	33.02			
AV	11.49145G	50.73	54.00	-3.27	33.83	3	Horizontal	246	1.80	-	39.07	10.85	33.02			
PK	17.2381G	59.94	68.20	-8.26	41.27	3	Horizontal	210	1.80	-	38.65	13.01	32.99			

5.725-5.85GHz_802.11a_Nss1,(6Mbps)_4TX

5785MHz_TX




EUT Y_4TX
Setting 24
06-D-G-4-10

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)			
PK	5.6295G	60.50	68.20	-7.70	53.08	3	Vertical	124	2.03	-	31.74	7.25	31.57			
PK	5.7865G	126.09	Inf	-Inf	118.02	3	Vertical	124	2.03	-	32.27	7.38	31.58			
AV	5.7855G	116.54	Inf	-Inf	108.47	3	Vertical	124	2.03	-	32.27	7.38	31.58			
PK	5.9345G	64.02	68.20	-4.18	55.61	3	Vertical	124	2.03	-	32.57	7.44	31.60			

5.725-5.85GHz_802.11a_Nss1,(6Mbps)_4TX

5785MHz_TX




EUT Y_4TX
Setting 24
06-D-G-4-10

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)			
PK	5.55G	58.64	68.20	-9.56	51.11	3	Horizontal	90	1.80	-	31.90	7.19	31.56			
PK	5.7815G	122.58	Inf	-Inf	114.53	3	Horizontal	90	1.80	-	32.26	7.37	31.58			
AV	5.7805G	112.26	Inf	-Inf	104.21	3	Horizontal	90	1.80	-	32.26	7.37	31.58			
PK	6.0245G	60.14	68.20	-8.06	51.66	3	Horizontal	90	1.80	-	32.55	7.49	31.56			

5.725-5.85GHz_802.11a_Nss1,(6Mbps)_4TX

5785MHz_TX




EUT_Y_4TX
Setting 19
05-M-J-8

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)			
PK	11.56715G	68.35	74.00	-5.65	51.71	3	Vertical	122	1.58	-	38.83	10.88	33.07			
AV	11.5675G	53.82	54.00	-0.18	37.18	3	Vertical	122	1.58	-	38.83	10.88	33.07			
PK	17.3662G	60.21	68.20	-7.99	41.46	3	Vertical	-0	2.67	-	38.80	13.07	33.12			

5.725-5.85GHz_802.11a_Nss1,(6Mbps)_4TX

5785MHz_TX




EUT_Y_4TX
Setting 19
05-M-J-8

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)			
PK	11.5727G	65.86	74.00	-8.14	49.24	3	Horizontal	248	1.52	-	38.81	10.88	33.07			
AV	11.5728G	52.57	54.00	-1.43	35.95	3	Horizontal	248	1.52	-	38.81	10.88	33.07			
PK	17.35535G	61.92	68.20	-6.28	43.17	3	Horizontal	50	2.00	-	38.80	13.06	33.11			

5.725-5.85GHz_802.11a_Nss1,(6Mbps)_4TX

5825MHz_TX




EUT Y_4TX
Setting 23
06-D-G-4-10

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)			
PK	5.585G	58.94	68.20	-9.26	51.46	3	Vertical	120	2.17	-	31.83	7.21	31.56			
PK	5.826G	124.58	Inf	-Inf	116.47	3	Vertical	120	2.17	-	32.30	7.40	31.59			
AV	5.8255G	115.01	Inf	-Inf	106.90	3	Vertical	120	2.17	-	32.30	7.40	31.59			
PK	6.0675G	60.29	68.20	-7.91	51.63	3	Vertical	120	2.17	-	32.60	7.52	31.46			

5.725-5.85GHz_802.11a_Nss1,(6Mbps)_4TX

5825MHz_TX




EUT Y_4TX
Setting 23
06-D-G-4-10

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)			
PK	5.6165G	58.49	68.20	-9.71	51.05	3	Horizontal	91	1.46	-	31.77	7.23	31.56			
PK	5.819G	120.71	Inf	-Inf	112.60	3	Horizontal	91	1.46	-	32.30	7.40	31.59			
AV	5.821G	111.27	Inf	-Inf	103.16	3	Horizontal	91	1.46	-	32.30	7.40	31.59			
PK	6.0605G	59.93	68.20	-8.27	51.29	3	Horizontal	91	1.46	-	32.60	7.52	31.48			

5.725-5.85GHz_802.11a_Nss1,(6Mbps)_4TX

5825MHz_TX




EUT_Y_4TX
Setting 19.5
05-M-J-8

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)			
PK	11.64705G	67.34	74.00	-6.66	51.15	3	Vertical	122	1.80	-	38.42	10.91	33.14			
AV	11.64655G	53.59	54.00	-0.41	37.40	3	Vertical	122	1.80	-	38.42	10.91	33.14			
PK	17.4583G	59.89	68.20	-8.31	41.08	3	Vertical	114	2.54	-	38.92	13.11	33.22			

5.725-5.85GHz_802.11a_Nss1,(6Mbps)_4TX

5825MHz_TX




EUT Y_4TX
Setting 19.5
05-M-J-8

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)			
PK	11.6492G	66.40	74.00	-7.60	50.22	3	Horizontal	246	1.80	-	38.40	10.92	33.14			
AV	11.651G	52.62	54.00	-1.38	36.44	3	Horizontal	246	1.80	-	38.40	10.92	33.14			
PK	17.474G	61.28	68.20	-6.92	42.44	3	Horizontal	48	1.87	-	38.95	13.12	33.23			

5.15-5.25GHz_802.11ax HEW20_Nss1,(MCS0)_4TX

5180MHz_TX




EUT Y_4TX
Setting 19
06-D-G-4-10

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)			
PK	5.1492G	65.80	74.00	-8.20	58.15	3	Vertical	99	1.20	-	32.10	6.91	31.36			
AV	5.1496G	53.34	54.00	-0.66	45.69	3	Vertical	99	1.20	-	32.10	6.91	31.36			
PK	5.1795G	119.33	Inf	-Inf	111.86	3	Vertical	99	1.20	-	31.92	6.93	31.38			
AV	5.1785G	108.22	Inf	-Inf	100.74	3	Vertical	99	1.20	-	31.93	6.93	31.38			

5.15-5.25GHz_802.11ax HEW20_Nss1,(MCS0)_4TX

5180MHz_TX




EUT Y_4TX
Setting 19
06-D-G-4-10

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)			
PK	5.149G	62.36	74.00	-11.64	54.71	3	Horizontal	120	2.15	-	32.10	6.91	31.36			
AV	5.15G	49.98	54.00	-4.02	42.32	3	Horizontal	120	2.15	-	32.10	6.92	31.36			
PK	5.1811G	114.88	Inf	-Inf	107.42	3	Horizontal	120	2.15	-	31.91	6.93	31.38			
AV	5.1784G	104.01	Inf	-Inf	96.53	3	Horizontal	120	2.15	-	31.93	6.93	31.38			

5.15-5.25GHz_802.11ax HEW20_Nss1,(MCS0)_4TX

5180MHz_TX




EUT Y_4TX
Setting 19
06-D-G-4

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)			
PK	10.37332G	60.74	68.20	-7.46	43.24	3	Vertical	42	1.80	-	40.05	10.04	32.59			
PK	15.52746G	63.57	74.00	-10.43	45.00	3	Vertical	303	2.22	-	38.95	12.45	32.83			
AV	15.55371G	50.28	54.00	-3.72	31.77	3	Vertical	303	2.22	-	38.88	12.46	32.83			

5.15-5.25GHz_802.11ax HEW20_Nss1,(MCS0)_4TX

5180MHz_TX




EUT Y_4TX
Setting 19
06-D-G-4

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)			
PK	10.357G	59.38	68.20	-8.82	41.94	3	Horizontal	150	2.74	-	40.01	10.03	32.60			
PK	15.54G	63.27	74.00	-10.73	44.73	3	Horizontal	222	1.81	-	38.92	12.45	32.83			
AV	15.5502G	50.35	54.00	-3.65	31.82	3	Horizontal	222	1.81	-	38.90	12.46	32.83			

5.15-5.25GHz_802.11ax HEW20_Nss1,(MCS0)_4TX

5200MHz_TX




EUT Y_4TX
Setting 22.5
06-D-G-4-10

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)			
PK	5.15G	66.14	74.00	-7.86	58.48	3	Vertical	73	2.06	-	32.10	6.92	31.36			
AV	5.1494G	53.57	54.00	-0.43	45.92	3	Vertical	73	2.06	-	32.10	6.91	31.36			
PK	5.1992G	123.53	Inf	-Inf	116.18	3	Vertical	73	2.06	-	31.80	6.94	31.39			
AV	5.199G	110.87	Inf	-Inf	103.51	3	Vertical	73	2.06	-	31.81	6.94	31.39			

5.15-5.25GHz_802.11ax HEW20_Nss1,(MCS0)_4TX

5200MHz_TX




EUT Y_4TX
Setting 22.5
06-D-G-4-10

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)			
PK	5.1488G	63.02	74.00	-10.98	55.37	3	Horizontal	86	1.33	-	32.10	6.91	31.36			
AV	5.1498G	50.30	54.00	-3.70	42.65	3	Horizontal	86	1.33	-	32.10	6.91	31.36			
PK	5.2018G	119.82	Inf	-Inf	112.48	3	Horizontal	86	1.33	-	31.79	6.94	31.39			
AV	5.1982G	108.42	Inf	-Inf	101.06	3	Horizontal	86	1.33	-	31.81	6.94	31.39			

5.15-5.25GHz_802.11ax HEW20_Nss1,(MCS0)_4TX

5200MHz_TX




EUT Y_4TX
Setting 22.5
06-D-J-8

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)			
PK	10.40672G	62.77	68.20	-5.43	45.20	3	Vertical	73	2.73	-	40.11	10.05	32.59			
PK	15.60429G	64.52	74.00	-9.48	46.32	3	Vertical	211	1.71	-	38.56	12.48	32.84			
AV	15.59358G	50.87	54.00	-3.13	32.59	3	Vertical	211	1.71	-	38.64	12.48	32.84			

5.15-5.25GHz_802.11ax HEW20_Nss1,(MCS0)_4TX

5200MHz_TX




EUT Y_4TX
Setting 22.5
06-D-J-8

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)			
PK	10.39619G	61.72	68.20	-6.48	44.17	3	Horizontal	112	1.59	-	40.09	10.05	32.59			
PK	15.58935G	63.83	74.00	-10.17	45.54	3	Horizontal	229	1.15	-	38.66	12.47	32.84			
AV	15.59574G	50.79	54.00	-3.21	32.52	3	Horizontal	229	1.15	-	38.63	12.48	32.84			

5.15-5.25GHz_802.11ax HEW20_Nss1,(MCS0)_4TX

5240MHz_TX




EUT_Y_4TX
Setting 24.5
06-D-G-4-10

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)			
PK	5.1398G	63.00	74.00	-11.00	55.35	3	Vertical	73	2.24	-	32.10	6.91	31.36			
AV	5.1485G	49.98	54.00	-4.02	42.33	3	Vertical	73	2.24	-	32.10	6.91	31.36			
PK	5.2391G	125.00	Inf	-Inf	117.80	3	Vertical	73	2.24	-	31.64	6.97	31.41			
AV	5.2391G	112.66	Inf	-Inf	105.46	3	Vertical	73	2.24	-	31.64	6.97	31.41			
PK	5.3822G	58.91	74.00	-15.09	51.76	3	Vertical	73	2.24	-	31.56	7.08	31.49			
AV	5.3573G	47.75	54.00	-6.25	40.65	3	Vertical	73	2.24	-	31.51	7.06	31.47			

5.15-5.25GHz_802.11ax_HEW20_Nss1,(MCS0)_4TX

5240MHz_TX




EUT_Y_4TX
Setting 24.5
06-D-G-4-10

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)			
PK	5.1482G	61.18	74.00	-12.82	53.53	3	Horizontal	99	2.21	-	32.10	6.91	31.36			
AV	5.1392G	48.33	54.00	-5.67	40.68	3	Horizontal	99	2.21	-	32.10	6.91	31.36			
PK	5.2367G	121.90	Inf	-Inf	114.69	3	Horizontal	99	2.21	-	31.65	6.97	31.41			
AV	5.2412G	109.39	Inf	-Inf	102.19	3	Horizontal	99	2.21	-	31.64	6.97	31.41			
PK	5.3819G	58.11	74.00	-15.89	50.96	3	Horizontal	99	2.21	-	31.56	7.08	31.49			
AV	5.3789G	46.97	54.00	-7.03	39.82	3	Horizontal	99	2.21	-	31.56	7.07	31.48			

5.15-5.25GHz_802.11ax HEW20_Nss1,(MCS0)_4TX

5240MHz_TX




EUT Y_4TX
Setting 24.5
05-M-A-4

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)			
PK	10.47664G	59.93	68.20	-8.27	44.54	3	Vertical	81	2.57	-	38.80	10.40	33.81			
PK	15.73497G	64.76	74.00	-9.24	47.88	3	Vertical	92	1.80	-	37.77	12.34	33.23			
AV	15.71973G	51.75	54.00	-2.25	34.93	3	Vertical	92	1.80	-	37.74	12.34	33.26			

5.15-5.25GHz_802.11ax HEW20_Nss1,(MCS0)_4TX

5240MHz_TX




EUT Y_4TX
Setting 24.5
05-M-A-4

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBUV/m)	(dBUV/m)	(dB)	(dBUV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	10.47442G	59.11	68.20	-9.09	43.71	3	Horizontal	288	1.80	-	38.80	10.40	33.80			
PK	15.71787G	64.62	74.00	-9.38	47.80	3	Horizontal	231	1.80	-	37.74	12.34	33.26			
AV	15.71805G	52.30	54.00	-1.70	35.48	3	Horizontal	231	1.80	-	37.74	12.34	33.26			

5.25-5.35GHz_802.11ax HEW20_Nss1,(MCS0)_4TX

5260MHz_TX




EUT_Y_4TX
Setting 23.5
06-D-G-4-10

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)			
PK	5.1382G	60.54	74.00	-13.46	52.88	3	Vertical	70	1.99	-	32.10	6.91	31.35			
AV	5.131G	49.15	54.00	-4.85	41.49	3	Vertical	70	1.99	-	32.10	6.91	31.35			
PK	5.2591G	125.46	Inf	-Inf	118.32	3	Vertical	70	1.99	-	31.58	6.98	31.42			
AV	5.2606G	112.51	Inf	-Inf	105.36	3	Vertical	70	1.99	-	31.58	6.99	31.42			
PK	5.3536G	60.06	74.00	-13.94	52.96	3	Vertical	70	1.99	-	31.51	7.06	31.47			
AV	5.3593G	48.42	54.00	-5.58	41.31	3	Vertical	70	1.99	-	31.52	7.06	31.47			

5.25-5.35GHz_802.11ax_HEW20_Nss1,(MCS0)_4TX

5260MHz_TX




EUT_Y_4TX
Setting 23.5
06-D-G-4-10

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)			
PK	5.1421G	60.01	74.00	-13.99	52.36	3	Horizontal	100	2.32	-	32.10	6.91	31.36			
AV	5.1481G	48.63	54.00	-5.37	40.98	3	Horizontal	100	2.32	-	32.10	6.91	31.36			
PK	5.2621G	123.63	Inf	-Inf	116.48	3	Horizontal	100	2.32	-	31.58	6.99	31.42			
AV	5.2597G	110.32	Inf	-Inf	103.18	3	Horizontal	100	2.32	-	31.58	6.98	31.42			
PK	5.3818G	60.28	74.00	-13.72	53.13	3	Horizontal	100	2.32	-	31.56	7.08	31.49			
AV	5.3971G	48.44	54.00	-5.56	41.25	3	Horizontal	100	2.32	-	31.59	7.09	31.49			

5.25-5.35GHz_802.11ax HEW20_Nss1,(MCS0)_4TX

5260MHz_TX




EUT Y_4TX
Setting 23.5
06-D-J-8

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)			
PK	10.51454G	60.83	68.20	-7.37	43.20	3	Vertical	158	1.47	-	40.10	10.10	32.57			
PK	15.77832G	66.66	74.00	-7.34	48.68	3	Vertical	78	2.89	-	38.30	12.56	32.88			
AV	15.77742G	53.66	54.00	-0.34	35.68	3	Vertical	78	2.89	-	38.30	12.56	32.88			

5.25-5.35GHz_802.11ax HEW20_Nss1,(MCS0)_4TX

5260MHz_TX




EUT Y_4TX
Setting 23.5
06-D-J-8

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)			
PK	10.51484G	61.22	68.20	-6.98	43.59	3	Horizontal	230	2.71	-	40.10	10.10	32.57			
PK	15.77103G	64.77	74.00	-9.23	46.78	3	Horizontal	108	1.00	-	38.30	12.56	32.87			
AV	15.77526G	52.53	54.00	-1.47	34.55	3	Horizontal	108	1.00	-	38.30	12.56	32.88			

5.25-5.35GHz_802.11ax HEW20_Nss1,(MCS0)_4TX

5300MHz_TX




EUT Y_4TX
Setting 23.5
06-D-G-4-10

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)			
PK	5.3024G	124.62	Inf	-Inf	117.54	3	Vertical	69	2.01	-	31.50	7.02	31.44			
AV	5.2986G	112.09	Inf	-Inf	105.02	3	Vertical	69	2.01	-	31.50	7.01	31.44			
PK	5.351G	68.03	74.00	-5.97	60.95	3	Vertical	69	2.01	-	31.50	7.05	31.47			
AV	5.3514G	53.88	54.00	-0.12	46.80	3	Vertical	69	2.01	-	31.50	7.05	31.47			

5.25-5.35GHz_802.11ax HEW20_Nss1,(MCS0)_4TX

5300MHz_TX




EUT_Y_4TX
Setting 24.5
06-D-G-4-10

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)			
PK	5.2982G	121.10	Inf	-Inf	114.03	3	Horizontal	101	2.13	-	31.50	7.01	31.44			
AV	5.298G	109.24	Inf	-Inf	102.17	3	Horizontal	101	2.13	-	31.50	7.01	31.44			
PK	5.3516G	62.73	74.00	-11.27	55.65	3	Horizontal	101	2.13	-	31.50	7.05	31.47			
AV	5.35G	51.09	54.00	-2.91	44.01	3	Horizontal	101	2.13	-	31.50	7.05	31.47			

5.25-5.35GHz_802.11ax HEW20_Nss1,(MCS0)_4TX

5300MHz_TX




EUT Y_4TX
Setting 23.5
06-D-J-8

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)			
PK	10.60441G	60.57	74.00	-13.43	42.78	3	Vertical	256	2.65	-	40.20	10.15	32.56			
AV	10.61446G	47.59	54.00	-6.41	29.80	3	Vertical	256	2.65	-	40.20	10.15	32.56			
PK	15.89638G	65.80	74.00	-8.20	48.07	3	Vertical	78	2.89	-	38.01	12.62	32.90			
AV	15.90292G	52.90	54.00	-1.10	35.19	3	Vertical	78	2.89	-	37.99	12.62	32.90			

5.25-5.35GHz_802.11ax HEW20_Nss1,(MCS0)_4TX

5300MHz_TX




EUT Y_4TX
Setting 23.5
06-D-J-8

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)			
PK	10.60316G	59.81	74.00	-14.19	42.02	3	Horizontal	306	2.99	-	40.20	10.15	32.56			
AV	10.6062G	47.69	54.00	-6.31	29.90	3	Horizontal	306	2.99	-	40.20	10.15	32.56			
PK	15.90006G	64.70	74.00	-9.30	46.98	3	Horizontal	117	2.83	-	38.00	12.62	32.90			
AV	15.90154G	52.09	54.00	-1.91	34.37	3	Horizontal	117	2.83	-	38.00	12.62	32.90			

5.25-5.35GHz_802.11ax HEW20_Nss1,(MCS0)_4TX

5320MHz_TX




EUT Y_4TX
Setting 20
06-D-G-4-10

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)			
PK	5.3205G	121.64	Inf	-Inf	114.56	3	Vertical	71	2.10	-	31.50	7.03	31.45			
AV	5.3185G	109.03	Inf	-Inf	101.95	3	Vertical	71	2.10	-	31.50	7.03	31.45			
PK	5.3532G	66.23	74.00	-7.77	59.14	3	Vertical	71	2.10	-	31.51	7.05	31.47			
AV	5.3508G	53.22	54.00	-0.78	46.14	3	Vertical	71	2.10	-	31.50	7.05	31.47			

5.25-5.35GHz_802.11ax HEW20_Nss1,(MCS0)_4TX

5320MHz_TX




EUT Y_4TX
Setting 20
06-D-G-4-10

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)			
PK	5.3184G	117.39	Inf	-Inf	110.31	3	Horizontal	98	2.05	-	31.50	7.03	31.45			
AV	5.3188G	106.25	Inf	-Inf	99.17	3	Horizontal	98	2.05	-	31.50	7.03	31.45			
PK	5.3535G	63.12	74.00	-10.88	56.02	3	Horizontal	98	2.05	-	31.51	7.06	31.47			
AV	5.3507G	51.07	54.00	-2.93	43.99	3	Horizontal	98	2.05	-	31.50	7.05	31.47			

5.25-5.35GHz_802.11ax HEW20_Nss1,(MCS0)_4TX

5320MHz_TX




EUT Y_4TX
Setting 20
06-D-J-8

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)			
PK	10.63494G	61.48	74.00	-12.52	43.68	3	Vertical	83	2.44	-	40.20	10.16	32.56			
AV	10.63704G	49.56	54.00	-4.44	31.76	3	Vertical	83	2.44	-	40.20	10.16	32.56			
PK	15.9607G	61.75	74.00	-12.25	44.11	3	Vertical	61	2.09	-	37.90	12.65	32.91			
AV	15.96042G	49.44	54.00	-4.56	31.80	3	Vertical	61	2.09	-	37.90	12.65	32.91			

5.25-5.35GHz_802.11ax HEW20_Nss1,(MCS0)_4TX

5320MHz_TX




EUT Y_4TX
Setting 20
06-D-J-8

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)			
PK	10.6365G	60.94	74.00	-13.06	43.14	3	Horizontal	288	1.59	-	40.20	10.16	32.56			
AV	10.63688G	50.11	54.00	-3.89	32.31	3	Horizontal	288	1.59	-	40.20	10.16	32.56			
PK	15.96406G	61.91	74.00	-12.09	44.27	3	Horizontal	241	1.13	-	37.90	12.65	32.91			
AV	15.95714G	49.53	54.00	-4.47	31.89	3	Horizontal	241	1.13	-	37.90	12.65	32.91			

5.47-5.725GHz_802.11ax HEW20_Nss1,(MCS0)_4TX

5500MHz_TX




EUT Y_4TX
Setting 20
06-D-G-4-10

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)			
PK	5.4585G	62.43	74.00	-11.57	55.01	3	Vertical	67	1.92	-	31.82	7.13	31.53			
AV	5.4597G	49.59	54.00	-4.41	42.17	3	Vertical	67	1.92	-	31.82	7.13	31.53			
PK	5.4699G	67.53	68.20	-0.67	60.08	3	Vertical	67	1.92	-	31.84	7.14	31.53			
PK	5.5023G	121.83	Inf	-Inf	114.32	3	Vertical	67	1.92	-	31.90	7.16	31.55			
AV	5.5011G	108.48	Inf	-Inf	100.97	3	Vertical	67	1.92	-	31.90	7.16	31.55			

5.47-5.725GHz_802.11ax HEW20_Nss1,(MCS0)_4TX

5500MHz_TX




EUT Y_4TX
Setting 20
06-D-G-4-10

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)			
PK	5.4581G	59.86	74.00	-14.14	52.44	3	Horizontal	102	1.98	-	31.82	7.13	31.53			
AV	5.4597G	48.11	54.00	-5.89	40.69	3	Horizontal	102	1.98	-	31.82	7.13	31.53			
PK	5.4683G	65.09	68.20	-3.11	57.65	3	Horizontal	102	1.98	-	31.84	7.13	31.53			
PK	5.4992G	117.67	Inf	-Inf	110.17	3	Horizontal	102	1.98	-	31.90	7.15	31.55			
AV	5.4982G	106.62	Inf	-Inf	99.12	3	Horizontal	102	1.98	-	31.90	7.15	31.55			

5.47-5.725GHz_802.11ax HEW20_Nss1,(MCS0)_4TX

5500MHz_TX




EUT Y_4TX
Setting 20
06-D-J-8

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)			
PK	10.99626G	62.79	74.00	-11.21	44.47	3	Vertical	280	1.43	-	40.51	10.33	32.52			
AV	10.99688G	51.87	54.00	-2.13	33.55	3	Vertical	280	1.43	-	40.51	10.33	32.52			
PK	16.4994G	64.62	68.20	-3.58	44.82	3	Vertical	282	1.03	-	39.70	12.89	32.79			

5.47-5.725GHz_802.11ax HEW20_Nss1,(MCS0)_4TX

5500MHz_TX




EUT Y_4TX
Setting 20
06-D-J-8

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)			
PK	10.99682G	63.81	74.00	-10.19	45.49	3	Horizontal	85	2.63	-	40.51	10.33	32.52			
AV	10.99668G	51.35	54.00	-2.65	33.03	3	Horizontal	85	2.63	-	40.51	10.33	32.52			
PK	16.50392G	64.62	68.20	-3.58	44.84	3	Horizontal	311	2.41	-	39.68	12.90	32.80			

5.47-5.725GHz_802.11ax HEW20_Nss1,(MCS0)_4TX

5580MHz_TX




EUT Y_4TX
Setting 23.5
06-D-G-4-10

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)			
PK	5.4456G	60.07	74.00	-13.93	52.69	3	Vertical	64	1.57	-	31.78	7.12	31.52			
AV	5.4224G	48.52	54.00	-5.48	41.24	3	Vertical	64	1.57	-	31.69	7.10	31.51			
PK	5.464G	59.49	68.20	-8.71	52.06	3	Vertical	64	1.57	-	31.83	7.13	31.53			
PK	5.5788G	123.85	Inf	-Inf	116.36	3	Vertical	64	1.57	-	31.84	7.21	31.56			
AV	5.5812G	112.20	Inf	-Inf	104.71	3	Vertical	64	1.57	-	31.84	7.21	31.56			
PK	5.7524G	61.20	68.20	-7.00	53.23	3	Vertical	64	1.57	-	32.20	7.35	31.58			

5.47-5.725GHz_802.11ax HEW20_Nss1,(MCS0)_4TX

5580MHz_TX




EUT_Y_4TX
Setting 23.5
06-D-G-4-10

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)			
PK	5.4168G	59.52	74.00	-14.48	52.26	3	Horizontal	103	1.23	-	31.67	7.10	31.51			
PK	5.4644G	57.82	68.20	-10.38	50.39	3	Horizontal	103	1.23	-	31.83	7.13	31.53			
AV	5.4568G	47.60	54.00	-6.40	40.19	3	Horizontal	103	1.23	-	31.81	7.13	31.53			
PK	5.5788G	122.03	Inf	-Inf	114.54	3	Horizontal	103	1.23	-	31.84	7.21	31.56			
AV	5.5784G	109.85	Inf	-Inf	102.36	3	Horizontal	103	1.23	-	31.84	7.21	31.56			
PK	5.748G	59.41	68.20	-8.79	51.45	3	Horizontal	103	1.23	-	32.19	7.35	31.58			

5.47-5.725GHz_802.11ax HEW20_Nss1,(MCS0)_4TX

5580MHz_TX




EUT Y_4TX
Setting 23.5
06-D-J-8

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)			
PK	11.1598G	65.75	74.00	-8.25	48.07	3	Vertical	130	1.27	-	39.88	10.41	32.61			
AV	11.1635G	53.25	54.00	-0.75	35.58	3	Vertical	130	1.27	-	39.87	10.41	32.61			
PK	16.73976G	68.10	68.20	-0.10	48.15	3	Vertical	88	2.59	-	40.14	13.00	33.19			

5.47-5.725GHz_802.11ax HEW20_Nss1,(MCS0)_4TX

5580MHz_TX




EUT Y_4TX
Setting 23.5
06-D-J-8

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)			
PK	11.16008G	66.79	74.00	-7.21	49.11	3	Horizontal	133	1.74	-	39.88	10.41	32.61			
AV	11.16164G	53.81	54.00	-0.19	36.13	3	Horizontal	133	1.74	-	39.88	10.41	32.61			
PK	16.7371G	68.04	68.20	-0.16	48.11	3	Horizontal	117	1.76	-	40.12	13.00	33.19			

5.47-5.725GHz_802.11ax HEW20_Nss1,(MCS0)_4TX

5700MHz_TX




EUT Y_4TX
Setting 17.5
06-D-G-4-10

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)			
PK	5.7005G	120.13	Inf	-Inf	112.49	3	Vertical	69	1.51	-	31.90	7.31	31.57			
AV	5.7005G	106.44	Inf	-Inf	98.80	3	Vertical	69	1.51	-	31.90	7.31	31.57			
PK	5.725G	67.57	68.20	-0.63	59.77	3	Vertical	69	1.51	-	32.05	7.33	31.58			

5.47-5.725GHz_802.11ax HEW20_Nss1,(MCS0)_4TX

5700MHz_TX




EUT Y_4TX
Setting 17.5
06-D-G-4-10

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)			
PK	5.6992G	114.89	Inf	-Inf	107.26	3	Horizontal	93	1.53	-	31.90	7.30	31.57			
AV	5.6981G	103.30	Inf	-Inf	95.68	3	Horizontal	93	1.53	-	31.89	7.30	31.57			
PK	5.725G	62.20	68.20	-6.00	54.40	3	Horizontal	93	1.53	-	32.05	7.33	31.58			

5.47-5.725GHz_802.11ax HEW20_Nss1,(MCS0)_4TX

5700MHz_TX




EUT Y_4TX
Setting 17.5
06-D-J-8

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)			
PK	11.402G	62.06	74.00	-11.94	44.28	3	Vertical	129	1.78	-	40.00	10.53	32.75			
AV	11.4012G	50.87	54.00	-3.13	33.08	3	Vertical	129	1.78	-	40.00	10.53	32.74			
PK	17.2992G	64.86	68.20	-3.34	43.98	3	Vertical	111	1.72	-	40.80	13.25	33.17			

5.47-5.725GHz_802.11ax HEW20_Nss1,(MCS0)_4TX

5700MHz_TX




EUT Y_4TX
Setting 17.5
06-D-J-8

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)			
PK	11.3996G	61.93	74.00	-12.07	44.15	3	Horizontal	69	1.31	-	40.00	10.52	32.74			
AV	11.4016G	50.42	54.00	-3.58	32.63	3	Horizontal	69	1.31	-	40.00	10.53	32.74			
PK	17.2508G	65.61	68.20	-2.59	45.12	3	Horizontal	193	1.22	-	40.50	13.23	33.24			

5.47-5.725GHz_802.11ax HEW20_Nss1,(MCS0)_4TX

5720MHz Straddle 5.47-5.725GHz_TX




EUT Y_4TX
Setting 24
06-D-G-4-10

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)			
PK	5.7224G	126.42	Inf	-Inf	118.65	3	Vertical	65	1.63	-	32.03	7.32	31.58			
AV	5.7212G	112.46	Inf	-Inf	104.69	3	Vertical	65	1.63	-	32.03	7.32	31.58			
PK	5.9156G	60.23	68.20	-7.97	51.86	3	Vertical	65	1.63	-	32.53	7.44	31.60			

5.47-5.725GHz_802.11ax HEW20_Nss1,(MCS0)_4TX

5720MHz Straddle 5.47-5.725GHz_TX




EUT Y_4TX
Setting 24
06-D-G-4-10

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)			
PK	5.7184G	120.15	Inf	-Inf	112.40	3	Horizontal	108	1.32	-	32.01	7.32	31.58			
AV	5.7184G	109.03	Inf	-Inf	101.28	3	Horizontal	108	1.32	-	32.01	7.32	31.58			
PK	5.8908G	60.09	68.20	-8.11	51.80	3	Horizontal	108	1.32	-	32.46	7.43	31.60			

5.47-5.725GHz_802.11ax HEW20_Nss1,(MCS0)_4TX

5720MHz Straddle 5.47-5.725GHz_TX




EUT Y_4TX
Setting 24
06-D-J-8

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)			
PK	11.4276G	66.20	74.00	-7.80	48.42	3	Vertical	126	1.73	-	40.00	10.54	32.76			
AV	11.4408G	53.89	54.00	-0.11	36.12	3	Vertical	126	1.73	-	40.00	10.54	32.77			
PK	17.3444G	67.77	68.20	-0.43	46.36	3	Vertical	83	1.58	-	41.24	13.27	33.10			

5.47-5.725GHz_802.11ax HEW20_Nss1,(MCS0)_4TX

5720MHz Straddle 5.47-5.725GHz_TX




EUT Y_4TX
Setting 24
06-D-J-8

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)			
PK	11.4436G	64.07	74.00	-9.93	46.29	3	Horizontal	133	1.62	-	40.00	10.55	32.77			
AV	11.44G	52.02	54.00	-1.98	34.25	3	Horizontal	133	1.62	-	40.00	10.54	32.77			
PK	17.3524G	65.98	68.20	-2.22	44.46	3	Horizontal	271	1.21	-	41.33	13.28	33.09			

5.725-5.85GHz_802.11ax HEW20_Nss1,(MCS0)_4TX

5745MHz_TX




EUT Y_4TX
Setting 23
06-D-G-4-10

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)			
PK	5.5945G	60.01	68.20	-8.19	52.54	3	Vertical	67	1.31	-	31.81	7.22	31.56			
PK	5.747G	126.54	Inf	-Inf	118.60	3	Vertical	67	1.31	-	32.18	7.34	31.58			
AV	5.7455G	112.69	Inf	-Inf	104.76	3	Vertical	67	1.31	-	32.17	7.34	31.58			
PK	5.9535G	59.70	68.20	-8.50	51.26	3	Vertical	67	1.31	-	32.59	7.45	31.60			

5.725-5.85GHz_802.11ax HEW20_Nss1,(MCS0)_4TX

5745MHz_TX




EUT Y_4TX
Setting 23
06-D-G-4-10

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)			
PK	5.5645G	58.66	68.20	-9.54	51.15	3	Horizontal	94	1.41	-	31.87	7.20	31.56			
PK	5.7405G	121.07	Inf	-Inf	113.17	3	Horizontal	94	1.41	-	32.14	7.34	31.58			
AV	5.7435G	109.25	Inf	-Inf	101.33	3	Horizontal	94	1.41	-	32.16	7.34	31.58			
PK	5.945G	59.09	68.20	-9.11	50.65	3	Horizontal	94	1.41	-	32.59	7.45	31.60			

5.725-5.85GHz_802.11ax HEW20_Nss1,(MCS0)_4TX

5745MHz_TX




EUT Y_4TX
Setting 23
06-D-J-8

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)			
PK	11.49018G	65.84	74.00	-8.16	47.98	3	Vertical	125	1.65	-	40.08	10.57	32.79			
AV	11.48958G	53.60	54.00	-0.40	35.74	3	Vertical	125	1.65	-	40.08	10.57	32.79			
PK	17.23436G	67.07	68.20	-1.13	46.58	3	Vertical	83	1.41	-	40.53	13.23	33.27			

5.725-5.85GHz_802.11ax HEW20_Nss1,(MCS0)_4TX

5745MHz_TX




EUT Y_4TX
Setting 23
06-D-J-8

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)			
PK	11.49716G	65.22	74.00	-8.78	47.36	3	Horizontal	244	1.41	-	40.09	10.57	32.80			
AV	11.489G	52.47	54.00	-1.53	34.61	3	Horizontal	244	1.41	-	40.08	10.57	32.79			
PK	17.22604G	67.87	68.20	-0.33	47.38	3	Horizontal	121	1.07	-	40.55	13.22	33.28			

5.725-5.85GHz_802.11ax HEW20_Nss1,(MCS0)_4TX

5785MHz_TX




EUT Y_4TX
Setting 22.5
06-D-G-4-10

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)			
PK	5.6335G	59.92	68.20	-8.28	52.51	3	Vertical	66	1.42	-	31.73	7.25	31.57			
PK	5.784G	123.13	Inf	-Inf	115.06	3	Vertical	66	1.42	-	32.27	7.38	31.58			
AV	5.7885G	112.16	Inf	-Inf	104.08	3	Vertical	66	1.42	-	32.28	7.38	31.58			
PK	5.9345G	60.14	68.20	-8.06	51.73	3	Vertical	66	1.42	-	32.57	7.44	31.60			

5.725-5.85GHz_802.11ax HEW20_Nss1,(MCS0)_4TX

5785MHz_TX




EUT Y_4TX
Setting 22.5
06-D-G-4-10

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)			
PK	5.6155G	59.89	68.20	-8.31	52.45	3	Horizontal	92	1.76	-	31.77	7.23	31.56			
PK	5.7875G	121.15	Inf	-Inf	113.08	3	Horizontal	92	1.76	-	32.27	7.38	31.58			
AV	5.7845G	108.78	Inf	-Inf	100.71	3	Horizontal	92	1.76	-	32.27	7.38	31.58			
PK	5.948G	61.72	68.20	-6.48	53.27	3	Horizontal	92	1.76	-	32.60	7.45	31.60			

5.725-5.85GHz_802.11ax HEW20_Nss1,(MCS0)_4TX

5785MHz_TX




EUT Y_4TX
Setting 22.5
06-D-J-8

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)			
PK	11.56868G	66.30	74.00	-7.70	48.53	3	Vertical	129	2.01	-	39.99	10.61	32.83			
AV	11.57118G	53.08	54.00	-0.92	35.33	3	Vertical	129	2.01	-	39.97	10.61	32.83			
PK	17.36066G	68.17	68.20	-0.03	46.53	3	Vertical	46	2.51	-	41.43	13.28	33.07			

5.725-5.85GHz_802.11ax HEW20_Nss1,(MCS0)_4TX

5785MHz_TX




EUT Y_4TX
Setting 22.5
06-D-J-8

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)			
PK	11.57114G	65.34	74.00	-8.66	47.59	3	Horizontal	207	2.21	-	39.97	10.61	32.83			
AV	11.57266G	52.09	54.00	-1.91	34.35	3	Horizontal	207	2.21	-	39.96	10.61	32.83			
PK	17.35958G	68.10	68.20	-0.10	46.49	3	Horizontal	40	2.93	-	41.41	13.28	33.08			

5.725-5.85GHz_802.11ax HEW20_Nss1,(MCS0)_4TX

5825MHz_TX




EUT Y_4TX
Setting 22.5
06-D-G-4-10

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)			
PK	5.628G	59.77	68.20	-8.43	52.36	3	Vertical	67	1.43	-	31.74	7.24	31.57			
PK	5.8275G	123.70	Inf	-Inf	115.59	3	Vertical	67	1.43	-	32.30	7.40	31.59			
AV	5.824G	112.34	Inf	-Inf	104.23	3	Vertical	67	1.43	-	32.30	7.40	31.59			
PK	5.938G	60.88	68.20	-7.32	52.45	3	Vertical	67	1.43	-	32.58	7.45	31.60			

5.725-5.85GHz_802.11ax HEW20_Nss1,(MCS0)_4TX

5825MHz_TX




EUT Y_4TX
Setting 22.5
06-D-G-4-10

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)			
PK	5.607G	60.09	68.20	-8.11	52.63	3	Horizontal	27	1.99	-	31.79	7.23	31.56			
PK	5.825G	120.72	Inf	-Inf	112.61	3	Horizontal	27	1.99	-	32.30	7.40	31.59			
AV	5.8245G	109.41	Inf	-Inf	101.30	3	Horizontal	27	1.99	-	32.30	7.40	31.59			
PK	6.075G	60.24	68.20	-7.96	51.56	3	Horizontal	27	1.99	-	32.60	7.53	31.45			

5.725-5.85GHz_802.11ax HEW20_Nss1,(MCS0)_4TX

5825MHz_TX




EUT Y_4TX
Setting 22.5
06-D-J-8

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)			
PK	11.64646G	65.01	74.00	-8.99	58.22	3	Vertical	122	1.80	-	39.43	10.64	43.28			
AV	11.64694G	52.39	54.00	-1.61	45.61	3	Vertical	122	1.80	-	39.42	10.64	43.28			
PK	17.695G	64.50	68.20	-3.70	48.50	3	Vertical	51	3.00	-	44.24	13.43	41.67			

5.725-5.85GHz_802.11ax HEW20_Nss1,(MCS0)_4TX

5825MHz_TX




EUT Y_4TX
Setting 22.5
06-D-J-8

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	11.6535G	63.34	74.00	-10.66	56.58	3	Horizontal	244	1.62	-	39.39	10.65	43.28			
AV	11.6545G	51.45	54.00	-2.55	44.70	3	Horizontal	244	1.62	-	39.38	10.65	43.28			
PK	17.4741G	68.02	68.20	-0.18	54.23	3	Horizontal	122	1.05	-	42.44	13.33	41.98			

5.15-5.25GHz_802.11ax HEW40_Nss1,(MCS0)_4TX

5190MHz_TX




EUT Y_4TX
Setting 16.5
06-D-J-8-10

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)			
PK	5.1486G	65.31	74.00	-8.69	57.66	3	Vertical	91	1.38	-	32.10	6.91	31.36			
AV	5.15G	53.19	54.00	-0.81	45.53	3	Vertical	91	1.38	-	32.10	6.92	31.36			
PK	5.187G	115.86	Inf	-Inf	108.43	3	Vertical	91	1.38	-	31.88	6.93	31.38			
AV	5.1888G	104.17	Inf	-Inf	96.75	3	Vertical	91	1.38	-	31.87	6.93	31.38			

5.15-5.25GHz_802.11ax HEW40_Nss1,(MCS0)_4TX

5190MHz_TX




EUT_Y_4TX
Setting 16.5
06-D-J-8-10

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)			
PK	5.1488G	63.46	74.00	-10.54	55.81	3	Horizontal	90	1.42	-	32.10	6.91	31.36			
AV	5.1488G	51.37	54.00	-2.63	43.72	3	Horizontal	90	1.42	-	32.10	6.91	31.36			
PK	5.1942G	111.94	Inf	-Inf	104.55	3	Horizontal	90	1.42	-	31.83	6.94	31.38			
AV	5.1892G	100.99	Inf	-Inf	93.58	3	Horizontal	90	1.42	-	31.86	6.93	31.38			

5.15-5.25GHz_802.11ax HEW40_Nss1,(MCS0)_4TX

5190MHz_TX




EUT Y_4TX
Setting 16.5
06-D-J-8

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	10.4728G	59.21	68.20	-8.99	41.55	3	Vertical	344	1.34	-	40.15	10.08	32.57			
PK	15.564G	60.92	74.00	-13.08	42.47	3	Vertical	360	1.80	-	38.82	12.46	32.83			
AV	15.4778G	49.25	54.00	-4.75	30.56	3	Vertical	360	1.80	-	39.09	12.42	32.82			

5.15-5.25GHz_802.11ax HEW40_Nss1,(MCS0)_4TX

5190MHz_TX




EUT Y_4TX
Setting 16.5
06-D-J-8

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)			
PK	10.417G	58.28	68.20	-9.92	40.67	3	Horizontal	159	1.05	-	40.13	10.06	32.58			
PK	15.525G	60.90	74.00	-13.10	42.34	3	Horizontal	345	3.00	-	38.95	12.44	32.83			
AV	15.516G	49.04	54.00	-4.96	30.45	3	Horizontal	345	3.00	-	38.97	12.44	32.82			

5.15-5.25GHz_802.11ax HEW40_Nss1,(MCS0)_4TX

5230MHz_TX




EUT Y_4TX
Setting 21
06-D-J-8-10

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)			
PK	5.1499G	72.71	74.00	-1.29	65.06	3	Vertical	71	2.29	-	32.10	6.91	31.36			
AV	5.1496G	53.97	54.00	-0.03	46.32	3	Vertical	71	2.29	-	32.10	6.91	31.36			
PK	5.2267G	120.24	Inf	-Inf	112.99	3	Vertical	71	2.29	-	31.69	6.96	31.40			
AV	5.2312G	108.39	Inf	-Inf	101.15	3	Vertical	71	2.29	-	31.68	6.96	31.40			
PK	5.3524G	60.88	74.00	-13.12	53.80	3	Vertical	71	2.29	-	31.50	7.05	31.47			
AV	5.3515G	48.63	54.00	-5.37	41.55	3	Vertical	71	2.29	-	31.50	7.05	31.47			

5.15-5.25GHz_802.11ax_HEW40_Nss1,(MCS0)_4TX

5230MHz_TX




EUT_Y_4TX
Setting 21
06-D-J-8-10

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)			
PK	5.1466G	67.08	74.00	-6.92	59.43	3	Horizontal	91	1.37	-	32.10	6.91	31.36			
AV	5.149G	50.97	54.00	-3.03	43.32	3	Horizontal	91	1.37	-	32.10	6.91	31.36			
PK	5.2291G	116.31	Inf	-Inf	109.07	3	Horizontal	91	1.37	-	31.68	6.96	31.40			
AV	5.2288G	105.15	Inf	-Inf	97.91	3	Horizontal	91	1.37	-	31.68	6.96	31.40			
PK	5.3653G	58.65	74.00	-15.35	51.54	3	Horizontal	91	1.37	-	31.53	7.06	31.48			
AV	5.3659G	47.14	54.00	-6.86	40.03	3	Horizontal	91	1.37	-	31.53	7.06	31.48			

5.15-5.25GHz_802.11ax HEW40_Nss1,(MCS0)_4TX

5230MHz_TX




EUT Y_4TX
Setting 21
06-D-J-8

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	15.68943G	62.13	74.00	-11.87	44.29	3	Vertical	240	2.90	-	38.18	12.52	32.86			
AV	15.69311G	49.79	54.00	-4.21	31.94	3	Vertical	240	2.90	-	38.19	12.52	32.86			

5.15-5.25GHz_802.11ax HEW40_Nss1,(MCS0)_4TX

5230MHz_TX




EUT Y_4TX
Setting 21
06-D-J-8

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	15.69361G	62.33	74.00	-11.67	44.48	3	Horizontal	82	2.99	-	38.19	12.52	32.86			
AV	15.68536G	49.87	54.00	-4.13	32.04	3	Horizontal	82	2.99	-	38.17	12.52	32.86			

5.25-5.35GHz_802.11ax HEW40_Nss1,(MCS0)_4TX

5270MHz_TX




EUT Y_4TX
Setting 22
06-D-J-8-10

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)			
PK	5.15G	64.57	74.00	-9.43	56.91	3	Vertical	76	1.67	-	32.10	6.92	31.36			
AV	5.1479G	49.12	54.00	-4.88	41.47	3	Vertical	76	1.67	-	32.10	6.91	31.36			
PK	5.2691G	119.04	Inf	-Inf	111.92	3	Vertical	76	1.67	-	31.56	6.99	31.43			
AV	5.2709G	108.30	Inf	-Inf	101.18	3	Vertical	76	1.67	-	31.56	6.99	31.43			
PK	5.35G	68.12	74.00	-5.88	61.04	3	Vertical	76	1.67	-	31.50	7.05	31.47			
AV	5.35G	53.14	54.00	-0.86	46.06	3	Vertical	76	1.67	-	31.50	7.05	31.47			

5.25-5.35GHz_802.11ax HEW40_Nss1,(MCS0)_4TX

5270MHz_TX




EUT_Y_4TX
Setting 22
06-D-J-8-10

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)			
PK	5.1443G	62.28	74.00	-11.72	54.63	3	Horizontal	99	2.32	-	32.10	6.91	31.36			
AV	5.1395G	48.10	54.00	-5.90	40.45	3	Horizontal	99	2.32	-	32.10	6.91	31.36			
PK	5.2709G	117.30	Inf	-Inf	110.18	3	Horizontal	99	2.32	-	31.56	6.99	31.43			
AV	5.2691G	106.16	Inf	-Inf	99.04	3	Horizontal	99	2.32	-	31.56	6.99	31.43			
PK	5.351G	66.34	74.00	-7.66	59.26	3	Horizontal	99	2.32	-	31.50	7.05	31.47			
AV	5.3513G	51.78	54.00	-2.22	44.70	3	Horizontal	99	2.32	-	31.50	7.05	31.47			

5.25-5.35GHz_802.11ax_HEW40_Nss1,(MCS0)_4TX

5270MHz_TX




EUT_Y_4TX
Setting 22
06-D-J-8

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	15.80715G	61.65	74.00	-12.35	43.68	3	Vertical	235	1.59	-	38.27	12.58	32.88			
AV	15.81003G	49.93	54.00	-4.07	31.97	3	Vertical	235	1.59	-	38.26	12.58	32.88			

5.25-5.35GHz_802.11ax_HEW40_Nss1,(MCS0)_4TX

5270MHz_TX




EUT_Y_4TX
Setting 22
06-D-J-8

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	15.81469G	62.01	74.00	-11.99	44.07	3	Horizontal	114	1.93	-	38.24	12.58	32.88			
AV	15.81024G	49.68	54.00	-4.32	31.72	3	Horizontal	114	1.93	-	38.26	12.58	32.88			

5.25-5.35GHz_802.11ax HEW40_Nss1,(MCS0)_4TX

5310MHz_TX




EUT Y_4TX
Setting 18
06-D-J-8-10

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)			
PK	5.3114G	116.14	Inf	-Inf	109.07	3	Vertical	69	2.14	-	31.50	7.02	31.45			
AV	5.311G	104.48	Inf	-Inf	97.41	3	Vertical	69	2.14	-	31.50	7.02	31.45			
PK	5.3508G	66.99	74.00	-7.01	59.91	3	Vertical	69	2.14	-	31.50	7.05	31.47			
AV	5.35G	53.75	54.00	-0.25	46.67	3	Vertical	69	2.14	-	31.50	7.05	31.47			

5.25-5.35GHz_802.11ax_HEW40_Nss1,(MCS0)_4TX

5310MHz_TX




EUT Y_4TX
Setting 18
06-D-J-8-10

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)			
PK	5.3112G	113.14	Inf	-Inf	106.07	3	Horizontal	106	2.38	-	31.50	7.02	31.45			
AV	5.3088G	101.24	Inf	-Inf	94.17	3	Horizontal	106	2.38	-	31.50	7.02	31.45			
PK	5.3506G	63.49	74.00	-10.51	56.41	3	Horizontal	106	2.38	-	31.50	7.05	31.47			
AV	5.35G	51.81	54.00	-2.19	44.73	3	Horizontal	106	2.38	-	31.50	7.05	31.47			

5.25-5.35GHz_802.11ax_HEW40_Nss1,(MCS0)_4TX

5310MHz_TX




EUT Y_4TX
Setting 18
06-D-J-8

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	15.92774G	61.68	74.00	-12.32	44.01	3	Vertical	208	1.78	-	37.94	12.64	32.91			
AV	15.93254G	49.32	54.00	-4.68	31.66	3	Vertical	208	1.78	-	37.93	12.64	32.91			

5.25-5.35GHz_802.11ax HEW40_Nss1,(MCS0)_4TX

5310MHz_TX




EUT Y_4TX
Setting 18
06-D-J-8

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	15.93448G	61.60	74.00	-12.40	43.94	3	Horizontal	245	2.65	-	37.93	12.64	32.91			
AV	15.93187G	49.15	54.00	-4.85	31.48	3	Horizontal	245	2.65	-	37.94	12.64	32.91			

5.47-5.725GHz_802.11ax HEW40_Nss1,(MCS0)_4TX

5510MHz_TX




EUT_Y_4TX
Setting 18.5
06-D-J-8-10

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)			
PK	5.46G	60.62	74.00	-13.38	53.20	3	Vertical	68	1.99	-	31.82	7.13	31.53			
AV	5.4596G	49.85	54.00	-4.15	42.43	3	Vertical	68	1.99	-	31.82	7.13	31.53			
PK	5.4686G	67.43	68.20	-0.77	59.99	3	Vertical	68	1.99	-	31.84	7.13	31.53			
PK	5.5114G	116.60	Inf	-Inf	109.09	3	Vertical	68	1.99	-	31.90	7.16	31.55			
AV	5.5076G	105.06	Inf	-Inf	97.55	3	Vertical	68	1.99	-	31.90	7.16	31.55			

5.47-5.725GHz_802.11ax HEW40_Nss1,(MCS0)_4TX

5510MHz_TX




EUT_Y_4TX
Setting 18.5
06-D-J-8-10

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)			
PK	5.4562G	61.25	74.00	-12.75	53.84	3	Horizontal	105	1.42	-	31.81	7.13	31.53			
AV	5.459G	49.33	54.00	-4.67	41.91	3	Horizontal	105	1.42	-	31.82	7.13	31.53			
PK	5.4698G	65.81	68.20	-2.39	58.36	3	Horizontal	105	1.42	-	31.84	7.14	31.53			
PK	5.5114G	113.11	Inf	-Inf	105.60	3	Horizontal	105	1.42	-	31.90	7.16	31.55			
AV	5.5108G	101.78	Inf	-Inf	94.27	3	Horizontal	105	1.42	-	31.90	7.16	31.55			

5.47-5.725GHz_802.11ax HEW40_Nss1,(MCS0)_4TX

5510MHz_TX




EUT Y_4TX
Setting 18.5
06-D-J-8

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	11.02445G	60.60	74.00	-13.40	42.38	3	Vertical	265	2.09	-	40.40	10.35	32.53			
AV	11.02049G	47.60	54.00	-6.40	29.37	3	Vertical	265	2.09	-	40.42	10.34	32.53			

5.47-5.725GHz_802.11ax HEW40_Nss1,(MCS0)_4TX

5510MHz_TX




EUT Y_4TX
Setting 18.5
06-D-J-8

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	11.01578G	59.83	74.00	-14.17	41.58	3	Horizontal	111	2.51	-	40.44	10.34	32.53			
AV	11.02004G	48.03	54.00	-5.97	29.80	3	Horizontal	111	2.51	-	40.42	10.34	32.53			

5.47-5.725GHz_802.11ax HEW40_Nss1,(MCS0)_4TX

5550MHz_TX




EUT Y_4TX
Setting 20
06-D-J-8-10

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)			
PK	5.46G	68.61	74.00	-5.39	61.19	3	Vertical	68	1.97	-	31.82	7.13	31.53			
AV	5.46G	49.81	54.00	-4.19	42.39	3	Vertical	68	1.97	-	31.82	7.13	31.53			
PK	5.4636G	68.04	68.20	-0.16	60.61	3	Vertical	68	1.97	-	31.83	7.13	31.53			
PK	5.5515G	118.32	Inf	-Inf	110.79	3	Vertical	68	1.97	-	31.90	7.19	31.56			
AV	5.547G	106.54	Inf	-Inf	99.01	3	Vertical	68	1.97	-	31.90	7.19	31.56			

5.47-5.725GHz_802.11ax HEW40_Nss1,(MCS0)_4TX

5550MHz_TX




EUT_Y_4TX
Setting 20
06-D-J-8-10

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)			
PK	5.46G	61.44	74.00	-12.56	54.02	3	Horizontal	99	2.14	-	31.82	7.13	31.53			
AV	5.46G	47.66	54.00	-6.34	40.24	3	Horizontal	99	2.14	-	31.82	7.13	31.53			
PK	5.4666G	63.33	68.20	-4.87	55.90	3	Horizontal	99	2.14	-	31.83	7.13	31.53			
PK	5.5464G	115.62	Inf	-Inf	108.09	3	Horizontal	99	2.14	-	31.90	7.19	31.56			
AV	5.5491G	103.96	Inf	-Inf	96.43	3	Horizontal	99	2.14	-	31.90	7.19	31.56			

5.47-5.725GHz_802.11ax HEW40_Nss1,(MCS0)_4TX

5550MHz_TX




EUT Y_4TX
Setting 20
06-D-J-8

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	11.10489G	59.82	74.00	-14.18	41.94	3	Vertical	272	1.10	-	40.08	10.38	32.58			
AV	11.1047G	47.27	54.00	-6.73	29.39	3	Vertical	272	1.10	-	40.08	10.38	32.58			

5.47-5.725GHz_802.11ax HEW40_Nss1,(MCS0)_4TX

5550MHz_TX




EUT Y_4TX
Setting 20
06-D-J-8

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)			
PK	11.09553G	60.13	74.00	-13.87	42.20	3	Horizontal	86	1.63	-	40.12	10.38	32.57			
AV	11.10479G	47.67	54.00	-6.33	29.79	3	Horizontal	86	1.63	-	40.08	10.38	32.58			

5.47-5.725GHz_802.11ax HEW40_Nss1,(MCS0)_4TX

5670MHz_TX




EUT_Y_4TX
Setting 20
06-D-J-8-10

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)			
PK	5.6718G	117.96	Inf	-Inf	110.46	3	Vertical	67	1.80	-	31.79	7.28	31.57			
AV	5.6692G	106.62	Inf	-Inf	99.13	3	Vertical	67	1.80	-	31.78	7.28	31.57			
PK	5.7254G	67.32	68.20	-0.88	59.52	3	Vertical	67	1.80	-	32.05	7.33	31.58			

5.47-5.725GHz_802.11ax HEW40_Nss1,(MCS0)_4TX

5670MHz_TX




EUT_Y_4TX
Setting 20
06-D-J-8-10

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)			
PK	5.6708G	114.38	Inf	-Inf	106.89	3	Horizontal	98	1.35	-	31.78	7.28	31.57			
AV	5.6734G	103.37	Inf	-Inf	95.87	3	Horizontal	98	1.35	-	31.79	7.28	31.57			
PK	5.729G	62.66	68.20	-5.54	54.84	3	Horizontal	98	1.35	-	32.07	7.33	31.58			

5.47-5.725GHz_802.11ax HEW40_Nss1,(MCS0)_4TX

5670MHz_TX




EUT Y_4TX
Setting 20
06-D-J-8

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	11.33925G	60.26	74.00	-13.74	42.59	3	Vertical	22	1.30	-	39.88	10.50	32.71			
AV	11.33513G	47.31	54.00	-6.69	29.66	3	Vertical	22	1.30	-	39.87	10.49	32.71			

5.47-5.725GHz_802.11ax HEW40_Nss1,(MCS0)_4TX

5670MHz_TX




EUT Y_4TX
Setting 20
06-D-J-8

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)			
PK	11.3367G	59.74	74.00	-14.26	42.09	3	Horizontal	333	2.74	-	39.87	10.49	32.71			
AV	11.33964G	47.37	54.00	-6.63	29.70	3	Horizontal	333	2.74	-	39.88	10.50	32.71			

5.47-5.725GHz_802.11ax HEW40_Nss1,(MCS0)_4TX

5710MHz Straddle 5.47-5.725GHz_TX




EUT Y_4TX
Setting 24.5
06-D-J-8-10

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)			
PK	5.7064G	121.55	Inf	-Inf	113.87	3	Vertical	66	1.58	-	31.94	7.31	31.57			
AV	5.7092G	110.66	Inf	-Inf	102.97	3	Vertical	66	1.58	-	31.96	7.31	31.58			
PK	5.8588G	66.20	68.20	-2.00	58.04	3	Vertical	66	1.58	-	32.34	7.41	31.59			

5.47-5.725GHz_802.11ax HEW40_Nss1,(MCS0)_4TX

5710MHz Straddle 5.47-5.725GHz_TX




EUT Y_4TX
Setting 24.5
06-D-J-8-10

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)			
PK	5.7136G	119.19	Inf	-Inf	111.47	3	Horizontal	91	1.72	-	31.98	7.32	31.58			
AV	5.7112G	106.96	Inf	-Inf	99.26	3	Horizontal	91	1.72	-	31.97	7.31	31.58			
PK	5.8524G	66.31	68.20	-1.89	58.18	3	Horizontal	91	1.72	-	32.31	7.41	31.59			

5.47-5.725GHz_802.11ax HEW40_Nss1,(MCS0)_4TX

5710MHz Straddle 5.47-5.725GHz_TX




EUT Y_4TX
Setting 20
06-D-J-8

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	11.42014G	60.38	74.00	-13.62	42.61	3	Vertical	103	2.29	-	40.00	10.53	32.76			
AV	11.42018G	47.25	54.00	-6.75	29.48	3	Vertical	103	2.29	-	40.00	10.53	32.76			

5.47-5.725GHz_802.11ax HEW40_Nss1,(MCS0)_4TX

5710MHz Straddle 5.47-5.725GHz_TX




EUT Y_4TX
Setting 20
06-D-J-8

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	11.42308G	60.31	74.00	-13.69	42.53	3	Horizontal	127	1.27	-	40.00	10.54	32.76			
AV	11.42355G	47.32	54.00	-6.68	29.54	3	Horizontal	127	1.27	-	40.00	10.54	32.76			

5.725-5.85GHz_802.11ax HEW40_Nss1,(MCS0)_4TX

5755MHz_TX




EUT Y_4TX
Setting 23
06-D-J-8-10

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)			
PK	5.651G	65.98	68.94	-2.96	58.59	3	Vertical	68	1.40	-	31.70	7.26	31.57			
PK	5.7535G	122.20	Inf	-Inf	114.22	3	Vertical	68	1.40	-	32.21	7.35	31.58			
AV	5.754G	111.23	Inf	-Inf	103.25	3	Vertical	68	1.40	-	32.21	7.35	31.58			
PK	5.924G	62.15	68.94	-6.79	53.76	3	Vertical	68	1.40	-	32.55	7.44	31.60			

5.725-5.85GHz_802.11ax HEW40_Nss1,(MCS0)_4TX

5755MHz_TX




EUT Y_4TX
Setting 23
06-D-J-8-10

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)			
PK	5.6485G	61.14	68.20	-7.06	53.75	3	Horizontal	93	1.37	-	31.70	7.26	31.57			
PK	5.7585G	119.06	Inf	-Inf	111.07	3	Horizontal	93	1.37	-	32.22	7.35	31.58			
AV	5.757G	107.54	Inf	-Inf	99.56	3	Horizontal	93	1.37	-	32.21	7.35	31.58			
PK	5.939G	60.51	68.20	-7.69	52.08	3	Horizontal	93	1.37	-	32.58	7.45	31.60			

5.725-5.85GHz_802.11ax HEW40_Nss1,(MCS0)_4TX

5755MHz_TX




EUT Y_4TX
Setting 23
06-D-S-5

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)			
PK	11.50442G	63.14	74.00	-10.86	45.27	3	Vertical	124	1.46	-	40.10	10.57	32.80			
AV	11.5086G	50.67	54.00	-3.33	32.79	3	Vertical	124	1.46	-	40.10	10.58	32.80			
PK	17.26646G	65.08	68.20	-3.12	44.46	3	Vertical	80	1.52	-	40.60	13.24	33.22			

5.725-5.85GHz_802.11ax HEW40_Nss1,(MCS0)_4TX

5755MHz_TX




EUT Y_4TX
Setting 23
06-D-S-5

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)			
PK	11.51756G	60.81	74.00	-13.19	42.94	3	Horizontal	307	2.09	-	40.10	10.58	32.81			
AV	11.50208G	47.91	54.00	-6.09	30.04	3	Horizontal	307	2.09	-	40.10	10.57	32.80			
PK	17.2636G	67.84	68.20	-0.36	47.24	3	Horizontal	124	1.11	-	40.58	13.24	33.22			

5.725-5.85GHz_802.11ax HEW40_Nss1,(MCS0)_4TX

5795MHz_TX




EUT_Y_4TX
Setting 22.5
06-D-J-8-10

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)			
PK	5.6475G	60.17	68.20	-8.03	52.77	3	Vertical	110	1.44	-	31.71	7.26	31.57			
PK	5.7985G	122.28	Inf	-Inf	114.18	3	Vertical	110	1.44	-	32.30	7.39	31.59			
AV	5.7935G	111.01	Inf	-Inf	102.93	3	Vertical	110	1.44	-	32.29	7.38	31.59			
PK	5.9245G	65.73	68.57	-2.84	57.34	3	Vertical	110	1.44	-	32.55	7.44	31.60			

5.725-5.85GHz_802.11ax HEW40_Nss1,(MCS0)_4TX

5795MHz_TX




EUT_Y_4TX
Setting 22.5
06-D-J-8-10

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)			
PK	5.6005G	59.87	68.20	-8.33	52.41	3	Horizontal	95	1.80	-	31.80	7.22	31.56			
PK	5.796G	118.21	Inf	-Inf	110.12	3	Horizontal	95	1.80	-	32.29	7.39	31.59			
AV	5.794G	107.47	Inf	-Inf	99.39	3	Horizontal	95	1.80	-	32.29	7.38	31.59			
PK	5.9255G	62.66	68.20	-5.54	54.27	3	Horizontal	95	1.80	-	32.55	7.44	31.60			

5.725-5.85GHz_802.11ax HEW40_Nss1,(MCS0)_4TX

5795MHz_TX




EUT Y_4TX
Setting 22.5
06-D-J-8

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)			
PK	11.59603G	63.37	74.00	-10.63	56.21	3	Vertical	124	1.75	-	39.82	10.62	43.28			
AV	11.57872G	51.29	54.00	-2.71	44.04	3	Vertical	124	1.75	-	39.93	10.61	43.29			
PK	17.38875G	62.29	68.20	-5.91	49.24	3	Vertical	29	1.80	-	41.76	13.29	42.00			

5.725-5.85GHz_802.11ax HEW40_Nss1,(MCS0)_4TX

5795MHz_TX




EUT Y_4TX
Setting 22.5
06-D-J-8

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)			
PK	11.59726G	63.15	74.00	-10.85	55.99	3	Horizontal	245	1.31	-	39.82	10.62	43.28			
AV	11.59558G	50.78	54.00	-3.22	43.61	3	Horizontal	245	1.31	-	39.83	10.62	43.28			
PK	17.37726G	67.95	68.20	-0.25	55.03	3	Horizontal	122	1.07	-	41.63	13.29	42.00			

5.15-5.25GHz_802.11ax HEW80_Nss1,(MCS0)_4TX

5210MHz_TX




EUT Y_4TX
Setting 15
06-D-S-5-10

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)			
PK	5.1455G	65.53	74.00	-8.47	57.88	3	Vertical	67	1.98	-	32.10	6.91	31.36			
AV	5.15G	53.99	54.00	-0.01	46.33	3	Vertical	67	1.98	-	32.10	6.92	31.36			
PK	5.204G	111.44	Inf	-Inf	104.11	3	Vertical	67	1.98	-	31.78	6.94	31.39			
AV	5.2115G	99.55	Inf	-Inf	92.24	3	Vertical	67	1.98	-	31.75	6.95	31.39			
PK	5.4245G	59.34	74.00	-14.66	52.04	3	Vertical	67	1.98	-	31.70	7.11	31.51			
AV	5.4275G	47.78	54.00	-6.22	40.47	3	Vertical	67	1.98	-	31.71	7.11	31.51			

5.15-5.25GHz_802.11ax HEW80_Nss1,(MCS0)_4TX

5210MHz_TX




EUT Y_4TX
Setting 15
06-D-S-5-10

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)			
PK	5.15G	65.39	74.00	-8.61	57.73	3	Horizontal	84	1.37	-	32.10	6.92	31.36			
AV	5.1495G	52.39	54.00	-1.61	44.74	3	Horizontal	84	1.37	-	32.10	6.91	31.36			
PK	5.204G	107.33	Inf	-Inf	100.00	3	Horizontal	84	1.37	-	31.78	6.94	31.39			
AV	5.212G	96.28	Inf	-Inf	88.97	3	Horizontal	84	1.37	-	31.75	6.95	31.39			
PK	5.4505G	59.47	74.00	-14.53	52.07	3	Horizontal	84	1.37	-	31.80	7.12	31.52			
AV	5.442G	47.50	54.00	-6.50	40.13	3	Horizontal	84	1.37	-	31.77	7.12	31.52			

5.15-5.25GHz_802.11ax HEW80_Nss1,(MCS0)_4TX

5210MHz_TX




EUT Y_4TX
Setting 15
06-D-S-5

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	15.62615G	62.10	74.00	-11.90	44.12	3	Vertical	354	2.32	-	38.34	12.49	32.85			
AV	15.63132G	49.70	54.00	-4.30	31.77	3	Vertical	354	2.32	-	38.29	12.49	32.85			

5.15-5.25GHz_802.11ax HEW80_Nss1,(MCS0)_4TX

5210MHz_TX




EUT Y_4TX
Setting 16.5
06-D-S-5

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	15.63203G	62.26	74.00	-11.74	44.33	3	Horizontal	157	1.25	-	38.28	12.50	32.85			
AV	15.63256G	49.80	54.00	-4.20	31.88	3	Horizontal	157	1.25	-	38.27	12.50	32.85			

5.25-5.35GHz_802.11ax HEW80_Nss1,(MCS0)_4TX

5290MHz_TX




EUT Y_4TX
Setting 16
06-D-S-5-10

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)			
PK	5.08G	59.22	74.00	-14.78	51.60	3	Vertical	63	2.20	-	32.06	6.88	31.32			
AV	5.117G	48.05	54.00	-5.95	40.39	3	Vertical	63	2.20	-	32.10	6.90	31.34			
PK	5.295G	112.07	Inf	-Inf	104.99	3	Vertical	63	2.20	-	31.51	7.01	31.44			
AV	5.2905G	99.41	Inf	-Inf	92.32	3	Vertical	63	2.20	-	31.52	7.01	31.44			
PK	5.35G	64.89	74.00	-9.11	57.81	3	Vertical	63	2.20	-	31.50	7.05	31.47			
AV	5.3505G	53.74	54.00	-0.26	46.66	3	Vertical	63	2.20	-	31.50	7.05	31.47			
PK	5.5255G	59.85	68.20	-8.35	52.33	3	Vertical	63	2.20	-	31.90	7.17	31.55			

5.25-5.35GHz_802.11ax HEW80_Nss1,(MCS0)_4TX

5290MHz_TX




EUT_Y_4TX
Setting 16
06-D-S-5-10

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)			
PK	5.1135G	59.21	74.00	-14.79	51.55	3	Horizontal	98	2.26	-	32.10	6.90	31.34			
AV	5.133G	47.82	54.00	-6.18	40.16	3	Horizontal	98	2.26	-	32.10	6.91	31.35			
PK	5.293G	108.45	Inf	-Inf	101.37	3	Horizontal	98	2.26	-	31.51	7.01	31.44			
AV	5.292G	96.78	Inf	-Inf	89.69	3	Horizontal	98	2.26	-	31.52	7.01	31.44			
PK	5.351G	63.18	74.00	-10.82	56.10	3	Horizontal	98	2.26	-	31.50	7.05	31.47			
AV	5.3505G	52.05	54.00	-1.95	44.97	3	Horizontal	98	2.26	-	31.50	7.05	31.47			
PK	5.4715G	59.13	68.20	-9.07	51.68	3	Horizontal	98	2.26	-	31.84	7.14	31.53			

5.25-5.35GHz_802.11ax HEW80_Nss1,(MCS0)_4TX

5290MHz_TX




EUT Y_4TX
Setting 16
06-D-S-5

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	15.86867G	62.30	74.00	-11.70	44.52	3	Vertical	184	1.37	-	38.06	12.61	32.89			
AV	15.86552G	49.67	54.00	-4.33	31.88	3	Vertical	184	1.37	-	38.07	12.61	32.89			

5.25-5.35GHz_802.11ax_HEW80_Nss1,(MCS0)_4TX

5290MHz_TX




EUT Y_4TX
Setting 16
06-D-S-5

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	15.86877G	61.79	74.00	-12.21	44.01	3	Horizontal	343	2.48	-	38.06	12.61	32.89			
AV	15.87491G	49.75	54.00	-4.25	31.98	3	Horizontal	343	2.48	-	38.05	12.61	32.89			

5.47-5.725GHz_802.11ax HEW80_Nss1,(MCS0)_4TX

5530MHz_TX




EUT_Y_4TX
Setting 17.5
06-D-S-5-10

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)			
PK	5.312G	59.19	68.20	-9.01	52.12	3	Vertical	65	2.05	-	31.50	7.02	31.45			
PK	5.4545G	64.82	74.00	-9.18	57.41	3	Vertical	65	2.05	-	31.81	7.13	31.53			
AV	5.4575G	52.80	54.00	-1.20	45.38	3	Vertical	65	2.05	-	31.82	7.13	31.53			
PK	5.4695G	67.75	68.20	-0.45	60.30	3	Vertical	65	2.05	-	31.84	7.14	31.53			
PK	5.5295G	112.72	Inf	-Inf	105.20	3	Vertical	65	2.05	-	31.90	7.17	31.55			
AV	5.531G	101.19	Inf	-Inf	93.66	3	Vertical	65	2.05	-	31.90	7.18	31.55			
PK	5.7265G	59.60	68.20	-8.60	51.79	3	Vertical	65	2.05	-	32.06	7.33	31.58			

5.47-5.725GHz_802.11ax HEW80_Nss1,(MCS0)_4TX

5530MHz_TX




EUT_Y_4TX
Setting 17.5
06-D-S-5-10

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)			
PK	5.332G	58.68	68.20	-9.52	51.60	3	Horizontal	98	2.08	-	31.50	7.04	31.46			
PK	5.459G	63.15	74.00	-10.85	55.73	3	Horizontal	98	2.08	-	31.82	7.13	31.53			
AV	5.458G	52.07	54.00	-1.93	44.65	3	Horizontal	98	2.08	-	31.82	7.13	31.53			
PK	5.47G	66.01	68.20	-2.19	58.56	3	Horizontal	98	2.08	-	31.84	7.14	31.53			
PK	5.531G	109.76	Inf	-Inf	102.23	3	Horizontal	98	2.08	-	31.90	7.18	31.55			
AV	5.532G	98.47	Inf	-Inf	90.94	3	Horizontal	98	2.08	-	31.90	7.18	31.55			
PK	5.78G	60.23	68.20	-7.97	52.18	3	Horizontal	98	2.08	-	32.26	7.37	31.58			

5.47-5.725GHz_802.11ax HEW80_Nss1,(MCS0)_4TX

5530MHz_TX




EUT Y_4TX
Setting 17.5
06-D-S-5

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	11.06228G	59.94	74.00	-14.06	41.88	3	Vertical	347	1.97	-	40.25	10.36	32.55			
AV	11.05878G	47.62	54.00	-6.38	29.55	3	Vertical	347	1.97	-	40.26	10.36	32.55			

5.47-5.725GHz_802.11ax HEW80_Nss1,(MCS0)_4TX

5530MHz_TX




EUT Y_4TX
Setting 17.5
06-D-S-5

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)			
PK	11.05845G	60.25	74.00	-13.75	42.17	3	Horizontal	36	1.26	-	40.27	10.36	32.55			
AV	11.05854G	47.62	54.00	-6.38	29.54	3	Horizontal	36	1.26	-	40.27	10.36	32.55			

5.47-5.725GHz_802.11ax HEW80_Nss1,(MCS0)_4TX

5610MHz_TX




EUT_Y_4TX
Setting 20.5
06-D-S-5-10

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)			
PK	5.3376G	59.23	68.20	-8.97	52.15	3	Vertical	61	1.92	-	31.50	7.04	31.46			
PK	5.46G	62.61	74.00	-11.39	55.19	3	Vertical	61	1.92	-	31.82	7.13	31.53			
AV	5.4588G	50.91	54.00	-3.09	43.49	3	Vertical	61	1.92	-	31.82	7.13	31.53			
PK	5.4624G	64.14	68.20	-4.06	56.72	3	Vertical	61	1.92	-	31.82	7.13	31.53			
PK	5.6118G	116.90	Inf	-Inf	109.45	3	Vertical	61	1.92	-	31.78	7.23	31.56			
AV	5.6118G	104.43	Inf	-Inf	96.98	3	Vertical	61	1.92	-	31.78	7.23	31.56			
PK	5.7288G	67.79	68.20	-0.41	59.97	3	Vertical	61	1.92	-	32.07	7.33	31.58			

5.47-5.725GHz_802.11ax HEW80_Nss1,(MCS0)_4TX

5610MHz_TX




EUT_Y_4TX
Setting 20.5
06-D-S-5-10

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)			
PK	5.3394G	58.29	68.20	-9.91	51.21	3	Horizontal	101	1.34	-	31.50	7.04	31.46			
PK	5.4588G	59.56	74.00	-14.44	52.14	3	Horizontal	101	1.34	-	31.82	7.13	31.53			
AV	5.4588G	48.23	54.00	-5.77	40.81	3	Horizontal	101	1.34	-	31.82	7.13	31.53			
PK	5.463G	60.32	68.20	-7.88	52.89	3	Horizontal	101	1.34	-	31.83	7.13	31.53			
PK	5.6064G	113.44	Inf	-Inf	105.98	3	Horizontal	101	1.34	-	31.79	7.23	31.56			
AV	5.6112G	100.70	Inf	-Inf	93.25	3	Horizontal	101	1.34	-	31.78	7.23	31.56			
PK	5.7258G	62.04	68.20	-6.16	54.24	3	Horizontal	101	1.34	-	32.05	7.33	31.58			

5.47-5.725GHz_802.11ax HEW80_Nss1,(MCS0)_4TX

5610MHz_TX




EUT Y_4TX
Setting 20.5
06-D-S-5

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	11.22194G	59.53	74.00	-14.47	41.93	3	Vertical	286	1.30	-	39.80	10.44	32.64			
AV	11.21918G	47.10	54.00	-6.90	29.50	3	Vertical	286	1.30	-	39.80	10.44	32.64			

5.47-5.725GHz_802.11ax HEW80_Nss1,(MCS0)_4TX

5610MHz_TX




EUT Y_4TX
Setting 20.5
06-D-S-5

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	11.22217G	59.74	74.00	-14.26	42.14	3	Horizontal	243	2.18	-	39.80	10.44	32.64			
AV	11.21618G	47.13	54.00	-6.87	29.53	3	Horizontal	243	2.18	-	39.80	10.44	32.64			

5.47-5.725GHz_802.11ax HEW80_Nss1,(MCS0)_4TX

5690MHz Straddle 5.47-5.725GHz_TX




EUT Y_4TX
Setting 23
06-D-S-5-10

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)			
PK	5.4362G	62.19	74.00	-11.81	54.86	3	Vertical	57	2.02	-	31.74	7.11	31.52			
PK	5.462G	62.16	68.20	-6.04	54.74	3	Vertical	57	2.02	-	31.82	7.13	31.53			
AV	5.456G	50.13	54.00	-3.87	42.72	3	Vertical	57	2.02	-	31.81	7.13	31.53			
PK	5.6822G	118.89	Inf	-Inf	111.34	3	Vertical	57	2.02	-	31.83	7.29	31.57			
AV	5.6918G	106.91	Inf	-Inf	99.31	3	Vertical	57	2.02	-	31.87	7.30	31.57			
PK	5.8538G	67.98	68.20	-0.22	59.84	3	Vertical	57	2.02	-	32.32	7.41	31.59			

5.47-5.725GHz_802.11ax HEW80_Nss1,(MCS0)_4TX

5690MHz Straddle 5.47-5.725GHz_TX




EUT_Y_4TX
Setting 23
06-D-S-5-10

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)			
PK	5.4584G	59.42	74.00	-14.58	52.00	3	Horizontal	89	2.06	-	31.82	7.13	31.53			
AV	5.46G	48.46	54.00	-5.54	41.04	3	Horizontal	89	2.06	-	31.82	7.13	31.53			
PK	5.4662G	59.92	68.20	-8.28	52.49	3	Horizontal	89	2.06	-	31.83	7.13	31.53			
PK	5.6882G	115.12	Inf	-Inf	107.55	3	Horizontal	89	2.06	-	31.85	7.29	31.57			
AV	5.6882G	103.32	Inf	-Inf	95.75	3	Horizontal	89	2.06	-	31.85	7.29	31.57			
PK	5.8514G	65.24	68.20	-2.96	57.11	3	Horizontal	89	2.06	-	32.31	7.41	31.59			

5.47-5.725GHz_802.11ax HEW80_Nss1,(MCS0)_4TX

5690MHz Straddle 5.47-5.725GHz_TX




EUT Y_4TX
Setting 23
06-D-S-5

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	11.38223G	59.68	74.00	-14.32	41.93	3	Vertical	7	2.25	-	39.96	10.52	32.73			
AV	11.38074G	47.33	54.00	-6.67	29.58	3	Vertical	7	2.25	-	39.96	10.52	32.73			

5.47-5.725GHz_802.11ax HEW80_Nss1,(MCS0)_4TX

5690MHz Straddle 5.47-5.725GHz_TX




EUT Y_4TX
Setting 23
06-D-S-5

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)			
PK	11.38396G	59.89	74.00	-14.11	42.14	3	Horizontal	28	1.63	-	39.97	10.52	32.74			
AV	11.37865G	47.45	54.00	-6.55	29.71	3	Horizontal	28	1.63	-	39.96	10.51	32.73			

5.725-5.85GHz_802.11ax HEW80_Nss1,(MCS0)_4TX

5775MHz_TX




EUT Y_4TX
Setting 22
06-D-S-5-10

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)			
PK	5.6385G	65.78	68.20	-2.42	58.38	3	Vertical	60	1.51	-	31.72	7.25	31.57			
PK	5.7675G	118.92	Inf	-Inf	110.90	3	Vertical	60	1.51	-	32.24	7.36	31.58			
AV	5.7765G	106.90	Inf	-Inf	98.86	3	Vertical	60	1.51	-	32.25	7.37	31.58			
PK	5.9235G	69.03	69.31	-0.28	60.64	3	Vertical	60	1.51	-	32.55	7.44	31.60			

5.725-5.85GHz_802.11ax HEW80_Nss1,(MCS0)_4TX

5775MHz_TX




EUT_Y_4TX
Setting 22
06-D-S-5-10

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)			
PK	5.649G	64.26	68.20	-3.94	56.87	3	Horizontal	87	1.54	-	31.70	7.26	31.57			
PK	5.7715G	115.10	Inf	-Inf	107.07	3	Horizontal	87	1.54	-	32.24	7.37	31.58			
AV	5.771G	102.81	Inf	-Inf	94.78	3	Horizontal	87	1.54	-	32.24	7.37	31.58			
PK	5.9315G	63.80	68.20	-4.40	55.40	3	Horizontal	87	1.54	-	32.56	7.44	31.60			

5.725-5.85GHz_802.11ax HEW80_Nss1,(MCS0)_4TX

5775MHz_TX




EUT Y_4TX
Setting 22
06-D-S-5

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	11.55321G	60.02	74.00	-13.98	42.16	3	Vertical	347	1.27	-	40.08	10.60	32.82			
AV	11.55376G	47.38	54.00	-6.62	29.52	3	Vertical	347	1.27	-	40.08	10.60	32.82			

5.725-5.85GHz_802.11ax HEW80_Nss1,(MCS0)_4TX

5775MHz_TX




EUT Y_4TX
Setting 22
06-D-S-5

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	11.55197G	59.82	74.00	-14.18	41.95	3	Horizontal	167	1.32	-	40.09	10.60	32.82			
AV	11.5505G	47.43	54.00	-6.57	29.55	3	Horizontal	167	1.32	-	40.10	10.60	32.82			

5.25-5.35GHz_802.11ax HEW160_Nss1,(MCS0)_4TX

5250MHz Straddle 5.25-5.35GHz_TX




EUT Y_4TX
Setting 16
06-D-S-5-10

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)			
PK	5.1436G	67.82	74.00	-6.18	60.17	3	Vertical	57	2.68	-	32.10	6.91	31.36			
AV	5.1412G	53.94	54.00	-0.06	46.29	3	Vertical	57	2.68	-	32.10	6.91	31.36			
PK	5.2428G	108.10	Inf	-Inf	100.91	3	Vertical	57	2.68	-	31.63	6.97	31.41			
AV	5.2548G	95.45	Inf	-Inf	88.30	3	Vertical	57	2.68	-	31.59	6.98	31.42			
PK	5.3508G	63.89	74.00	-10.11	56.81	3	Vertical	57	2.68	-	31.50	7.05	31.47			
AV	5.35G	52.42	54.00	-1.58	45.34	3	Vertical	57	2.68	-	31.50	7.05	31.47			
PK	5.4852G	58.95	68.20	-9.25	51.47	3	Vertical	57	2.68	-	31.87	7.15	31.54			

5.25-5.35GHz_802.11ax HEW160_Nss1,(MCS0)_4TX

5250MHz Straddle 5.25-5.35GHz_TX




EUT Y_4TX
Setting 16
06-D-S-5-10

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)			
PK	5.118G	63.81	74.00	-10.19	56.15	3	Horizontal	107	2.36	-	32.10	6.90	31.34			
AV	5.146G	51.41	54.00	-2.59	43.76	3	Horizontal	107	2.36	-	32.10	6.91	31.36			
PK	5.2572G	104.66	Inf	-Inf	97.51	3	Horizontal	107	2.36	-	31.59	6.98	31.42			
AV	5.2588G	92.18	Inf	-Inf	85.04	3	Horizontal	107	2.36	-	31.58	6.98	31.42			
PK	5.3548G	61.70	74.00	-12.30	54.60	3	Horizontal	107	2.36	-	31.51	7.06	31.47			
AV	5.35G	50.23	54.00	-3.77	43.15	3	Horizontal	107	2.36	-	31.50	7.05	31.47			
PK	5.65G	58.63	68.20	-9.57	51.24	3	Horizontal	107	2.36	-	31.70	7.26	31.57			

5.25-5.35GHz_802.11ax HEW160_Nss1,(MCS0)_4TX

5250MHz Straddle 5.25-5.35GHz_TX




EUT Y_4TX
Setting 16
06-D-S-5

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	15.74531G	62.45	74.00	-11.55	44.48	3	Vertical	5	1.87	-	38.29	12.55	32.87			
AV	15.75438G	50.01	54.00	-3.99	32.03	3	Vertical	5	1.87	-	38.30	12.55	32.87			

5.25-5.35GHz_802.11ax HEW160_Nss1,(MCS0)_4TX

5250MHz Straddle 5.25-5.35GHz_TX




EUT Y_4TX
Setting 16
06-D-S-5

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	15.74813G	62.06	74.00	-11.94	44.08	3	Horizontal	4	1.93	-	38.30	12.55	32.87			
AV	15.75335G	49.83	54.00	-4.17	31.85	3	Horizontal	4	1.93	-	38.30	12.55	32.87			

5.47-5.725GHz_802.11ax_HEW160_Nss1,(MCS0)_4TX

5570MHz_TX




EUT_V_4TX
Setting 16
06-D-S-5-10

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)			
PK	5.2092G	58.86	68.20	-9.34	51.54	3	Vertical	66	2.05	-	31.76	6.95	31.39			
PK	5.442G	65.33	74.00	-8.67	57.96	3	Vertical	66	2.05	-	31.77	7.12	31.52			
AV	5.4492G	51.54	54.00	-2.46	44.14	3	Vertical	66	2.05	-	31.80	7.12	31.52			
PK	5.4636G	67.42	68.20	-0.78	59.99	3	Vertical	66	2.05	-	31.83	7.13	31.53			
PK	5.582G	107.69	Inf	-Inf	100.20	3	Vertical	66	2.05	-	31.84	7.21	31.56			
AV	5.566G	95.85	Inf	-Inf	88.34	3	Vertical	66	2.05	-	31.87	7.20	31.56			
PK	5.7332G	61.38	68.20	-6.82	53.53	3	Vertical	66	2.05	-	32.10	7.33	31.58			

5.47-5.725GHz_802.11ax HEW160_Nss1,(MCS0)_4TX

5570MHz_TX




EUT_V_4TX
Setting 16
06-D-S-5-10

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)			
PK	5.2636G	59.07	68.20	-9.13	51.93	3	Horizontal	101	1.48	-	31.57	6.99	31.42			
PK	5.4476G	65.02	74.00	-8.98	57.63	3	Horizontal	101	1.48	-	31.79	7.12	31.52			
AV	5.4476G	51.40	54.00	-2.60	44.01	3	Horizontal	101	1.48	-	31.79	7.12	31.52			
PK	5.466G	64.39	68.20	-3.81	56.96	3	Horizontal	101	1.48	-	31.83	7.13	31.53			
PK	5.5668G	104.63	Inf	-Inf	97.12	3	Horizontal	101	1.48	-	31.87	7.20	31.56			
AV	5.5668G	91.94	Inf	-Inf	84.43	3	Horizontal	101	1.48	-	31.87	7.20	31.56			
PK	5.7268G	59.85	68.20	-8.35	52.04	3	Horizontal	101	1.48	-	32.06	7.33	31.58			

5.47-5.725GHz_802.11ax HEW160_Nss1,(MCS0)_4TX


5570MHz_TX

EUT Y_4TX
Setting 16
06-D-S-5

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)			
PK	11.14205G	59.46	74.00	-14.54	41.73	3	Vertical	138	1.52	-	39.93	10.40	32.60			
AV	11.1398G	46.83	54.00	-7.17	29.09	3	Vertical	138	1.52	-	39.94	10.40	32.60			

5.47-5.725GHz_802.11ax HEW160_Nss1,(MCS0)_4TX

5570MHz_TX



EUT Y_4TX
Setting 16
06-D-S-5


Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)			
PK	11.14016G	59.89	74.00	-14.11	42.15	3	Horizontal	0	2.08	-	39.94	10.40	32.60			
AV	11.14444G	46.74	54.00	-7.26	29.02	3	Horizontal	0	2.08	-	39.92	10.40	32.60			



Summary

Mode	Result	Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Condition
Mode 1	Pass	AV	1.98669G	41.96	54.00	-12.04	Horizontal


Mode 1



EUT Y
Power AC120V/60Hz
05-M-G-5

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB/m)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	Raw (dBuV/m)	AF (dB/m)	CL (dB)	PA (dB)		
PK	1.12094G	39.19	74.00	-34.81	-8.18	3	Vertical	307	2.91	-	47.37	25.70	2.98	36.86		
AV	1.12514G	30.72	54.00	-23.28	-8.17	3	Vertical	307	2.91	-	38.89	25.70	2.99	36.86		
PK	1.98202G	44.97	74.00	-29.03	-6.40	3	Vertical	201	2.16	-	51.37	26.32	3.98	36.70		
AV	1.98534G	36.98	54.00	-17.02	-6.36	3	Vertical	201	2.16	"Worst"	43.34	26.35	3.99	36.70		
PK	3.12671G	42.07	74.00	-31.93	-1.67	3	Vertical	232	1.42	-	43.74	29.80	4.93	36.40		
AV	3.12565G	34.25	54.00	-19.75	-1.67	3	Vertical	232	1.42	-	35.92	29.80	4.93	36.40		
PK	8.79265G	42.79	74.00	-31.21	11.96	3	Vertical	321	2.58	-	30.83	37.70	8.10	33.84		
AV	8.8246G	31.36	54.00	-22.64	12.04	3	Vertical	321	2.58	-	19.32	37.75	8.11	33.82		
PK	12.25627G	40.19	74.00	-33.81	15.24	3	Vertical	354	2.98	-	24.95	38.90	9.52	33.18		
AV	12.24432G	33.42	54.00	-20.58	15.22	3	Vertical	354	2.98	-	18.20	38.90	9.51	33.19		
PK	17.24819G	41.91	74.00	-32.09	17.09	3	Vertical	101	1.16	-	24.82	38.69	11.40	33.00		
AV	17.25495G	29.92	54.00	-24.08	17.09	3	Vertical	101	1.16	-	12.83	38.70	11.40	33.01		

Mode 1



EUT Y
Power AC120V/60Hz
05-M-G-5

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB/m)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	Raw (dBuV/m)	AF (dB/m)	CL (dB)	PA (dB)		
PK	1.1202G	41.00	74.00	-33.00	-8.18	3	Horizontal	151	1.22	-	49.18	25.70	2.98	36.86		
AV	1.12175G	35.74	54.00	-18.26	-8.18	3	Horizontal	151	1.22	-	43.92	25.70	2.98	36.86		
PK	1.98536G	50.17	74.00	-23.83	-6.36	3	Horizontal	136	1.00	-	56.53	26.35	3.99	36.70		
AV	1.98669G	41.96	54.00	-12.04	-6.34	3	Horizontal	136	1.00	"Worst"	48.30	26.37	3.99	36.70		
PK	3.12445G	46.53	74.00	-27.47	-1.69	3	Horizontal	297	2.42	-	48.22	29.80	4.92	36.41		
AV	3.1296G	39.25	54.00	-14.75	-1.67	3	Horizontal	297	2.42	-	40.92	29.80	4.93	36.40		
PK	8.79305G	42.96	74.00	-31.04	11.96	3	Horizontal	341	1.35	-	31.00	37.70	8.10	33.84		
AV	8.8177G	31.32	54.00	-22.68	12.03	3	Horizontal	341	1.35	-	19.29	37.74	8.11	33.82		
PK	12.2476G	42.42	74.00	-31.58	15.22	3	Horizontal	299	1.10	-	27.20	38.90	9.51	33.19		
AV	12.26137G	34.31	54.00	-19.69	15.25	3	Horizontal	299	1.10	-	19.06	38.90	9.52	33.17		
PK	17.26014G	40.84	74.00	-33.16	17.09	3	Horizontal	156	3.00	-	23.75	38.70	11.40	33.01		
AV	17.2537G	29.93	54.00	-24.07	17.10	3	Horizontal	156	3.00	-	12.83	38.70	11.40	33.00		