TESTING LABORATORY
CERTIFICATE#4323.01

FCC PART 15.247
TEST REPORT

For

Soundking Electronics&Sound Co., Ltd.

No.818 Integrity Road, Yinzhou District, Ningbo City, Zhejiang Province, China

FCC ID: 2AU7P-ARTOS1000

Report Type:	**Product Type:**
Original Report	Sound Column Audio System

Test Engineer:	Winnie Yang
Report Number:	RSHD191025007-00A
Report Date:	2019-12-06
Reviewed By:	Oscar Ye EMC Manager
Prepared By:	Bay Area Compliance Laboratories Corp. (Kunshan) No.248 Chenghu Road,Kunshan,Jiangsu province,China Tel: +86-0512-86175000 Fax: +86-0512-88934268 www.baclcorp.com.cn

Note: This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliant Laboratories Corp. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

TABLE OF CONTENTS

GENERAL INFORMATION **4**
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT) 4
OBJECTIVE 4
RELATED SUBMITTAL(S)/GRANT(S) 4
TEST METHODOLOGY 4
MEASUREMENT UNCERTAINTY 5
TEST FACILITY 5
SYSTEM TEST CONFIGURATION **6**
DESCRIPTION OF TEST CONFIGURATION 6
EUT EXERCISE SOFTWARE 6
SPECIAL ACCESSORIES 6
EQUIPMENT MODIFICATIONS 6
SUPPORT EQUIPMENT LIST AND DETAILS 7
EXTERNAL I/O CABLE 7
BLOCK DIAGRAM OF TEST SETUP 7
SUMMARY OF TEST RESULTS **9**
TEST EQUIPMENT LIST **10**
FCC §1.1310 & §2.1091 –MAXIMUM PERMISSIBLE EXPOSURE (MPE) **11**
FCC §15.203 – ANTENNA REQUIREMENT **12**
APPLICABLE STANDARD 12
ANTENNA CONNECTOR CONSTRUCTION 12
FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS **13**
APPLICABLE STANDARD 13
EUT SETUP 13
EMI TEST RECEIVER SETUP 13
TEST PROCEDURE 14
CORRECTED FACTOR & OVER LIMIT CALCULATION 14
TEST RESULTS SUMMARY 14
TEST DATA 14
FCC §15.205, §15.209 & §15.247(d) – RADIATED EMISSIONS **17**
APPLICABLE STANDARD 17
EUT SETUP 17
EMI TEST RECEIVER SETUP 18
TEST PROCEDURE 18
CORRECTED AMPLITUDE & MARGIN CALCULATION 18
TEST RESULTS SUMMARY 18
TEST DATA 19
FCC §15.247(a) (1)-CHANNEL SEPARATION TEST **30**
APPLICABLE STANDARD 30
TEST PROCEDURE 30
TEST DATA 30
FCC §15.247(a) (1) – 20 dB EMISSION BANDWIDTH **36**
APPLICABLE STANDARD 36
TEST PROCEDURE 36
TEST DATA 36
FCC §15.247(a) (1) (iii)-QUANTITY OF HOPPING CHANNEL TEST **42**

APPLICABLE STANDARD 42
TEST PROCEDURE 42
TEST DATA 42

FCC §15.247(a) (1) (iii) - TIME OF OCCUPANCY (DWELL TIME) 45

APPLICABLE STANDARD 45
TEST PROCEDURE 45
TEST DATA 45

FCC §15.247(b) (1) - PEAK OUTPUT POWER MEASUREMENT 61

APPLICABLE STANDARD 61
TEST PROCEDURE 61
TEST DATA 61

FCC §15.247(d) - BAND EDGES TESTING 68

APPLICABLE STANDARD 68
TEST PROCEDURE 68
TEST DATA 68

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

Applicant	Soundking Electronics&Sound Co., Ltd.
Tested Model	ARTOS1000
Series Model	ARTOS1200
Model Difference	Model names
Product Type	Sound Column Audio System
Power Supply	AC 100-240V
RF Function	Classic BT
Operating Band /Frequency	Bluetooth: 2402-2480MHz
Channel Number:	Bluetooth:79
Antenna Type	PCB Antenna
Maximum Antenna Gain	1.70dBi

**All measurement and test data in this report was gathered from production sample serial number: 20191025007. (Assigned by the BACL. The EUT supplied by the applicant was received on 2019-10-25)*

Objective

This test report is prepared on behalf of *Soundking Electronics&Sound Co., Ltd.* in accordance with Part 2-Subpart J, Part 15-Subparts A and C of the Federal Communication Commissions rules.

The tests were performed in order to determine Compliance with FCC Part 15, Subpart C, section 15.203, 15.205, 15.207, 15.209 and 15.247 rules.

Related Submittal(s)/Grant(s)

No Related Submittal(s)/Grant(s).

Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices and 558074 D01 15.247 Meas Guidance v05r02.

All emissions measurement was performed and Bay Area Compliance Laboratories Corp. (Kunshan). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Measurement Uncertainty

Item		Uncertainty
AC Power Lines Conducted Emissions		3.19dB
RF conducted test with spectrum		0.9dB
RF Output Power with Power meter		0.5dB
Radiated emission	30MHz~1GHz	6.11dB
	1GHz~6GHz	4.45dB
	6GHz~18GHz	5.23dB
	18GHz~40GHz	5.65dB
Occupied Bandwidth		0.5kHz
Temperature		1.0℃
Humidity		6%

Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty.

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Kunshan) to collect test data is located on the No.248 Chenghu Road, Kunshan, Jiangsu province, China.

Bay Area Compliance Laboratories Corp. (Kunshan) Lab is accredited to ISO/IEC 17025 by A2LA (Lab code: 4323.01), the FCC designation No. CN1185 under the FCC KDB 974614 D01 and CAB identifier CN0004 under the ISED requirement. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-2014

SYSTEM TEST CONFIGURATION

Description of Test Configuration

Channel list for BT3.0:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	40	2442
1	2403	…	…
…	…	…	…
…	…	78	2480
39	2441	/	/

EUT was tested with Channel 0, 39 and 78.

EUT Exercise Software

RF test software: BT Tool

Mode	Data Rate	Power Level Setting
GFSK	Low	7
	Middle	7
	High	7
π/4-DQPSK	Low	7
	Middle	7
	High	7
8DPSK	Low	7
	Middle	7
	High	7

Special Accessories

No special accessory.

Equipment Modifications

No modification was made to the EUT tested.

Support Equipment List and Details

Manufacturer	Description	Model	Serial Number
/	/	/	/

External I/O Cable

Cable Description	Length (m)	From Port	To
Power Cable	0.8	EUT	LISN

Block Diagram of Test Setup

For Conducted Emissions:



For Radiated Emissions(Below 1GHz):



For Radiated Emissions(Above 1GHz):



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
FCC §1.1310 & §2.1091	Maximum Permissible Exposure (MPE)	Compliant
§15.203	Antenna Requirement	Compliant
§15.207(a)	AC Line Conducted Emissions	Compliant
§15.205, §15.209 & §15.247(d)	Radiated Emissions & Restricted Bands Emissions	Compliant
§15.247(a)(1)	20 dB Emission Bandwidth	Compliant
§15.247(a)(1)	Channel Separation Test	Compliant
§15.247(a)(1)(iii)	Time of Occupancy (Dwell Time)	Compliant
§15.247(a)(1)(iii)	Quantity of hopping channel Test	Compliant
§15.247(b)(1)	Peak Output Power Measurement	Compliant
§15.247(d)	Band Edges	Compliant

TEST EQUIPMENT LIST

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Radiated Emission Test（Chamber 1#）					
Rohde & Schwarz	EMI Test Receiver	ESCI	100195	2018-11-30	2019-11-29
Sunol Sciences	Broadband Antenna	JB3	A090413-1	2016-12-26	2019-12-25
Sonoma Instrunent	Pre-amplifier	310N	171205	2019-08-15	2020-08-14
Rohde & Schwarz	Auto test Software	EMC32	100361	/	/
MICRO-COAX	Coaxial Cable	Cable-8	008	2019-08-15	2020-08-14
MICRO-COAX	Coaxial Cable	Cable-9	009	2019-08-15	2020-08-14
MICRO-COAX	Coaxial Cable	Cable-10	010	2019-08-15	2020-08-14
Radiated Emission Test（Chamber 2#）					
Rohde & Schwarz	EMI Test Receiver	ESU40	100207	2019-05-30	2020-05-29
ETS-LINDGREN	Horn Antenna	3115	9207-3900	2017-07-15	2020-07-14
ETS-LINDGREN	Horn Antenna	3116	00084159	2016-12-12	2019-12-11
A.H.Systems, inc	Amplifier	2641-1	491	2019-02-20	2020-02-19
SELECTOR	Amplifier	EM18G40G	060726	2019-03-22	2020-03-21
MICRO-TRONICS	Band Reject Filter	BRM50702	G024	2019-08-05	2020-08-04
Narda	Attenuator	10dB	010	2019-08-15	2020-08-14
Rohde & Schwarz	Auto test Software	EMC32	100361	/	/
MICRO-COAX	Coaxial Cable	Cable-6	006	2019-08-15	2020-08-14
MICRO-COAX	Coaxial Cable	Cable-11	011	2019-08-15	2020-08-14
MICRO-COAX	Coaxial Cable	Cable-12	012	2019-08-15	2020-08-14
MICRO-COAX	Coaxial Cable	Cable-13	013	2019-08-15	2020-08-14
RF Conducted Test					
Rohde & Schwarz	Signal Analyzer	FSV40	101116	2019-07-23	2020-07-22
Rohde & Schwarz	Signal Analyzer	FSIQ26	836131/009	2018-11-30	2019-11-29
Narda	Attenuator	10dB	010	2019-08-15	2020-08-14
Soundking Electronics	RF Cable	Soundking Electronics C01	C01	Each Time	N/A
Conducted Emission Test					
Rohde & Schwarz	EMI Test Receiver	ESR	1316.3003K03-101746-zn	2019-07-11	2020-07-10
Rohde & Schwarz	LISN	ENV216	3560655016	2018-11-30	2019-11-29
Audix	Test Software	e3	V9	--	--
Narda	Attenuator/6dB	10690812-2	26850-6	2019-01-10	2020-01-09
MICRO-COAX	Coaxial Cable	Cable-15	015	2019-08-15	2020-08-14

*** Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Kunshan) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

FCC §1.1310 & §2.1091 –MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Applicable Standard

According to subpart §2.1091 and subpart §1.1310, systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

Limits for Maximum Permissible Exposure (MPE) (§1.1310, §2.1091)

(B) Limits for General Population/Uncontrolled Exposure				
Frequency Range (MHz)	**Electric Field Strength (V/m)**	**Magnetic Field Strength (A/m)**	**Power Density (mW/cm^2)**	**Averaging Time (minutes)**
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*($180/f^2$)	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	f/1500	30
1500-100,000	/	/	1.0	30

f = frequency in MHz; * = Plane-wave equivalent power density;

According to §1.1310 and §2.1091 RF exposure is calculated.

Calculated Formulary:
Predication of MPE limit at a given distance
$S = PG/4\pi R^2$ = power density (in appropriate units, e.g. mW/cm^2);
P = power input to the antenna (in appropriate units, e.g., mW);
G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain;
R = distance to the center of radiation of the antenna (appropriate units, e.g., cm);

Calculated Data:

Mode	Frequency Range (MHz)	Antenna Gain		Tune-up Conducted Power		Evaluation Distance (cm)	Power Density (mW/cm^2)	MPE Limit (mW/cm^2)
		(dBi)	(numeric)	(dBm)	(mW)			
BT	2402~2480	1.70	1.48	6.00	3.98	20	0.0012	1.0

Note: For the above Tune-up Conducted Power were all declared by the manufacturer.

Conclusion: The device meets FCC MPE at 20 cm distance.

FCC §15.203 – ANTENNA REQUIREMENT

Applicable Standard

According to FCC § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

Antenna Connector Construction

The EUT has a PCB antenna for BT, the antenna gain is 1.7dBi, fulfill the requirement of this section. Please refer to the EUT photos.

Result: Compliant.

FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS

Applicable Standard

FCC §15.207(a)

EUT Setup



Note: 1. Support units were connected to second LISN.
2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The measurement procedure of EUT setup is according with ANSI C63.10-2013. The related limit was specified in FCC Part 15.207.

The spacing between the peripherals was 10 cm.

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

Test Procedure

ANSI C63.10-2013 clause 6.2

During the conducted emission test, the adapter was connected to the outlet of the LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All final data was recorded in the Quasi-peak and average detection mode.

Corrected Factor & Over Limit Calculation

The Corrected factor is calculated by adding LISN VDF (Voltage Division Factor), Cable Loss and Transient Limiter Attenuation. The basic equation is as follows:

Factor (dB) = LISN VDF (dB) + Cable Loss (dB) + Transient Limiter Attenuation (dB)

The "**Over Limit**" column of the following data tables indicates the degree of compliance with the applicable limit. For example, an over Limit of 7dB means the emission is 7 dB above the limit. The equation for over Limit calculation is as follows:

Over Limit (dB) = Read level (dBμV) + Factor (dB) - Limit (dBμV)

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Part 15.207.

Test Data

Environmental Conditions

Temperature:	22 ℃
Relative Humidity:	50 %
ATM Pressure:	101.3 kPa

The testing was performed by Winnie Yang on 2019-11-25.

Test Result: Compliant.

EUT operation mode: Transmitting in low channel

AC 120V/60 Hz, Line



	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	
1	0.251	20.30	19.82	40.12	51.73	-11.61	Average
2	0.251	27.80	19.82	47.62	61.73	-14.11	QP
3	2.779	7.00	19.47	26.47	46.00	-19.53	Average
4	2.779	17.30	19.47	36.77	56.00	-19.23	QP
5	5.058	-2.10	19.49	17.39	50.00	-32.61	Average
6	5.058	8.80	19.49	28.29	60.00	-31.71	QP
7	6.698	-1.71	19.52	17.81	50.00	-32.19	Average
8	6.698	12.49	19.52	32.01	60.00	-27.99	QP
9	9.966	6.10	19.55	25.65	50.00	-24.35	Average
10	9.966	23.70	19.55	43.25	60.00	-16.75	QP
11	18.622	17.70	19.87	37.57	50.00	-12.43	Average
12	18.622	28.40	19.87	48.27	60.00	-11.73	QP

AC 120V/60 Hz, Neutral



	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	
1	0.251	19.60	19.82	39.42	51.73	-12.31	Average
2	0.251	27.10	19.82	46.92	61.73	-14.81	QP
3	2.779	5.30	19.47	24.77	46.00	-21.23	Average
4	2.779	13.60	19.47	33.07	56.00	-22.93	QP
5	4.672	2.19	19.49	21.68	46.00	-24.32	Average
6	4.672	16.49	19.49	35.98	56.00	-20.02	QP
7	7.062	6.70	19.52	26.22	50.00	-23.78	Average
8	7.062	23.50	19.52	43.02	60.00	-16.98	QP
9	10.342	-0.40	19.56	19.16	50.00	-30.84	Average
10	10.342	11.60	19.56	31.16	60.00	-28.84	QP
11	18.820	12.90	19.89	32.79	50.00	-17.21	Average
12	18.820	25.90	19.89	45.79	60.00	-14.21	QP

Note:

1) Factor (dB) = LISN VDF (dB) + Cable Loss (dB) + Transient Limiter Attenuation (dB)
2) Over Limit (dB) = Read level (dBµV) + Factor (dB) - Limit (dBµV)

FCC §15.205, §15.209 & §15.247(d) – RADIATED EMISSIONS

Applicable Standard

FCC §15.205; §15.209; §15.247(d)

EUT Setup

Below 1 GHz:



Above 1GHz:



The radiated emission tests were performed in the 3 meters, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209 and FCC 15.247 limits.

EMI Test Receiver Setup

The system was investigated from 30 MHz to 25 GHz.

During the radiated emission test, the EMI test receiver Setup was set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Detector
30 MHz – 1000 MHz	120 kHz	300 kHz	120 kHz	QP
Above 1GHz	1MHz	3 MHz	/	PK
	1MHz	3 MHz	/	Ave.

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

All final data was recorded in Quasi-peak detection mode for frequency range of 30 MHz -1 GHz and peak and Average detection modes for frequencies above 1 GHz.

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

Corrected Amplitude (dBμV/m) = Meter Reading (dBμV) + Antenna Factor (dB/m) + Cable Loss (dB) - Amplifier Gain (dB)

The "**Margin**" column of the following data tables indicates the degree of Compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

Margin (dB) = Limit (dBμV/m) – Corrected Amplitude (dBμV/m)

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Title 47, Part 15, Subpart C, section 15.205, 15.209 and 15.247.

Test Data

Environmental Conditions

Temperature:	19.0℃~21.2℃
Relative Humidity:	50 %~51 %
ATM Pressure:	101.3 kPa~102.2 kPa

The testing was performed by Winnie Yang from 2019-11-16 to 2019-11-20.

EUT operation mode: Transmitting

Spurious Emission Test:
30MHz-1GHz:

Pre-Scan with GFSK, π/4-DQPSK, 8DPSK modes of operation in the X,Y and Z axes of orientation, the worst case ***low channel of 8DPSK Mode in Z-axis of orientation*** *was recorded*



Frequency (MHz)	Corrected Amplitude	Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBµV/m)	Margin (dB)
	Quasi-peak (dBµV/m)	Height (cm)	Polar (H/V)				
52.338500	33.68	100.0	V	60.0	-17.6	40.00	6.32
62.422950	26.59	100.0	V	195.0	-17.8	40.00	13.41
98.408400	27.38	100.0	V	247.0	-15.3	43.50	16.12
150.855900	30.26	100.0	V	164.0	-12.4	43.50	13.24
196.964850	33.23	100.0	V	206.0	-12.5	43.50	10.27
246.168600	33.57	100.0	V	206.0	-12.1	46.00	12.43

1GHz-18GHz:

Pre-Scan with GFSK, π/4-DQPSK, 8DPSK modes of operation in the X,Y and Z axes of orientation, the worst case ***8DPSK Mode in Z-axis of orientation*** *was recorded*

Note:
1. This test was performed with the 2.4-2.5 GHz notch filter.
2. Corrected Factor (dB/m) = Antenna factor (RX) (dB/m) + Cable Loss (dB) – Amplifier Factor (dB)
   Corrected Amplitude (dBμV/m) = Corrected Factor (dB/m) + Reading (dBμV)
   Margin (dB) = Limit (dBμV/m) – Corrected Amplitude (dBμV/m)

Low Channel: 2402MHz



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV/m)	Average (dBμV/m)	Height (cm)	Polar (H/V)				
1110.50	---	30.47	150.0	H	111.0	-12.0	54.00	23.53
1110.50	45.58	---	150.0	H	111.0	-12.0	74.00	28.42
3109.70	40.84	---	200.0	H	290.0	-4.2	74.00	33.16
3109.70	---	32.21	200.0	H	290.0	-4.2	54.00	21.79
4804.00	---	43.01	150.0	H	19.0	-0.6	54.00	10.99
4804.00	49.21	---	150.0	H	19.0	-0.6	74.00	24.79
7206.00	---	46.97	200.0	H	290.0	5.7	54.00	7.03
7206.00	53.45	---	200.0	H	290.0	5.7	74.00	20.55
12753.80	---	43.95	150.0	H	141.0	11.2	54.00	10.05
12753.80	53.63	---	150.0	H	141.0	11.2	74.00	20.37
17559.70	---	47.80	200.0	V	0.0	14.2	54.00	6.20
17559.70	56.95	---	200.0	V	0.0	14.2	74.00	17.05

Middle Channel: 2441MHz



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBµV/m)	Margin (dB)
	MaxPeak (dBµV/m)	Average (dBµV/m)	Height (cm)	Polar (H/V)				
1100.30	---	32.39	150.0	H	117.0	-12.1	54.00	21.61
1100.30	45.63	---	150.0	H	117.0	-12.1	74.00	28.37
3521.10	---	33.18	150.0	V	351.0	-3.5	54.00	20.82
3521.10	42.12	---	150.0	V	351.0	-3.5	74.00	31.88
4882.00	---	39.19	150.0	H	23.0	-0.4	54.00	14.81
4882.00	46.45	---	150.0	H	23.0	-0.4	74.00	27.55
7323.00	---	43.18	200.0	H	38.0	5.8	54.00	10.82
7323.00	49.28	---	200.0	H	38.0	5.8	74.00	24.72
12765.70	---	44.70	200.0	V	20.0	11.2	54.00	9.30
12765.70	54.02	---	200.0	V	20.0	11.2	74.00	19.98
17626.00	---	47.13	150.0	V	215.0	14.1	54.00	6.87
17626.00	56.55	---	150.0	V	215.0	14.1	74.00	17.45

High Channel: 2480MHz



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBµV/m)	Margin (dB)
	MaxPeak (dBµV/m)	Average (dBµV/m)	Height (cm)	Polar (H/V)				
1113.90	---	34.19	200.0	H	112.0	-12.0	54.00	19.81
1115.60	47.92	---	200.0	H	112.0	-12.0	74.00	26.08
2849.60	---	30.27	150.0	V	155.0	-5.1	54.00	23.73
2849.60	39.89	---	150.0	V	155.0	-5.1	74.00	34.11
4960.00	45.25	---	150.0	H	330.0	-0.3	74.00	28.75
4960.00	---	37.64	150.0	H	330.0	-0.3	54.00	16.36
7440.00	---	38.88	200.0	V	214.0	6.1	54.00	15.12
7440.00	50.18	---	200.0	V	214.0	6.1	74.00	23.82
12170.70	---	43.72	150.0	V	244.0	10.2	54.00	10.28
12170.70	53.50	---	150.0	V	244.0	10.2	74.00	20.50
17813.00	55.78	---	150.0	H	0.0	13.8	74.00	18.22
17813.00	---	47.63	150.0	H	0.0	13.8	54.00	6.37

18GHz-25GHz:

Pre-Scan with GFSK, π/4-DQPSK, 8DPSK modes of operation in the X,Y and Z axes of orientation, the worst case ***low channel of 8DPSK Mode in Z-axis of orientation*** *was recorded*

Horizontal



Date: 20.NOV.2019 14:59:53

Vertical



Date: 20.NOV.2019 15:18:44

Restricted Bands Emissions:

Pre-Scan with GFSK, π/4-DQPSK, 8DPSK modes of operation in the X,Y and Z axes of orientation, the worst case ***8DPSK Mode in Z-axis of orientation*** *was recorded*

Note:
1. Corrected Factor (dB/m) = Antenna factor (RX) (dB/m) + Cable Loss (dB) – Amplifier Factor (dB)
   Corrected Amplitude (dBμV/m) = Corrected Factor (dB/m) + Reading (dBμV)
   Margin (dB) = Limit (dBμV/m) – Corrected Amplitude (dBμV/m)

Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV/m)	Average (dBμV/m)	Height (cm)	Polar (H/V)				
Low Channel: 2402MHz								
2390.00	46.96	---	200.0	H	89.0	2.8	74.00	27.04
2390.00	---	40.48	200.0	H	89.0	2.8	54.00	13.52
High Channel: 2480MHz								
2483.50	---	37.14	150.0	V	251.0	3.0	54.00	16.86
2483.50	45.56	---	150.0	V	251.0	3.0	74.00	28.44

Conducted Spurious Emissions at Antenna Port

BDR (GFSK): Low Channel



BDR (GFSK): Middle Channel



BDR (GFSK): High Channel



EDR (π/4-DQPSK): Low Channel



EDR (π/4-DQPSK): Middle Channel



EDR (π/4-DQPSK): High Channel



EDR (8DPSK): Low Channel



EDR (8DPSK): Middle Channel



EDR (8DPSK): High Channel



FCC §15.247(a) (1)-CHANNEL SEPARATION TEST

Applicable Standard

Frequency hopping systems shall have hoping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater provided the systems operate with an output power no greater than 125 mW.

Test Procedure

The EUT shall have its hopping function enabled. Use the following spectrum analyzer settings:

a. Span: Wide enough to capture the peaks of two adjacent channels.
b. RBW: Start with the RBW set to approximately 30% of the channel spacing; adjust as necessary to best identify the center of each individual channel.
c. Video (or average) bandwidth (VBW) ≥ RBW.
d. Sweep: Auto.
e. Detector function: Peak.
f. Trace: Max hold.
g. Allow the trace to stabilize.

Use the marker-delta function to determine the separation between the peaks of the adjacent channels.

Test Data

Environmental Conditions

Temperature:	20 ℃
Relative Humidity:	51 %
ATM Pressure:	102.0 kPa

The testing was performed by Winnie Yang on 2019-11-16.

EUT operation mode: Transmitting

Test Result: Compliant.

Mode	Channel	Frequency (MHz)	Channel Separation (MHz)	Limit (MHz)	Result
BDR (GFSK)	Low	2402	1.004	0.693	Pass
	Adjacent	2403			
	Middle	2441	1.004	0.693	Pass
	Adjacent	2442			
	High	2480	1.004	0.693	Pass
	Adjacent	2479			
EDR (π/4-DQPSK)	Low	2402	1.010	0.874	Pass
	Adjacent	2403			
	Middle	2441	1.004	0.874	Pass
	Adjacent	2442			
	High	2480	1.004	0.882	Pass
	Adjacent	2479			
EDR (8DPSK)	Low	2402	0.998	0.870	Pass
	Adjacent	2403			
	Middle	2441	1.004	0.870	Pass
	Adjacent	2442			
	High	2480	0.998	0.870	Pass
	Adjacent	2479			

Note: For BDR mode and EDR mode, Limit = 20 dB bandwidth*2/3

BDR (GFSK): Low Channel



BDR (GFSK): Middle Channel



BDR (GFSK): High Channel



EDR (π/4-DQPSK): Low Channel



EDR (π/4-DQPSK): Middle Channel



EDR (π/4-DQPSK): High Channel



EDR (8DPSK): Low Channel



EDR (8DPSK): Middle Channel



EDR (8DPSK): High Channel



FCC §15.247(a) (1) – 20 dB EMISSION BANDWIDTH

Applicable Standard

Alternatively, frequency hopping systems operating in the 2400–2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
3. Measure the frequency difference of two frequencies that were attenuated 20 dB from the reference level. Record the frequency difference as the emission bandwidth.
4. Repeat above procedures until all frequencies measured were complete.

Test Data

Environmental Conditions

Temperature:	18.2℃
Relative Humidity:	52 %
ATM Pressure:	101.3kPa

The testing was performed by Winnie Yang on 2019-11-16.

EUT operation mode: Transmitting

Test Result: Compliant.

Mode	Channel	Frequency (MHz)	20 dB Emission Bandwidth (MHz)
BDR (GFSK)	Low	2402	1.040
	Middle	2441	1.040
	High	2480	1.040
EDR (π/4-DQPSK)	Low	2402	1.311
	Middle	2441	1.311
	High	2480	1.323
EDR (8DPSK)	Low	2402	1.305
	Middle	2441	1.305
	High	2480	1.305

BDR (GFSK): Low Channel



BDR (GFSK): Middle Channel



Date: 16.NOV.2019 09:40:31

BDR (GFSK): High Channel



Date: 16.NOV.2019 09:44:02

EDR (π/4-DQPSK): Low Channel



EDR(π/4-DQPSK): Middle Channel



EDR (π/4-DQPSK): High Channel



EDR (8DPSK): Low Channel



EDR (8DPSK): Middle Channel



EDR (8DPSK): High Channel



FCC §15.247(a) (1) (iii)-QUANTITY OF HOPPING CHANNEL TEST

Applicable Standard

Frequency hopping systems in the 2400–2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

Test Procedure

The EUT shall have its hopping function enabled. Use the following spectrum analyzer settings:

a. Span: The frequency band of operation. Depending on the number of channels the device supports, it may be necessary to divide the frequency range of operation across multiple spans, to allow the individual channels to be clearly seen.
b. RBW: To identify clearly the individual channels, set the RBW to less than 30% of the channel spacing or the 20 dB bandwidth, whichever is smaller.
c. VBW ≥ RBW.
d. Sweep: Auto.
e. Detector function: Peak.
f. Trace: Max hold.
g. Allow the trace to stabilize.

It might prove necessary to break the span up into subranges to show clearly all of the hopping frequencies.

Test Data

Environmental Conditions

Temperature:	20 ℃
Relative Humidity:	51 %
ATM Pressure:	102.0 kPa

The testing was performed by Winnie Yang on 2019-11-16.

EUT operation mode: Hopping

Test Result: Compliant.

Mode	Frequency Range (MHz)	Number of Hopping Channel (CH)	Limit (CH)
BDR (GFSK)	2400-2483.5	79	≥15
EDR (π/4-DQPSK)	2400-2483.5	79	≥15
EDR (8DPSK)	2400-2483.5	79	≥15

BDR (GFSK): Number of Hopping Channels



EDR (π/4-DQPSK): Number of Hopping Channels



EDR (8DPSK): Number of Hopping Channels



FCC §15.247(a) (1) (iii) - TIME OF OCCUPANCY (DWELL TIME)

Applicable Standard

Frequency hopping systems in the 2400-2483.5 MHz shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

Test Procedure

The EUT shall have its hopping function enabled. Use the following spectrum analyzer settings:

a Span: Zero span, centered on a hopping channel.
b RBW shall be ≤ channel spacing and where possible RBW should be set ≥ 1 / T, where T is the expected dwell time per channel.
c Sweep: As necessary to capture the entire dwell time per hopping channel; where possible use a video trigger and trigger delay so that the transmitted signal starts a little to the right of the start of the plot. The trigger level might need slight adjustment to prevent triggering when the system hops on an adjacent channel; a second plot might be needed with a longer sweep time to show two successive hops on a channel.
d Detector function: Peak.
e Trace: Max hold.

Test Data

Environmental Conditions

Temperature:	20 ℃
Relative Humidity:	51 %
ATM Pressure:	102.0 kPa

The testing was performed by Winnie Yang on 2019-11-16.

EUT operation mode: Hopping

Mode		Channel	Pulse Width (ms)	Dwell Time (s)	Limit (s)	Result
BDR (GFSK)	DH1	Low	0.409	0.131	0.4	Pass
		Middle	0.411	0.132	0.4	Pass
		High	0.409	0.131	0.4	Pass
		Note: DH1:Dwell time = Pulse time*(1600/2/79)*31.6S				
	DH3	Low	1.689	0.270	0.4	Pass
		Middle	1.683	0.269	0.4	Pass
		High	1.677	0.268	0.4	Pass
		Note: DH3:Dwell time = Pulse time*(1600/4/79)*31.6S				
	DH5	Low	2.943	0.314	0.4	Pass
		Middle	2.943	0.314	0.4	Pass
		High	2.919	0.311	0.4	Pass
		Note: DH5:Dwell time = Pulse time*(1600/6/79)*31.6S				
EDR (π/4-DQPSK)	2DH1	Low	0.416	0.133	0.4	Pass
		Middle	0.428	0.137	0.4	Pass
		High	0.420	0.134	0.4	Pass
		Note: 2DH1:Dwell time = Pulse time*(1600/2/79)*31.6S				
	2DH3	Low	1.701	0.272	0.4	Pass
		Middle	1.689	0.270	0.4	Pass
		High	1.689	0.270	0.4	Pass
		Note: 2DH3:Dwell time = Pulse time*(1600/4/79)*31.6S				
	2DH5	Low	2.939	0.313	0.4	Pass
		Middle	2.955	0.315	0.4	Pass
		High	2.947	0.314	0.4	Pass
		Note: 2DH5:Dwell time = Pulse time*(1600/6/79)*31.6S				
EDR (8DPSK)	3DH1	Low	0.424	0.136	0.4	Pass
		Middle	0.424	0.136	0.4	Pass
		High	0.426	0.136	0.4	Pass
		Note:3 DH1:Dwell time = Pulse time*(1600/2/79)*31.6S				
	3DH3	Low	1.676	0.268	0.4	Pass
		Middle	1.682	0.269	0.4	Pass
		High	1.688	0.270	0.4	Pass
		Note: 3DH3:Dwell time = Pulse time*(1600/4/79)*31.6S				
	3DH5	Low	2.947	0.314	0.4	Pass
		Middle	2.939	0.313	0.4	Pass
		High	2.971	0.317	0.4	Pass
		Note: 3DH5:Dwell time = Pulse time*(1600/6/79)*31.6S				

BDR (GFSK): Pulse time, Low Channel, DH1



BDR (GFSK): Pulse time, Middle Channel, DH1



BDR (GFSK): Pulse time, High Channel, DH1



BDR (GFSK): Pulse time, Low Channel, DH3



BDR (GFSK): Pulse time, Middle Channel, DH3



BDR (GFSK): Pulse time, High Channel, DH3



BDR (GFSK): Pulse time, Low Channel, DH5



BDR (GFSK): Pulse time, Middle Channel, DH5



BDR (GFSK): Pulse time, High Channel, DH5



Date: 16.NOV.2019 13:56:46

EDR (π/4-DQPSK): Pulse time, Low Channel, 2DH1



Date: 16.NOV.2019 13:57:59

EDR (π/4-DQPSK):Pulse time, Middle Channel, 2DH1



EDR (π/4-DQPSK):Pulse time, High Channel, 2DH1



EDR (π/4-DQPSK):Pulse time, Low Channel, 2DH3



EDR (π/4-DQPSK):Pulse time, Middle Channel, 2DH3



EDR (π/4-DQPSK):Pulse time, High Channel, 2DH3



EDR (π/4-DQPSK):Pulse time, Low Channel, 2DH5



EDR (π/4-DQPSK):Pulse time, Middle Channel, 2DH5



EDR (π/4-DQPSK):Pulse time, High Channel, 2DH5



EDR (8DPSK): Pulse time, Low Channel, 3DH1



EDR (8DPSK): Pulse time, Middle Channel, 3DH1



EDR (8DPSK): Pulse time, High Channel, 3DH1



EDR (8DPSK): Pulse time, Low Channel, 3DH3



EDR (8DPSK): Pulse time, Middle Channel, 3DH3



EDR (8DPSK): Pulse time, High Channel, 3DH3



EDR (8DPSK): Pulse time, Low Channel, 3DH5



EDR (8DPSK): Pulse time, Middle Channel, 3DH5



EDR (8DPSK): Pulse time, High Channel, 3DH5



FCC §15.247(b) (1) - PEAK OUTPUT POWER MEASUREMENT

Applicable Standard

According to §15.247(b) (1), for frequency hopping systems operating in the 2400–2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. And for all other frequency hopping systems in the 2400–2483.5 MHz band: 0.125 watts.

Test Procedure

a. Use the following spectrum analyzer settings:
   1) Span: Approximately five times the 20 dB bandwidth, centered on a hopping channel.
   2) RBW > 20 dB bandwidth of the emission being measured.
   3) VBW ≥ RBW.
   4) Sweep: Auto.
   5) Detector function: Peak.
   6) Trace: Max hold.

b. Allow trace to stabilize.
c. Use the marker-to-peak function to set the marker to the peak of the emission.
d. The indicated level is the peak output power, after any corrections for external attenuators and cables.
e. A plot of the test results and setup description shall be included in the test report.

Test Data

Environmental Conditions

Temperature:	20℃
Relative Humidity:	51%
ATM Pressure:	102.0kPa

The testing was performed by Winnie Yang on 2019-11-16.

EUT operation mode: Transmitting

Test Result: Compliant.

Mode	Frequency (MHz)	Output Power		Limit (mW)
		(dBm)	(mW)	
BDR (GFSK)	2402	2.47	1.77	125
	2441	1.70	1.48	125
	2480	0.48	1.12	125
EDR (π/4-DQPSK)	2402	4.91	3.10	125
	2441	3.99	2.51	125
	2480	2.97	1.98	125
EDR (8DPSK)	2402	5.52	3.56	125
	2441	4.65	2.92	125
	2480	3.48	2.23	125

BDR (GFSK): 2402MHz



BDR (GFSK): 2441MHz



BDR (GFSK): 2480MHz



EDR(π/4-DQPSK): 2402MHz



EDR(π/4-DQPSK): 2441MHz



Date: 16.NOV.2019 10:05:31

EDR(π/4-DQPSK): 2480MHz



Date: 16.NOV.2019 10:06:08

EDR(8DPSK): 2402MHz



EDR(8DPSK): 2441MHz



EDR(8DPSK): 2480MHz



FCC §15.247(d) - BAND EDGES TESTING

Applicable Standard

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates Compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Remove the antenna from the EUT and then connect to a low loss RF cable from the antenna port to a EMI test receiver, then turn on the EUT and make it operate in transmitting mode. Then set it to Low Channel and High Channel within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW of spectrum analyzer to 100 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.

Test Data

Environmental Conditions

Temperature:	20~21.2 ℃
Relative Humidity:	50~51%
ATM Pressure:	101.3~102.0 kPa

The testing was performed by Winnie Yang on 2019-11-16 .

EUT operation mode: Transmitting & Hopping.

Test Result: Compliant.

Band Edge

BDR (GFSK): Left Side - Transmitting



BDR (GFSK): Right Side - Transmitting



EDR (π/4-DQPSK): Left Side - Transmitting



EDR (π/4-DQPSK): Right Side - Transmitting



EDR (8DPSK): Left Side - Transmitting



EDR (8DPSK): Right Side - Transmitting



BDR (GFSK): Left Side - Hopping



BDR (GFSK): Right Side- Hopping



EDR (π/4-DQPSK): Left Side- Hopping



EDR (π/4-DQPSK): Right Side- Hopping



EDR (8DPSK): Left Side- Hopping



EDR (8DPSK): Right Side- Hopping



******* END OF REPORT *******