

RF-EXPOSURE REPORT FCC 47 CFR Part 2.1091 Maximum permissible exposure	
Report Reference No	G0M-2512-3459-TFC091MP01-V01
Testing Laboratory	Eurofins Product Service GmbH
Address	Storkower Str. 38c 15526 Reichenwalde Germany
Accreditation	  DAkkS - Deutsche Akkreditierungsstelle D-PL-12092-01-00 DAkkS - Registration number : D-PL-12092-01-00 FCC Filed Test Laboratory, Reg.-No.: 96970
Applicant	UAB Axioma Metering
Address	Veterinaru str. 52, Biruliskes, Kaunas county 54469 Kaunas Lithuania
Test Specification	According to FCC rules
Standard	FCC 47 CFR 2.1091
Non-Standard Test Method	None
Equipment under Test (EUT):	
Product Description	Ultrasonic water meter
Model(s)	Qalcosonic W1 DN15
Additional Model(s)	None
Brand Name(s)	Axioma Metering
Hardware Version(s)	T003.L2.04.00
Software Version(s)	5.X.X+I
FCC-ID	2AU8N-QW1
Test Result	PASSED

Possible test case verdicts:		
required by standard but not tested	N/T	
not required by standard	N/R	
test object does meet the requirement	P(PASS)	
test object does not meet the requirement	F(FAIL)	
Testing:		
Test Lab Temperature	20 °C - 30 °C	
Test Lab Humidity	25 % - 55 %	
Date of performance	2026-04-02	
Date of receipt of test item	See test sample identification table on page 8	
Report:		
Compiled by	Ehsan Sohrabi	
Tested by (+ signature) (Responsible for Test)	Ehsan Sohrabi	 Digitally signed by Ehsan Sohrabi Date: 2026.04.28 16:40:56 +02'00'
Approved by (+ signature) (Senior Radio Expert)	Radwan Jaafar	 Digitally signed by Radwan Jafaar Date: 2026.04.28 17:22:28 +02'00'
Date of Issue	2026-04-28	
Total number of pages	15	
General Remarks:		
The test results presented in this report relate only to the object tested. The results contained in this report reflect the results for this particular model and serial number. It is the responsibility of the manufacturer to ensure that all production models meet the intent of the requirements detailed within this report. This report shall not be reproduced, except in full, without the written approval of the Issuing testing laboratory. The above equipment has been tested by Eurofins Product Service GmbH, and found compliance with the requirements of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's RF characteristics under the conditions specified in this report. Compliance of electromagnetic emission from electronic and electrical equipment with the basic restrictions usually is determined by measurements and, in some cases, calculation of the exposure level. If the electrical power used by or radiated by the equipment is sufficiently low, the electromagnetic fields emitted will be incapable of producing exposures that exceed the basic restrictions. Any relevant compliance assessment procedure which is consistent with the state of the art, reproducible and gives valid results can be used.		

For transmitters intended for use with more than one antenna configuration option, the combination of transmitter and antenna(s) which generates the highest available antenna power and/or average total radiated power shall be assessed.

Additional Comments:

RF-Exposure calculation is based on measurement results from reference documents.

ADDITIONAL VARIANTS

Additional Variants (not tested and not evaluated variants)		
Not-tested Variant	Description	
1	Product Type Description	Ultrasonic water meter
	Model name	Qalcosonic W1 DN20
	Brand name	Axioma Metering
	Hardware Version	T003.L2.04.00
	Software Version	5.X.X+I
2	Product Type Description	Ultrasonic water meter
	Model name	Qalcosonic W1 DN25
	Brand name	Axioma Metering
	Hardware Version	T003.L2.04.00
	Software Version	5.X.X+I
3	Product Type Description	Ultrasonic water meter
	Model name	Qalcosonic W1 DN32
	Brand name	Axioma Metering
	Hardware Version	T003.L2.04.00
	Software Version	5.X.X+I
4	Product Type Description	Ultrasonic water meter
	Model name	Qalcosonic W1 DN40
	Brand name	Axioma Metering
	Hardware Version	T00C.L2.04.00
	Software Version	5.X.X+I
5	Product Type Description	Ultrasonic water meter
	Model name	Qalcosonic W1 DN50
	Brand name	Axioma Metering
	Hardware Version	T00C.L2.04.00
	Software Version	5.X.X+I
Comment: Those named additional variants above have not been tested. Those additional variants of the series have been declared by the manufacturer. The test report explicitly states that those variants were neither tested nor assessed nor evaluated.		

VERSION HISTORY

Version History			
Version	Issue Date	Remarks	Revised By
01	2026-04-28	Initial Release	--

ABBREVIATIONS AND ACRONYMS

Acronyms	
Acronym	Description
EIRP	Equivalent Isotropic Radiated Power
EUT	Equipment Under Test
MPE	Maximum Permissible Exposure

REPORT INDEX

1	Equipment (Test Item) Under Test.....	8
1.1	Reference Documents.....	9
1.2	Power density radiation sources.....	10
1.3	Field strength radiation sources	10
1.4	Concurrent Sources	10
2	Result Summary	11
3	RF-Exposure classification	12
4	RF-Exposure limits	13
5	RF-Exposure Evaluation.....	14
6	Single Source Evaluation Results - FCC.....	15

1 Equipment (Test Item) Under Test

Description	Ultrasonic water meter			
Model	Qalcosonic W1 DN15			
Additional Model(s)	None			
Brand Name(s)	Axioma Metering			
Sample Identification	EUT #	Sample-ID	Serial Number	Date of receipt
	EUT 1	See reference documents	See reference documents	See reference documents
Hardware Version(s)	T003.L2.04.00			
Software Version(s)	5.X.X+I			
FCC ID	2AU8N-QW1			
Equipment type	End Product			
Number of antenna ports	1			
Number of radios	1			
Radio Module	Type	SRD		
	Model	SX1262		
	Manufacturer	Semtech		
	HW Version	2.1		
	SW Version	2.1		
	FCC-ID	N/A		
Antenna	Type	Integrated antenna		
	Model	A002.05.01		
	Manufacturer	Axioma		
	Gain	4 dBi (antenna data sheet)		
Supply Voltage	V _{NOM}	3.6 V DC via internal lithium battery		
Dedicated AC/DC-Adaptor	None			
Environment	General public			

1.1 Reference Documents

Document Type	Document No.	Issued by	Date
Radio Test Report	G0M-2512-3459-TFC247DT01-V01	Eurofins Product Service GmbH	2026-04-28
Antenna data sheet	A002.05.01_datasheet	Axioma Metering	2026-04-01

1.2 Power density radiation sources

Mode	Operating Frequency [MHz]	Maximum conducted power [dBm]	Maximum radiated power [dBm EIRP]	Maximum duty cycle [%]	Tune-up tolerance [dB]	Maximum antenna gain [dBi]	Maximum antenna diameter [cm]
SRD 915 MHz	903	22.3	26.3	100	2.0	4	N/A
	915	21.9	25.9	100	2.0	4	N/A
	927	20.2	24.2	100	2.0	4	N/A
Comment: All conducted and radiated power values in this and all further tables are adjusted by given tune-up tolerance. The higher value of conducted and radiated power is chosen for evaluation. EIRP= Conducted power + Antenna gain							

1.3 Field strength radiation sources

None

1.4 Concurrent Sources

No concurrent radiation sources

2 Result Summary

FCC MPE Evaluation - Single radiation sources					
Product Standard Reference	Requirement	Reference Method	Mode	Distance [m]	Verdict
47 CFR 2.1091	Maximum permissible exposure	FCC KDB 447498	SRD 915 MHz	0.20	PASS
Comment: --					

3 RF-Exposure classification

RF-Exposure Categories	
Fixed	A fixed device is defined as a device physically secured at one fixed location and cannot be easily re-located.
Mobile	A mobile device is defined as a transmitting device designed to be used in other than fixed locations and to generally be used in such a way that a separation distance of at least 20 centimeters is normally maintained between the transmitter's radiating structure(s) and the body of the user or nearby persons.
Portable	A portable device is defined as a transmitting device designed to be used so that the radiating structure(s) of the device is/are within 20 centimeters of the body of the user.

RF-Exposure Categories	
Occupational / Controlled	Limits apply in situations in which persons are exposed as a consequence of their employment provided those persons are fully aware of the potential for exposure and can exercise control over their exposure. Limits for occupational/controlled exposure also apply in situations when an individual is transient through a location where occupational/controlled limits apply provided he or she is made aware of the potential for exposure.
General population / Uncontrolled	Exposures apply in situations in which the general public may be exposed, or in which persons that are exposed as a consequence of their employment may not be fully aware of the potential for exposure or cannot exercise control over their exposure.

4 RF-Exposure limits

FCC Limits – General Population / Uncontrolled Exposure				
Frequency range [MHz]	Electric field strength [V/M]	Magnetic field strength [A/M]	Power density [W/m ²]	Averaging time [min]
0.3 – 1.34	614	1.63	1000	30
1.34 – 30	824/f	2.19/f	1800/f ²	30
30 – 300	27.5	0.073	2	30
300 – 1500	-	-	f/150	30
1500 – 100000	-	-	10.0	30

FCC Limits – Occupational / Controlled Exposure				
Frequency range [MHz]	Electric field strength [V/M]	Magnetic field strength [A/M]	Power density [W/m ²]	Averaging time [min]
0.3 – 3.0	614	1.63	1000	6
3.0 – 30	1842/f	4.89/f	9000/f ²	6
30 – 300	61.4	0.163	10.0	6
300 – 1500	-	-	f/30	6
1500 – 100000	-	-	50	6

5 RF-Exposure Evaluation

Evaluation Relations
$\lambda[m] = \frac{c \left[\frac{m}{s} \right]}{f[Hz]} ; R_{FF}[m] \geq \frac{2 \cdot D[m]^2}{\lambda[m]}$ $S[W/m^2] = \frac{P_{E.I.R.P.}[W]}{4\pi R[m]^2} ; R[m] = \sqrt{\frac{P_{E.I.R.P.}[W]}{4\pi S[W/m^2]}}$ $DCC [dB] = 10 \cdot \log_{10} \left(\frac{DC[\%]}{100} \right)$ $\sum_{i=1}^N \frac{S_i \left[\frac{W}{m^2} \right]}{S_{Li} \left[\frac{W}{m^2} \right]} + \sum_{j=1}^M \left(\frac{E_j \left[\frac{V}{m} \right]}{E_{Lj} \left[\frac{V}{m} \right]} \right)^2 + \sum_{k=1}^O \left(\frac{H_k \left[\frac{A}{m} \right]}{H_{Lk} \left[\frac{A}{m} \right]} \right)^2 < 1$

Evaluation Procedure
<u>Standalone operation evaluation:</u> For each radio and frequency band the worst case transmission mode with the highest peak conducted or radiated power is evaluated at the frequency that results in the most restrictive rf-exposure limit. From the peak power values, antenna gains and duty cycles taken from the reference documents, the source average radiated power values are calculated. From the average radiated power the power densities at antenna far-field distance is calculated. The distance from the radiation source for compliance power density is calculated. If the separation distance is lower than the far-field distance, the far-field distance is given as compliance separation distance because the plane wave power density assessment is only valid in the far-field of the radiation source. For radiation sources for which the average electric and magnetic fields are measured using field probes, the measured field strength values are compared to the reference limits. For those sources no calculations are performed. Compliance with the reference values is determined with the near field measurements. <u>Concurrent operation evaluation:</u> First the evaluation distance is set to an appropriate value. For all radiation sources for which power densities are calculated, the power densities at the evaluation distance are calculated and for all other sources the electric or magnetic field strengths are measured using field probes. Finally the ratios of the power densities and/or field strength values and the corresponding limits are calculated and summed and the sum is compared to the maximum of 1.

6 Single Source Evaluation Results - FCC

SRD 915 MHz			
Transmission Mode			
Transmission Frequency (f) [MHz]	903	915	927
Antenna far-field distance			
Maximum antenna diameter (D) [m]	N/A	N/A	N/A
Transmission wavelength (λ) [m]	N/A	N/A	N/A
Antenna far-field distance (R_{FF}) [m]	N/A	N/A	N/A
Source average power			
Peak radiated power (PR) [dBm EIRP]	26.3	25.9	24.2
Maximum transmission duty cycle (DC)	1.00	1.00	1.00
Duty cycle correction (DCC) [dB]	0.00	0.00	0.00
Average radiated power (PRAVG) [dBm EIRP]	26.30	25.90	24.20
Power density			
Compliance power density limit [W/m ²]	6.020	6.100	6.180
Power density (S) @ Antenna far-field distance [W/m ²]	N/A	N/A	N/A
Power density (S) @ 0.20 m [W/m ²]	0.849	0.774	0.523
Power density ratio @ 0.20 m	0.14	0.13	0.08
Distance for compliance power density (S=SL) [m]	0.075	0.071	0.058
Compliance			
Verdict	PASS	PASS	PASS
Comment: --			

=== End of test report ===