LTA
Laboratory for Test & Approval Co.,Ltd.

243 Jubug-Ri,Yangji-Myeon, Yongin-Si, Gyeonggi-Do, Korea 17159
Tel: +82-31-323-6008 Fax: +82-31-323-6010
http://www.ltalab.com

Dates of Tests: Jun 11, 2020 ~ Jun 30, 2020
Test Report S/N: LR500112007C
Test Site : LTA CO., LTD.

CERTIFICATION OF COMPLIANCE

FCC ID. **2AU8YREBE-TZ21K**

APPLICANT **ATECAP Co., LTD.**

Equipment Class	:	**Digital Transmission System (DTS)**
Manufacturing Description	:	**Electronic Shelf Label**
Manufacturer	:	**ATECAP Co., LTD.**
Model name	:	**REBE-TZ21K**
Test Device Serial No.:	:	**Identical prototype**
Rule Part(s)	:	**FCC Part 15.247 Subpart C ; ANSI C63.10 - 2013**
Frequency Range	:	**Zigbee 2405 ~ 2480 MHz**
Max. Output Power	:	**Max 7.17 dBm - Conducted**
Data of issue	:	**July 01, 2020**

This test report is issued under the authority of:

JaBeom.Koo

Ja-Beom Koo, Manager

The test was supervised by:

Eun-Hwan Jung, Test Engineer

This test result only responds to the tested sample. It is not allowed to copy this report even partly without the allowance of the test laboratory. The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the Federal Government.

NVLAP

NVLAP LAB Code.: 200723-0

Copyright © 2020, LTA Co., Ltd.

TAZigbee OF CONTENTS

1. GENERAL INFORMATION ---------- 3

2. INFORMATION ABOUT TEST ITEM ---------- 4

3. TEST REPORT ---------- 5

3.1 SUMMARY OF TESTS ---------- 5

3.2 TECHNICAL CHARACTERISTICS TEST ---------- 6

3.2.1 6 dB BANDWIDTH ---------- 6

3.2.2 PEAK OUTPUT POWER ---------- 8

3.2.3 POWER SPECTRAL DENSITY ---------- 10

3.2.4 BAND EDGE ---------- 12

3.2.5 CONDUCTED SPURIOUS EMISSIONS ---------- 14

3.2.6 RADIATED SPURIOUS EMISSIONS ---------- 16

APPENDIX

APPENDIX TEST EQUIPMENT USED FOR TESTS ---------- 34

Copyright © 2020, LTA Co., Ltd.

1. General information

1-1 Test Performed

Company name : LTA Co., Ltd.
Address : 243, Jubug-ri,Yangji-Myeon,Youngin-Si, Kyunggi-Do, Korea. 17159
Web site : http://www.ltalab.com
E-mail : chahn@ltalab.com
Telephone : +82-31-323-6008
Facsimile +82-31-323-6010

Quality control in the testing laboratory is implemented as per ISO/IEC 17025 which is the "General requirements for the competents of calibration and testing laboratory".

1-2 Accredited agencies

LTA Co., Ltd. is approved to perform EMC testing by the following agencies:

Agency	Country	Accreditation No.	Validity	Reference
NVLAP	U.S.A	200723-0	2020-09-30	ECT accredited Lab.
RRA	KOREA	KR0049	-	EMC accredited Lab.
FCC	U.S.A	649054	2021-04-11	FCC CAB
VCCI	JAPAN	C-4948,	2020-09-10	VCCI registration
VCCI	JAPAN	T-2416,	2020-09-10	VCCI registration
VCCI	JAPAN	R-4483(10 m),	2020-10-15	VCCI registration
VCCI	JAPAN	G-847	2021-12-13	VCCI registration
IC	CANADA	5799A-1	2021-06-16	IC filing
KOLAS	KOREA	NO.551	2021-08-20	KOLAS accredited Lab.

Copyright © 2020, LTA Co., Ltd.

2. Information about test item

2-1 Client & Manufacturer

Client Company name	:	ATECAP Co., LTD.
Address	:	289, Pangyo-ro, Bundang-gu, Seongnam-si, Gyeonggi-do, 13488, South Korea
Tel / Fax	:	+82-10-5790-6171 / +82-31-696-1534
Manufacturer		ATECAP Co., LTD.
Address		53-94 Jinwisandan-ro, jinwi-myeon, Pyeongtaek-si, Gyeonggi-do, Korea
Tel / Fax		+82-10-5790-6171 / +82-31-696-1534

2-2 Equipment Under Test (EUT)

Model name	:	REBE-TZ21K
Serial number	:	Identical prototype
Date of receipt	:	June 11, 2020
EUT condition	:	Pre-production, not damaged
Antenna type	:	Pattern Antenna (Max Gain : -4.72 dBi)
Frequency Range	:	Zigbee 2405 ~ 2480 MHz
RF output power	:	Max 7.17 dBm – Conducted
Type of Modulation	:	Pi/4 DQPSK, 8DPSK
Power Source	:	DC 3.0 V

2-3 Tested frequency

	LOW	MID	HIGH
Frequency (MHz) Zigbee	2405	2440	2480

2-4 Ancillary Equipment

Equipment	Model No.	Serial No.	Manufacturer
Notebook	-	MS-1736	MSI

Copyright © 2020, LTA Co., Ltd.

3. Test Report

3.1 Summary of tests

FCC Part Section(s)	Parameter	Test Condition	Status (note 1)
15.247(a)	6 dB Bandwidth	Conducted	C
15.247(b)	Transmitter Peak Output Power		C
15.247(e)	Transmitter Power Spectral Density		C
15.247(d)	Band Edge & Conducted Spurious emission		C
15.209	Transmitter emission	Radiated	C
15.207	AC Conducted Emissions	Conducted	N/A
15.203	Antenna requirement	-	C

N/A : This product is battery-enabled and excludes the test.

The above equipment was tested by LTA Co., Ltd. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.10-2013 and the energy emitted by the sample EUT tested as described in this report is in compliance with the requirements of FCC Rules Part 2 and Part 15.247 The test results of this report relate only to the tested sample identified in this report.
The tests were performed according to the method of measurements prescribed in KDB No.558074.

→ Antenna Requirement
ATECAP Co., LTD. FCC ID: 2AU8YREBE-TZ21K unit complies with the requirement of §15.203.
The antenna type is FPCB Antenna

Copyright © 2020, LTA Co., Ltd.

3.2 Technical Characteristics Test

3.2.1 6 dB Bandwidth

Procedure:

The bandwidth at 6 dB below the highest in-band spectral density was measured with a spectrum analyzer connected to the antenna terminal, while EUT is operating in transmission mode at the appropriate frequencies.

After the trace being stable, Use the marker-to-peak function to set the marker to the peak of the emission. Use the marker-delta function to measure 6 dB down one side of the emission. Reset the marker-delta function, and move the marker to the other side of the emission, until it is (as close as possible to) even with the reference marker level. The marker-delta reading at this point is the 6 dB bandwidth of the emission.

The spectrum analyzer is set to:

Center frequency = the highest, middle and the lowest channels

RBW = 100 kHz

Span = 3 X RBW

VBW = 3 X RBW

Sweep = auto

Trace = max hold

Detector function = peak

Measurement Data : Complies

Zigbee Mode

Frequency (MHz)	Test Results	
	Measured Bandwidth (MHz)	Result
2405	**1.852**	Complies
2440	**1.889**	Complies
2480	**1.845**	Complies

- See next pages for actual measured spectrum plots.

Minimum Standard:

6 dB Bandwidth ≥ 500 kHz

Measurement Setup



Figure 1: Measurement setup for the carrier frequency separation

Zigbee


Spectrum
Spectrum 2
Spectrum 3
Spectrum 4
Ref Level 20.00 dBm Offset 0.70 dB RBW 100 kHz
Att 35 dB SWT 1 ms VBW 300 kHz Mode Sweep
1Pk Max
M1[1] 1.18 dBm
2.40500000 GHz
ndB 6.00 dB
Bw 1.852400000 MHz
Q factor 1298.3
10 dBm
0 dBm
-10 dBm
-20 dBm
-30 dBm
-40 dBm
-50 dBm
-60 dBm
-70 dBm
CF 2.405 GHz
691 pts
Span 5.0 MHz
Marker
Type Ref Trc X-value Y-value Function Function Result
M1 1 2.405 GHz 1.18 dBm ndB down 1.8524 MHz
T1 1 2.4040666 GHz -4.96 dBm ndB 6.00 dB
T2 1 2.405919 GHz -4.73 dBm Q factor 1298.3
Measuring...
17.06.2020
11:30:52


Spectrum
Spectrum 2
Spectrum 3
Spectrum 4
Ref Level 20.00 dBm Offset 0.70 dB RBW 100 kHz
Att 35 dB SWT 1 ms VBW 300 kHz Mode Sweep
1Pk Max
M1[1] 0.98 dBm
2.44000000 GHz
ndB 6.00 dB
Bw 1.888600000 MHz
Q factor 1292.0
10 dBm
0 dBm
-10 dBm
-20 dBm
-30 dBm
-40 dBm
-50 dBm
-60 dBm
-70 dBm
CF 2.44 GHz
691 pts
Span 5.0 MHz
Marker
Type Ref Trc X-value Y-value Function Function Result
M1 1 2.44 GHz 0.98 dBm ndB down 1.8886 MHz
T1 1 2.4390449 GHz -5.03 dBm ndB 6.00 dB
T2 1 2.4409334 GHz -5.12 dBm Q factor 1292.0
Measuring...


Spectrum
Spectrum 2
Spectrum 3
Spectrum 4
Ref Level 20.00 dBm Offset 0.70 dB RBW 100 kHz
Att 35 dB SWT 1 ms VBW 300 kHz Mode Sweep
1Pk Max
M1[1] 1.46 dBm
2.48000000 GHz
ndB 6.00 dB
Bw 1.845200000 MHz
Q factor 1344.1
10 dBm
0 dBm
-10 dBm
-20 dBm
-30 dBm
-40 dBm
-50 dBm
-60 dBm
-70 dBm
CF 2.48 GHz
691 pts
Span 5.0 MHz
Marker
Type Ref Trc X-value Y-value Function Function Result
M1 1 2.48 GHz 1.46 dBm ndB down 1.8452 MHz
T1 1 2.4790738 GHz -4.41 dBm ndB 6.00 dB
T2 1 2.480919 GHz -4.59 dBm Q factor 1344.1
Measuring...
17.06.2020
11:31:42

3.2.2 Peak Output Power Measurement

Procedure:

The following procedure can be used when the maximum available RBW of the instrument is less than the DTS bandwidth :

The spectrum analyzer is set to:

Center frequency = the highest, middle and the lowest channels

RBW ≥ DTS Bandwidth

Span ≥ 3 X RBW

VBW = 3 X RBW

Sweep = auto

Detector function = peak

Measurement Data : Complies

Zigbee Mode

Frequency (MHz)	Test Results	
	Measured data (dBm)	Result
2405	**6.77**	Complies
2440	**7.05**	Complies
2480	**7.17**	Complies

- See next pages for actual measured spectrum plots.

Minimum Standard:

Peak output power	≤ 1 W(30 dBm)

Measurement Setup

Same as the Chapter 3.2.1 (Figure 1)

Copyright © 2020, LTA Co., Ltd.

Zigbee







Copyright © 2020, LTA Co., Ltd.

3.2.3 Power Spectral Density

Procedure:

This procedure shall be used if maximum peak conducted output power was used to demonstrate compliance.

The spectrum analyzer is set to:

RBW = 3 kHz (3 kHz≤RBW≤100 kHz) Span ≥ 1.5 times the DTS bandwidth

VBW = 3 X RBW Sweep = auto

Detector function = peak Trace = max hold

Measurement Data : Complies

Zigbee Mode

Frequency (MHz)	Test Results	
	dBm / 3 kHz BW	Result
2405	**-9.54**	Complies
2440	**-9.42**	Complies
2480	**-8.92**	Complies

- See next pages for actual measured spectrum plots.

Minimum Standard:

Power Spectral Density	≤ 8 dBm @ 3 kHz BW

Measurement Setup

Same as the Chapter 3.2.1 (Figure 1)

Zigbee







Copyright © 2020, LTA Co., Ltd.

3.2.4 Band Edge

Procedure:

The Unwanted emission from the EUT were measured according to the dictates PKPSD measurement procedure in section 11.11 of ANSI C63.10-2013.

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated device is operating, the RF power that is produced shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided that the transmitter demonstrates compliance with the peak conducted power limits.

If the transmitter complies with the conducted power limits based on the use of root-mean-square averaging over a time interval, as permitted under Section 5.4(4), the attenuation required shall be 30 dB instead of 20 dB..

The spectrum analyzer is set to:

Center frequency = the highest, middle and the lowest channels

RBW = 1 MHz VBW ≥ 3 X RBW

Detector function = peak Trace = max hold

Sweep = auto

Measurement Data: Complies

- All conducted emission in any 100 kHz bandwidth outside of the spread spectrum band was at least 20 dB lower than the highest inband spectral density. Therefore the applying equipment meets the require ment.

- See next pages for actual measured spectrum plots.

Minimum Standard:	≤ 20 dBc

Copyright © 2020, LTA Co., Ltd.

Zigbee


Spectrum
Spectrum 2
Spectrum 3
Spectrum 4
Ref Level 12.00 dBm Offset 0.70 dB RBW 100 kHz
Att 30 dB SWT 38 µs VBW 300 kHz Mode Auto FFT
1Pk Max
D1[1]
M1[1]
M1
-41.70 dB
-4.8340 MHz
3.76 dBm
2.4047470 GHz
0 dBm
-10 dBm
-20 dBm
-30 dBm
-40 dBm
-50 dBm
-60 dBm
-70 dBm
-80 dBm
D1
CF 2.4 GHz
691 pts
Span 20.0 MHz
Measuring...
17.06.2020
11:45:36


Spectrum
Spectrum 2
Spectrum 3
Spectrum 4
Ref Level 12.00 dBm Offset 0.70 dB RBW 100 kHz
Att 30 dB SWT 38 µs VBW 300 kHz Mode Auto FFT
1Pk Max
D1[1]
M1[1]
M1
-36.65 dB
4.1680 MHz
4.28 dBm
2.4797370 GHz
0 dBm
-10 dBm
-20 dBm
-30 dBm
-40 dBm
-50 dBm
-60 dBm
-70 dBm
-80 dBm
D1
CF 2.4835 GHz
691 pts
Span 20.0 MHz
Measuring...
17.06.2020
11:46:10

3.2.5 Conducted Spurious Emissions

Procedure:

The test follows KDB558074. The conducted spurious emissions were measured with a spectrum analyzer connected to the antenna terminal, while EUT had its hopping function disabled at the highest, middle and the lowest available channels.

After the trace being stable, set the marker on the peak of any spurious emission recorded.

The spectrum analyzer is set to:

Span = wide enough to capture the peak level of the in-band emission and all spurious emissions

RBW = 100 kHz Sweep = auto

VBW = 100 kHz Detector function = peak

Trace = max hold

Measurement Data: Complies

- All conducted emission in any 100 kHz bandwidth outside of the spread spectrum band was at least 20 dB lower than the highest inband spectral density. Therefore the applying equipment meets the require ment.
- See next pages for actual measured spectrum plots.

Minimum Standard:	≥ 20 dBc

Measurement Setup

Same as the Chapter 3.2.1 (Figure 1)

Unwanted Emission – Zigbee (Low,Middle,High)







Copyright © 2020, LTA Co., Ltd.

3.2.6 Radiated Spurious Emissions

Procedure:

Radiated emissions from 30 MHz to 25 GHz were measured according to the methods defines in ANSI C63.10-2013. The EUT is a placed on as turn table. For emissions testing at or below 1 GHz, the table height shall be 0.8 m above the reference ground plane. For emission measurements above 1 GHz, the table height shall be 1.5 m. The turn table shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3m away from the receiving antenna which varied from 1m to 4m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the max. emission, the relative positions of this hand-held transmitter (EUT) was rotated through three orthogonal axes and measurement procedures for electric field radiated emissions above 1 GHz the EUT measurement is to be made "while keeping the antenna in the 'cone of radiation' from that area and pointed at the area both in azimuth and elevation, with polarization oriented for maximum response." is still within the 3dB illumination BW of the measurement antenna.

The spectrum analyzer is set to:

Center frequency = the worst channel

Frequency Range = 9 kHz ~ 10th harmonic.

RBW = 120 kHz (30 MHz ~ 1 GHz) VBW ≥ RBW

= 1 MHz (1 GHz ~ 10th harmonic)

Trace = max hold Detector function = peak

Sweep = auto

Duty cycle : 98.89 %

The EUT configureal to transmit continuously(D ≥ 98%)/ Duty Factor = 0

below 30 MHz



below 1 GHz (30 MHz to 1 GHz)



above 1 GHz



Measurement Data: Complies

- See next pages for actual measured data.
- No other emissions were detected at a level greater than 20 dB below limit include from 9 kHz to 30MHz.
- The test results for the worst of the various operating modes are presented in accordance with 6.3.4 of ANSI C63.10.
- Checked with a red circle is the fundamental frequency.

Minimum Standard: FCC Part 15.209(a)

Frequency (MHz)	Limit (uV/m) @ 3 m
0.009 ~ 0.490	2400/F(kHz) **(@ 300 m)**
0.490 ~ 1.705	24000/F(kHz) **(@ 30 m)**
1.705 ~ 30	30**(@ 30 m)**
30 ~ 88	100 **
88 ~ 216	150 **
216 ~ 960	200 **
Above 960	500

** Except as provided in 15.209(g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g. 15.231 and 15.241.

Copyright © 2020, LTA Co., Ltd.

Radiated Emissions – Zigbee

LTA

4, Songjuro 236Beon-gil, yanggi-myeon,
Yongin-si, Gyeonggi-do, Korea
Tel : +82-31-3236008,9
Fax : +82-31-3236010
www.ltalab.com

EUT/Model No.: REBE-TZ21K Temp/Humi: 23 'C / 45 % R.H.

Test Mode : Operating mode Tested by: JUGN E H

Power :



No.	Freq MHz	Reading dBµV	C.F dB	Result QP dBµV/m	Limit dBµV/m	Margin dB	Height cm	Angle deg	Polarity
1.	192.00	50.58	-17.39	33.19	43.52	10.33	208	0	horizontal
2.	336.04	49.25	-13.18	36.07	46.02	9.95	100	0	horizontal
3.	408.05	44.98	-12.31	32.67	46.02	13.35	100	199	horizontal

Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain

- 1 -

Copyright © 2020, LTA Co., Ltd.

LTA

4, Songjuro 236Beon-gil, yanggi-myeon,
Yongin-si, Gyeonggi-do, Korea
Tel : +82-31-3236008,9
Fax : +82-31-3236010
www.ltalab.com

EUT/Model No.: REBE-TZ21K Temp/Humi: 23 'C / 45 % R.H.

Test Mode : Operating mode Tested by: JUGN E H

Power :



No.	Freq MHz	Reading dBµV	C.F dB	Result QP dBµV/m	Limit dBµV/m	Margin dB	Height cm	Angle deg	Polarity
1.	41.82	40.23	-15.02	25.21	40.00	14.79	100	304	vertical
2.	140.03	43.01	-15.18	27.83	43.52	15.69	100	352	vertical
3.	600.11	44.27	-9.20	35.07	46.02	10.95	100	141	vertical

Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain

- 1 -

Copyright © 2020, LTA Co., Ltd.

4, Songjuro 236Beon-gil, yanggi-myeon,
Yongin-si, Gyeonggi-do, Korea
Tel : +82-31-3236008,9
Fax : +82-31-3236010
www.ltalab.com

EUT/Model No.: REBE-TZ21K Temp/Humi: 23 'C / 45 % R.H.

Test Mode : Operating mode-M Tested by: JUGN E H

Power :



No.	Freq MHz	Reading dBµV	C.F dB	Result QP dBµV/m	Limit dBµV/m	Margin dB	Height cm	Angle deg	Polarity
1.	168.05	49.10	-14.93	34.17	43.52	9.35	100	208	horizontal
2.	192.00	51.06	-17.39	33.67	43.52	9.85	192	0	horizontal
3.	336.04	49.80	-13.18	36.62	46.02	9.40	100	0	horizontal

Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain

- 1 -

Copyright © 2020, LTA Co., Ltd.

4, Songjuro 236Beon-gil, yanggi-myeon,
Yongin-si, Gyeonggi-do, Korea
Tel : +82-31-3236008,9
Fax : +82-31-3236010
www.ltalab.com

EUT/Model No.: REBE-TZ21K Temp/Humi: 23 'C / 45 % R.H.

Test Mode : Operating mode-M Tested by: JUGN E H

Power :



No.	Freq MHz	Reading dBµV	C.F dB	Result QP dBµV/m	Limit dBµV/m	Margin dB	Height cm	Angle deg	Polarity
1.	140.10	41.93	-15.17	26.76	43.52	16.76	100	0	vertical
2.	504.04	37.93	-11.14	26.79	46.02	19.23	100	233	vertical
3.	600.11	39.98	-9.20	30.78	46.02	15.24	100	186	vertical

Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain

- 1 -

Copyright © 2020, LTA Co., Ltd.

4, Songjuro 236Beon-gil, yanggi-myeon,
Yongin-si, Gyeonggi-do, Korea
Tel : +82-31-3236008,9
Fax : +82-31-3236010
www.ltalab.com

EUT/Model No.: REBE-TZ21K Temp/Humi: 23 'C / 45 % R.H.

Test Mode : Operating mode-H Tested by: JUGN E H

Power :



No.	Freq MHz	Reading dBµV	C.F dB	Result QP dBµV/m	Limit dBµV/m	Margin dB	Height cm	Angle deg	Polarity
1.	168.05	48.78	-14.93	33.85	43.52	9.67	100	207	horizontal
2.	192.00	50.89	-17.39	33.50	43.52	10.02	137	0	horizontal
3.	336.04	49.16	-13.18	35.98	46.02	10.04	100	347	horizontal

Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain

Copyright © 2020, LTA Co., Ltd.

LTA

4, Songjuro 236Beon-gil, yanggi-myeon,
Yongin-si, Gyeonggi-do, Korea
Tel : +82-31-3236008,9
Fax : +82-31-3236010
www.ltalab.com

EUT/Model No.: REBE-TZ21K Temp/Humi: 23 'C / 45 % R.H.

Test Mode : Operating mode-H Tested by: JUGN E H

Power :



No.	Freq MHz	Reading dBµV	C.F dB	Result QP dBµV/m	Limit dBµV/m	Margin dB	Height cm	Angle deg	Polarity
1.	139.18	41.94	-15.19	26.75	43.52	16.77	100	12	vertical
2.	504.04	37.25	-11.14	26.11	46.02	19.91	100	232	vertical
3.	600.11	39.47	-9.20	30.27	46.02	15.75	100	197	vertical

Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain

- 1 -

Copyright © 2020, LTA Co., Ltd.

LTA

4, Songjuro 236Beon-gil, yanggi-myeon,
Yongin-si, Gyeonggi-do, Korea
Tel : +82-31-3236008,9
Fax : +82-31-3236010
www.ltalab.com

EUT/Model No.: REBE-TZ21K Temp/Humi: 23 'C / 45 % R.H.

Test Mode : Operating mode Tested by: JUGN E H

Power :



No.	Freq MHz	Reading dBμV	C.F dB	Result QP dBμV/m	Limit dBμV/m	Margin dB	Height cm	Angle deg	Polarity
1.	1736.83	41.53	-9.16	32.37	74.00	41.63	100	16	horizontal
2.	4879.33	42.23	0.92	43.15	74.00	30.85	100	158	horizontal

Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain

- 1 -

Copyright © 2020, LTA Co., Ltd.

4, Songjuro 236Beon-gil, yanggi-myeon,
Yongin-si, Gyeonggi-do, Korea
Tel : +82-31-3236008,9
Fax : +82-31-3236010
www.ltalab.com

EUT/Model No.: REBE-TZ21K Temp/Humi: 23 'C / 45 % R.H.

Test Mode : Operating mode Tested by: JUGN E H

Power :



No.	Freq MHz	Reading dBμV	C.F dB	Result QP dBμV/m	Limit dBμV/m	Margin dB	Height cm	Angle deg	Polarity
1.	1795.53	44.99	-8.84	36.15	74.00	37.85	100	190	vertical
2.	2999.19	48.84	-4.33	44.51	74.00	29.49	100	84	vertical

Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain

- 1 -

Copyright © 2020, LTA Co., Ltd.

LTA

4, Songjuro 236Beon-gil, yanggi-myeon,
Yongin-si, Gyeonggi-do, Korea
Tel : +82-31-3236008,9
Fax : +82-31-3236010
www.ltalab.com

EUT/Model No.: REBE-TZ21K Temp/Humi: 23 'C / 45 % R.H.

Test Mode : Operating mode-M Tested by: JUGN E H

Power :



No.	Freq MHz	Reading dBµV	C.F dB	Result QP dBµV/m	Limit dBµV/m	Margin dB	Height cm	Angle deg	Polarity
1.	1194.54	46.69	-11.26	35.43	74.00	38.57	100	0	horizontal
2.	1798.78	45.97	-8.82	37.15	74.00	36.85	100	0	horizontal
3.	4881.09	41.92	0.92	42.84	74.00	31.16	100	153	horizontal

Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain

Copyright © 2020, LTA Co., Ltd.

4, Songjuro 236Beon-gil, yanggi-myeon,
Yongin-si, Gyeonggi-do, Korea
Tel : +82-31-3236008,9
Fax : +82-31-3236010
www.ltalab.com

EUT/Model No.: REBE-TZ21K Temp/Humi: 23 'C / 45 % R.H.

Test Mode : Operating mode-M Tested by: JUGN E H

Power :



No.	Freq MHz	Reading dBμV	C.F dB	Result QP dBμV/m	Limit dBμV/m	Margin dB	Height cm	Angle deg	Polarity
1.	1197.13	46.65	-11.26	35.39	74.00	38.61	100	360	vertical
2.	1996.75	43.55	-5.96	37.59	74.00	36.41	100	353	vertical

Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain

- 1 -

Copyright © 2020, LTA Co., Ltd.

4, Songjuro 236Beon-gil, yanggi-myeon,
Yongin-si, Gyeonggi-do, Korea
Tel : +82-31-3236008,9
Fax : +82-31-3236010
www.ltalab.com

EUT/Model No.: REBE-TZ21K Temp/Humi: 23 'C / 45 % R.H.

Test Mode : Operating mode-H Tested by: JUGN E H

Power :



No.	Freq MHz	Reading dBμV	C.F dB	Result QP dBμV/m	Limit dBμV/m	Margin dB	Height cm	Angle deg	Polarity
1.	1796.83	46.96	-8.83	38.13	74.00	35.87	100	347	horizontal
2.	4961.10	41.50	1.16	42.66	74.00	31.34	100	358	horizontal

Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain

- 1 -

Copyright © 2020, LTA Co., Ltd.

4, Songjuro 236Beon-gil, yanggi-myeon,
Yongin-si, Gyeonggi-do, Korea
Tel : +82-31-3236008,9
Fax : +82-31-3236010
www.ltalab.com

EUT/Model No.: REBE-TZ21K Temp/Humi: 23 'C / 45 % R.H.

Test Mode : Operating mode-H Tested by: JUGN E H

Power :



No.	Freq MHz	Reading dBµV	C.F dB	Result QP dBµV/m	Limit dBµV/m	Margin dB	Height cm	Angle deg	Polarity
1.	1199.29	48.27	-11.24	37.03	74.00	36.97	100	299	vertical
2.	1792.94	49.21	-8.85	40.36	74.00	33.64	100	286	vertical
3.	1996.03	47.33	-5.98	41.35	74.00	32.65	100	82	vertical
4.	2401.62	88.28	-6.31	81.97	74.00	-7.97	100	24	vertical

Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain

- 1 -

Copyright © 2020, LTA Co., Ltd.

LTA

4, Songjuro 236Beon-gil, yanggi-myeon,
Yongin-si, Gyeonggi-do, Korea
Tel : +82-31-3236008,9
Fax : +82-31-3236010
www.ltalab.com

EUT/Model No.: REBE-TZ21K Temp/Humi: 23 'C / 45 % R.H.

Test Mode : Operating mode Tested by: JUGN E H

Power :



- 1 -

Copyright © 2020, LTA Co., Ltd.

4, Songjuro 236Beon-gil, yanggi-myeon,
Yongin-si, Gyeonggi-do, Korea
Tel : +82-31-3236008,9
Fax : +82-31-3236010
www.ltalab.com

EUT/Model No.: REBE-TZ21K
Temp/Humi: 23 'C / 45 % R.H.
Test Mode : Operating mode
Tested by: JUGN E H
Power :



- 1 -

Copyright © 2020, LTA Co., Ltd.

3.2.7 AC Conducted Emissions

Procedure:

The conducted emissions are measured in the shielded room with a spectrum analyzer in peak hold. While the measurement, EUT had its hopping function disabled at the middle channels in line with Section 15.31(m). Emissions closest to the limit are measured in the quasi-peak mode (QP) with the tuned receiver using a bandwidth of 9 kHz. The emissions are maximized further by cable manipulation and Exerciser operation. The highest emissions relative to the limit are listed.

Minimum Standard: FCC Part 15.207(a) / EN 55022

Measurement Data: N/A

Class B

Frequency Range	quasi-peak	Average
0.15 ~ 0.5	66 to 56 *	56 to 46 *
0.5 ~ 5	56	46
5 ~ 30	60	50

* Decreases with the logarithm of the frequency

Copyright © 2020, LTA Co., Ltd.

APPENDIX

TEST EQUIPMENT USED FOR TESTS

	Use	Description	Model No.	Serial No.	Manufacturer	Interval	Next Cal. Date
1	■	Signal Analyzer (9 kHz ~ 30 GHz)	FSV30	100757	R&S	1 year	2020-09-06
2	■	Signal Generator (~3.2 GHz)	8648C	3623A02597	HP	1 year	2020-03-20
3		SYNTHESIZED CW GENERATOR	83711B	US34490456	HP	1 year	2020-03-20
4		Attenuator (3 dB)	8491A	37822	HP	1 year	2020-09-06
5		Attenuator (10 dB)	8491A	63196	HP	1 year	2020-09-06
6	■	EMI Test Receiver (~7 GHz)	ESCI7	100722	R&S	1 year	2020-09-06
7		RF Amplifier (~1.3 GHz)	8447D OPT 010	2944A07684	HP	1 year	2020-09-06
8		RF Amplifier (1~26.5 GHz)	8449B	3008A02126	HP	1 year	2020-03-20
9	■	Horn Antenna (1~18 GHz)	3115	00114105	ETS	2 year	2020-08-04
10		DRG Horn (Small)	3116B	81109	ETS-Lindgren	2 year	2020-03-18
11		DRG Horn (Small)	3116B	133350	ETS-Lindgren	2 year	2020-03-18
12	■	TRILOG Antenna	VULB 9160	9160-3237	SCHWARZBECK	2 year	2021-03-20
13		Temp.Humidity Data Logger	SK-L200TH II A	00801	SATO	1 year	2020-03-20
14		Splitter (SMA)	ZFSC-2-2500	SF617800326	Mini-Circuits	-	-
15	■	DC Power Supply	6674A	3637A01657	Agilent	-	-
17	■	Power Meter	EPM-441A	GB32481702	HP	1 year	2020-03-20
18	■	Power Sensor	8481A	3318A94972	HP	1 year	2020-09-06
19		Audio Analyzer	8903B	3729A18901	HP	1 year	2020-09-06
20		Moduleation Analyzer	8901B	3749A05878	HP	1 year	2020-09-06
21		TEMP & HUMIDITY Chamber	YJ-500	LTAS06041	JinYoung Tech	1 year	2020-09-06
22		Stop Watch	HS-3	812Q08R	CASIO	2 year	2020-03-18
23		LISN	KNW-407	8-1430-1	Kyoritsu	1 year	2020-09-06
24		Two-Lime V-Network	ESH3-Z5	893045/017	R&S	1 year	2020-03-18
25		UNIVERSAL RADIO COMMUNICATION TESTER	CMU200	106243	R&S	1 year	2020-03-18
26		Highpass Filter	WHKX1.5/15G-10SS	74	Wainwright Instruments	1 year	2020-03-18
27		Highpass Filter	WHKX3.0/18G-10SS	118	Wainwright Instruments	1 year	2020-03-18
28		OSP120 BASE UNIT	OSP120	101230	R&S	1 year	2020-03-18
29		Signal Generator(100 kHz ~ 40 GHz)	SMB100A03	177621	R&S	1 year	2020-03-18
30		Signal Analyzer (10 Hz ~ 40 GHz)	FSV40	101367	R&S	1 year	2020-03-18
31	■	Active Loop Antenna	FMZB 1519	1519-031	SCHWARZBECK	2 year	2021-02-26

Copyright © 2020, LTA Co., Ltd.