FCC TEST REPORT

Product Name:	Electronic Visitor Verification PDA
Trade Mark:	N/A
Model No.:	T5
Add. Model No.:	N/A
FCC ID:	2AU94T5
Report Number:	191226037EMC-1
Test Standards:	FCC 47 CFR Part 15 Subpart B
Test Result:	PASS
Date of Issue:	April 2, 2020

Prepared for:

Sandata Technologies, LLC
26 Harbor Park Drive, Port Washington, NY 11050

Prepared by:

Shenzhen UnionTrust Quality and Technology Co., Ltd.
16/F, Block A, Building 6, Baoneng Science and Technology Park,
Qingxiang Road No.1, Longhua New District, Shenzhen, China
TEL: +86-755-2823 0888
FAX: +86-755-2823 0886

Prepared by:	Tony Wang Project Engineer	Reviewed by:	Kevin Liang Assistant Manager
Approved by:	Billy Li Technical Director	Date:	April 2, 2020

UnionTrust Laboratories UnionTrust * Certified *

Version

Version No.	Date	Description
V1.0	April 2, 2020	Original

CONTENTS

1. GENERAL INFORMATION 4
   1.1 CLIENT INFORMATION 4
   1.2 EUT INFORMATION 4
      1.2.1 GENERAL DESCRIPTION OF EUT 4
      1.2.2 DESCRIPTION OF ACCESSORIES 4
   1.3 DESCRIPTION OF SUPPORT UNITS 5
   1.4 TEST LOCATION 5
   1.5 TEST FACILITY 5
   1.6 DEVIATION FROM STANDARDS 5
   1.7 ABNORMALITIES FROM STANDARD CONDITIONS 5
   1.8 OTHER INFORMATION REQUESTED BY THE CUSTOMER 6
   1.9 MEASUREMENT UNCERTAINTY 6
2. TEST SUMMARY 7
3. EQUIPMENT LIST 8
4. TEST CONFIGURATION 9
   4.1 ENVIRONMENTAL CONDITIONS FOR TESTING 9
      4.1.1 NORMAL OR EXTREME TEST CONDITIONS 9
      4.1.2 RECORD OF NORMAL ENVIRONMENT 9
   4.2 TEST MODES 9
   4.3 TEST SETUP 9
      4.3.1 FOR RADIATED EMISSIONS TEST SETUP 9
      4.3.2 FOR CONDUCTED EMISSIONS TEST SETUP 10
   4.4 SYSTEM TEST CONFIGURATION 10
5. REFERENCE DOCUMENTS FOR TESTING 11
6. EMC REQUIREMENTS SPECIFICATION 11
   6.1 RADIATED EMISSION 11
   6.2 CONDUCTED EMISSION 16

APPENDIX 1 PHOTOS OF TEST SETUP 19
APPENDIX 2 PHOTOS OF EUT CONSTRUCTIONAL DETAILS 19

1. GENERAL INFORMATION

1.1 CLIENT INFORMATION

Applicant:	Sandata Technologies, LLC
Address of Applicant:	26 Harbor Park Drive, Port Washington, NY 11050
Manufacturer:	Sandata Technologies, LLC
Address of Manufacturer:	26 Harbor Park Drive, Port Washington, NY 11050

1.2 EUT INFORMATION

1.2.1 General Description of EUT

Product Name:	Electronic Visitor Verification PDA
Model No.:	T5
Add. Model No.:	N/A
Trade Mark:	N/A
DUT Stage:	Identical Prototype
Rated Voltage:	☒ 100-240V~50/60Hz, 0.2A and/or 3.8Vdc (1x3.8V Li-ion Rechargeable battery)
Classification of digital devices:	Class B
Highest Internal Frequency:	5845 MHz
Software Version:	Sandata_T5_20200102
Hardware Version:	H5E3H V2 20191109
Sample Received Date:	March 5, 2020
Sample Tested Date:	March 5, 2020 to March 25, 2020

1.2.2 Description of Accessories

Adapter	
Model No.:	TPA-46B050100UU
Input:	100-240 V~50/60 Hz 0.2A
Output:	5.0 V ⎓ 1000m A

Battery	
Model No.:	T5
Battery Type:	Lithium-ion Rechargeable Battery
Rated Voltage:	3.8 Vdc
Limited Charge Voltage:	4.35 Vdc
Rated Capacity:	2000 mAh

Cable	
Description:	USB Micro-B Plug Cable
Cable Type:	Unshielded without ferrite

1.3 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested with associated equipment below.

1) Support Equipment

Description	Manufacturer	Model No.	Serial Number	Supplied by
Notebook	Lenovo	E450	SL10G10780	UnionTrust
Wireless AP	SiZong	WN1200A3	WS1505000003	UnionTrust
TF Card	Sandisk	/	/	UnionTrust
Earphone	/	/	/	UnionTrust

1.4 TEST LOCATION

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6, Baoneng Science and Technology Park, Qingxiang Road No.1, Longhua New District, Shenzhen, China 518109
Telephone: +86 (0) 755 2823 0888
Fax: +86 (0) 755 2823 0886

1.5 TEST FACILITY

The test facility is recognized, certified, or accredited by the following organizations:

CNAS-Lab Code: L9069
The measuring equipment utilized to perform the tests documented in this report has been calibrated once a year or in accordance with the manufacturer's recommendations, and is traceable under the ISO/IEC/EN 17025 to international or national standards. Equipment has been calibrated by accredited calibration laboratories.

A2LA-Lab Certificate No.: 4312.01
Shenzhen UnionTrust Quality and Technology Co., Ltd. has been accredited by A2LA for technical competence in the field of electrical testing, and proved to be in compliance with ISO/IEC 17025: 2005 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing.

ISED Wireless Device Testing Laboratories
CAB identifier: CN0032

FCC Accredited Lab.
Designation Number: CN1194
Test Firm Registration Number: 259480

1.6 DEVIATION FROM STANDARDS

None.

1.7 ABNORMALITIES FROM STANDARD CONDITIONS

None.

1.8 OTHER INFORMATION REQUESTED BY THE CUSTOMER

None.

1.9 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the Product as specified in CISPR 16-4-2. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

No.	Item	Measurement Uncertainty
1	Conducted emission 9KHz-150KHz	±3.8 dB
2	Conducted emission 150KHz-30MHz	±3.4 dB
3	Radiated emission 9KHz-30MHz	±4.9 dB
4	Radiated emission 30MHz-1GHz	±4.7 dB
5	Radiated emission 1GHz-18GHz	±5.1 dB
6	Radiated emission 18GHz-26GHz	±5.2 dB
7	Radiated emission 26GHz-40GHz	±5.2 dB

2. TEST SUMMARY

FCC 47 CFR Part 15 Subpart B Test Cases			
Test Item	**Test Requirement**	**Test Method**	**Result**
Conducted Emission	FCC 47 CFR Part 15.107	ANSI C63.4-2014	PASS
Radiated Emission	FCC 47 CFR Part 15.109	ANSI C63.4-2014	PASS

3. EQUIPMENT LIST

Radiated Emission Test Equipment List						
Used	**Equipment**	**Manufacturer**	**Model No.**	**Serial Number**	**Cal. date (mm dd, yyyy)**	**Cal. Due date (mm dd, yyyy)**
☒	3M Chamber & Accessory Equipment	ETS-LINDGREN	3M	N/A	Dec. 03, 2018	Dec. 03, 2021
☒	Receiver	R&S	ESIB26	100114	Nov. 24, 2019	Nov. 23, 2020
☐	Loop Antenna	ETS-LINDGREN	6502	00202525	Nov. 24, 2019	Nov. 23, 2020
☒	Broadband Antenna	ETS-LINDGREN	3142E	00201566	Nov. 16, 2019	Nov. 15, 2020
☒	6dB Attenuator	Talent	RA6A5-N-18	18103001	Nov. 16, 2019	Nov. 15, 2020
☒	Preamplifier	HP	8447F	2805A02960	Nov. 16, 2019	Nov. 15, 2020
☐	Broadband Antenna (Pre-amplifier)	ETS-LINDGREN	3142E-PA	00201891	Nov. 24, 2019	Nov. 23, 2020
☐	6dB Attenuator	Talent	RA6A5-N-18	18103002	Nov. 24, 2019	Nov. 23, 2020
☒	Horn Antenna	ETS-LINDGREN	3117	00164202	Nov. 24, 2019	Nov. 23, 2020
☒	Horn Antenna (Pre-amplifier)	ETS-LINDGREN	3117-PA	00201874	Nov. 16, 2019	Nov. 15, 2020
☐	Horn Antenna	ETS-LINDGREN	3116C	00200180	May 18, 2019	May 18, 2020
☒	Horn Antenna (Pre-amplifier)	ETS-LINDGREN	3116C-PA	00202652	Jun. 23, 2019	Jun. 23, 2020
☒	Multi device Controller	ETS-LINDGREN	7006-001	00160105	N/A	N/A
☒	Test Software	Audix	e3	Software Version: 9.160323		

Conducted Emission Test Equipment List						
Used	**Equipment**	**Manufacturer**	**Model No.**	**Serial Number**	**Cal. date (mm dd, yyyy)**	**Cal. Due date (mm dd, yyyy)**
☒	Receiver	R&S	ESR7	1316.3003K07 -101181-K3	Nov. 24, 2019	Nov. 23, 2020
☒	Pulse Limiter	R&S	ESH3-Z2	0357.8810.54	Nov. 24, 2019	Nov. 23, 2020
☒	LISN	R&S	ESH2-Z5	860014/024	Nov. 24, 2019	Nov. 23, 2020
☐	LISN	ETS-Lindgren	3816/2SH	00201088	Nov. 24, 2019	Nov. 23, 2020
☒	Test Software	Audix	e3	Software Version: 9.160323		

4. TEST CONFIGURATION

4.1 ENVIRONMENTAL CONDITIONS FOR TESTING

4.1.1 Normal or Extreme Test Conditions

Environment Parameter	Selected Values During Tests		
Test Condition	Ambient		
	Temperature (°C)	Voltage (V)	Relative Humidity (%)
NT/NV	+15 to +35	3.8	20 to 75
Remark: 1) NV: Normal Voltage; NT: Normal Temperature			

4.1.2 Record of Normal Environment

Test Item	Temperature (°C)	Relative Humidity (%)	Pressure (kPa)	Tested by
Conducted Emission	24.0	41.0	100. 21	Bert Xiong
Radiated Emission	25.2	52.0	100.02	Andy Lin

4.2 TEST MODES

Test Item	EMI Test Modes
Radiated Emission	Mode 1: Charging from 120 Vac + MP4 playing (With TF Card) + Earphone **Mode 2: Charging from 120 Vac + FM (With Earphone) + Camera (Front)+ With TF Card+ Earphone** Mode 3 Charging from 240 Vac + Worse from mode 1~2 + GPS on+ Earphone Mode 4: USB Cable (data transfer with notebook) + With TF Card+ Earphone
Conducted Emission	Mode 1: Charging from 120 Vac + MP4 playing (With TF Card) + Earphone Mode 2: Charging from 120 Vac + FM (With Earphone) + Camera (Front)+ With TF Card+ Earphone **Mode 3 Charging from 240 Vac + Worse from mode 1~2+ GPS on+ Earphone** Mode 4: USB Cable (data transfer with notebook) + With TF Card+ Earphone

4.3 TEST SETUP

4.3.1 For Radiated Emissions test setup

Figure 1. 30MHz to 1GHz



Figure 2. Above 1GHz



Test setup for radiated emissions of tabletop equipment (Above 1 GHz)

4.3.2 For Conducted Emissions test setup

Figure 3. Conducted Emissions setup



Test setup for conducted emissions of tabletop equipment (AC mains power ports)

4.4 SYSTEM TEST CONFIGURATION

All readings are extrapolated back to the equivalent three meter reading using inverse scaling with distance. Analyzer resolution is 100 kHz or greater for frequencies below 1000MHz. The resolution is 1 MHz or greater for frequencies above 1000MHz. The spurious emissions more than 20 dB below the permissible value are not reported.

Radiated emission measurement were performed from the lowest radio frequency signal generated in the device which is greater than 9 kHz to the tenth harmonic (according to KDB 896810 D02 SDoC FAQ v01r01) of the highest fundamental frequency or to 40 GHz, whichever is lower.

5. REFERENCE DOCUMENTS FOR TESTING

No.	Identity	Document Title
1	FCC 47 CFR Part15 Subpart B	Unintentional Radiators
2	ANSI C63.4-2014	American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz
3	KDB 174176 D01 Line Conducted FAQ v01r01	AC power-line conducted emission frequency asked questions
4	KDB 896810 D02 SDoC FAQ v01r02	Supplier's Declaration of Conformity frequency asked questions

6. EMC REQUIREMENTS SPECIFICATION

6.1 RADIATED EMISSION

Test Requirement: FCC 47 CFR Part 15.109

Test Method: ANSI C63.4-2014

Receiver Setup:

Frequency: (f) (MHz)	Detector type	Measurement receiver bandwidth	
		RBW	VBW
30 ≤ f ≤ 1 000	Quasi Peak	120 kHz	300 kHz
f ≥1000	Peak	1 MHz	3 MHz
	Average	1 MHz	3 MHz

Measured frequency range

Highest frequency generated or used in the device or on which the device operates or tunes (MHz)	Upper frequency of measurement range (MHz)
Below 1.705	30.
1.705-108	1000.
108-500	2000.
500-1000	5000.
Above 1000	5th harmonic of the highest frequency or 40 GHz, whichever is lower.

Limits:

Limits for Class B devices

Frequency (MHz)	limits at 3m (dBμV/m)		
	QP Detector	PK Detector	AV Detector
30-88	40.0	--	--
88-216	43.5	--	--
216-960	46.0	--	--
960 to 1000	54.0	--	--
Above 1000	--	74.0	54.0

Remark:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBμV/m) = 20 log Emission level (μV/m).
3. For frequencies above 1000 MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20 dB under any condition of modulation.

Test Setup: Refer to section 4.3.1 for details.

Test Procedures:

1. From 30 MHz to 1GHz test procedure as below:

1) The Product was placed on the non-conductive turntable 0.8 m above the ground at a chamber.
2) Set the spectrum analyzer/receiver in Peak detector, Max Hold mode, and 120 kHz RBW. Record the maximum field strength of all the pre-scan process in the full band when the antenna is varied between 1~4 m in both horizontal and vertical, and the turntable is rotated from 0 to 360 degrees.
3) For each frequency whose maximum record was higher or close to limit, measure its QP value: vary the antenna's height and rotate the turntable from 0 to 360 degrees to find the height and degree where Product radiated the maximum emission, then set the test frequency analyzer/receiver to QP Detector and specified bandwidth with Maximum Hold Mode, and record the maximum value.

2. Above 1GHz test procedure as below:

1) The Product was placed on the non-conductive turntable 0.8 m above the ground at a chamber.
2) Set the spectrum analyzer/receiver in Peak detector, Max Hold mode, and 1MHz RBW. Record the maximum field strength of all the pre-scan process in the full band when the antenna is varied in both horizontal and vertical, and the turntable is rotated from 0 to 360 degrees.
3) For each frequency whose maximum record was higher or close to limit, measure its AV value: rotate the turntable from 0 to 360 degrees to find the degree where Product radiated the maximum emission, then set the test frequency analyzer/receiver to AV value and specified bandwidth with Maximum Hold Mode, and record the maximum value.

Equipment Used: Refer to section 3 for details.

Test Result: Pass

The measurement data as follows:

Below 1GHz(Quasi Peak):
Mode2
Horizontal



No.	Frequency (MHz)	Reading (dBuV)	Correction factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	31.073	38.91	-6.04	32.87	40.00	-7.13	QP
2	42.035	42.39	-11.37	31.02	40.00	-8.98	QP
3	90.420	35.98	-13.30	22.68	43.50	-20.82	QP
4	290.317	35.74	-6.36	29.38	46.00	-16.62	QP
5	363.523	37.53	-4.46	33.07	46.00	-12.93	QP
6	804.252	33.42	3.48	36.90	46.00	-9.10	QP

Vertical



No.	Frequency (MHz)	Reading (dBuV)	Correction factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	36.268	43.34	-9.20	34.14	40.00	-5.86	QP
2	41.741	44.54	-12.15	32.39	40.00	-7.61	QP
3	56.864	44.25	-14.67	29.58	40.00	-10.42	QP
4	89.787	41.36	-13.36	28.00	43.50	-15.50	QP
5	363.523	34.18	-4.46	29.72	46.00	-16.28	QP
6	833.013	29.50	3.24	32.74	46.00	-13.26	QP

Above 1GHz(Peak & Average)
Mode2
Horizontal



No.	Frequency (MHz)	Reading (dBuV)	Correction factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	1407.405	45.48	-10.49	34.99	74.00	-39.01	Peak
2	4181.646	37.13	4.66	41.79	74.00	-32.21	Peak
3	7376.898	40.17	6.80	46.97	74.00	-27.03	Peak
4	9685.139	41.77	8.88	50.65	74.00	-23.35	Peak
5	12642.190	40.16	11.51	51.67	74.00	-22.33	Peak
6	14277.410	38.81	13.50	52.31	74.00	-21.69	Peak

Vertical



No.	Frequency (MHz)	Reading (dBuV)	Correction factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	1391.194	54.35	-10.35	44.00	74.00	-30.00	Peak
2	3702.714	37.21	3.33	40.54	74.00	-33.46	Peak
3	9034.809	41.28	8.16	49.44	74.00	-24.56	Peak
4	12863.790	39.59	12.07	51.66	74.00	-22.34	Peak
5	14868.200	40.01	12.66	52.67	74.00	-21.33	Peak
6	16694.370	39.76	13.01	52.77	74.00	-21.23	Peak

Remark:

1. Correct Factor = Antenna Factor + Cable Loss - Amplifier Gain, the value was added to Original Receiver Reading by the software automatically.
2. Result = Reading + Correct Factor.
3. Margin = Result – Limit
4. All possible modes of operation were investigated, and testing at two nominal voltages of 240V/50Hz and 120V/60Hz, only the worst case emissions reported.
5. For Radiated Emission above 18GHz, there was not any unwanted emission detected.
6. As shown in this section, for frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. So, only the peak measurements were shown in the report.

6.2 CONDUCTED EMISSION

Test Requirement: FCC 47 CFR Part 15.107

Test Method: ANSI C63.4-2014

Limits:

Limits for Class B devices

Frequency range (MHz)	Limits (dB(μV)	
	Quasi-peak	Average
0,15 to 0,50	66 to 56	56 to 46
0,50 to 5	56	46
5 to 30	60	50

Remark:

1. The lower limit shall apply at the transition frequencies.
2. The limit decreases linearly with the logarithm of the frequency in the range 0.15 to 0.50 MHz.

Test Setup: Refer to section 4.3.2 for details.

Test Procedures:

1) The Product was placed on a nonconductive table 0.8 m above the horizontal ground reference plane, and 0.4 m from the vertical ground reference plane, and connected to the main through Line Impedance Stability Network (L.I.S.N).
2) The RBW of the receiver was set at 9 kHz in 150 kHz ~ 30MHz with Peak and AVG detector in Max Hold mode. Run the receiver's pre-scan to record the maximum disturbance generated from Product in all power lines in the full band.
3) For each frequency whose maximum record was higher or close to limit, measure its QP and AVG values and record.

Equipment Used: Refer to section 3 for details.

Test Result: Pass

The measurement data as follows:
Quasi Peak and Average:
Mode 3

Live Line



No.	Frequency (MHz)	Reading (dBuV)	Correction factor (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.446	29.48	9.26	38.74	46.95	-8.21	Average
2	0.446	34.59	9.26	43.85	56.95	-13.10	QP
3	0.490	29.71	9.32	39.03	46.17	-7.14	Average
4	0.490	37.80	9.32	47.12	56.17	-9.05	QP
5	0.982	30.37	9.42	39.79	46.00	-6.21	Average
6	0.982	33.65	9.42	43.07	56.00	-12.93	QP

Neutral Line



No.	Frequency (MHz)	Reading (dBuV)	Correction factor (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.442	32.61	9.26	41.87	47.02	-5.15	Average
2	0.442	39.72	9.26	48.98	57.02	-8.04	QP
3	0.486	32.22	9.34	41.56	46.24	-4.68	Average
4	0.486	40.80	9.34	50.14	56.24	-6.10	QP
5	0.930	33.51	9.42	42.93	46.00	-3.07	Average
6	0.930	38.60	9.42	48.02	56.00	-7.98	QP

Remark:

1. Correct Factor = LISN Factor + Cable Loss + Pulse Limiter Factor, the value was added to Original Receiver Reading by the software automatically.
2. Result = Reading + Correct Factor.
3. Margin = Result - Limit
4. An initial pre-scan was performed on the Phase and neutral lines with peak detector. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission were detected.
5. All possible modes of operation were investigated, and testing at two nominal voltages of 240V/50Hz and 120V/60Hz, only the worst case emissions reported.

APPENDIX 1 PHOTOS OF TEST SETUP

See test photos attached in Appendix 1 for the actual connections between Product and support equipment.

APPENDIX 2 PHOTOS OF EUT CONSTRUCTIONAL DETAILS

Refer to Appendix 2 for EUT external and internal photos.

*** End of Report ***

The test report is effective only with both signature and specialized stamp. The result(s) shown in this report refer only to the sample(s) tested. Without written approval of UnionTrust, this report can't be reproduced except in full.