



FCC §15.247 (i), §2.1091 – RF Exposure

FCC ID: 2AUA9-RQZY016

Applied procedures / limit

According to FCC §15.247(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

Limits for Occupational / Controlled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842 / f	4.89 / f	(900 / f)*	6
30-300	61.4	0.163	1.0	6
300-1500			F/300	6
1500-100,000			5	6

Note: f is frequency in MHz

* = Power density limit is applicable at frequencies greater than 100 MHz

Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-100,000			1.0	30

Note: f = frequency in MHz

* = Plane-wave equivalent power density



MPE PREDICTION

Predication of MPE limit at a given distance, Equation from OET Bulletin 65, Edition 97-01

$$S = PG/4\pi R^2$$

Where: S = power density

P = power input to antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna, R=0.2m

TEST RESULTS

Maximum Emissions Level								
Mode	Max. Power (dBm)	Tune-up Power (dBm)	Tune-up Power (mW)	Antenna Gain (dBi)	Antenna Gain (mW)	Power Density (mW/cm ²)	Limit (mW/cm ²)	Result
BR,EDR	6.47	6.5	4.47	1.99	1.58	0.001406	1.0	PASS
BLE	2.90	3.0	2.00	1.99	1.58	0.000628		
WIFI2.4G	13.88	14.0	25.12	1.99	1.58	0.007904		
WIFI5.1G	13.48	13.5	22.39	0.96	1.25	0.005557		
WIFI 5.8G	11.71	12.0	15.85	1.58	1.44	0.004538		

Bluetooth and WiFi share the same antenna cannot send signals at the same time.

For the max result: $0.007904 < 1.0$, compliance with FCC's RF Exposure