

RF EXPOSURE EVALUATION

1. PRODUCT INFORMATION

Product Description	Smart watch
Model Name	M32
Series Model	M30, M30PRO, M30PLUS, M31, M31PRO, M31PLUS, M32PRO, M32PLUS, M33, M33PRO, M33PLUS, M34, M34PRO, N34PLUS, M35, M35PRO, M35PLUS
FCC ID	2AUAY-M32

2. EVALUATION METHOD

According to 447498 D01 General RF Exposure Guidance v06

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR.

Where $f(\text{GHz})$ is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation

3. CALCULATION

BR&EDR-BK3266 Chip:

$P_t = -0.796\text{dBm} = 0.83\text{mW}$

The value of the Maximum output power P_t is referred to the test report of the CFR47 §15.247.

The result for RF exposure evaluation $\text{SAR} = (0.83\text{mW} / 5\text{mm}) \cdot [\sqrt{2.480\text{GHz}}] = 0.261 < 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR.

BLE-RTL8762D Chip:

$P_t = 6.006\text{dBm} = 3.99\text{mW}$

The value of the Maximum output power P_t is referred to the test report of the CFR47 §15.247.

The result for RF exposure evaluation $\text{SAR} = (3.99\text{mW} / 5\text{mm}) \cdot [\sqrt{2.480\text{GHz}}] = 1.253 < 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR.

BR&EDR-BK3266 Chip+ BLE-RTL8762D Chip:

$(0.261/3) + (1.253/3) = 0.505$

Note: The BR&EDR-BK3266 Chip and BLE-RTL8762D Chip can transmit simultaneously.

4. CONCLUSION

The SAR evaluation is not required.