EMC TEST REPORT

Test Report No.	:	KES-E1-19T0529-R1
Date of Issue	:	Sep. 11, 2019
Product name	:	Trimm One
Model/Type No.	:	Trimm One
Variant Mode	:	-
Applicant	:	Ratio LLC
Applicant Address	:	Rm. 505, 12, Muwon-ro 6beon-gil, Deogyang-gu, Goyang-si, Gyeonggi-do, Republic of Korea
Manufacturer	:	Ratio LLC
Manufacturer Address	:	Rm. 505, 12, Muwon-ro 6beon-gil, Deogyang-gu, Goyang-si, Gyeonggi-do, Republic of Korea
FCC ID	:	2AUCE-TRIMMONE
Date of Receipt	:	May. 22, 2019
Test date	:	Aug. 11, 2019 ~ Aug. 13, 2019
Test Results	:	☒ **In Compliance** ☐ **Not in Compliance**

Tested by

Dae Hyun, Kim
EMC Test Engineer

Reviewed by

Dong-Hun, Jang
EMC Technical Manager

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact shchoi@kes.co.kr

REPORT REVISION HISTORY

Date	Test Report No.	Revision History
Sep. 04, 2019	KES-E1-19T0529	Issued
Sep. 11, 2019	KES-E1-19T0529-R1	added measurement uncertainty and phrase (Page 12).

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd. This document may be altered or revised by KES Co., Ltd. personnel only, and shall be noted in the revision section of the document. Any alteration of this document not carried out by KES Co., Ltd. will constitute fraud and shall nullify the document.

TABLE OF CONTENTS

1.0 General Product Description 4
1.1 Test Voltage & Frequency 5
1.2 Variant Model Differences 5
1.3 Device Modifications 5
1.4 Equipment Under Test 5
1.5 Support Equipments 5
1.6 External I/O Cabling 6
1.7 EUT Operating Mode(s) 6
1.8 Configuration 7
1.9 Remarks when standards applied 8
1.10 Calibration Details of Equipment Used for Measurement 8
1.11 Test Facility 8
1.12 Laboratory Accreditations and Listings 8
2.0 Test Regulations 9
2.1 Conducted Emissions at Mains Power Ports 11
2.2 Radiated Electric Field Emissions(Below 1 ㎓) 12
2.3 Radiated Electric Field Emissions(Above 1 ㎓) 13
APPENDIX A – TEST DATA 14
Conducted Emissions at Mains Power Ports 14
Radiated Electric Field Emissions(Below 1 ㎓) 16
Radiated Electric Field Emissions(Above 1 ㎓) 18
APPENDIX B - Test Setup Photos and Configuration 21
Conducted Voltage Emissions 21
Radiated Electric Field Emissions(Below 1 ㎓) 22
Radiated Electric Field Emissions(Above 1 ㎓) 24

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact shchoi@kes.co.kr

1.0 General Product Description

Main Specifications of EUT are:

Item	spec
Operating Frequency	Bluetooth, ANT+, GPS
Power	DC 5 V(USB)
Size	(96 x 55 x 9) ㎜
Weight	164 g

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact shchoi@kes.co.kr

1.1 Test Voltage & Frequency

Unless indicated otherwise on the individual data sheet or test results, the test voltage and frequency was as indicated below.

Voltage ☐ 230 Vac ☒ 120 Vac ☐ 12 Vdc ☐ DC 3.7 V (Battery)

Frequency ☐ 50 Hz ☒ 60 Hz ☐ Hz

1.2 Variant Model Differences

Not applicable

1.3 Device Modifications

Not applicable

1.4 Equipment Under Test

Description	Model Number	Serial Number	Manufacturer	Remarks
Trimm One	Trimm One	-	Ratio LLC	EUT

1.5 Support Equipments

Description	Model Number	Serial Number	Manufacturer	Remarks
Adapter	MCS-04KD	-	Dongdo Electroncs(Yantal) Co., Ltd	-
Smart Phone	A1429	-	APPLE INC.	-
Test Jig	-	-	-	-
GPS Reradiating Antenna	VRA-400	-	VW tech. corp.	-
GPS Reradiating Antenna Adpater	Sd10009-1001	-	-	-

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact shchoi@kes.co.kr

1.6 External I/O Cabling

■ Operating Mode

Start		END		Cable Spec.	
Description	**I/O Port**	**Description**	**I/O Port**	**Length**	**Shield**
Trimm One (EUT)	Wireless	Smart Phone	Wireless	-	-
	Wireless	Test Jig	Wireless	-	-
	Wireless	GPS Reradiating Antenna	Wireless	-	-

■ Charge Mode

Start		END		Cable Spec.	
Description	**I/O Port**	**Description**	**I/O Port**	**Length**	**Shield**
Trimm One (EUT)	3 Pin	Adapter	USB	0.8	U

1.7 EUT Operating Mode(s)

Test mode	operating
Operating	Bluetooth connected the smartphone and the EUT. Confirmed normal operation with a smartphone 'app'. Confirmed the gps receive and test of EUT through display of the lcd. (It was also EMS tested in standby mode.)
Charge	Confirmed the charge of EUT through display of the lcd.

EUT Test operating S/W		
Name	**Version**	**Manufacture Company**
TestFlight	2.4.0	Apple Distribution International

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact shchoi@kes.co.kr

1.8 Configuration

■ AC Main
□ DC Main

■ Operating Mode



■ Charge Mode



This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact shchoi@kes.co.kr

1.9 Remarks when standards applied

N/A

1.10 Calibration Details of Equipment Used for Measurement

Test equipment and test accessories are calibrated on regular basis. The maximum time between calibrations is one year or what is recommended by the manufacturer, whichever is less.

1.11 Test Facility

The measurement facility is located at 473-21 Gayeo-ro, Yeoju-si, Gyeonggi-do, 12658, Korea. The sites are constructed in conformance with the requirements of ANSI C63.4:2014 and CISPR 16-1-4:2012

1.12 Laboratory Accreditations and Listings

Country	Agency	Scope of Accreditation	Logo
KOREA	**RRA**	EMI (3 m & 10 m Semi-Aechoic Chamber ,10 m Open Area and conducted test site) EMS (ESD, RS, EFT/Burst, Surge, CS, Magnetic, Dips and interruptions)	KR0100
International	**KOLAS**	EMI (3 m & 10 m Semi-Aechoic Chamber , and conducted test site) EMS (ESD, RS, EFT/Burst, Surge, CS, Magnetic, Dips and interruptions)	KT489
USA	**FCC**	3 m & 10 m Semi-Aechoic Chamber, 10 m Open Area and Conducted test site to perform FCC Part 15/18 measurements.	KR0100
Canada	**ISED**	3 m & 10 m Semi-Aechoic Chamber and Conducted test site	23298-1
JAPAN	**VCCI**	Mains Ports Conducted Interference Measurement, Telecommunication Ports Conducted Disturbance Measurement and Radiation 10 meter site, Facility for measuring radiated disturbance above 1 GHz	R-20056, C-20036 T-20040, G-20057
Europe	**TÜV SÜD**	EMI (3 m & 10 m Semi-Aechoic Chamber , 10 m Open Area and conducted test site) EMS (ESD, RS, EFT/Burst, Surge, CS, Magnetic, Dips and interruptions)	CARAT 001633 0003

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact shchoi@kes.co.kr

2.0 Test Regulations

The emissions tests were performed according to following regulations:

☐ **EMC – Directive 2014/30/EU**

☐ EN 61000-6-3:2011

☐ EN 61000-6-1:2007

☐ EN 61000-6-4:2007 +A1:2011

☐ EN 61000-6-2:2005

☐ EN 55011:2007 +A1:2010 ☐ Group 1 ☐ Class A ☐ Group 2 ☐ Class B

☐ EN 55014-1:2006 +A2:2011

☐ EN 55014-2:1997 +A2:2008

☐ EN 55015:2013

☐ EN 55032:2015 ☐ Class A ☐ Class B

☐ EN 55024:2010

☐ EN 50130-4:2011 +A1:2014

☐ EN 61000-3-2:2014

☐ EN 61000-3-3:2013

☐ EN 61326-1:2013

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact shchoi@kes.co.kr

☐ **VCCI V-3 / 2015.04** ☐ Class A ☐ Class B

☐ **AS/NZS:2013** ☐ Class A ☐ Class B

☒ **47 CFR Part 15, Subpart B**

- ☐ CISPR 22:2009 +A1:2010 ☐ Class A ☐ Class B
- ☒ ANSI C63.4-2014 ☐ Class A ☒ Class B

☐ **IC Regulation ICES-003 : 2016**

- ☐ CAN/CSA CISPR 22-10 ☐ Class A ☐ Class B
- ☐ ANSI C63.4-2014 ☐ Class A ☐ Class B

☐ **RE– Directive 2014/53/EU**

☐ EN 301 489-1 V1.9.2

- ☐ Equipment for fixed use
- ☐ Equipment for vehicular use
- ☐ Equipment for portable use

☐ EN 301 489-3 V1.6.1

☐ EN 301 489-17 V2.2.1

☐ EN 60945:2002

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact shchoi@kes.co.kr

2.1 Conducted Emissions at Mains Power Ports

Test Date
Aug. 11, 2019

Test Location
Electro wave Shieldroom #6

Test Equipment

Used	Description	Model Number	Manufacturer	Serial Number	Cal. Due
☒	EMI Test S/W	EMC32	R & S	9.12.00	-
☒	EMI TEST RECEIVER	ESR3	R & S	101781	04, 22, 2020
☒	LISN	ENV216	R & S	101787	01, 04, 2020
☐	LISN	ESH2-Z5	R & S	100450	04, 22, 2020
☒	PULSE LIMITER	ESH3-Z2	R & S	101915	11, 26, 2019

Test Conditions
Temperature: 25.3 ℃
Relative Humidity: 55.0 % R.H.

Frequency Range of Measurement
150 ㎑ to 30 ㎒

Instrument Settings
IF Band Width: 9 ㎑

Test Results
The requirements are:

☒ PASS
☐ NOT PASS
☐ NOT APPLICABLE

Remarks
See Appendix A for test data.

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact shchoi@kes.co.kr

2.2 Radiated Electric Field Emissions(Below 1 ㎓)

Test Date
Aug. 12, 2019

Test Location
☐ OPEN AREA TEST SITE #2 ☒ SEMI ANECHOIC CHAMBER #4(10 m)

Test Equipment

Used	Description	Model Number	Manufacturer	Serial Number	Cal. Due
☒	EMI Test S/W	EP5/RE	TOYO Corporation	6.0.0	-
☒	EMI TEST RECEIVER	ESU26	R & S	100551	04, 09, 2020
☒	AMPLIFIER	SCU 01	R & S	100603	11, 26, 2019
☒	TRILOG-BROADBAND ANTENNA	VULB9163	Schwarzbeck	715	11, 29, 2020
☒	ATTENUATOR	8491A	HP	32173	03, 11, 2020

Test Conditions
Temperature: 23.9 ℃
Relative Humidity: 54.1 % R.H.

Frequency Range of Measurement
30 ㎒ to 1 ㎓

Instrument Settings
IF Band Width: 120 ㎑

Test Results
The requirements are:

☒ PASS
☐ NOT PASS
☐ NOT APPLICABLE

Remarks
- See Appendix A for test data.
- The fundamental of the EUT was investigated in thre orthogonal orientations X, Y and Z, it was determined that X orientation was worst-case orientation; therefore, al final radiated testing was performed with the EUT in X orientation.

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact shchoi@kes.co.kr

2.3 Radiated Electric Field Emissions(Above 1 ㎓)

Test Date
Aug. 13, 2019

Test Location
SEMI ANECHOIC CHAMBER #4(10 m)

Test Equipment

Used	Description	Model Number	Manufacturer	Serial Number	Cal. Due
☒	EMI Test S/W	EP5/RE	TOYO Corporation	6.0.0	-
☒	EMI TEST RECEIVER	ESU26	R & S	100551	04, 09, 2020
☒	PREAMPLIFIER	8449B	AGILENT	3008A01742	01, 08, 2020
☒	ATTENUATOR	8491A	HP	35496	03, 11, 2020
☒	HORN ANTENNA	BBHA 9120D	SCHWARZBECK	9120D-1802	03, 12, 2020

Test Conditions
Temperature: 23.9 ℃
Relative Humidity: 54.1 % R.H.

Frequency Range of Measurement
1 ㎓ to 12.5 ㎓

Instrument Settings
IF Band Width: 1 ㎒

Test Results
The requirements are:

☒ PASS
☐ NOT PASS
☐ NOT APPLICABLE

Remarks
See Appendix A for test data.

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact shchoi@kes.co.kr

APPENDIX A – TEST DATA

Conducted Emissions at Mains Power Ports

■ Charge Mode

HOT LINE

Common Information

Test Description:	Conducted Emission
Model No.:	Trimm One
Phase:	
Mode:	Charge / FCC
Operator Name:	KES



Final_Result

Frequency (MHz)	QuasiPeak (dB¥µ V)	CAverage (dB¥µ V)	Limit (dB¥µ V)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)
0.774000	---	4.17	46.00	41.83	1000.0	9.000	L1	20.2
0.774000	14.30	---	56.00	41.70	1000.0	9.000	L1	20.2
0.842000	---	4.49	46.00	41.51	1000.0	9.000	L1	20.2
0.842000	15.90	---	56.00	40.10	1000.0	9.000	L1	20.2
4.254000	---	6.61	46.00	39.39	1000.0	9.000	L1	19.7
4.254000	18.91	---	56.00	37.09	1000.0	9.000	L1	19.7
4.346000	---	6.46	46.00	39.54	1000.0	9.000	L1	19.7
4.346000	18.46	---	56.00	37.54	1000.0	9.000	L1	19.7
15.106000	---	9.77	50.00	40.23	1000.0	9.000	L1	20.3
15.106000	26.64	---	60.00	33.36	1000.0	9.000	L1	20.3
16.502000	---	9.61	50.00	40.39	1000.0	9.000	L1	20.3
16.502000	28.39	---	60.00	31.61	1000.0	9.000	L1	20.3

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact shchoi@kes.co.kr

NEUTRAL LINE

Common Information

Test Description:	Conducted Emission
Model No.:	Trimm One
Phase:	
Mode:	Charge / FCC
Operator Name:	KES



Final_Result

Frequency (MHz)	QuasiPeak (dB¥µ V)	CAverage (dB¥µ V)	Limit (dB¥µ V)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)
0.486000	---	5.10	46.24	41.14	1000.0	9.000	N	19.8
0.486000	16.65	---	56.24	39.59	1000.0	9.000	N	19.8
0.490000	---	5.38	46.17	40.79	1000.0	9.000	N	19.8
0.490000	16.76	---	56.17	39.41	1000.0	9.000	N	19.8
3.622000	---	5.35	46.00	40.65	1000.0	9.000	N	19.9
3.622000	10.06	---	56.00	45.94	1000.0	9.000	N	19.9
4.234000	---	5.54	46.00	40.46	1000.0	9.000	N	19.7
4.234000	10.54	---	56.00	45.46	1000.0	9.000	N	19.7
15.894000	---	6.68	50.00	43.32	1000.0	9.000	N	20.3
15.894000	19.50	---	60.00	40.50	1000.0	9.000	N	20.3
29.702000	---	8.34	50.00	41.66	1000.0	9.000	N	20.8
29.702000	10.47	---	60.00	49.53	1000.0	9.000	N	20.8

♦ Calculation
QuasiPeak[dBuV] / CAverage [dBuV] = Reading Value[dBuV] + Corr. [dB]
QuasiPeak / CAverage : The Final Value
Reading Value : Not shown in the table.
Corr. : Correction values (LISN FACTOR + (Cable Loss + Pulse Limiter FACTOR))

Uncertainty of measurement

HOT Line : Uncertainty of measurement 2.38 dB
(Confidence level: Approx. 95 %, *k*=2)

Neutral Line : Uncertainty of measurement 2.38 dB
(Confidence level: Approx. 95 %, *k*=2)

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact shchoi@kes.co.kr

Radiated Electric Field Emissions(Below 1 ㎓)

■ Operating Mode



Final Result

No.	Frequency [MHz]	(P)	Reading QP [dB(uV)]	c.f [dB(1/m)]	Result QP [dB(uV/m)]	Limit QP [dB(uV/m)]	Margin QP [dB]	Height [cm]	Angle [deg]	Remark
1	45.763	H	38.3	-22.4	15.9	40.0	24.1	354.0	269.0	
2	60.191	V	40.6	-23.1	17.5	40.0	22.5	155.0	151.0	
3	60.434	H	39.0	-23.2	15.8	40.0	24.2	240.0	189.0	
4	102.750	H	38.9	-23.3	15.6	43.5	27.9	296.0	202.0	
5	104.690	V	41.9	-23.3	18.6	43.5	24.9	137.0	142.0	
6	111.359	V	40.6	-23.6	17.0	43.5	26.5	164.0	241.0	
7	112.329	H	39.7	-23.7	16.0	43.5	27.5	349.0	98.0	
8	113.056	V	42.3	-23.8	18.5	43.5	25.0	143.0	241.0	
9	148.098	V	44.6	-26.9	17.7	43.5	25.8	113.0	82.0	
10	249.948	V	40.3	-21.2	19.1	46.0	26.9	100.0	356.0	
11	312.513	H	38.0	-19.2	18.8	46.0	27.2	206.0	350.0	
12	483.596	H	36.9	-14.9	22.0	46.0	24.0	321.0	254.0	

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact shchoi@kes.co.kr

■ Charge Mode



Final Result

No.	Frequency [MHz]	(P)	Reading QP [dB(uV)]	c.f [dB(1/m)]	Result QP [dB(uV/m)]	Limit QP [dB(uV/m)]	Margin QP [dB]	Height [cm]	Angle [deg]	Remark
1	33.055	V	49.7	-25.6	24.1	40.0	15.9	114.0	228.0	
2	36.074	V	48.8	-25.3	23.5	40.0	16.5	128.0	26.0	
3	43.739	V	44.7	-22.6	22.1	40.0	17.9	150.0	286.0	
4	51.951	H	39.0	-22.0	17.0	40.0	23.0	347.0	319.0	
5	55.836	V	40.3	-22.5	17.8	40.0	22.2	138.0	85.0	
6	104.071	H	38.7	-23.3	15.4	43.5	28.1	220.0	97.0	
7	104.676	V	44.2	-23.3	20.9	43.5	22.6	174.0	66.0	
8	124.953	V	46.3	-25.6	20.7	43.5	22.8	110.0	59.0	
9	124.940	H	43.6	-25.6	18.0	43.5	25.5	291.0	137.0	
10	250.058	H	40.3	-21.2	19.1	46.0	26.9	380.0	91.0	
11	327.973	H	40.5	-18.4	22.1	46.0	23.9	301.0	345.0	
12	442.622	H	42.4	-16.3	26.1	46.0	19.9	290.0	193.0	

♦ Calculation – SAC #4(10 m)
Result(QP) [dB(㎶/m)] = (Reading(QP)[dB(㎶)] + c.f[dB(1/m)]
Margin(QP)[dB] = Limit[dB(㎶/m)] - Result(QP) [dB(㎶/m)]
Reading(QP) : Reading value, Result(QP) : Reading value + Factor value
Limit(QP) : Limit value, c.f : (ANT Factor + Cable Loss - Preamp Factor), Margin: Margin value

Uncertainty of measurement

Horizontal : Uncertainty of measurement 4.16 dB
(Confidence level: Approx. 95 %, *k*=2)

Vertical : Uncertainty of measurement 4.24 dB
(Confidence level: Approx. 95 %, *k*=2)

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact shchoi@kes.co.kr

Radiated Electric Field Emissions(Above 1 GHz)

■ Operating Mode – (1 ~ 5) GHz



Final Result

No.	Frequency [MHz]	(P)	Reading PK [dB(uV)]	Reading CAV [dB(uV)]	c.f [dB(1/m)]	Result PK [dB(uV/m)]	Result CAV [dB(uV/m)]	Margin PK [dB]	Margin CAV [dB]	Height [cm]	Angle [deg]	Remark
1	1214.720	V	42.6	29.0	-4.8	37.8	24.2	36.2	29.8	124.0	48.0	
2	1610.750	H	41.4	27.7	-2.3	39.1	25.4	34.9	28.6	314.0	44.0	
3	1908.190	V	40.0	26.8	-0.9	39.1	25.9	34.9	28.1	351.0	209.0	
4	3172.845	H	38.0	24.7	4.3	42.3	29.0	31.7	25.0	221.0	314.0	
5	4040.425	V	37.0	23.7	7.9	44.9	31.6	29.1	22.4	169.0	2.0	
6	4824.530	H	37.3	22.7	10.8	48.1	33.5	25.9	20.5	203.0	46.0	
7	2233.455	V	39.3	25.7	0.6	39.9	26.3	34.1	27.7	180.0	305.0	
8	2405.000	H	--------	--------	1.4	--------	--------	--------	--------	100.0	327.0	
9	2464.000	H	--------	--------	1.7	--------	--------	--------	--------	100.0	111.0	

* Operating Mode Exclusion Bands : 2.4 GHz

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact shchoi@kes.co.kr

– (5 ~ 12.5) GHz


KES
SAC #4(10 m)
<<D (1 – 18) GHz RE TEST>>
KES D-SAC #4(10 m)
Model : Trimm One
Op. Mode : Operating
Operator : KES
Power :
Remark1 :
Standard : FCC Class B GHz 3m
ANT : BBHA 9120D, KOLAS
[dB(uV/m)]
Level
Frequency
[MHz]
5000.00
10000.00
12500.00
<FCC B GHz 3m>
Limit(PK)
Limit(AV)
<Trimm One_Operating_5 ~ 12.5 GHz_RE(FCC)>
Spectrum(H,PK)
Spectrum(V,PK)
Final Item(H,PK)
Final Item(H,CAV)

■ Charge Mode



Final Result

No.	Frequency [MHz]	(P)	Reading PK [dB(uV)]	Reading CAV [dB(uV)]	c.f [dB(1/m)]	Result PK [dB(uV/m)]	Result CAV [dB(uV/m)]	Margin PK [dB]	Margin CAV [dB]	Height [cm]	Angle [deg]	Remark
1	1157.325	H	43.0	29.6	-5.2	37.8	24.4	36.2	29.6	221.0	100.0	
2	1671.975	V	40.9	27.4	-2.0	38.9	25.4	35.1	28.6	136.0	214.0	
3	2244.450	H	39.7	26.0	0.6	40.3	26.6	33.7	27.4	195.0	245.0	
4	4276.565	V	36.5	23.3	8.6	45.1	31.9	28.9	22.1	116.0	181.0	
5	4798.180	H	35.8	23.0	10.7	46.5	33.7	27.5	20.3	218.0	224.0	

♦ Calculation

Result(PK/CAV) [dB(㎶/m)] = (Reading(PK/CAV)[dB(㎶)] + c.f[dB(1/m)]
Margin(PK/CAV)[dB] = Limit[dB(㎶/m)] - Result(PK/CAV) [dB(㎶/m)]
Reading(PK/CAV) : Reading value, Result(PK/CAV) : Reading value + Factor value
Limit(QP) : Limit value, c.f : (ANT Factor + Cable Loss + ATT Factor - Preamp Factor), Margin: Marjin value

* No spurious emission were detected above 5 ㎓.

Uncertainty of measurement

Uncertainty of measurement 5.76 ㏈
(Confidence level: Approx. 95 %, *k*=2)