

Appendix B

RF Test Data for BT LE (Conducted Measurement)

Product Name: H2O TRI ULTRA PRO

Test Model: H2O TRI ULTRA PRO

Environmental Conditions


Temperature:	24.5°C
Relative Humidity:	53.2%
ATM Pressure:	100.0 kPa
Test Engineer:	Zhang hai
Supervised by:	Fengliu Tang


B.1 DTS Bandwidth

Test Result

TestMode	Antenna	Freq(MHz)	DTS BW [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
BLE_1M	Ant1	2402	0.664	2401.660	2402.324	0.5	PASS
		2440	0.664	2439.660	2440.324	0.5	PASS
		2480	0.664	2479.660	2480.324	0.5	PASS

Test Graphs







B.2 Maximum Peak conducted output power

Test Result Peak

TestMode	Antenna	Freq(MHz)	Conducted Peak Power[dBm]	Conducted Limit[dBm]	EIRP[dBm]	EIRP Limit[dBm]	Verdict
BLE_1M	Ant1	2402	-1.97	≤30	0.73	≤36	PASS
		2440	1.12	≤30	3.82	≤36	PASS
		2480	-1.11	≤30	1.59	≤36	PASS

Test Graphs Peak






B.3 Maximum power spectral density

Test Result

TestMode	Antenna	Freq(MHz)	Result[dBm/3kHz]	Limit[dBm/3kHz]	Verdict
BLE_1M	Ant1	2402	-18.86	≤8.00	PASS
		2440	-15.76	≤8.00	PASS
		2480	-18.00	≤8.00	PASS

Test Graphs



BLE_1M_Ant1_2440

Keysight Spectrum Analyzer - Swept SA

Center Freq 2.440000000 GHz

Ref Offset 11.27 dB
Ref 20.00 dBm

10 dB/div
Log

Mkr1 2.440 006 06 GHz
-15.762 dBm

1

Center 2.44000000 GHz
#Res BW 3.0 kHz

#VBW 10 kHz

Sweep 110.0 ms (30000 pts)

Frequency

Auto Tune

Center Freq
2.440000000 GHz


Start Freq
2.439485400 GHz

Stop Freq
2.440514600 GHz

CF Step
102.920 kHz
Auto
Man

Freq Offset
0 Hz

BLE_1M_Ant1_2480




B.4 Band edge measurements

Test Result

TestMode	Antenna	Channel	Freq(MHz)	RefLevel[dBm]	Result[dBm]	Limit[dBm]	Verdict
BLE_1M	Ant1	Low	2402	-2.81	-46.33	≤-22.81	PASS
		High	2480	-1.97	-46.07	≤-21.97	PASS

Test Graphs





B.5 Conducted Spurious Emission


Test Result


TestMode	Antenna	Freq(MHz)	FreqRange [MHz]	RefLevel [dBm]	Result[dBm]	Limit[dBm]	Verdict
BLE_1M	Ant1	2402	Reference	-2.79	-2.79	---	PASS
			30~1000	-2.79	-54.48	≤-22.79	PASS
			1000~26500	-2.79	-41.42	≤-22.79	PASS
		2440	Reference	0.33	0.33	---	PASS
			30~1000	0.33	-51.05	≤-19.67	PASS
			1000~26500	0.33	-45.13	≤-19.67	PASS
		2480	Reference	-1.86	-1.86	---	PASS
			30~1000	-1.86	-50.66	≤-21.86	PASS
			1000~26500	-1.86	-31.51	≤-21.86	PASS

Test Graphs











B.6 Duty Cycle

Test Result

TestMode	Antenna	Freq(MHz)	ON Time [ms]	Period [ms]	X	DC [%]	xFactor	Limit	Verdict
BLE_1M	Ant1	2402	1.64	1.88	0.8723	87.23	0.59	---	---
		2440	1.63	1.87	0.8717	87.17	0.60	---	---
		2480	1.64	1.88	0.8723	87.23	0.59	---	---

Test Graphs





B.7 Emissions in Restricted Bands

Test Result

TestMode	Antenna	ChName	Freq(MHz)	Detector	Freq [MHz]	Result [dBm]	Limit [dBm]	Gain [dBi]	DC Factor [dB]	Result [dBuV/m]	Limit [dBuV/m]	Verdict
BLE_1M	Ant1	Low	2402	AV	2310.000	-58.61	≤-43.79	2.70	0.59	39.88	≤54	PASS
				AV	2331.815	-56.98	≤-43.79	2.70	0.59	41.51	≤54	PASS
				AV	2390.000	-58.26	≤-43.79	2.70	0.59	40.23	≤54	PASS
				Peak	2310.000	-50.41	≤-23.20	2.70	0.00	47.49	≤74	PASS
				Peak	2388.725	-47.46	≤-23.20	2.70	0.00	50.44	≤74	PASS
				Peak	2390.000	-49.97	≤-23.20	2.70	0.00	47.93	≤74	PASS
		High	2480	AV	2483.500	-57.23	≤-43.79	2.70	0.59	41.26	≤54	PASS
				AV	2484.880	-56.71	≤-43.79	2.70	0.59	41.78	≤54	PASS
				AV	2500.000	-58.15	≤-43.79	2.70	0.59	40.34	≤54	PASS
				Peak	2483.500	-49.93	≤-23.20	2.70	0.00	47.97	≤74	PASS
				Peak	2498.400	-46.56	≤-23.20	2.70	0.00	51.34	≤74	PASS
				Peak	2500.000	-49.7	≤-23.20	2.70	0.00	48.20	≤74	PASS

Note:

1. The Antenna Gain is compensated in the graph.
2. The limit in dBm for average detector is conversion from 54dBuV/m, according to 15.209(a). The limit in dBm for peak detector is 20dB above the limit of average detector in dBm.

Test Graphs

