



FCC SAR TEST REPORT

Report No.: STS1906274H01

Issued for

FX Technology Limited

38a High Street, Northwood, Middlesex, United Kingdom,
HA6 1BN

Product Name:	Smartphone
Brand Name:	Fxtec
Model Name:	QX1000
Series Model:	N/A
FCC ID:	2AUCLQX1000
Test Standard:	ANSI/IEEE Std. C95.1
	FCC 47 CFR Part 2 (2.1093)
	IEEE 1528: 2013
Max. Report SAR (1g):	Head:0.375 W/kg
	Body:0.397 W/kg

Any reproduction of this document must be done in full. No single part of this document may be reproduced without permission from STS, All Test Data Presented in this report is only applicable to presented Test sample.





Test Report Certification

Applicant's name : FX Technology Limited
Address : 38a High Street, Northwood, Middlesex, United Kingdom, HA6 1BN
Manufacture's Name : UWIN INNOVATION (HONGKONG) LIMITED
Address : 1 Queen's Road Central, Hong Kong


Product description


Product name : Smartphone
Brand name : Fxtec
Model name : QX1000
Series Model : N/A

Standards : ANSI/IEEE Std. C95.1-1992
FCC 47 CFR Part 2 (2.1093)
IEEE 1528: 2013

The device was tested by Shenzhen STS Test Services Co., Ltd. in accordance with the measurement methods and procedures specified in KDB 865664. The test results in this report apply only to the tested sample of the stated device/equipment. Other similar device/equipment will not necessarily produce the same results due to production tolerance and measurement uncertainties.

Date of Test :
Date (s) of performance of tests : 12 Aug 2019~20 Aug 2019
Date of Issue : 27 Aug 2019
Test Result : **Pass**

Testing Engineer : 
(Aaron Bu)

Technical Manager : 
(Jason Lu)

Authorized Signatory : 
(Vita Li)





Table of Contents

1.General Information	5
1.1 EUT Description	5
1.2 Test Environment	7
1.3 Test Factory	7
2.Test Standards And Limits	8
3. SAR Measurement System	9
3.1 Definition Of Specific Absorption Rate (SAR)	9
3.2 SAR System	9
4. Tissue Simulating Liquids	12
4.1 Simulating Liquids Parameter Check	12
5. SAR System Validation	14
5.1 Validation System	14
5.2 Validation Result	15
6. SAR Evaluation Procedures	16
7. EUT Antenna Location Sketch	17
7.1 SAR test exclusion consider table	18
8. EUT Test Position	19
8.1 Define Two Imaginary Lines On The Handset	19
8.2 Hotspot mode exposure position condition	20
9. Uncertainty	21
9.1 Measurement Uncertainty	21
9.2 System validation Uncertainty	22
10. Conducted Power Measurement	23
10.1 Test Result	23
10.2 Tune-up Power	45
10.3 SAR Test Exclusions Applied	50
11. EUT And Test Setup Photo	53
11.1 EUT Photo	53
11.2 Setup Photo	57
12. SAR Result Summary	63
12.1 Head SAR	63
12.2 Body-worn and Hotspot SAR	67
13. Equipment List	74
Appendix A. System Validation Plots	75
Appendix B. SAR Test Plots	105
Appendix C. Probe Calibration And Dipole Calibration Report	138

**Revision History**

Rev.	Issue Date	Report No.	Effect Page	Contents
00	27 Aug 2019	STS1906274H01	ALL	Initial Issue
Note: Format version of the report -V01				





1. General Information

Environmental evaluation measurements of specific absorption rate (SAR) distributions in emulated human head and body tissues exposed to radio frequency (RF) radiation from wireless portable devices for compliance with the rules and regulations of the U.S. Federal Communications Commission (FCC).

1.1 EUT Description

Product Name	Smartphone
Brand Name	Fxtec
Model Name	QX1000
Series Model	N/A
FCC ID	2AUCLQX1000
Model Difference	N/A
Battery	Rated Voltage: 3.85V; Charge Limit: 4.4V; Capacity: 3150mAh
Device Category	Portable
Product stage	Production unit
RF Exposure Environment	General Population / Uncontrolled
IMEI	356979054792291
Hardware Version	T5_MB_P2
Software Version	QX1000_EEA_20190829102646
Frequency Range	GSM 850:824.2~848.8MHz PCS1900:1850.2~1909.8MHz WCDMA Band II:1852.4~1907.6MHz WCDMA IV:1712.4~1752.6 MHz WCDMA Band V:826.4~846.6MHz LTE Band 2:1850.7~1909.3MHz LTE Band 4:1710.7~1754.3MHz LTE Band 5:824.7~848.3MHz LTE Band 7:2502.5~2567.5MHz LTE Band 12:699.7~715.3MHz LTE Band 13:779.5~784.5MHz LTE Band 17:706.5~713.5MHz LTE Band 41: 2496MHz~2690 MHz WLAN 802.11b/g/n(HT20):2412~2462MHz WLAN 802.11a/n/ac(HT20/40/80):5150~5250 MHz; WLAN 802.11a/n/ac(HT20/40/80):5250~5350 MHz; WLAN 802.11a/n/ac(HT20/40/80):5470~5725 MHz; WLAN 802.11a/n/ac(HT20/40/80):5725~5875 MHz; Bluetooth:2402~ 2480MHz GPS: 1575.42MHz NFC: 13.56 MHz



	Band	Mode	Head (W/kg)	Body Worn and Hotspot(W/kg)
Max. Reported SAR(1g): (Limit:1.6W/kg)	PCE	GSM 850	0.145	0.068
	PCE	GSM 1900	0.096	0.200
	PCE	WCDMA Band II	0.093	0.177
	PCE	WCDMA Band IV	0.210	0.052
	PCE	WCDMA Band V	0.023	0.108
	PCE	LTE Band 2	0.197	0.369
	PCE	LTE Band 4	0.375	0.205
	PCE	LTE Band 5	0.126	0.070
	PCE	LTE Band 7	0.168	0.115
	PCE	LTE Band 12	0.088	0.240
	PCE	LTE Band 13	0.107	0.164
	PCE	LTE Band 17	0.047	0.145
	PCE	LTE Band 41	0.026	0.112
	DTS	2.4G WLAN ANT A ^{Note}	0.088	0.209
	DTS	2.4G WLAN ANT B ^{Note}	0.167	0.083
	DTS	2.4G WLAN ANT A+B ^{Note}	0.210	0.105
	NII	5.2G WLAN ANT A ^{Note}	0.200	0.152
	NII	5.2G WLAN ANT B ^{Note}	0.121	0.061
	NII	5.2G WLAN ANT A+B ^{Note}	0.316	0.304
	NII	5.3G WLAN ANT A ^{Note}	0.229	0.307
	NII	5.3G WLAN ANT B ^{Note}	0.161	0.081
	NII	5.3G WLAN ANT A+B ^{Note}	0.286	0.386
	NII	5.6G WLAN ANT A ^{Note}	0.217	0.316
	NII	5.6G WLAN ANT B ^{Note}	0.200	0.100
	NII	5.6G WLAN ANT A+B ^{Note}	0.310	0.397
	NII	5.8G WLAN ANT A ^{Note}	0.203	0.102
	NII	5.8G WLAN ANT B ^{Note}	0.081	0.040
	NII	5.8G WLAN ANT A+B ^{Note}	0.256	0.128
	DSS	Bluetooth ^{Note}	0.167	0.084
1-g Sum SAR			0.691	0.766
FCC Equipment Class	Licensed Portable Transmitter Held to Ear (PCE) Part 15 Spread Spectrum Transmitter (DSS) Digital Transmission System (DTS) Unlicensed National Information Infrastructure TX (NII)			
Operating Mode:	GSM: GSM Voice; GPRS; EGPRS Class 12; WCDMA:RMC,HSDPA,HSUPA Release 6; LTE:QPSK,16QAM; WLAN: 802.11 b/g/n(HT20) /n(HT40); Bluetooth: 4.0+EDR (GFSK + π /4DQPSK+8DPSK) ; BLE NFC:ASK			
Antenna Specification:	GSM,WCDMA,LTE: PIFA Antenna BT,WLAN: PIFA Antenna			
SIM Card	Support dual-SIM, dual standby, the multiple SIM card with two lines cannot transmitting at the same time			
Hotspot Mode:	Support			
DTM Mode:	Not Support			

Note:

1. Bluetooth,2.4G WLAN ANT A body,2.4G WLAN ANT B,2.4G WLAN ANT A+B, 5.2G WLAN ANT A body,5.2G WLAN ANT B,5.2G WLAN ANT A+B body, 5.3G WLAN ANT A body,5.3G WLAN ANT B,5.3G WLAN ANT A+B body 5.6G WLAN ANT A body,5.6G WLAN ANT B,5.6G WLAN ANT A+B body 5.8G WLAN ANT A body,5.8G WLAN ANT B and 5.8G WLAN ANT A+B SAR was estimated
2. The dual SIM card mobile has 2 SIM slots and supports dual SIM dual standby. The WWAN radio transmission will be enabled by either one SIM at a time (Single active)
3. After pre-scan two SIM cards power, we found test result of the SIM1 was the worse, so we chose SIM1 card to



perform all tests.

4. The EUT battery must be fully charged and checked periodically during the test to ascertain uniform power

1.2 Test Environment

Ambient conditions in the SAR laboratory:

Items	Required
Temperature (°C)	18-25
Humidity (%RH)	30-70

1.3 Test Factory

SHENZHEN STS TEST SERVICES CO.,LTD.

A 1/F, Building B, Zhuoke Science Park, No.190 Chongqing Road, HepingShequ, Fuyong Sub-District, Bao'an District, Shenzhen, Guang Dong, China

FCC test Firm Registration No.: 625569

IC Registration No.: 12108A

A2LA Certificate No.: 4338.01





2. Test Standards And Limits

No.	Identity	Document Title
1	47 CFR Part 2	Frequency Allocations and Radio Treaty Matters; General Rules and Regulations
2	ANSI/IEEE Std. C95.1-1992	IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz
3	IEEE Std. 1528-2013	Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques
4	FCC KDB 447498 D01 v06	Mobile and Portable Device RF Exposure Procedures and Equipment Authorization Policies
5	FCC KDB 865664 D01 v01r04	SAR Measurement 100 MHz to 6 GHz
6	FCC KDB 865664 D02 v01r02	RF Exposure Reporting
7	FCC KDB 941225 D01 v03r01	SAR Measurement Procedures for 3G Devices
8	FCC KDB 941225 D05 v02r05	SAR for LTE Devices
9	FCC KDB 941225 D06 v02r01	Hotspot Mode SAR
10	FCC KDB 648474 D04 v01r03	SAR Evaluation Considerations for Wireless Handsets
11	FCC KDB 248227 D01 Wi-Fi SAR v02r02	SAR Considerations for 802.11 Devices

(A). Limits for Occupational/Controlled Exposure (W/kg)

Whole-Body	Partial-Body	Hands, Wrists, Feet and Ankles
0.4	8.0	20.0

(B). Limits for General Population/Uncontrolled Exposure (W/kg)

Whole-Body	Partial-Body	Hands, Wrists, Feet and Ankles
0.08	1.6	4.0

NOTE: Whole-Body SAR is averaged over the entire body, partial-body SAR is averaged over any 1 gram of tissue defined as a tissue volume in the shape of a cube. SAR for hands, wrists, feet and ankles is averaged over any 10 grams of tissue defined as a tissue volume in the shape of a cube.

Population/Uncontrolled Environments:

are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure.

Occupational/Controlled Environments:

are defined as locations where there is exposure that may be incurred by people who are aware of the potential for exposure, (i.e. as a result of employment or occupation).

NOTE

GENERAL POPULATION/UNCONTROLLED EXPOSURE

PARTIAL BODY LIMIT

1.6 W/kg

3. SAR Measurement System

3.1 Definition Of Specific Absorption Rate (SAR)

SAR is related to the rate at which energy is absorbed per unit mass in an object exposed to a radio field. The SAR distribution in a biological body is complicated and is usually carried out by experimental techniques or numerical modeling. The standard recommends limits for two tiers of groups, occupational/controlled and general population/uncontrolled, based on a person's awareness and ability to exercise control over his or her exposure. In general, occupational/controlled exposure limits are higher than the limits for general population/uncontrolled.

The SAR definition is the time derivative (rate) of the incremental energy (dW) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dv) of a given density (ρ). The equation description is as below:

$$SAR = \frac{d}{dt} \left(\frac{dW}{dm} \right) = \frac{d}{dt} \left(\frac{dW}{\rho dv} \right)$$


SAR is expressed in units of Watts per kilogram (W/kg) SAR measurement can be related to the electrical field in the tissue by

$$SAR = \frac{\sigma E^2}{\rho}$$

Where: σ is the conductivity of the tissue,
ρ is the mass density of the tissue and E is the RMS electrical field strength.

3.2 SAR System

MVG SAR System Diagram:



Comosar is a system that is able to determine the SAR distribution inside a phantom of human being according to different standards. The Comosar system consists of the following items:

- Main computer to control all the system
- 6 axis robot
- Data acquisition system
- Miniature E-field probe
- Phone holder
- Head simulating tissue

The following figure shows the system.



The EUT under test operating at the maximum power level is placed in the phone holder, under the phantom, which is filled with head simulating liquid. The E-Field probe measures the electric field inside the phantom. The OpenSAR software computes the results to give a SAR value in a 1g or 10g mass.

3.2.1 Probe

For the measurements the Specific Dosimetric E-Field Probe SN 45/15 EPGO281 with following specifications is used

- Dynamic range: 0.01-100 W/kg
- Tip Diameter: 2.5 mm
- Length of Individual Dipoles: 2 mm
- Maximum external diameter: 8 mm
- Distance between dipole/probe extremity: 8 mm (repeatability better than +/- 1mm)
- Probe linearity: $0 \pm 2.60\%$ (0.11dB)
- Axial Isotropy: < 0.25 dB
- Spherical Isotropy: < 0.25 dB
- Calibration range: 450 MHz to 6 GHz for head & body simulating liquid.
- Angle between probe axis (evaluation axis) and surface normal line: less than 30°



Figure 1 – MVG COMOSAR Dosimetric E field Dipole

3.2.2 Phantom

For the measurements the Specific Anthropomorphic Mannequin (SAM) defined by the IEEE SCC-34/SC2 group is used. The phantom is a polyurethane shell integrated in a wooden table. The thickness of the phantom amounts to 2mm +/- 0.2mm. It enables the dosimetric evaluation of left and right phone usage and includes an additional flat phantom part for the simplified performance check. The phantom set-up includes a cover, which prevents the evaporation of the liquid.

SN 32/14 SAM115



SN 32/14 SAM116



3.2.3 Device Holder



The SAR in the phantom is approximately inversely proportional to the square of the distance between the source and the liquid surface. For a source at 5 mm distance, a positioning uncertainty of ± 0.5 mm would produce a SAR uncertainty of ± 20 %. Accurate device positioning is therefore crucial for accurate and repeatable measurements. The positions in which the devices must be measured are defined by the standards.



4. Tissue Simulating Liquids

4.1 Simulating Liquids Parameter Check

The head tissue dielectric parameters recommended by the IEEE SCC-34/SC-2 in P1528 have been incorporated in the following table. These head parameters are derived from planar layer models simulating the highest expected SAR for the dielectric properties and tissue thickness variations in a human head. Other head and body tissue parameters that have not been specified in P1528 are derived from the tissue dielectric parameters computed from the 4-Cole-Cole equations described in Reference [12] and extrapolated according to the head parameters specified in P1528.

Head Tissue

Frequency (MHz)	cellulose %	DGBE %	HEC %	NaCl %	Preventol %	Sugar %	X100 %	Water %	Conductivity σ	Permittivity ϵ_r
750	0.2	/	/	1.4	0.2	57.0	/	41.1	0.89	41.9
835	0.2	/	/	1.4	0.2	57.9	/	40.3	0.90	41.5
900	0.2	/	/	1.4	0.2	57.9	/	40.3	0.97	41.5
1800	/	44.5	/	0.3	/	/	30.45	55.2	1.4	40.0
1900	/	44.5	/	0.3	/	/	30.45	55.2	1.4	40.0
2000	/	44.5	/	0.3	/	/	/	55.2	1.4	40.0
2450	/	44.9	/	0.1	/	/	/	55.0	1.80	39.2
2600	/	45.0	/	0.1	/	/	/	54.9	1.96	39.0

Body Tissue

Frequency (MHz)	cellulose %	DGBE %	HEC %	NaCl %	Preventol %	Sugar %	X100 %	Water %	Conductivity σ	Permittivity ϵ_r
750	0.2	/	/	0.9	0.1	47.2	/	51.7	0.96	55.5
835	0.2	/	/	0.9	0.1	48.2	/	50.8	0.97	55.2
900	0.2	/	/	0.9	0.1	48.2	/	50.8	1.05	55.0
1800	/	29.4	/	0.4	/	/	30.45	70.2	1.52	53.3
1900	/	29.4	/	0.4	/	/	30.45	70.2	1.52	53.3
2000	/	29.4	/	0.4	/	/	/	70.2	1.52	53.3
2450	/	31.3	/	0.1	/	/	/	68.6	1.95	52.7
2600	/	31.7	/	0.1	/	/	/	68.2	2.16	52.3

Tissue dielectric parameters for head and body phantoms				
Frequency	ϵ_r		σ S/m	
	Head	Body	Head	Body
300	45.3	58.2	0.87	0.92
450	43.5	56.7	0.87	0.94
900	41.5	55.0	0.97	1.05
1450	40.5	54.0	1.20	1.30
1800	40.0	53.3	1.40	1.52
2450	39.2	52.7	1.80	1.95
3000	38.5	52.0	2.40	2.73
5800	35.3	48.2	5.27	6.00

**LIQUID MEASUREMENT RESULTS**

Date	Ambient condition		Head Simulating Liquid		Parameters	Target	Measured	Deviation [%]	Limited [%]
	Temp. [°C]	Humidity [%]	Frequency	Temp. [°C]					
2019-08-13	23.0	47	750 MHz	22.7	Permittivity:	41.9	41.78	-0.29	±5
					Conductivity:	0.89	0.90	1.74	±5
2019-08-14	22.4	51	835 MHz	22.1	Permittivity:	41.5	41.75	0.60	±5
					Conductivity:	0.9	0.91	0.99	±5
2019-08-15	22.2	53	1800 MHz	21.9	Permittivity:	40	39.61	-0.97	±5
					Conductivity:	1.40	1.42	1.13	±5
2019-08-16	20.8	51	1900 MHz	20.5	Permittivity:	40	41.27	3.16	±5
					Conductivity:	1.4	1.41	0.93	±5
2019-08-19	21.3	52	2450 MHz	21.0	Permittivity:	39.2	40.47	3.23	±5
					Conductivity:	1.8	1.79	-0.39	±5
2019-08-20	21.1	58	2600 MHz	20.7	Permittivity:	39	38.73	-0.68	±5
					Conductivity:	1.96	1.92	-1.93	±5
2019-08-12	22.8	45	5200 MHz	22.5	Permittivity	36	34.73	-3.53	±5
					Conductivity	4.66	4.63	-0.64	±5
2019-08-12	22.8	45	5300 MHz	22.5	Permittivity	35.8	36.47	1.87	±5
					Conductivity	4.86	4.86	0.00	±5
2019-08-12	22.8	45	5600 MHz	22.5	Permittivity	35.5	36.10	1.69	±5
					Conductivity	5.07	5.11	0.79	±5


Date	Ambient condition		Body Simulating Liquid		Parameters	Target	Measured	Deviation [%]	Limited [%]
	Temp. [°C]	Humidity [%]	Frequency	Temp. [°C]					
2019-08-13	23.0	47	750 MHz	22.7	Permittivity:	55.5	55.51	0.03	±5
					Conductivity:	0.96	0.95	-0.86	±5
2019-08-14	22.4	51	835 MHz	22.1	Permittivity:	55.2	54.94	-0.46	±5
					Conductivity:	0.97	0.98	0.57	±5
2019-08-15	22.2	53	1800 MHz	21.9	Permittivity:	53.3	53.05	-0.47	±5
					Conductivity:	1.52	1.54	1.28	±5
2019-08-16	20.8	51	1900 MHz	20.5	Permittivity:	53.3	54.01	1.34	±5
					Conductivity:	1.52	1.52	-0.08	±5
2019-08-19	21.3	52	2450 MHz	21.0	Permittivity:	52.7	53.92	2.31	±5
					Conductivity:	1.95	1.96	0.54	±5
2019-08-20	21.1	58	2600 MHz	20.7	Permittivity:	52.5	52.49	-0.03	±5
					Conductivity:	2.16	2.13	-1.37	±5

5. SAR System Validation

5.1 Validation System

Each MVG system is equipped with one or more system validation kits. These units, together with the predefined measurement procedures within the MVG software, enable the user to conduct the system performance check and system validation. System kit includes a dipole, and dipole device holder.

The system check verifies that the system operates within its specifications. It's performed daily or before every SAR measurement. The system check uses normal SAR measurement in the flat section of the phantom with a matched dipole at a specified distance. The system validation setup is shown as below.





5.2 Validation Result

Comparing to the original SAR value provided by MVG, the validation data should be within its specification of 10 %.

Freq.(MHz)	Power(mW)	Tested Value (W/Kg)	Normalized SAR (W/kg/W)	Target (W/Kg/W)	Tolerance(%)	Date
750 Head	100	0.835	8.35	8.49	-1.61	2019-08-13
750 Body	100	0.845	8.45	8.49	-0.42	2019-08-13
835 Head	100	0.957	9.57	9.56	0.07	2019-08-14
835 Body	100	0.953	9.53	9.56	-0.29	2019-08-14
1800 Head	100	3.834	38.34	38.4	-0.16	2019-08-15
1800 Body	100	4.068	40.68	38.4	5.94	2019-08-15
1900 Head	100	3.766	37.66	39.7	-5.13	2019-08-16
1900 Body	100	3.908	39.08	39.7	-1.55	2019-08-16
2450 Head	100	5.033	50.33	52.4	-3.95	2019-08-19
2450 Body	100	5.045	50.45	52.4	-3.71	2019-08-19
2600 Head	100	5.689	56.89	55.3	2.88	2019-08-20
2600 Body	100	5.513	55.13	55.3	-0.30	2019-08-20
5200 Head	100	5.724	57.24	56.9	0.60	2019-08-12
5300 Head	100	5.830	58.30	58.43	-0.22	2019-08-12
5600 Head	100	6.023	60.23	59.97	0.43	2019-08-12

Note:

1. The tolerance limit of System validation $\pm 10\%$.
2. The dipole input power (forward power) was 100 mW.
3. The results are normalized to 1 W input power.



6. SAR Evaluation Procedures

The procedure for assessing the average SAR value consists of the following steps:

The following steps are used for each test position

- Establish a call with the maximum output power with a base station simulator. The connection between the mobile and the base station simulator is established via air interface
- Measurement of the local E-field value at a fixed location. This value serves as a reference value for calculating a possible power drift.
- Measurement of the SAR distribution with a grid of 8 to 16mm * 8 to 16 mm and a constant distance to the inner surface of the phantom. Since the sensors cannot directly measure at the inner phantom surface, the values between the sensors and the inner phantom surface are extrapolated. With these values the area of the maximum SAR is calculated by an interpolation scheme.
- Around this point, a cube of 30 * 30 * 30 mm or 32 * 32 * 32 mm is assessed by measuring 5 or 8 * 5 or 8*4 or 5 mm. With these data, the peak spatial-average SAR value can be calculated.


➤ Area Scan& Zoom Scan

First Area Scan is used to locate the approximate location(s) of the local peak SAR value(s). The measurement grid within an Area Scan is defined by the grid extent, grid step size and grid offset. Next, in order to determine the EM field distribution in a three-dimensional spatial extension, Zoom Scan is required. The Zoom Scan is performed around the highest E-field value to determine the averaged SAR-distribution over 10 g. Area scan and zoom scan resolution setting follows KDB 865664 D01 quoted below.

When the 1-g SAR of the highest peak is within 2 dB of the SAR limit, additional zoom scans are required for other peaks within 2 dB of the highest peak that have not been included in any zoom scan to ensure there is no increase in SAR.

7. EUT Antenna Location Sketch

It is a Smartphone



 WWAN Antenna

 WLAN/BT Antenna

Note 1: The antenna information refer the manufacturer provide report, applicable only to the tested sample identified in the report.



7.1 SAR test exclusion consider table

According with FCC KDB 447498 D01, appendix A, <SAR test exclusion thresholds for 100MHz ~6GHz and ≤50mm> table, this device SAR test configurations consider as following:

Band	Test position configurations					
	Front	Back	Right edge	Left edge	Top edge	Bottom edge
WWAN	<5mm	<5mm	<5mm	<5mm	142mm	<5mm
	Yes	Yes	Yes	Yes	No	Yes
WLAN/BT	<5mm	<5mm	58mm	<5mm	<5mm	130mm
	Yes	Yes	No	Yes	Yes	No

Note:

1. maximum power is the source-based time-average power and represents the maximum RF output power among production units.
2. per KDB 447498 D01, for larger devices, the test separation distance of adjacent edge configuration is determined by the closest separation between the antenna and the user.
3. per KDB 447498 D01, standalone SAR test exclusion threshold is applied; if the distance of the antenna to the user is <5mm, 5mm is user to determine SAR exclusion threshold
4. per KDB 447498 D01, the 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distance ≤50mm are determined by:
$$[(\text{max. power of channel, including tune-up tolerance, Mw}) / (\text{min. test separation distance, mm})] * \sqrt{f(\text{GHz})} \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR}$$
$$f(\text{GHz}) \text{ is the RF channel transmit frequency in GHz. Power and distance are rounded to the nearest mW and mm before calculation. The result is rounded to one decimal place for comparison}$$

For <50mm distance, we just calculate mW of the exclusion threshold value(3.0) to do compare
5. per KDB 447498 D01, at 100 MHz to 6GHz and for test separation distances >50mm, the SAR test exclusion threshold is determined according to the following
 - a) [threshold at 50mm in step 1] + (test separation distance - 50mm) * (f (MHz)/150)] Mw, at 100 MHz to 1500 MHz
 - b) [threshold at 50mm in step 1] + (test separation distance - 50mm) * 10] mW at > 1500MHz and ≤6GHz
6. Per KDB 447498 D02, RMC 12.2kbps setting is used to evaluate SAR. If HSDPA/ HSUPA/DC-HSDPA output power is <0.25db higher than RMC 12.2Kbps, or reported SAR with RMC 12.2kbps setting is ≤1.2W/Kg, HSDPA/HSUPA/DC-HSDPA SAR evaluation can be excluded.
7. Per KDB 248227 D01, choose the highest output power channel to test SAR and determine further SAR exclusion 8. for each frequency band, testing at higher data rates and higher order modulations is not required when the maximum average output power for each of each of these configurations is less than 1/4db higher than those measured at the lower data rate than 11b mode, thus the SAR can be excluded.

8. EUT Test Position


This EUT was tested in Right Cheek, Right Titled, Left Cheek, Left Titled, Front Face and Rear Face.

8.1 Define Two Imaginary Lines On The Handset

(1) The vertical centerline passes through two points on the front side of the handset the midpoint of the width w_t of the handset at the level of the acoustic output, and the midpoint of the width w_b of the handset.

(2) The horizontal line is perpendicular to the vertical centerline and passes through the center of the acoustic output. The horizontal line is also tangential to the face of the handset at point A.


(3) The two lines intersect at point A. Note that for many handsets, point A coincides with the center of the acoustic output; however, the acoustic output may be located elsewhere on the horizontal line. Also note that the vertical centerline is not necessarily to the front face of the handset, especially for clamshell handsets, handsets with flip covers, and other irregularly shaped handsets.



Cheek Position

1) To position the device with the vertical center line of the body of the device and the horizontal line crossing the center piece in a plane parallel to the sagittal plane of the phantom. While maintaining the device in this plane, align the vertical center line with the reference plane containing the ear and mouth reference point (M: Mouth, RE: Right Ear, and LE: Left Ear) and align the center of the ear piece with the line RE-LE.


2) To move the device towards the phantom with the ear piece aligned with the line LE-RE until the phone touched the ear. While maintaining the device in the reference plane and maintaining the phone contact with ear, move the bottom of the phone until any point on the front side is in contact with the cheek of the phantom or until contact with the ear is lost



Title Position


(1) To position the device in the "cheek" position described above.

(2) While maintaining the device in the reference plane described above and pivoting against the ear, moves it outward away from the mouth by an angle of 15 degrees or until with the ear is lost.




Body-worn Position Conditions:

Body-worn accessory exposure is typically related to voice mode operations when handsets are carried in body-worn accessories. The body-worn accessory procedures in KDB Publication 447498 D01 should be used to test for body-worn accessory SAR compliance, without a headset connected to it. When the same wireless transmission configuration is used for testing body-worn accessory and hotspot mode SAR, respectively, in voice and data mode, SAR results for the most conservative *test separation distance* configuration may be used to support both SAR conditions. When the *reported* SAR for a body-worn accessory, measured without a headset connected to the handset, is $> 1.2 \text{ W/kg}$, the highest *reported* SAR configuration for that wireless mode and frequency band should be repeated for the body-worn accessory with a headset attached to the handset.



8.2 Hotspot mode exposure position condition

For handsets that support hotspot mode operations, with wireless router capabilities and various web browsing function, the relevant hand and body exposure condition are tested according to the hotspot SAR procedures in KDB 941225. A test separation distance of 10 mm is required between the phantom and all surface and edges with a transmitting antenna located within 25 mm from that surface or edge. When form factor of a handset is smaller than 9cm x 5cm, a test separation distance of 5mm (instead of 10mm) is required for testing hotspot mode. When the separate distance required for body-worn accessory testing is larger than or equal to that tested for hotspot mode, in the same wireless mode and for the same surface of the phone, the hotspot mode SAR data may be used to support body-worn accessory SAR compliance for that particular configuration(surface).





9. Uncertainty

9.1 Measurement Uncertainty

The following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in IEEE 1528: 2013. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.

Uncertainty Component	Tol (+/- %)	Prob. Dist.	Div.	Ci (1g)	Ci (10g)	1g Ui (+/-%)	10g Ui (+/-%)	vi
Measurement System								
Probe calibration	5.831	N	1	1	1	5.83	5.83	∞
Axial Isotropy	0.695	R	$\sqrt{3}$	$\sqrt{0.5}$	$\sqrt{0.5}$	0.28	0.28	∞
Hemispherical Isotropy	1.045	R	$\sqrt{3}$	$\sqrt{0.5}$	$\sqrt{0.5}$	0.43	0.43	∞
Boundary effect	1.0	R	$\sqrt{3}$	1	1	0.58	0.58	∞
Linearity	0.685	R	$\sqrt{3}$	1	1	0.40	0.40	∞
System detection limits	1.0	R	$\sqrt{3}$	1	1	0.58	0.58	∞
Modulation response	3.0	R	$\sqrt{3}$	1	1	1.73	1.73	∞
Readout Electronics	0.021	N	1	1	1	0.021	0.021	∞
Response Time	0	R	$\sqrt{3}$	1	1	0	0	∞
Integration Time	1.4	R	$\sqrt{3}$	1	1	0.81	0.81	∞
RF ambient conditions-Noise	3.0	R	$\sqrt{3}$	1	1	1.73	1.73	∞
RF ambient conditions-reflections	3.0	R	$\sqrt{3}$	1	1	1.73	1.73	∞
Probe positioner mechanical tolerance	1.4	R	$\sqrt{3}$	1	1	0.81	0.81	∞
Probe positioning with respect to phantom shell	1.4	R	$\sqrt{3}$	1	1	0.81	0.81	∞
Post-processing	2.3	R	$\sqrt{3}$	1	1	1.33	1.33	∞
Test sample Related								
Test sample positioning	2.6	N	1	1	1	2.6	2.6	∞
Device holder uncertainty	3	N	1	1	1	3	3	∞
SAR drift measurement	5	R	$\sqrt{3}$	1	1	2.89	2.89	∞
SAR scaling	5	R	$\sqrt{3}$	1	1	2.89	2.89	∞
Phantom and tissue parameters								
Phantom uncertainty (shape and thickness uncertainty)	4	R	$\sqrt{3}$	1	1	2.31	2.31	∞
Uncertainty in SAR correction for deviations in permittivity and conductivity	1.9	N	1	1	0.84	1.90	1.60	∞
Liquid conductivity (temperature uncertainty)	2.5	R	$\sqrt{3}$	0.78	0.71	1.13	1.02	∞
Liquid conductivity (measured)	4	N	1	0.78	0.71	3.12	2.84	M
Liquid permittivity (temperature uncertainty)	2.5	R	$\sqrt{3}$	0.23	0.26	0.33	0.38	∞
Liquid permittivity (measured)	5	N	1	0.23	0.26	1.15	1.30	M
Combined Standard Uncertainty		RSS				9.79	9.59	
Expanded Uncertainty (95% Confidence interval)		K=2				19.58	19.18	



9.2 System validation Uncertainty

Uncertainty Component	Tol (+ - %)	Prob. Dist.	Div.	Ci (1g)	Ci (10g)	1g Ui (+-%)	10g Ui (+-%)	vi
Measurement System								
Probe calibration	5.831	N	1	1	1	5.83	5.83	∞
Axial Isotropy	0.695	R	$\sqrt{3}$	1	1	0.40	0.40	∞
Hemispherical Isotropy	1.045	R	$\sqrt{3}$	0	0	0.00	0.00	∞
Boundary effect	1.0	R	$\sqrt{3}$	1	1	0.58	0.58	∞
Linearity	0.685	R	$\sqrt{3}$	1	1	0.40	0.40	∞
System detection limits	1.0	R	$\sqrt{3}$	1	1	0.58	0.58	∞
Modulation response	3.0	R	$\sqrt{3}$	0	0	0.00	0.00	∞
Readout Electronics	0.021	N	1	1	1	0.021	0.021	∞
Response Time	0.0	R	$\sqrt{3}$	0	0	0.00	0.00	∞
Integration Time	1.4	R	$\sqrt{3}$	0	0	0.00	0.00	∞
RF ambient conditions-Noise	3.0	R	$\sqrt{3}$	1	1	1.73	1.73	∞
RF ambient conditions-reflections	3.0	R	$\sqrt{3}$	1	1	1.73	1.73	∞
Probe positioner mechanical tolerance	1.4	R	$\sqrt{3}$	1	1	0.81	0.81	∞
Probe positioning with respect to phantom shell	1.4	R	$\sqrt{3}$	1	1	0.81	0.81	∞
Post-Processing	2.3	R	$\sqrt{3}$	1	1	1.33	1.33	∞
System validation source								
Deviation of experimental dipole from numerical dipole	5.0	N	1	1	1	5.00	5.00	∞
Input power and SAR drift measurement	5.0	R	$\sqrt{3}$	1	1	2.89	2.89	∞
Other source contribution Uncertainty	2.0	R	$\sqrt{3}$	1	1	1.15	1.15	∞
Phantom and set-up								
Phantom uncertainty (shape and thickness uncertainty)	4.0	R	$\sqrt{3}$	1	1	2.31	2.31	∞
Uncertainty in SAR correction for deviations in permittivity and conductivity	1.9	N	1	1	0.84	1.90	1.60	∞
Liquid conductivity (temperature uncertainty)	2.5	R	$\sqrt{3}$	0.78	0.71	1.13	1.02	∞
Liquid conductivity (measured)	4	N	1	0.78	0.71	3.12	2.84	M
Liquid permittivity (temperature uncertainty)	2.5	R	$\sqrt{3}$	0.23	0.26	0.33	0.38	∞
Liquid permittivity (measured)	5	N	1	0.23	0.26	1.15	1.30	M
Combined Standard Uncertainty		RSS				9.718	9.517	
Expanded Uncertainty (95% Confidence interval)		K=2				19.44	19.04	



10. Conducted Power Measurement

10.1 Test Result

Burst Average Power (dBm)						
Band	GSM 850			PCS 1900		
Channel	128	190	251	512	661	810
Frequency (MHz)	824.2	836.6	848.8	1850.2	1880.0	1909.8
GSM(GMSK, 1-Slot)	32.36	33.04	32.82	29.43	29.32	29.03
GPRS (GMSK, 1-Slot)	27.55	28.24	28.39	25.74	26.15	26.15
GPRS (GMSK, 2-Slot)	27.07	27.75	27.98	25.25	25.69	25.73
GPRS (GMSK, 3-Slot)	26.60	27.27	27.49	24.85	25.26	25.32
GPRS (GMSK, 4-Slot)	26.16	26.85	27.03	24.41	24.79	24.82
EGPRS(8PSK, 1-Slot)	27.59	28.28	28.41	22.76	23.16	23.20
EGPRS(8PSK, 2-Slot)	26.81	27.55	27.65	22.05	22.46	22.43
EGPRS(8PSK, 3-Slot)	26.04	26.79	26.89	21.35	21.66	21.65
EGPRS(8PSK, 4-Slot)	25.32	26.03	26.16	20.61	20.88	20.92
Remark: GPRS, CS4 coding scheme. EGPRS, MCS9 coding scheme. Multi-Slot Class 8 , Support Max 4 downlink, 1 uplink , 5 working link Multi-Slot Class 10 , Support Max 4 downlink, 2 uplink , 5 working link Multi-Slot Class 12 , Support Max 4 downlink, 4 uplink , 5 working link						

Fram- Average Power(dBm)						
Band	GSM 850			PCS 1900		
Channel	128	190	251	512	661	810
Frequency (MHz)	824.2	836.6	848.8	1850.2	1880.0	1909.8
GSM(GMSK, 1-Slot)	23.33	24.01	23.79	20.40	20.29	20.00
GPRS (GMSK, 1-Slot)	18.52	19.21	19.36	16.71	17.12	17.12
GPRS (GMSK, 2-Slot)	21.05	21.73	21.96	19.23	19.67	19.71
GPRS (GMSK, 3-Slot)	22.34	23.01	23.23	20.59	21.00	21.06
GPRS (GMSK, 4-Slot)	23.15	23.84	24.02	21.40	21.78	21.81
EGPRS(8PSK, 1-Slot)	18.56	19.25	19.38	13.73	14.13	14.17
EGPRS(8PSK, 2-Slot)	20.79	21.53	21.63	16.03	16.44	16.41
EGPRS(8PSK, 3-Slot)	21.78	22.53	22.63	17.09	17.40	17.39
EGPRS(8PSK, 4-Slot)	22.31	23.02	23.15	17.60	17.87	17.91
Remark : 1. SAR testing was performed on the maximum frame-averaged power mode. 2. The frame-averaged power is linearly proportion to the slot number configured and it is linearly scaled the maximum burst-averaged power based on time slots. The calculated method is shown as below: Frame-averaged power = Burst averaged power (1 Tx Slot) – 9.03 dB Frame-averaged power = Burst averaged power (2 Tx Slots) – 6.02 dB Frame-averaged power = Burst averaged power (3 Tx Slots) - 4.26 dB Frame-averaged power = Burst averaged power (4 Tx Slots) – 3.01 dB						

**WCDMA**

Band	WCDMA Band V			WCDMA Band IV			WCDMA Band II		
Channel	4132	4183	4233	1312	1413	1513	9262	9400	9538
Frequency (MHz)	826.4	836.6	846.6	1712.6	1740	1752.4	1852.4	1880.0	1907.6
AMR 12.2Kbps	22.61	22.42	22.83	23.13	22.77	22.84	22.58	22.63	22.38
RMC 12.2Kbps	22.63	22.49	22.88	23.20	22.78	22.89	22.67	22.69	22.44
HSDPA Subtest-1	21.67	21.77	21.94	22.87	22.62	22.71	22.48	22.35	22.04
HSDPA Subtest-2	21.26	21.29	21.52	22.41	22.20	22.29	22.07	21.90	21.59
HSDPA Subtest-3	20.77	20.86	21.15	21.98	21.75	21.93	21.66	21.50	21.10
HSDPA Subtest-4	20.42	20.41	20.70	21.52	21.33	21.62	21.30	21.10	20.67
HSUPA Subtest-1	21.65	21.71	21.45	22.84	22.56	22.25	22.47	22.35	21.60
HSUPA Subtest-2	20.73	20.77	20.52	21.92	21.57	21.29	21.64	21.43	20.64
HSUPA Subtest-3	20.68	20.36	20.09	21.87	21.17	20.81	21.45	20.96	20.32
HSUPA Subtest-4	20.29	19.96	19.65	21.51	20.78	20.45	21.09	20.48	19.83
HSUPA Subtest-5	18.81	18.51	18.18	20.01	19.29	18.96	19.64	19.00	18.40

According to 3GPP 25.101 sub-clause 6.2.2 , the maximum output power is allowed to be reduced by following the table.

Table 6.1A: UE maximum output power with HS-DPCCH and E-DCH

UE Transmit Channel Configuration	CM(db)	MPR(db)
For all combinations of ,DPDCH,DPCCH HS-DPDCH,E-DPDCH and E-DPCCH	$0 \leq CM \leq 3.5$	$MAX(CM-1,0)$
Note: CM=1 for $\beta_c/\beta_d=12/15$, $\beta_{hs}/\beta_c=24/15$.For all other combinations of DPDCH, DPCCH, HS-DPCCH, E-DPDCH and E-DPCCH the MPR is based on the relative CM difference.		

The device supports MPR to solve linearity issues (ACLR or SEM) due to the higher peak-to average ratios (PAR) of the HSUPA signal. This prevents saturating the full range of the TX DAC inside of device and provides a reduced power output to the RF transceiver chip according to the Cubic Metric (a function of the combinations of DPDCH, DPCCH, HS-DPCCH, E-DPDCH and E-DPCCH).

When E-DPDCH channels are present the beta gains on those channels are reduced firsts to try to get the power under the allowed limit. If the beta gains are lowered as far as possible, then a hard limiting is applied at the maximum allowed level.

The SW currently recalculates the cubic metric every time the beta gains on the E-DPDCH are reduced.

The cubic metric will likely get lower each time this is done .However, there is no reported reduction of maximum output power in the HSUPA mode since the device also provides a compensation for the power back-off by increasing the gain of TX_AGC in the transceiver (PA) device.

The end effect is that the DUT output power is identical to the case where there is no MPR in the device.

**WLAN**

Mode	Channel Number	Frequency (MHz)	Average Power (dBm)		
			ANT A	ANT B	ANT A+B
802.11b	1	2412	9.71	5.42	N/A
	6	2437	9.73	5.34	N/A
	11	2462	9.87	5.51	N/A
802.11g	1	2412	5.16	1.10	N/A
	6	2437	5.08	1.67	N/A
	11	2462	5.18	2.12	N/A
802.11 n-HT20	1	2412	5.19	0.74	6.52
	6	2437	4.88	0.95	6.36
	11	2462	4.94	1.04	6.42

WLAN (5.2Gband)

Mode	Channel Number	Frequency (MHz)	Output Power (dBm)		
			ANT A	ANT B	ANT A+B
802.11a	36	5180	8.26	2.27	/
	40	5200	8.51	2.36	/
	48	5240	8.74	2.56	/
802.11 n-HT20	36	5180	8.19	2.20	9.17
	40	5200	8.42	2.27	9.36
	48	5240	8.59	2.46	9.54
802.11 n-HT40	38	5190	8.24	2.19	9.20
	46	5230	8.35	2.21	9.30
802.11 ac-VHT20	36	5180	8.16	2.17	9.14
	40	5200	8.41	2.26	9.35
	48	5240	8.62	2.44	9.56
802.11 ac-VHT40	38	5190	8.16	2.21	9.14
	46	5230	8.51	2.50	9.48
802.11 ac-VHT80	42	5210	7.87	1.36	8.75

**WLAN (5.3Gband)**

Mode	Channel Number	Frequency (MHz)	Output Power (dBm)		
			ANT A	ANT B	ANT A+B
802.11a	52	5260	8.80	2.76	/
	60	5300	9.03	3.18	/
	64	5320	9.01	3.51	/
802.11 n-HT20	52	5260	8.72	2.65	9.68
	60	5300	8.94	3.12	9.95
	64	5320	9.04	3.39	10.09
802.11 n-HT40	54	5270	8.65	2.72	9.64
	62	5310	8.89	3.25	9.94
802.11 ac-VHT20	52	5260	7.75	2.67	8.92
	60	5300	8.93	3.10	9.94
	64	5320	8.94	3.41	10.01
802.11 ac-VHT40	54	5270	8.66	2.72	9.65
	62	5310	8.85	3.15	9.89
802.11 ac-VHT80	58	5290	8.32	3.26	9.50

WLAN (5.6Gband)

Mode	Channel Number	Frequency (MHz)	Output Power (dBm)		
			ANT A	ANT B	ANT A+B
802.11a	100	5500	9.29	4.27	/
	116	5580	8.41	3.61	/
	140	5700	5.41	1.32	/
802.11 n-HT20	100	5500	8.99	4.19	10.23
	116	5580	8.13	3.51	9.42
	140	5700	5.11	1.23	6.60
802.11 n-HT40	102	5510	8.61	3.20	9.71
	110	5550	8.16	3.73	9.50
	134	5670	5.76	1.14	7.05
802.11 ac-VHT20	100	5500	8.83	4.18	10.11
	116	5580	7.99	3.50	9.31
	140	5700	5.09	1.21	6.58
802.11 ac-VHT40	102	5510	8.60	4.74	10.10
	110	5550	8.18	3.73	9.51
	134	5670	5.80	1.15	7.08
802.11 ac-VHT80	106	5530	6.89	1.98	8.11
	122	5610	4.41	-0.06	5.74

**WLAN (5.8Gband)**

Mode	Channel Number	Frequency (MHz)	Output Power (dBm)		
			ANT A	ANT B	ANT A+B
802.11a	149	5745	4.52	0.14	/
	157	5785	4.43	-0.30	/
	165	5825	4.36	-1.60	/
802.11 n-HT20	149	5745	4.43	0.05	5.781
	157	5785	4.32	-0.80	5.485
	165	5825	4.24	-1.74	5.217
802.11 n-HT40	151	5755	4.70	-0.22	5.913
	159	5795	4.65	-1.07	5.681
802.11 ac-VHT20	149	5745	4.46	0.06	5.805
	157	5785	4.33	-0.86	5.478
	165	5825	4.19	-1.72	5.181
802.11 ac-VHT40	151	5755	4.55	-0.23	5.797
	159	5795	4.47	-1.06	5.542
802.11 ac-VHT80	155	5775	3.14	0.63	5.074

Bluetooth

Mode	Channel Number	Frequency (MHz)	Average Power (dBm)
GFSK(1Mbps)	0	2402	5.41
	39	2441	4.37
	78	2480	5.62
$\pi/4$ -DQPSK(2Mbps)	0	2402	-0.86
	39	2441	-1.95
	78	2480	-0.48
8DPSK(3Mbps)	0	2402	-0.85
	39	2441	-1.94
	78	2480	-0.47

BLE

Mode	Channel Number	Frequency (MHz)	Average Power (dBm)
GFSK(1Mbps)	0	2402	-6.31
	19	2440	-6.14
	39	2480	-7.12
GFSK(2Mbps)	0	2402	-9.08
	19	2440	-8.94
	39	2480	-9.93



LTE Conducted Power

General Note:

1. Anritsu CMW500 base station simulator was used to setup the connection with EUT; the frequency band, channel bandwidth, RB allocation configuration, modulation type are set in the base station simulator to configure EUT transmitting at maximum power and at different configurations which are requested to be reported to FCC, for conducted power measurement and SAR testing.
2. Per KDB 941225 D05, when a properly configured base station simulator is used for the SAR and power measurements, spectrum plots for each RB allocation and offset configuration is not required.
3. Per KDB 941225 D05, start with the largest channel bandwidth and measure SAR for QPSK with 1 RB allocation, using the RB offset and required test channel combination with the highest maximum output power for RB offsets at the upper edge, middle and lower edge of each required test channel.
4. Per KDB 941225 D05, 50% RB allocation for QPSK SAR testing follows 1RB QPSK allocation procedure.
5. Per KDB 941225 D05, For QPSK with 100% RB allocation, SAR is not required when the highest maximum output power for 100 % RB allocation is less than the highest maximum output power in 50% and 1 RB allocations and the highest reported SAR for 1 RB and 50% RB allocation are ≤ 0.8 W/kg. Otherwise, SAR is measured for the highest output power channel; and if the reported SAR is > 1.45 W/kg, the remaining required test channels must also be tested.
6. Per KDB 941225 D05, 16QAM output power for each RB allocation configuration is $> \text{not } \frac{1}{2}$ dB higher than the same configuration in QPSK and the reported SAR for the QPSK configuration is ≤ 1.45 W/kg; Per KDB 941225 D05, 16QAM SAR testing is not required.
7. Per KDB 941225 D05, Smaller bandwidth output power for each RB allocation configuration is $> \text{not } \frac{1}{2}$ dB higher than the same configuration in the largest supported bandwidth, and the reported SAR for the largest supported bandwidth is ≤ 1.45 W/kg; Per KDB 941225 D05, smaller bandwidth SAR testing is not required.



LTE Band 2

LTE Band 2 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
1.4	1	0	QPSK	21.77	21.87	21.8
1.4	1	2		21.54	21.64	21.51
1.4	1	5		21.34	21.42	21.25
1.4	3	0		21.13	21.14	21.01
1.4	3	1		20.89	20.92	20.76
1.4	3	2		20.65	20.65	20.5
1.4	6	0		20.36	20.44	20.27
1.4	1	0	16-QAM	21.55	21.61	21.54
1.4	1	2		21.34	21.41	21.33
1.4	1	5		21.12	21.19	21.06
1.4	3	0		20.84	20.92	20.84
1.4	3	1		20.64	20.71	20.54
1.4	3	2		20.38	20.5	20.32
1.4	6	0		20.11	20.22	20.1
3	1	0	QPSK	21.77	21.67	21.76
3	1	7		21.52	21.38	21.53
3	1	14		21.24	21.08	21.27
3	8	0		21.02	20.87	21.05
3	8	4		20.78	20.65	20.78
3	8	7		20.54	20.43	20.51
3	15	0		20.34	20.21	20.25
3	1	0	16-QAM	21.57	21.38	21.47
3	1	7		21.3	21.18	21.21
3	1	14		21.08	20.95	20.98
3	8	0		20.79	20.73	20.7
3	8	4		20.55	20.5	20.42
3	8	7		20.32	20.26	20.17
3	15	0		20.04	20.06	19.93



LTE BAND 2

LTE Band 2 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
5	1	0	QPSK	21.53	21.5	21.32
5	1	12		21.26	21.26	21.04
5	1	24		20.97	21.05	20.76
5	12	0		20.7	20.84	20.48
5	12	6		20.44	20.62	20.27
5	12	11		20.2	20.33	20.06
5	25	0		19.93	20.06	19.83
5	1	0	16-QAM	21.31	21.26	21.08
5	1	12		21.11	21.05	20.8
5	1	24		20.88	20.81	20.57
5	12	0		20.6	20.59	20.36
5	12	6		20.34	20.31	20.09
5	12	11		20.11	20.06	19.81
5	25	0		19.84	19.78	19.59
10	1	0	QPSK	21.4	21.34	21.23
10	1	24		21.1	21.08	20.97
10	1	49		20.81	20.78	20.74
10	25	0		20.54	20.57	20.45
10	25	12		20.24	20.31	20.18
10	25	24		19.98	20.04	19.93
10	50	0		19.76	19.84	19.67
10	1	0	16-QAM	21.18	21.11	20.95
10	1	24		20.95	20.82	20.73
10	1	49		20.69	20.53	20.46
10	25	0		20.42	20.28	20.17
10	25	12		20.18	20	19.97
10	25	24		19.91	19.71	19.77
10	50	0		19.64	19.47	19.48



LTE BAND 2

LTE Band 2 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
15	1	0	QPSK	21.14	20.96	21.2
15	1	37		20.94	20.68	20.93
15	1	74		20.64	20.45	20.72
15	36	0		20.4	20.24	20.48
15	36	18		20.19	19.98	20.27
15	36	39		19.95	19.77	19.99
15	75	0		19.74	19.47	19.73
15	1	0	16-QAM	20.84	20.72	21
15	1	38		20.57	20.52	20.76
15	1	75		20.33	20.28	20.52
15	36	0		20.06	20	20.26
15	36	18		19.82	19.74	20.01
15	36	39		19.61	19.44	19.77
15	75	0		19.37	19.23	19.5
20	1	0	QPSK	21.93	21.96	22.06
20	1	49		21.71	21.72	21.86
20	1	99		21.43	21.43	21.6
20	50	0		21.16	21.16	21.33
20	50	24		20.89	20.9	21.03
20	50	49		20.61	20.68	20.73
20	100	0		20.36	20.46	20.52
20	1	0	16-QAM	21.7	21.72	21.81
20	1	49		21.49	21.47	21.61
20	1	99		21.2	21.17	21.36
20	50	0		20.94	20.94	21.1
20	50	24		20.7	20.71	20.85
20	50	49		20.44	20.45	20.62
20	100	0		20.19	20.17	20.41



LTE BAND 4

LTE Band 4 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
1.4	1	0	QPSK	21.86	22.3	21.98
1.4	1	2		21.61	22.01	21.7
1.4	1	5		21.4	21.75	21.47
1.4	3	0		21.11	21.49	21.23
1.4	3	1		20.87	21.2	20.94
1.4	3	2		20.65	20.96	20.66
1.4	6	0		20.43	20.7	20.41
1.4	1	0	16-QAM	21.64	22.01	21.71
1.4	1	2		21.42	21.77	21.48
1.4	1	5		21.13	21.48	21.27
1.4	3	0		20.89	21.28	21.01
1.4	3	1		20.59	21.04	20.72
1.4	3	2		20.34	20.8	20.44
1.4	6	0		20.12	20.56	20.22
3	1	0	QPSK	21.85	22.06	21.83
3	1	7		21.56	21.79	21.55
3	1	14		21.32	21.51	21.25
3	8	0		21.1	21.28	20.98
3	8	4		20.88	21	20.69
3	8	7		20.59	20.72	20.49
3	15	0		20.32	20.43	20.25
3	1	0	16-QAM	21.61	21.77	21.59
3	1	7		21.41	21.5	21.33
3	1	14		21.2	21.27	21.08
3	8	0		21	21	20.86
3	8	4		20.76	20.75	20.66
3	8	7		20.52	20.55	20.46
3	15	0		20.3	20.26	20.19



LTE BAND 4

LTE Band 4 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
5	1	0	QPSK	21.58	21.6	21.32
5	1	12		21.37	21.4	21.09
5	1	24		21.1	21.11	20.82
5	12	0		20.88	20.83	20.57
5	12	6		20.58	20.59	20.3
5	12	11		20.37	20.38	20.01
5	25	0		20.17	20.12	19.73
5	1	0	16-QAM	21.31	21.33	21.03
5	1	12		21.04	21.07	20.78
5	1	24		20.75	20.77	20.57
5	12	0		20.47	20.54	20.32
5	12	6		20.26	20.27	20.06
5	12	11		20.01	20.05	19.83
5	25	0		19.81	19.82	19.6
10	1	0	QPSK	20.9	21.68	21.42
10	1	24		20.66	21.42	21.16
10	1	49		20.43	21.15	20.9
10	25	0		20.22	20.86	20.69
10	25	12		20.01	20.62	20.43
10	25	24		19.72	20.37	20.21
10	50	0		19.51	20.13	19.98
10	1	0	16-QAM	20.68	21.39	21.16
10	1	24		20.48	21.16	20.95
10	1	49		20.23	20.87	20.74
10	25	0		19.95	20.64	20.45
10	25	12		19.73	20.39	20.2
10	25	24		19.48	20.15	19.91
10	50	0		19.25	19.85	19.65



LTE BAND 4

LTE Band 4 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
15	1	0	QPSK	21.25	21.23	21.04
15	1	37		20.98	21.02	20.78
15	1	74		20.75	20.82	20.52
15	36	0		20.49	20.6	20.26
15	36	18		20.25	20.3	19.96
15	36	39		19.95	20.01	19.75
15	75	0		19.68	19.73	19.54
15	1	0	16-QAM	20.98	20.94	20.77
15	1	38		20.77	20.68	20.52
15	1	75		20.5	20.45	20.25
15	36	0		20.22	20.24	20.02
15	36	18		19.94	19.98	19.79
15	36	39		19.72	19.77	19.55
15	75	0		19.43	19.55	19.34
20	1	0	QPSK	22.44	22.31	22.48
20	1	49		22.22	22.04	22.26
20	1	99		21.98	21.77	21.97
20	50	0		21.68	21.51	21.76
20	50	24		21.41	21.26	21.53
20	50	49		21.19	21.05	21.26
20	100	0		20.9	20.79	20.99
20	1	0	16-QAM	22.15	22.03	22.24
20	1	49		21.94	21.73	22.04
20	1	99		21.72	21.44	21.74
20	50	0		21.52	21.16	21.46
20	50	24		21.26	20.92	21.24
20	50	49		20.97	20.63	20.97
20	100	0		20.75	20.38	20.69



LTE BAND 5

LTE Band 5 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
1.4	1	0	QPSK	20.79	21	21.38
1.4	1	2		20.58	20.73	21.12
1.4	1	5		20.32	20.48	20.85
1.4	3	0		20.05	20.26	20.64
1.4	3	1		19.76	19.98	20.35
1.4	3	2		19.54	19.71	20.09
1.4	6	0		19.29	19.44	19.79
1.4	1	0	16-QAM	20.5	20.72	21.11
1.4	1	2		20.24	20.49	20.83
1.4	1	5		20	20.22	20.54
1.4	3	0		19.76	19.98	20.3
1.4	3	1		19.55	19.68	20.05
1.4	3	2		19.27	19.38	19.8
1.4	6	0		19.06	19.15	19.52
3	1	0	QPSK	20.65	20.84	21.17
3	1	7		20.43	20.61	20.92
3	1	14		20.22	20.39	20.64
3	8	0		19.97	20.18	20.4
3	8	4		19.72	19.94	20.15
3	8	7		19.49	19.72	19.9
3	15	0		19.2	19.5	19.64
3	1	0	16-QAM	20.44	20.63	20.93
3	1	7		20.17	20.42	20.64
3	1	14		19.93	20.18	20.34
3	8	0		19.72	19.91	20.09
3	8	4		19.46	19.63	19.84
3	8	7		19.24	19.36	19.59
3	15	0		18.98	19.07	19.3



LTE BAND 5

LTE Band 5 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
5	1	0	QPSK	21.07	21.33	21.65
5	1	12		20.84	21.04	21.36
5	1	24		20.6	20.76	21.07
5	12	0		20.37	20.48	20.85
5	12	6		20.13	20.26	20.56
5	12	11		19.92	20.02	20.3
5	25	0		19.66	19.8	20.1
5	1	0	16-QAM	20.86	21.09	21.42
5	1	12		20.57	20.8	21.22
5	1	24		20.27	20.52	20.98
5	12	0		19.98	20.28	20.7
5	12	6		19.75	19.99	20.4
5	12	11		19.52	19.79	20.1
5	25	0		19.23	19.55	19.85
10	1	0	QPSK	21.27	21.56	21.70
10	1	24		21.02	21.31	21.47
10	1	49		20.76	21.01	21.19
10	25	0		20.56	20.78	20.92
10	25	12		20.3	20.52	20.7
10	25	24		20.01	20.25	20.44
10	50	0		19.78	19.96	20.18
10	1	0	16-QAM	21.02	21.35	21.42
10	1	24		20.75	21.09	21.21
10	1	49		20.52	20.82	20.98
10	25	0		20.29	20.62	20.69
10	25	12		20.05	20.33	20.41
10	25	24		19.84	20.04	20.15
10	50	0		19.57	19.76	19.91



LTE BAND 7

LTE Band 7 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
5	1	0	QPSK	21.38	21.43	21.25
5	1	12		21.16	21.19	20.97
5	1	24		20.96	20.93	20.76
5	12	0		20.72	20.7	20.55
5	12	6		20.51	20.45	20.33
5	12	11		20.24	20.21	20.1
5	25	0		19.94	19.98	19.8
5	1	0	16-QAM	21.14	21.18	20.95
5	1	12		20.9	20.95	20.68
5	1	24		20.67	20.69	20.46
5	12	0		20.41	20.44	20.24
5	12	6		20.14	20.21	20.04
5	12	11		19.9	19.99	19.8
5	25	0		19.68	19.76	19.53
10	1	0	QPSK	21.62	21.4	21.58
10	1	24		21.34	21.14	21.29
10	1	49		21.14	20.85	21
10	25	0		20.93	20.57	20.72
10	25	12		20.69	20.35	20.42
10	25	24		20.4	20.11	20.13
10	50	0		20.18	19.89	19.88
10	1	0	16-QAM	21.37	21.16	21.31
10	1	24		21.07	20.88	21.07
10	1	49		20.79	20.67	20.84
10	25	0		20.53	20.38	20.64
10	25	12		20.3	20.17	20.39
10	25	24		20.05	19.93	20.13
10	50	0		19.8	19.69	19.86



LTE BAND 7

LTE Band 7 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
15	1	0	QPSK	20.68	20.85	20.73
15	1	37		20.4	20.57	20.52
15	1	74		20.18	20.33	20.26
15	36	0		19.94	20.11	19.98
15	36	18		19.7	19.86	19.76
15	36	39		19.45	19.65	19.49
15	75	0		19.19	19.41	19.25
15	1	0	16-QAM	20.42	20.61	20.48
15	1	38		20.21	20.37	20.27
15	1	75		19.96	20.13	19.98
15	36	0		19.73	19.87	19.76
15	36	18		19.53	19.62	19.55
15	36	39		19.31	19.37	19.27
15	75	0		19.09	19.17	19.02
20	1	0	QPSK	21.58	21.7	21.63
20	1	49		21.36	21.46	21.39
20	1	99		21.06	21.17	21.13
20	50	0		20.78	20.96	20.92
20	50	24		20.52	20.74	20.68
20	50	49		20.32	20.48	20.39
20	100	0		20.06	20.27	20.14
20	1	0	16-QAM	21.37	21.44	21.42
20	1	49		21.09	21.17	21.18
20	1	99		20.85	20.89	20.9
20	50	0		20.61	20.62	20.69
20	50	24		20.38	20.42	20.42
20	50	49		20.16	20.2	20.22
20	100	0		19.91	19.99	19.93



LTE BAND 12

LTE Band 12 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
1.4	1	0	QPSK	21.5	20.97	21.24
1.4	1	2		21.29	20.71	20.95
1.4	1	5		21.07	20.43	20.66
1.4	3	0		20.85	20.19	20.42
1.4	3	1		20.57	19.96	20.15
1.4	3	2		20.32	19.71	19.86
1.4	6	0		20.04	19.44	19.59
1.4	1	0	16-QAM	21.26	20.69	20.94
1.4	1	2		21.03	20.48	20.67
1.4	1	5		20.73	20.26	20.37
1.4	3	0		20.51	19.97	20.14
1.4	3	1		20.28	19.69	19.93
1.4	3	2		20.04	19.44	19.69
1.4	6	0		19.81	19.21	19.4
3	1	0	QPSK	21.26	20.88	21.24
3	1	7		21.06	20.66	20.97
3	1	14		20.82	20.44	20.74
3	8	0		20.52	20.21	20.47
3	8	4		20.31	19.92	20.26
3	8	7		20.1	19.64	20.05
3	15	0		19.89	19.35	19.82
3	1	0	16-QAM	21.06	20.65	21
3	1	7		20.86	20.42	20.74
3	1	14		20.61	20.14	20.5
3	8	0		20.36	19.89	20.24
3	8	4		20.16	19.59	19.97
3	8	7		19.95	19.31	19.74
3	15	0		19.74	19.04	19.47



LTE Band 12 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
5	1	0	QPSK	21.57	21.64	21.58
5	1	12		21.32	21.37	21.36
5	1	24		21.07	21.12	21.1
5	12	0		20.83	20.89	20.83
5	12	6		20.61	20.67	20.57
5	12	11		20.32	20.43	20.3
5	25	0		20.11	20.19	20.06
5	1	0	16-QAM	21.29	21.43	21.29
5	1	12		21.05	21.2	21.07
5	1	24		20.79	20.91	20.77
5	12	0		20.56	20.7	20.52
5	12	6		20.31	20.49	20.28
5	12	11		20.04	20.27	19.99
5	25	0		19.75	20	19.74
10	1	0	QPSK	21.93	21.94	21.71
10	1	24		21.64	21.7	21.49
10	1	49		21.43	21.49	21.22
10	25	0		21.2	21.26	20.98
10	25	12		20.9	20.96	20.77
10	25	24		20.69	20.67	20.55
10	50	0		20.4	20.42	20.31
10	1	0	16-QAM	21.71	21.7	21.45
10	1	24		21.43	21.47	21.19
10	1	49		21.17	21.18	20.94
10	25	0		20.96	20.92	20.73
10	25	12		20.72	20.63	20.52
10	25	24		20.52	20.35	20.26
10	50	0		20.22	20.08	19.97



LTE BAND 13

LTE Band 13 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
5	1	0	QPSK	20.66	20.6	21.01
5	1	12		20.43	20.36	20.73
5	1	24		20.22	20.12	20.52
5	12	0		20.01	19.83	20.26
5	12	6		19.78	19.62	20.02
5	12	11		19.55	19.33	19.74
5	25	0		19.3	19.08	19.53
5	1	0	16-QAM	20.41	20.33	20.79
5	1	12		20.17	20.11	20.53
5	1	24		19.95	19.88	20.32
5	12	0		19.69	19.66	20.09
5	12	6		19.46	19.42	19.85
5	12	11		19.23	19.19	19.57
5	25	0		18.97	18.89	19.27
10	1	0	QPSK	N/A	21.06	N/A
10	1	24		N/A	20.81	N/A
10	1	49		N/A	20.54	N/A
10	25	0		N/A	20.25	N/A
10	25	12		N/A	20.04	N/A
10	25	24		N/A	19.76	N/A
10	50	0		N/A	19.47	N/A
10	1	0	16-QAM	N/A	20.77	N/A
10	1	24		N/A	20.51	N/A
10	1	49		N/A	20.27	N/A
10	25	0		N/A	20.01	N/A
10	25	12		N/A	19.77	N/A
10	25	24		N/A	19.49	N/A
10	50	0		N/A	19.2	N/A



LTE BAND 17

LTE Band 17 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
5	1	0	QPSK	22.91	22.89	22.86
5	1	12		22.65	22.63	22.61
5	1	24		22.44	22.38	22.37
5	12	0		22.23	22.15	22.17
5	12	6		21.95	21.90	21.87
5	12	11		21.71	21.68	21.59
5	25	0		21.42	21.44	21.37
5	1	0	16-QAM	22.64	22.62	22.62
5	1	12		22.34	22.33	22.41
5	1	24		22.06	22.13	22.13
5	12	0		21.82	21.84	21.90
5	12	6		21.60	21.56	21.61
5	12	11		21.35	21.33	21.38
5	25	0		21.06	21.09	21.17
10	1	0	QPSK	23.38	23.32	23.29
10	1	24		23.08	23.06	23.03
10	1	49		22.88	22.84	22.78
10	25	0		22.68	22.62	22.48
10	25	12		22.48	22.37	22.20
10	25	24		22.21	22.15	21.98
10	50	0		21.98	21.93	21.69
10	1	0	16-QAM	23.08	23.05	23.06
10	1	24		22.80	22.77	22.83
10	1	49		22.58	22.50	22.58
10	25	0		22.35	22.26	22.34
10	25	12		22.11	22.01	22.05
10	25	24		21.81	21.73	21.81
10	50	0		21.53	21.49	21.56



LTE BAND 41

LTE Band 41 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
5	1	0	QPSK	22.15	22	21.63
5	1	12		21.92	21.71	21.4
5	1	24		21.7	21.45	21.11
5	12	0		21.49	21.24	20.9
5	12	6		21.28	21.03	20.67
5	12	11		21.06	20.77	20.45
5	25	0		20.77	20.53	20.18
5	1	0	16-QAM	21.88	21.77	21.34
5	1	12		21.68	21.52	21.06
5	1	24		21.44	21.26	20.76
5	12	0		21.23	21.04	20.47
5	12	6		21.01	20.75	20.2
5	12	11		20.81	20.53	19.99
5	25	0		20.55	20.28	19.78
10	1	0	QPSK	21.09	21.1	20.68
10	1	24		20.87	20.82	20.4
10	1	49		20.58	20.59	20.14
10	25	0		20.3	20.3	19.84
10	25	12		20.08	20.1	19.63
10	25	24		19.81	19.83	19.35
10	50	0		19.58	19.54	19.07
10	1	0	16-QAM	20.8	20.82	20.44
10	1	24		20.58	20.61	20.18
10	1	49		20.28	20.38	19.96
10	25	0		20.05	20.15	19.67
10	25	12		19.8	19.86	19.42
10	25	24		19.51	19.58	19.16
10	50	0		19.21	19.37	18.87



LTE Band 41 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
15	1	0	QPSK	20.13	20.39	20.28
15	1	37		19.89	20.11	20.08
15	1	74		19.68	19.85	19.78
15	36	0		19.4	19.55	19.53
15	36	18		19.14	19.33	19.28
15	36	39		18.87	19.1	19.04
15	75	0		18.57	18.87	18.8
15	1	0	16-QAM	19.87	20.13	19.98
15	1	38		19.66	19.89	19.75
15	1	75		19.39	19.66	19.47
15	36	0		19.13	19.37	19.25
15	36	18		18.89	19.15	19.01
15	36	39		18.64	18.85	18.79
15	75	0		18.35	18.56	18.52
20	1	0	QPSK	22.47	22.45	22.11
20	1	49		22.2	22.19	21.9
20	1	99		21.91	21.93	21.64
20	50	0		21.69	21.66	21.42
20	50	24		21.39	21.37	21.15
20	50	49		21.13	21.12	20.87
20	100	0		20.92	20.91	20.57
20	1	0	16-QAM	22.18	22.22	21.91
20	1	49		21.98	22.01	21.61
20	1	99		21.77	21.76	21.36
20	50	0		21.53	21.52	21.06
20	50	24		21.27	21.29	20.78
20	50	49		21.01	21.05	20.55
20	100	0		20.72	20.81	20.25

**10.2 Tune-up Power**

Mode	GSM850(AVG)	GSM1900(AVG)
GSM/PCS	33±1dBm	29±1dBm
GPRS (1 Slot)	28±1dBm	26±1dBm
GPRS (2 Slot)	27±1dBm	25±1dBm
GPRS (3 Slot)	27±1dBm	25±1dBm
GPRS (4 Slot)	27±1dBm	24±1dBm
EDGE (1 Slot)	28±1dBm	23±1dBm
EDGE (2 Slot)	27±1dBm	22±1dBm
EDGE (3 Slot)	26±1dBm	21±1dBm
EDGE (4 Slot)	26±1dBm	20±1dBm

Mode	WCDMA Band V(AVG)	WCDMA Band IV(AVG)	WCDMA Band II(AVG)
AMR	22±1dBm	23±1dBm	22±1dBm
RMC	22±1dBm	23±1dBm	22±1dBm
HSDPA Subtest-1	21±1dBm	22±1dBm	22±1dBm
HSDPA Subtest-2	21±1dBm	22±1dBm	22±1dBm
HSDPA Subtest-3	21±1dBm	21±1dBm	21±1dBm
HSDPA Subtest-4	20±1dBm	21±1dBm	21±1dBm
HSUPA Subtest-1	21±1dBm	22±1dBm	22±1dBm
HSUPA Subtest-2	20±1dBm	21±1dBm	21±1dBm
HSUPA Subtest-3	20±1dBm	21±1dBm	21±1dBm
HSUPA Subtest-4	20±1dBm	21±1dBm	20.1±1dBm
HSUPA Subtest-5	18±1dBm	19.1±1dBm	19±1dBm

Mode	2.4G WLAN(AVG)		
	ANT A	ANT B	ANT A+B
IEEE 802.11b	9±1dBm	5±1dBm	N/A
IEEE 802.11g	5±1dBm	2±1dBm	N/A
IEEE 802.11n(HT 20)	5±1dBm	1±1dBm	6±1dBm

Mode	5.2G WLAN(AVG)		
	ANT A	ANT B	ANT A+B
IEEE 802.11a	8±1dBm	2±1dBm	N/A
IEEE 802.11n(HT 20)	8±1dBm	2±1dBm	N/A
IEEE 802.11n(HT 40)	8±1dBm	2±1dBm	9±1dBm
IEEE 802.11ac(VHT 20)	8±1dBm	2±1dBm	9±1dBm
IEEE 802.11ac(VHT 40)	8±1dBm	2±1dBm	9±1dBm
IEEE 802.11ac(VHT 80)	7±1dBm	1±1dBm	8±1dBm



Mode	5.3G WLAN(AVG)		
	ANT A	ANT B	ANT A+B
IEEE 802.11a	9±1dBm	3±1dBm	N/A
IEEE 802.11n(HT 20)	9±1dBm	3±1dBm	10±1dBm
IEEE 802.11n(HT 40)	8±1dBm	3±1dBm	9±1dBm
IEEE 802.11ac(VHT 20)	8±1dBm	3±1dBm	10±1dBm
IEEE 802.11ac(VHT 40)	8±1dBm	3±1dBm	9±1dBm
IEEE 802.11ac(VHT 80)	8±1dBm	3±1dBm	9±1dBm

Mode	Channel	5.6G WLAN(AVG)		
		ANT A	ANT B	ANT A+B
IEEE 802.11a	100	9±1dBm	4±1dBm	N/A
	116	8±1dBm	3±1dBm	N/A
	140	5±1dBm	1±1dBm	N/A
IEEE 802.11n(HT 20)	100	8±1dBm	4±1dBm	10±1dBm
	116	8±1dBm	3±1dBm	9±1dBm
	140	5±1dBm	1±1dBm	6±1dBm
IEEE 802.11n(HT 40)	102	8±1dBm	3±1dBm	9±1dBm
	110	8±1dBm	3±1dBm	9±1dBm
	134	5±1dBm	1±1dBm	7±1dBm
IEEE 802.11ac(VHT 20)	100	8±1dBm	4±1dBm	10±1dBm
	116	7±1dBm	3±1dBm	9±1dBm
	140	5±1dBm	1±1dBm	6±1dBm
IEEE 802.11ac(VHT 40)	102	8±1dBm	4±1dBm	10±1dBm
	110	8±1dBm	3±1dBm	9±1dBm
	134	5±1dBm	1±1dBm	7±1dBm
IEEE 802.11ac(VHT 80)	106	6±1dBm	1±1dBm	8±1dBm
	122	4±1dBm	0±1dBm	5±1dBm

Mode	5.8G WLAN(AVG)		
	ANT A	ANT B	ANT A+B
IEEE 802.11a	4±1dBm	0±1dBm	N/A
IEEE 802.11n(HT 20)	4±1dBm	0±1dBm	5±1dBm
IEEE 802.11n(HT 40)	4±1dBm	0±1dBm	5±1dBm
IEEE 802.11ac(VHT 20)	4±1dBm	0±1dBm	5±1dBm
IEEE 802.11ac(VHT 40)	4±1dBm	0±1dBm	5±1dBm
IEEE 802.11ac(VHT 80)	3±1dBm	0±1dBm	5±1dBm



Mode	BT(AVG)
GFSK	5±1dBm
$\pi/4$ -DQPSK	-1±1dBm
8DPSK	-1±1dBm

Mode	BLE(AVG)
GFSK(1Mbps)	-7±1dBm
GFSK(2Mbps)	-9±1dBm





LTE

BW[MHz]	RB Size	Mode	Band 2	Band 4	Band 5	Band 7
1.4	1	QPSK	21±1dBm	22±1dBm	21±1dBm	N/A
1.4	3		21±1dBm	21±1dBm	20±1dBm	N/A
1.4	6		20±1dBm	20±1dBm	19±1dBm	N/A
1.4	1	16- QAM	21±1dBm	22±1dBm	21±1dBm	N/A
1.4	3		20±1dBm	21±1dBm	20±1dBm	N/A
1.4	6		20±1dBm	20±1dBm	19±1dBm	N/A
3	1	QPSK	21±1dBm	22±1dBm	21±1dBm	N/A
3	8		21±1dBm	21±1dBm	20±1dBm	N/A
3	15		20±1dBm	20±1dBm	19±1dBm	N/A
3	1	16- QAM	21±1dBm	21±1dBm	20±1dBm	N/A
3	8		20±1dBm	21±1dBm	20±1dBm	N/A
3	15		20±1dBm	20±1dBm	19±1dBm	N/A
5	1	QPSK	21±1dBm	21±1dBm	21±1dBm	21±1dBm
5	12		20±1dBm	20±1dBm	20±1dBm	20±1dBm
5	25		20±1dBm	20±1dBm	20±1dBm	19±1dBm
5	1	16- QAM	21±1dBm	21±1dBm	21±1dBm	21±1dBm
5	12		20±1dBm	20±1dBm	20±1dBm	20±1dBm
5	25		19±1dBm	19±1dBm	19±1dBm	19±1dBm
10	1	QPSK	21±1dBm	21±1dBm	21±1dBm	21±1dBm
10	25		20±1dBm	20±1dBm	20±1dBm	20±1dBm
10	50		19±1dBm	20±1dBm	20±1dBm	20±1dBm
10	1	16- QAM	21±1dBm	21±1dBm	21±1dBm	21±1dBm
10	25		20±1dBm	20±1dBm	20±1dBm	20±1dBm
10	50		19±1dBm	19±1dBm	19±1dBm	19±1dBm
15	1	QPSK	21±1dBm	21±1dBm	N/A	20±1dBm
15	36		20±1dBm	20±1dBm	N/A	20±1dBm
15	75		19±1dBm	19±1dBm	N/A	19±1dBm
15	1	16- QAM	21±1dBm	20±1dBm	N/A	20±1dBm
15	36		20±1dBm	20±1dBm	N/A	19±1dBm
15	75		19±1dBm	19±1dBm	N/A	19±1dBm
20	1	QPSK	21±1dBm	22±1dBm	N/A	21±1dBm
20	50		21±1dBm	21±1dBm	N/A	20±1dBm
20	100		20±1dBm	20±1dBm	N/A	20±1dBm
20	1	16- QAM	21±1dBm	22±1dBm	N/A	21±1dBm
20	50		21±1dBm	21±1dBm	N/A	20±1dBm
20	100		20±1dBm	20±1dBm	N/A	19±1dBm



BW[MHz]	RB Size	Mode	Band 12	Band 13	Band 17	Band 41
1.4	1	QPSK	21±1dBm	N/A	N/A	N/A
1.4	3		20±1dBm	N/A	N/A	N/A
1.4	6		20±1dBm	N/A	N/A	N/A
1.4	1	16- QAM	21±1dBm	N/A	N/A	N/A
1.4	3		20±1dBm	N/A	N/A	N/A
1.4	6		19±1dBm	N/A	N/A	N/A
3	1	QPSK	21±1dBm	N/A	N/A	N/A
3	8		20±1dBm	N/A	N/A	N/A
3	15		19±1dBm	N/A	N/A	N/A
3	1	16- QAM	21±1dBm	N/A	N/A	N/A
3	8		20±1dBm	N/A	N/A	N/A
3	15		19±1dBm	N/A	N/A	N/A
5	1	QPSK	21±1dBm	20±1dBm	22±1dBm	21±1dBm
5	12		20±1dBm	20±1dBm	22±1dBm	21±1dBm
5	25		20±1dBm	19±1dBm	21±1dBm	20±1dBm
5	1	16- QAM	21±1dBm	20±1dBm	22±1dBm	21±1dBm
5	12		20±1dBm	20±1dBm	21±1dBm	21±1dBm
5	25		20±1dBm	19±1dBm	21±1dBm	20±1dBm
10	1	QPSK	21±1dBm	21±1dBm	23±1dBm	21±1dBm
10	25		21±1dBm	20±1dBm	22±1dBm	20±1dBm
10	50		20±1dBm	9±1dBm	21±1dBm	19±1dBm
10	1	16- QAM	21±1dBm	20±1dBm	23±1dBm	20±1dBm
10	25		20±1dBm	20±1dBm	22±1dBm	20±1dBm
10	50		20±1dBm	19±1dBm	21±1dBm	19±1dBm
15	1	QPSK	N/A	N/A	N/A	20±1dBm
15	36		N/A	N/A	N/A	19±1dBm
15	75		N/A	N/A	N/A	18±1dBm
15	1	16- QAM	N/A	N/A	N/A	20±1dBm
15	36		N/A	N/A	N/A	19±1dBm
15	75		N/A	N/A	N/A	18±1dBm
20	1	QPSK	N/A	N/A	N/A	22±1dBm
20	50		N/A	N/A	N/A	21±1dBm
20	100		N/A	N/A	N/A	20±1dBm
20	1	16- QAM	N/A	N/A	N/A	22±1dBm
20	50		N/A	N/A	N/A	21±1dBm
20	100		N/A	N/A	N/A	20±1dBm



10.3 SAR Test Exclusions Applied

Per FCC KDB 447498D01, the 1-g SAR and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot \sqrt{f(\text{GHz})} \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where:

- $f(\text{GHz})$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

$$\frac{\text{Max Power of Channel (mW)}}{\text{Test Separation Dist (mm)}} * \sqrt{\text{Frequency (GHz)}} \leq 3.0$$

Based on the maximum conducted power of **Bluetooth Head** (rounded to the nearest mW) and the antenna to user separation distance,

Bluetooth Head SAR was not required; $[(3.981/5) * \sqrt{2.480}] = 1.25 < 3.0$.

Based on the maximum conducted power of **Bluetooth Body** (rounded to the nearest mW) and the antenna to user separation distance,

Bluetooth Body SAR was not required; $[(3.981/10) * \sqrt{2.480}] = 0.63 < 3.0$.

Based on the maximum conducted power of **2.4 GHz WLAN ANT A Head** (rounded to the nearest mW) and the antenna to user separation distance,

2.4 GHz WLAN ANT A SAR was required; $[(10.000/5) * \sqrt{2.462}] = 3.14 > 3.0$.

Based on the maximum conducted power of **2.4 GHz WLAN ANT A Body** (rounded to the nearest mW) and the antenna to user separation distance,

2.4 GHz WLAN ANT A SAR was not required; $[(10.000/10) * \sqrt{2.462}] = 1.57 < 3.0$.

Based on the maximum conducted power of **2.4 GHz WLAN ANT B Head** (rounded to the nearest mW) and the antenna to user separation distance,

2.4 GHz WLAN ANT B SAR was not required; $[(3.981/5) * \sqrt{2.462}] = 1.25 < 3.0$.

Based on the maximum conducted power of **2.4 GHz WLAN ANT B Body** (rounded to the nearest mW) and the antenna to user separation distance,

2.4 GHz WLAN ANT B SAR was not required; $[(3.981/10) * \sqrt{2.462}] = 0.63 < 3.0$.

Based on the maximum conducted power of **2.4 GHz WLAN ANT A+B Head** (rounded to the nearest mW) and the antenna to user separation distance,

2.4 GHz WLAN ANT A+B SAR was not required; $[(5.012/5) * \sqrt{2.462}] = 1.57 < 3.0$.

Based on the maximum conducted power of **2.4 GHz WLAN ANT A+B Body** (rounded to the nearest mW) and the antenna to user separation distance,

2.4 GHz WLAN ANT A+B SAR was not required; $[(5.012/10) * \sqrt{2.462}] = 0.79 < 3.0$.



Based on the maximum conducted power of **5.2 GHz WLAN ANT A Head** (rounded to the nearest mW) and the antenna to user separation distance,

5.2 GHz WLAN ANT A SAR was required; $[(7.943/5) * \sqrt{5.200}] = 3.62 > 3.0$.

Based on the maximum conducted power of **5.2 GHz WLAN ANT A Body** (rounded to the nearest mW) and the antenna to user separation distance,

5.2 GHz WLAN ANT A SAR was not required; $[(7.943/5) * \sqrt{5.200}] = 1.81 < 3.0$.

Based on the maximum conducted power of **5.2 GHz WLAN ANT B Head** (rounded to the nearest mW) and the antenna to user separation distance,

5.2 GHz WLAN ANT B SAR was not required; $[(1.585/5) * \sqrt{5.200}] = 0.72 < 3.0$.

Based on the maximum conducted power of **5.2 GHz WLAN ANT B Body** (rounded to the nearest mW) and the antenna to user separation distance,

5.2 GHz WLAN ANT B SAR was not required; $[(1.585/5) * \sqrt{5.200}] = 0.36 < 3.0$.

Based on the maximum conducted power of **5.2 GHz WLAN ANT A+B Head** (rounded to the nearest mW) and the antenna to user separation distance,

5.2 GHz WLAN ANT A+B SAR was required; $[(1.0000/5) * \sqrt{5.200}] = 4.56 > 3.0$.

Based on the maximum conducted power of **5.2 GHz WLAN ANT A+B Body** (rounded to the nearest mW) and the antenna to user separation distance,

5.2 GHz WLAN ANT A+B SAR was required; $[(1.0000/5) * \sqrt{5.200}] = 2.28 < 3.0$.

Based on the maximum conducted power of **5.3 GHz WLAN ANT A Head** (rounded to the nearest mW) and the antenna to user separation distance,

5.3 GHz WLAN ANT A SAR was required; $[(10.000/5) * \sqrt{5.300}] = 4.60 > 3.0$.

Based on the maximum conducted power of **5.3 GHz WLAN ANT A Body** (rounded to the nearest mW) and the antenna to user separation distance,

5.3 GHz WLAN ANT A SAR was not required; $[(10.000/5) * \sqrt{5.300}] = 2.30 < 3.0$.

Based on the maximum conducted power of **5.3 GHz WLAN ANT B Head** (rounded to the nearest mW) and the antenna to user separation distance,

5.3 GHz WLAN ANT B SAR was not required; $[(2.512/5) * \sqrt{5.300}] = 1.16 < 3.0$.

Based on the maximum conducted power of **5.3 GHz WLAN ANT B Body** (rounded to the nearest mW) and the antenna to user separation distance,

5.3 GHz WLAN ANT B SAR was not required; $[(2.512/5) * \sqrt{5.300}] = 0.58 < 3.0$.

Based on the maximum conducted power of **5.3 GHz WLAN ANT A+B Head** (rounded to the nearest mW) and the antenna to user separation distance,

5.3 GHz WLAN ANT A+B SAR was required; $[(12.589/5) * \sqrt{5.300}] = 5.80 > 3.0$.

Based on the maximum conducted power of **5.3 GHz WLAN ANT A+B Body** (rounded to the nearest mW) and the antenna to user separation distance,

5.3 GHz WLAN ANT A+B SAR was not required; $[(12.589/5) * \sqrt{5.300}] = 2.90 < 3.0$.



Based on the maximum conducted power of **5.6 GHz WLAN ANT A Head** (rounded to the nearest mW) and the antenna to user separation distance,

5.6 GHz WLAN ANT A SAR was required; $[(10.000/5)^* \sqrt{5.600}] = 4.73 > 3.0$.

Based on the maximum conducted power of **5.6 GHz WLAN ANT A Body** (rounded to the nearest mW) and the antenna to user separation distance,

5.6 GHz WLAN ANT A SAR was not required; $[(10.000/5)^* \sqrt{5.600}] = 2.37 < 3.0$.

Based on the maximum conducted power of **5.6 GHz WLAN ANT B Head** (rounded to the nearest mW) and the antenna to user separation distance,

5.6 GHz WLAN ANT B SAR was not required; $[(3.162/5)^* \sqrt{5.600}] = 1.50 < 3.0$.

Based on the maximum conducted power of **5.6 GHz WLAN ANT B Body** (rounded to the nearest mW) and the antenna to user separation distance,

5.6 GHz WLAN ANT B SAR was not required; $[(3.162/5)^* \sqrt{5.600}] = 0.75 < 3.0$.

Based on the maximum conducted power of **5.6 GHz WLAN ANT A+B Head** (rounded to the nearest mW) and the antenna to user separation distance,

5.6 GHz WLAN ANT A+B SAR was required; $[(12.589/5)^* \sqrt{5.600}] = 5.96 > 3.0$.

Based on the maximum conducted power of **5.6 GHz WLAN ANT A+B Body** (rounded to the nearest mW) and the antenna to user separation distance,

5.6 GHz WLAN ANT A+B SAR was required; $[(12.589/5)^* \sqrt{5.600}] = 2.98 < 3.0$.

Based on the maximum conducted power of **5.8 GHz WLAN ANT A Head** (rounded to the nearest mW) and the antenna to user separation distance,

5.8 GHz WLAN ANT A SAR was not required; $[(3.162/5)^* \sqrt{5.800}] = 1.52 < 3.0$.

Based on the maximum conducted power of **5.8 GHz WLAN ANT A Body** (rounded to the nearest mW) and the antenna to user separation distance,

5.8 GHz WLAN ANT A SAR was not required; $[(3.162/5)^* \sqrt{5.800}] = 0.76 < 3.0$.

Based on the maximum conducted power of **5.8 GHz WLAN ANT B Head** (rounded to the nearest mW) and the antenna to user separation distance,

5.8 GHz WLAN ANT B SAR was not required; $[(1.259/5)^* \sqrt{5.800}] = 0.61 < 3.0$.

Based on the maximum conducted power of **5.8 GHz WLAN ANT B Body** (rounded to the nearest mW) and the antenna to user separation distance,

5.8 GHz WLAN ANT B SAR was not required; $[(1.259/5)^* \sqrt{5.800}] = 1.92 < 3.0$.

Based on the maximum conducted power of **5.8 GHz WLAN ANT A+B Head** (rounded to the nearest mW) and the antenna to user separation distance,

5.8 GHz WLAN ANT A+B SAR was not required; $[(3.981/5)^* \sqrt{5.800}] = 1.92 < 3.0$.

Based on the maximum conducted power of **5.8 GHz WLAN ANT A+B Body** (rounded to the nearest mW) and the antenna to user separation distance,

5.8 GHz WLAN ANT A+B SAR was not required; $[(3.981/5)^* \sqrt{5.800}] = 0.96 < 3.0$.

11. EUT And Test Setup Photo

11.1 EUT Photo

Front side



Back side






Top side



Bottom side



Left side



Right side






Open mode




11.2 Setup Photo


Right Touch




Right Tilt




Left Touch




Left Tilt



Body Front side(separation distance is 10mm)



Body Back side(separation distance is 10mm)



Body left side(separation distance is 10mm)



Body right side(separation distance is 10mm)




Body top side(separation distance is 10mm)



Body Bottom side(separation distance is 10mm)



Liquid depth (15 cm)





12. SAR Result Summary

12.1 Head SAR

Band	Mode	Test Position	Ch.	Result 1g (W/Kg)	Power Drift(%)	Max.Turn-up Power(dBm)	Meas.Output Power(dBm)	Scaled SAR (W/Kg)	Meas. No.
GSM 850	Voice	Right Cheek	190	0.068	-2.95	34	33.04	0.085	/
		Right Tilt	190	0.103	-3.13	34	33.04	0.128	/
		Left Cheek	190	0.116	2.26	34	33.04	0.145	1
		Left Tilt	190	0.071	-0.13	34	33.04	0.089	/
GSM1900	Voice	Right Cheek	512	0.079	-2.13	30	29.43	0.090	/
		Right Tilt	512	0.053	-0.93	30	29.43	0.060	/
		Left Cheek	512	0.084	2.91	30	29.43	0.096	3
		Left Tilt	512	0.062	-0.34	30	29.43	0.071	/
WCDMA II	RMC	Right Cheek	9400	0.015	-0.70	23	22.69	0.016	/
		Right Tilt	9400	0.010	1.21	23	22.69	0.011	/
		Left Cheek	9400	0.087	-1.73	23	22.69	0.093	5
		Left Tilt	9400	0.064	0.55	23	22.69	0.069	/
WCDMA IV	RMC	Right Cheek	1413	0.103	3.59	24	23.20	0.124	/
		Right Tilt	1413	0.071	2.95	24	23.20	0.085	/
		Left Cheek	1413	0.175	-3.83	24	23.20	0.210	7
		Left Tilt	1413	0.118	3.31	24	23.20	0.142	/
WCDMA V	RMC	Right Cheek	4233	0.020	0.27	23	22.88	0.021	/
		Right Tilt	4233	0.014	2.01	23	22.88	0.014	/
		Left Cheek	4233	0.022	3.94	23	22.88	0.023	9
		Left Tilt	4233	0.017	-0.96	23	22.88	0.017	/



Band	Mode	Test Position	Ch.	Result 1g (W/Kg)	Power Drift(%)	Max.Turn-up Power(dBm)	Meas.Output Power(dBm)	Duty cycle(%)	Scaled SAR (W/Kg)	Meas. No.
2.4G WLAN ANT A	802.11b	Right Cheek	11	0.085	3.67	10	9.87	100%	0.088	27
		Right Tilt	11	0.063	0.63	10	9.87	100%	0.065	/
		Left Cheek	11	0.081	3.87	10	9.87	100%	0.083	/
		Left Tilt	11	0.059	1.88	10	9.87	100%	0.061	/
5.2G WLAN ANT A	802.11a	Right Cheek	48	0.188	3.45	9	8.74	100%	0.200	28
		Right Tilt	48	0.140	3.35	9	8.74	100%	0.149	/
		Left Cheek	48	0.182	0.10	9	8.74	100%	0.193	/
		Left Tilt	48	0.134	0.37	9	8.74	100%	0.142	/
5.2G WLAN ANT A+B	802.11ac	Right Cheek	48	0.251	0.60	10	9.56	100%	0.278	/
		Right Tilt	48	0.188	3.02	10	9.56	100%	0.208	/
		Left Cheek	48	0.286	0.40	10	9.56	100%	0.316	29
		Left Tilt	48	0.203	-2.43	10	9.56	100%	0.225	/
5.3G WLAN ANT A	802.11a	Right Cheek	60	0.174	-0.04	10	9.03	100%	0.218	/
		Right Tilt	60	0.105	-3.12	10	9.03	100%	0.131	/
		Left Cheek	60	0.183	1.63	10	9.03	100%	0.229	30
		Left Tilt	60	0.117	-1.70	10	9.03	100%	0.146	/
5.3G WLAN ANT A+B	802.11n	Right Cheek	64	0.204	-1.72	11	10.09	100%	0.252	/
		Right Tilt	64	0.132	1.02	11	10.09	100%	0.163	/
		Left Cheek	64	0.232	0.82	11	10.09	100%	0.286	31
		Left Tilt	64	0.180	1.44	11	10.09	100%	0.222	/
5.6G WLAN ANT A	802.11a	Right Cheek	100	0.153	0.00	10	9.29	100%	0.180	/
		Right Tilt	100	0.088	2.05	10	9.29	100%	0.104	/
		Left Cheek	100	0.184	-1.61	10	9.29	100%	0.217	32
		Left Tilt	100	0.104	-2.81	10	9.29	100%	0.122	/
5.6G WLAN ANT A+B	802.11n	Right Cheek	100	0.241	3.05	11	10.23	100%	0.288	/
		Right Tilt	100	0.158	-2.02	11	10.23	100%	0.189	/
		Left Cheek	100	0.260	2.55	11	10.23	100%	0.310	33
		Left Tilt	100	0.179	-0.54	11	10.23	100%	0.214	/

Note:

- Per KDB 447498 D01, the reported SAR is the measured SAR value adjusted for maximum tune-up tolerance.
 - Tune-up scaling Factor = tune-up limit power (mW) / EUT RF power (mW), where tune-up limit is the maximum rated power among all production units.
 - For WWAN: Scaled SAR(W/kg)= Measured SAR(W/kg)*Tune-up Scaling Factor
- Per KDB 248227- When the highest reported SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power and the adjusted SAR is ≤ 1.2 W/kg. (The highest reported SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power was **0.032** W/Kg for Head)
- Per KDB865664 D01, Repeated measurement is not required when the original highest measured SAR is <0.80 W/kg



Band	BW (MHz)	Mod.	RB Size	RB offset	Test Position	Ch.	Result 1g (W/Kg)	Power Drift(%)	Max. Turn-up Power(dBm)	Meas. Output Power(dBm)	Scaled SAR (W/Kg)	Meas. No.
LTE Band 2	20M	QPSK	1	0	Right Cheek	19100	0.120	3.24	23	22.06	0.149	/
			50	0	Right Cheek	19100	0.111	1.76	22	21.33	0.130	/
			1	0	Right Tilt	19100	0.078	-0.32	23	22.06	0.097	/
			50	0	Right Tilt	19100	0.063	-1.23	22	21.33	0.074	/
			1	0	Left Cheek	19100	0.159	-1.45	23	22.06	0.197	11
			50	0	Left Cheek	19100	0.133	-3.67	22	21.33	0.155	/
			1	0	Left Tilt	19100	0.125	-2.51	23	22.06	0.155	/
			50	0	Left Tilt	19100	0.101	2.09	22	21.33	0.118	/
LTE Band 4	20M	QPSK	1	0	Right Cheek	20050	0.309	0.12	23	22.48	0.348	/
			50	0	Right Cheek	20050	0.237	-1.58	22	21.76	0.250	/
			1	0	Right Tilt	20050	0.196	0.05	23	22.48	0.221	/
			50	0	Right Tilt	20050	0.171	-0.60	22	21.76	0.181	/
			1	0	Left Cheek	20050	0.333	-0.07	23	22.48	0.375	13
			50	0	Left Cheek	20050	0.308	-0.30	22	21.76	0.325	/
			1	0	Left Tilt	20050	0.249	1.40	23	22.48	0.281	/
			50	0	Left Tilt	20050	0.204	-0.22	22	21.76	0.216	/
LTE Band 5	10M	QPSK	1	0	Right Cheek	20600	0.113	-0.68	22	21.70	0.121	/
			25	0	Right Cheek	20600	0.071	0.64	21	20.92	0.072	/
			1	0	Right Tilt	20600	0.100	3.90	22	21.70	0.107	/
			25	0	Right Tilt	20600	0.063	-0.59	21	20.92	0.064	/
			1	0	Left Cheek	20600	0.118	-3.97	22	21.70	0.126	15
			25	0	Left Cheek	20600	0.107	-1.54	21	20.92	0.109	/
			1	0	Left Tilt	20600	0.075	1.35	22	21.70	0.080	/
			25	0	Left Tilt	20600	0.070	-1.38	21	20.92	0.071	/
LTE Band 7	20M	QPSK	1	0	Right Cheek	21100	0.050	-3.45	22	21.70	0.054	/
			50	0	Right Cheek	21100	0.039	-0.44	21	20.96	0.039	/
			1	0	Right Tilt	21100	0.021	-3.91	22	21.70	0.023	/
			50	0	Right Tilt	21100	0.017	-2.95	21	20.96	0.017	/
			1	0	Left Cheek	21100	0.157	-1.89	22	21.70	0.168	17
			50	0	Left Cheek	21100	0.123	-2.58	21	20.96	0.124	/
			1	0	Left Tilt	21100	0.083	1.91	22	21.70	0.089	/
			50	0	Left Tilt	21100	0.072	-2.66	21	20.96	0.073	/
LTE Band 12	10M	QPSK	1	0	Right Cheek	23095	0.075	1.37	22	21.94	0.076	/
			25	0	Right Cheek	23095	0.063	3.43	22	21.26	0.075	/
			1	0	Right Tilt	23095	0.039	-2.28	22	21.94	0.040	/
			25	0	Right Tilt	23095	0.031	-1.13	22	21.26	0.037	/
			1	0	Left Cheek	23095	0.087	0.78	22	21.94	0.088	19
			25	0	Left Cheek	23095	0.063	-0.45	22	21.26	0.075	/
			1	0	Left Tilt	23095	0.052	-3.82	22	21.94	0.053	/
			25	0	Left Tilt	23095	0.047	0.54	22	21.26	0.056	/



LTE Band 13	10M	QPSK	1	0	Right Cheek	23230	0.071	2.68	22	21.06	0.088	/
			25	0	Right Cheek	23230	0.062	-0.83	21	20.25	0.074	/
			1	0	Right Tilt	23230	0.040	2.06	22	21.06	0.050	/
			25	0	Right Tilt	23230	0.034	-3.22	21	20.25	0.040	/
			1	0	Left Cheek	23230	0.086	-2.49	22	21.06	0.107	21
			25	0	Left Cheek	23230	0.072	-2.05	21	20.25	0.086	/
			1	0	Left Tilt	23230	0.051	2.07	22	21.06	0.063	/
			25	0	Left Tilt	23230	0.043	3.08	21	20.25	0.051	/
LTE Band 17	10M	QPSK	1	0	Right Cheek	23780	0.035	1.00	24	23.38	0.040	/
			25	0	Right Cheek	23780	0.030	3.72	23	22.68	0.032	/
			1	0	Right Tilt	23780	0.013	2.12	24	23.38	0.015	/
			25	0	Right Tilt	23780	0.010	-2.14	23	22.68	0.011	/
			1	0	Left Cheek	23780	0.041	-2.80	24	23.38	0.047	23
			25	0	Left Cheek	23780	0.032	2.80	23	22.68	0.034	/
			1	0	Left Tilt	23780	0.020	3.52	24	23.38	0.023	/
			25	0	Left Tilt	23780	0.014	-0.46	23	22.68	0.015	/
LTE Band 41	20M	QPSK	1	0	Right Cheek	39750	0.013	2.32	23	22.47	0.015	/
			50	0	Right Cheek	39750	0.010	0.73	22	21.69	0.011	/
			1	0	Right Tilt	39750	0.007	3.38	23	22.47	0.008	/
			50	0	Right Tilt	39750	0.004	-2.11	22	21.69	0.004	/
			1	0	Left Cheek	39750	0.023	3.81	23	22.47	0.026	25
			50	0	Left Cheek	39750	0.017	-2.82	22	21.69	0.018	/
			1	0	Left Tilt	39750	0.009	-2.68	23	22.47	0.010	/
			50	0	Left Tilt	39750	0.006	-3.94	22	21.69	0.006	/



12.2 Body-worn and Hotspot SAR

Band	Mode	Test Position	Ch.	Result 1g (W/Kg)	Power Drift(%)	Max.Turn-up Power(dBm)	Meas.Output Power(dBm)	Scaled SAR (W/Kg)	Meas. No.
GSM 850	GPRS Data-4 Slot	Front side	251	0.035	-3.91	28	27.03	0.044	/
		Back side	251	0.054	-0.03	28	27.03	0.068	2
		Left side	251	0.010	-3.32	28	27.03	0.013	/
		Right side	251	0.013	2.01	28	27.03	0.016	/
		Bottom side	251	0.037	-3.96	28	27.03	0.046	/
GSM1900	GPRS Data-4 Slot	Front side	810	0.129	0.91	26	25.32	0.151	/
		Back side	810	0.171	2.15	26	25.32	0.200	4
		Left side	810	0.057	-2.95	26	25.32	0.067	/
		Right side	810	0.079	3.77	26	25.32	0.092	/
		Bottom side	810	0.086	-2.64	26	25.32	0.101	/
WCDMA II	RMC	Front side	9400	0.133	-0.45	23	22.69	0.035	/
		Back side	9400	0.165	-2.08	23	22.69	0.177	6
		Left side	9400	0.021	-1.63	23	22.69	0.023	/
		Right side	9400	0.027	-0.34	23	22.69	0.029	/
		Bottom side	9400	0.051	-2.08	23	22.69	0.055	6
WCDMA IV	RMC	Front side	1413	0.027	3.92	24	23.20	0.032	/
		Back side	1413	0.043	1.50	24	23.20	0.052	8
		Left side	1413	0.009	1.30	24	23.20	0.011	/
		Right side	1413	0.011	-3.50	24	23.20	0.013	/
		Bottom side	1413	0.039	3.87	24	23.20	0.047	/
WCDMA V	RMC	Front side	4233	0.079	2.31	23	22.88	0.081	/
		Back side	4233	0.105	-0.67	23	22.88	0.108	10
		Left side	4233	0.010	-1.85	23	22.88	0.010	/
		Right side	4233	0.017	-3.93	23	22.88	0.017	/
		Bottom side	4233	0.052	3.57	23	22.88	0.053	/

Note:

- The test separation of all above table is 10mm.
- Per KDB 447498 D01, the reported SAR is the measured SAR value adjusted for maximum tune-up tolerance.
 - Tune-up scaling Factor = tune-up limit power (mW) / EUT RF power (mW), where tune-up limit is the maximum rated power among all production units.
 - For WWAN: Scaled SAR(W/kg)= Measured SAR(W/kg)*Tune-up Scaling Factor
- When the user enables the personal Wireless router functions for the handsets, actual operations include simultaneous transmission of both the Wi-Fi transmitting frequency and thus cannot be evaluated for SAR under actual use conditions. The "Portable Hotspot" feature on the handset was NOT activated, to ensure the SAR measurements were evaluated for a single transmission frequency RF signal.



Band	BW (MHz)	Mod.	RB Size	RB offset	Test Position	Ch.	Result 1g (W/Kg)	Power Drift(%)	Max. Turn-up Power(dBm)	Meas. Output Power(dBm)	Scaled SAR (W/Kg)	Meas. No.
LTE Band 2	20M	QPSK	1	0	Front side	19100	0.234	-0.06	23	22.06	0.291	/
			50	0	Front side	19100	0.201	1.79	22	21.33	0.235	/
			1	0	Back Side	19100	0.297	-1.94	23	22.06	0.369	12
			50	0	Back Side	19100	0.251	-1.49	22	21.33	0.293	/
			1	0	Left Side	19100	0.102	0.53	23	22.06	0.127	/
			50	0	Left Side	19100	0.075	-3.36	22	21.33	0.088	/
			1	0	Right Side	19100	0.129	-1.49	23	22.06	0.160	/
			50	0	Right Side	19100	0.091	2.62	22	21.33	0.106	/
			1	0	Bottom Side	19100	0.159	3.67	23	22.06	0.197	/
			50	0	Bottom Side	19100	0.150	2.14	22	21.33	0.175	/
LTE Band 4	20M	QPSK	1	0	Front side	20050	0.134	-2.29	23	22.48	0.151	/
			50	0	Front side	20050	0.104	-0.62	22	21.76	0.110	/
			1	0	Back Side	20050	0.182	-3.55	23	22.48	0.205	14
			50	0	Back Side	20050	0.150	-0.81	22	21.76	0.159	/
			1	0	Left Side	20050	0.059	-0.26	23	22.48	0.067	/
			50	0	Left Side	20050	0.051	2.90	22	21.76	0.054	/
			1	0	Right Side	20050	0.063	3.57	23	22.48	0.071	/
			50	0	Right Side	20050	0.055	0.30	22	21.76	0.058	/
			1	0	Bottom Side	20050	0.079	-2.55	23	22.48	0.089	/
			50	0	Bottom Side	20050	0.064	3.48	22	21.76	0.068	/
LTE Band 5	10M	QPSK	1	0	Front side	20600	0.041	0.42	22	21.70	0.044	/
			25	0	Front side	20600	0.037	2.21	21	20.92	0.038	/
			1	0	Back Side	20600	0.065	3.33	22	21.70	0.070	16
			25	0	Back Side	20600	0.053	-0.59	21	20.92	0.054	/
			1	0	Left Side	20600	0.011	-3.65	22	21.70	0.012	/
			25	0	Left Side	20600	0.014	1.34	21	20.92	0.014	/
			1	0	Right Side	20600	0.021	-1.78	22	21.70	0.023	/
			25	0	Right Side	20600	0.016	-0.61	21	20.92	0.016	/
			1	0	Bottom Side	20600	0.030	-0.27	22	21.70	0.032	/
			25	0	Bottom Side	20600	0.026	-3.49	21	20.92	0.026	/
LTE Band 7	20M	QPSK	1	0	Front side	21100	0.081	3.27	22	21.70	0.087	/
			50	0	Front side	21100	0.053	-3.76	21	20.96	0.053	/
			1	0	Back Side	21100	0.107	-3.60	22	21.70	0.115	18
			50	0	Back Side	21100	0.078	-0.91	21	20.96	0.079	/
			1	0	Left Side	21100	0.008	-1.13	22	21.70	0.009	/
			50	0	Left Side	21100	0.007	-3.46	21	20.96	0.007	/
			1	0	Right Side	21100	0.013	-0.87	22	21.70	0.014	/
			50	0	Right Side	21100	0.010	-0.09	21	20.96	0.010	/
			1	0	Bottom Side	21100	0.051	2.41	22	21.70	0.055	/
			50	0	Bottom Side	21100	0.039	-0.74	21	20.96	0.039	/



LTE Band 12	10M	QPSK	1	0	Front side	23095	0.159	0.25	22	21.94	0.161	/
			25	0	Front side	23095	0.127	-3.93	22	21.26	0.151	/
			1	0	Back Side	23095	0.237	1.05	22	21.94	0.240	20
			25	0	Back Side	23095	0.201	1.86	22	21.26	0.238	/
			1	0	Left Side	23095	0.059	3.49	22	21.94	0.060	/
			25	0	Left Side	23095	0.038	-0.58	22	21.26	0.045	/
			1	0	Right Side	23095	0.086	-3.60	22	21.94	0.087	/
			25	0	Right Side	23095	0.061	2.92	22	21.26	0.072	/
			1	0	Bottom Side	23095	0.110	3.46	22	21.94	0.112	/
			25	0	Bottom Side	23095	0.095	3.49	22	21.26	0.113	/
LTE Band 13	10M	QPSK	1	0	Front side	23230	0.108	1.56	22	21.06	0.134	/
			25	0	Front side	23230	0.091	-3.81	21	20.25	0.108	/
			1	0	Back Side	23230	0.132	2.34	22	21.06	0.164	22
			25	0	Back Side	23230	0.115	0.56	21	20.25	0.137	/
			1	0	Left Side	23230	0.023	2.09	22	21.06	0.029	/
			25	0	Left Side	23230	0.020	1.57	21	20.25	0.024	/
			1	0	Right Side	23230	0.032	0.00	22	21.06	0.040	/
			25	0	Right Side	23230	0.024	-0.01	21	20.25	0.029	/
			1	0	Bottom Side	23230	0.059	0.20	22	21.06	0.073	/
			25	0	Bottom Side	23230	0.050	3.27	21	20.25	0.059	/
LTE Band 17	10M	QPSK	1	0	Front side	23780	0.101	-0.32	24	23.38	0.116	/
			25	0	Front side	23780	0.087	0.49	23	22.68	0.094	/
			1	0	Back Side	23780	0.126	-1.95	24	23.38	0.145	24
			25	0	Back Side	23780	0.107	1.24	23	22.68	0.115	/
			1	0	Left Side	23780	0.021	-2.29	24	23.38	0.024	/
			25	0	Left Side	23780	0.013	1.32	23	22.68	0.014	/
			1	0	Right Side	23780	0.036	3.52	24	23.38	0.042	/
			25	0	Right Side	23780	0.025	-1.38	23	22.68	0.027	/
			1	0	Bottom Side	23780	0.071	1.73	24	23.38	0.082	/
			25	0	Bottom Side	23780	0.064	-0.09	23	22.68	0.069	/
LTE Band 41	20M	QPSK	1	0	Front side	39750	0.061	0.41	23	22.47	0.069	/
			50	0	Front side	39750	0.052	-0.81	22	21.69	0.056	/
			1	0	Back Side	39750	0.099	1.01	23	22.47	0.112	26
			50	0	Back Side	39750	0.080	-0.21	22	21.69	0.086	/
			1	0	Left Side	39750	0.011	3.15	23	22.47	0.012	/
			50	0	Left Side	39750	0.007	-0.27	22	21.69	0.008	/
			1	0	Right Side	39750	0.014	0.25	23	22.47	0.016	/
			50	0	Right Side	39750	0.010	-2.87	22	21.69	0.011	/
			1	0	Bottom Side	39750	0.042	3.10	23	22.47	0.047	/
			50	0	Bottom Side	39750	0.030	-3.91	22	21.69	0.032	/

**Simultaneous Multi-band Transmission Evaluation:**

Application Simultaneous Transmission information:

Position	Simultaneous state
Head	1. GSM + WLAN
	2. GSM + Bluetooth
	3. WCDMA + WLAN
	4. WCDMA + Bluetooth
	5. LTE + WLAN
	6. LTE + Bluetooth
Body	1. GSM + WLAN
	2. GSM + Bluetooth
	3. WCDMA + WLAN
	4. WCDMA + Bluetooth
	5. LTE + WLAN
	6. LTE + Bluetooth

NOTE:

1. Bluetooth and WLAN can't simultaneous transmission at the same time.
2. For simultaneous transmission at head and body exposure position, 2 transmitters simultaneous transmission was the worst state.
3. Based upon KDB 447498 D01, BT SAR is excluded as below table.
4. If the test separation distance is <5mm, 5mm is used for excluded SAR calculation.
5. For minimum test separation distance $\leq 50\text{mm}$, Bluetooth standalone SAR is excluded according to $[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f} (\text{GHz}) / x] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR
6. The reported SAR summation is calculated based on the same configuration and test position.
7. KDB 447498 / 4.3.2 (2) when standalone SAR test exclusion applies to an antenna that transmits simultaneously with other antennas, the standalone SAR must be estimated according to following to determine simultaneous transmission SAR test exclusion:
 - a) $(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm}) \cdot [\sqrt{f} (\text{GHz}) / x] \text{ W/kg}$ for test separation distances $\leq 50 \text{ mm}$; Where $x = 7.5$ for 1-g SAR, and $x = 18.75$ for 10-g SAR.
 - b) 0.4W/Kg for 1-g SAR and 1.0W/Kg for 10-g SAR, when the separation distance is $>50\text{mm}$.



Estimated SAR		Maximum Power		Antenna to user(mm)	Frequency(GHz)	Stand alone SAR(1g) [W/kg]
		dBm	mW			
BT	Head	6	3.981	5	2.480	0.167
	Body			10	2.480	0.084
2.4G WLAN ANT A	Body	10	10.000	10	2.462	0.209
2.4G WLAN ANT B	Head	6	3.981	5	2.462	0.167
	Body			10	2.462	0.083
2.4G WLAN ANT A+B	Head	7	5.012	5	2.462	0.210
	Body			10	2.462	0.105
5.2G WLAN ANT A	Body	7	5.012	10	5.200	0.152
5.2G WLAN ANT B	Head	3	1.995	5	5.200	0.121
	Body			10	5.200	0.061
5.2G WLAN ANT A+B	Body	10	10.000	10	5.200	0.304
5.3G WLAN ANT A	Body	10	10.000	10	5.300	0.307
5.3G WLAN ANT B	Head	4	2.512	5	5.300	0.161
	Body			10	5.300	0.081
5.3G WLAN ANT A+B	Body	11	12.589	10	5.300	0.386
5.6G WLAN ANT A	Body	10	10.000	10	5.600	0.316
5.6G WLAN ANT B	Head	5	3.162	5	5.600	0.200
	Body			10	5.600	0.100
5.6G WLAN ANT A+B	Body	11	12.589	10	5.600	0.397
5.8G WLAN ANT A	Head	5	3.162	5	5.800	0.203
	Body			10	5.800	0.102
5.8G WLAN ANT B	Head	1	1.259	5	5.800	0.081
	Body			10	5.800	0.040
5.8G WLAN ANT A+B	Head	6	3.981	5	5.800	0.256
	Body			10	5.800	0.128




Simultaneous Mode	Position	Mode	Max. 1-g SAR (W/kg)	1-g Sum SAR (W/kg)
GSM + 2.4G WLAN	Head	GSM Voice	0.145	0.355
		2.4G WLAN	0.210	
	Body	GSM Data	0.200	0.409
		2.4G WLAN	0.209	
GSM + 5G WLAN	Head	GSM Voice	0.145	0.461
		5G WLAN	0.316	
	Body	GSM Data	0.200	0.597
		5G WLAN	0.397	
GSM + Bluetooth	Head	GSM Voice	0.145	0.312
		Bluetooth	0.167	
	Body	GSM Data	0.200	0.284
		Bluetooth	0.084	
WCDMA + 2.4G WLAN	Head	WCDMA RMC	0.210	0.420
		2.4G WLAN	0.210	
	Body	WCDMA RMC	0.177	0.386
		2.4G WLAN	0.209	
WCDMA + 5G WLAN	Head	WCDMA RMC	0.210	0.526
		5G WLAN	0.316	
	Body	WCDMA RMC	0.177	0.574
		5G WLAN	0.397	
WCDMA + Bluetooth	Head	WCDMA RMC	0.210	0.377
		Bluetooth	0.167	
	Body	WCDMA RMC	0.177	0.261
		Bluetooth	0.084	
LTE + 2.4G WLAN	Head	LTE RMC	0.375	0.585
		2.4G WLAN	0.210	
	Body	LTE RMC	0.369	0.578
		2.4G WLAN	0.209	



LTE + 5G WLAN	Head	LTE RMC	0.375	0.691
		5G WLAN	0.316	
	Body	LTE RMC	0.369	0.766
		5G WLAN	0.397	
LTE + Bluetooth	Head	LTE RMC	0.375	0.542
		Bluetooth	0.167	
	Body	LTE RMC	0.369	0.453
		Bluetooth	0.084	

Simultaneous transmission SAR test exclusion is determined for each operating configuration and exposure condition according to the reported standalone SAR of each applicable simultaneous transmitting antenna.

When the sum of SAR 1g of all simultaneously transmitting antennas in an operating mode and exposure condition combination is within the SAR limit (SAR-1g 1.6 W/kg), the simultaneous transmission SAR is not required. When the sum of SAR 1g is greater than the SAR limit (SAR-1g 1.6 W/kg), SAR test exclusion is determined by the SPLSR.





13. Equipment List

Kind of Equipment	Manufacturer	Type No.	Serial No.	Last Calibration	Calibrated Until
750MHz Dipole	MVG	SID750	SN 30/14 DIP0G750-331	2017.08.15	2020.08.14
835MHz Dipole	MVG	SID835	SN 30/14 DIP0G835-332	2017.08.15	2020.08.14
1800MHz Dipole	MVG	SID1800	SN 30/14 DIP1G800-329	2017.08.15	2020.08.14
1900MHz Dipole	MVG	SID1900	SN 30/14 DIP1G900-333	2017.08.15	2020.08.14
2450MHz Dipole	MVG	SID2450	SN 30/14 DIP2G450-335	2017.08.15	2020.08.14
2600MHz Dipole	MVG	SID2600	SN 30/14 DIP2G600-336	2017.08.15	2020.08.14
Waveguide	SATIMO	SWG5500	SN 13/14 WGA32	2017.08.15	2020.08.14
E-Field Probe	MVG	SSE2	SN 45/15 EPOG281	2019.03.25	2020.03.24
Dielectric Probe Kit	MVG	SCLMP	SN 32/14 OCPG67	2018.12.01	2019.11.30
Antenna	MVG	ANTA3	SN 07/13 ZNTA52	N/A	N/A
Phantom1	MVG	SAM	SN 32/14 SAM115	N/A	N/A
Phantom2	MVG	SAM	SN 32/14 SAM116	N/A	N/A
Phone holder	MVG	N/A	SN 32/14 MSH97	N/A	N/A
Laptop holder	MVG	N/A	SN 32/14 LSH29	N/A	N/A
Attenuator	Agilent	99899	DC-18GHz	N/A	N/A
Directional coupler	Narda	4226-20	3305	N/A	N/A
Network Analyzer	Agilent	8753ES	US38432810	2019.03.02	2020.03.01
Multi Meter	Keithley	Multi Meter 2000	4050073	2018.10.13	2019.10.12
Signal Generator	Agilent	N5182A	MY50140530	2018.10.16	2019.10.15
Wireless Communication Test Set	Agilent	8960-E5515C	MY48360751	2018.10.16	2019.10.15
Wireless Communication Test Set	R&S	CMW500	117239	2018.10.13	2019.10.12
Power Amplifier	DESAY	ZHL-42W	9638	2018.10.13	2019.10.12
Power Meter	R&S	NRP	100510	2018.10.26	2019.10.25
Power Meter	Agilent	E4418B	GB43312526	2018.10.26	2019.10.25
Power Sensor	R&S	NRP-Z11	101919	2018.10.13	2019.10.12
Power Sensor	Agilent	E9301A	MY41497725	2018.10.13	2019.10.12
hygrothermograph	MiEO	HH660	N/A	2018.10.11	2019.10.10
Thermograph	Elitech	RC-4	S/N EF7176501537	2018.10.15	2019.10.14

Note:

Per KDB 865664 D01, Dipole SAR Validation Verification, STS LAB has adopted 3 years calibration intervals. On annual basis, every measurement dipole has been evaluated and is in compliance with the following criteria:

1. There is no physical damage on the dipole
2. System validation with specific dipole is within 10% of calibrated value

Return-loss in within 20% of calibrated measurement



Appendix A. System Validation Plots

System Performance Check Data (750MHz Head)

Type: Phone measurement (Complete)

Area scan resolution: dx=8mm,dy=8mm


Zoom scan resolution: dx=8mm, dy=8mm, dz=5mm

Date of measurement: 2019-08-13

Measurement duration: 13 minutes 25 seconds

Experimental conditions




Phantom	Validation plane
Device Position	-
Band	750MHz
Channels	-
Signal	CW
Frequency (MHz)	750MHz
Relative permittivity	41.78
Conductivity (S/m)	0.90
Power drift (%)	-0.20
Probe	SN 45/15 EPGO281
ConvF:	1.53
Crest factor:	1:1



Maximum location: X=2.00, Y=1.00

SAR 10g (W/Kg)	0.535218
SAR 1g (W/Kg)	0.835121

Z Axis Scan





System Performance Check Data (750MHz Body)

Type: Phone measurement (Complete)

Area scan resolution: dx=8mm,dy=8mm


Zoom scan resolution: dx=8mm, dy=8mm, dz=5mm

Date of measurement: 2019-08-13

Measurement duration: 14 minutes 12 seconds

Experimental conditions.




Probe	
Phantom	Validation plane
Device Position	-
Band	750MHz
Channels	-
Signal	CW
Frequency (MHz)	750MHz
Relative permittivity	55.51
Conductivity (S/m)	0.95
Power drift (%)	1.44
Probe	SN 45/15 EPGO281
ConvF:	1.59
Crest factor:	1:1



Maximum location: X=1.00, Y=-1.00

SAR 10g (W/Kg)	0.524586
SAR 1g (W/Kg)	0.845247

Z Axis Scan





System Performance Check Data (835MHz Head)

Type: Phone measurement (Complete)

Area scan resolution: dx=8mm,dy=8mm


Zoom scan resolution: dx=8mm, dy=8mm, dz=5mm

Date of measurement: 2019-08-14

Measurement duration: 13 minutes 27 seconds

Experimental conditions




Phantom	Validation plane
Device Position	-
Band	835MHz
Channels	-
Signal	CW
Frequency (MHz)	835MHz
Relative permittivity	41.75
Conductivity (S/m)	0.91
Power drift (%)	0.07
Probe	SN 45/15 EPGO281
ConvF:	1.78
Crest factor:	1:1



Maximum location: X=-7.00, Y=-1.00

SAR 10g (W/Kg)	0.621024
SAR 1g (W/Kg)	0.956803

Z Axis Scan





System Performance Check Data (835MHz Body)

Type: Phone measurement (Complete)

Area scan resolution: dx=8mm,dy=8mm


Zoom scan resolution: dx=8mm, dy=8mm, dz=5mm

Date of measurement: 2019-08-14

Measurement duration: 14 minutes 13 seconds

Experimental conditions.




Probe	
Phantom	Validation plane
Device Position	-
Band	835MHz
Channels	-
Signal	CW
Frequency (MHz)	835MHz
Relative permittivity	54.94
Conductivity (S/m)	0.98
Power drift (%)	-0.37
Probe	SN 45/15 EPGO281
ConvF:	1.85
Crest factor:	1:1



Maximum location: X=-7.00, Y=-1.00

SAR 10g (W/Kg)	0.610148
SAR 1g (W/Kg)	0.953409

Z Axis Scan





System Performance Check Data(1800MHz Head)

Type: Phone measurement (Complete)


Area scan resolution: dx=8mm,dy=8mm

Zoom scan resolution: dx=8mm, dy=8mm, dz=5mm

Date of measurement: 2019-08-15

Experimental conditions.




Phantom	Validation plane
Device Position	-
Band	1800MHz
Channels	-
Signal	CW
Frequency (MHz)	1800MHz
Relative permittivity	39.61
Conductivity (S/m)	1.42
Power drift (%)	0.23
Probe	SN 45/15 EPGO281
ConvF	1.83
Crest factor:	1:1



Maximum location: X=5.00, Y=1.00

SAR 10g (W/Kg)	2.021559
SAR 1g (W/Kg)	3.834018

Z Axis Scan





System Performance Check Data(1800MHz Body)

Type: Phone measurement (Complete)


Area scan resolution: dx=8mm,dy=8mm

Zoom scan resolution: dx=8mm, dy=8mm, dz=5mm

Date of measurement: 2019-08-15

Experimental conditions.




Phantom	Validation plane
Device Position	-
Band	1800MHz
Channels	-
Signal	CW
Frequency (MHz)	1800MHz
Relative permittivity	53.05
Conductivity (S/m)	1.54
Power drift (%)	-0.28
Probe	SN 45/15 EPGO281
ConvF	1.87
Crest factor:	1:1



Maximum location: X=-3.00, Y=-2.00

SAR 10g (W/Kg)	2.095482
SAR 1g (W/Kg)	4.067749

Z Axis Scan





System Performance Check Data (1900MHz Head)

Type: Phone measurement (Complete)

Area scan resolution: dx=8mm,dy=8mm


Zoom scan resolution: dx=8mm, dy=8mm, dz=5mm

Date of measurement: 2019-08-16

Measurement duration: 14 minutes 12 seconds

Experimental conditions.




Phantom	Validation plane
Device Position	-
Band	1900MHz
Channels	-
Signal	CW
Frequency (MHz)	1900MHz
Relative permittivity	41.27
Conductivity (S/m)	1.41
Power drift (%)	0.46
Probe	SN 45/15 EPGO281
ConvF:	2.10
Crest factor:	1:1



Maximum location: X=3.00, Y=-2.00

SAR 10g (W/Kg)	2.095321
SAR 1g (W/Kg)	3.766488

Z Axis Scan





System Performance Check Data (1900MHz Body)

Type: Phone measurement (Complete)

Area scan resolution: dx=8mm,dy=8mm


Zoom scan resolution: dx=8mm, dy=8mm, dz=5mm

Date of measurement: 2019-08-16

Measurement duration: 14 minutes 46 seconds

Experimental conditions.

Device Position	-
Band	1900MHz
Channels	-
Signal	CW
Frequency (MHz)	1900
Relative permittivity	54.01
Conductivity (S/m)	1.52
Power drift (%)	-0.31
Probe	SN 45/15 EPGO281
ConvF:	2.16
Crest factor:	1:1






Maximum location: X=-3.00, Y=-2.00

SAR Peak: 5.27 W/kg

SAR 10g (W/Kg)	2.065486
SAR 1g (W/Kg)	3.908004

Z Axis Scan





System Performance Check Data (2450MHz Head)

Type: Phone measurement (Complete)

Area scan resolution: dx=8mm,dy=8mm


Zoom scan resolution: dx=8mm, dy=8mm, dz=5mm

Date of measurement: 2019-08-19

Measurement duration: 13 minutes 51seconds

Experimental conditions.




Device Position	Validation plane
Band	2450 MHz
Channels	-
Signal	CW
Frequency (MHz)	2450
Relative permittivity	40.47
Conductivity (S/m)	1.79
Power drift (%)	-0.38
Probe	SN 45/15 EPGO281
ConvF	2.21
Crest factor:	1:1



Maximum location: X=1.00, Y=0.00

SAR 10g (W/Kg)	2.489526
SAR 1g (W/Kg)	5.033247

Z Axis Scan





System Performance Check Data (2450MHz Body)

Type: Phone measurement (Complete)

Area scan resolution: dx=8mm,dy=8mm


Zoom scan resolution: dx=8mm, dy=8mm, dz=5mm

Date of measurement: 2019-08-19

Measurement duration: 14 minutes 23 seconds

Experimental conditions.




Device Position	Validation plane
Band	2450 MHz
Channels	-
Signal	CW
Frequency (MHz)	2450
Relative permittivity	53.92
Conductivity (S/m)	1.96
Power drift (%)	-0.30
Probe	SN 45/15 EPGO281
ConvF	2.28
Crest factor:	1:1



Maximum location: X=1.00, Y=0.00

SAR 10g (W/Kg)	2.401595
SAR 1g (W/Kg)	5.044817

Z Axis Scan





System Performance Check Data(2600MHz Head)

Type: Phone measurement (Complete)


Area scan resolution: dx=8mm,dy=8mm

Zoom scan resolution: dx=8mm, dy=8mm, dz=5mm

Date of measurement: 2019-08-20

Experimental conditions.




Device Position	Validation plane
Band	2600 MHz
Channels	-
Signal	CW
Frequency (MHz)	2600
Relative permittivity	38.73
Conductivity (S/m)	1.92
Power drift (%)	0.63
Probe	SN 45/15 EPGO281
ConvF	2.32
Crest factor:	1:1



Maximum location: X=1.00, Y=0.00

SAR 10g (W/Kg)	2.359411
SAR 1g (W/Kg)	5.688704

Z Axis Scan





System Performance Check Data(2600MHz Body)

Type: Phone measurement (Complete)


Area scan resolution: dx=8mm,dy=8mm

Zoom scan resolution: dx=8mm, dy=8mm, dz=5mm

Date of measurement: 2019-08-20

Experimental conditions.




Device Position	Validation plane
Band	2600 MHz
Channels	-
Signal	CW
Frequency (MHz)	2600
Relative permittivity	52.49
Conductivity (S/m)	2.13
Power drift (%)	-0.30
Probe	SN 45/15 EPGO281
ConvF	2.38
Crest factor:	1:1



Maximum location: X=3.00, Y=1.00

SAR 10g (W/Kg)	2.346564
SAR 1g (W/Kg)	5.512880

Z Axis Scan





System Performance Check Data(5200MHz Head)

Type: Dipole measurement (Complete)


Area scan resolution: dx=8mm,dy=8mm

Zoom scan resolution: dx=4mm, dy=4mm, dz=2mm

Date of measurement: 2019-08-12

Experimental conditions.


Device Position	Validation plane
Band	5200 MHz
Channels	-
Signal	CW
Frequency (MHz)	5200
Relative permittivity	34.73
Conductivity (S/m)	4.63
Power drift (%)	4.14
Probe	SN 45/15 EPGO281
ConvF	2.46
Crest factor:	1:1



Maximum location: X=7.00, Y=2.00

SAR 10g (W/Kg)	5.724125
SAR 1g (W/Kg)	15.870438

Z Axis Scan



**System Performance Check Data(5400MHz Head)**

Type: Dipole measurement (Complete)


Area scan resolution: dx=8mm,dy=8mm

Zoom scan resolution: dx=4mm, dy=4mm, dz=2mm

Date of measurement: 2019-08-12


Experimental conditions.

Device Position	Validation plane
Band	5400 MHz
Channels	-
Signal	CW
Frequency (MHz)	5400
Relative permittivity	36.47
Conductivity (S/m)	4.86
Power drift (%)	-1.77
Probe	SN 45/15 EPGO281
ConvF	2.70
Crest factor:	1:1

**Maximum location: X=7.00, Y=2.00**

SAR 10g (W/Kg)	5.830216
SAR 1g (W/Kg)	16.894975

Z Axis Scan



**System Performance Check Data(5600MHz Head)**

Type: Dipole measurement (Complete)


Area scan resolution: dx=8mm,dy=8mm

Zoom scan resolution: dx=4mm, dy=4mm, dz=2mm

Date of measurement: 2019-08-12


Experimental conditions.

Device Position	Validation plane
Band	5600 MHz
Channels	-
Signal	CW
Frequency (MHz)	5600
Relative permittivity	36.10
Conductivity (S/m)	5.11
Power drift (%)	1.86
Probe	SN 45/15 EPGO281
ConvF	2.74
Crest factor:	1:1

**Maximum location: X=7.00, Y=2.00**

SAR 10g (W/Kg)	6.022689
SAR 1g (W/Kg)	17.319624

Z Axis Scan



Appendix B. SAR Test Plots


Plot 1: DUT: Smartphone; EUT Model: QX1000

Test Date	2019-08-14
Probe	SN 45/15 EPGO281
ConvF	1.78
Area Scan	dx=8mm dy=8mm, h= 5.00 mm
ZoomScan	5x5x7,dx=8mm dy=8mm dz=5mm, Complete/ndx=8mm dy=8mm, h= 5.00 mm
Phantom	Left head
Device Position	Cheek
Band	GSM850
Channels	Middle
Signal	TDMA (Crest factor: 8.32)
Frequency (MHz)	836.6
Relative permittivity (real part)	41.50
Conductivity (S/m)	0.90
Variation (%)	2.2.6

Maximum location: X=-10.00, Y=9.00

SAR Peak: 0.23 W/kg

SAR 10g (W/Kg)	0.047344
SAR 1g (W/Kg)	0.115535




Plot 2: DUT: Smartphone; EUT Model: QX1000

Test Date	2019-08-14
Probe	SN 45/15 EPGO281
ConvF	1.85
Area Scan	dx=8mm dy=8mm, h= 5.00 mm
ZoomScan	5x5x7,dx=8mm dy=8mm dz=5mm, Complete/ndx=8mm dy=8mm, h= 5.00 mm
Phantom	Validation plane
Device Position	Body back
Band	GPRS 850
Channels	High
Signal	Duty Cycle: 2.00 (Crest factor: 2.0)
Frequency (MHz)	848.8
Relative permittivity (real part)	55.20
Conductivity (S/m)	0.97
Variation (%)	-0.03

Maximum location: X=22.00, Y=-2.00

SAR Peak: 0.11 W/kg

SAR 10g (W/Kg)	0.020247
SAR 1g (W/Kg)	0.054076




Plot 3: DUT: Smartphone; EUT Model: QX1000

Test Date	2019-08-16
Probe	SN 45/15 EPGO281
ConvF	2.10
Area Scan	dx=8mm dy=8mm, h= 5.00 mm
ZoomScan	5x5x7,dx=8mm dy=8mm dz=5mm, Complete/ndx=8mm dy=8mm, h= 5.00 mm
Phantom	Left head
Device Position	Cheek
Band	GSM1900
Channels	Low
Signal	TDMA (Crest factor: 8.32)
Frequency (MHz)	1850.2
Relative permittivity (real part)	40.00
Conductivity (S/m)	1.40
Variation (%)	2.91

Maximum location: X=-8.00, Y=10.00

SAR Peak: 0.17 W/kg

SAR 10g (W/Kg)	0.028850
SAR 1g (W/Kg)	0.083780




Plot 4: DUT: Smartphone; EUT Model: QX1000

Test Date	2019-08-16
Probe	SN 45/15 EPGO281
ConvF	2.16
Area Scan	dx=8mm dy=8mm, h= 5.00 mm
ZoomScan	5x5x7, dx=8mm dy=8mm dz=5mm, Complete/ndx=8mm dy=8mm, h= 5.00 mm
Phantom	Validation plane
Device Position	Body back
Band	GPRS 1900
Channels	High
Signal	Duty Cycle: 1:2.00 (Crest factor: 2.0)
Frequency (MHz)	1909.8
Relative permittivity (real part)	53.30
Conductivity (S/m)	1.52
Variation (%)	2.15

Maximum location: X=6.00, Y=18.00

SAR Peak: 0.36 W/kg

SAR 10g (W/Kg)	0.060582
SAR 1g (W/Kg)	0.170932




Plot 5: DUT: Smartphone; EUT Model: QX1000

Test Date	2019-08-16
Probe	SN 45/15 EPGO281
ConvF	2.10
Area Scan	dx=8mm dy=8mm, h= 5.00 mm
ZoomScan	5x5x7, dx=8mm dy=8mm dz=5mm, Complete/ndx=8mm dy=8mm, h= 5.00 mm
Phantom	Left head
Device Position	Cheek
Band	WCDMA II
Channels	Middle
Signal	WCDMA (Crest factor: 1.0)
Frequency (MHz)	1880.0
Relative permittivity (real part)	40.00
Conductivity (S/m)	1.40
Variation (%)	-1.73

Maximum location: X=-7.00, Y=8.00

SAR Peak: 0.39 W/kg

SAR 10g (W/Kg)	0.086528
SAR 1g (W/Kg)	0.209135




Plot 6: DUT: Smartphone; EUT Model: QX1000

Test Date	2019-08-16
Probe	SN 45/15 EPGO281
ConvF	2.16
Area Scan	dx=8mm dy=8mm, h= 5.00 mm
ZoomScan	5x5x7, dx=8mm dy=8mm dz=5mm, Complete/ndx=8mm dy=8mm, h= 5.00 mm
Phantom	Validation plane
Device Position	Body Top side
Band	WCDMA II
Channels	Middle
Signal	WCDMA (Crest factor: 1.0)
Frequency (MHz)	1880.0
Relative permittivity (real part)	53.30
Conductivity (S/m)	1.52
Variation (%)	-2.08

Maximum location: X=10.00, Y=0.00

SAR Peak: 0.27 W/kg

SAR 10g (W/Kg)	0.079546
SAR 1g (W/Kg)	0.165399




Plot 7: DUT: Smartphone; EUT Model: QX1000

Test Date	2019-08-16
Probe	SN 45/15 EPGO281
ConvF	1.83
Area Scan	dx=8mm dy=8mm, h= 5.00 mm
ZoomScan	5x5x7, dx=8mm dy=8mm dz=5mm, Complete/ndx=8mm dy=8mm, h= 5.00 mm
Phantom	Left head
Device Position	Cheek
Band	WCDMA IV
Channels	Middle
Signal	WCDMA (Crest factor: 1.0)
Frequency (MHz)	1740.0
Relative permittivity (real part)	40.00
Conductivity (S/m)	1.40
Variation (%)	-1.38

Maximum location: X=-7.00, Y=8.00

SAR Peak: 0.36 W/kg

SAR 10g (W/Kg)	0.062854
SAR 1g (W/Kg)	0.175044




Plot 8: DUT: Smartphone; EUT Model: QX1000

Test Date	2019-08-16
Probe	SN 45/15 EPGO281
ConvF	1.87
Area Scan	dx=8mm dy=8mm, h= 5.00 mm
ZoomScan	5x5x7,dx=8mm dy=8mm dz=5mm, Complete/ndx=8mm dy=8mm, h= 5.00 mm
Phantom	Validation plane
Device Position	Body back side
Band	WCDMA IV
Channels	Middle
Signal	WCDMA (Crest factor: 1.0)
Frequency (MHz)	1740.0
Relative permittivity (real part)	53.30
Conductivity (S/m)	1.52
Variation (%)	1.50

Maximum location: X=18.00, Y=8.00

SAR Peak: 0.11 W/kg

SAR 10g (W/Kg)	0.019070
SAR 1g (W/Kg)	0.048158







Plot 9: DUT: Smartphone; EUT Model: QX1000

Test Date	2019-08-14
Probe	SN 45/15 EPGO281
ConvF	1.78
Area Scan	dx=8mm dy=8mm, h= 5.00 mm
ZoomScan	5x5x7, dx=8mm dy=8mm dz=5mm, Complete/ndx=8mm dy=8mm, h= 5.00 mm
Phantom	Left head
Device Position	Cheek
Band	WCDMA V
Channels	High
Signal	WCDMA (Crest factor: 1.0)
Frequency (MHz)	846.6
Relative permittivity (real part)	41.50
Conductivity (S/m)	0.90
Variation (%)	3.94

Maximum location: X=-18.00, Y=-8.00

SAR Peak: 0.06 W/kg

SAR 10g (W/Kg)	0.006544
SAR 1g (W/Kg)	0.022355

SURFACE SAR

VOLUME SAR

3D screen shot

Z Axis Scan



Plot 10: DUT: Smartphone; EUT Model: QX1000

Test Date	2019-08-14
Probe	SN 45/15 EPGO281
ConvF	1.85
Area Scan	dx=8mm dy=8mm, h= 5.00 mm
ZoomScan	5x5x7,dx=8mm dy=8mm dz=5mm, Complete/ndx=8mm dy=8mm, h= 5.00 mm
Phantom	Validation plane
Device Position	Body back
Band	WCDMA V
Channels	High
Signal	WCDMA (Crest factor: 1.0)
Frequency (MHz)	846.6
Relative permittivity (real part)	55.20
Conductivity (S/m)	0.97
Variation (%)	-0.67

Maximum location: X=-8.00, Y=7.00

SAR Peak: 0.22 W/kg

SAR 10g (W/Kg)	0.036095
SAR 1g (W/Kg)	0.105017




Plot 11: DUT: Smartphone; EUT Model: QX1000

Test Date	2019-08-16
Probe	SN 45/15 EPGO281
ConvF	2.10
Area Scan	dx=8mm dy=8mm, h= 5.00 mm
ZoomScan	5x5x7,dx=8mm dy=8mm dz=5mm, Complete/ndx=8mm dy=8mm, h= 5.00 mm
Phantom	Left head
Device Position	Cheek
Band	LTE Band 2 (RB 1)
Channels	High
Signal	LTE (Crest factor: 1.0)
Frequency (MHz)	1900
Relative permittivity (real part)	40.00
Conductivity (S/m)	1.40
Variation (%)	-1.45

Maximum location: X=-7.00, Y=5.00

SAR Peak: 0.28 W/kg

SAR 10g (W/Kg)	0.071634
SAR 1g (W/Kg)	0.158719




Plot 12: DUT: Smartphone; EUT Model: QX1000

Test Date	2019-08-16
Probe	SN 45/15 EPGO281
ConvF	2.16
Area Scan	dx=8mm dy=8mm, h= 5.00 mm
ZoomScan	5x5x7,dx=8mm dy=8mm dz=5mm, Complete/ndx=8mm dy=8mm, h= 5.00 mm
Phantom	Validation plane
Device Position	Body back
Band	LTE Band 2(RB 1)
Channels	High
Signal	LTE (Crest factor: 1.0)
Frequency (MHz)	1900
Relative permittivity (real part)	53.30
Conductivity (S/m)	1.52
Variation (%)	-1.94

Maximum location: X=-21.00, Y=-9.00

SAR Peak: 0.52 W/kg

SAR 10g (W/Kg)	0.151253
SAR 1g (W/Kg)	0.297038




Plot 13: DUT: Smartphone; EUT Model: QX1000

Test Date	2019-08-15
Probe	SN 45/15 EPGO281
ConvF	1.83
Area Scan	dx=8mm dy=8mm, h= 5.00 mm
ZoomScan	5x5x7,dx=8mm dy=8mm dz=5mm, Complete/ndx=8mm dy=8mm, h= 5.00 mm
Phantom	Left head
Device Position	Cheek
Band	LTE Band 4 (RB 1)
Channels	Low
Signal	LTE (Crest factor: 1.0)
Frequency (MHz)	1720
Relative permittivity (real part)	40.00
Conductivity (S/m)	1.40
Variation (%)	-0.07

Maximum location: X=-9.00, Y=-7.00

SAR Peak: 0.82 W/kg

SAR 10g (W/Kg)	0.111748
SAR 1g (W/Kg)	0.333313




Plot 14: DUT: Smartphone; EUT Model: QX1000

Test Date	2019-08-15
Probe	SN 45/15 EPGO281
ConvF	1.87
Area Scan	dx=8mm dy=8mm, h= 5.00 mm
ZoomScan	5x5x7, dx=8mm dy=8mm dz=5mm, Complete/ndx=8mm dy=8mm, h= 5.00 mm
Phantom	Validation plane
Device Position	Body back
Band	LTE Band 4 (RB 1)
Channels	Low
Signal	LTE (Crest factor: 1.0)
Frequency (MHz)	1720
Relative permittivity (real part)	53.30
Conductivity (S/m)	1.52
Variation (%)	0.77

Maximum location: X=-15.00, Y=-16.00

SAR Peak: 0.34 W/kg

SAR 10g (W/Kg)	0.093559
SAR 1g (W/Kg)	0.182141




Plot 15: DUT: Smartphone; EUT Model: QX1000

Test Date	2019-08-14
Probe	SN 45/15 EPGO281
ConvF	1.78
Area Scan	dx=8mm dy=8mm, h= 5.00 mm
ZoomScan	5x5x7,dx=8mm dy=8mm dz=5mm, Complete/ndx=8mm dy=8mm, h= 5.00 mm
Phantom	Left head
Device Position	Cheek
Band	LTE Band 5 (RB 1)
Channels	High
Signal	LTE (Crest factor: 1.0)
Frequency (MHz)	844
Relative permittivity (real part)	41.5
Conductivity (S/m)	0.90
Variation (%)	-3.97

Maximum location: X=-10.00, Y=11.00

SAR Peak: 0.25 W/kg

SAR 10g (W/Kg)	0.111748
SAR 1g (W/Kg)	0.333313




Plot 16: DUT: Smartphone; EUT Model: QX1000

Test Date	2019-08-14
Probe	SN 45/15 EPGO281
ConvF	1.85
Area Scan	dx=8mm dy=8mm, h= 5.00 mm
ZoomScan	5x5x7,dx=8mm dy=8mm dz=5mm, Complete/ndx=8mm dy=8mm, h= 5.00 mm
Phantom	Validation plane
Device Position	Body back
Band	LTE Band 5 (RB 1)
Channels	High
Signal	LTE (Crest factor: 1.0)
Frequency (MHz)	844
Relative permittivity (real part)	55.20
Conductivity (S/m)	0.97
Variation (%)	3.33

Maximum location: X=2.00, Y=-8.00

SAR Peak: 0.11 W/kg

SAR 10g (W/Kg)	0.029748
SAR 1g (W/Kg)	0.065000




Plot 17: DUT: Smartphone; EUT Model: QX1000

Test Date	2019-08-20
Probe	SN 45/15 EPGO281
ConvF	2.32
Area Scan	dx=8mm dy=8mm, h= 5.00 mm
ZoomScan	5x5x7,dx=8mm dy=8mm dz=5mm, Complete/ndx=8mm dy=8mm, h= 5.00 mm
Phantom	Left head
Device Position	Cheek
Band	LTE Band 7 (RB 1)
Channels	Middle
Signal	LTE (Crest factor: 1.0)
Frequency (MHz)	2535
Relative permittivity (real part)	39.0
Conductivity (S/m)	1.96
Variation (%)	-1.89

Maximum location: X=-34.00, Y=14.00

SAR Peak: 0.32 W/kg

SAR 10g (W/Kg)	0.058970
SAR 1g (W/Kg)	0.157166




Plot 18: DUT: Smartphone; EUT Model: QX1000

Test Date	2019-08-20
Probe	SN 45/15 EPGO281
ConvF	2.38
Area Scan	dx=8mm dy=8mm, h= 5.00 mm
ZoomScan	5x5x7,dx=8mm dy=8mm dz=5mm, Complete/ndx=8mm dy=8mm, h= 5.00 mm
Phantom	Validation plane
Device Position	Body back
Band	LTE Band 7 (RB 1)
Channels	Middle
Signal	LTE (Crest factor: 1.0)
Frequency (MHz)	2535
Relative permittivity (real part)	52.50
Conductivity (S/m)	2.16
Variation (%)	-3.60

Maximum location: X=-15.00, Y=0.00

SAR Peak: 0.41 W/kg

SAR 10g (W/Kg)	0.017255
SAR 1g (W/Kg)	0.106706




Plot 19: DUT: Smartphone; EUT Model: QX1000

Test Date	2019-08-13
Probe	SN 45/15 EPGO281
ConvF	1.53
Area Scan	dx=8mm dy=8mm, h= 5.00 mm
ZoomScan	5x5x7,dx=8mm dy=8mm dz=5mm, Complete/ndx=8mm dy=8mm, h= 5.00 mm
Phantom	Left head
Device Position	Cheek
Band	LTE Band 12 (RB 1)
Channels	Middle
Signal	LTE (Crest factor: 1.0)
Frequency (MHz)	707.5
Relative permittivity (real part)	41.90
Conductivity (S/m)	0.89
Variation (%)	0.78

Maximum location: X=-8.00, Y=15.00

SAR Peak: 0.19 W/kg

SAR 10g (W/Kg)	0.033876
SAR 1g (W/Kg)	0.087460





Plot 20: DUT: Smartphone; EUT Model: QX1000

Test Date	2019-08-13
Probe	SN 45/15 EPGO281
ConvF	1.59
Area Scan	dx=8mm dy=8mm, h= 5.00 mm
ZoomScan	5x5x7,dx=8mm dy=8mm dz=5mm, Complete/ndx=8mm dy=8mm, h= 5.00 mm
Phantom	Validation plane
Device Position	Body back
Band	LTE Band 12 (RB 1)
Channels	Middle
Signal	LTE (Crest factor: 1.0)
Frequency (MHz)	707.5
Relative permittivity (real part)	55.50
Conductivity (S/m)	0.96
Variation (%)	1.05

Maximum location: X=9.00, Y=-8.00

SAR Peak: 0.37 W/kg

SAR 10g (W/Kg)	0.126974
SAR 1g (W/Kg)	0.237397




Plot 21: DUT: Smartphone; EUT Model: QX1000

Test Date	2019-08-13
Probe	SN 45/15 EPGO281
ConvF	1.53
Area Scan	dx=8mm dy=8mm, h= 5.00 mm
ZoomScan	5x5x7,dx=8mm dy=8mm dz=5mm, Complete/ndx=8mm dy=8mm, h= 5.00 mm
Phantom	Left head
Device Position	Cheek
Band	LTE Band 13 (RB 1)
Channels	Middle
Signal	LTE (Crest factor: 1.0)
Frequency (MHz)	782
Relative permittivity (real part)	41.90
Conductivity (S/m)	0.89
Variation (%)	-2.49

Maximum location: X=-8.00, Y=14.00

SAR Peak: 0.20 W/kg

SAR 10g (W/Kg)	0.032913
SAR 1g (W/Kg)	0.085669





Plot 22: DUT: Smartphone; EUT Model: QX1000

Test Date	2019-08-13
Probe	SN 45/15 EPGO281
ConvF	1.59
Area Scan	dx=8mm dy=8mm, h= 5.00 mm
ZoomScan	5x5x7,dx=8mm dy=8mm dz=5mm, Complete/ndx=8mm dy=8mm, h= 5.00 mm
Phantom	Validation plane
Device Position	Body back
Band	LTE Band 13 (RB 1)
Channels	Middle
Signal	LTE (Crest factor: 1.0)
Frequency (MHz)	782
Relative permittivity (real part)	55.50
Conductivity (S/m)	0.96
Variation (%)	2.34

Maximum location: X=16.00, Y=-40.00

SAR Peak: 0.22 W/kg

SAR 10g (W/Kg)	0.070439
SAR 1g (W/Kg)	0.132362




Plot 23: DUT: Smartphone; EUT Model: QX1000

Test Date	2019-08-13
Probe	SN 45/15 EPGO281
ConvF	1.53
Area Scan	dx=8mm dy=8mm, h= 5.00 mm
ZoomScan	5x5x7,dx=8mm dy=8mm dz=5mm, Complete/ndx=8mm dy=8mm, h= 5.00 mm
Phantom	Left head
Device Position	Cheek
Band	LTE Band 17 (RB 1)
Channels	Low
Signal	LTE (Crest factor: 1.0)
Frequency (MHz)	709
Relative permittivity (real part)	41.90
Conductivity (S/m)	0.89
Variation (%)	-2.80

Maximum location: X=-17.00, Y=14.00

SAR Peak: 0.15 W/kg

SAR 10g (W/Kg)	0.016718
SAR 1g (W/Kg)	0.041331




Plot 24: DUT: Smartphone; EUT Model: QX1000

Test Date	2019-08-13
Probe	SN 45/15 EPGO281
ConvF	1.59
Area Scan	dx=8mm dy=8mm, h= 5.00 mm
ZoomScan	5x5x7,dx=8mm dy=8mm dz=5mm, Complete/ndx=8mm dy=8mm, h= 5.00 mm
Phantom	Validation plane
Device Position	Body back
Band	LTE Band 17 (RB 1)
Channels	Low
Signal	LTE (Crest factor: 1.0)
Frequency (MHz)	709
Relative permittivity (real part)	55.50
Conductivity (S/m)	0.96
Variation (%)	-1.95

Maximum location: X=16.00, Y=-40.00

SAR Peak: 0.24 W/kg

SAR 10g (W/Kg)	0.053650
SAR 1g (W/Kg)	0.125745




Plot 25: DUT: Smartphone; EUT Model: QX1000

Test Date	2019-08-20
Probe	SN 45/15 EPGO281
ConvF	2.23
Area Scan	dx=8mm dy=8mm, h= 5.00 mm
ZoomScan	5x5x7,dx=8mm dy=8mm dz=5mm, Complete/ndx=8mm dy=8mm, h= 5.00 mm
Phantom	Left head
Device Position	Cheek
Band	LTE Band 41 (RB 1)
Channels	Low
Signal	LTE (Crest factor: 1.0)
Frequency (MHz)	2506
Relative permittivity (real part)	39.00
Conductivity (S/m)	1.96
Variation (%)	3.81

Maximum location: X=-23.00, Y=23.00

SAR Peak: 0.08 W/kg

SAR 10g (W/Kg)	0.005453
SAR 1g (W/Kg)	0.022893





Plot 26: DUT: Smartphone; EUT Model: QX1000

Test Date	2019-08-20
Probe	SN 45/15 EPGO281
ConvF	2.38
Area Scan	dx=8mm dy=8mm, h= 5.00 mm
ZoomScan	5x5x7,dx=8mm dy=8mm dz=5mm, Complete/ndx=8mm dy=8mm, h= 5.00 mm
Phantom	Validation plane
Device Position	Body back
Band	LTE Band 41 (RB 1)
Channels	Low
Signal	LTE (Crest factor: 1.0)
Frequency (MHz)	2506
Relative permittivity (real part)	52.50
Conductivity (S/m)	2.16
Variation (%)	1.01

Maximum location: X=-17.00, Y=8.00

SAR Peak: 0.25 W/kg

SAR 10g (W/Kg)	0.029696
SAR 1g (W/Kg)	0.099333







Plot 27: DUT:Smartphone; EUT Model: QX1000

Test Date	2019-08-19
Probe	SN 45/15 EPGO281
ConvF	2.21
Area Scan	dx=8mm dy=8mm, h= 5.00 mm
ZoomScan	5x5x7,dx=8mm dy=8mm dz=5mm, Complete/ndx=8mm dy=8mm, h= 5.00 mm
Phantom	Right head
Device Position	Cheek
Antenna	A
Band	IEEE 802.11b ISM
Channels	High
Signal	IEEE802.b (Crest factor: 1.0)
Frequency (MHz)	2462
Relative permittivity (real part)	39.20
Conductivity (S/m)	1.80
Variation (%)	3.69

Maximum location: X=-7.00, Y=32.00

SAR Peak: 0.21 W/kg

SAR 10g (W/Kg)	0.028148
SAR 1g (W/Kg)	0.085098

SURFACE SAR

VOLUME SAR

3D

Z Axis Scan






Plot 28: DUT:Smartphone; EUT Model: QX1000

Test Date	2019-08-12
Probe	SN 45/15 EPGO281
ConvF	2.46
Area Scan	dx=8mm dy=8mm, h= 5.00 mm
ZoomScan	5x5x7, dx=8mm dy=8mm dz=5mm, Complete/ndx=8mm dy=8mm, h= 5.00 mm
Phantom	Right head
Device Position	Cheek
Antenna	A
Band	IEEE 802.11a ISM
Channels	48
Signal	IEEE802.a (Crest factor: 1.0)
Frequency (MHz)	5240
Relative permittivity (real part)	36
Conductivity (S/m)	4.66
Variation (%)	3.45

Maximum location: X=-10.00, Y=17.00

SAR Peak: 0.53 W/kg

SAR 10g (W/Kg)	0.074007
SAR 1g (W/Kg)	0.187702

SURFACE SAR

VOLUME SAR

3D

Z Axis Scan






Plot 29: DUT:Smartphone; EUT Model: QX1000

Test Date	2019-08-12
Probe	SN 45/15 EPGO281
ConvF	2.46
Area Scan	dx=8mm dy=8mm, h= 5.00 mm
ZoomScan	5x5x7,dx=8mm dy=8mm dz=5mm, Complete/ndx=8mm dy=8mm, h= 5.00 mm
Phantom	Left head
Device Position	Cheek
Antenna	A+B
Band	IEEE 802.11ac ISM
Channels	48
Signal	IEEE802.ac (Crest factor: 1.0)
Frequency (MHz)	5240
Relative permittivity (real part)	36
Conductivity (S/m)	4.66
Variation (%)	0.40

Maximum location: X=16.00, Y=0.00

SAR Peak: 0.64 W/kg

SAR 10g (W/Kg)	0.118306
SAR 1g (W/Kg)	0.285766

SURFACE SAR

VOLUME SAR

3D

Z Axis Scan






Plot 30: DUT:Smartphone; EUT Model: QX1000

Test Date	2019-08-12
Probe	SN 45/15 EPGO281
ConvF	2.70
Area Scan	dx=8mm dy=8mm, h= 5.00 mm
ZoomScan	5x5x7,dx=8mm dy=8mm dz=5mm, Complete/ndx=8mm dy=8mm, h= 5.00 mm
Phantom	Left head
Device Position	Cheek
Antenna	A
Band	IEEE 802.11a ISM
Channels	60
Signal	IEEE802.a (Crest factor: 1.0)
Frequency (MHz)	5300
Relative permittivity (real part)	35.8
Conductivity (S/m)	4.86
Variation (%)	1.63

Maximum location: X=15.00, Y=-8.00

SAR Peak: 0.57 W/kg

SAR 10g (W/Kg)	0.066318
SAR 1g (W/Kg)	0.182541

SURFACE SAR

VOLUME SAR

3D

Z Axis Scan






Plot 31: DUT:Smartphone; EUT Model: QX1000

Test Date	2019-08-12
Probe	SN 45/15 EPGO281
ConvF	2.70
Area Scan	dx=8mm dy=8mm, h= 5.00 mm
ZoomScan	5x5x7,dx=8mm dy=8mm dz=5mm, Complete/ndx=8mm dy=8mm, h= 5.00 mm
Phantom	Left head
Device Position	Cheek
Antenna	A+B
Band	IEEE 802.11n ISM
Channels	64
Signal	IEEE802.n (Crest factor: 1.0)
Frequency (MHz)	5320
Relative permittivity (real part)	35.8
Conductivity (S/m)	4.86
Variation (%)	0.82

Maximum location: X=16.00, Y=1.00

SAR Peak: 0.52 W/kg

SAR 10g (W/Kg)	0.098722
SAR 1g (W/Kg)	0.231586

SURFACE SAR

VOLUME SAR

3D

Z Axis Scan






Plot 32: DUT:Smartphone; EUT Model: QX1000

Test Date	2019-08-12
Probe	SN 45/15 EPGO281
ConvF	2.74
Area Scan	dx=8mm dy=8mm, h= 5.00 mm
ZoomScan	5x5x7,dx=8mm dy=8mm dz=5mm, Complete/ndx=8mm dy=8mm, h= 5.00 mm
Phantom	Left head
Device Position	Cheek
Antenna	A
Band	IEEE 802.11a ISM
Channels	100
Signal	IEEE802.a (Crest factor: 1.0)
Frequency (MHz)	5500
Relative permittivity (real part)	35.5
Conductivity (S/m)	5.07
Variation (%)	-1.61

Maximum location: X=15.00, Y=-8.00

SAR Peak: 0.70 W/kg

SAR 10g (W/Kg)	0.065217
SAR 1g (W/Kg)	0.183719

SURFACE SAR

VOLUME SAR

3D

Z Axis Scan






Plot 33: DUT:Smartphone; EUT Model: QX1000

Test Date	2019-08-12
Probe	SN 45/15 EPGO281
ConvF	2.74
Area Scan	dx=8mm dy=8mm, h= 5.00 mm
ZoomScan	5x5x7,dx=8mm dy=8mm dz=5mm, Complete/ndx=8mm dy=8mm, h= 5.00 mm
Phantom	Left head
Device Position	Cheek
Antenna	A+B
Band	IEEE 802.11n ISM
Channels	100
Signal	IEEE802.n (Crest factor: 1.0)
Frequency (MHz)	5500
Relative permittivity (real part)	35.5
Conductivity (S/m)	5.07
Variation (%)	2.55

Maximum location: X=16.00, Y=-7.00

SAR Peak: 0.75 W/kg

SAR 10g (W/Kg)	0.103672
SAR 1g (W/Kg)	0.260158

SURFACE SAR

VOLUME SAR

3D

Z Axis Scan




Appendix C. Probe Calibration And Dipole Calibration Report

Refer the appendix Calibration Report.

*****END OF THE REPORT*****

