FCC TEST REPORT

According to
CFR47 § 15.247

Applicant :	Guangzhou Shizhen Information Technology Co., Ltd.
Address :	5 Floors,192 Kezhu Road,Guangzhou Economic & Technology Development District, Guangzhou,Guangdong 510530 ,China
Equipment :	Speakerphone
Model No. :	BM21, BMXX(XX=A-Z,a-z or blank)
Trademark :	N/A
FCC ID :	2AUCW-BM21

I HEREBY CERTIFY THAT :

The sample was received on Jun. 08, 2020 and the testing was completed on Jun. 16, 2020 at Cerpass Technology (Suzhou) Co., Ltd. The test result refers exclusively to the test presented test model / sample. Without written approval of Cerpass Technology (Suzhou) Co., Ltd., the test report shall not be reproduced except in full.

Approved by:

Miro Chueh
EMC/RF Manager

Laboratory Accreditation:
Cerpass Technology Corporation Test Laboratory

☐ **TAF LAB Code: 1439**

Cerpass Technology (SuZhou) Co., Ltd.

☒ **A2LA LAB Code: 4981.01**

Contents

1. Report of Measurements and Examinations 5
1.1 List of Measurements and Examinations 5
2. Test Configuration of Equipment under Test 6
2.1 Feature of Equipment under Test 6
2.2 Carrier Frequency of Channels 6
2.3 Test Mode & Test Software 7
2.4 Description of Test System 7
2.5 General Information of Test 8
2.6 Measurement Uncertainty 9
3. Test Equipment and Ancillaries Used for Tests 10
4. Antenna Requirements 11
4.1 Standard Applicable 11
4.2 Antenna Construction and Directional Gain 11
5. Test of Conducted Emission 12
5.1 Test Limit 12
5.2 Test Procedures 12
5.3 Typical Test Setup 13
5.4 Test Result and Data 14
6. Test of Radiated Emission 16
6.1 Test Limit 16
6.2 Test Procedures 17
6.3 Typical Test Setup 18
7. 20dB Bandwidth Measurement Data 33
7.1 Test Limit 33
7.2 Test Procedures 33
7.3 Test Setup Layout 33
7.4 Test Result and Data 33
8. Frequencies Separation 39
8.1 Test Limit 39
8.2 Test Procedures 39
8.3 Test Setup Layout 39
8.4 Test Result and Data 39
9. Dwell Time on each channel 42
9.1 Test Limit 42
9.2 Test Procedures 42
9.3 Test Setup Layout 42
9.4 Test Result and Data 43
10. Number of Hopping Channels 49
10.1 Test Limit 49
10.2 Test Procedures 49
10.3 Test Setup Layout 49
10.4 Test Result and Data 49

11. Maximum Peak Output Power 52
11.1 Test Limit 52
11.2 Test Procedures 52
11.3 Test Setup Layout 52
11.4 Test Result and Data 52
12. Band Edges Measurement 58
12.1 Test Limit 58
12.2 Test Procedure 58
12.3 Test Setup Layout 58
12.4 Test Result and Data 59
12.5 Restrict band emission Measurement Data 64
13. Restricted Bands of Operation 76

History of this test report

☐ Original

■ Additional attachment as following record:

Attachment No.	Issue Date	Description
SEFB2006035	Jun. 16, 2020	Initial Issue

Report Type		Description
■	Original report	NA
☐	Derivative Report	NA

1. Report of Measurements and Examinations

1.1 List of Measurements and Examinations

ANSI C63.10: 2013
KDB 558074 D01 DTS Meas Guidance v05r02
FCC Rules and Regulations Part 15 Subpart C §15.247

FCC Rule	. Description of Test	Result
§ 15.203	. Antenna Requirement	Pass
§ 15.207(a)	. Conducted Emission	Pass
§ 15.209(a)	. Radiated Emission	Pass
§ 15.247(a)(1)	. Channel Carrier Frequencies Separation	Pass
§ 15.247(a)(1)	. 20dB Bandwidth Measurement	Pass
§ 15.247(a)(1)	. Dwell Time	Pass
§ 15.247(b)	. Number of Hopping Channels	Pass
§ 15.247(b)	. Peak Output Power Measurement Data	Pass
§ 15.247(d)	. Band Edges Measurement Data	Pass

2. Test Configuration of Equipment under Test

2.1 Feature of Equipment under Test

Equipment	Bluetooth Speaker
Model Name	BM21,BMXX(XX=A-Z,a-z or blank)
Model Discrepancy	All models are electrically identical, different model names are for marketing purpose.
Frequency Range	2402~2480MHz
Number of Channels	79
Modulation	GFSK (1Mbps), Π/4 DQPSK (2Mbps) ,8DPSK(3Mbps)
Data Rates	Bluetooth: 1, 2, 3Mbps
Antenna Type	PCB Antenna / 3dBi
Power Source	Input: 5Vdc, 2A
	Rechargeable Li-ion Battery Model: ICR18650-2S Spec: 7.4V, 2200mAh, 16.28Wh

Note: for more details, please refer to the User's manual of the EUT.

2.2 Carrier Frequency of Channels

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
00	2402	20	2422	40	2442	60	2462
01	2403	21	2423	41	2443	61	2463
02	2404	22	2424	42	2444	62	2464
03	2405	23	2425	43	2445	63	2465
04	2406	24	2426	44	2446	64	2466
05	2407	25	2427	45	2447	65	2467
06	2408	26	2428	46	2448	66	2468
07	2409	27	2429	47	2449	67	2469
08	2410	28	2430	48	2450	68	2470
09	2411	29	2431	49	2451	69	2471
10	2412	30	2432	50	2452	70	2472
11	2413	31	2433	51	2453	71	2473
12	2414	32	2434	52	2454	72	2474
13	2415	33	2435	53	2455	73	2475
14	2416	34	2436	54	2456	74	2476
15	2417	35	2437	55	2457	75	2477
16	2418	36	2438	56	2458	76	2478
17	2419	37	2439	57	2459	77	2479
18	2420	38	2440	58	2460	78	2480
19	2421	39	2441	59	2461	---	---

2.3 Test Mode & Test Software

a. During testing, the interface cables and equipment positions were varied according to ANSI C63.10

b. The complete test system included support units and EUT for RF test.

c. Run the test software "SecureCRT. exe".

d. The following test mode was performed for conduction and radiation test:

Test Mode 1: GFSK: CH 00: 2402MHz, CH 39: 2441MHz, CH 78: 2480MHz.

Test Mode 2: π/4 DQPSK：CH 00: 2402MHz, CH 39: 2441MHz, CH 78: 2480MHz.

Test Mode 3: 8DPSK：CH 00: 2402MHz, CH 39: 2441MHz, CH 78: 2480MHz.

2.4 Description of Test System

Device	Manufacturer	Model No.	Description
Notebook	Sony	PCG-71811P	R33021

Used cable

Cable	Quantity	Description
Type-C Cable	1	1.0m Non Shielding

2.5 General Information of Test

☐	Test Site	**Cerpass Technology Corporation Test Laboratory** Address: No.10, Ln. 2, Lianfu St., Luzhu Dist., Taoyuan City 33848, Taiwan (R.O.C.) Tel:+886-3-3226-888 Fax:+886-3-3226-881
	TAF	1439
	FCC	TW1079, TW1061
	IC	4934E-1, 4934E-2
	VCCI	T-2205 for Telecommunication Test C-4663 for Conducted emission test R-4399, R-4218 for Radiated emission test G-812, G-813 for radiated disturbance above 1GHz
☒	Test Site	Cerpass Technology (Suzhou) Co.,Ltd Address: No.66,Tangzhuang Road, Suzhou Industrial Park, Jiangsu 215006, China Tel: +86-512-6917-5888 Fax: +86-512-6917-5666
	CNAS	L5515
	FCC	CN1243
	A2LA	4981.01
	IC	7290A
	VCCI	T-11945 for Telecommunication Test C-12919 for Conducted emission test R-12670 for Radiated emission test G-10227 for radiated disturbance above 1GHz

2.6 Measurement Uncertainty

ISO/IEC 17025 requires that an estimate of the measurement uncertainties associated with the emissions test results be included in the report. The measurement uncertainties given below are based on a 95% confidence level (based on a coverage factor (k=2).

RF Conducted Measurement

Test Item		Uncertainty	Limit
Radio Frequency		±8.7X10^{-7}	±1X10^{-5}
RF output power, conducted		±0.63dB	±1.5dB
Power density, conducted		±1.21dB	±3dB
Unwanted emissions, conducted	30-1000MHz	±0.51dB	±3dB
	1-12.75GHz	±0.67dB	±3dB
All emissions, radiated	30-1000MHz	±2.28dB	±6dB
	1-12.75GHz	±2.59dB	±6dB
Temperature		±0.8℃	±1℃
Humidity		±3%	±5%
DC and low frequency voltages		±3%	±3%

AC Conducted Measurement

Measurement	Frequency	Uncertainty
Conducted emissions(LINE)	9KHz-30MHz	+/- 0.7738 dB
Conducted emissions(NEUTRAL)	9KHz-30MHz	+/- 0.7886 dB
Conducted emissions(10Mbps)	150KHz-30MHz	+/- 1.3013dB
Conducted emissions(100Mbps)	150KHz-30MHz	+/- 1.3197 dB
Conducted emissions(1000Mbps)	150KHz-30MHz	+/- 1.2987 dB

Radiated Measurement

Measurement	Polarity	Frequency	Uncertainty
Radiated emissions	Horizontal	below 1GHz	+/- 3.8936 dB
	Vertical	below 1GHz	+/- 3.8928 dB
	Horizontal	above 1GHz	+/- 5.18858dB
	Vertical	above 1GHz	+/- 5.18928 dB

3. Test Equipment and Ancillaries Used for Tests

Instrument/Ancillary	Manufacturer	Model No.	Serial No.	Calibration Date	Valid Date.
EMI Receiver	R&S	ESCI3	100563	2019.06.21	2020.06.20
LISN	Schwarzbeck	NSLK 8127	8127-920	2019.09.25	2020.09.24
Pulse Limiter	R&S	ESH3-Z2	100529	2020.03.11	2021.03.10
Software	Farad	Ez-EMC	ver.ct3a1	N/A	N/A

Instrument/Ancillary	Manufacturer	Model No.	Serial No.	Calibration Date	Valid Date.
Bilog Antenna	Sunol	JB1	A072414-2-2	2019.07.13	2020.07.13
EMI Receiver	R&S	ESCI3	101183	2019.06.28	2020.06.27
EMI Receiver	R&S	ESCI7	100968	2019.07.28	2020.07.27
Preamplifier	EM Electronics corp.	EM330	60618	2020.03.11	2021.03.10
Horn Antenna	Schwarzbeck	BBHA9120 D	9120D-619	2019.07.13	2020.07.13
Horn Antenna	Schwarzbeck	BBHA9170	9170-348	2019.06.23	2020.06.22
Spectrum Analyzer	R&S	FSP40	100324	2019.07.13	2020.07.12
Preamplifier	EMCI	EMCI 030-00-3230	SN016723	2020.03.11	2021.03.10
Preamplifier	EM Electronics corp.	EM01G18G	SN060714	2020.03.23	2021.03.22
Spectrum Analyzer	KEYSIGHT	N9010A	MY53400169	2019.08.25	2020.08.24
Software	E3	AUDIX	Version: 8.14.806b	N/A	N/A

4. Antenna Requirements

4.1 Standard Applicable

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

4.2 Antenna Construction and Directional Gain

Antenna	Peak Gain
PCB Antenna	3dBi

5. Test of Conducted Emission

5.1 Test Limit

Conducted Emissions were measured from 150 kHz to 30 MHz with a bandwidth of 9 KHz on the 120 VAC power and return leads of the EUT according to the methods defined in ANSI C63.10-2013. The EUT was placed on a nonmetallic stand in a shielded room 0.8 meters above the ground plane as shown in section 6.2.2. The interface cables and equipment positioning were varied within limits of reasonable applications to determine the position produced maximum conducted emissions

Frequency (MHz)	Quasi Peak (dB μ V)	Average (dB μ V)
0.15 – 0.5	66-56*	56-46*
0.5 – 5.0	56	46
5.0 – 30.0	60	50

*Decreases with the logarithm of the frequency.

5.2 Test Procedures

a. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
b. Connect EUT to the power mains through a line impedance stabilization network (LISN).
c. All the support units are connecting to the other LISN.
d. The LISN provides 50 ohm coupling impedance for the measuring instrument.
e. The FCC states that a 50 ohm, 50 micro-Henry LISN should be used.
f. Both sides of AC line were checked for maximum conducted interference.
g. The frequency range from 150 kHz to 30 MHz was searched.
h. Set the test-receiver system to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.

5.3 Typical Test Setup



5.4 Test Result and Data

Power:	AC 120V/60Hz	Pol/Phase:	LINE
Test Mode:	Mode 1		



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.1620	10.06	26.33	36.39	65.36	-28.97	QP
2	0.1620	10.06	18.88	28.94	55.36	-26.42	AVG
3	0.3020	10.00	27.48	37.48	60.19	-22.71	QP
4	0.3020	10.00	18.90	28.90	50.19	-21.29	AVG
5	0.4180	9.94	28.74	38.68	57.49	-18.81	QP
6	0.4180	9.94	17.45	27.39	47.49	-20.10	AVG
7	0.5940	9.97	23.22	33.19	56.00	-22.81	QP
8	0.5940	9.97	16.08	26.05	46.00	-19.95	AVG
9	1.0980	10.22	24.07	34.29	56.00	-21.71	QP
10	1.0980	10.22	16.11	26.33	46.00	-19.67	AVG
11	2.1540	11.02	28.29	39.31	56.00	-16.69	QP
12	2.1540	11.02	17.30	28.32	46.00	-17.68	AVG

Note: Level = Reading + Factor

Margin = Level – Limit

Power:	AC 120V/60Hz	Pol/Phase:	NEUTRAL
Test Mode:	Mode 1		



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.4140	9.94	32.35	42.29	57.57	-15.28	QP
2	0.4140	9.94	18.33	28.27	47.57	-19.30	AVG
3	0.9180	10.11	30.53	40.64	56.00	-15.36	QP
4	0.9180	10.11	17.63	27.74	46.00	-18.26	AVG
5	1.2540	10.14	31.05	41.19	56.00	-14.81	QP
6	1.2540	10.14	18.16	28.30	46.00	-17.70	AVG
7	2.2139	10.17	31.30	41.47	56.00	-14.53	QP
8	2.2139	10.17	18.71	28.88	46.00	-17.12	AVG
9	4.3020	10.23	28.24	38.47	56.00	-17.53	QP
10	4.3020	10.23	16.71	26.94	46.00	-19.06	AVG
11	17.6259	10.46	26.45	36.91	60.00	-23.09	QP
12	17.6259	10.46	17.96	28.42	50.00	-21.58	AVG

Note: Level = Reading + Factor

Margin = Level – Limit

6. Test of Radiated Emission

6.1 Test Limit

In any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. If the transmitter measurement is based on the maximum conducted output power, the attenuation required under this paragraph shall be 30dB instead of 20dB. In addition, radiated emissions which fall in section 15.205(a) the restricted bands must also comply with the radiated emission limit specified in section 15.209(a).

FREQUENCIES(MHz)	FIELD STRENGTH(microvolts/meter)	MEASUREMENT DISTANCE(meters)
0.009~0.490	2400/F(kHz)	300
0.490~1.705	24000/F(kHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

For unintentional device, according to CISPR PUB.22, for Class B digital devices, the general requirement of field strength of radiated emissions from intentional radiators at a distance of 10 meters shall not exceed the above table.

Frequency (MHz)	Distance Meters	Radiated (dB μ V/ M)
30-230	10	30
230-1000	10	37

6.2 Test Procedures

a. The EUT was placed on a rotatable table top 0.8 meter above ground; above 1GHz, the height was 1.5m.

b. The EUT was set 3 meters from the interference receiving antenna which was mounted on the top of a variable height antenna tower.

c. The table was rotated 360 degrees to determine the position of the highest radiation.

d. The antenna is a broadband antenna and its height is varied between one meter and four meters above ground to find the maximum value of the field strength both horizontal polarization and vertical polarization of the antenna are set to make the measurement.

e. For each suspected emission the EUT was arranged to its worst case and then tune the antenna tower (from 1 M to 4 M) and turn table (from 0 degree to 360 degrees) to find the maximum reading.

f. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function and specified bandwidth with Maximum Hold Mode.

g. If the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method and reported.

h. For testing above 1GHz, the emission level of the EUT in peak mode was 20dB lower than average limit (that means the emission level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.

6.3 Typical Test Setup

Below 30MHz test setup



30MHz- 1GHz Test Setup



Above 1GHz Test Setup



6.3.1 Test Result and Data

Below 1GHz

Power	AC 120V/60Hz	Pol/Phase	VERTICAL
Test Mode	Mode 1		

Note : Level = Reading + Factor
Margin = Level – Limit
Factor = Antenna Factor + Cable Loss – Amplifier Factor
The 9KHz -30MHz spurious emission is under limit 20dB more



No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (deg)
1	76.5600	-16.03	46.07	30.04	40.00	-9.96	peak	100	247
2	185.1999	-11.43	42.67	31.24	43.50	-12.26	peak	100	204
3	335.5500	-5.78	39.71	33.93	46.00	-12.07	peak	100	15
4	359.8000	-5.87	42.91	37.04	46.00	-8.96	peak	100	147
5	455.8299	-4.03	37.45	33.42	46.00	-12.58	peak	100	144
6	600.3600	-1.92	33.43	31.51	46.00	-14.49	peak	100	104

Power	AC 120V/60Hz	Pol/Phase	HORIZONTAL
Test Mode	Mode 1		

Note : Level = Reading + Factor
Margin = Level – Limit
Factor = Antenna Factor + Cable Loss – Amplifier Factor
The 9KHz -30MHz spurious emission is under limit 20dB more



No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (deg)
1	95.9599	-12.44	42.36	29.92	43.50	-13.58	peak	100	123
2	184.2298	-9.97	44.69	34.72	43.50	-8.78	peak	100	141
3	323.9100	-7.32	40.82	33.50	46.00	-12.50	peak	100	214
4	359.8000	-5.87	43.64	37.77	46.00	-8.23	peak	100	41
5	414.1200	-6.09	41.02	34.93	46.00	-11.07	peak	100	25
6	480.0799	-1.92	36.19	34.27	46.00	-11.73	peak	100	174

Above 1GHz

Power	DC 3.7V	Pol/Phase	VERTICAL
Test Mode	Mode 1, CH 00	Operation mode	TX

Note : Level = Reading + Factor
Margin = Level – Limit
Factor = Antenna Factor + Cable Loss – Amplifier Factor
The 18000MHz - 25000MHz spurious emission is under limit 20dB more.



No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.
1	2133.333	-11.16	54.27	43.11	74.00	-30.89	peak
2	3408.333	-4.08	44.59	40.51	74.00	-33.49	peak
3	4804.021	1.23	42.16	43.39	74.00	-30.61	peak
4	5420.000	1.95	38.87	40.82	74.00	-33.18	peak
5	6553.333	3.63	37.83	41.46	74.00	-32.54	peak
6	7206.012	5.88	38.82	44.70	74.00	-29.30	peak

Power	DC 3.7V	Pol/Phase	HORIZONTAL
Test Mode	Mode 1, CH 00	Operation mode	TX

Note : Level = Reading + Factor
Margin = Level – Limit
Factor = Antenna Factor + Cable Loss – Amplifier Factor
The 18000MHz - 25000MHz spurious emission is under limit 20dB more.



No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.
1	2133.333	-11.16	53.55	42.39	74.00	-31.61	peak
2	3578.333	-3.33	43.75	40.42	74.00	-33.58	peak
3	4804.012	1.23	39.99	41.22	74.00	-32.78	peak
4	5561.667	2.17	38.61	40.78	74.00	-33.22	peak
5	6241.667	3.36	37.48	40.84	74.00	-33.16	peak
6	7206.520	5.89	36.75	42.64	74.00	-31.36	peak

Power	DC 3.7V	Pol/Phase	VERTICAL
Test Mode	Mode 1, CH 39	Operation mode	TX

Note : Level = Reading + Factor
Margin = Level – Limit
Factor = Antenna Factor + Cable Loss – Amplifier Factor
The 18000MHz - 25000MHz spurious emission is under limit 20dB more.



No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.
1	2133.333	-11.16	55.95	44.79	74.00	-29.21	peak
2	3578.333	-3.33	43.27	39.94	74.00	-34.06	peak
3	4882.063	1.38	39.24	40.62	74.00	-33.38	peak
4	5590.000	2.24	38.24	40.48	74.00	-33.52	peak
5	6666.667	4.00	38.16	42.16	74.00	-31.84	peak
6	7323.063	6.34	36.92	43.26	74.00	-30.74	peak

Power	DC 3.7V	Pol/Phase	HORIZONTAL
Test Mode	Mode 1, CH 39	Operation mode	TX

Note : Level = Reading + Factor
Margin = Level – Limit
Factor = Antenna Factor + Cable Loss – Amplifier Factor
The 18000MHz - 25000MHz spurious emission is under limit 20dB more.



No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.
1	3295.000	-4.68	45.08	40.40	74.00	-33.60	peak
2	4882.054	1.38	39.42	40.80	74.00	-33.20	peak
3	5618.333	2.31	38.78	41.09	74.00	-32.91	peak
4	6241.667	3.36	38.36	41.72	74.00	-32.28	peak
5	7176.667	5.77	37.01	42.78	74.00	-31.22	peak
6	7323.015	6.34	36.88	43.22	74.00	-30.78	peak

Power	DC 3.7V	Pol/Phase	VERTICAL
Test Mode	Mode 1, CH 78	Operation mode	TX

Note : Level = Reading + Factor
Margin = Level – Limit
Factor = Antenna Factor + Cable Loss – Amplifier Factor
The 18000MHz - 25000MHz spurious emission is under limit 20dB more.



No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.
1	3578.333	-3.33	43.54	40.21	74.00	-33.79	peak
2	4230.000	-0.72	41.14	40.42	74.00	-33.58	peak
3	4960.120	1.53	39.30	40.83	74.00	-33.17	peak
4	5760.000	2.66	38.80	41.46	74.00	-32.54	peak
5	6836.667	4.55	36.87	41.42	74.00	-32.58	peak
6	7440.063	6.80	36.81	43.61	74.00	-30.39	peak

Power	DC 3.7V	Pol/Phase	HORIZONTAL
Test Mode	Mode 1, CH 78	Operation mode	TX

Note : Level = Reading + Factor
Margin = Level – Limit
Factor = Antenna Factor + Cable Loss – Amplifier Factor
The 18000MHz - 25000MHz spurious emission is under limit 20dB more.



No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.
1	2133.333	-11.16	53.71	42.55	74.00	-31.45	peak
2	3578.333	-3.33	43.25	39.92	74.00	-34.08	peak
3	4960.154	1.53	39.03	40.56	74.00	-33.44	peak
4	5703.333	2.52	39.35	41.87	74.00	-32.13	peak
5	6666.667	4.00	38.17	42.17	74.00	-31.83	peak
6	7440.363	6.80	36.72	43.52	74.00	-30.48	peak

Power	DC 3.7V	Pol/Phase	VERTICAL
Test Mode	Mode 3, CH 00	Operation mode	TX

Note : Level = Reading + Factor
Margin = Level – Limit
Factor = Antenna Factor + Cable Loss – Amplifier Factor
The 18000MHz - 25000MHz spurious emission is under limit 20dB more.



No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.
1	2133.333	-11.16	53.30	42.14	74.00	-31.86	peak
2	3210.000	-5.13	48.25	43.12	74.00	-30.88	peak
3	4804.044	1.23	39.56	40.79	74.00	-33.21	peak
4	5618.333	2.31	39.34	41.65	74.00	-32.35	peak
5	7206.034	5.88	36.75	42.63	74.00	-31.37	peak
6	8168.333	7.73	35.16	42.89	74.00	-31.11	peak

s

Power	DC 3.7V	Pol/Phase	HORIZONTAL
Test Mode	Mode 3, CH 00	Operation mode	TX

Note : Level = Reading + Factor
Margin = Level – Limit
Factor = Antenna Factor + Cable Loss – Amplifier Factor
The 18000MHz - 25000MHz spurious emission is under limit 20dB more.



No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.
1	2133.333	-11.16	55.34	44.18	74.00	-29.82	peak
2	3210.000	-5.13	45.46	40.33	74.00	-33.67	peak
3	4804.120	1.23	40.30	41.53	74.00	-32.47	peak
4	6100.000	3.30	37.78	41.08	74.00	-32.92	peak
5	6666.667	4.00	38.68	42.68	74.00	-31.32	peak
6	7206.036	5.88	38.89	44.77	74.00	-29.23	peak

Power	DC 3.7V	Pol/Phase	VERTICAL
Test Mode	Mode 3, CH 39	Operation mode	TX

Note : Level = Reading + Factor
Margin = Level – Limit
Factor = Antenna Factor + Cable Loss – Amplifier Factor
The 18000MHz - 25000MHz spurious emission is under limit 20dB more.



No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.
1	2133.333	-11.16	53.67	42.51	74.00	-31.49	peak
2	3011.667	-6.17	47.27	41.10	74.00	-32.90	peak
3	4882.036	1.38	43.49	44.87	74.00	-29.13	peak
4	5391.667	1.93	38.47	40.40	74.00	-33.60	peak
5	6071.667	3.29	37.96	41.25	74.00	-32.75	peak
6	7323.063	6.34	37.55	43.89	74.00	-30.11	peak

Power	DC 3.7V	Pol/Phase	HORIZONTAL
Test Mode	Mode 3, CH 39	Operation mode	TX

Note : Level = Reading + Factor
Margin = Level – Limit
Factor = Antenna Factor + Cable Loss – Amplifier Factor
The 18000MHz - 25000MHz spurious emission is under limit 20dB more.



No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.
1	2133.333	-11.16	54.10	42.94	74.00	-31.06	peak
2	3465.000	-3.78	43.97	40.19	74.00	-33.81	peak
3	4882.015	1.38	39.75	41.13	74.00	-32.87	peak
4	5760.000	2.66	38.37	41.03	74.00	-32.97	peak
5	6610.000	3.82	37.26	41.08	74.00	-32.92	peak
6	7323.036	6.34	36.53	42.87	74.00	-31.13	peak

Power	DC 3.7V	Pol/Phase	VERTICAL
Test Mode	Mode 3, CH 78		

Note : Level = Reading + Factor
Margin = Level – Limit
Factor = Antenna Factor + Cable Loss – Amplifier Factor
The 18000MHz - 25000MHz spurious emission is under limit 20dB more.



No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.
1	2133.333	-11.16	54.56	43.40	74.00	-30.60	peak
2	3351.667	-4.38	44.76	40.38	74.00	-33.62	peak
3	4960.036	1.52	39.62	41.14	74.00	-32.86	peak
4	5590.000	2.24	38.04	40.28	74.00	-33.72	peak
5	6298.333	3.38	38.87	42.25	74.00	-31.75	peak
6	7440.054	6.80	35.69	42.49	74.00	-31.51	peak

Power	DC 3.7V	Pol/Phase	HORIZONTAL
Test Mode	Mode 3, CH 78	Operation mode	TX

Note : Level = Reading + Factor
Margin = Level – Limit
Factor = Antenna Factor + Cable Loss – Amplifier Factor
The 18000MHz - 25000MHz spurious emission is under limit 20dB more.



No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.
1	ss	-11.16	51.11	39.95	74.00	-34.05	peak
2	3578.333	-3.33	43.57	40.24	74.00	-33.76	peak
3	4960.015	1.52	39.90	41.42	74.00	-32.58	peak
4	5278.333	1.83	38.68	40.51	74.00	-33.49	peak
5	6015.000	3.27	37.43	40.70	74.00	-33.30	peak
6	7440.063	6.80	35.93	42.73	74.00	-31.27	peak

7. 20dB Bandwidth Measurement Data

7.1 Test Limit

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400–2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than125 mW.

7.2 Test Procedures

a. The transmitter output was connected to the spectrum analyzer.

b. Set RBW of spectrum analyzer to 30 KHz and VBW to 100 KHz.

c. The 20 dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 20 dB.

7.3 Test Setup Layout



7.4 Test Result and Data

Modulation Type	Channel	Frequency (MHz)	20dB Bandwidth (MHz)	2/3 20dB Bandwidth(KHz)
GFSK (1Mbps)	00	2402	0.694	463
	39	2441	0.692	461
	78	2480	0.694	463
π/4-DQPSK (2Mbps)	00	2402	1.218	812
	39	2441	1.217	811
	78	2480	1.218	812
8DPSK (3Mbps)	00	2402	1.216	811
	39	2441	1.216	811
	78	2480	1.217	811
Note	2/3*20dB Bandwidth=20dB Bandwidth x 2/3			

Modulation Standard: GFSK (1Mbps)
Channel: 00



Modulation Standard: GFSK (1Mbps)
Channel: 39



Modulation Standard: GFSK (1Mbps)
Channel: 78



Modulation Standard: π/4 DQPSK (2Mbps)
Channel: 00



Modulation Standard: π /4 DQPSK (2Mbps)
Channel: 39



Modulation Standard: π /4 DQPSK (2Mbps)
Channel: 78



Modulation Standard: 8DPSK (3Mbps)
Channel: 00



Modulation Standard: 8DPSK (3Mbps)
Channel: 39



Modulation Standard: 8DPSK (3Mbps)
Channel: 78



8. Frequencies Separation

8.1 Test Limit

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater.

8.2 Test Procedures

a. The transmitter output was connected to the spectrum analyzer.
b. Set RBW of spectrum analyzer to 30 KHz and VBW to 100 KHz.
c. By using the MaxHold function record the separation of two adjacent channels.
d. Measure the frequency difference of these two adjacent channels.

8.3 Test Setup Layout



8.4 Test Result and Data

1M

Frequency (MHz)	Channel Separation (MHz)	Limit (MHz)	2/3 of 20dB Bandwidth (MHz)
2402	1.000	≥ 2/3 of 20dB Bandwidth	0.463
2441	1.000	≥ 2/3 of 20dB Bandwidth	0.461
2480	1.000	≥ 2/3 of 20dB Bandwidth	0.463

2M

Frequency (MHz)	Channel Separation (MHz)	Limit (MHz)	2/3 of 20dB Bandwidth (MHz)
2402	1.000	≥ 2/3 of 20dB Bandwidth	0.812
2441	1.000	≥ 2/3 of 20dB Bandwidth	0.811
2480	1.000	≥ 2/3 of 20dB Bandwidth	0.812

3M

Frequency (MHz)	Channel Separation (MHz)	Limit (MHz)	2/3 of 20dB Bandwidth (MHz)
2402	1.000	≥ 2/3 of 20dB Bandwidth	0.811
2441	1.000	≥ 2/3 of 20dB Bandwidth	0.811
2480	1.000	≥ 2/3 of 20dB Bandwidth	0.811

Modulation Standard: GFSK (1Mbps)



Modulation Standard: π/4 DQPSK (2Mbps)



Modulation Standard:8DPSK (3Mbps)



9. Dwell Time on each channel

9.1 Test Limit

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

9.2 Test Procedures

1. The transmitter output was connected to the spectrum analyzer.
2. Adjust the center frequency to measure frequency, then set zero span mode.
2. Set RBW of spectrum analyzer to 1 MHz and VBW to 1 MHz.
4. Measure the time duration of one transmission on the measured frequency.

9.3 Test Setup Layout



9.4 Test Result and Data

Test Period = 0.4 (second/ channel) x 79 Channel = 31.6 sec

Modulation Standard: GFSK(1Mbps)

DH 1

Pulse Time (ms)	Total of Dwell (ms)	Period Time (s)	Limit (ms)	Result
0.37	118.4	31.6	400	PASS

Remark:Total of Dwell =pulse Time*(1600/2)/79*Period Time

DH 3

Pulse Time (ms)	Total of Dwell (ms)	Period Time (s)	Limit (ms)	Result
1.632	261.12	31.6	400	PASS

Remark:Total of Dwell =pulse Time*(1600/4)/79*Period Time

DH 5

Pulse Time (ms)	Total of Dwell (ms)	Period Time (s)	Limit (ms)	Result
2.885	307.73	31.6	400	PASS

Remark:Total of Dwell =pulse Time*(1600/6)/79*Period Time

Modulation Standard: π/4 DQPSK(2Mbps)

DH 1

Pulse Time (ms)	Total of Dwell (ms)	Period Time (s)	Limit (ms)	Result
0.386	123.52	31.6	400	PASS

Remark:Total of Dwell =pulse Time*(1600/2)/79*Period Time

DH 3

Pulse Time (ms)	Total of Dwell (ms)	Period Time (s)	Limit (ms)	Result
1.644	263.04	31.6	400	PASS

Remark:Total of Dwell =pulse Time*(1600/4)/79*Period Time

DH 5

Pulse Time (ms)	Total of Dwell (ms)	Period Time (s)	Limit (ms)	Result
2.895	308.80	31.6	400	PASS

Remark:Total of Dwell =pulse Time*(1600/6)/79*Period Time

Modulation Standard: 8DPSK(3Mbps)

DH 1

Pulse Time (ms)	Total of Dwell (ms)	Period Time (s)	Limit (ms)	Result
0.388	124.16	31.6	400	PASS

Remark:Total of Dwell =pulse Time*(1600/2)/79*Period Time

DH 3

Pulse Time (ms)	Total of Dwell (ms)	Period Time (s)	Limit (ms)	Result
1.641	262.56	31.6	400	PASS

Remark:Total of Dwell =pulse Time*(1600/4)/79*Period Time

DH 5

Pulse Time (ms)	Total of Dwell (ms)	Period Time (s)	Limit (ms)	Result
2.9	309.33	31.6	400	PASS

Remark:Total of Dwell =pulse Time*(1600/6)/79*Period Time

Modulation Standard: GFSK (1Mbps)
DH1



Modulation Standard: GFSK (1Mbps)
DH3



Modulation Standard: GFSK (1Mbps)
DH5



Modulation Standard: π /4-DQPSK(2Mbps)
DH1



Modulation Standard: π /4-DQPSK(2Mbps)
DH3



Modulation Standard: π /4-DQPSK(2Mbps)
DH5



Modulation Standard: 8DPSK(3Mbps)
DH1



Modulation Standard: 8DPSK(3Mbps)
DH3



Modulation Standard: 8DPSK(3Mbps)
DH5



Test Period = 0.4 (second/ channel) x 20 Channel = 8 sec

Modulation Type	Frequency (MHz)	Length of transmission time (ms)	Number of transmission in a 8 (20 Hopping*0.4)	Dwell Time (ms)	Limit (ms)
AFH (DH1)	2402-2421	0.378	160	60.48	400
AFH (DH3)	2402-2421	1.641	80	131.28	400
AFH (DH5)	2402-2421	2.890	53.33	154.124	400

Modulation Type: AFH (DH1)



Modulation Type: AFH (DH3)



Modulation Type: AFH (DH5)



10. Number of Hopping Channels

10.1 Test Limit

Frequency hopping systems in the 2400 ~ 2483.5 MHz band shall use at least 15 channels.

10.2 Test Procedures

a. The transmitter output was connected to the spectrum analyzer.

b. 2. Set RBW of spectrum analyzer to 300 KHz and VBW to 300 KHz.

c. 3. Set the MaxHold function, and then keep the EUT in hopping mode. Record all the signals from each channel until each one has been record.

10.3 Test Setup Layout



10.4 Test Result and Data

Modulation Standard: GFSK (1Mbps)

Number of hopping channels:	79	Channels

Modulation Standard: π/4 DQPSK (2Mbps)

Number of hopping channels:	79	Channels

Modulation Standard: 8DPSK (3Mbps)

Number of hopping channels:	79	Channels

Modulation Standard: GFSK (1Mbps)



Modulation Standard: π/4 DQPSK (2Mbps)



Modulation Standard: 8DPSK (3Mbps)



11. Maximum Peak Output Power

11.1 Test Limit

The Maximum Peak Output Power Measurement is 21dBm.

11.2 Test Procedures

The antenna port(RF output)of the EUT was connected to the input(RF input)of a power meter. Power was read directly from the meter and cable loss connection was added to the reading to obtain power at the EUT antenna terminal. The EUT Output Power was set to maximum to produce the worse case test result.

11.3 Test Setup Layout



11.4 Test Result and Data

Modulation Type	Channel	Frequency (MHz)	Peak Power Output (dBm)	Peak Power Output (mW)
GFSK (1Mbps)	00	2402	6.666	4.641
	39	2441	4.734	2.974
	78	2480	4.270	2.673
π /4 DQPSK (2Mbps)	00	2402	7.265	5.327
	39	2441	6.273	4.239
	78	2480	5.628	3.654
8DPSK (3Mbps)	00	2402	7.364	5.450
	39	2441	6.306	4.272
	78	2480	4.562	2.859

Modulation Standard: GFSK (1Mbps)
Channel: 00



Modulation Standard: GFSK (1Mbps)
Channel: 39



Modulation Standard: GFSK (1Mbps)
Channel: 78



Modulation Standard: π/4 DQPSK (2Mbps)
Channel: 00



Modulation Standard: π/4 DQPSK (2Mbps)
Channel: 39



Modulation Standard: π/4 DQPSK (2Mbps)
Channel: 78



Modulation Standard: 8DPSK (3Mbps)
Channel: 00



Modulation Standard: 8DPSK (3Mbps)
Channel: 39



Modulation Standard: 8DPSK (3Mbps)S
Channel: 78



12. Band Edges Measurement

12.1 Test Limit

Below –20dB of the highest emission level of operating band (in 100kHz Resolution Bandwidth).

12.2 Test Procedure

a. The transmitter output was connected to the spectrum analyzer via a low lose cable.
b. Set both RBW and VBW of spectrum analyzer to 100 KHz with convenient frequency span including 100 KHz bandwidth from band edge.
c. The band edges was measured and recorded.

12.3 Test Setup Layout



12.4 Test Result and Data

Single test

Modulation Standard: GFSK (1Mbps)

Channel: 00





Modulation Standard: GFSK (1Mbps)

Channel: 39





Modulation Standard: GFSK (1Mbps)

Channel: 78





Modulation Standard: π/4 DQPSK (2Mbps)
Channel: 00





Modulation Standard: π/4 DQPSK (2Mbps)
Channel: 39





Modulation Standard: π/4 DQPSK (2Mbps)
Channel: 78





Modulation Standard: 8DPSK (3Mbps)
Channel: 00





Modulation Standard: 8DPSK (3Mbps)
Channel: 39





Modulation Standard: 8DPSK (3Mbps)
Channel: 78





Hopping test

Modulation Standard: GFSK (1Mbps)



Modulation Standard: GFSK (1Mbps)



Modulation Standard: GFSK (1Mbps)



Modulation Standard: π/4 DQPSK (2Mbps)

Channel: 39



Modulation Standard: π/4 DQPSK (2Mbps)

Channel: 78



Modulation Standard: 8DPSK (3Mbps)



Modulation Standard: 8DPSK (3Mbps)



Modulation Standard: 8DPSK (3Mbps)



12.5 Restrict band emission Measurement Data

Power	DC 3.7V	Pol/Phase	VERTICAL
Test Mode	GFSK, CH00		

Note : Level = Reading + Factor
Margin = Level – Limit



No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.
1	2390.000	-10.05	48.17	38.12	74.00	-35.88	peak
2	2390.000	-10.05	35.07	25.02	54.00	-28.98	AVG

Power	DC 3.7V	Pol/Phase	HORIZONTAL
Test Mode	GFSK, CH00		

Note : Level = Reading + Factor
Margin = Level – Limit



No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.
1	2390.000	-10.05	46.29	36.24	74.00	-37.76	peak
2	2390.000	-10.05	34.11	24.06	54.00	-29.94	AVG

Power	DC 3.7V	Pol/Phase	VERTICAL
Test Mode	GFSK, CH78		

Note : Level = Reading + Factor
Margin = Level – Limit



No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.
1	2483.500	-9.65	47.07	37.42	74.00	-36.58	peak
2	2483.500	-9.65	33.67	24.02	54.00	-29.98	AVG

Power	DC 3.7V	Pol/Phase	HORIZONTAL
Test Mode	GFSK, CH78		

Note : Level = Reading + Factor
Margin = Level – Limit



No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.
1	2483.500	-9.65	47.06	37.41	74.00	-36.59	peak
2	2483.500	-9.65	33.33	23.68	54.00	-30.32	AVG

Power	DC 3.7V	Pol/Phase	VERTICAL
Test Mode	π /4-DQPSK , CH00		

Note : Level = Reading + Factor
Margin = Level – Limit



No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.
1	2390.000	-10.05	48.47	38.42	74.00	-35.58	peak
2	2390.000	-10.05	34.07	24.02	54.00	-29.98	AVG

Power	DC 3.7V	Pol/Phase	HORIZONTAL
Test Mode	π /4-DQPSK , CH00		

Note : Level = Reading + Factor
Margin = Level – Limit



No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.
1	2390.000	-10.05	47.82	37.77	74.00	-36.23	peak
2	2390.000	-10.05	33.68	23.63	54.00	-30.37	AVG

Power	DC 3.7V	Pol/Phase	VERTICAL
Test Mode	π /4-DQPSK , CH78		

Note : Level = Reading + Factor
Margin = Level – Limit



No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.
1	2483.500	-9.65	47.04	37.39	74.00	-36.61	peak
2	2483.500	-9.65	33.09	23.44	54.00	-30.56	AVG

Power	DC 3.7V	Pol/Phase	HORIZONTAL
Test Mode	π /4-DQPSK , CH78		

Note : Level = Reading + Factor
Margin = Level – Limit



No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.
1	2483.500	-9.65	46.78	37.13	74.00	-36.87	peak
2	2483.500	-9.65	33.28	23.63	54.00	-30.37	AVG

Power	DC 3.7V	Pol/Phase	VERTICAL
Test Mode	8DPSK, CH00		

Note : Level = Reading + Factor
Margin = Level – Limit



No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.
1	2390.000	-10.05	47.12	37.07	74.00	-36.93	peak
2	2390.000	-10.05	33.57	23.52	54.00	-30.48	AVG

Power	DC 3.7V	Pol/Phase	HORIZONTAL
Test Mode	8DPSK, CH00		

Note : Level = Reading + Factor
Margin = Level – Limit



No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.
1	2390.000	-10.05	46.93	36.88	74.00	-37.12	peak
2	2390.000	-10.05	33.12	23.07	54.00	-30.93	AVG

Power	DC 3.7V	Pol/Phase	VERTICAL
Test Mode	8DPSK , CH78		

Note : Level = Reading + Factor
Margin = Level – Limit



No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.
1	2483.500	-9.65	47.10	37.45	74.00	-36.55	peak
2	2483.500	-9.65	33.69	24.04	54.00	-29.96	AVG

Power	DC 3.7V	Pol/Phase	HORIZONTAL
Test Mode	8DPSK, CH78		

Note : Level = Reading + Factor
Margin = Level – Limit



No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.
1	2483.500	-9.65	47.41	37.76	74.00	-36.24	peak
2	2483.500	-9.65	33.19	23.54	54.00	-30.46	AVG

13. Restricted Bands of Operation

Only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.09000 – 0.11000	16.42000 – 16.42300	399.9 – 410.0	4.500 – 5.250
0.49500 – 0.505**	16.69475 – 16.69525	608.0 – 614.0	5.350 – 5.460
2.17350 – 2.19050	16.80425 – 16.80475	960.0 – 1240.0	7.250 – 7.750
4.12500 – 4.12800	25.50000 – 25.67000	1300.0 – 1427.0	8.025 – 8.500
4.17725 – 4.17775	37.50000 – 38.25000	1435.0 – 1626.5	9.000 – 9.200
4.20725 – 4.20775	73.00000 – 74.60000	1645.5 – 1646.5	9.300 – 9.500
6.21500 – 6.21800	74.80000 – 75.20000	1660.0 – 1710.0	10.600 – 12.700
6.26775 – 6.26825	108.00000 – 121.94000	1718.8 – 1722.2	13.250 – 13.400
6.31175 – 6.31225	123.00000 – 138.00000	2200.0 – 2300.0	14.470 – 14.500
8.29100 – 8.29400	149.90000 – 150.05000	2310.0 – 2390.0	15.350 – 16.200
8.36200 – 8.36600	156.52475 – 156.52525	2483.5 – 2500.0	17.700 – 21.400
8.37625 – 8.38675	156.70000 – 156.90000	2655.0 – 2900.0	22.010 – 23.120
8.41425 – 8.41475	162.01250 – 167.17000	3260.0 – 3267.0	23.600 – 24.000
12.29000 – 12.29300	167.72000 – 173.20000	3332.0 – 3339.0	31.200 – 31.800
12.51975 – 12.52025	240.00000 – 285.00000	3345.8 – 3358.0	36.430 – 36.500
12.57675 – 12.57725	322.00000 – 335.40000	3600.0 – 4400.0	Above 38.6
13.36000 – 13.41000			

**: Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz

---------- End of the report ----------