FCC RF Test Report

APPLICANT	:	vivo Mobile Communication Co., Ltd.
EQUIPMENT	:	Mobile Phone
BRAND NAME	:	vivo
MODEL NAME	:	V2343
FCC ID	:	2AUCY-V2343
STANDARD	:	47 CFR Part 2, 22(H), 24(E), 27(L)
CLASSIFICATION	:	PCS Licensed Transmitter Held to Ear (PCE)
TEST DATE(S)	:	Mar. 14, 2024 ~ Mar. 20, 2024

We, Sporton International Inc. (ShenZhen), would like to declare that the tested sample has been evaluated in accordance with the procedures given in ANSI C63.26-2015 and shown compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International Inc. (ShenZhen), the test report shall not be reproduced except in full.

Jason Jia

Approved by: Jason Jia

ACCREDITED
Cert #5145.01

Sporton International Inc. (ShenZhen)

1/F, 2/F, Bldg 5, Shiling Industrial Zone, Xinwei Village, Xili, Nanshan, Shenzhen, 518055

People's Republic of China

TABLE OF CONTENTS

REVISION HISTORY **3**

SUMMARY OF TEST RESULT **4**

1 GENERAL DESCRIPTION **5**

1.1 Applicant 5
1.2 Manufacturer 5
1.3 Product Feature of Equipment Under Test 5
1.4 Product Specification of Equipment Under Test 5
1.5 Modification of EUT 6
1.6 Maximum ERP/EIRP Power, and Emission Designator 7
1.7 Testing Location 7
1.8 Test Software 8
1.9 Applicable Standards 8

2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST **9**

2.1 Test Mode 9
2.2 Connection Diagram of Test System 10
2.3 Support Unit used in test configuration 10
2.4 Measurement Results Explanation Example 11
2.5 Frequency List of Low/Middle/High Channels 11

3 CONDUCTED TEST RESULT **12**

3.1 Measuring Instruments 12
3.2 Test Setup 12
3.3 Test Result of Conducted Test 12
3.4 Conducted Output Power and ERP/EIRP 13
3.5 Peak-to-Average Ratio 14
3.6 99% Occupied Bandwidth and 26dB Bandwidth Measurement 15
3.7 Conducted Band Edge 16
3.8 Conducted Spurious Emission 17
3.9 Frequency Stability 18

4 RADIATED TEST ITEMS **19**

4.1 Measuring Instruments 19
4.2 Test Setup 19
4.3 Test Result of Radiated Test 20
4.4 Field Strength of Spurious Radiation Measurement 21

5 LIST OF MEASURING EQUIPMENT **22**

6 MEASUREMENT UNCERTAINTY **23**

APPENDIX A. TEST RESULTS OF CONDUCTED TEST

APPENDIX B. TEST RESULTS OF RADIATED TEST

APPENDIX C. TEST SETUP PHOTOGRAPHS

REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FG420616A	Rev. 01	Initial issue of report	Apr. 12, 2024

SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.4	§2.1046	Conducted Output Power	-	Report Only	-
	§22.913(a)(5)	Effective Radiated Power	< 7 Watts	PASS	-
	§24.232(c)	Equivalent Isotropic Radiated Power	< 2 Watts	PASS	-
	§27.50(d)(4)	Equivalent Isotropic Radiated Power	< 1 Watts	PASS	-
3.5	§24.232(d)	Peak-to-Average Ratio	< 13 dB	PASS	-
3.6	§2.1049	Occupied Bandwidth	Reporting Only	PASS	-
3.7	§2.1051 §22.917(a) §24.238(a) §27.53(h)	Band Edge Measurement	< 43+10log10(P[Watts])	PASS	-
3.8	§2.1051 §22.917(a) §24.238(a) §27.53(h)	Conducted Emission	< 43+10log10(P[Watts])	PASS	-
3.9	§2.1055 §22.355	Frequency Stability for Temperature & Voltage	< 2.5 ppm for Part 22	PASS	-
	§2.1055 §24.235 §27.54		Within Authorized Band		
4.4	§2.1053; §22.917(a); §24.238(a); §27.53(h)	Field Strength of Spurious Radiation	< 43+10log10(P[Watts])	PASS	Under limit 35.75 dB at 1672.80 MHz

Conformity Assessment Condition:

1. The test results (PASS/FAIL) with all measurement uncertainty excluded are presented against the regulation limits or in accordance with the requirements stipulated by the applicant/manufacturer who shall bear all the risks of non-compliance that may potentially occur if measurement uncertainty is taken into account.
2. The measurement uncertainty please refer to each test result in the section “Measurement Uncertainty”

Disclaimer:

The product specifications of the EUT presented in the test report that may affect the test assessments are declared by the manufacturer who shall take full responsibility for the authenticity.

1 General Description

1.1 Applicant

vivo Mobile Communication Co., Ltd.
No.1, vivo Road, Chang'an, Dongguan, Guangdong, China

1.2 Manufacturer

vivo Mobile Communication Co., Ltd.
No.1, vivo Road, Chang'an, Dongguan, Guangdong, China

1.3 Product Feature of Equipment Under Test

Product Feature	
Equipment	Mobile Phone
Brand Name	vivo
Model Name	V2343
FCC ID	2AUCY-V2343
IMEI Code	Conducted: 864567079786631/864567079786623 Radiation: 864567079786532/864567079786524
HW Version	MP_0.1
SW Version	PD2354HF_EX_A_14.0.4.6.W30
EUT Stage	Identical Prototype

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

1.4 Product Specification of Equipment Under Test

Standards-related Product Specification	
Tx Frequency	**GSM/GPRS/EDGE:** 850: 824 MHz ~ 849 MHz 1900: 1850MHz ~ 1910MHz **WCDMA:** Band V: 824 MHz ~ 849 MHz Band II: 1850 MHz ~ 1910 MHz Band IV: 1710 MHz ~ 1755 MHz
Rx Frequency	**GSM/GPRS/EDGE:** 850: 869 MHz ~ 894 MHz 1900: 1930 MHz ~ 1990 MHz **WCDMA:** Band V: 869 MHz ~ 894 MHz Band II: 1930 MHz ~ 1990 MHz Band IV: 2110 MHz ~ 2155 MHz

Maximum Output Power to Antenna	**Ant 13:** **GSM/GPRS/EDGE:** 850: 32.92 dBm 1900: 29.86 dBm **WCDMA:** Band V: 24.40 dBm Band II: 23.91 dBm Band IV: 23.97 dBm **Ant 31:** **GSM/GPRS/EDGE:** 850: 32.95 dBm 1900: 29.91 dBm **WCDMA:** Band V: 24.39 dBm Band II: 23.95 dBm Band IV: 23.97 dBm
Antenna Type	PIFA Antenna
Antenna Gain	**Ant 13:** Cellular Band: -5.10 dBi PCS Band: -3.20 dBi AWS Band: -4.10 dBi **Ant 31:** Cellular Band: -5.90 dBi PCS Band: -0.90 dBi AWS Band: -3.00 dBi
Type of Modulation	GSM: GMSK GPRS: GMSK EDGE: GMSK / 8PSK WCDMA : BPSK HSPA : QPSK HSPA+ : 16QAM DC-HSDPA : 64QAM

Note: The maximum ERP/EIRP is calculated from max output power and max antenna gain, so only the maximum ERP/EIRP of Ant.13 for GSM850/ WDCMA Band V and Ant.31 for GSM1900/ WCDMA Band II / IV are shown in the report.

1.5 Modification of EUT

No modifications are made to the EUT during all test items.

1.6 Maximum ERP/EIRP and Emission Designator

FCC Rule	Frequency Band	Frequency Range (MHz)	Type of Modulation	Maximum ERP/EIRP(W)	Emission Designator
Part 22	GSM850 (GPRS)	824.2 ~ 848.8	GMSK	0.3690	241KGXW
Part 22	GSM850 (EDGE)	824.2 ~ 848.8	8PSK	0.0914	245KG7W
Part 22	WCDMA Band V	826.4 ~ 846.6	BPSK	0.0519	4M14F9W
Part 24	GSM1900 (GPRS)	1850.2 ~ 1909.8	GMSK	0.7962	245KGXW
Part 24	GSM1900 (EDGE)	1850.2 ~ 1909.8	8PSK	0.3243	248KG7W
Part 24	WCDMA Band II	1852.4 ~ 1907.6	BPSK	0.2018	4M15F9W
Part 27	WCDMA Band IV	1712.4 ~ 1752.6	BPSK	0.1250	4M16F9W

1.7 Testing Location

Sporton International Inc. (ShenZhen) is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.01.

Test Firm	Sporton International Inc. (ShenZhen)		
Test Site Location	1/F, 2/F, Bldg 5, Shiling Industrial Zone, Xinwei Village, Xili, Nanshan, Shenzhen, 518055 People's Republic of China TEL: +86-755-86379589 FAX: +86-755-86379595		
Test Site No.	**Sporton Site No.**	**FCC Designation No.**	**FCC Test Firm Registration No.**
	TH01-SZ	CN1256	421272

Test Firm	Sporton International Inc. (ShenZhen)		
Test Site Location	101, 1st Floor, Block B, Building 1, No. 2, Tengfeng 4th Road, Fenghuang Community, Fuyong Street, Baoan District, Shenzhen City, Guangdong Province 518103 People's Republic of China TEL: +86-755-86066985		
Test Site No.	**Sporton Site No.**	**FCC Designation No.**	**FCC Test Firm Registration No.**
	03CH01-SZ	CN1256	421272

1.8 Test Software

Item	Site	Manufacturer	Name	Version
1.	03CH01-SZ	AUDIX	E3	6.2009-8-24

1.9 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- 47 CFR Part 2, 22(H), 24(E), 27(L)
- ANSI C63.26-2015
- FCC KDB 971168 D01 Power Meas. License Digital Systems v03r01
- FCC KDB 412172 D01 Determining ERP and EIRP v01r01

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

2 Test Configuration of Equipment Under Test

2.1 Test Mode

Antenna port conducted and radiated test items were performed according to KDB 971168 D01 Power Meas. License Digital Systems v03r01 with maximum output power.

Radiated measurements were performed with rotating EUT in different three orthogonal test planes to find the maximum emission (X/Y Plane).

Radiated emissions were investigated as following frequency range:

1. 30 MHz to 9000 MHz for GSM850 and WCDMA Band V
2. 30 MHz to 18000 MHz for WCDMA Band IV.
3. 30 MHz to 19100 MHz for GSM1900 and WCDMA Band II

All modes and data rates and positions were investigated.

Test modes are chosen to be reported as the worst case configuration below:

Test Modes		
Band	**Radiated TCs**	**Conducted TCs**
GSM 850	■ GSM Link ■ EDGE 1 Tx slots Link	■ GSM Link ■ EDGE 1 Tx slots Link
GSM 1900	■ GSM Link ■ EDGE 1 Tx slots Link	■ GSM Link ■ EDGE 1 Tx slots Link
WCDMA Band V	■ RMC 12.2Kbps Link	■ RMC 12.2Kbps Link
WCDMA Band II	■ RMC 12.2Kbps Link	■ RMC 12.2Kbps Link
WCDMA Band IV	■ RMC 12.2Kbps Link	■ RMC 12.2Kbps Link

2.2 Connection Diagram of Test System



The EUT has been configuration operated in a manner tended to maximize its emission characteristics in a typical application.

2.3 Support Unit used in test configuration

Item	Equipment	Trade Name	Model No.	FCC ID	Data Cable	Power Cord
1.	System Simulator	Anritsu	MT8820C	Fcc DoC	N/A	Unshielded, 1.8 m
2.	Earphone	N/A	N/A	N/A	N/A	N/A

2.4 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between RF conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level will be exactly the RF output level.

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

The following shows an offset computation example with RF cable loss 4.0 dB and a 10dB attenuator.

Example :

Offset(dB) = RF cable loss(dB) + attenuator factor(dB).

= 4.0 + 10 = 14.0 (dB)

2.5 Frequency List of Low/Middle/High Channels

Frequency List				
Band	**Channel/Frequency(MHz)**	**Lowest**	**Middle**	**Highest**
GSM850	Channel	128	189	251
	Frequency	824.2	836.4	848.8
WCDMA Band V	Channel	4132	4182	4233
	Frequency	826.4	836.4	846.6
GSM1900	Channel	512	661	810
	Frequency	1850.2	1880.0	1909.8
WCDMA Band II	Channel	9262	9400	9538
	Frequency	1852.4	1880.0	1907.6
WCDMA Band IV	Channel	1312	1413	1513
	Frequency	1712.4	1732.6	1752.6

3 Conducted Test Result

3.1 Measuring Instruments

See list of measuring instruments of this test report.

3.2 Test Setup

3.2.1 Conducted Output Power



3.2.2 Peak-to-Average Ratio, Occupied Bandwidth, Conducted Band-Edge and Conducted Spurious Emission



3.2.3 Frequency Stability



3.3 Test Result of Conducted Test

Please refer to Appendix A.

3.4 Conducted Output Power and ERP/EIRP

3.4.1 Description of the Conducted Output Power and ERP/EIRP

A system simulator was used to establish communication with the EUT. Its parameters were set to enforce EUT transmitting at the maximum power. The measured power in the radio frequency on the transmitter output terminals shall be reported.

The ERP of mobile transmitters must not exceed 7 Watts for GSM850 and WCDMA Band V.

The EIRP of mobile transmitters must not exceed 2 Watts for GSM1900 and WCDMA Band II.

The EIRP of mobile transmitters must not exceed 1 Watts for WCDMA Band IV.

According to KDB 412172 D01 Power Approach,

EIRP = $P_T + G_T – L_C$, ERP = EIRP -2.15, where

P_T = transmitter output power in dBm

G_T = gain of the transmitting antenna in dBi

L_C = signal attenuation in the connecting cable between the transmitter and antenna in dB

3.4.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.2
2. The transmitter output port was connected to the system simulator.
3. Set EUT at maximum power through the system simulator.
4. Select lowest, middle, and highest channels for each band and different modulation.
5. Measure and record the power level from the system simulator.

3.5 Peak-to-Average Ratio

3.5.1 Description of the PAR Measurement

The peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.

3.5.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.2.3.4 (CCDF).
2. The EUT was connected to spectrum and system simulator via a power divider.
3. Set the CCDF (Complementary Cumulative Distribution Function) option in spectrum analyzer.
4. The highest RF powers were measured and recorded the maximum PAPR level associated with a probability of 0.1 %.
5. Record the deviation as Peak to Average Ratio.

3.6 99% Occupied Bandwidth and 26dB Bandwidth Measurement

3.6.1 Description of 99% Occupied Bandwidth and 26dB Bandwidth Measurement

The occupied bandwidth is the width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5% of the total mean transmitted power.

The 26 dB emission bandwidth is defined as the frequency range between two points, one above and one below the carrier frequency, at which the spectral density of the emission is attenuated 26 dB below the maximum in-band spectral density of the modulated signal. Spectral density (power per unit bandwidth) is to be measured with a detector of resolution bandwidth equal to approximately 1.0% of the emission bandwidth.

3.6.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.4
2. The EUT was connected to spectrum analyzer and system simulator via a power divider.
3. The spectrum analyzer center frequency is set to the nominal EUT channel center frequency. The span range for the spectrum analyzer shall be between two and five times the anticipated OBW.
4. The nominal resolution bandwidth (RBW) shall be in the range of 1 to 5 % of the anticipated OBW, and the VBW shall be at least 3 times the RBW.
5. Set the detection mode to peak, and the trace mode to max hold.
6. Determine the reference value: Set the EUT to transmit a modulated signal. Allow the trace to stabilize. Set the spectrum analyzer marker to the highest level of the displayed trace. (this is the reference value)
7. Determine the “-26 dB down amplitude” as equal to (Reference Value – X).
8. Place two markers, one at the lowest and the other at the highest frequency of the envelope of the spectral display such that each marker is at or slightly below the “–X dB down amplitude” determined in step 6. If a marker is below this “-X dB down amplitude” value it shall be placed as close as possible to this value. The OBW is the positive frequency difference between the two markers.
9. Use the 99 % power bandwidth function of the spectrum analyzer and report the measured bandwidth.

3.7 Conducted Band Edge

3.7.1 Description of Conducted Band Edge Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least 43 + 10 log (P) dB.

3.7.2 Test Procedures

1. The testing follows ANSI C63.26 section 5.7
2. The EUT was connected to the spectrum analyzer and system simulator via a power divider.
3. The RF output of EUT was connected to the spectrum analyzer by an RF cable and attenuator. The path loss was compensated to the results for each measurement.
4. The band edges of low and high channels for the highest RF powers were measured.
5. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
6. The limit line is derived from 43 + 10log(P) dB below the transmitter power P(Watts)

3.8 Conducted Spurious Emission

3.8.1 Description of Conducted Spurious Emission Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least 43 + 10 log (P) dB.

It is measured by means of a calibrated spectrum analyzer and scanned from 30 MHz up to a frequency including its 10th harmonic.

3.8.2 Test Procedures

1. The testing follows ANSI C63.26 section 5.7
2. The EUT was connected to the spectrum analyzer and system simulator via a power divider.
3. The RF output of EUT was connected to the spectrum analyzer by an RF cable and attenuator. The path loss was compensated to the results for each measurement.
4. The middle channel for the highest RF power within the transmitting frequency was measured.
5. The conducted spurious emission for the whole frequency range was taken.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
7. The limit line is derived from 43 + 10log(P) dB below the transmitter power P(Watts)

3.9 Frequency Stability

3.9.1 Description of Frequency Stability Measurement

The frequency stability shall be measured by variation of ambient temperature and variation of primary supply voltage to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within ±0.00025% (±2.5ppm) of the center frequency.

3.9.2 Test Procedures for Temperature Variation

1. The testing follows ANSI C63.26 section 5.6.4
2. The EUT was set up in the thermal chamber and connected with the system simulator.
3. With power OFF, the temperature was decreased to -30°C and the EUT was stabilized before testing. Power was applied and the maximum change in frequency was recorded within one minute.
4. With power OFF, the temperature was raised in 10°C step up to 50°C. The EUT was stabilized at each step for at least half an hour. Power was applied and the maximum frequency change was recorded within one minute.

3.9.3 Test Procedures for Voltage Variation

1. The testing follows ANSI C63.26 section 5.6.5
2. The EUT was placed in a temperature chamber at 20±5°C and connected with the system simulator.
3. The power supply voltage to the EUT was varied from 85% to 115% of the nominal value for other than hand carried battery equipment.
4. For hand carried, battery powered equipment, reduce the primary ac or dc supply voltage to the battery operating end point, which shall be specified by the manufacturer.
5. The variation in frequency was measured for the worst case.

4 Radiated Test Items

4.1 Measuring Instruments

See list of measuring instruments of this test report.

4.2 Test Setup

4.2.1 For radiated test below 30MHz



4.2.2 For radiated test from 30MHz to 1GHz



4.2.3 For radiated test above 1GHz



4.3 Test Result of Radiated Test

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

Please refer to Appendix B.

4.4 Field Strength of Spurious Radiation Measurement

4.4.1 Description of Field Strength of Spurious Radiated Measurement

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least 43 + 10 log (P) dB. The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.

4.4.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.5
2. The EUT was placed on a rotatable wooden table 0.8 meters for frequency below 1GHz and 1.5 meter for frequency above 1GHz above the ground.
3. The EUT was set 3 meters from the receiving antenna, which was mounted on the antenna tower.
4. The table was rotated 360 degrees to determine the position of the highest spurious emission.
5. The height of the receiving antenna is varied between one meter and four meters to search for the maximum spurious emission for both horizontal and vertical polarizations.
6. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, taking record of maximum spurious emission.
7. A horn antenna was substituted in place of the EUT and was driven by a signal generator.
8. Tune the output power of signal generator to the same emission level with EUT maximum spurious emission.
9. Taking the record of output power at antenna port.
10. Repeat step 7 to step 8 for another polarization.
11. EIRP (dBm) = S.G. Power – Tx Cable Loss + Tx Antenna Gain
12. ERP (dBm) = EIRP - 2.15
13. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
14. The limit line is derived from 43 + 10log(P) dB below the transmitter power P(Watts)

5 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSV40	101078	10Hz~40GHz	Apr. 06, 2023	Mar. 14, 2024~ Mar. 15, 2024	Apr. 05, 2024	Conducted (TH01-SZ)
DC Power Supply	TTI	PL330P	290070	Max 32V，3A	Oct. 16, 2023	Mar. 14, 2024~ Mar. 15, 2024	Oct. 15, 2024	Conducted (TH01-SZ)
Power Divider	TOJOIN	PS-2SM-04 265	60.06.020.007 7	0.4GHz~26.5GH z	Dec. 25, 2023	Mar. 14, 2024~ Mar. 15, 2024	Dec. 24, 2024	Conducted (TH01-SZ)
Thermal Chamber	Ten Billion Hongzhangroup	LP-150U	H2014081803	-40~+150°C	Jul. 05, 2023	Mar. 14, 2024~ Mar. 15, 2024	Jul. 04, 2024	Conducted (TH01-SZ)
EMI Test Receiver&SA	Agilent	N9038A	MY52260185	20Hz~26.5GHz	Dec. 27, 2023	Mar. 20, 2024	Dec. 26, 2024	Radiation (03CH01-SZ)
Loop Antenna	R&S	HFH2-Z2	100354	9kHz~30MHz	Jul. 28, 2022	Mar. 20, 2024	Jul. 27, 2024	Radiation (03CH01-SZ)
HF Amplifier	KEYSIGHT	83017A	MY53270105	0.5GHz~26.5Ghz	Oct. 18, 2023	Mar. 20, 2024	Oct. 17, 2024	Radiation (03CH01-SZ
Bilog Antenna	TeseQ	CBL6112D	35407	30MHz-2GHz	Oct. 24, 2023	Mar. 20, 2024	Oct. 23, 2025	Radiation (03CH01-SZ)
Double Ridge Horn Antenna	ETS-Lindgren	3117	00119436	1GHz~18GHz	Jul. 08, 2023	Mar. 20, 2024	Jul. 07, 2024	Radiation (03CH01-SZ)
SHF-EHF Horn	com-power	AH-840	101071	18Ghz-40GHz	Apr. 08, 2023	Mar. 20, 2024	Apr. 07, 2024	Radiation (03CH01-SZ)
LF Amplifier	Burgeon	BPA-530	102209	0.01~3000Mhz	Apr. 04, 2023	Mar. 20, 2024	Apr. 03, 2024	Radiation (03CH01-SZ)
HF Amplifier	MITEQ	AMF-7D-00 101800-30-1 0P-R	1943528	1GHz~18GHz	Oct. 18, 2023	Mar. 20, 2024	Oct. 17, 2024	Radiation (03CH01-SZ)
HF Amplifier	MITEQ	TTA1840-35 -HG	1871923	18GHz~40GHz	Jul. 07, 2023	Mar. 20, 2024	Jul. 06, 2024	Radiation (03CH01-SZ)
AC Power Source	Chroma	61601	61601000198 5	N/A	Oct. 18, 2023	Mar. 20, 2024	Oct. 17, 2024	Radiation (03CH01-SZ)
Turn Table	EM	EM1000	N/A	0~360 degree	NCR	Mar. 20, 2024	NCR	Radiation (03CH01-SZ)
Antenna Mast	EM	EM1000	N/A	1 m~4 m	NCR	Mar. 20, 2024	NCR	Radiation (03CH01-SZ)
Thermo meter	Anymetre	JR593	#2	- 10℃ ~ 50℃ 10%RH~99%RH	Apr. 12, 2023	Mar. 20, 2024	Apr. 11, 2024	Radiation (03CH01-SZ)

NCR: No Calibration Required

6 Measurement Uncertainty

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI 63.26-2015. All the measurement uncertainty value were shown with a coverage K=2 to indicate 95% level of confidence. The measurement data show herein meets or exceeds the CISPR measurement uncertainty values specified in CISPR 16-4-2 and can be compared directly to specified limit to determine compliance.

Uncertainty of Conducted Measurement

Test Item	Uncertainty
Conducted Spurious Emission & Bandedge	±1.34 dB
Occupied Channel Bandwidth	±0.012 MHz
Conducted Power	±1.34 dB
Peak to Average Ratio	±1.34 dB
Frequency Stability	±1.3 Hz

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	2.48dB

Uncertainty of Radiated Emission Measurement (1 GHz ~ 18 GHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	3.53dB

–

Uncertainty of Radiated Emission Measurement (18 GHz ~ 40 GHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	4.02dB

---------- THE END ----------

Appendix A. Test Results of Conducted Test

Test Engineer :	Hank Lin	Temperature :	24~26℃
		Relative Humidity :	50~53%

Conducted Output Power(Average power) and ERP/EIRP

GSM850_Ant.13	Burst Average Power (dBm)			ERP(W)		
TX Channel	128	189	251			
Frequency (MHz)	824.2	836.4	848.8	L	M	H
GSM 1 Tx slot	32.65	32.92	32.78	0.3467	0.3690	0.3573
GPRS 1 Tx slot	32.63	32.90	32.74	0.3451	0.3673	0.3540
GPRS 2 Tx slots	30.33	30.53	30.45	0.2032	0.2128	0.2089
GPRS 3 Tx slots	28.36	28.89	28.01	0.1291	0.1459	0.1191
GPRS 4 Tx slots	27.17	27.40	27.22	0.0982	0.1035	0.0993
EDGE 1 Tx slot	26.86	26.79	26.80	0.0914	0.0899	0.0902
EDGE 2 Tx slots	25.12	25.01	25.02	0.0612	0.0597	0.0598
EDGE 3 Tx slots	22.97	23.01	23.05	0.0373	0.0377	0.0380
EDGE 4 Tx slots	21.52	21.56	21.63	0.0267	0.0270	0.0274

GSM1900_Ant.31	Burst Average Power (dBm)			EIRP(W)		
TX Channel	512	661	810			
Frequency (MHz)	1850.2	1880	1909.8	L	M	H
GSM 1 Tx slot	29.86	29.91	29.83	0.7870	0.7962	0.7816
GPRS 1 Tx slot	29.85	29.90	29.81	0.7852	0.7943	0.7780
GPRS 2 Tx slots	27.62	27.67	27.43	0.4699	0.4753	0.4498
GPRS 3 Tx slots	25.53	25.53	25.34	0.2904	0.2904	0.2780
GPRS 4 Tx slots	24.42	24.31	24.44	0.2249	0.2193	0.2259
EDGE 1 Tx slot	25.91	25.96	26.01	0.3170	0.3206	0.3243
EDGE 2 Tx slots	24.20	24.20	24.23	0.2138	0.2138	0.2153
EDGE 3 Tx slots	22.18	22.17	22.35	0.1343	0.1340	0.1396
EDGE 4 Tx slots	20.64	20.57	20.56	0.0942	0.0927	0.0925

Band		WCDMA Band V_Ant.13			ERP(W)		
TX Channel		4132	4182	4233			
Rx Channel		4357	4407	4458			
Frequency (MHz)		826.4	836.4	846.6	L	M	H
3GPP Rel 99	AMR 12.2Kbps	24.33	24.38	24.36	0.0511	0.0516	0.0514
3GPP Rel 99	RMC 12.2Kbps	24.35	24.40	24.37	0.0513	0.0519	0.0515
3GPP Rel 6	HSDPA Subtest-1	23.52	23.61	23.58	0.0424	0.0433	0.0430
3GPP Rel 6	HSDPA Subtest-2	23.54	23.57	23.59	0.0426	0.0429	0.0431
3GPP Rel 6	HSDPA Subtest-3	22.99	23.08	23.08	0.0375	0.0383	0.0383
3GPP Rel 6	HSDPA Subtest-4	23.02	23.09	23.08	0.0378	0.0384	0.0383
3GPP Rel 8	DC-HSDPA Subtest-1	23.39	23.54	23.55	0.0411	0.0426	0.0427
3GPP Rel 8	DC-HSDPA Subtest-2	23.50	23.41	23.48	0.0422	0.0413	0.0420
3GPP Rel 8	DC-HSDPA Subtest-3	22.97	22.96	23.00	0.0373	0.0372	0.0376
3GPP Rel 8	DC-HSDPA Subtest-4	22.99	22.96	22.99	0.0375	0.0372	0.0375
3GPP Rel 6	HSUPA Subtest-1	23.52	23.55	23.60	0.0424	0.0427	0.0432
3GPP Rel 6	HSUPA Subtest-2	21.54	21.59	21.59	0.0269	0.0272	0.0272
3GPP Rel 6	HSUPA Subtest-3	22.59	22.57	22.57	0.0342	0.0340	0.0340
3GPP Rel 6	HSUPA Subtest-4	21.56	21.59	21.58	0.0270	0.0272	0.0271
3GPP Rel 6	HSUPA Subtest-5	23.60	23.60	23.60	0.0432	0.0432	0.0432
3GPP Rel 7	HSPA+ (16QAM) Subtest-1	22.66	22.67	22.64	0.0348	0.0348	0.0346

Band		WCDMA Band IV_Ant.31			EIRP(W)		
TX Channel		1312	1413	1513			
Rx Channel		1537	1638	1738			
Frequency (MHz)		1712.4	1732.6	1752.6	L	M	H
3GPP Rel 99	AMR 12.2Kbps	23.89	23.95	23.87	0.1227	0.1245	0.1222
3GPP Rel 99	RMC 12.2Kbps	23.90	23.97	23.90	0.1230	0.1250	0.1230
3GPP Rel 6	HSDPA Subtest-1	23.02	23.10	23.02	0.1005	0.1023	0.1005
3GPP Rel 6	HSDPA Subtest-2	22.99	23.13	23.02	0.0998	0.1030	0.1005
3GPP Rel 6	HSDPA Subtest-3	22.52	22.62	22.57	0.0895	0.0916	0.0906
3GPP Rel 6	HSDPA Subtest-4	22.59	22.63	22.54	0.0910	0.0918	0.0899
3GPP Rel 8	DC-HSDPA Subtest-1	23.00	22.97	22.98	0.1000	0.0993	0.0995
3GPP Rel 8	DC-HSDPA Subtest-2	22.94	23.09	23.00	0.0986	0.1021	0.1000
3GPP Rel 8	DC-HSDPA Subtest-3	22.48	22.56	22.56	0.0887	0.0904	0.0904
3GPP Rel 8	DC-HSDPA Subtest-4	22.44	22.61	22.49	0.0879	0.0914	0.0889
3GPP Rel 6	HSUPA Subtest-1	23.02	23.12	23.02	0.1005	0.1028	0.1005
3GPP Rel 6	HSUPA Subtest-2	21.02	21.09	20.99	0.0634	0.0644	0.0630
3GPP Rel 6	HSUPA Subtest-3	21.93	22.14	22.04	0.0782	0.0820	0.0802
3GPP Rel 6	HSUPA Subtest-4	21.00	21.12	21.15	0.0631	0.0649	0.0653
3GPP Rel 6	HSUPA Subtest-5	23.00	23.10	23.00	0.1000	0.1023	0.1000
3GPP Rel 7	HSPA+ (16QAM) Subtest-1	21.96	22.15	22.09	0.0787	0.0822	0.0811

Band		WCDMA Band II_Ant.31			EIRP(W)		
TX Channel		9262	9400	9538			
Rx Channel		9662	9800	9938			
Frequency (MHz)		1852.4	1880	1907.6	L	M	H
3GPP Rel 99	AMR 12.2Kbps	23.93	23.94	23.87	0.2009	0.2014	0.1982
3GPP Rel 99	RMC 12.2Kbps	23.94	23.95	23.89	0.2014	0.2018	0.1991
3GPP Rel 6	HSDPA Subtest-1	22.98	22.95	22.91	0.1614	0.1603	0.1589
3GPP Rel 6	HSDPA Subtest-2	23.00	22.95	22.93	0.1622	0.1603	0.1596
3GPP Rel 6	HSDPA Subtest-3	22.49	22.42	22.45	0.1442	0.1419	0.1429
3GPP Rel 6	HSDPA Subtest-4	22.52	22.43	22.45	0.1452	0.1422	0.1429
3GPP Rel 8	DC-HSDPA Subtest-1	22.95	22.92	22.79	0.1603	0.1592	0.1545
3GPP Rel 8	DC-HSDPA Subtest-2	22.99	22.89	22.82	0.1618	0.1581	0.1556
3GPP Rel 8	DC-HSDPA Subtest-3	22.37	22.26	22.29	0.1403	0.1368	0.1377
3GPP Rel 8	DC-HSDPA Subtest-4	22.50	22.39	22.31	0.1445	0.1409	0.1384
3GPP Rel 6	HSUPA Subtest-1	22.99	22.99	22.94	0.1618	0.1618	0.1600
3GPP Rel 6	HSUPA Subtest-2	20.92	20.96	20.93	0.1005	0.1014	0.1007
3GPP Rel 6	HSUPA Subtest-3	21.88	21.96	21.97	0.1253	0.1276	0.1279
3GPP Rel 6	HSUPA Subtest-4	20.94	20.90	20.90	0.1009	0.1000	0.1000
3GPP Rel 6	HSUPA Subtest-5	23.00	22.90	22.90	0.1622	0.1585	0.1585
3GPP Rel 7	HSPA+ (16QAM) Subtest-1	21.89	22.05	21.88	0.1256	0.1303	0.1253

GSM

Peak-to-Average Ratio

Mode	GSM850(dB)		Limit: 13dB
Mod.	GSM	EDGE class 8	Result
Lowest CH	0.14	3.16	PASS
Middle CH	0.12	3.22	
Highest CH	0.12	2.90	

Mode	GSM1900(dB)		Limit: 13dB
Mod.	GSM	EDGE class 8	Result
Lowest CH	0.23	2.93	PASS
Middle CH	0.26	3.13	
Highest CH	0.26	3.01	

GSM850 (GSM)	GSM850 (EDGE class 8)
Lowest Channel	**Lowest Channel**
	
Middle Channel	**Middle Channel**
	
Highest Channel	**Highest Channel**
	

GSM1900 (GSM)	GSM1900 (EDGE class 8)
Lowest Channel	**Lowest Channel**
	
Middle Channel	**Middle Channel**
	
Highest Channel	**Highest Channel**
	

26dB Bandwidth

Mode	GSM850(MHz)	
Mod.	GSM	EDGE class 8
Lowest CH	0.31	0.31
Middle CH	0.31	0.31
Highest CH	0.31	0.31

Mode	GSM1900(MHz)	
Mod.	GSM	EDGE class 8
Lowest CH	0.31	0.31
Middle CH	0.31	0.31
Highest CH	0.31	0.31

GSM850 (GSM)	GSM850 (EDGE class 8)
Lowest Channel	**Lowest Channel**
	
Middle Channel	**Middle Channel**
	
Highest Channel	**Highest Channel**
	

GSM1900 (GSM)

Lowest Channel



Middle Channel



Highest Channel



GSM1900 (EDGE class 8)

Lowest Channel



Middle Channel



Highest Channel



Occupied Bandwidth

Mode	GSM850(MHz)	
Mod.	GSM	EDGE class 8
Lowest CH	0.241	0.242
Middle CH	0.241	0.240
Highest CH	0.240	0.245

Mode	GSM1900(MHz)	
Mod.	GSM	EDGE class 8
Lowest CH	0.245	0.248
Middle CH	0.240	0.247
Highest CH	0.241	0.242

GSM850 (GSM)	GSM850 (EDGE class 8)
Lowest Channel	**Lowest Channel**
	
Middle Channel	**Middle Channel**
	
Highest Channel	**Highest Channel**
	

GSM1900 (GSM)	GSM1900 (EDGE class 8)
Lowest Channel	**Lowest Channel**
	
Middle Channel	**Middle Channel**
	
Highest Channel	**Highest Channel**
	

Conducted Band Edge

GSM850 (GSM)

Lowest Band Edge



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
820.000 MHz	823.000 MHz	100.000 kHz	822.75275 MHz	-48.20 dBm	-35.20 dB
823.000 MHz	824.000 MHz	3.000 kHz	823.99301 MHz	-19.51 dBm	-6.51 dB
824.000 MHz	824.500 MHz	10.000 kHz	824.26896 MHz	21.39 dBm	-13.61 dB

Date: 14.MAR.2024 22:55:40

Highest Band Edge



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
848.500 MHz	849.000 MHz	10.000 kHz	848.87076 MHz	22.82 dBm	-12.18 dB
849.000 MHz	850.000 MHz	3.000 kHz	849.02096 MHz	-18.87 dBm	-5.87 dB
850.000 MHz	855.000 MHz	100.000 kHz	850.28222 MHz	-47.40 dBm	-34.40 dB

Date: 14.MAR.2024 23:01:28

GSM850 (EDGE class 8)

Lowest Band Edge



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
820.000 MHz	823.000 MHz	100.000 kHz	822.71379 MHz	-47.97 dBm	-34.97 dB
823.000 MHz	824.000 MHz	3.000 kHz	823.99701 MHz	-20.62 dBm	-7.62 dB
824.000 MHz	824.500 MHz	10.000 kHz	824.18812 MHz	20.78 dBm	-14.22 dB

Date: 14.MAR.2024 23:41:06

Highest Band Edge



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
848.500 MHz	849.000 MHz	10.000 kHz	848.80190 MHz	15.49 dBm	-19.51 dB
849.000 MHz	850.000 MHz	3.000 kHz	849.01697 MHz	-26.81 dBm	-13.81 dB
850.000 MHz	855.000 MHz	100.000 kHz	850.25225 MHz	-48.58 dBm	-35.58 dB

Date: 14.MAR.2024 23:48:03

GSM1900 (GSM)

Lowest Band Edge



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
1.845 GHz	1.849 GHz	1.000 MHz	1.84899 GHz	-38.62 dBm	-25.62 dB
1.849 GHz	1.850 GHz	3.000 kHz	1.85000 GHz	-20.18 dBm	-7.18 dB
1.850 GHz	1.851 GHz	10.000 kHz	1.85027 GHz	21.87 dBm	-13.13 dB

Date: 14.MAR.2024 23:30:00

Highest Band Edge



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
1.909 GHz	1.910 GHz	10.000 kHz	1.90983 GHz	21.16 dBm	-13.84 dB
1.910 GHz	1.911 GHz	3.000 kHz	1.91002 GHz	-20.92 dBm	-7.92 dB
1.911 GHz	1.915 GHz	1.000 MHz	1.91101 GHz	-37.89 dBm	-24.89 dB

Date: 14.MAR.2024 23:35:35

GSM1900 (EDGE class 8)

Lowest Band Edge



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
1.845 GHz	1.849 GHz	1.000 MHz	1.84899 GHz	-39.83 dBm	-26.83 dB
1.849 GHz	1.850 GHz	3.000 kHz	1.84998 GHz	-26.91 dBm	-13.91 dB
1.850 GHz	1.851 GHz	10.000 kHz	1.85020 GHz	16.92 dBm	-18.08 dB

Date: 14.MAR.2024 23:54:42

Highest Band Edge



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
1.909 GHz	1.910 GHz	10.000 kHz	1.90978 GHz	17.03 dBm	-17.97 dB
1.910 GHz	1.911 GHz	3.000 kHz	1.91001 GHz	-28.56 dBm	-15.56 dB
1.911 GHz	1.915 GHz	1.000 MHz	1.91102 GHz	-39.44 dBm	-26.44 dB

Date: 15.MAR.2024 00:11:55

Conducted Spurious Emission

GSM850 (GSM)

Lowest Channel



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
30.000 MHz	820.000 MHz	1.000 MHz	794.93003 MHz	-39.24 dBm	-26.24 dB
855.000 MHz	1.000 GHz	1.000 MHz	866.34058 MHz	-36.64 dBm	-23.64 dB
1.000 GHz	3.000 GHz	1.000 MHz	1.64879 GHz	-34.80 dBm	-21.80 dB
3.000 GHz	7.000 GHz	1.000 MHz	6.89976 GHz	-32.38 dBm	-19.38 dB
7.000 GHz	9.000 GHz	1.000 MHz	7.07762 GHz	-31.98 dBm	-18.98 dB

Middle Channel



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
30.000 MHz	820.000 MHz	1.000 MHz	147.45377 MHz	-38.58 dBm	-25.58 dB
855.000 MHz	1.000 GHz	1.000 MHz	990.18116 MHz	-37.67 dBm	-24.67 dB
1.000 GHz	3.000 GHz	1.000 MHz	1.67329 GHz	-34.49 dBm	-21.49 dB
3.000 GHz	7.000 GHz	1.000 MHz	6.88426 GHz	-32.12 dBm	-19.12 dB
7.000 GHz	9.000 GHz	1.000 MHz	7.30284 GHz	-32.23 dBm	-19.23 dB

Highest Channel



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
30.000 MHz	820.000 MHz	1.000 MHz	814.27536 MHz	-39.19 dBm	-26.19 dB
855.000 MHz	1.000 GHz	1.000 MHz	957.35507 MHz	-36.69 dBm	-23.69 dB
1.000 GHz	3.000 GHz	1.000 MHz	2.51169 GHz	-36.94 dBm	-23.94 dB
3.000 GHz	7.000 GHz	1.000 MHz	6.90276 GHz	-31.87 dBm	-18.87 dB
7.000 GHz	9.000 GHz	1.000 MHz	7.01462 GHz	-32.48 dBm	-19.48 dB

GSM850 (EDGE class 8)

Lowest Channel



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
30.000 MHz	820.000 MHz	1.000 MHz	471.98151 MHz	-38.24 dBm	-25.24 dB
855.000 MHz	1.000 GHz	1.000 MHz	949.67391 MHz	-36.65 dBm	-23.65 dB
1.000 GHz	3.000 GHz	1.000 MHz	1.64879 GHz	-34.40 dBm	-21.40 dB
3.000 GHz	7.000 GHz	1.000 MHz	6.89276 GHz	-32.23 dBm	-19.23 dB
7.000 GHz	9.000 GHz	1.000 MHz	7.26059 GHz	-32.86 dBm	-19.86 dB

Middle Channel



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
30.000 MHz	820.000 MHz	1.000 MHz	485.01000 MHz	-38.21 dBm	-25.21 dB
855.000 MHz	1.000 GHz	1.000 MHz	955.68841 MHz	-36.87 dBm	-23.87 dB
1.000 GHz	3.000 GHz	1.000 MHz	2.61492 GHz	-35.63 dBm	-22.63 dB
3.000 GHz	7.000 GHz	1.000 MHz	5.84289 GHz	-32.42 dBm	-19.42 dB
7.000 GHz	9.000 GHz	1.000 MHz	7.27859 GHz	-32.80 dBm	-19.80 dB

Highest Channel



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
30.000 MHz	820.000 MHz	1.000 MHz	657.53873 MHz	-38.51 dBm	-25.51 dB
855.000 MHz	1.000 GHz	1.000 MHz	945.76087 MHz	-37.43 dBm	-24.43 dB
1.000 GHz	3.000 GHz	1.000 MHz	2.51244 GHz	-36.55 dBm	-23.55 dB
3.000 GHz	7.000 GHz	1.000 MHz	6.81127 GHz	-31.83 dBm	-18.83 dB
7.000 GHz	9.000 GHz	1.000 MHz	8.69866 GHz	-33.17 dBm	-20.17 dB

GSM1900 (GSM)

Lowest Channel



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
30.000 MHz	1.000 GHz	1.000 MHz	660.42729 MHz	-37.23 dBm	-24.23 dB
1.000 GHz	1.845 GHz	1.000 MHz	1.59817 GHz	-37.77 dBm	-24.77 dB
1.915 GHz	3.000 GHz	1.000 MHz	2.92765 GHz	-36.39 dBm	-23.39 dB
3.000 GHz	7.000 GHz	1.000 MHz	5.94038 GHz	-32.52 dBm	-19.52 dB
7.000 GHz	13.600 GHz	1.000 MHz	13.30373 GHz	-32.07 dBm	-19.07 dB
13.600 GHz	19.100 GHz	1.000 MHz	18.24501 GHz	-27.04 dBm	-14.04 dB

Date: 14.MAR.2024 23:30:43

Middle Channel



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
30.000 MHz	1.000 GHz	1.000 MHz	955.64468 MHz	-38.67 dBm	-25.67 dB
1.000 GHz	1.845 GHz	1.000 MHz	1.54919 GHz	-36.98 dBm	-23.98 dB
1.915 GHz	3.000 GHz	1.000 MHz	2.49466 GHz	-34.93 dBm	-21.93 dB
3.000 GHz	7.000 GHz	1.000 MHz	6.79028 GHz	-31.81 dBm	-18.81 dB
7.000 GHz	13.600 GHz	1.000 MHz	7.01485 GHz	-31.97 dBm	-18.97 dB
13.600 GHz	19.100 GHz	1.000 MHz	15.55020 GHz	-26.59 dBm	-13.59 dB

Date: 14.MAR.2024 23:32:19

Highest Channel



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
30.000 MHz	1.000 GHz	1.000 MHz	677.87856 MHz	-36.91 dBm	-23.91 dB
1.000 GHz	1.845 GHz	1.000 MHz	1.71810 GHz	-37.47 dBm	-24.47 dB
1.915 GHz	3.000 GHz	1.000 MHz	2.59636 GHz	-35.44 dBm	-22.44 dB
3.000 GHz	7.000 GHz	1.000 MHz	6.96625 GHz	-30.60 dBm	-17.60 dB
7.000 GHz	13.600 GHz	1.000 MHz	13.35228 GHz	-31.95 dBm	-18.95 dB
13.600 GHz	19.100 GHz	1.000 MHz	15.81457 GHz	-26.21 dBm	-13.21 dB

Date: 14.MAR.2024 23:34:01

GSM1900 (EDGE class 8)

Lowest Channel



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
30.000 MHz	1.000 GHz	1.000 MHz	933.83058 MHz	-36.63 dBm	-23.63 dB
1.000 GHz	1.845 GHz	1.000 MHz	1.03948 GHz	-37.37 dBm	-24.37 dB
1.915 GHz	3.000 GHz	1.000 MHz	2.51039 GHz	-35.52 dBm	-22.52 dB
3.000 GHz	7.000 GHz	1.000 MHz	6.92376 GHz	-31.37 dBm	-18.37 dB
7.000 GHz	13.600 GHz	1.000 MHz	10.62196 GHz	-32.46 dBm	-19.46 dB
13.600 GHz	19.100 GHz	1.000 MHz	16.68548 GHz	-27.26 dBm	-14.26 dB

Date: 15.MAR.2024 00:06:06

Middle Channel



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
30.000 MHz	1.000 GHz	1.000 MHz	858.69315 MHz	-37.84 dBm	-24.84 dB
1.000 GHz	1.845 GHz	1.000 MHz	1.80805 GHz	-37.72 dBm	-24.72 dB
1.915 GHz	3.000 GHz	1.000 MHz	2.64694 GHz	-35.15 dBm	-22.15 dB
3.000 GHz	7.000 GHz	1.000 MHz	6.97575 GHz	-31.37 dBm	-18.37 dB
7.000 GHz	13.600 GHz	1.000 MHz	11.37431 GHz	-32.29 dBm	-19.29 dB
13.600 GHz	19.100 GHz	1.000 MHz	15.82164 GHz	-26.92 dBm	-13.92 dB

Date: 15.MAR.2024 00:08:10

Highest Channel



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
30.000 MHz	1.000 GHz	1.000 MHz	962.91604 MHz	-38.35 dBm	-25.35 dB
1.000 GHz	1.845 GHz	1.000 MHz	1.02555 GHz	-37.84 dBm	-24.84 dB
1.915 GHz	3.000 GHz	1.000 MHz	2.95206 GHz	-34.65 dBm	-21.65 dB
3.000 GHz	7.000 GHz	1.000 MHz	6.91376 GHz	-29.93 dBm	-16.93 dB
7.000 GHz	13.600 GHz	1.000 MHz	12.58249 GHz	-32.15 dBm	-19.15 dB
13.600 GHz	19.100 GHz	1.000 MHz	15.88607 GHz	-26.53 dBm	-13.53 dB

Date: 15.MAR.2024 00:09:56

Frequency Stability

Test Conditions	Middle Channel	GSM850 (GSM)	GSM850 (EDGE class 8)	Limit 2.5ppm
Temperature (°C)	Voltage (Volt)	Deviation (ppm)		Result
50	Normal Voltage	0.0008	0.0024	PASS
40	Normal Voltage	0.0005	0.0029	
30	Normal Voltage	0.0037	0.0012	
20(Ref.)	Normal Voltage	0.0000	0.0000	
10	Normal Voltage	0.0012	0.0081	
0	Normal Voltage	0.0103	0.0093	
-10	Normal Voltage	0.0001	0.0076	
-20	Normal Voltage	0.0024	0.0090	
-30	Normal Voltage	0.0022	0.0082	
20	Maximum Voltage	0.0004	0.0023	
20	Normal Voltage	0.0000	0.0000	
20	Battery End Point	0.0020	0.0002	

Test Conditions	Middle Channel	GSM1900 (GSM)	GSM1900 (EDGE class 8)	Limit Note 2.
Temperature (°C)	Voltage (Volt)	Deviation (ppm)		Result
50	Normal Voltage	0.0052	0.0006	PASS
40	Normal Voltage	0.0062	0.0018	
30	Normal Voltage	0.0057	0.0013	
20(Ref.)	Normal Voltage	0.0000	0.0000	
10	Normal Voltage	0.0057	0.0019	
0	Normal Voltage	0.0079	0.0014	
-10	Normal Voltage	0.0051	0.0007	
-20	Normal Voltage	0.0002	0.0013	
-30	Normal Voltage	0.0057	0.0006	
20	Maximum Voltage	0.0056	0.0001	
20	Normal Voltage	0.0000	0.0000	
20	Battery End Point	0.0061	0.0016	

Note:

1. Normal Voltage = 3.91V. ; Battery End Point (BEP) = 3.7 V. ; Maximum Voltage =4.4 V
2. The frequency fundamental emissions stay within the authorized frequency block based on the frequency deviation measured is small.

WCDMA

Peak-to-Average Ratio

Mode	WCDMA Band V(dB)	WCDMA Band II(dB)	WCDMA Band IV(dB)	Limit: 13dB
Mod.	RMC 12.2Kbps	RMC 12.2Kbps	RMC 12.2Kbps	Result
Lowest CH	2.78	2.90	2.99	PASS
Middle CH	2.87	3.04	2.70	
Highest CH	2.87	2.81	3.10	

WCDMA Band V (RMC 12.2Kbps)	WCDMA Band II (RMC 12.2Kbps)
Lowest Channel	**Lowest Channel**
	
Middle Channel	**Middle Channel**
	
Highest Channel	**Highest Channel**
	

WCDMA Band IV (RMC 12.2Kbps)

Lowest Channel



Middle Channel



Highest Channel



26dB Bandwidth

Mode	WCDMA Band V(MHz)	WCDMA Band II(MHz)	WCDMA Band IV(MHz)
Mod.	RMC 12.2Kbps	RMC 12.2Kbps	RMC 12.2Kbps
Lowest CH	4.73	4.73	4.73
Middle CH	4.73	4.72	4.74
Highest CH	4.72	4.73	4.72

WCDMA Band V (RMC 12.2Kbps)

Lowest Channel



Middle Channel



Highest Channel



WCDMA Band II (RMC 12.2Kbps)

Lowest Channel



Middle Channel



Highest Channel



WCDMA Band IV (RMC 12.2Kbps)

Lowest Channel



Middle Channel



Highest Channel



Occupied Bandwidth

Mode	WCDMA Band V(MHz)	WCDMA Band II(MHz)	WCDMA Band IV(MHz)
Mod.	RMC 12.2Kbps	RMC 12.2Kbps	RMC 12.2Kbps
Lowest CH	4.14	4.14	4.16
Middle CH	4.14	4.15	4.15
Highest CH	4.13	4.15	4.15

WCDMA Band V (RMC 12.2Kbps)	WCDMA Band II (RMC 12.2Kbps)
Lowest Channel	**Lowest Channel**
	
Middle Channel	**Middle Channel**
	
Highest Channel	**Highest Channel**