FCC Test Report

Applicant	:	**Dongguan Zhongjin Electronic Technology Co., LTD**
Address	:	**Building A, DongXing Industrial Park Kangle Rd., Hengli Town, Dongguan, Guangdong, China**
Product Name	:	**Thermostat**
Report Date	:	**Jul. 30, 2024**

Shenzhen Anbotek Compliance Laboratory Limited

Contents

1. General Information 6
1.1. Client Information 6
1.2. Description of Device (EUT) 6
1.3. Auxiliary Equipment Used During Test 7
1.4. Description of Test Configuration 7
1.5. Description of Test Setup 8
1.6. Test Equipment List 9
1.7. Measurement Uncertainty 10
1.8. Description of Test Facility 10
1.9. Disclaimer 11
2. Summary of Test Results 12
3. Conducted Emission Test 13
3.1. Test Standard and Limit 13
3.2. Test Setup 13
3.3. Test Procedure 13
3.4. Test Data 13
4. Radiation Spurious Emission and Band Edge Test 16
4.1. Test Standard and Limit 16
4.2. Test Setup 16
4.3. Test Procedure 17
4.4. Test Data 18
5. Maximum Conducted Output Power Test 28
5.1. Test Standard and Limit 28
5.2. Test Setup 28
5.3. Test Procedure 28
5.4. Test Data 28
6. 6dB Bandwidth and 99% Occupied Bandwidth Test 29
6.1. Test Standard and Limit 29
6.2. Test Setup 29
6.3. Test Procedure 29
6.4. Test Data 29
7. Maximum Power Spectral Density Test 30
7.1. Test Standard and Limit 30
7.2. Test Setup 30
7.3. Test Procedure 30
7.4. Test Data 30
8. Conducted Spurious Emission and Band Edge Test 31
8.1. Test Standard and Limit 31

8.2. Test Setup 31
8.3. Test Procedure 31
8.4. Test Data 31
9. Antenna Requirement 32
9.1. Test Standard and Requirement 32
9.2. Antenna Connected Construction 32
APPENDIX I -- TEST SETUP PHOTOGRAPH 33
APPENDIX II -- EXTERNAL PHOTOGRAPH 33
APPENDIX III -- INTERNAL PHOTOGRAPH 33

TEST REPORT

Applicant	:	Dongguan Zhongjin Electronic Technology Co., LTD
Manufacturer	:	Dongguan Zhongjin Electronic Technology Co., LTD
Product Name	:	Thermostat
Model No.	:	RTC500-WIFI
Trade Mark	:	OCSTAT
Rating(s)	:	Input: 100V-240VAC, 15mA Output: 100V-240VAC, 10A
Test Standard(s)	**:**	**47 CFR Part 15.247**
Test Method(s)	**:**	**ANSI C63.10: 2020, KDB 558074 D01 15.247 Meas Guidance v05r02**

The device described above is tested by Shenzhen Anbotek Compliance Laboratory Limited to determine the maximum emission levels emanating from the device and the severe levels of the device can endure and its performance criterion. The measurement results are contained in this test report and Shenzhen Anbotek Compliance Laboratory Limited is assumed full of responsibility for the accuracy and completeness of these measurements. Also, this report shows that the EUT (Equipment Under Test) is technically compliant with the 47 CFR Part 15.247 requirements.

This report applies to above tested sample only and shall not be reproduced in part without written approval of Shenzhen Anbotek Compliance Laboratory Limited.

Date of Receipt	May 22, 2024
Date of Test	May 22, 2024 to Jun. 03, 2024
Prepared by	(TuTu Hong)
Approved & Authorized Signer	(Edward Pan)

Revision History

Report Version	Description	Issued Date
R00	Original Issue.	Jul. 30, 2024

1. General Information

1.1. Client Information

Applicant	:	Dongguan Zhongjin Electronic Technology Co.,Ltd
Address	:	Building A, DongXing Industrial Park Kangle Rd., Hengli Town, Dongguan, Guangdong, China
Manufacturer	:	Dongguan Zhongjin Electronic Technology Co., LTD
Address	:	Building A, DongXing Industrial Park Kangle Rd., Hengli Town, Dongguan, Guangdong, China
Factory	:	Dongguan Zhongjin Electronic Technology Co., LTD
Address	:	Building A, DongXing Industrial Park Kangle Rd., Hengli Town, Dongguan, Guangdong, China

1.2. Description of Device (EUT)

Product Name	:	Thermostat
Model No.	:	RTC500-WIFI
Trade Mark	:	OCSTAT
Test Power Supply	:	AC 120V/60Hz
Test Sample No.	:	1-2-1(Normal Sample), 1-2-2(Engineering Sample)
Adapter	:	N/A
RF Specification		
Operation Mode	:	☒802.11b ☒802.11g ☒802.11n(HT20) ☒802.11n(HT40)
Operation Frequency	:	2412~2462MHz
Number of Channel	:	11 Channel for 20MHz bandwidth (2412~2462MHz) 7 channels for 40MHz bandwidth (2422~2452MHz)
Modulation Type	:	☒ 802.11b: DSSS (CCK, DQPSK, DBPSK) ☒ 802.11g: OFDM (BPSK, QPSK, 16QAM, 64QAM) ☒ 802.11n: OFDM (BPSK, QPSK, 16QAM, 64QAM)
Antenna Type	:	PCB Antenna
Antenna Gain(Peak)	:	1.05 dBi (Provided by customer)
Remark: 1) All of the RF specification are provided by customer. 2) For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.		

1.3. Auxiliary Equipment Used During Test

Description	Rating(s)
--	--

1.4. Description of Test Configuration

Channel	Freq. (MHz)	Channel	Freq. (MHz)	Channel	Freq. (MHz)	Channel	Freq. (MHz)
01	**2412**	04	2427	07	2442	10	2457
02	2417	05	2432	08	2447	**11**	**2462**
03	**2422**	**06**	**2437**	**09**	**2452**		

Note:

1. The engineering test program was provided and the EUT was programmed to be in continuously transmitting mode.
2. For 802.11b, 802.11g, and 802.11n(HT20) modes were test with channel 1, 6, 11. For 802.11n(HT40) modes were test with channel 3, 6, 9.

1.5. Description of Test Setup

CE



RE



1.6. Test Equipment List

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	L.I.S.N. Artificial Mains Network	Rohde & Schwarz	ENV216	100055	Jan. 18, 2024	1 Year
2.	Three Phase V-type Artificial Power Network	CYBERTEK	EM5040DT	E215040DT001	Jan. 18, 2024	1 Year
3.	EMI Test Receiver	Rohde & Schwarz	ESCI	100627	Oct. 12, 2023	1 Year
4.	EMI Test Receiver	Rohde & Schwarz	ESR26	101481	Jan. 23, 2024	1 Year
5.	MXA Spectrum Analysis	Agilent	N9020A	MY51170037	Oct. 12, 2023	1 Year
6.	EMI Preamplifier	SKET Electronic	LNPA-0118G -45	SKET-PA-002	Jan. 17, 2024	1 Year
7.	Double Ridged Horn Antenna	SCHWARZBECK	BBHA 9120D	02555	Oct. 16, 2022	3 Year
8.	Bilog Broadband Antenna	Schwarzbeck	VULB9163	345	Oct. 23, 2022	3 Year
9.	Loop Antenna	Schwarzbeck	FMZB1519B	00053	Oct. 12, 2023	1 Year
10.	Horn Antenna	A-INFO	LB-180400-KF	J211060628	Oct. 12, 2023	1 Year
11.	Pre-amplifier	SONOMA	310N	186860	Jan. 17, 2024	1 Year
12.	EMI Test Software EZ-EMC	SHURPLE	N/A	N/A	N/A	N/A
13.	MXA Spectrum Analysis	KEYSIGHT	N9020A	MY53280032	Oct. 12, 2023	1 Year
14.	MXG RF Vector Signal Generator	Agilent	N5182A	MY48180656	Oct. 12, 2023	1 Year
15.	Signal Generator	Agilent	E4421B	MY41000743	Oct. 12, 2023	1 Year
16.	DC Power Supply	IVYTECH	IV3605	1804D360510	Oct. 20, 2023	1 Year
17.	Constant Temperature Humidity Chamber	ZHONGJIAN	ZJ-KHWS80 B	N/A	Oct. 16, 2023	1 Year
18.	Wideband Radio Communication Tester	Rohde & Schwarz	CMW500	104209	Oct. 12, 2023	1 Year

1.7. Measurement Uncertainty

Parameter	Uncertainty
Conducted emissions (AMN 150kHz~30MHz)	3.8dB
Occupied Bandwidth	925Hz
Conducted Output Power	0.76dB
Conducted Spurious Emission	1.24dB
Radiated spurious emissions (Below 30MHz)	3.53dB
Radiated spurious emissions (30MHz~1GHz)	Horizontal: 3.92dB; Vertical: 4.52dB
Radiated spurious emissions (above 1GHz)	1G-6GHz: 4.78dB; 6G-18GHz: 4.88dB 18G-40GHz: 5.68dB
The measurement uncertainty and decision risk evaluated according to AB/WI-RF-F-032. The measurement uncertainty and decision risk evaluated according to AB/WI-RF-F-032. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.	

1.8. Description of Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

FCC-Registration No.: 434132

Shenzhen Anbotek Compliance Laboratory Limited, EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration No. 434132.

ISED-Registration No.: 8058A

Shenzhen Anbotek Compliance Laboratory Limited, EMC Laboratory has been registered and fully described in a report filed with the (ISED) Innovation, Science and Economic Development Canada. The acceptance letter from the ISED is maintained in our files. Registration 8058A.

Test Location

Shenzhen Anbotek Compliance Laboratory Limited.
1/F, Building D, Sogood Science and Technology Park, Sanwei community, Hangcheng Street, Bao'an District, Shenzhen, Guangdong, China.

1.9. Disclaimer

1. The test report is invalid if not marked with the signatures of the persons responsible for preparing and approving the test report.
2. The test report is invalid if there is any evidence and/or falsification.
3. The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein.
4. This document may not be altered or revised in any way unless done so by Anbotek and all revisions are duly noted in the revisions section.
5. Content of the test report, in part or in full, cannot be used for publicity and/or promotional purposes without prior written approval from the laboratory.
6. The authenticity of the information provided by the customer is the responsibility of the customer and the laboratory is not responsible for its authenticity.

The laboratory is only responsible for the data released by the laboratory, except for the part provided by the applicant.

2. Summary of Test Results

Standard Section	Test Item	Result
15.203/15.247(c)	Antenna Requirement	PASS
15.207	Conducted Emission	PASS
15.205/15.209	Radiated Spurious Emission and Band Edge	PASS
15.247(b)(3)	Maximum Conduct Output Power	PASS
15.247(a)(2)	6dB Bandwidth	PASS
N/A	99% Occupied Bandwidth	Report only
15.247(e)	Maximum Power Spectral Density	PASS
15.247(d)	Conducted Spurious Emission and Band Edge	PASS
Remark: “N/A” is an abbreviation for Not Applicable.		

3. Conducted Emission Test

3.1. Test Standard and Limit

Test Standard	FCC Part15 Section 15.207		
Test Limit	Frequency	Maximum RF Line Voltage (dBuV)	
		Quasi-peak Level	Average Level
	150kHz~500kHz	66 ~ 56 *	56 ~ 46 *
	500kHz~5MHz	56	46
	5MHz~30MHz	60	50
Remark: (1) *Decreasing linearly with logarithm of the frequency. (2) The lower limit shall apply at the transition frequency.			

3.2. Test Setup



3.3. Test Procedure

The EUT system is connected to the power mains through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm coupling impedance for the EUT system. Please refer the block diagram of the test setup and photographs. Both sides of AC line are checked to find out the maximum conducted emission. In order to find the maximum emission levels, the relative positions of equipment and all of the interface cables shall be changed according to FCC ANSI C63.10: 2020 on Conducted Emission Measurement.

The bandwidth of test receiver (ESCI) set at 9kHz.

The frequency range from 150kHz to 30MHz is checked.

3.4. Test Data

During the test, pre-scan all modes, only the worst case is recorded in the report.

AC conducted emission pre-test at both at AC 120V/60Hz and AC 240V/60Hz modes, recorded worst case AC 120V/60Hz.

Please to see the following pages.

Conducted Emission Test Data

Test Site:	1# Shielded Room
Operating Condition:	802.11g 2462MHz
Test Specification:	AC 120V, 60Hz
Comment:	Live Line
Temp.(℃)/Hum.(%RH):	22.1℃/52%RH



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit (dBuV)	Over Limit (dB)	Detector	Remark
1	0.1940	17.27	17.83	35.10	53.86	-18.76	AVG	
2	0.2100	31.55	17.83	49.38	63.20	-13.82	QP	
3	0.5180	23.04	17.85	40.89	56.00	-15.11	QP	
4	0.5780	12.66	17.86	30.52	46.00	-15.48	AVG	
5	1.3220	22.87	17.84	40.71	56.00	-15.29	QP	
6	1.3779	13.55	17.84	31.39	46.00	-14.61	AVG	
7	1.6660	19.61	17.84	37.45	56.00	-18.55	QP	
8	1.7300	9.05	17.84	26.89	46.00	-19.11	AVG	
9	2.1180	6.91	17.83	24.74	46.00	-21.26	AVG	
10	2.1460	16.39	17.83	34.22	56.00	-21.78	QP	
11	3.1260	2.14	17.84	19.98	46.00	-26.02	AVG	
12	3.3700	12.78	17.84	30.62	56.00	-25.38	QP	

Conducted Emission Test Data

Test Site:	1# Shielded Room
Operating Condition:	802.11g 2462MHz
Test Specification:	AC 120V, 60Hz
Comment:	Neutral Line
Temp.(℃)/Hum.(%RH):	22.1℃/52%RH



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit (dBuV)	Over Limit (dB)	Detector	Remark
1	0.1780	32.97	17.83	50.80	64.57	-13.77	QP	
2	0.2380	15.86	17.83	33.69	52.16	-18.47	AVG	
3	0.3020	25.10	17.83	42.93	60.19	-17.26	QP	
4	0.5660	26.67	17.86	44.53	56.00	-11.47	QP	
5	0.5660	14.37	17.86	32.23	46.00	-13.77	AVG	
6	1.2820	13.50	17.84	31.34	46.00	-14.66	AVG	
7	1.2980	23.57	17.84	41.41	56.00	-14.59	QP	
8	1.6540	19.08	17.84	36.92	56.00	-19.08	QP	
9	1.6660	9.04	17.84	26.88	46.00	-19.12	AVG	
10	1.9860	7.50	17.83	25.33	46.00	-20.67	AVG	
11	2.2260	17.60	17.83	35.43	56.00	-20.57	QP	
12	2.3980	5.78	17.83	23.61	46.00	-22.39	AVG	

4. Radiation Spurious Emission and Band Edge Test

4.1. Test Standard and Limit

Test Standard	FCC Part15 C Section 15.209 and 15.205				
Test Limit	Frequency (MHz)	Field strength (microvolt/meter)	Limit (dBuV/m)	Remark	Measurement distance (m)
	0.009MHz~0.490MHz	2400/F(kHz)	-	-	300
	0.490MHz-1.705MHz	24000/F(kHz)	-	-	30
	1.705MHz-30MHz	30	-	-	30
	30MHz~88MHz	100	40.0	Quasi-peak	3
	88MHz~216MHz	150	43.5	Quasi-peak	3
	216MHz~960MHz	200	46.0	Quasi-peak	3
	960MHz~1000MHz	500	54.0	Quasi-peak	3
	Above 1000MHz	500	54.0	Average	3
		-	74.0	Peak	3

Remark:
(1)The lower limit shall apply at the transition frequency.
(2) 15.35(b), Unless otherwise specified, the limit on peak radio frequency emissions is 20dB above the maximum permitted average emission limit applicable to the equipment under test. This peak limit applies to the total peak emission level radiated by the device.

4.2. Test Setup



Figure 1. Below 30MHz



Figure 2. 30MHz to 1GHz



Figure 3. Above 1 GHz

4.3. Test Procedure

For below 1GHz: The EUT is placed on a turntable, which is 0.8m above the ground plane.
For above 1GHz: The EUT is placed on a turntable, which is 1.5m above the ground plane.
The turn table can rotate 360 degrees to determine the position of the maximum emission level. The EUT is set 3 meters away from the receiving antenna which is mounted on a antenna tower. The antenna can be moved up and down from 1 to 4 meters to find out the maximum emission level. Rotated the EUT through three orthogonal axes to determine the maximum emissions, both horizontal and vertical polarization of the antenna are set on test. The EUT is tested in 9*6*6 Chamber. The device is evaluated in xyz orientation.

For the radiated emission test above 1GHz:
Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.

For 9kHz to 150kHz, Set the spectrum analyzer as:
RBW = 200Hz, VBW =1kHz, Detector= Quasi-Peak, Trace mode= Max hold, Sweep- auto couple.

For 150kHz to 30MHz, Set the spectrum analyzer as:
RBW = 9KHz, VBW =30kHz, Detector= Quasi-Peak, Trace mode= Max hold, Sweep- auto couple.

For 30MHz to 1000MHz, Set the spectrum analyzer as:
RBW = 100kHz, VBW =300kHz, Detector= Quasi-Peak, Trace mode= Max hold, Sweep- auto couple.
.

For above 1GHz,Set the spectrum analyzer as:
RBW =1MHz, VBW =1MHz, Detector= Peak, Trace mode= Max hold, Sweep- auto couple.
For average measurement:
–VBW=10Hz, When duty cycle is no less than 98 percent
–VBW ⩾ 1/T, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation, so refer to this clause 5.4 duty cycle.

4.4. Test Data

PASS

During the test, Pre-scan all kind of the place mode (X-axis, Y-axis, Z-axis), and found the X-axis is the worst case.

The test results of 9kHz-30MHz was attenuated more than 20dB below the permissible limits, so the results don't record in the report.

During the test, pre-scan all modes, only the worst case is recorded in the report.

Test Results (30~1000MHz)

Test Mode:	802.11g 2462MHz
Power Source:	AC 120V, 60Hz
Polarization:	Horizontal
Temp.(℃)/Hum.(%RH):	22.5℃/50%RH

No.	Freq. (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Detector			
1	46.9948	31.63	-15.43	16.20	40.00	-23.80	QP			
2	169.0054	40.17	-23.65	16.52	43.50	-26.98	QP			
3	239.9874	48.00	-21.66	26.34	46.00	-19.66	QP			
4	319.9370	40.63	-16.70	23.93	46.00	-22.07	QP			
5	884.5029	34.29	-6.62	27.67	46.00	-18.33	QP			
6	975.7529	34.04	-5.19	28.85	54.00	-25.15	QP			

Test Results (30~1000MHz)

Test Mode:	802.11g 2462MHz
Power Source:	AC 120V, 60Hz
Polarization:	Vertical
Temp.(℃)/Hum.(%RH):	22.5℃/50%RH

No.	Freq. (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Detector			
1	42.6000	36.55	-14.81	21.74	40.00	-18.26	QP			
2	91.4949	50.38	-17.47	32.91	43.50	-10.59	QP			
3	100.9339	46.79	-16.72	30.07	43.50	-13.43	QP			
4	170.7926	48.00	-21.09	26.91	43.50	-16.59	QP			
5	810.2654	34.88	-8.11	26.77	46.00	-19.23	QP			
6	989.5355	33.68	-4.95	28.73	54.00	-25.27	QP			

Test Results (Above 1000MHz)

Test Mode: 802.11n (HT20) Mode			Test channel: Lowest			
Peak value:						
Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4824.00	27.29	15.31	42.60	74.00	-31.40	Vertical
7236.00	28.03	18.06	46.09	74.00	-27.91	Vertical
9648.00	28.83	23.77	52.60	74.00	-21.40	Vertical
12060.00	*			74.00		Vertical
14472.00	*			74.00		Vertical
4824.00	26.87	15.31	42.18	74.00	-31.82	Horizontal
7236.00	29.46	18.06	47.52	74.00	-26.48	Horizontal
9648.00	28.72	23.77	52.49	74.00	-21.51	Horizontal
12060.00	*			74.00		Horizontal
14472.00	*			74.00		Horizontal
Average value:						
Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4824.00	18.37	15.31	33.68	54.00	-20.32	Vertical
7236.00	18.90	18.06	36.96	54.00	-17.04	Vertical
9648.00	19.18	23.77	42.95	54.00	-11.05	Vertical
12060.00	*			54.00		Vertical
14472.00	*			54.00		Vertical
4824.00	18.40	15.31	33.71	54.00	-20.29	Horizontal
7236.00	20.70	18.06	38.76	54.00	-15.24	Horizontal
9648.00	19.47	23.77	43.24	54.00	-10.76	Horizontal
12060.00	*			54.00		Horizontal
14472.00	*			54.00		Horizontal

Test Results (Above 1000MHz)

Test Mode: 802.11n (HT20) Mode				Test channel: Middle		
Peak value:						
Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4874.00	27.34	15.41	42.75	74.00	-31.25	Vertical
7311.00	28.09	18.01	46.10	74.00	-27.90	Vertical
9748.00	28.85	23.79	52.64	74.00	-21.36	Vertical
12185.00	*			74.00		Vertical
14622.00	*			74.00		Vertical
4874.00	27.72	15.41	43.13	74.00	-30.87	Horizontal
7311.00	29.08	18.01	47.09	74.00	-26.91	Horizontal
9748.00	29.04	23.79	52.83	74.00	-21.17	Horizontal
12185.00	*			74.00		Horizontal
14622.00	*			74.00		Horizontal
Average value:						
Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4874.00	18.18	15.41	33.59	54.00	-20.41	Vertical
7311.00	19.41	18.01	37.42	54.00	-16.58	Vertical
9748.00	20.10	23.79	43.89	54.00	-10.11	Vertical
12185.00	*			54.00		Vertical
14622.00	*			54.00		Vertical
4874.00	19.83	15.41	35.24	54.00	-18.76	Horizontal
7311.00	20.17	18.01	38.18	54.00	-15.82	Horizontal
9748.00	18.76	23.79	42.55	54.00	-11.45	Horizontal
12185.00	*			54.00		Horizontal
14622.00	*			54.00		Horizontal

Test Results (Above 1000MHz)

Test Mode: 802.11n (HT20) Mode				Test channel: Highest		
Peak value:						
Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4924.00	27.90	15.51	43.41	74.00	-30.59	Vertical
7386.00	28.79	17.97	46.76	74.00	-27.24	Vertical
9848.00	29.66	23.82	53.48	74.00	-20.52	Vertical
12310.00	*			74.00		Vertical
14772.00	*			74.00		Vertical
4924.00	27.11	15.51	42.62	74.00	-31.38	Horizontal
7386.00	28.04	17.97	46.01	74.00	-27.99	Horizontal
9848.00	28.64	23.82	52.46	74.00	-21.54	Horizontal
12310.00	*			74.00		Horizontal
14772.00	*			74.00		Horizontal
Average value:						
Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4924.00	17.81	15.51	33.32	54.00	-20.68	Vertical
7386.00	18.71	17.97	36.68	54.00	-17.32	Vertical
9848.00	19.66	23.82	43.48	54.00	-10.52	Vertical
12310.00	*			54.00		Vertical
14772.00	*			54.00		Vertical
4924.00	17.47	15.51	32.98	54.00	-21.02	Horizontal
7386.00	18.51	17.97	36.48	54.00	-17.52	Horizontal
9848.00	18.25	23.82	42.07	54.00	-11.93	Horizontal
12310.00	*			54.00		Horizontal
14772.00	*			54.00		Horizontal

Remark:

1. During the test, pre-scan the 802.11b,g,n(HT20),n(HT40) mode, and found the 802.11n20 mode is worse case , the report only record this mode.
2. Result=Reading + Factor
3. "*" means the test results were attenuated more than 20dB below the permissible limits, so the results don't record in the report.

Radiated Band Edge:

Test Mode: 802.11b Mode				Test channel: Lowest		
Peak value:						
Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2310.00	38.06	9.58	47.64	74.00	-26.36	Horizontal
2390.00	40.54	9.73	50.27	74.00	-23.73	Horizontal
2310.00	39.33	9.58	48.91	74.00	-25.09	Vertical
2390.00	46.13	9.73	55.86	74.00	-18.14	Vertical
Average value:						
Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2310.00	28.69	9.58	38.27	54.00	-15.73	Horizontal
2390.00	35.87	9.73	45.60	54.00	-8.40	Horizontal
2310.00	30.04	9.58	39.62	54.00	-14.38	Vertical
2390.00	38.21	9.73	47.94	54.00	-6.06	Vertical

Test Mode: 802.11b Mode				Test channel: Highest		
Peak value:						
Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.50	46.23	9.91	56.14	74.00	-17.86	Horizontal
2500.00	40.17	9.94	50.11	74.00	-23.89	Horizontal
2483.50	46.59	9.91	56.50	74.00	-17.50	Vertical
2500.00	39.81	9.94	49.75	74.00	-24.25	Vertical
Average value:						
Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.50	37.40	9.91	47.31	54.00	-6.69	Horizontal
2500.00	29.20	9.94	39.14	54.00	-14.86	Horizontal
2483.50	38.92	9.91	48.83	54.00	-5.17	Vertical
2500.00	29.64	9.94	39.58	54.00	-14.42	Vertical

Remark: 1. Result=Reading + Factor

Radiated Band Edge:

Test Mode: 802.11g Mode				Test channel: Lowest		
Peak value:						
Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2310.00	36.85	9.58	46.43	74.00	-27.57	Horizontal
2390.00	40.49	9.73	50.22	74.00	-23.78	Horizontal
2310.00	38.82	9.58	48.40	74.00	-25.60	Vertical
2390.00	42.47	9.73	52.20	74.00	-21.80	Vertical
Average value:						
Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2310.00	29.11	9.58	38.69	54.00	-15.31	Horizontal
2390.00	35.36	9.73	45.09	54.00	-8.91	Horizontal
2310.00	30.06	9.58	39.64	54.00	-14.36	Vertical
2390.00	35.84	9.73	45.57	54.00	-8.43	Vertical

Test Mode: 802.11g Mode				Test channel: Highest		
Peak value:						
Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.50	46.24	9.91	56.15	74.00	-17.85	Horizontal
2500.00	40.11	9.94	50.05	74.00	-23.95	Horizontal
2483.50	46.35	9.91	56.26	74.00	-17.74	Vertical
2500.00	39.72	9.94	49.66	74.00	-24.34	Vertical
Average value:						
Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.50	35.57	9.91	45.48	54.00	-8.52	Horizontal
2500.00	28.30	9.94	38.24	54.00	-15.76	Horizontal
2483.50	37.87	9.91	47.78	54.00	-6.22	Vertical
2500.00	29.17	9.94	39.11	54.00	-14.89	Vertical

Remark: 1. Result=Reading + Factor

Radiated Band Edge:

Test Mode: 802.11n (HT20) Mode				Test channel: Lowest		
Peak value:						
Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2310.00	34.85	9.58	44.43	74.00	-29.57	Horizontal
2390.00	38.49	9.73	48.22	74.00	-25.78	Horizontal
2310.00	37.82	9.58	47.40	74.00	-26.60	Vertical
2390.00	40.47	9.73	50.20	74.00	-23.80	Vertical
Average value:						
Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2310.00	27.79	9.58	37.37	54.00	-16.63	Horizontal
2390.00	33.12	9.73	42.85	54.00	-11.15	Horizontal
2310.00	27.67	9.58	37.25	54.00	-16.75	Vertical
2390.00	33.84	9.73	43.57	54.00	-10.43	Vertical

Test Mode: 802.11n (HT20) Mode				Test channel: Highest		
Peak value:						
Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.50	44.10	9.91	54.01	74.00	-19.99	Horizontal
2500.00	38.35	9.94	48.29	74.00	-25.71	Horizontal
2483.50	45.69	9.91	55.60	74.00	-18.40	Vertical
2500.00	40.01	9.94	49.95	74.00	-24.05	Vertical
Average value:						
Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.50	33.70	9.91	43.61	54.00	-10.39	Horizontal
2500.00	28.64	9.94	38.58	54.00	-15.42	Horizontal
2483.50	34.90	9.91	44.81	54.00	-9.19	Vertical
2500.00	29.46	9.94	39.40	54.00	-14.60	Vertical

Remark: 1. Result=Reading + Factor

Radiated Band Edge:

Test Mode: 802.11n (HT40) Mode				Test channel: Lowest		
Peak value:						
Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2310.00	37.47	9.58	47.05	74.00	-26.95	Horizontal
2390.00	41.70	9.73	51.43	74.00	-22.57	Horizontal
2310.00	40.09	9.58	49.67	74.00	-24.33	Vertical
2390.00	43.01	9.73	52.74	74.00	-21.26	Vertical
Average value:						
Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2310.00	28.97	9.58	38.55	54.00	-15.45	Horizontal
2390.00	34.39	9.73	44.12	54.00	-9.88	Horizontal
2310.00	29.07	9.58	38.65	54.00	-15.35	Vertical
2390.00	33.38	9.73	43.11	54.00	-10.89	Vertical

Test Mode: 802.11n (HT40) Mode				Test channel: Highest		
Peak value:						
Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.50	44.01	9.91	53.92	74.00	-20.08	Horizontal
2500.00	39.03	9.94	48.97	74.00	-25.03	Horizontal
2483.50	45.82	9.91	55.73	74.00	-18.27	Vertical
2500.00	40.51	9.94	50.45	74.00	-23.55	Vertical
Average value:						
Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.50	33.40	9.91	43.31	54.00	-10.69	Horizontal
2500.00	30.64	9.94	40.58	54.00	-13.42	Horizontal
2483.50	34.90	9.91	44.81	54.00	-9.19	Vertical
2500.00	30.46	9.94	40.40	54.00	-13.60	Vertical

Remark: 1. Result=Reading + Factor

5. Maximum Conducted Output Power Test

5.1. Test Standard and Limit

Test Standard	FCC Part15 C Section 15.247 (b)(3)
Test Limit	1W (30dBm)

5.2. Test Setup



5.3. Test Procedure

1. Measure the duty cycle D of the transmitter output signal.
2. Set span to at least 1.5 times the OBW.
3. Set RBW = 1% to 5% of the OBW, not to exceed 1 MHz.
4. Set VBW ≥ [3 × RBW].
5. Number of points in sweep ≥ [2 × span / RBW].
6. Sweep time = auto.
7. Detector = RMS
8. Trace average at least 100 traces in power averaging (rms) mode; however, the number of traces to be averaged shall be increased above 100 as needed such that the average accurately represents the true average over the ON and OFF periods of the transmitter.
9. Compute power by integrating the spectrum across the OBW of the signal using the instrument's band power measurement function with band limits set equal to the OBW band edges. If the instrument does not have a band power function, then sum the spectrum levels (in power units) at intervals equal to the RBW extending across the entire OBW of the spectrum.
10. Add [10 log (1 / D)], where D is the duty cycle, to the measured power to compute the average power during the actual transmission times.

Note: The cable loss and attenuator loss were offset into measure device as amplitude offset.

5.4. Test Data

Pass

Please refer to Appendix C of the Appendix Test Data.

Test for Duty Cycle.

Please refer to Appendix G of the Appendix Test Data.

6. 6dB Bandwidth and 99% Occupied Bandwidth Test

6.1. Test Standard and Limit

Test Standard	FCC Part15 C Section 15.247 (a)(2)
Test Limit	≥500kHz

6.2. Test Setup



6.3. Test Procedure

1. Place the EUT on the table and set it in the transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
3. Set the spectrum analyzer as:
   RBW= 100kHz, VBW≥3*RBW
   Detector= Peak
   Trace mode= Max hold.
   Sweep- auto couple.
4. Mark the peak frequency and –6dB (upper and lower) frequency.
5. Repeat until all the rest channels are investigated.

99% Bandwidth:

RBW=1~5% OBW, VBW=3*RBW, Sweep Time= Auto, Detector= Peak, Trace= Max hold

6.4. Test Data

Pass

Please refer to Appendix A&B of the Appendix Test Data.

7. Maximum Power Spectral Density Test

7.1. Test Standard and Limit

Test Standard	FCC Part15 C Section
Test Limit	8dBm/3KHz

7.2. Test Setup



7.3. Test Procedure

1. Place the EUT on the table and set it in transmitting mode. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
2. Set the spectrum analyzer as 3kHz ≤ RBW ≤ 100kHz, VBW ≥ 3*RBW, Span = 1.5xDTS BW
3. Record the max. reading.
4. Repeat the above procedure until the measurements for all frequencies are completed.

7.4. Test Data

Pass

Please refer to Appendix D of the Appendix Test Data.

8. Conducted Spurious Emission and Band Edge Test

8.1. Test Standard and Limit

Test Standard	FCC Part15 C Section 15.247 (d)
Test Limit	In any 100 kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator in operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in15.209(a).

8.2. Test Setup



8.3. Test Procedure

Using the following spectrum analyzer setting:

1. Set the RBW = 100KHz.
2. Set the VBW = 300KHz.
3. Sweep time = auto couple.
4. Detector function = peak.
5. Trace mode = max hold.
6. Allow trace to fully stabilize.

8.4. Test Data

Pass

Please refer to Appendix E&F of the Appendix Test Data.

9. Antenna Requirement

9.1. Test Standard and Requirement

Test Standard	FCC Part15 Section 15.203 /247(c)
Requirement	1) 15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. 2) 15.247(c) (1)(i) requirement: Systems operating in the 2400-2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi.

9.2. Antenna Connected Construction

The antenna is a PCB antenna which permanently attached, and the best case gain of the antenna is 1.05dBi It complies with the standard requirement.

APPENDIX I -- TEST SETUP PHOTOGRAPH

Please refer to separated files Appendix I -- Test Setup Photograph_RF

APPENDIX II -- EXTERNAL PHOTOGRAPH

Please refer to separated files Appendix II -- External Photograph

APPENDIX III -- INTERNAL PHOTOGRAPH

Please refer to separated files Appendix III -- Internal Photograph

---------- End of Report ----------