



## Shenzhen Huaxia Testing Technology Co., Ltd.

1F., Block A of Tongsheng Technology Building, Huahui Road, Dalang Street, Longhua District, Shenzhen, China

Telephone: +86-755-26648640

Fax: +86-755-26648637

Website: [www.cqa-cert.com](http://www.cqa-cert.com)

Report Template Version: V05


Report Template Revision Date: 2021-11-03

# RF Exposure Evaluation Report

**Report No.:** CQASZ20240701495E -02  
**Applicant:** Shenzhen Itian Technology Co., LTD  
**Address of Applicant:** 6F, Building D, Phase 2nd, Anfeng Industrial Park, Dalang Street, Longhua District Shenzhen, China  
**Equipment Under Test (EUT):**  
**Product:** Magnetic Power Bank  
**Model No.:** MP08  
**Test Model No.:** MP08  
**Brand Name:** ITIAN  
**FCC ID:** 2AUDO-MP08  
**Standards:** 47 CFR Part 1.1307  
47 CFR Part 1.1310  
KDB 680106 D01 RF Exposure Wireless Charging Base App v04r01  
**Date of Receipt:** 2024-7-26  
**Date of Test:** 2024-7-26 to 2024-8-1  
**Date of Issue:** 2024-8-13  
**Test Result :** **PASS\***

\*In the configuration tested, the EUT complied with the standards specified above

**Tested By:**   
( Joe Wang )

**Reviewed By:**   
( Timo Lei )

**Approved By:**   
( Alex Wang )



## 1 Version

### Revision History Of Report

| Report No.            | Version | Description    | Issue Date |
|-----------------------|---------|----------------|------------|
| CQASZ20240701495E -02 | Rev.01  | Initial report | 2024-8-13  |

## 2 Contents

|                                                             | Page |
|-------------------------------------------------------------|------|
| 1 VERSION .....                                             | 2    |
| 2 CONTENTS .....                                            | 3    |
| .....                                                       | 3    |
| 3 GENERAL INFORMATION .....                                 | 4    |
| 3.1 CLIENT INFORMATION .....                                | 4    |
| 3.2 GENERAL DESCRIPTION OF EUT .....                        | 4    |
| 3.3 PRODUCT SPECIFICATION SUBJECTIVE TO THIS STANDARD ..... | 4    |
| 3.4 TEST ENVIRONMENT .....                                  | 5    |
| 3.5 DESCRIPTION OF SUPPORT UNITS .....                      | 5    |
| 3.6 TEST LOCATION .....                                     | 6    |
| 3.7 TEST FACILITY .....                                     | 6    |
| 3.8 EQUIPMENT LIST .....                                    | 6    |
| 3.9 TEST SOFTWARE .....                                     | 7    |
| 3.10 .....                                                  | 8    |
| 4 RF EXPOSURE EVALUATION .....                              | 8    |
| 4.1 RF EXPOSURE COMPLIANCE REQUIREMENT .....                | 8    |
| 4.1.1 Limits .....                                          | 8    |
| 4.1.2 Test Procedure .....                                  | 8    |
| 4.1.3 Test Setup .....                                      | 10   |
| 4.1.4 Test Results .....                                    | 10   |
| 4.1.5 Test Results .....                                    | 10   |
| 4.1.6 Test condition: Mode c .....                          | 11   |
| APPENDIX A: PHOTOGRAPHS OF TEST SETUP .....                 | 12   |

### 3 General Information

#### 3.1 Client Information

|                          |                                                                                                    |
|--------------------------|----------------------------------------------------------------------------------------------------|
| Applicant:               | Shenzhen Itian Technology Co., LTD                                                                 |
| Address of Applicant:    | 6F, Building D, Phase 2nd, Anfeng Industrial Park, Dalang Street, Longhua District Shenzhen, China |
| Manufacturer:            | Shenzhen Itian Technology Co., LTD                                                                 |
| Address of Manufacturer: | 6F, Building D, Phase 2nd, Anfeng Industrial Park, Dalang Street, Longhua District Shenzhen, China |
| Factory:                 | Shenzhen Itian Technology Co., LTD                                                                 |
| Address of Factory:      | 6F, Building D, Phase 2nd, Anfeng Industrial Park, Dalang Street, Longhua District Shenzhen, China |

#### 3.2 General Description of EUT

|                   |                                                                                                            |
|-------------------|------------------------------------------------------------------------------------------------------------|
| Product Name:     | Magnetic Power Bank                                                                                        |
| Model No.:        | MP08                                                                                                       |
| Test Model No.:   | MP08                                                                                                       |
| Brand Name:       | ITIAN                                                                                                      |
| Software Version: | V1.0                                                                                                       |
| Hardware Version: | V1.0                                                                                                       |
| EUT Power Supply: | DC 5V $\overline{=}$ 2A, 9V $\overline{=}$ 2A ,12V $\overline{=}$ 1.5A<br>Battery: 5000mAh/ 19.50Wh/ 3.90V |

#### 3.3 Product Specification subjective to this standard

|                            |                   |
|----------------------------|-------------------|
| Equipment Category:        | Non-ISM frequency |
| Operation Frequency range: | 115kHz-205kHz     |
| Modulation Type:           | ASK               |
| Antenna Type:              | Induction coil    |
| Antenna Gain:              | 0dBi              |

Note:

1. In section 15.31(m), regards to the operating frequency range less 1 MHz.

### 3.4 Test Environment

| Operating Environment:                                                                                                                             |                                           |
|----------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------|
| Temperature:                                                                                                                                       | 25.5 °C                                   |
| Humidity:                                                                                                                                          | 53 % RH                                   |
| Atmospheric Pressure:                                                                                                                              | 1009 mbar                                 |
| Test Mode:                                                                                                                                         |                                           |
| Mode a:                                                                                                                                            | Keep the EUT Charging+Wireless Out Put 5W |
| Mode b:                                                                                                                                            | Keep the EUT Wireless Out Put 5W          |
| Mode c:                                                                                                                                            | Keep the EUT Wireless Out Put 7.5W        |
| Mode d:                                                                                                                                            | Keep the EUT Wireless Out Put 10W(Max)    |
| Note: The above test modes all include full load,empty load,and half load, The worst-case state reflected in this report is the fully loaded state |                                           |

### 3.5 Description of Support Units

The EUT has been tested with associated equipment below.

#### 1) Support equipment

| Description          | Manufacturer | Model No.       | Certification | Supplied by |
|----------------------|--------------|-----------------|---------------|-------------|
| Adapter              | /            | LPL-C010050200Z | /             | CQA         |
| Wireless charge load | /            | /               | /             | CQA         |

#### 2) Cable

| Cable No. | Description | Manufacturer | Cable Type/Length | Supplied by |
|-----------|-------------|--------------|-------------------|-------------|
| /         | /           | /            | /                 | /           |

### 3.6 Test Location

Shenzhen Huaxia Testing Technology Co., Ltd.

1F., Block A of Tongsheng Technology Building, Huahui Road, Dalang Street, Longhua District, Shenzhen, China

### 3.7 Test Facility

• **A2LA (Certificate No. 4742.01)**

Shenzhen Huaxia Testing Technology Co., Ltd., Shenzhen EMC Laboratory is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 4742.01.

• **FCC Registration No.: 522263**

Shenzhen Huaxia Testing Technology Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration No.:522263

### 3.8 Equipment List

| Test Equipment                               | Manufacturer                    | Model No.      | Instrument No. | Calibration Date | Calibration Due Date |
|----------------------------------------------|---------------------------------|----------------|----------------|------------------|----------------------|
| Magnetic Amplitude and Gradient Probe System | Schmid & Partner Engineering AG | MAGPy-8H3D+E3D | 3096           | 2024/3/12        | 2025/3/12            |
| Magnetic Amplitude and Gradient Probe System | Schmid & Partner Engineering AG | MAGPy-DAS      | 3093           | 2024/3/12        | 2025/3/12            |

### 3.9 Test Software

| Software name | Manufacturer                       | Model      | Version |
|---------------|------------------------------------|------------|---------|
| MAGPy V2.0    | Schmid & Partner<br>Engineering AG | MAGPy V2.0 | V2.0    |

### 3.10

## 4 RF Exposure Evaluation

### 4.1 RF Exposure Compliance Requirement

#### 4.1.1 Limits

According to FCC Part1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in part1.1307(b)

TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

| Frequency range (MHz)                                          | Electric field strength (V/m) | Magnetic field strength (A/m) | Power density (mW/cm <sup>2</sup> ) | Averaging time (minutes) |
|----------------------------------------------------------------|-------------------------------|-------------------------------|-------------------------------------|--------------------------|
| <b>(A) Limits for Occupational/Controlled Exposures</b>        |                               |                               |                                     |                          |
| 0.3–3.0 .....                                                  | 614                           | 1.63                          | *(100)                              | 6                        |
| 3.0–30 .....                                                   | 1842/f                        | 4.89/f                        | *(900/f <sup>2</sup> )              | 6                        |
| 30–300 .....                                                   | 61.4                          | 0.163                         | 1.0                                 | 6                        |
| 300–1500 .....                                                 | .....                         | .....                         | f/300                               | 6                        |
| 1500–100,000 .....                                             | .....                         | .....                         | 5                                   | 6                        |
| <b>(B) Limits for General Population/Uncontrolled Exposure</b> |                               |                               |                                     |                          |
| 0.3–1.34 .....                                                 | 614                           | 1.63                          | *(100)                              | 30                       |
| 1.34–30 .....                                                  | 824/f                         | 2.19/f                        | *(180/f <sup>2</sup> )              | 30                       |
| 30–300 .....                                                   | 27.5                          | 0.073                         | 0.2                                 | 30                       |
| 300–1500 .....                                                 | .....                         | .....                         | f/1500                              | 30                       |
| 1500–100,000 .....                                             | .....                         | .....                         | 1.0                                 | 30                       |

Note 1: f = frequency in MHz ; \*Plane-wave equivalent power density

Note 2: For the applicable limit, see FCC 1.1310, 680106 D01 RF Exposure Wireless Charging Apps v04

Note 3: Emissions between 100 kHz to 300 kHz should be assessed versus the limits at 300 kHz in Table 1 of Section 1.1310: 614 V/m and 1.63 A/m. A KDB inquiry is required to determine the applicable exposure limits below 100 kHz.

Note 4: The aggregate H-field strengths 20 cm above the top surface from all simultaneous transmitting coils are demonstrated to be less than 50% of the MPE limit .

#### 4.1.2 Test Procedure


- The RF exposure test was performed in anechoic chamber.
- Perform H-field measurements for each edge/top surface of the host/client pair at every 2 cm, starting from as close as possible out to 20 cm.
- The highest emission level was recorded and compared with limit.
- The EUT was measured according to the dictates of TCB Workshop "41-Part-18-&-Wireless-Power-Transfer - April 27,2022"

Equipment Approval Considerations item 5 b) of KDB 680106 D01 Wireless Power Transfer v04

| Requirement                                                               | Device                                                                   |
|---------------------------------------------------------------------------|--------------------------------------------------------------------------|
| 1.Power transfer frequency is less than 1 MHz                             | Yes. The operating frequencies are.Operating Frequency: 115 kHz - 205KHz |
| 2. Output power from each primary coil is less than or equal to 15 watts. | Yes. The maximum output power is:Wireless Output: 10W(Max)               |
| 3. The system may consist of more than one                                | Yes. EUT has a source primary coil                                       |

|                                                                                                                                                                                                                                                                                                        |                                                                                                                                                                                              |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| source primary coils, charging one or more clients.<br>If more than one primary coil is present, the coil pairs may be powered on at the same time.                                                                                                                                                    |                                                                                                                                                                                              |
| 4. Client device is placed directly in contact with the transmitter.                                                                                                                                                                                                                                   | Yes. The client device is placed directly in contact with the transmitter.                                                                                                                   |
| 5. Mobile exposure conditions only (portable exposure conditions are not covered by this exclusion)                                                                                                                                                                                                    | No, This EUT is mounted under a desk/table and the user's legs may be in direct contact with the device for long periods of time, so this device was evaluated as a portable WPT             |
| 6. The aggregate H-field strengths anywhere at or beyond 20 cm surrounding the device, and 20cm away from the surface from all coils that by design can simultaneously transmit, and while those coils are simultaneously energized, are demonstrated to be less than 50% of the applicable MPE limit. | Yes, The H-field measurements for each edge/top surface of the host/client pair at every 2cm, starting from as close as possible out to 20cm were also evaluated for portable use condition. |

#### 4.1.3 Test Setup



Note: Perform H-field measurements for each edge/top surface of the host/client pair at every 2 cm, starting from as close as possible out to 20 cm

#### 4.1.4 Test Results

For portable exposure condition:

The client running mode (no load, half load, full load) only shows that the client device is in the worst state when it is fully loaded.

H-field measurements taken every 2 cm (starting as close to 20 cm as possible) on each edge/top surface of the host/client pair were also evaluated for portable use conditions. The report reflects data for the worst 0 cm test distance mode only.

Test condition 1: Mode c operating mode with client device (full load status of client device)

-test distance: 0cm

#### 4.1.5 Test Results

For portable exposure condition:

Operating modes with client device (1 %, 50%, 99% battery status of client device) have been test, only show the data of worst case of 1% battery status of client device.

H-field measurements taken every 2 cm (starting as close to 20 cm as possible) on each edge/top surface of the host/client pair were also evaluated for portable use conditions. The report reflects data for the worst 0 cm test distance mode only.

Test condition 1: Mode 3 operating mode with client device (1 % battery status of client device) -test distance: 0cm

#### 4.1.6 Test condition: Mode c

H-field strength test result:

test distance: 0cm

I-Measurement results directly tested using MAGPy.

| Maximum permissible Exposure |            |                   |               |              |
|------------------------------|------------|-------------------|---------------|--------------|
| Battery levels               | Test sides | Test distance(cm) | E -field(V/m) | H-field(A/m) |
| <1%                          | Top        | 0                 | 26.9          | 0.19         |
| <1%                          | Left       | 0                 | 16.6          | 0.13         |
| <1%                          | Right      | 0                 | 17.5          | 0.15         |
| <1%                          | Front      | 0                 | 51.3          | 0.31         |
| <1%                          | Back       | 0                 | 50.1          | 0.21         |
| <1%                          | Bottom     | 0                 | 66.2          | 0.42         |
| Limit                        |            |                   | 614           | 1.63         |
| test result                  |            |                   | PASS          | PASS         |


J-When setting MAGPy to select compliance location as probe tip, the

K-measured value is extrapolated to 0mm as the result.


| Maximum permissible Exposure |            |                   |               |              |
|------------------------------|------------|-------------------|---------------|--------------|
| Battery levels               | Test sides | Test distance(cm) | E -field(V/m) | H-field(A/m) |
| <1%                          | Top        | 0                 | 24.5          | 0.13         |
| <1%                          | Left       | 0                 | 17.4          | 0.09         |
| <1%                          | Right      | 0                 | 14.1          | 0.13         |
| <1%                          | Front      | 0                 | 45.2          | 0.28         |
| <1%                          | Back       | 0                 | 46.3          | 0.10         |
| <1%                          | Bottom     | 0                 | 62.6          | 0.31         |
| Limit                        |            |                   | 614           | 1.63         |
| test result                  |            |                   | PASS          | PASS         |

## APPENDIX A: PHOTOGRAPHS OF TEST SETUP

DC



AC



\*\*\* END OF REROPT \*\*\*