



TESTING LABORATORY
CERTIFICATE#4323.01



SAR EVALUATION REPORT

For

Shanghai ZoomSmart Technology Co., Ltd

Room 802 Hengxi Road No.809 Pujiang Town Minhang district, Shanghai, 201114 China

FCC ID: 2AUFL-LT702

Report Type: Original Report		Product Type: Rugged Tablet	
Project Engineer:	Chris Wang	<i>Chris. Wang</i>	
Report Number:	RSHD200817001-20B		
Report Date:	2020-12-08		
Reviewed By:	Oscar Ye	<i>Oscar.Ye</i>	
	EMC Manager		
Test Laboratory:	Bay Area Compliance Laboratories Corp. (Kunshan) No.248 Chenghu Road,Kunshan,Jiangsu province,China Tel: +86-0512-86175000 Fax: +86-0512-88934268 www.baclcorp.com.cn		

Attestation of Test Results			
EUT Information	EUT Description	Rugged Tablet	
	Tested Model	LT702	
	FCC ID	2AUFL-LT702	
	Serial Number	RSHD200817001	
	Test Date	2020-08-23~ 2020-08-30	
MODE		Max. SAR Level(s) Reported(W/kg)	Limit (W/kg)
Body supported Mode	GSM 850	0.25 W/kg 1g SAR	1.6
	PCS 1900	0.55 W/kg 1g SAR	
	WCDMA 2	0.44 W/kg 1g SAR	
	WCDMA 5	0.69 W/kg 1g SAR	
	CDMA	0.75 W/kg 1g SAR	
	LTE Band 2	0.66 W/kg 1g SAR	
	LTE Band 4	0.56 W/kg 1g SAR	
	LTE Band 5	0.74 W/kg 1g SAR	
	LTE Band 7	0.67 W/kg 1g SAR	
	LTE Band 17	0.84 W/kg 1g SAR	
	LTE Band 41	0.88 W/kg 1g SAR	
	2.4GHz WLAN	0.49 W/kg 1g SAR	
	5GHz WLAN	0.62 W/kg 1g SAR	
	Hotspot	1.35 W/kg 1g SAR	
	Simultaneous	1.35 W/kg 1g SAR	
Applicable Standards	FCC 47 CFR part 2.1093 Radiofrequency radiation exposure evaluation: portable devices		
	RF Exposure Procedures: TCB Workshop April 2019		
	IEEE1528:2013 IEEE Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques		
	IEC 62209-1:2016 Measurement procedure for the assessment of specific absorption rate of human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices – Part 1: Devices used next to the ear (Frequency range of 300 MHz to 6 GHz)		
	IEC 62209-2:2010 Human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices-Human models, instrumentation, and procedures-Part 2: Procedure to determine the specific absorption rate (SAR) for wireless communication devices used in close proximity to the human body (frequency range of 30 MHz to 6 GHz)		
	KDB procedures KDB 447498 D01 General RF Exposure Guidance v06 KDB 648474 D04 Handset SAR v01r03 KDB 865664 D01 SAR Measurement 100 MHz to 6 GHz v01r04 KDB 865664 D02 RF Exposure Reporting v01r02 KDB 941225 D01 3G SAR Procedures v03r01 KDB 941225 D05 SAR for LTE Devices v02r05 KDB 248227 D01 802 11 Wi-Fi SAR v02r02		
	Note: This wireless device has been shown to be capable of compliance for localized specific absorption rate (SAR) for General Population/Uncontrolled Exposure limits specified in FCC 47 CFR part 2.1093 and has been tested in accordance with the measurement procedures specified in IEEE 1528-2013 and RF exposure KDB procedures. The results and statements contained in this report pertain only to the device(s) evaluated.		

TABLE OF CONTENTS

DOCUMENT REVISION HISTORY	4
EUT DESCRIPTION	5
TECHNICAL SPECIFICATION	5
REFERENCE, STANDARDS, AND GUIDELINES.....	6
SAR LIMITS	6
FACILITIES.....	7
DESCRIPTION OF TEST SYSTEM	8
EQUIPMENT LIST AND CALIBRATION	15
EQUIPMENTS LIST & CALIBRATION INFORMATION	15
SAR MEASUREMENT SYSTEM VERIFICATION	16
LIQUID VERIFICATION	16
SYSTEM ACCURACY VERIFICATION	18
SAR SYSTEM VALIDATION DATA	19
EUT TEST STRATEGY AND METHODOLOGY	27
TEST POSITIONS FOR DEVICE OPERATING NEXT TO A PERSON’S EAR	27
CHEEK/TOUCH POSITION	28
EAR/TILT POSITION	28
TEST POSITIONS FOR BODY-WORN AND OTHER CONFIGURATIONS	29
TEST DISTANCE FOR SAR EVALUATION	29
SAR EVALUATION PROCEDURE	30
CONDUCTED OUTPUT POWER MEASUREMENT	31
PROVISION APPLICABLE	31
TEST PROCEDURE	31
RADIO CONFIGURATION	31
MAXIMUM TARGET OUTPUT POWER	36
TEST RESULTS:	37
STANDALONE SAR TEST EXCLUSION CONSIDERATIONS	56
STANDALONE SAR TEST EXCLUSION CONSIDERATIONS	57
STANDALONE SAR ESTIMATION:	58
STANDALONE SAR TEST EXCLUSION CONSIDERATIONS:	58
SAR TEST EXCLUSION FOR THE EUT EDGE CONSIDERATIONS RESULT	59
SAR TEST EXCLUSION FOR THE EUT EDGE CONSIDERATIONS DETIAL:	59
SAR MEASUREMENT RESULTS.....	60
SAR TEST DATA	60
SAR SIMULTANEOUS TRANSMISSION DESCRIPTION	72
SAR PLOTS.....	73
APPENDIX A MEASUREMENT UNCERTAINTY	88
APPENDIX B EUT TEST POSITION PHOTOS	90
APPENDIX C CALIBRATION CERTIFICATES	93

DOCUMENT REVISION HISTORY

Revision Number	Report Number	Description of Revision	Date of Revision
1.0	RSHD200817001-20B	Original Report	2020-12-08

EUT DESCRIPTION

This report has been prepared on behalf of **Shanghai ZoomSmart Technology Co., Ltd** and their product **Rugged Tablet**, Model: **LT702**, FCC ID: **2AUFL-LT702** or the EUT (Equipment under Test) as referred to in the rest of this report.

**All measurement and test data in this report was gathered from production sample serial number: RKSA200310001(Assigned by BACL).The EUT supplied by the applicant was received on 2020-08-10.*

Technical Specification

Device Type:	Rugged Tablet
Exposure Category:	Population / Uncontrolled
Antenna Type(s):	FPC antenna
Body-Worn Accessories:	None
Face-Head Accessories:	None
Operation Mode :	GSM Voice, GPRS Data, EGPRS Data, WCDMA(R99 (Voice+Data), HSDPA/HSUPA) CDMA FDD-LTE/ TDD-LTE WLAN2.4G/WLAN 5G Bluetooth
Frequency Band:	GSM/GPRS/EGPRS 850: 824-849 MHz(TX), 869-894 MHz(RX) GSM/GPRS/EGPRS 1900: 1850-1910 MHz(TX), 1930-1990 MHz(RX) WCDMA Band II: 1850-1910 MHz(TX), 1930-1990 MHz(RX) WCDMA Band V: 824-849 MHz(TX), 869-894 MHz(RX) CDMA850 Band: 824-849 MHz(TX), 869-894 MHz(RX) LTE Band 2: 1850-1910 MHz(TX), 1930MHz-1990 MHz(RX) LTE Band 4: 1710-1755 MHz(TX), 2110-2155 MHz(RX) LTE Band 5: 824-849 MHz(TX), 869-894 MHz(RX) LTE Band 7: 2500-2570 MHz(TX), 2620-2690 MHz(RX) LTE Band 17: 704-716 MHz(TX), 734-746 MHz(RX) LTE Band 41: 2555-2655 MHz(TX), 2555-2655 MHz(RX) 2.4G Wi-Fi: 2412~2462 MHz (802.11b/g/n20), 2422~2452 MHz (802.11n40) BT/BLE(1Mbps): 2402-2480MHz 5G Wi-Fi B1: 5180-5240 MHz, B4: 5745-5825 MHz
Conducted RF Power:	GSM 850: 33.52 dBm; PCS 1900: 31.59 dBm WCDMA Band 2: 20.97dBm;WCDMA Band 5: 22.54 dBm CDMA BC0:22.31 dBm LTE Band 2: 22.09 dBm; LTE Band 4: 21.86 dBm LTE Band 5: 24.34 dBm ;LTE Band 7: 21.71 dBm LTE Band 17: 22.22 dBm; LTE Band 41: 22.21 dBm WLAN 2.4G: 14.68 dBm; WLAN 5.2G: 14.48 dBm WLAN 5.8G: 10.51 dBm Bluetooth(BDR/EDR); 7.08 dBm; BLE(1Mbps):1.59dBm
Dimensions (L*W*H):	20.8 cm (H) x 12.8 cm (W) x 1.3 cm (D)
Power Source:	DC 3.8V from battery and DC 5V from external power supply
Normal Operation:	Body Supported

REFERENCE, STANDARDS, AND GUIDELINES

FCC:

The Report and Order requires routine SAR evaluation prior to equipment authorization of portable transmitter devices, including portable telephones. For consumer products, the applicable limit is 1.6 mW/g as recommended by the ANSI/IEEE standard C95.1-1992 [6] for an uncontrolled environment (Paragraph 65). According to the Supplement C of OET Bulletin 65 "Evaluating Compliance with FCC Guide-lines for Human Exposure to Radio frequency Electromagnetic Fields", released on Jun 29, 2001 by the FCC, the device should be evaluated at maximum output power (radiated from the antenna) under "worst-case" conditions for normal or intended use, incorporating normal antenna operating positions, device peak performance frequencies and positions for maximum RF energy coupling.

This report describes the methodology and results of experiments performed on wireless data terminal. The objective was to determine if there is RF radiation and if radiation is found, what is the extent of radiation with respect to safety limits. SAR (Specific Absorption Rate) is the measure of RF exposure determined by the amount of RF energy absorbed by human body (or its parts) – to determine how the RF energy couples to the body or head which is a primary health concern for body worn devices. The limit below which the exposure to RF is considered safe by regulatory bodies in North America is 1.6 mW/g average over 1 gram of tissue mass.

SAR Limits

FCC Limit

EXPOSURE LIMITS	SAR (W/kg)	
	(General Population / Uncontrolled Exposure Environment)	(Occupational / Controlled Exposure Environment)
Spatial Average (averaged over the whole body)	0.08	0.4
Spatial Peak (averaged over any 1 g of tissue)	1.60	8.0
Spatial Peak (hands/wrists/feet/ankles averaged over 10 g)	4.0	20.0

Population/Uncontrolled Environments are defined as locations where there is the exposure of individual who have no knowledge or control of their exposure.

Occupational/Controlled Environments are defined as locations where there is exposure that may be incurred by people who are aware of the potential for exposure (i.e. as a result of employment or occupation).


General Population/Uncontrolled environments Spatial Peak limit 1.6W/kg for 1g Body SAR and 4.0 W/kg for 10g Extremity SAR applied to the EUT.

FACILITIES


The test site used by Bay Area Compliance Laboratories Corp. (Kunshan) to collect test data is located on the No.248 Chenghu Road, Kunshan, Jiangsu province, China.

Bay Area Compliance Laboratories Corp. (Kunshan) Lab is accredited to ISO/IEC 17025 by A2LA (Lab code: 4323.01) and the FCC designation No. CN1185 under the FCC KDB 974614 D01 and CAB identifier CN0004 under the ISED requirement. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-2014.

These measurements were performed with the automated near-field scanning system DASY6 from Schmid & Partner Engineering AG (SPEAG) which is the Fifth generation of the system shown in the figure hereinafter:



The DASY6 system for performing compliance tests consists of the following items:



- A standard high precision 6-axis robot (Staubli TX=RX family) with controller, teach pendant and software. An arm extension for accommodating the data acquisition electronics (DAE).
- An isotropic field probe optimized and calibrated for the targeted measurement.
- A data acquisition electronics (DAE) which performs the signal application, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. The unit is battery powered with standard or rechargeable batteries. The signal is optically transmitted to the EOC.
- The Electro-optical converter (EOC) performs the conversion from optical to electrical signals for the digital communication to the DAE. To use optical surface detection, a special version of the EOC is required. The EOC signal is transmitted to the measurement server.
- The function of the measurement server is to perform the time critical tasks such as signal filtering, control of the robot operation and fast movement interrupts.
- The Light Beam used is for probe alignment. This improves the (absolute) accuracy of the probe positioning.
- A computer running Win7 professional operating system and the DASY52 software.
- Remote control and teach pendant as well as additional circuitry for robot safety such as warning lamps, etc.
- The phantom, the device holder and other accessories according to the targeted measurement.

DASY6 Measurement Server

The DASY6 measurement server is based on a PC/104 CPU board with a 400 MHz Intel ULV Celeron, 128 MB chip-disk and 128 MB RAM. The necessary circuits for communication with the DAE4 (or DAE3) electronics box, as well as the 16-bit AD converter system for optical detection and digital I/O interface are contained on the DASY6 I/O board, which is directly connected to the PC/104 bus of the CPU board.



The measurement server performs all real-time data evaluations of field measurements and surface detection, controls robot movements, and handles safety operations. The PC operating system cannot interfere with these time-critical processes. All connections are supervised by a watchdog, and disconnection of any of the cables to the measurement server will automatically disarm the robot and disable all program- controlled robot movements. Furthermore, the measurement server is equipped with an expansion port, which is reserved for future applications. Please note that this expansion port does not have a standardized pinout, and therefore only devices provided by SPEAG can be connected. Connection of devices from any other supplier could seriously damage the measurement server.

Data Acquisition Electronics

The data acquisition electronics (DAE4) consist of a highly sensitive electrometer-grade preamplifier with auto-zeroing, a channel and gain-switching multiplexer, a fast 16 bit AD-converter and a command decoder with a control logic unit. Transmission to the measurement server is accomplished through an optical downlink for data and status information, as well as an optical uplink for commands and the clock.

The mechanical probe mounting device includes two different sensor systems for frontal and sideways probe contacts. They are used for mechanical surface detection and probe collision detection.

The input impedance of both the DAE4 as well as of the DAE3 box is 200M Ω ; the inputs are symmetrical and floating. Common mode rejection is above 80 dB.

EX3DV4 E-Field Probes

Frequency	10 MHz to > 6 GHz Linearity: ± 0.2 dB (30 MHz to 6 GHz)
Directivity	± 0.3 dB in TSL (rotation around probe axis) ± 0.5 dB in TSL (rotation normal to probe axis)
Dynamic Range	10 μ W/g to > 100 mW/g Linearity: ± 0.2 dB (noise: typically < 1 μ W/g)
Dimensions	Overall length: 337 mm (Tip: 20 mm) Tip diameter: 2.5 mm (Body: 12 mm) Typical distance from probe tip to dipole centers: 1 mm
Application	High precision dosimetric measurements in any exposure scenario (e.g., very strong gradient fields); the only probe that enables compliance testing for frequencies up to 6 GHz with precision of better 30%.
Compatibility	DASY3, DASY4, DASY52 SAR and higher, EASY4/MRI

SAM Twin Phantom

The SAM Twin Phantom (shown in front of DASY6) is a fiberglass shell phantom with shell thickness 2 mm, except in the ear region where the thickness is increased to 6 mm. The phantom has three measurement areas: 1) Left Head, 2) Right Head, and 3) Flat Section. For larger devices, the use of the ELI-Phantom (shown behind DASY6) is required. For devices such as glasses with a wireless link, the Face Down Phantom is the most suitable (between the SAM Twin and ELI phantoms).

When the phantom is mounted inside allocated slot of the DASY6 platform, phantom reference points can be taught directly in the DASY5 V5.2 software. When the DASY6 platform is used to mount the Phantom, some of the phantom teaching points cannot be reached by the robot in DASY5 V5.2. A special tool called P1a-P2aX-Former is provided to transform two of the three points, P1 and P2, to reachable locations. To use these new teaching points, a revised phantom configuration file is required.


In addition to our standard broadband liquids, the phantom can be used with the following tissue simulating liquids:

Sugar-water-based liquids can be left permanently in the phantom. Always cover the liquid when the system is not in use to prevent changes in liquid parameters due to water evaporation.

DGBE-based liquids should be used with care. As DGBE is a softener for most plastics, the liquid should be taken out of the phantom, and the phantom should be dried when the system is not in use (desirable at least once a week).

Do not use other organic solvents without previously testing the solvent resistivity of the phantom.

Approximately 25 liters of liquid is required to fill the SAM Twin phantom.




ELI Phantom

The ELI phantom is intended for compliance testing of handheld and body-mounted wireless devices in the frequency range of 30MHz to 6 GHz. ELI is fully compatible with the latest draft of the standard IEC 62209-2 and the use of all known tissue simulating liquids. ELI has been optimized for performance and can be integrated into a SPEAG standard phantom table. A cover is provided to prevent evaporation of water and changes in liquid parameters. Reference markings on the phantom allow installation of the complete setup, including all predefined phantom positions and measurement grids, by teaching three points.

The phantom can be used with the following tissue simulating liquids:

- Sugar-water-based liquids can be left permanently in the phantom. Always cover the liquid when the system is not in use to prevent changes in liquid parameters due to water evaporation.
- DGBE-based liquids should be used with care. As DGBE is a softener for most plastics, the liquid should be taken out of the phantom, and the phantom should be dried when the system is not in use (desirable at least once a week).
- Do not use other organic solvents without previously testing the solvent resistivity of the phantom.

Approximately 25 liters of liquid is required to fill the ELI phantom.



Robots

The DASY6 system uses the high-precision industrial robots TX60L, TX90XL, and RX160L from Staubli SA (France). The TX robot family - the successor of the well-known RX robot family - continues to offer the features important for DASY6 applications:

- High precision (repeatability 0.02mm)
- High reliability (industrial design)
- Low maintenance costs (virtually maintenance free due to direct drive gears; no belt drives)
- Jerk-free straight movements (brushless synchrony motors; no stepper motors)
- Low ELF interference (motor control fields shielded via the closed metallic construction shields)

The robots are controlled by the Staubli CS8c robot controllers. All information regarding the use and maintenance of the robot arm and the robot controller is provided

Area Scans

Area scans are defined prior to the measurement process being executed with a user defined variable spacing between each measurement point (integral) allowing low uncertainty measurements to be conducted. Scans defined for FCC applications utilize a 15mm 2 step integral, with 1.5mm interpolation used to locate the peak SAR area used for zoom scan assessments.

Where the system identifies multiple SAR peaks (which are within 25% of peak value) the system will provide the user with the option of assessing each peak location individually for zoom scan averaging.

Zoom Scan (Cube Scan Averaging)

The averaging zoom scan volume utilized in the DASY5 software is in the shape of a cube and the side dimension of a 1 g or 10 g mass is dependent on the density of the liquid representing the simulated tissue. A density of 1000 kg/m³ is used to represent the head and body tissue density and not the phantom liquid density, in order to be consistent with the definition of the liquid dielectric properties, i.e. the side length of the 1g cube is 10mm, with the side length of the 10g cube is 21.5mm.

When the cube intersects with the surface of the phantom, it is oriented so that 3 vertices touch the surface of the shell or the center of a face is tangent to the surface. The face of the cube closest to the surface is modified in order to conform to the tangent surface.

The zoom scan integer steps can be user defined so as to reduce uncertainty, but normal practice for typical test applications (including FCC) utilize a physical step of 7 x 7 x 7 (5mmx5mmx5mm) providing a volume of 30 mm in the X & Y & Z axis.

Calibration Frequency Points for EX3DV4 E-Field Probes SN: 7557 Calibrated: 2019/10/04

Calibration Frequency Point(MHz)	Frequency Range(MHz)		Conversion Factor		
	From	To	X	Y	Z
750 Head	650	810	10.41	10.41	10.41
835 Head	810	935	10.10	10.10	10.10
1750 Head	1650	1810	8.67	8.67	8.67
1900 Head	1810	2000	8.36	8.36	8.36
2300 Head	2200	2399	7.79	7.79	7.79
2450 Head	2399	2500	7.41	7.41	7.41
2600 Head	2500	2700	7.21	7.21	7.21
5250 Head	5140	5360	5.38	5.38	5.38
5600 Head	5490	5700	4.75	4.75	4.75
5800 Head	5700	5910	4.70	4.70	4.70

Tissue Dielectric Parameters for Head and Body Phantoms

The head tissue dielectric parameters recommended by the IEC 62209-1:2016

Recommended Tissue Dielectric Parameters for Head liquid

Table A.3 – Dielectric properties of the head tissue-equivalent liquid

Frequency MHz	Relative permittivity ϵ_r	Conductivity (σ) S/m
300	45,3	0,87
450	43,5	0,87
750	41,9	0,89
835	41,5	0,90
900	41,5	0,97
1 450	40,5	1,20
1 500	40,4	1,23
1 640	40,2	1,31
1 750	40,1	1,37
1 800	40,0	1,40
1 900	40,0	1,40
2 000	40,0	1,40
2 100	39,8	1,49
2 300	39,5	1,67
2 450	39,2	1,80
2 600	39,0	1,96
3 000	38,5	2,40
3 500	37,9	2,91
4 000	37,4	3,43
4 500	36,8	3,94
5 000	36,2	4,45
5 200	36,0	4,66
5 400	35,8	4,86
5 600	35,5	5,07
5 800	35,3	5,27
6 000	35,1	5,48

NOTE For convenience, permittivity and conductivity values at those frequencies which are not part of the original data provided by Drossos et al. [33] or the extension to 5 800 MHz are provided (i.e. the values shown *in italics*). These values were linearly interpolated between the values in this table that are immediately above and below these values, except the values at 6 000 MHz that were linearly extrapolated from the values at 3 000 MHz and 5 800 MHz.

Note:

- 1, Effective February 19, 2019, FCC has permitted the use of single head-tissue simulating liquid specified in IEC 62209-1 for all SAR tests.
- 2, Mix and Match of traditional FCC SAR TSLs and IEC 62209-1 TSL in a single application is not permitted TSL can be changed in a Permissive Change.
- 3, If SAR increases and original SAR > 1.2 W/kg, additional SAR measurements will be required IEC 62209-1 TSL is an alternative, not mandatory at this time.
- 4, If FCC parameters are used, $\pm 5\%$ tolerance. If IEC parameters, $\pm 10\%$.
- 5, In this case, IEC parameters applied.


EQUIPMENT LIST AND CALIBRATION

Equipments List & Calibration Information

Equipment	Model	S/N	Calibration Date	Calibration Due Date
DASY5 Test Software	DASY52 52.10.2	N/A	N/A	N/A
DASY6 Measurement Server	DASY6 6.0.31	N/A	N/A	N/A
Data Acquisition Electronics	DAE4	527	2020/07/9	2021/07/8
E-Field Probe	EX3DV4	7557	2019/10/04	2020/10/03
Mounting Device	MD4HHTV5	SD 000 H01 KA	N/A	N/A
Twin-SAM Phantom	QD 000 P41 AA	1963	N/A	N/A
Dipole, 750MHz	D750V3	1166	2018/09/05	2021/09/04
Dipole, 835MHz	D835V2	445	2019/12/17	2022/12/16
Dipole, 1750MHz	D1750V2	1140	2018/06/25	2021/06/24
Dipole, 1900MHz	D1900V2	5d206	2018/09/11	2021/09/10
Dipole, 2450MHz	D2450V2	970	2018/06/26	2021/06/25
Dipole, 2600MHz	D2600V2	1162	2019/10/02	2022/10/01
Dipole, 5000MHz	D5GHzV2	1296	2019/10/03	2022/10/02
Simulated Tissue Liquid Head	HBBL600-6000V6	180611-3	Each Time	
Network Analyzer	8753B	3625A00809	2019/12/14	2020/12/13
Dielectric Assessment Kit	DAK-3.5	SM DAK 300AB	N/A	N/A
Signal Generator	N5182B	MY53051592	2019/12/14	2020/12/13
Power Meter	E4419B	GB43312421	2020/08/04	2021/08/03
Power Amplifier	5S1G4	71377	N/A	N/A
Directional Coupler	4242-10	3307	N/A	N/A
Attenuator	3dB	5402	N/A	N/A
Attenuator	10dB	AU 3842	N/A	N/A

SAR MEASUREMENT SYSTEM VERIFICATION

Liquid Verification



Liquid Verification Setup Block Diagram

Liquid Verification Results

Frequency (MHz)	Liquid Type	Liquid Parameter		Target Value		Delta (%)		Tolerance (%)
		σ (S/m)	ϵ_r	σ (S/m)	ϵ_r	$\Delta \sigma$	$\Delta \epsilon_r$	
835	Head	0.906	42.024	0.900	41.500	0.67	1.26	± 5
836.6	Head	0.908	42.001	0.900	41.500	0.89	1.21	± 5
836.52	Head	0.908	41.999	0.900	41.500	0.89	1.20	± 5
836.5	Head	0.908	42.001	0.900	41.500	0.89	1.21	± 5

*Liquid Verification above was performed on 2020/08/23.

Frequency (MHz)	Liquid Type	Liquid Parameter		Target Value		Delta (%)		Tolerance (%)
		σ (S/m)	ϵ_r	σ (S/m)	ϵ_r	$\Delta \sigma$	$\Delta \epsilon_r$	
750	Head	0.893	41.266	0.890	41.900	0.34	-1.51	± 5
710	Head	0.856	41.786	0.887	42.102	-3.82	-0.75	± 5

*Liquid Verification above was performed on 2020/08/24.

Frequency (MHz)	Liquid Type	Liquid Parameter		Target Value		Delta (%)		Tolerance (%)
		σ (S/m)	ϵ_r	σ (S/m)	ϵ_r	$\Delta \sigma$	$\Delta \epsilon_r$	
1750	Head	1.370	40.851	1.387	40.038	-1.44	2.03	± 5
1732.5	Head	1.353	40.926	1.377	40.067	-1.96	2.14	± 5

*Liquid Verification above was performed on 2020/08/25.

Frequency (MHz)	Liquid Type	Liquid Parameter		Target Value		Delta (%)		Tolerance (%)
		σ (S/m)	ϵ_r	σ (S/m)	ϵ_r	$\Delta \sigma$	$\Delta \epsilon_r$	
1900	Head	1.411	38.720	1.400	40	0.79	-3.20	± 5
1880	Head	1.390	38.807	1.400	40	-0.71	-2.98	± 5

*Liquid Verification above was performed on 2020/08/26.

Frequency (MHz)	Liquid Type	Liquid Parameter		Target Value		Delta (%)		Tolerance (%)
		O (S/m)	ϵ_r	O (S/m)	ϵ_r	ΔO	$\Delta \epsilon_r$	
2450	Head	1.876	39.225	1.800	39.200	4.22	0.06	±5
2437	Head	1.860	39.273	1.788	39.219	3.91	0.14	±5
2441	Head	1.866	39.256	1.791	39.213	4.25	0.12	±5

*Liquid Verification above was performed on 2020/08/27.

Frequency (MHz)	Liquid Type	Liquid Parameter		Target Value		Delta (%)		Tolerance (%)
		O (S/m)	ϵ_r	O (S/m)	ϵ_r	ΔO	$\Delta \epsilon_r$	
2600	Head	1.999	37.519	1.960	39.000	1.99	-3.80	±5
2535	Head	1.971	37.768	1.888	39.084	4.29	-3.36	±5
2565	Head	1.955	37.656	1.921	39.045	1.82	-3.57	±5
2605	Head	2.005	37.501	1.966	38.994	1.78	-3.82	±5
2645	Head	2.048	37.322	2.009	38.943	1.89	-4.16	±5

*Liquid Verification above was performed on 2020/08/28.

Frequency (MHz)	Liquid Type	Liquid Parameter		Target Value		Delta (%)		Tolerance (%)
		O (S/m)	ϵ_r	O (S/m)	ϵ_r	ΔO	$\Delta \epsilon_r$	
5250	Head	4.606	36.725	4.711	35.950	-2.21	2.16	±5
5180	Head	4.513	36.874	4.639	36.020	-2.74	2.37	±5

*Liquid Verification above was performed on 2020/08/29.

Frequency (MHz)	Liquid Type	Liquid Parameter		Target Value		Delta (%)		Tolerance (%)
		O (S/m)	ϵ_r	O (S/m)	ϵ_r	ΔO	$\Delta \epsilon_r$	
5800	Head	5.245	35.523	5.270	35.300	-0.47	0.63	±5
5785	Head	5.233	35.553	5.255	35.315	-0.51	0.66	±5

*Liquid Verification above was performed on 2020/08/30.


System Accuracy Verification

Prior to the assessment, the system validation kit was used to test whether the system was operating within its specifications of $\pm 10\%$. The validation results are tabulated below. And also the corresponding SAR plot is attached as well in the SAR plots files.

The spacing distances in the **System Verification Setup Block Diagram** is given by the following:

- $s = 15 \text{ mm} \pm 0,2 \text{ mm}$ for $300 \text{ MHz} \leq f \leq 1\,000 \text{ MHz}$;
- $s = 10 \text{ mm} \pm 0,2 \text{ mm}$ for $1\,000 \text{ MHz} < f \leq 3\,000 \text{ MHz}$;
- $s = 10 \text{ mm} \pm 0,2 \text{ mm}$ for $3\,000 \text{ MHz} < f \leq 6\,000 \text{ MHz}$.

System Verification Setup Block Diagram



System Accuracy Check Results

Date	Frequency Band	Liquid Type	Input Power (mW)	Measured SAR (W/kg)		Normalized to 1W (W/kg)	Target Value (W/kg)	Delta (%)	Tolerance (%)
2020/08/24	750MHz	Head	250	1g	2.05	8.20	8.26	-0.73	± 10
2020/08/23	835 MHz	Head	250	1g	2.38	9.52	9.52	0	± 10
2020/08/25	1750 MHz	Head	250	1g	8.38	33.52	36.50	-8.16	± 10
2020/08/26	1900MHz	Head	250	1g	10.30	41.20	39.20	5.10	± 10
2020/08/27	2450 MHz	Head	250	1g	13.60	54.40	53.30	2.06	± 10
2020/08/28	2600 MHz	Head	250	1g	13.10	52.40	55.40	-5.42	± 10
2020/08/29	5250 MHz	Head	100	1g	7.39	73.90	79.20	-6.69	± 10
2020/08/30	5800 MHz	Head	100	1g	8.50	85.00	79.90	6.38	± 10


*The SAR values above are normalized to 1 Watt forward power.

SAR SYSTEM VALIDATION DATA**System Performance Check 750MHz****DUT: D750V3; Type: D750V3; Serial: D750V3 - SN:1166**

Communication System: UID 0, CW (0); Frequency: 750 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 750 \text{ MHz}$; $\sigma = 0.893 \text{ S/m}$; $\epsilon_r = 41.266$; $\rho = 1000 \text{ kg/m}^3$ **DASY5 Configuration:**

- Probe: EX3DV4 - SN7557; ConvF(10.41, 10.41, 10.41); Calibrated: 10/4/2019;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn527; Calibrated: 7/9/2020
- Phantom: ELI V8.0; Type: QD OVA 004 Ax; Serial: 2095
- Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7437)

Pin=250mW/Area Scan (61x61x1): Interpolated grid: $dx=1.500 \text{ mm}$, $dy=1.500 \text{ mm}$ Maximum value of SAR (interpolated) = 2.60 W/kg **Pin=250mW/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$ Reference Value = 52.04 V/m ; Power Drift = -0.03 dB Peak SAR (extrapolated) = 3.09 W/kg **SAR(1 g) = 2.05 W/kg ; SAR(10 g) = 1.35 W/kg** Maximum value of SAR (measured) = 2.59 W/kg  $0 \text{ dB} = 2.59 \text{ W/kg} = 4.13 \text{ dBW/kg}$

System Check_Head_835MHz

DUT: Dipole 835 MHz D835V2; Type: D835V2; Serial: D835V2 - SN:445

Communication System: UID 0, Systemperformance Check MHz (0); Frequency: 835 MHz;Duty Cycle: 1:1

Medium parameters used: $f = 835 \text{ MHz}$; $\sigma = 0.906 \text{ S/m}$; $\epsilon_r = 42.024$; $\rho = 1000 \text{ kg/m}^3$

DASY5 Configuration:

- Probe: EX3DV4 - SN7557;ConvF(10.1, 10.1, 10.1); Calibrated: 10/4/2019;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn527; Calibrated: 7/9/2020
- Phantom: ELI V8.0; Type: QD OVA 004 Ax; Serial: 2095
- Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7437)


Pin=250mW/Area Scan (101x201x1): Interpolated grid: $dx=1.500 \text{ mm}$, $dy=1.500 \text{ mm}$
Maximum value of SAR (interpolated) = 2.57 W/kg

Pin=250mW/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$
Reference Value = 53.49 V/m ; Power Drift = -0.04 dB

Peak SAR (extrapolated) = 3.58 W/kg

SAR(1 g) = 2.38 W/kg ; SAR(10 g) = 1.55 W/kg

Maximum value of SAR (measured) = 2.58 W/kg



0 dB = $2.58 \text{ W/kg} = 4.12 \text{ dBW/kg}$

System Check_Head_1750MHz

DUT: Dipole 1750 MHz D1750V2; Type: D1750V2; Serial: D1750V2 - SN:1140

Communication System: UID 0, Systemperformance Check (0); Frequency: 1750 MHz;Duty Cycle: 1:1

Medium parameters used: $f = 1750 \text{ MHz}$; $\sigma = 1.37 \text{ S/m}$; $\epsilon_r = 40.851$; $\rho = 1000 \text{ kg/m}^3$

DASY5 Configuration:

- Probe: EX3DV4 - SN7557;ConvF(8.67, 8.67, 8.67); Calibrated: 10/4/2019;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn527; Calibrated: 7/9/2020
- Phantom: ELI V8.0; Type: QD OVA 004 Ax; Serial: 2095
- Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7437)


Pin=250mW/Area Scan (101x141x1): Interpolated grid: $dx=1.500 \text{ mm}$, $dy=1.500 \text{ mm}$
Maximum value of SAR (interpolated) = 9.39 W/kg

Pin=250mW/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$
Reference Value = 86.68 V/m ; Power Drift = -0.03 dB

Peak SAR (extrapolated) = 15.4 W/kg

SAR(1 g) = 8.38 W/kg ; SAR(10 g) = 4.44 W/kg

Maximum value of SAR (measured) = 9.08 W/kg



0 dB = 9.08 W/kg = 9.58 dBW/kg

System Check_Head_1900MHz

DUT: Dipole 1900 MHz D1900V2; Type: D1900V2; Serial: D1900V2 - SN:5d206

Communication System: UID 0, Systemperformance Check MHz (0); Frequency: 1900 MHz;Duty Cycle: 1:1

Medium parameters used: $f = 1900$ MHz; $\sigma = 1.411$ S/m; $\epsilon_r = 38.72$; $\rho = 1000$ kg/m³

DASY5 Configuration:

- Probe: EX3DV4 - SN7557;ConvF(8.36, 8.36, 8.36); Calibrated: 10/4/2019;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn527; Calibrated: 7/9/2019
- Phantom: ELI V8.0; Type: QD OVA 004 Ax; Serial: 2095
- Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7437)


Pin=250mW/Area Scan (101x141x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 12.1 W/kg

Pin=250mW/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 96.75 V/m; Power Drift = -0.06 dB

Peak SAR (extrapolated) = 19.2 W/kg

SAR(1 g) = 10.3 W/kg; SAR(10 g) = 5.33 W/kg

Maximum value of SAR (measured) = 11.6 W/kg



0 dB = 11.6 W/kg = 10.64 dBW/kg

System Check_Head_2450MHz

DUT: Dipole 2450 MHz D2450V2; Type: D2450V2; Serial: D2450V2 - SN:970

Communication System: UID 0, Systemperformance Check 2450MHz (0); Frequency: 2450 MHz;Duty Cycle: 1:1

Medium parameters used: $f = 2450$ MHz; $\sigma = 1.876$ S/m; $\epsilon_r = 39.225$; $\rho = 1000$ kg/m³

DASY5 Configuration:

- Probe: EX3DV4 - SN7557;ConvF(7.41, 7.41, 7.41); Calibrated: 10/4/2019;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn527; Calibrated: 6/13/2019
- Phantom: Twin-SAM; Type: QD 000 P41 Ax; Serial: 1963
- Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7437)

Pin=250mW/2450MHz 2/Area Scan (101x121x1): Interpolated grid: dx=1.200 mm, dy=1.200 mm

Maximum value of SAR (interpolated) = 15.6 W/kg


Pin=250mW2450MHz 2/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 89.74 V/m; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 28.8 W/kg

SAR(1 g) = 13.6 W/kg; SAR(10 g) = 6.32 W/kg

Maximum value of SAR (measured) = 15.6 W/kg



0 dB = 15.6 W/kg = 11.93 dBW/kg

System Check_Head_2600MHz

DUT: Dipole 2600 MHz D2600V2; Type: D2600V2; Serial: D2600V2 - SN:1162

Communication System: UID 0, Systemperformance Check MHz (0); Frequency: 2600 MHz;Duty Cycle: 1:1

Medium parameters used: $f = 2600$ MHz; $\sigma = 1.999$ S/m; $\epsilon_r = 37.519$; $\rho = 1000$ kg/m³

DASY5 Configuration:

- Probe: EX3DV4 - SN7557;ConvF(7.21, 7.21, 7.21); Calibrated: 10/4/2019;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn527; Calibrated: 7/9/2020
- Phantom: ELI V8.0; Type: QD OVA 004 Ax; Serial: 2095
- Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7437)


Pin=250mW/Area Scan (81x121x1): Interpolated grid: dx=1.200 mm, dy=1.200 mm
Maximum value of SAR (interpolated) = 15.3 W/kg

Pin=250mW/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 93.07 V/m; Power Drift = -0.02 dB

Peak SAR (extrapolated) = 26.5 W/kg

SAR(1 g) = 13.1 W/kg; SAR(10 g) = 6.27 W/kg

Maximum value of SAR (measured) = 14.9 W/kg



0 dB = 14.9 W/kg = 11.73 dBW/kg

System Check_Head_5250MHz

DUT: D5GHzV2; Type: D5GHzV2; Serial: D5GHzV2 - SN:1296

Communication System: UID 0, CW (0); Frequency: 5250 MHz;Duty Cycle: 1:1

Medium parameters used: $f = 5250$ MHz; $\sigma = 4.606$ S/m; $\epsilon_r = 36.725$; $\rho = 1000$ kg/m³

DASY5 Configuration:

- Probe: EX3DV4 - SN7557;ConvF(5.38, 5.38, 5.38); Calibrated: 10/4/2019;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn527; Calibrated: 7/9/2020
- Phantom: ELI V8.0; Type: QD OVA 004 Ax; Serial: 2095
- Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7437)

Pin=100mW/Area Scan (71x71x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm
Maximum value of SAR (interpolated) = 17.7 W/kg


/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 66.99 V/m; Power Drift = -0.14 dB

Peak SAR (extrapolated) = 28.6 W/kg

SAR(1 g) = 7.39 W/kg; SAR(10 g) = 2.09 W/kg

Maximum value of SAR (measured) = 17.6 W/kg



0 dB = 17.6 W/kg = 12.46 dBW/kg

System Check_Head_5800MHz

DUT: D5GHzV2; Type: D5GHzV2; Serial: D5GHzV2 - SN:1296

Communication System: UID 0, CW (0); Frequency: 5800 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 5800$ MHz; $\sigma = 5.245$ S/m; $\epsilon_r = 35.523$; $\rho = 1000$ kg/m³

DASY5 Configuration:

- Probe: EX3DV4 - SN7557; ConvF(4.70, 4.70, 4.70); Calibrated: 10/4/2019;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn527; Calibrated: 7/9/2020
- Phantom: ELI V8.0; Type: QD OVA 004 Ax; Serial: 2095
- Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7437)

Pin=100mW/Area Scan (71x71x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm
Maximum value of SAR (interpolated) = 22.2 W/kg


Pin=100mW/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 68.41 V/m; Power Drift = 0.03 dB

Peak SAR (extrapolated) = 40.3 W/kg

SAR(1 g) = 8.5 W/kg; SAR(10 g) = 2.33 W/kg

Maximum value of SAR (measured) = 22.2 W/kg





0 dB = 22.2 W/kg = 13.46 dBW/kg

EUT TEST STRATEGY AND METHODOLOGY

Test Positions for Device Operating Next to a Person's Ear

This category includes most wireless handsets with fixed, retractable or internal antennas located toward the top half of the device, with or without a foldout, sliding or similar keypad cover. The handset should have its earpiece located within the upper ¼ of the device, either along the centerline or off-centered, as perceived by its users. This type of handset should be positioned in a normal operating position with the “test device reference point” located along the “vertical centerline” on the front of the device aligned to the “ear reference point”. The “test device reference point” should be located at the same level as the center of the earpiece region. The “vertical centerline” should bisect the front surface of the handset at its top and bottom edges. A “ear reference point” is located on the outer surface of the head phantom on each ear spacer. It is located 1.5 cm above the center of the ear canal entrance in the “phantom reference plane” defined by the three lines joining the center of each “ear reference point” (left and right) and the tip of the mouth.

A handset should be initially positioned with the earpiece region pressed against the ear spacer of a head phantom. For the SCC-34/SC-2 head phantom, the device should be positioned parallel to the “N-F” line defined along the base of the ear spacer that contains the “ear reference point”. For interim head phantoms, the device should be positioned parallel to the cheek for maximum RF energy coupling. The “test device reference point” is aligned to the “ear reference point” on the head phantom and the “vertical centerline” is aligned to the “phantom reference plane”. This is called the “initial ear position”. While maintaining these three alignments, the body of the handset is gradually adjusted to each of the following positions for evaluating SAR:



Cheek/Touch Position

The device is brought toward the mouth of the head phantom by pivoting against the “ear reference point” or along the “N-F” line for the SCC-34/SC-2 head phantom.


This test position is established:

When any point on the display, keypad or mouthpiece portions of the handset is in contact with the phantom.

(or) When any portion of a foldout, sliding or similar keypad cover opened to its intended self-adjusting normal use position is in contact with the cheek or mouth of the phantom.

For existing head phantoms – when the handset loses contact with the phantom at the pivoting point, rotation should continue until the device touches the cheek of the phantom or breaks its last contact from the ear spacer.

Cheek /Touch Position




Ear/Tilt Position

With the handset aligned in the “Cheek/Touch Position”:

1) If the earpiece of the handset is not in full contact with the phantom’s ear spacer (in the “Cheek/Touch position”) and the peak SAR location for the “Cheek/Touch” position is located at the ear spacer region or corresponds to the earpiece region of the handset, the device should be returned to the “initial ear position” by rotating it away from the mouth until the earpiece is in full contact with the ear spacer.

2) (otherwise) The handset should be moved (translated) away from the cheek perpendicular to the line passes through both “ear reference points” (note: one of these ear reference points may not physically exist on a split head model) for approximate 2-3 cm. While it is in this position, the device handset is tilted away from the mouth with respect to the “test device reference point” until the inside angle between the vertical centerline on the front surface of the phone and the horizontal line passing through the ear reference point is by 15 80°. After the tilt, it is then moved (translated) back toward the head perpendicular to the line passes through both “ear reference points” until the device touches the phantom or the ear spacer. If the antenna touches the head first, the positioning process should be repeated with a tilt angle less than 15° so that the device and its antenna would touch the phantom simultaneously. This test position may require a device holder or positioner to achieve the translation and tilting with acceptable positioning repeatability.

If a device is also designed to transmit with its keypad cover closed for operating in the head position, such positions should also be considered in the SAR evaluation. The device should be tested on the left and right side of the head phantom in the “Cheek/Touch” and “Ear/Tilt” positions. When applicable, each configuration should be tested with the antenna in its fully extended and fully retracted positions. These test configurations should be tested at the high, middle and low frequency channels of each operating mode; for example, AMPS, CDMA, and TDMA. If the SAR measured at the middle channel for each test configuration (left, right, Cheek/Touch, Tilt/Ear, extended and retracted) is at least 2.0 dB lower than the SAR limit, testing at the high and low channels is optional for such test configuration(s). If the transmission band of the test device is less than 10 MHz, testing at the high and low frequency channels is optional.

Ear /Tilt 15° Position**Test positions for body-worn and other configurations**

Body-worn operating configurations should be tested with the belt-clips and holsters attached to the device and positioned against a flat phantom in normal use configurations. Devices with a headset output should be tested with a headset connected to the device. When multiple accessories that do not contain metallic components are supplied with the device, the device may be tested with only the accessory that dictates the closest spacing to the body. When multiple accessories that contain metallic components are supplied with the device, the device must be tested with each accessory that contains a unique metallic component. If multiple accessories share an identical metallic component (e.g., the same metallic belt-clip used with different holsters with no other metallic components), only the accessory that dictates the closest spacing to the body must be tested.

Body-worn accessories may not always be supplied or available as options for some devices that are intended to be authorized for body-worn use. A separation distance of 1.5 cm between the back of the device and a flat phantom is recommended for testing body-worn SAR compliance under such circumstances. Other separation distances may be used, but they should not exceed 2.5 cm. In these cases, the device may use body-worn accessories that provide a separation distance greater than that tested for the device provided however that the accessory contains no metallic components.




Figure 5 – Test positions for body-worn devices

Test Distance for SAR Evaluation

In this case the EUT(Equipment Under Test) is set against from the phantom, the test distance is 0mm.

SAR Evaluation Procedure

The evaluation was performed with the following procedure:

Step 1: Measurement of the SAR value at a fixed location above the ear point or central position was used as a reference value for assessing the power drop. The SAR at this point is measured at the start of the test and then again at the end of the testing.

Step 2: The SAR distribution at the exposed side of the head was measured at a distance of 4 mm from the inner surface of the shell. The area covered the entire dimension of the head or radiating structures of the EUT, the horizontal grid spacing was 15 mm x 15 mm, and the SAR distribution was determined by integrated grid of 1.5mm x 1.5mm. Based on these data, the area of the maximum absorption was determined by spline interpolation. The first Area Scan covers the entire dimension of the EUT to ensure that the hotspot was correctly identified.

Step 3: Around this point, a volume of 30 mm x 30 mm x 30 mm was assessed by measuring 7x 7 x 7 points. On the basis of this data set, the spatial peak SAR value was evaluated under the following procedure:

- 1) The data at the surface were extrapolated, since the center of the dipoles is 1.2 mm away from the tip of the probe and the distance between the surface and the lowest measuring point is 1.3 mm. The extrapolation was based on a least square algorithm. A polynomial of the fourth order was calculated through the points in z-axes. This polynomial was then used to evaluate the points between the surface and the probe tip.

- 2) The maximum interpolated value was searched with a straightforward algorithm. Around this maximum the SAR values averaged over the spatial volumes (1 g or 10 g) were computed by the 3D-Spline interpolation algorithm. The 3D-Spline is composed of three one dimensional splines with the "Not a knot"-condition (in x, y and z-directions). The volume was integrated with the trapezoidal-algorithm. One thousand points (10 x 10 x 10) were interpolated to calculate the averages.

All neighboring volumes were evaluated until no neighboring volume with a higher average value was found.

Step 4: Re-measurement of the SAR value at the same location as in Step 1. If the value changed by more than 5%, the evaluation was repeated.


CONDUCTED OUTPUT POWER MEASUREMENT

Provision Applicable

The measured peak output power should be greater and within 5% than EMI measurement.

Test Procedure

The RF output of the transmitter was connected to the input of the EMI Test Receiver through Connector.



GSM/WCDMA/CDMA/LTE

Radio Configuration

The power measurement was configured by the Wireless Communication Test Set.

GSM/GPRS/EGPRS

Function: Menu select > GSM Mobile Station > GSM 850/1900

Press Connection control to choose the different menus

Press RESET > choose all the reset all settings

Connection Press Signal Off to turn off the signal and change settings

Network Support > GSM + GPRS or GSM + EGSM

Main Service > Packet Data

Service selection > Test Mode A – Auto Slot Config. off

MS Signal Press Slot Config Bottom on the right twice to select and change the number of time slots and power setting

> Slot configuration > Uplink/Gamma

> 33 dBm for GPRS 850

> 30 dBm for GPRS 1900

> 27 dBm for EGPRS 850

> 26 dBm for EGPRS 1900

BS Signal Enter the same channel number for TCH channel (test channel) and BCCH channel

Frequency Offset > + 0 Hz

Mode > BCCH and TCH

BCCH Level > -85 dBm (May need to adjust if link is not stable)

BCCH Channel > choose desired test channel [Enter the same channel number for TCH channel (test channel) and BCCH channel]

Channel Type > Off

P0 > 4 dB

Slot Config > Unchanged (if already set under MS signal)

TCH > choose desired test channel

Hopping > Off

Main Timeslot > 3

Network Coding Scheme > CS4 (GPRS) and MCS5 (EGPRS)

Bit Stream > 2E9-1 PSR Bit Stream

AF/RF Enter appropriate offsets for Ext. Att. Output and Ext. Att. Input

Connection Press Signal on to turn on the signal and change settings

WCDMA Release 99

The following tests were conducted according to the test requirements outlines in section 5.2 of the 3GPP TS34.121-1 specification. The EUT has a nominal maximum output power of 24dBm (+1.7/-3.7).

WCDMA General Settings	Loopback Mode	Test Mode 1
	Rel99 RMC	12.2kbps RMC
	Power Control Algorithm	Algorithm2
	β_c/β_d	8/15

HSDPA

The following tests were conducted according to the test requirements outlines in section 5.2 of the 3GPP TS34.121-1 specification.

	Mode	HSDPA	HSDPA	HSDPA	HSDPA
	Subset	1	2	3	4
WCDMA General Settings	Loopback Mode	Test Mode 1			
	Rel99 RMC	12.2kbps RMC			
	HSDPA FRC	H-Set1			
	Power Control Algorithm	Algorithm2			
	β_c	2/15	12/15	15/15	15/15
	β_d	15/15	15/15	8/15	4/15
	$\beta_d(\text{SF})$	64			
	β_c/β_d	2/15	12/15	15/8	15/4
	β_{hs}	4/15	24/15	30/15	30/15
	MPR(dB)	0	0	0.5	0.5
HSDPA Specific Settings	DACK	8			
	DNAK	8			
	DCQI	8			
	Ack-Nack repetition factor	3			
	CQI Feedback	4ms			
	CQI Repetition Factor	2			
	$A_{hs}=\beta_{hs}/\beta_c$	30/15			

HSUPA

The following tests were conducted according to the test requirements outlines in section 5.2 of the 3GPP TS34.121-1 specification.

	Mode	HSUPA	HSUPA	HSUPA	HSUPA	HSUPA
	Subset	1	2	3	4	5
WCDMA General Settings	Loopback Mode	Test Mode 1				
	Rel99 RMC	12.2kbps RMC				
	HSDPA FRC	H-Set1				
	HSUPA Test	HSUPA Loopback				
	Power Control Algorithm	Algorithm2				
	β_c	11/15	6/15	15/15	2/15	15/15
	β_d	15/15	15/15	9/15	15/15	0
	β_{cc}	209/225	12/15	30/15	2/15	5/15
	β_c / β_d	11/15	6/15	15/9	2/15	-
	β_{hs}	22/15	12/15	30/15	4/15	5/15
	CM(dB)	1.0	3.0	2.0	3.0	1.0
	MPR(dB)	0	2	1	2	0
HSDPA Specific Settings	DACK	8				
	DNAK	8				
	DCQI	8				
	Ack-Nack repetition factor	3				
	CQI Feedback	4ms				
	CQI Repetition Factor	2				
	$A_{hs} = \beta_{hs} / \beta_c$	30/15				
HSUPA Specific Settings	DE-DPCCH	6	8	8	5	7
	DHARQ	0	0	0	0	0
	AG Index	20	12	15	17	21
	ETFCI	75	67	92	71	81
	Associated Max UL Data Rate kbps	242.1	174.9	482.8	205.8	308.9
	Reference E_FCI	E-TFCI 11 E-TFCI PO 4 E-TFCI 67 E-TFCI PO 18 E-TFCI 71 E-TFCI PO23 E-TFCI 75 E-TFCI PO26 E-TFCI 81 E-TFCI PO 27	E-TFCI 11 E-TFCI PO4 E-TFCI 92 E-TFCI PO 18	E-TFCI 11 E-TFCI PO 4 E-TFCI 67 E-TFCI PO 18 E-TFCI 71 E-TFCI PO23 E-TFCI 75 E-TFCI PO26 E-TFCI 81 E-TFCI PO 27	E-TFCI 11 E-TFCI PO 4 E-TFCI 67 E-TFCI PO 18 E-TFCI 71 E-TFCI PO23 E-TFCI 75 E-TFCI PO26 E-TFCI 81 E-TFCI PO 27	E-TFCI 11 E-TFCI PO 4 E-TFCI 67 E-TFCI PO 18 E-TFCI 71 E-TFCI PO23 E-TFCI 75 E-TFCI PO26 E-TFCI 81 E-TFCI PO 27

DC-HSDPA

The following tests were conducted according to the test requirements in Table C.8.1.12 of 3GPP TS 34.121-1

Table C.8.1.12: Fixed Reference Channel H-Set 12

Parameter	Unit	Value
Nominal Avg. Inf. Bit Rate	kbps	60
Inter-TTI Distance	TTI's	1
Number of HARQ Processes	Processes	6
Information Bit Payload (N_{INF})	Bits	120
Number Code Blocks	Blocks	1
Binary Channel Bits Per TTI	Bits	960
Total Available SML's in UE	SML's	19200
Number of SML's per HARQ Proc.	SML's	3200
Coding Rate		0.15
Number of Physical Channel Codes	Codes	1
Modulation		QPSK
Note 1: The RMC is intended to be used for DC-HSDPA mode and both cells shall transmit with identical parameters as listed in the table.		
Note 2: Maximum number of transmission is limited to 1, i.e., retransmission is not allowed. The redundancy and constellation version 0 shall be used.		

HSPA+

Sub-test	β_c (Note3)	β_d	β_{HS} (Note1)	β_{ec}	β_{ed} (2xSF2) (Note 4)	β_{ed} (2xSF4) (Note 4)	CM (dB) (Note 2)	MPR (dB) (Note 2)	AG Index (Note 4)	E-TFCI (Note 5)	E-TFCI (boost)
1	1	0	30/15	30/15	β_{ed1} : 30/15 β_{ed2} : 30/15	β_{ed3} : 24/15 β_{ed4} : 24/15	3.5	2.5	14	105	105
Note 1: Δ_{ACK} , Δ_{NACK} and $\Delta_{CQI} = 30/15$ with $\beta_{hs} = 30/15 * \beta_c$. Note 2: CM = 3.5 and the MPR is based on the relative CM difference, MPR = MAX(CM-1,0). Note 3: DPDCH is not configured, therefore the β_c is set to 1 and $\beta_d = 0$ by default. Note 4: β_{ed} can not be set directly; it is set by Absolute Grant Value. Note 5: All the sub-tests require the UE to transmit 2SF2+2SF4 16QAM EDCH and they apply for UE using E-DPDCH category 7. E-DCH TTI is set to 2ms TTI and E-DCH table index = 2. To support these E-DCH configurations DPDCH is not allocated. The UE is signalled to use the extrapolation algorithm.											

The following tests were conducted according to the test requirements in Table C.11.1.4 of 3GPP TS 34.121-1

LTE

For UE Power Class 1 and 3, the allowed Maximum Power Reduction (MPR) for the maximum output power in Table 6.2.2-1 due to higher order modulation and transmit bandwidth configuration (resource blocks) is specified in Table 6.2.3-1.

Table 6.2.3-1: Maximum Power Reduction (MPR) for Power Class 1 and 3

Modulation	Channel bandwidth / Transmission bandwidth (N_{RB})						MPR (dB)
	1.4 MHz	3.0 MHz	5 MHz	10 MHz	15 MHz	20 MHz	
QPSK	> 5	> 4	> 8	> 12	> 16	> 18	≤ 1
16 QAM	≤ 5	≤ 4	≤ 8	≤ 12	≤ 16	≤ 18	≤ 1
16 QAM	> 5	> 4	> 8	> 12	> 16	> 18	≤ 2

For UE Power Class 1 and 3 the specific requirements and identified sub clauses are specified in Table 6.2.4-1 along with the allowed A-MPR values that may be used to meet these requirements. The allowed A-MPR values specified below in Table 6.2.4-1 to 6.2.4-15 are in addition to the allowed MPR requirements specified in sub clause 6.2.3.

Table 6.2.4-1: Additional Maximum Power Reduction (A-MPR)

Network Signalling value	Requirements (subclause)	E-UTRA Band	Channel bandwidth (MHz)	Resources Blocks (N_{RB})	A-MPR (dB)
NS_01	6.6.2.1.1	Table 5.5-1	1.4, 3, 5, 10, 15, 20	Table 5.6-1	N/A
NS_03	6.6.2.2.1	2, 4, 10, 23, 25, 35, 36	3	>5	≤ 1
			5	>6	≤ 1
			10	>6	≤ 1
			15	>8	≤ 1
			20	>10	≤ 1
NS_04	6.6.2.2.2	41	5	>6	≤ 1
NS_05	6.6.3.3.1	1	10, 15, 20	Table 6.2.4-4	
NS_06	6.6.2.2.3	12, 13, 14, 17	1.4, 3, 5, 10	≥ 50	≤ 1
NS_07	6.6.2.2.3 6.6.3.3.2	13	10	Table 5.6-1	N/A
NS_08	6.6.3.3.3	19	10, 15	Table 6.2.4-2	
NS_09	6.6.3.3.4	21	10, 15	> 44	≤ 3
				> 40	≤ 1
				> 55	≤ 2
NS_10		20	15, 20	Table 6.2.4-3	
NS_11	6.6.2.2.1	23	1.4, 3, 5, 10, 15, 20	Table 6.2.4-5	
NS_12	6.6.3.3.5	26	1.4, 3, 5	Table 6.2.4-6	
NS_13	6.6.3.3.6	26	5	Table 6.2.4-7	
NS_14	6.6.3.3.7	26	10, 15	Table 6.2.4-8	
NS_15	6.6.3.3.8	26	1.4, 3, 5, 10, 15	Table 6.2.4-9 Table 6.2.4-10	
NS_16	6.6.3.3.9	27	3, 5, 10	Table 6.2.4-11, Table 6.2.4-12, Table 6.2.4-13	
NS_17	6.6.3.3.10	28	5, 10	Table 5.6-1	N/A
NS_18	6.6.3.3.11	28	5	≥ 2	≤ 1
			10, 15, 20	≥ 1	≤ 4
NS_19	6.6.3.3.12	44	10, 15, 20	Table 6.2.4-14	
NS_20	6.2.2 6.6.2.2.1 6.6.3.2	23	5, 10, 15, 20	Table 6.2.4-15	
...					
NS_32	-	-	-	-	-

Maximum Target Output Power

Max Target Power(dBm)			
Mode/Band	Channel		
	Low	Middle	High
GSM850	34	34	34
GPRS 4 TX Slot	30	30	30
DCS1900	32	32	32
GPRS 4 TX Slot	27	27	27
WCDMA Band 5	23	23	23
WCDMA Band 2	23	23	23
CDMA	22.5	22.5	22.5
LTE Band 2	23.5	23.5	23.5
LTE Band 4	23	23	23
LTE Band 5	24.5	24.5	24.5
LTE Band 7	23	23	23
LTE Band 17	22.5	22.5	22.5
LTE Band 41	22.5	22.5	22.5
WLAN(2.4G)	14	15	14
Bluetooth	6.5	7.5	4.5
BLE	2	3	0.5
WLAN(5.2G)	15	15	13
WLAN(5.8G)	10.8	10	10

Test Results:**GSM**

Mode	Channel	Frequency (MHz)	Average Output Power (dBm)
GSM 850	128	824.2	33.48
	190	836.6	33.36
	251	848.8	33.19
PCS 1900	512	1850.2	30.58
	661	1880	30.64
	810	1909.8	30.98

GPRS:

Band	Channel No.	Frequency (MHz)	RF Output Power (dBm)			
			1 slot	2 slots	3 slots	4 slots
GSM 850	128	824.2	32.02	31.20	30.27	29.34
	190	836.6	32.26	31.55	30.63	29.56
	251	848.8	32.31	31.68	30.47	29.40
PCS 1900	512	1850.2	29.34	28.84	27.84	26.68
	661	1880.0	28.96	28.70	27.70	26.75
	810	1909.8	28.67	27.93	26.86	25.77

EDGE:

Band	Channel No.	Frequency (MHz)	RF Output Power (dBm)			
			1 slot	2 slots	3 slots	4 slots
GSM 850	128	824.2	25.99	25.05	24.04	22.90
	190	836.6	26.23	25.32	24.19	23.09
	251	848.8	26.25	25.30	24.23	23.10
PCS 1900	512	1850.2	24.97	23.94	22.88	21.77
	661	1880.0	24.69	23.60	22.46	21.35
	810	1909.8	24.54	23.42	22.33	21.08

For SAR, the time based average power is relevant, the difference in between depends on the duty cycle of the TDMA signal.

Number of Time slot	1	2	3	4
Duty Cycle	1:8	1:4	1:2.66	1:2
Time based Ave. power compared to slotted Ave. power	-9 dB	-6 dB	-4.25 dB	-3 dB
Crest Factor	8	4	2.66	2

The time based average power for GSM

Mode	Channel	Frequency (MHz)	Average Output Power (dBm)
GSM 850	128	824.2	24.48
	190	836.6	24.36
	251	848.8	24.19
PCS 1900	512	1850.2	21.58
	661	1880	21.64
	810	1909.8	21.98

The time based average power for GPRS

Band	Channel No.	Frequency (MHz)	Time based average Power (dBm)			
			1 slot	2 slot	3 slots	4 slots
GSM 850	128	824.2	23.02	25.2	26.01	26.34
	190	836.6	23.26	25.55	26.37	26.56
	251	848.8	23.31	25.68	26.21	26.40
PCS 1900	512	1850.2	20.34	22.84	23.58	23.68
	661	1880	19.96	22.7	23.44	23.75
	810	1909.8	19.67	21.93	22.60	22.77

The time based average power for EDGE

Band	Channel No.	Frequency (MHz)	Time based average Power (dBm)			
			1 slot	2 slot	3 slots	4 slots
GSM 850	128	824.2	16.99	19.05	19.78	19.9
	190	836.6	17.23	19.32	19.93	20.09
	251	848.8	17.25	19.3	19.97	20.10
PCS 1900	512	1850.2	15.97	17.94	18.62	18.77
	661	1880	15.69	17.6	18.2	18.35
	810	1909.8	15.54	17.42	18.07	18.08

Note:

1. Rohde & Schwarz Radio Communication Tester (CMU200) was used for the measurement of GSM peak and average output power for active timeslots.
2. For GSM voice, 1 timeslot has been activated with power level 5 (850 MHz band) and 0 (1900 MHz band).
3. For GPRS, 1, 2, 3 and 4 timeslots has been activated separately with power level 3(850 MHz band) and 3(1900 MHz band).
4. According to KDB941225D01-SAR for EGPRS mode are not required when the source-based time-averaged output power for data mode is lower than that in the normal GPRS mode.

WCDMA:**WCDMA Band II**

Mode	Test Condition	Test Mode	3GPP Sub Test	Average Output Power (dBm)		
				Low Frequency	Middle Frequency	High Frequency
WCDMA (Band II)	Normal	Rel 99	1	20.91	20.66	20.97
		HSDPA	1	20.8	20.65	20.77
			2	20.82	20.58	20.58
			3	20.72	20.59	20.68
			4	20.71	20.45	20.69
		HSUPA	1	20.71	20.56	20.74
			2	20.75	20.51	20.61
			3	20.78	20.58	20.66
			4	20.64	20.67	20.71
			5	20.67	20.58	20.65
		HSPA+	1	20.83	20.42	20.66

WCDMA Band V

Mode	Test Condition	Test Mode	3GPP Sub Test	Average Output Power (dBm)		
				Low Frequency	Middle Frequency	High Frequency
WCDMA (Band V)	Normal	Rel 99	1	22.32	22.54	22.28
		HSDPA	1	22.04	22.01	22.19
			2	21.96	22.03	22.07
			3	22.09	21.93	22.00
			4	22.08	22.03	22.12
		HSUPA	1	22.00	22.10	22.14
			2	22.02	22.09	22.17
			3	21.95	22.11	22.08
			4	22.03	22.09	22.16
			5	22.02	22.01	22.11
		HSPA+	1	22.06	22.08	22.09

CDMA

Mode	Test Mode	Channel	Frequency (MHz)	Average Output Power (dBm)	Limit (dBm)
CDMA	EVDO (BC0)	1013	824.70	22.19	38.45
		384	836.52	22.31	38.45
		777	848.31	22.13	38.45

Mode	Test Mode	Channel	Frequency (MHz)	Average Output Power (dBm)	Limit (dBm)
CDMA	1xRTT	1013	824.70	22.02	38.45
		384	836.52	22.06	38.45
		777	848.31	21.98	38.45

Note:

1. The default test configuration is to measure SAR with an established radio link between the EUT and a communication test set using a 12.2 kbps RMC (reference measurement Channel) Configured in Test Loop Model 1.
2. KDB 941225 D01-Body SAR is not required for HSDPA/HSUPA/HSPA+ when the maximum average output of each RF channel is less than 1/4 dB higher than measured 12.2kbps RMC or the maximum SAR for 12.2kbps RMC is < 75% of SAR limit.

Maximum Output Power:**LTE Band 2**

Test Bandwidth	Test Modulation	Resource Block & RB offset	Low Channel (dBm)	Middle Channel (dBm)	High Channel (dBm)
1.4M	QPSK	1#0	20.78	20.88	21.46
		1#3	20.96	21.03	21.21
		1#5	20.86	20.47	21.5
		3#0	21.25	20.46	20.42
		3#1	21.42	20.89	20.65
		3#3	20.93	21.29	20.53
		6#0	21.13	21.22	21.23
	16-QAM	1#0	21.11	20.93	20.55
		1#3	21.65	21.01	20.66
		1#5	21.64	20.57	20.62
		3#0	20.87	20.42	21.16
		3#1	21.5	21.36	21.43
		3#3	21.69	20.5	21.38
		6#0	21.4	20.72	20.36
3M	QPSK	1#0	21.53	21.39	21.17
		1#7	21.35	21.48	20.95
		1#14	21.44	20.8	20.48
		8#0	20.92	21.3	21.37
		8#4	21.7	20.82	21.22
		8#7	20.89	21.14	20.64
		15#0	21.26	20.94	20.89
	16-QAM	1#0	21.4	21.34	20.63
		1#7	21.46	21.45	20.77
		1#14	20.74	20.54	20.5
		8#0	20.88	21.21	20.94
		8#4	21.21	20.84	20.73
		8#7	21.39	20.94	20.74
		15#0	20.94	21.26	21.02

Test Bandwidth	Test Modulation	Resource Block & RB offset	Low Channel (dBm)	Middle Channel (dBm)	High Channel (dBm)
5M	QPSK	1#0	21.57	20.64	20.64
		1#12	21.02	20.54	20.66
		1#24	21.31	20.76	20.76
		12#0	21.14	20.66	21.41
		12#6	21.82	20.43	20.99
		12#11	21.11	20.62	21
		25#0	21.15	21.18	20.69
	16-QAM	1#0	20.92	20.59	21.27
		1#12	21.6	20.79	21.21
		1#24	21.58	21.27	20.63
		12#0	21.44	20.88	20.57
		12#6	21.79	20.79	20.68
		12#11	21.37	20.69	20.56
		25#0	21.79	20.85	21.03
10M	QPSK	1#0	21.55	21.36	20.94
		1#24	21.34	20.89	21.15
		1#49	21.79	21.11	21.04
		25#0	20.92	20.44	21.39
		25#12	21.05	21.02	20.66
		25#24	21.77	21.16	20.84
		50#0	21.83	20.39	21.54
	16-QAM	1#0	21.33	20.66	21.46
		1#24	21.58	20.44	20.88
		1#49	21.32	21.03	20.85
		25#0	21.69	21.24	21.33
		25#12	21.45	21.1	20.95
		25#24	21.54	20.5	21.27
		50#0	21	20.52	21.16

Test Bandwidth	Test Modulation	Resource Block & RB offset	Low Channel (dBm)	Middle Channel (dBm)	High Channel (dBm)
15M	QPSK	1#0	21.87	21.93	21.22
		1#37	21.85	21.38	21.07
		1#74	21.97	21.29	21.06
		36#0	21.33	21.48	21.08
		36#17	21.94	21.38	20.94
		36#35	21.9	21.29	21.16
		75#0	21.64	21.8	21.55
	16-QAM	1#0	21.38	21.66	21.68
		1#37	21.28	21.9	20.85
		1#74	21.46	21.4	21.15
		36#0	21.79	21.58	21.08
		36#17	21.83	21.68	21.36
		36#35	21.64	21.71	20.79
		75#0	21.3	21.95	21.17
20M	QPSK	1#0	21.88	22.09	21.99
		1#49	21.16	21.76	21.54
		1#99	21.76	21.75	21.7
		50#0	21.6	21.63	21.56
		50#24	21.95	21.45	21.46
		50#49	21.41	22.07	21.44
		100#0	21.36	21.43	21.08
	16-QAM	1#0	21.94	21.56	21.38
		1#49	22.04	21.4	21.22
		1#99	21.61	21.79	20.74
		50#0	21.21	21.97	20.77
		50#24	21.79	21.6	21.35
		50#49	21.73	22.02	21.68
		100#0	21.88	21.53	21.27

LTE Band 4

Test Bandwidth	Test Modulation	Resource Block & RB offset	Low Channel (dBm)	Middle Channel (dBm)	High Channel (dBm)
1.4M	QPSK	1#0	20.82	20.69	21.05
		1#3	20.93	21.3	21.45
		1#5	21.51	21.49	21.66
		3#0	20.89	21.6	21.48
		3#1	21.81	21.08	21.6
		3#3	21.25	20.89	21.83
		6#0	21.27	21.41	21.11
	16-QAM	1#0	21.25	21.06	21.73
		1#3	21.38	20.87	21.74
		1#5	21.47	20.85	21.36
		3#0	21.06	21.33	21.86
		3#1	21.57	20.69	21.8
		3#3	21.79	21.27	21.31
		6#0	21.7	21.01	21.6
3M	QPSK	1#0	21.19	21.02	21.31
		1#7	21.09	21.14	21.81
		1#14	21.45	21.64	21.56
		8#0	21.49	21.12	21.85
		8#4	21.6	21.52	21.56
		8#7	21.7	21.25	21.35
		15#0	21.65	20.75	21.44
	16-QAM	1#0	21.66	21.39	21.29
		1#7	21.62	21.65	21.82
		1#14	21.62	21.38	21.37
		8#0	20.96	20.73	21.22
		8#4	20.93	20.85	21.86
		8#7	21.5	21.67	21.7
		15#0	21.04	20.72	21.27

Test Bandwidth	Test Modulation	Resource Block & RB offset	Low Channel (dBm)	Middle Channel (dBm)	High Channel (dBm)
5M	QPSK	1#0	20.68	20.79	20.79
		1#12	21.31	21.63	21.31
		1#24	21.16	21.25	21.32
		12#0	20.72	21	21.4
		12#6	20.8	20.91	21.73
		12#11	21.65	21.61	21.8
		25#0	21.29	21.1	21.35
	16-QAM	1#0	21.55	21.17	21.49
		1#12	20.86	20.86	21.77
		1#24	21.08	21.33	21.56
		12#0	20.74	21.22	21.74
		12#6	20.72	20.99	21.01
		12#11	21.57	21.61	21.15
		25#0	21.43	21.52	21.05
10M	QPSK	1#0	21.14	21.66	21.04
		1#24	21.58	21.15	21.45
		1#49	21.48	21.3	21.42
		25#0	21.47	21.73	21.43
		25#12	21.02	21.69	21.48
		25#24	20.8	21.57	21.55
		50#0	21.47	21.53	21.32
	16-QAM	1#0	20.76	20.92	21.34
		1#24	21.1	21.68	21.64
		1#49	20.79	21.19	21.05
		25#0	20.93	21.46	21.37
		25#12	21.69	21.1	21.22
		25#24	20.76	20.94	21.05
		50#0	21.41	20.89	21.52

Test Bandwidth	Test Modulation	Resource Block & RB offset	Low Channel (dBm)	Middle Channel (dBm)	High Channel (dBm)
15M	QPSK	1#0	21.16	20.79	20.69
		1#37	20.83	21.04	21.49
		1#74	21.11	21.52	21.03
		36#0	20.98	20.71	21.21
		36#17	21.75	20.86	21.16
		36#35	20.83	21.45	21.6
		75#0	21.37	21.32	21.48
	16-QAM	1#0	21.32	21.1	21.67
		1#37	21.29	21.21	21.59
		1#74	20.99	21	21.08
		36#0	20.84	20.75	21.45
		36#17	21.5	21.51	21.71
		36#35	20.98	20.94	21.75
		75#0	21.31	21.31	21.42
20M	QPSK	1#0	21.41	21.78	21.66
		1#49	21.53	21.45	21.55
		1#99	21.25	21.34	21.39
		50#0	21.08	21.33	21.17
		50#24	20.89	21.29	20.94
		50#49	21.62	20.93	21.19
		100#0	21.01	21.26	21.16
	16-QAM	1#0	21.59	20.64	21.75
		1#49	21.05	20.67	21.26
		1#99	21	20.82	21.32
		50#0	21.29	20.77	21.36
		50#24	21.45	20.98	21.53
		50#49	21.62	20.98	21.72
		100#0	21.52	20.93	21.21

LTE Band 5

Test Bandwidth	Test Modulation	Resource Block & RB offset	Low Channel (dBm)	Middle Channel (dBm)	High Channel (dBm)
1.4M	QPSK	1#0	23.46	23.09	23.49
		1#3	24.06	24.15	23.56
		1#5	23.87	23.74	23.36
		3#0	24.29	23.58	23.20
		3#1	23.46	23.88	23.56
		3#3	24.17	23.56	23.30
		6#0	23.93	23.28	23.62
	16-QAM	1#0	24.25	24.05	24.08
		1#3	24.17	24.01	23.70
		1#5	23.86	23.39	23.53
		3#0	23.86	24.01	23.48
		3#1	23.94	24.05	23.48
		3#3	23.77	24.04	23.81
		6#0	23.44	23.55	23.83
3M	QPSK	1#0	23.96	23.91	23.63
		1#7	23.63	23.67	23.34
		1#14	23.87	23.54	23.65
		8#0	24.16	23.92	23.26
		8#4	23.40	24.12	23.47
		8#7	23.55	23.68	23.20
		15#0	23.73	24.16	23.62
	16-QAM	1#0	23.46	23.74	23.63
		1#7	24.30	23.77	24.07
		1#14	24.00	23.73	23.92
		8#0	23.90	23.88	23.58
		8#4	24.23	23.65	23.95
		8#7	24.02	23.29	23.97
		15#0	23.68	23.61	23.44

Test Bandwidth	Test Modulation	Resource Block & RB offset	Low Channel (dBm)	Middle Channel (dBm)	High Channel (dBm)
5M	QPSK	1#0	23.19	23.43	23.29
		1#12	24.72	23.80	23.81
		1#24	23.67	23.63	23.78
		12#0	24.23	23.68	23.38
		12#6	24.13	24.14	23.74
		12#11	24.04	23.71	23.56
		25#0	23.59	23.69	23.76
	16-QAM	1#0	24.09	23.95	23.58
		1#12	23.89	23.90	23.83
		1#24	24.09	23.67	23.51
		12#0	24.00	24.24	23.63
		12#6	23.87	23.83	24.12
		12#11	23.71	23.51	23.67
		25#0	24.09	23.89	24.30
10M	QPSK	1#0	24.28	24.34	24.32
		1#24	23.56	23.33	24.14
		1#49	24.21	23.48	23.98
		25#0	23.72	23.86	23.74
		25#12	23.75	23.48	24.02
		25#24	23.71	23.59	24.21
		50#0	23.54	23.82	23.76
	16-QAM	1#0	23.66	23.75	23.84
		1#24	23.92	23.82	24.13
		1#49	24.04	24.15	23.38
		25#0	23.89	23.60	23.46
		25#12	24.30	23.84	24.01
		25#24	23.89	23.60	23.93
		50#0	23.53	24.19	23.84

LTE Band 7

Test Bandwidth	Test Modulation	Resource Block & RB offset	Low Channel (dBm)	Middle Channel (dBm)	High Channel (dBm)
5M	QPSK	1#0	21.22	21.58	21.74
		1#12	21.53	20.77	21.32
		1#24	21.56	20.93	21.62
		12#0	21.70	21.03	21.25
		12#6	21.63	21.41	21.09
		12#11	21.29	21.38	21.14
		25#0	21.58	21.12	21.28
	16-QAM	1#0	21.29	20.73	21.52
		1#12	21.34	20.89	21.71
		1#24	21.66	21.48	21.45
		12#0	20.98	20.9	21.49
		12#6	21.45	21.14	21.35
		12#11	21.3	21.45	21.46
		25#0	21.22	20.84	21.36
10M	QPSK	1#0	21.4	20.74	21.15
		1#24	21.04	21.38	21.49
		1#49	21.61	21.64	21.12
		25#0	21.68	21.12	21.27
		25#12	21.33	20.99	21.19
		25#24	21.67	21.56	21.69
		50#0	21.76	21.37	21.7
	16-QAM	1#0	21.32	21.01	21.55
		1#24	21.49	21.13	21.46
		1#49	21.18	20.98	21.41
		25#0	21.28	21.14	21.56
		25#12	21.18	21.45	21.06
		25#24	21.44	20.75	21.70
		50#0	21.27	20.89	22.02

Test Bandwidth	Test Modulation	Resource Block & RB offset	Low Channel (dBm)	Middle Channel (dBm)	High Channel (dBm)
15M	QPSK	1#0	21.16	21.63	21.93
		1#37	21.32	21.18	21.27
		1#74	21.16	20.91	21.55
		36#0	21.41	21.4	21.65
		36#17	21.54	20.94	21.3
		36#35	21.65	21.15	21.37
		75#0	21.28	21.12	21.1
	16-QAM	1#0	20.95	20.72	21.85
		1#37	21.49	21.69	21.65
		1#74	21.15	21.31	21.95
		36#0	21.25	21.09	21.93
		36#17	21.63	21.62	21.86
		36#35	21.5	21.1	21.16
		75#0	20.94	21.35	21.06
20M	QPSK	1#0	21.7	21.71	21.63
		1#49	21.31	21.05	21.21
		1#99	21.43	21.19	21.2
		50#0	21.14	21.73	21.48
		50#24	21.47	21.62	21.52
		50#49	20.85	21.24	21.56
		100#0	20.82	21.53	21.11
	16-QAM	1#0	21.44	21.28	21.72
		1#49	20.89	21.05	21.68
		1#99	21.26	21.45	21.52
		50#0	21.72	21.65	21.56
		50#24	21.35	21.24	21.32
		50#49	21.66	21.17	21.11
		100#0	21.52	21.47	21.34

LTE Band 17

Test Bandwidth	Test Modulation	Resource Block & RB offset	Low Channel (dBm)	Middle Channel (dBm)	High Channel (dBm)
5M	QPSK	1#0	21.58	21.95	21.16
		1#12	22.22	21.47	21.42
		1#24	21.92	21.15	21.15
		12#0	21.28	21.14	21.34
		12#6	21.77	21.24	21.04
		12#11	21.57	21.43	21.29
		25#0	21.90	22.06	21.23
	16-QAM	1#0	21.44	21.63	21.84
		1#12	22.01	21.45	21.47
		1#24	22.04	21.89	21.69
		12#0	22.08	22.00	21.73
		12#6	21.46	21.62	21.28
		12#11	21.39	22.09	21.38
		25#0	22.09	22.10	21.11
10M	QPSK	1#0	21.33	21.58	21.58
		1#24	21.48	21.64	21.31
		1#49	21.86	21.57	21.21
		25#0	21.45	21.48	21.38
		25#12	21.48	21.19	21.67
		25#24	21.53	21.28	22.15
		50#0	21.47	21.71	21.94
	16-QAM	1#0	21.67	21.41	21.72
		1#24	21.66	21.70	21.33
		1#49	21.48	21.81	21.61
		25#0	22.04	21.76	21.63
		25#12	21.69	21.38	21.81
		25#24	21.42	21.88	21.84
		50#0	22.01	21.17	22.08

LTE Band 41

Test Bandwidth	Test Modulation	Resource Block & RB offset	Low Channel (dBm)	Middle Channel (dBm)	High Channel (dBm)
5M	QPSK	1#0	21.75	21.87	21.94
		1#12	21.54	21.61	21.54
		1#24	21.63	21.84	21.66
		12#0	21.51	22.09	21.97
		12#6	22.03	21.43	21.39
		12#11	22.02	22.11	21.59
		25#0	21.63	21.46	21.04
	16-QAM	1#0	22.12	21.28	21.93
		1#12	21.84	21.40	21.63
		1#24	22.12	21.59	21.04
		12#0	21.47	21.13	21.91
		12#6	22.00	21.70	21.44
		12#11	21.39	21.88	21.35
		25#0	22.13	21.29	21.73
10M	QPSK	1#0	21.78	22.01	21.35
		1#24	22.09	21.41	21.91
		1#49	21.37	21.92	21.26
		25#0	21.58	21.38	21.34
		25#12	21.38	21.16	21.37
		25#24	21.28	21.79	21.67
		50#0	21.60	21.44	21.72
	16-QAM	1#0	21.47	22.00	22.11
		1#24	21.99	21.79	21.47
		1#49	21.65	21.92	22.14
		25#0	21.73	22.09	21.26
		25#12	21.82	21.77	21.92
		25#24	21.41	22.09	22.08
		50#0	21.31	22.05	21.89

Test Bandwidth	Test Modulation	Resource Block & RB offset	Low Channel (dBm)	Middle Channel (dBm)	High Channel (dBm)
15M	QPSK	1#0	22.06	22.02	21.18
		1#37	22.21	21.28	21.36
		1#74	22.02	21.36	21.10
		36#0	21.73	21.17	21.80
		36#17	21.52	21.35	21.67
		36#35	21.62	21.15	21.74
		75#0	22.09	21.61	21.29
	16-QAM	1#0	21.87	21.48	21.26
		1#37	21.96	21.65	21.68
		1#74	21.37	21.84	21.87
		36#0	21.81	21.28	21.82
		36#17	21.34	21.87	21.41
		36#35	21.74	21.57	21.58
		75#0	21.45	22.09	21.94
20M	QPSK	1#0	21.55	21.84	21.20
		1#49	22.03	21.27	21.31
		1#99	21.17	21.45	21.36
		50#0	21.45	21.61	21.49
		50#24	22.03	21.42	21.80
		50#49	21.19	21.82	21.59
		100#0	22.14	21.50	21.33
	16-QAM	1#0	21.37	21.22	21.67
		1#49	21.71	21.85	21.68
		1#99	22.08	21.24	21.89
		50#0	22.05	21.87	21.53
		50#24	21.44	22.00	21.57
		50#49	21.83	21.31	21.27
		100#0	21.18	21.21	21.55

WLAN 2.4G:

Mode	Channel frequency (MHz)	Data Rate	Conducted Average Output Power(dBm)
802.11b	2412	1Mbps	13.41
	2437		14.68
	2462		13.60
802.11g	2412	6Mbps	7.12
	2437		6.57
	2462		6.89
802.11n HT20	2412	MCS0	7.20
	2437		6.25
	2462		6.93
802.11n HT40	2422	MCS0	6.61
	2437		7.34
	2452		5.75

WLAN 5.2G:

Test mode	Band	Frequency (MHz)	Average Conducted Output Power (dBm)
802.11a	5150-5250 MHz	5180	14.48
		5200	14.36
		5240	12.67
802.11ac20	5150-5250 MHz	5180	14.28
		5200	14.36
		5240	12.64
802.11n-HT20	5150-5250 MHz	5180	14.37
		5200	14.30
		5240	12.62
802.11ac40	5150-5250 MHz	5190	13.33
		5230	12.06
802.11n-HT40	5150-5250 MHz	5190	13.56
		5230	12.48
802.11ac80	5150-5250 MHz	5210	12.94

WLAN 5.8G:

Test mode	Band	Frequency (MHz)	Average Conducted Output Power (dBm)
802.11a	5725-5850 MHz	5745	10.51
		5785	9.72
		5825	9.87
802.11ac20	5725-5850 MHz	5745	10.73
		5785	9.86
		5825	9.61
802.11n-HT20	5725-5850 MHz	5745	10.58
		5785	10.21
		5825	9.01
802.11ac40	5725-5850 MHz	5755	9.34
		5795	8.51
802.11n-HT40	5725-5850 MHz	5755	9.37
		5795	9.05
802.11ac80	5725-5850 MHz	5775	8.89

Bluetooth:


Mode	Channel frequency (MHz)	RF Output Power (dBm)
BDR(GFSK)	2402	6.39
	2441	7.08
	2480	4.31
EDR($\pi/4$ -DQPSK)	2402	5.34
	2441	6.57
	2480	3.72
EDR(8DPSK)	2402	5.64
	2441	6.81
	2480	4.07

BLE:

Channel	Frequency (MHz)	Max Conducted Peak Output Power (dBm)
BLE Mode		
Low	2402	1.59
Middle	2440	2.70
High	2480	-0.00

Standalone SAR test exclusion considerations

Antennas Location:



Antenna Distance To Edge

Antenna	Antenna Distance To Edge(mm)					
	Back	Front	Left	Right	Top	Bottom
WWAN	<5	<5	196	<5	52	12
WIFI/BT	<5	<5	8	177	<5	113

Standalone SAR test exclusion considerations

Mode	Frequency (MHz)	Pavg (dBm)	Pavg (mW)	Distance (mm)	Calculated value	Threshold (1-g)	SAR Test Exclusion
WLAN 2.4G	2462	14	25.12	5	7.9	3	NO
WLAN 5.2G	5240	13	19.95	5	9.1	3	NO
WLAN 5.8G	5825	10	10	5	4.8	3	NO
Bluetooth	2441	7.5	5.62	5	0.9	3	YES

Note: The WLAN based average power for calculation. and Bluetooth based peak output power for calculation.

NOTE:

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot$

$[\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where

1. $f(\text{GHz})$ is the RF channel transmit frequency in GHz.

2. Power and distance are rounded to the nearest mW and mm before calculation.

3. The result is rounded to one decimal place for comparison.

4. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test Exclusion.

Standalone SAR estimation:

Mode	Frequency (MHz)	Pavg (dBm)	Pavg (mW)	Distance (mm)	Estimated 1-g (W/kg)
BT Body	2441	7.5	5.62	5	0.234

Note: The bluetooth based Peak power for calculation.

When standalone SAR test exclusion applies to an antenna that transmits simultaneously with other antennas, the standalone SAR must be estimated according to following to determine simultaneous transmission SAR test exclusion:

$$\left[\frac{\text{max. power of channel, including tune-up tolerance, mW}}{(\text{min. test separation distance, mm})} \right] \cdot \left[\sqrt{f(\text{GHz})/x} \right]$$

W/kg for test separation distances ≤ 50 mm;

where $x = 7.5$ for 1-g SAR. and $x = 18.75$ for 10-g SAR.

When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test Exclusion

Standalone SAR test exclusion considerations:

Mode	Frequency (MHz)	Pavg (dBm)	Pavg (mW)	Test exclusion Distance(mm)
GPRS 850	848.8	30	1000	198
GPRS 1900	1909.8	27	501	90
WCDMA Band2	1907.6	23	199.5	59
WCDMA Band5	846.6	23	199.5	56
CDMA850	848.31	23	199.5	56
LTE Band2	1909.3	23.5	223.9	62
LTE Band4	1754.3	23	199.5	59
LTE Band5	844.0	24.5	281.8	56
LTE Band7	2560	23	199.5	61
LTE Band17	711	22.5	177.8	52
LTE Band41	2645	22.5	177.8	59
Wi-Fi 2.4G	2462	14	25.1	14
Wi-Fi 5.2G	5240	13	20.0	17
Wi-Fi 5.8G	5825	10	10	9

Note: For GSM Mode(s), the maximum time based average power(4Slots) were used for calculation.

SAR test exclusion for the EUT edge considerations Result

Antenna Distance To Edge(mm)						
Mode	Front	Back	Left	Right	Top	Bottom
GSM850	Required	Required	Required	Required	Required	Required
GSM1900	Required	Required	Exclusion	Required	Required	Required
WCDMA Band2	Required	Required	Exclusion	Required	Required	Required
WCDMA Band5	Required	Required	Exclusion	Required	Required	Required
CDMA	Required	Required	Exclusion	Required	Required	Required
LTE Band2	Required	Required	Exclusion	Required	Required	Required
LTE Band4	Required	Required	Exclusion	Required	Required	Required
LTE Band5	Required	Required	Exclusion	Required	Required	Required
LTE Band7	Required	Required	Exclusion	Required	Required	Required
LTE Band17	Required	Required	Exclusion	Required	Required	Required
LTE Band41	Required	Required	Exclusion	Required	Required	Required
WLAN 2.4G	Required	Required	Required	Exclusion	Required	Exclusion
WLAN 5.2G	Required	Required	Required	Exclusion	Required	Exclusion
WLAN 5.8G	Required	Required	Required	Exclusion	Required	Exclusion

Note:

Required: The distance is less than **Test Exclusion Distance**, testing is required.

Exclusion*: SAR test exclusion evaluation has been done above.

Exclusion: The distance is larger than **Test Exclusion Distance**, testing is not required.

SAR test exclusion for the EUT edge considerations detail:**Distance<50mm(To Edges)**

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distance ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})]$

$[\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where

1. $f(\text{GHz})$ is the RF channel transmit frequency in GHz.

2. Power and distance are rounded to the nearest mW and mm before calculation.

3. The result is rounded to one decimal place for comparison.

4. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test Exclusion.

5. The Time based average Power is used for calculation.

Distance>50mm(To Edges)

At 100 MHz to 6 GHz and for *test separation distance* > 50 mm, the SAR test exclusion threshold is determined according to the following:

a) $[(\text{Power allowed at numeric threshold for 50mm in step 1}) + (\text{test separation distance} - 50\text{mm}) \cdot f(\text{MHz})/150]$ mW, at 100 MHz to 1500 MHz

a) $[(\text{Power allowed at numeric threshold for 50mm in step 1}) + (\text{test separation distance} - 50\text{mm}) \cdot 10]$ mW, at > 1500 MHz and ≤ 6 GHz.

SAR MEASUREMENT RESULTS

This page summarizes the results of the performed dosimetric evaluation.

SAR Test Data

Environmental Conditions

Temperature:	21.5-22.9 °C	21.1-22.4 °C	20.9-22.2 °C	20.8-21.8 °C	21.1-22.3 °C
Relative Humidity:	51 %	49 %	50 %	48 %	48 %
ATM Pressure:	101.8 kPa	101.5 kPa	101.7 kPa	101.6 kPa	101.5 kPa
Test Date:	2020/08/23	2020/08/24	2020/08/25	2020/08/26	2020/08/27
Temperature:	21.5-22.7 °C	21.5-22.6 °C	21.5-22.7 °C		
Relative Humidity:	53 %	49 %	50 %		
ATM Pressure:	101.7 kPa	101.8 kPa	101.8 kPa		
Test Date:	2020/08/28	2020/08/29	2020/08/30		

Testing was performed by Chris wang. and Bard Liu

GSM 850 :

EUT Position	Frequency (MHz)	Test Mode	Max Power (dBm)		Scaled Factor	1g SAR (W/kg)		Plot
			Meas.	Rated		Meas.	Rated	
Body-Front (0mm)	824.2	GPRS	/	/	/	/	/	/
	836.6	GPRS	29.56	30.0	1.170	0.222	0.246	#1
	848.8	GPRS	/	/	/	/	/	/
Body-Back (0mm)	824.2	GPRS	/	/	/	/	/	/
	836.6	GPRS	29.56	30.0	1.170	0.193	0.214	/
	848.8	GPRS	/	/	/	/	/	/
Body-Headset-Back(0mm)	824.2	GSM Voice	33.48	34.0	1.127	0.112	0.126	/
	836.6	GSM Voice	/	/	/	/	/	/
	848.8	GSM Voice	/	/	/	/	/	/
Body-Left (0mm)	824.2	GPRS	/	/	/	/	/	/
	836.6	GPRS	29.56	30.0	1.170	0.002	0.002	/
	848.8	GPRS	/	/	/	/	/	/
Body-Right (0mm)	824.2	GPRS	/	/	/	/	/	/
	836.6	GPRS	29.56	30.0	1.170	0.221	0.245	/
	848.8	GPRS	/	/	/	/	/	/
Body-Top (0mm)	824.2	GPRS	/	/	/	/	/	/
	836.6	GPRS	29.56	30.0	1.170	0.026	0.029	/
	848.8	GPRS	/	/	/	/	/	/
Body-Bottom (0mm)	824.2	GPRS	/	/	/	/	/	/
	836.6	GPRS	29.56	30.0	1.170	0.013	0.014	/
	848.8	GPRS	/	/	/	/	/	/

PCS 1900 :

EUT Position	Frequency (MHz)	Test Mode	Max Power (dBm)		Scaled Factor	1g SAR (W/kg)		Plot
			Meas.	Rated		Meas.	Rated	
Body-Front (0mm)	1850.2	GPRS	/	/	/	/	/	/
	1880	GPRS	26.75	27	1.059	0.395	0.418	/
	1909.8	GPRS	/	/	/	/	/	/
Body-Back (0mm)	1850.2	GPRS	/	/	/	/	/	/
	1880	GPRS	26.75	27	1.059	0.362	0.383	/
	1909.8	GPRS	/	/	/	/	/	/
Body-Headset-Back(0mm)	1850.2	GSM Voice	/	/	/	/	/	/
	1880	GSM Voice	/	/	/	/	/	/
	1909.8	GSM Voice	30.98	32	1.265	0.205	0.259	/
Body-Right (0mm)	1850.2	GPRS	/	/	/	/	/	/
	1880	GPRS	26.75	27	1.059	0.515	0.546	#2
	1909.8	GPRS	/	/	/	/	/	/
Body-Top (0mm)	1850.2	GPRS	/	/	/	/	/	/
	1880	GPRS	26.75	27	1.059	0.032	0.034	/
	1909.8	GPRS	/	/	/	/	/	/
Body-Bottom (0mm)	1850.2	GPRS	/	/	/	/	/	/
	1880	GPRS	26.75	27	1.059	0.010	0.011	/
	1909.8	GPRS	/	/	/	/	/	/

WCDMA Band 2 :

EUT Position	Frequency (MHz)	Test Mode	Max Power (dBm)		Scaled Factor	1g SAR (W/kg)		Plot
			Meas.	Rated		Meas.	Rated	
Body-Front (0mm)	1852.4	RMC	/	/	/	/	/	/
	1880	RMC	20.66	21	1.081	0.407	0.440	#4
	1907.6	RMC	/	/	/	/	/	/
Body-Back (0mm)	1852.4	RMC	/	/	/	/	/	/
	1880	RMC	20.66	21	1.081	0.361	0.390	/
	1907.6	RMC	/	/	/	/	/	/
Body-Right (0mm)	1852.4	RMC	/	/	/	/	/	/
	1880	RMC	20.66	21	1.081	0.325	0.351	/
	1907.6	RMC	/	/	/	/	/	/
Body-Top (0mm)	1852.4	RMC	/	/	/	/	/	/
	1880	RMC	20.66	21	1.081	0.132	0.143	/
	1907.6	RMC	/	/	/	/	/	/
Body-Bottom (0mm)	1852.4	RMC	/	/	/	/	/	/
	1880	RMC	20.66	21	1.081	0.024	0.026	/
	1907.6	RMC	/	/	/	/	/	/

WCDMA Band 5 :

EUT Position	Frequency (MHz)	Test Mode	Max Power (dBm)		Scaled Factor	1g SAR (W/kg)		Plot
			Meas.	Rated		Meas.	Rated	
Body-Front (0mm)	826.4	RMC	/	/	/	/	/	/
	836.4	RMC	22.54	23	1.112	0.586	0.651	/
	846.6	RMC	/	/	/	/	/	/
Body-Back (0mm)	826.4	RMC	/	/	/	/	/	/
	836.4	RMC	22.54	23	1.112	0.622	0.691	#3
	846.6	RMC	/	/	/	/	/	/
Body-Right (0mm)	826.4	RMC	/	/	/	/	/	/
	836.4	RMC	22.54	23	1.112	0.403	0.448	/
	846.6	RMC	/	/	/	/	/	/
Body-Top (0mm)	826.4	RMC	/	/	/	/	/	/
	836.4	RMC	22.54	23	1.112	0.122	0.136	/
	846.6	RMC	/	/	/	/	/	/
Body-Bottom (0mm)	826.4	RMC	/	/	/	/	/	/
	836.4	RMC	22.54	23	1.112	0.046	0.051	/
	846.6	RMC	/	/	/	/	/	/

CDMA BC0 :

EUT Position	Frequency (MHz)	Test Mode	Max Power (dBm)		Scaled Factor	1g SAR (W/kg)		Plot
			Meas.	Rated		Meas.	Rated	
Body-Front (0mm)	824.70	1xRTT	/	/	/	/	/	/
	836.52	1xRTT	22.06	22.5	1.107	0.673	0.745	#5
	848.31	1xRTT	/	/	/	/	/	/
Body-Back (0mm)	824.70	1xRTT	/	/	/	/	/	/
	836.52	1xRTT	22.06	22.5	1.107	0.551	0.610	/
	848.31	1xRTT	/	/	/	/	/	/
Body-Right (0mm)	824.70	1xRTT	/	/	/	/	/	/
	836.52	1xRTT	22.06	22.5	1.107	0.426	0.471	/
	848.31	1xRTT	/	/	/	/	/	/
Body-Top (0mm)	824.70	1xRTT	/	/	/	/	/	/
	836.52	1xRTT	22.06	22.5	1.107	0.132	0.146	/
	848.31	1xRTT	/	/	/	/	/	/
Body-Bottom (0mm)	824.70	1xRTT	/	/	/	/	/	/
	836.52	1xRTT	22.06	22.5	1.107	0.041	0.045	/
	848.31	1xRTT	/	/	/	/	/	/

EUT Position	Frequency (MHz)	Test Mode	Max Power (dBm)		Scaled Factor	1g SAR (W/kg)		Plot
			Meas.	Rated		Meas.	Rated	
Body-Front (0mm)	824.70	EVDO	/	/	/	/	/	/
	836.52	EVDO	22.31	22.5	1.045	0.606	0.633	#6
	848.31	EVDO	/	/	/	/	/	/
Body-Back (0mm)	824.70	EVDO	/	/	/	/	/	/
	836.52	EVDO	22.31	22.5	1.045	0.566	0.591	/
	848.31	EVDO	/	/	/	/	/	/
Body-Right (0mm)	824.70	EVDO	/	/	/	/	/	/
	836.52	EVDO	22.31	22.5	1.045	0.389	0.406	/
	848.31	EVDO	/	/	/	/	/	/
Body-Top (0mm)	824.70	EVDO	/	/	/	/	/	/
	836.52	EVDO	22.31	22.5	1.045	0.106	0.111	/
	848.31	EVDO	/	/	/	/	/	/
Body-Bottom (0mm)	824.70	EVDO	/	/	/	/	/	/
	836.52	EVDO	22.31	22.5	1.045	0.032	0.033	/
	848.31	EVDO	/	/	/	/	/	/

LTE Band 5 :

EUT Position	Frequency (MHz)	Bandwidth (MHz)	Test Mode	Max Power (dBm)		Scaled Factor	1g SAR (W/kg)		Plot
				Meas.	Rated		Meas.	Rated	
Body-Front (0mm)	829	10	1RB	/	/	/	/	/	/
	836.5	10	1RB	24.34	24.5	1.038	0.660	0.685	/
	844	10	1RB	/	/	/	/	/	/
	836.5	10	50%RB	2386	24.5	1.159	0.562	0.651	/
Body-Back (0mm)	829	10	1RB	/	/	/			/
	836.5	10	1RB	24.34	24.5	1.038	0.715	0.742	#8
	844	10	1RB	/	/	/			/
	836.5	10	50%RB	2386	24.5	1.159	0.558	0.647	/
Body-Right (0mm)	829	10	1RB	/	/	/			/
	836.5	10	1RB	24.34	24.5	1.038	0.490	0.508	/
	844	10	1RB	/	/	/			/
	836.5	10	50%RB	2386	24.5	1.159	0.432	0.501	/
Body-Top (0mm)	829	10	1RB	/	/	/	/	/	/
	836.5	10	1RB	21.83	22.0	1.040	0.041	0.042	/
	844	10	1RB	/	/	/			/
	836.5	10	50%RB	21.14	22.0	1.219	0.025	0.029	/
Body-Bottom (0mm)	829	10	1RB	/	/	/	/	/	/
	836.5	10	1RB	21.83	22.0	1.040	0.008	0.008	/
	844	10	1RB	/	/	/			/
	836.5	10	50%RB	21.14	22.0	1.219	0.003	0.003	/

LTE Band 7 :

EUT Position	Frequency (MHz)	Bandwidth (MHz)	Test Mode	Max Power (dBm)		Scaled Factor	1g SAR (W/kg)		Plot
				Meas.	Rated		Meas.	Rated	
Body-Front (0mm)	2510	20	1RB	/	/	/	/	/	/
	2535	20	1RB	21.71	22	1.069	0.629	0.672	#11
	2560	20	1RB	/	/	/	/	/	/
	2535	20	50%RB	21.73	22	1.064	0.467	0.497	/
Body-Back (0mm)	2510	20	1RB	/	/	/			/
	2535	20	1RB	21.71	22	1.069	0.268	0.287	
	2560	20	1RB	/	/	/			/
	2535	20	50%RB	21.73	22	1.064	0.221	0.235	/
Body-Right (0mm)	2510	20	1RB	/	/	/			/
	2535	20	1RB	21.71	22	1.069	0.365	0.390	/
	2560	20	1RB	/	/	/			/
	2535	20	50%RB	21.73	22	1.064	0.302	0.321	/
Body-Top (0mm)	2510	20	1RB	/	/	/	/	/	/
	2535	20	1RB	21.71	22	1.069	0.106	0.113	/
	2560	20	1RB	/	/	/			/
	2535	20	50%RB	21.73	22	1.064	0.084	0.089	/
Body-Bottom (0mm)	2510	20	1RB	/	/	/	/	/	/
	2535	20	1RB	21.71	22	1.069	0.003	0.003	/
	2560	20	1RB	/	/	/			/
	2535	20	50%RB	21.73	22	1.064	0.002	0.002	/

LTE Band 2:

EUT Position	Frequency (MHz)	Bandwidth (MHz)	Test Mode	Max Power (dBm)		Scaled Factor	1g SAR (W/kg)		Plot
				Meas.	Rated		Meas.	Rated	
Body-Front (0mm)	1860	20	1RB	/	/	/	/	/	/
	1880	20	1RB	22.09	22.5	1.099	0.597	0.656	#10
	1900	20	1RB	/	/	/	/	/	/
	1880	20	50%RB	21.63	22.5	1.222	0.483	0.590	/
Body-Back (0mm)	1860	20	1RB	/	/	/	/	/	/
	1880	20	1RB	22.09	22.5	1.099	0.477	0.524	
	1900	20	1RB	/	/	/	/	/	/
	1880	20	50%RB	21.63	22.5	1.222	0.372	0.455	/
Body-Right (0mm)	1860	20	1RB	/	/	/	/	/	/
	1880	20	1RB	22.09	22.5	1.099	0.579	0.636	/
	1900	20	1RB	/	/	/	/	/	/
	1880	20	50%RB	21.63	22.5	1.222	0.506	0.618	/
Body-Top (0mm)	1860	20	1RB	/	/	/	/	/	/
	1880	20	1RB	22.09	22.5	1.099	0.311	0.342	/
	1900	20	1RB	/	/	/	/	/	/
	1880	20	50%RB	21.63	22.5	1.222	0.235	0.287	/
Body-Bottom (0mm)	1860	20	1RB	/	/	/	/	/	/
	1880	20	1RB	22.09	22.5	1.099	0.012	0.013	/
	1900	20	1RB	/	/	/	/	/	/
	1880	20	50%RB	21.63	22.5	1.222	0.007	0.008	/

LTE Band 4:

EUT Position	Frequency (MHz)	Bandwidth (MHz)	Test Mode	Max Power (dBm)		Scaled Factor	1g SAR (W/kg)		Plot
				Meas.	Rated		Meas.	Rated	
Body-Front (0mm)	1720.0	20	1RB	/	/	/	/	/	/
	1732.5	20	1RB	21.78	22	1.052	0.336	0.353	/
	1745.0	20	1RB	/	/	/	/	/	/
	1732.5	20	50%RB	21.33	22	1.167	0.267	0.312	/
Body-Back (0mm)	1720.0	20	1RB	/	/	/	/	/	/
	1732.5	20	1RB	21.78	22	1.052	0.288	0.303	
	1745.0	20	1RB	/	/	/	/	/	/
	1732.5	20	50%RB	21.33	22	1.167	0.270	0.315	/
Body-Right (0mm)	1720.0	20	1RB	/	/	/	/	/	/
	1732.5	20	1RB	21.78	22	1.052	0.529	0.556	#9
	1745.0	20	1RB	/	/	/	/	/	/
	1732.5	20	50%RB	21.33	22	1.167	0.432	0.504	/
Body-Top (0mm)	1720.0	20	1RB	/	/	/	/	/	/
	1732.5	20	1RB	21.78	22	1.052	0.106	0.112	/
	1745.0	20	1RB	/	/	/	/	/	/
	1732.5	20	50%RB	21.33	22	1.167	0.085	0.099	/
Body-Bottom (0mm)	1720.0	20	1RB	/	/	/	/	/	/
	1732.5	20	1RB	21.78	22	1.052	0.026	0.027	/
	1745.0	20	1RB	/	/	/	/	/	/
	1732.5	20	50%RB	21.33	22	1.167	0.018	0.021	/

LTE Band 17:

EUT Position	Frequency (MHz)	Bandwidth (MHz)	Test Mode	Max Power (dBm)		Scaled Factor	1g SAR (W/kg)		Plot
				Meas.	Rated		Meas.	Rated	
Body-Front (0mm)	709.0	10	1RB	/	/	/	/	/	/
	710.0	10	1RB	21.58	22.5	1.236	0.636	0.786	/
	711.0	10	1RB	/	/	/	/	/	/
	710.0	10	50%RB	21.48	22.5	1.265	0.565	0.715	/
Body-Back (0mm)	709.0	10	1RB	/	/	/	/	/	/
	710.0	10	1RB	21.58	22.5	1.236	0.682	0.843	#7
	711.0	10	1RB	/	/	/	/	/	/
	710.0	10	50%RB	21.48	22.5	1.265	0.618	0.782	/
Body-Right (0mm)	709.0	10	1RB	/	/	/	/	/	/
	710.0	10	1RB	21.58	22.5	1.236	0.592	0.732	/
	711.0	10	1RB	/	/	/	/	/	/
	710.0	10	50%RB	21.48	22.5	1.265	0.485	0.613	/
Body-Top (0mm)	709.0	10	1RB	/	/	/	/	/	/
	710.0	10	1RB	21.58	22.5	1.236	0.066	0.082	/
	711.0	10	1RB	/	/	/	/	/	/
	710.0	10	50%RB	21.48	22.5	1.265	0.042	0.053	/
Body-Bottom (0mm)	709.0	10	1RB	/	/	/	/	/	/
	710.0	10	1RB	21.58	22.5	1.236	0.015	0.019	/
	711.0	10	1RB	/	/	/	/	/	/
	710.0	10	50%RB	21.48	22.5	1.265	0.013	0.016	/

LTE Band 41:

EUT Position	Frequency (MHz)	Bandwidth (MHz)	Test Mode	Max Power (dBm)		Scaled Factor	1g SAR (W/kg)		Plot
				Meas.	Rated		Meas.	Rated	
Body-Front (0mm)	2565	20	1RB	21.55	22.5	1.245	0.532	0.662	/
	2605	20	1RB	21.84	22.5	1.164	0.755	0.879	#12
	2645	20	1RB	21.2	22.5	1.349	0.556	0.750	/
	2565	20	50%RB	21.45	22.5	1.274	0.389	0.495	/
	2605	20	50%RB	21.61	22.5	1.227	0.605	0.743	/
	2645	20	50%RB	21.49	22.5	1.262	0.405	0.511	/
	2605	20	100%RB	21.5	22.5	1.259	0.589	0.742	/
Body-Back (0mm)	2565	20	1RB	/	/	/	/	/	/
	2605	20	1RB	21.84	22.5	1.164	0.287	0.334	/
	2645	20	1RB	/	/	/	/	/	/
	2605	20	50%RB	21.61	22.5	1.227	0.250	0.307	/
Body-Right (0mm)	2565	20	1RB	21.55	22.5	1.245	0.506	0.630	/
	2605	20	1RB	21.84	22.5	1.164	0.739	0.860	/
	2645	20	1RB	21.2	22.5	1.349	0.526	0.710	/
	2565	20	50%RB	21.45	22.5	1.274	0.521	0.663	/
	2605	20	50%RB	21.61	22.5	1.227	0.567	0.696	/
	2645	20	50%RB	21.49	22.5	1.262	0.503	0.635	/
	2605	20	100%RB	21.5	22.5	1.259	0.524	0.660	/
Body-Top (0mm)	2565	20	1RB	/	/	/	/	/	/
	2605	20	1RB	21.84	22.5	1.164	0.068	0.079	/
	2645	20	1RB	/	/	/	/	/	/
	2605	20	50%RB	21.61	22.5	1.227	0.045	0.055	/
Body-Bottom (0mm)	2565	20	1RB	/	/	/	/	/	/
	2605	20	1RB	21.84	22.5	1.164	0.021	0.024	/
	2645	20	1RB	/	/	/	/	/	/
	2605	20	50%RB	21.61	22.5	1.227	0.019	0.023	/

WLAN 2.4G:

EUT Position	Frequency (MHz)	Test Mode	Max. Meas. Power (dBm)	Max. Rated Power (dBm)	10g SAR (W/kg)			
					Scaled Factor	Meas. SAR	Scaled SAR	Plot
Body-Front (0mm)	2412	802.11b	/	/	/	/	/	/
	2437	802.11b	14.68	15.0	1.076	0.437	0.470	/
	2462	802.11b	/	/	/	/	/	/
Body-Back (0mm)	2412	802.11b	/	/	/			/
	2437	802.11b	14.68	15.0	1.076	0.451	0.485	#13
	2462	802.11b	/	/	/	/	/	/
Body- Left (0mm)	2412	802.11b	/	/	/	/	/	/
	2437	802.11b	14.68	15.0	1.076	0.430	0.463	
	2462	802.11b	/	/	/	/	/	/
Body-Top (0mm)	2412	802.11b	/	/	/	/	/	/
	2437	802.11b	14.68	15.0	1.076	0.236	0.254	/
	2462	802.11b	/	/	/	/	/	/

Note:

1. When the SAR Value is less than half of the limit, testing for other channels are optional.
2. When SAR or MPE is not measured at the maximum power level allowed for production units, the results must be scaled to the maximum tune-up tolerance limit according to the power applied to the individual channels tested to determine compliance.
3. KDB 248227 D01-SAR measurement is not required for 2.4 GHz OFDM(801.11g/n) when the highest reported SAR for DSSS(802.11b) is ≤ 1.2 W/kg, and the output power for DSSS is not less than that for OFDM.

WLAN 5G:

EUT Position	Frequency (MHz)	Test Mode	Bandwidth (MHz)	Max. Meas. Power (dBm)	Max. Rated Power (dBm)	1g SAR (W/kg)			
						Scaled Factor	Meas. SAR	Scaled SAR	Plot
Body Front (0mm)	5180	802.11a	20	14.48	15	1.127	0.253	0.285	/
	5200	802.11a	20	/	/	/	/	/	/
	5240	802.11a	20	/	/	/	/	/	/
Body-Back (0mm)	5180	802.11a	20	14.48	15	1.127	0.112	0.126	/
	5200	802.11a	20	/	/	/	/	/	/
	5240	802.11a	20	/	/	/	/	/	/
Body- Left (0mm)	5180	802.11a	20	14.48	15	1.127	0.309	0.348	/
	5200	802.11a	20	/	/	/	/	/	/
	5240	802.11a	20	/	/	/	/	/	/
Body-Top (0mm)	5180	802.11a	20	14.48	15	1.127	0.552	0.622	#14
	5200	802.11a	20	14.36	15	1.159	0.516	0.598	/
	5240	802.11a	20	12.67	13	1.079	0.402	0.434	/

EUT Position	Frequency (MHz)	Test Mode	Bandwidth (MHz)	Max. Meas. Power (dBm)	Max. Rated Power (dBm)	1g SAR (W/kg)			
						Scaled Factor	Meas. SAR	Scaled SAR	Plot
Body Front (0mm)	5745	802.11a	20	/	/	/	/	/	/
	5785	802.11a	20	10.51	10.8	1.069	0.051	0.055	/
	5825	802.11a	20	/	/	/	/	/	/
Body-Back (0mm)	5745	802.11a	20	/	/	/	/	/	/
	5785	802.11a	20	10.51	10.8	1.069	0.126	0.135	/
	5825	802.11a	20	/	/	/	/	/	/
Body-Left (0mm)	5745	802.11a	20	/	/	/	/	/	/
	5785	802.11a	20	10.51	10.8	1.069	0.076	0.081	/
	5825	802.11a	20	/	/	/	/	/	/
Body-Top (0mm)	5745	802.11a	20	/	/	/	/	/	/
	5785	802.11a	20	10.51	10.8	1.069	0.302	0.323	#15
	5825	802.11a	20	/	/	/	/	/	/

SAR SIMULTANEOUS TRANSMISSION DESCRIPTION

Simultaneous Transmission:

Description of Simultaneous Transmit Capabilities		
Transmitter Combination	Simultaneous?	Hotspot?
WWAN(GSM/WCDMA/LTE) + WLAN 2.4G	√	√
WWAN(GSM/WCDMA/LTE) + WLAN 5G	√	√
WWAN(GSM/WCDMA/LTE) + Bluetooth	√	X

Simultaneous Transmission Consideration Detail

Transmitter Combination	Position	Max SAR(W/kg)		Σ SAR< 1.6W/kg
		SAR1(WWAN)	SAR2(WLAN)	
WWAN+ WLAN 2.4G	Body Front	0.879	0.470	1.349
	Body Back	0.843	0.485	1.328
	Body Left	N/A	0.463	N/A
	Body Right	0.860	N/A	N/A
	Body Top	0.342	0.254	0.596

Transmitter Combination	Position	Max SAR(W/kg)		Σ SAR< 1.6W/kg
		SAR1(WWAN)	SAR2(WLAN)	
WWAN+ Bluetooth	Body Front	0.879	0.234	1.113
	Body Back	0.843	0.234	1.077
	Body Left	N/A	0.234	N/A
	Body Right	0.860	0.234	1.094
	Body Top	0.342	0.234	0.576

Transmitter Combination	Position	Max SAR(W/kg)		Σ SAR< 1.6W/kg
		SAR1(WWAN)	SAR2(WLAN)	
WWAN+ WLAN 5G	Body Front	0.879	0.285	1.164
	Body Back	0.843	0.135	0.978
	Body Left	N/A	0.348	N/A
	Body Right	0.860	N/A	N/A
	Body Top	0.342	0.622	0.964

Conclusion:

Sum of SAR: Σ SAR $\leq$ 1.6 W/kg for 1g Body SAR , therefore simultaneous transmission SAR with Volume Scans is **not required**.

SAR Plots

Test Plot 1# GSM850_GPRS 4 Tx slots_Front_0mm_Ch190

Communication System: UID 0, GSM850 (0); Frequency: 836.6 MHz; Duty Cycle: 1:2.08

Medium parameters used: $f = 836.6$ MHz; $\sigma = 0.908$ S/m; $\epsilon_r = 42.001$; $\rho = 1000$ kg/m³

DASY5 Configuration:

- Probe: EX3DV4 - SN7557; ConvF(10.1, 10.1, 10.1); Calibrated: 4/10/2019,
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn527; Calibrated: 7/9/2020
- Phantom: ELI V8.0; Type: QD OVA 004 Ax; Serial: 2095
- Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7437)

Area Scan (101x71x1): Interpolated grid: $dx=1.500$ mm, $dy=1.500$ mm

Maximum value of SAR (interpolated) = 0.316 W/kg


Zoom Scan (6x6x7)/Cube 0: Measurement grid: $dx=8$ mm, $dy=8$ mm, $dz=5$ mm

Reference Value = 2.603 V/m; Power Drift = -0.00 dB

Peak SAR (extrapolated) = 0.448 W/kg

SAR(1 g) = 0.222 W/kg; SAR(10 g) = 0.121 W/kg

Maximum value of SAR (measured) = 0.331 W/kg



0 dB = 0.331 W/kg = -4.80 dBW/kg

Test Plot 2# GSM1900_GPRS 4 Tx slots_Right Side_0mm_Ch661

Communication System: UID 0, GSM 1900 (0); Frequency: 1880 MHz; Duty Cycle: 1:2.08
Medium parameters used: $f = 1880$ MHz; $\sigma = 1.39$ S/m; $\epsilon_r = 38.807$; $\rho = 1000$ kg/m³

DASY5 Configuration:

- Probe: EX3DV4 - SN7557; ConvF(8.36, 8.36, 8.36); Calibrated: 4/10/2019,
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn527; Calibrated: 7/9/2020
- Phantom: ELI V8.0; Type: QD OVA 004 Ax; Serial: 2095
- Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7437)

Area Scan (31x91x1): Interpolated grid: $dx=1.500$ mm, $dy=1.500$ mm
Maximum value of SAR (interpolated) = 0.785 W/kg


Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8$ mm, $dy=8$ mm, $dz=5$ mm

Reference Value = 11.73 V/m; Power Drift = 0.03 dB

Peak SAR (extrapolated) = 0.903 W/kg

SAR(1 g) = 0.515 W/kg; SAR(10 g) = 0.285 W/kg

Maximum value of SAR (measured) = 0.752 W/kg



Test plot 3#WCDMA V_RMC 12.2Kbps_Back_0mm_Ch4182

Communication System: UID 0, WCDMA 3G (0); Frequency: 836.4 MHz; Duty Cycle: 1:1
Medium parameters used: $f = 836.4$ MHz; $\sigma = 0.908$ S/m; $\epsilon_r = 42.001$; $\rho = 1000$ kg/m³

DASY5 Configuration:

- Probe: EX3DV4 - SN7557; ConvF(10.1, 10.1, 10.1); Calibrated: 4/10/2019,
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn527; Calibrated: 7/9/2020
- Phantom: ELI V8.0; Type: QD OVA 004 Ax; Serial: 2095
- Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7437)

Area Scan (101x71x1): Interpolated grid: $dx=1.500$ mm, $dy=1.500$ mm

Maximum value of SAR (interpolated) = 0.663 W/kg


Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8$ mm, $dy=8$ mm, $dz=5$ mm

Reference Value = 6.211 V/m; Power Drift = 0.11 dB

Peak SAR (extrapolated) = 1.21 W/kg

SAR(1 g) = 0.622 W/kg; SAR(10 g) = 0.348 W/kg

Maximum value of SAR (measured) = 0.977 W/kg



0 dB = 0.977 W/kg = -0.10 dBW/kg

Test plot 4# WCDMA II_RMC 12.2Kbps_Front_0mm_Ch9400

Communication System: UID 0, WCDMA 3G (0); Frequency: 1880 MHz; Duty Cycle: 1:1
Medium parameters used: $f = 1880$ MHz; $\sigma = 1.39$ S/m; $\epsilon_r = 38.807$; $\rho = 1000$ kg/m³

DASY5 Configuration:

- Probe: EX3DV4 - SN7557; ConvF(8.36, 8.36, 8.36); Calibrated: 4/10/2019,
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn527; Calibrated: 7/9/2020
- Phantom: ELI V8.0; Type: QD OVA 004 Ax; Serial: 2095
- Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7437)

Area Scan (101x71x1): Interpolated grid: $dx=1.500$ mm, $dy=1.500$ mm
Maximum value of SAR (interpolated) = 0.462 W/kg


Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8$ mm, $dy=8$ mm, $dz=5$ mm

Reference Value = 0 V/m; Power Drift = 0.00 dB

Peak SAR (extrapolated) = 0.904 W/kg

SAR(1 g) = 0.407 W/kg; SAR(10 g) = 0.208 W/kg

Maximum value of SAR (measured) = 0.636 W/kg



0 dB = 0.636 W/kg = -1.97 dBW/kg

Test plot 5# CDMA_RC3 SO32 (F+SCH) _Front_0mm_Ch384

Communication System: UID 0, CDMA2000 BC0 (0); Frequency: 836.52 MHz; Duty Cycle: 1:1
Medium parameters used: $f = 837$ MHz; $\sigma = 0.908$ S/m; $\epsilon_r = 42.001$; $\rho = 1000$ kg/m³

DASY5 Configuration:

- Probe: EX3DV4 - SN7557; ConvF(10.1, 10.1, 10.1); Calibrated: 4/10/2019,
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn527; Calibrated: 7/9/2020
- Phantom: ELI V8.0; Type: QD OVA 004 Ax; Serial: 2095
- Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7437)

Area Scan (101x71x1): Interpolated grid: $dx=1.500$ mm, $dy=1.500$ mm
Maximum value of SAR (interpolated) = 0.701 W/kg


Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8$ mm, $dy=8$ mm, $dz=5$ mm

Reference Value = 3.498 V/m; Power Drift = -0.02 dB

Peak SAR (extrapolated) = 1.49 W/kg

SAR(1 g) = 0.673 W/kg; SAR(10 g) = 0.355 W/kg

Maximum value of SAR (measured) = 1.12 W/kg



Test plot 6#EVDO_RTAP 153.6Kbps _Front_0mm_Ch384

Communication System: UID 0, CDMA2000 BC0 (0); Frequency: 836.52 MHz; Duty Cycle: 1:1
Medium parameters used: $f = 837$ MHz; $\sigma = 0.908$ S/m; $\epsilon_r = 42.001$; $\rho = 1000$ kg/m³

DASY5 Configuration:

- Probe: EX3DV4 - SN7557; ConvF(10.1, 10.1, 10.1); Calibrated: 4/10/2019,
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn527; Calibrated: 7/9/2020
- Phantom: ELI V8.0; Type: QD OVA 004 Ax; Serial: 2095
- Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7437)

Area Scan (101x71x1): Interpolated grid: $dx=1.500$ mm, $dy=1.500$ mm
Maximum value of SAR (interpolated) = 0.676 W/kg


Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8$ mm, $dy=8$ mm, $dz=5$ mm

Reference Value = 3.384 V/m; Power Drift = -0.10 dB

Peak SAR (extrapolated) = 1.36 W/kg

SAR(1 g) = 0.606 W/kg; SAR(10 g) = 0.342 W/kg

Maximum value of SAR (measured) = 1.01 W/kg



Test plot 7#LTE Band 17_10M_QPSK_1RB_0offset_Back_0mm_Ch23790

Communication System: UID 0, FDD LTE 4G (0); Frequency: 710 MHz; Duty Cycle: 1:1
Medium parameters used: $f = 710 \text{ MHz}$; $\sigma = 0.856 \text{ S/m}$; $\epsilon_r = 41.786$; $\rho = 1000 \text{ kg/m}^3$

DASY5 Configuration:

- Probe: EX3DV4 - SN7382; ConvF(10.41, 10.41, 10.41); Calibrated: 4/10/2019,
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn527; Calibrated: 7/9/2020
- Phantom: ELI V8.0; Type: QD OVA 004 Ax; Serial: 2095
- Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7437)

Area Scan (101x61x1): Interpolated grid: $dx=1.500 \text{ mm}$, $dy=1.500 \text{ mm}$

Maximum value of SAR (interpolated) = 0.926 W/kg


Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 8.740 V/m ; Power Drift = 0.06 dB

Peak SAR (extrapolated) = 1.37 W/kg

SAR(1 g) = 0.682 W/kg ; SAR(10 g) = 0.384 W/kg

Maximum value of SAR (measured) = 1.09 W/kg



0 dB = 1.09 W/kg = 0.37 dBW/kg

Test plot 8#LTE Band 5_10M_QPSK_1RB_0offset_Back_0mm_Ch20525

Communication System: UID 0, FDD LTE 4G (0); Frequency: 836.5 MHz; Duty Cycle: 1:1
Medium parameters used: $f = 836.5$ MHz; $\sigma = 0.908$ S/m; $\epsilon_r = 42.001$; $\rho = 1000$ kg/m³

DASY5 Configuration:

- Probe: EX3DV4 - SN7557; ConvF(10.1, 10.1, 10.1); Calibrated: 4/10/2019,
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn527; Calibrated: 7/9/2020
- Phantom: ELI V8.0; Type: QD OVA 004 Ax; Serial: 2095
- Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7437)

Area Scan (101x61x1): Interpolated grid: $dx=1.500$ mm, $dy=1.500$ mm

Maximum value of SAR (interpolated) = 1.04 W/kg


Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8$ mm, $dy=8$ mm, $dz=5$ mm

Reference Value = 7.412 V/m; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 1.38 W/kg

SAR(1 g) = 0.715 W/kg; SAR(10 g) = 0.398 W/kg

Maximum value of SAR (measured) = 1.13 W/kg



0 dB = 1.13 W/kg = 0.53 dBW/kg

Test plot 9#LTE Band 4_20M_QPSK_1RB_0offset_Right Side_0mm_Ch20175

Communication System: UID 0, FDD LTE 4G (0); Frequency: 1732.5 MHz;Duty Cycle: 1:1
Medium parameters used: $f = 1733$ MHz; $\sigma = 1.38$ S/m; $\epsilon_r = 39.696$; $\rho = 1000$ kg/m³

DASY5 Configuration:

- Probe: EX3DV4 - SN7557;ConvF(8.67, 8.67, 8.67); Calibrated: 4/10/2019,
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn527; Calibrated: 7/9/2020
- Phantom: ELI V8.0; Type: QD OVA 004 Ax; Serial: 2095
- Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7437)

Area Scan (31x101x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.805 W/kg


Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 16.22 V/m; Power Drift = 0.05 dB

Peak SAR (extrapolated) = 0.962 W/kg

SAR(1 g) = 0.529 W/kg; SAR(10 g) = 0.290 W/kg

Maximum value of SAR (measured) = 0.781 W/kg



0 dB = 0.781 W/kg = -1.07 dBW/kg

Test plot 10#LTE Band 2_20M_QPSK_1RB_0offset_Front_0mm_Ch18900

Communication System: UID 0, FDD LTE 4G (0); Frequency: 1880 MHz;Duty Cycle: 1:1
Medium parameters used: $f = 1880$ MHz; $\sigma = 1.39$ S/m; $\epsilon_r = 38.807$; $\rho = 1000$ kg/m³

DASY5 Configuration:

- Probe: EX3DV4 - SN7557;ConvF(8.36, 8.36, 8.36); Calibrated: 4/10/2019, ConvF(8.29, 8.29, 8.29); Calibrated: 8/10/2018;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn527; Calibrated: 7/9/2020
- Phantom: ELI V8.0; Type: QD OVA 004 Ax; Serial: 2095
- Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7437)

Area Scan (101x61x1): Interpolated grid: $dx=1.500$ mm, $dy=1.500$ mm
Maximum value of SAR (interpolated) = 0.975 W/kg


Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8$ mm, $dy=8$ mm, $dz=5$ mm

Reference Value = 0.1070 V/m; Power Drift = 0.1 dB

Peak SAR (extrapolated) = 1.34 W/kg

SAR(1 g) = 0.597 W/kg; SAR(10 g) = 0.296 W/kg

Maximum value of SAR (measured) = 0.951 W/kg



0 dB = 0.951 W/kg = -0.22 dBW/kg

Test plot 11#LTE Band 7_20M_QPSK_1RB_0offset_Front_0mm_Ch21100

Communication System: UID 0, FDD LTE 4G (0); Frequency: 2535 MHz; Duty Cycle: 1:1
Medium parameters used: $f = 2535$ MHz; $\sigma = 1.971$ S/m; $\epsilon_r = 37.768$; $\rho = 1000$ kg/m³

DASY5 Configuration:

- Probe: EX3DV4 - SN7557; ConvF(7.21, 7.21, 7.21); Calibrated: 4/10/2019,
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn527; Calibrated: 7/9/2020
- Phantom: ELI V8.0; Type: QD OVA 004 Ax; Serial: 2095
- Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7437)

Area Scan (121x71x1): Interpolated grid: $dx=1.200$ mm, $dy=1.200$ mm

Maximum value of SAR (interpolated) = 0.907 W/kg


Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 0 V/m; Power Drift = 0.00 dB

Peak SAR (extrapolated) = 1.61 W/kg

SAR(1 g) = 0.629 W/kg; SAR(10 g) = 0.255 W/kg

Maximum value of SAR (measured) = 1.15 W/kg



0 dB = 1.15 W/kg = 0.61 dBW/kg

Test plot 12# LTE Band 41_20M_QPSK_1RB_0offset_Front_0mm_Ch40620

Communication System: UID 0, TDD LTE 4G (0); Frequency: 2593 MHz; Duty Cycle: 1:1.59
Medium parameters used: $f = 2593$ MHz; $\sigma = 1.991$ S/m; $\epsilon_r = 37.544$; $\rho = 1000$ kg/m³

DASY5 Configuration:

- Probe: EX3DV4 - SN7557; ConvF(7.21, 7.21, 7.21); Calibrated: 4/10/2019,
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn527; Calibrated: 7/9/2020
- Phantom: ELI V8.0; Type: QD OVA 004 Ax; Serial: 2095
- Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7437)

Area Scan (121x71x1): Interpolated grid: $dx=1.200$ mm, $dy=1.200$ mm
Maximum value of SAR (interpolated) = 1.07 W/kg


Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 0.3040 V/m; Power Drift = -0.07 dB

Peak SAR (extrapolated) = 1.87 W/kg

SAR(1 g) = 0.755 W/kg; SAR(10 g) = 0.295 W/kg

Maximum value of SAR (measured) = 1.36 W/kg



0 dB = 1.36 W/kg = 1.34 dBW/kg

Test plot 13#WLAN 2.4GHz_802.11b 1Mbps_Back_0mm_Ch6

Communication System: UID 0, WIFI2.4G (0); Frequency: 2437 MHz;Duty Cycle: 1:1
Medium parameters used: $f = 2437 \text{ MHz}$; $\sigma = 1.86 \text{ S/m}$; $\epsilon_r = 39.273$; $\rho = 1000 \text{ kg/m}^3$

DASY5 Configuration:

- Probe: EX3DV4 - SN7557;ConvF(7.41, 7.41, 7.41); Calibrated: 4/10/2019,
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn527; Calibrated: 7/9/2020
- Phantom: ELI V8.0; Type: QD OVA 004 Ax; Serial: 2095
- Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7437)

Area Scan (111x71x1): Interpolated grid: $dx=1.200 \text{ mm}$, $dy=1.200 \text{ mm}$

Maximum value of SAR (interpolated) = 0.788 W/kg


Zoom Scan (9x8x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Reference Value = 1.939 V/m ; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 0.932 W/kg

SAR(1 g) = 0.451 W/kg ; SAR(10 g) = 0.220 W/kg

Maximum value of SAR (measured) = 0.725 W/kg



$0 \text{ dB} = 0.725 \text{ W/kg} = -1.40 \text{ dBW/kg}$

Test plot 14#WLAN 5GHz_802.11n-HT20 MCS0_Top Side_0mm_Ch36

Communication System: UID 0, WIFI 5G (0); Frequency: 5180 MHz; Duty Cycle: 1:1
Medium parameters used: $f = 5180 \text{ MHz}$; $\sigma = 4.513 \text{ S/m}$; $\epsilon_r = 36.874$; $\rho = 1000 \text{ kg/m}^3$

DASY5 Configuration:

- Probe: EX3DV4 - SN7557; ConvF(5.38, 5.38, 5.38); Calibrated: 4/10/2019,
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn527; Calibrated: 7/9/2020
- Phantom: ELI V8.0; Type: QD OVA 004 Ax; Serial: 2095
- Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7437)

Area Scan (51x91x1): Interpolated grid: $dx=1.000 \text{ mm}$, $dy=1.000 \text{ mm}$

Maximum value of SAR (interpolated) = 2.54 W/kg


Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=4\text{mm}$, $dy=4\text{mm}$, $dz=1.4\text{mm}$

Reference Value = 0.7330 V/m ; Power Drift = 0.00 dB

Peak SAR (extrapolated) = 3.40 W/kg

SAR(1 g) = 0.552 W/kg ; SAR(10 g) = 0.084 W/kg

Maximum value of SAR (measured) = 1.96 W/kg



$0 \text{ dB} = 1.96 \text{ W/kg} = 2.92 \text{ dBW/kg}$

Test plot 15#WLAN 5GHz_802.11a 6Mbps_Top Side_0mm_Ch157


Communication System: UID 0, WIFI 5G (0); Frequency: 5785 MHz; Duty Cycle: 1:1
Medium parameters used: $f = 5785 \text{ MHz}$; $\sigma = 5.233 \text{ S/m}$; $\epsilon_r = 35.553$; $\rho = 1000 \text{ kg/m}^3$

DASY5 Configuration:

- Probe: EX3DV4 - SN7557; ConvF(4.70, 4.70, 4.70); Calibrated: 4/10/2019,
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn527; Calibrated: 7/9/2020
- Phantom: ELI V8.0; Type: QD OVA 004 Ax; Serial: 2095
- Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7437)

Area Scan (51x91x1): Interpolated grid: $dx=1.000 \text{ mm}$, $dy=1.000 \text{ mm}$
Maximum value of SAR (interpolated) = 1.13 W/kg

Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=4\text{mm}$, $dy=4\text{mm}$, $dz=1.4\text{mm}$
Reference Value = 0 V/m ; Power Drift = 0.00 dB
Peak SAR (extrapolated) = 1.67 W/kg
SAR(1 g) = 0.302 W/kg ; SAR(10 g) = 0.063 W/kg
Maximum value of SAR (measured) = 0.873 W/kg



$0 \text{ dB} = 0.873 \text{ W/kg} = -0.59 \text{ dBW/kg}$

APPENDIX A MEASUREMENT UNCERTAINTY

The uncertainty budget has been determined for the measurement system and is given in the following Table.

Measurement uncertainty evaluation for IEEE1528-2013 SAR test

Source of uncertainty	Tolerance/ uncertainty ± %	Probability distribution	Divisor	ci (1 g)	ci (10 g)	Standard uncertainty ± %, (1 g)	Standard uncertainty ± %, (10 g)
Measurement system							
Probe calibration	6.55	N	1	1	1	6.6	6.6
Axial Isotropy	4.7	R	$\sqrt{3}$	1	1	2.7	2.7
Hemispherical Isotropy	9.6	R	$\sqrt{3}$	0	0	0.0	0.0
Boundary effect	1.0	R	$\sqrt{3}$	1	1	0.6	0.6
Linearity	4.7	R	$\sqrt{3}$	1	1	2.7	2.7
Detection limits	1.0	R	$\sqrt{3}$	1	1	0.6	0.6
Readout electronics	0.3	N	1	1	1	0.3	0.3
Response time	0.0	R	$\sqrt{3}$	1	1	0.0	0.0
Integration time	0.0	R	$\sqrt{3}$	1	1	0.0	0.0
RF ambient conditions – noise	1.0	R	$\sqrt{3}$	1	1	0.6	0.6
RF ambient conditions–reflections	1.0	R	$\sqrt{3}$	1	1	0.6	0.6
Probe positioner mech. Restrictions	0.8	R	$\sqrt{3}$	1	1	0.5	0.5
Probe positioning with respect to phantom shell	6.7	R	$\sqrt{3}$	1	1	3.9	3.9
Post-processing	2.0	R	$\sqrt{3}$	1	1	1.2	1.2
Test sample related							
Test sample positioning	2.8	N	1	1	1	2.8	2.8
Device holder uncertainty	6.3	N	1	1	1	6.3	6.3
Drift of output power	5.0	R	$\sqrt{3}$	1	1	2.9	2.9
Phantom and set-up							
Phantom uncertainty (shape and thickness tolerances)	4.0	R	$\sqrt{3}$	1	1	2.3	2.3
Liquid conductivity target)	5.0	R	$\sqrt{3}$	0.64	0.43	1.8	1.2
Liquid conductivity meas.)	2.5	N	1	0.64	0.43	1.6	1.1
Liquid permittivity target)	5.0	R	$\sqrt{3}$	0.6	0.49	1.7	1.4
Liquid permittivity meas.)	2.5	N	1	0.6	0.49	1.5	1.2
Combined standard uncertainty		RSS				12.2	12.0
Expanded uncertainty 95 % confidence interval)						24.3	23.9

Measurement uncertainty evaluation for IEC62209-2 SAR test


Source of uncertainty	Tolerance/ uncertainty $\pm$ %	Probability distribution	Divisor	ci (1 g)	ci (10 g)	Standard uncertainty $\pm$ %, (1 g)	Standard uncertainty $\pm$ %, (10 g)
Measurement system							
Probe calibration	6.55	N	1	1	1	6.6	6.6
Axial Isotropy	4.7	R	$\sqrt{3}$	1	1	2.7	2.7
Hemispherical Isotropy	9.6	R	$\sqrt{3}$	0	0	0.0	0.0
Linearity	4.7	R	$\sqrt{3}$	1	1	2.7	2.7
Modulation Response	0.0	R	$\sqrt{3}$	1	1	0.0	0.0
Detection limits	1.0	R	$\sqrt{3}$	1	1	0.6	0.6
Boundary effect	1.0	R	$\sqrt{3}$	1	1	0.6	0.6
Readout electronics	0.3	N	1	1	1	0.3	0.3
Response time	0.0	R	$\sqrt{3}$	1	1	0.0	0.0
Integration time	0.0	R	$\sqrt{3}$	1	1	0.0	0.0
RF ambient conditions – noise	1.0	R	$\sqrt{3}$	1	1	0.6	0.6
RF ambient conditions–reflections	1.0	R	$\sqrt{3}$	1	1	0.6	0.6
Probe positioner mech. Restrictions	0.8	R	$\sqrt{3}$	1	1	0.5	0.5
Probe positioning with respect to phantom shell	6.7	R	$\sqrt{3}$	1	1	3.9	3.9
Post-processing	2.0	R	$\sqrt{3}$	1	1	1.2	1.2
Test sample related							
Device holder Uncertainty	6.3	N	1	1	1	6.3	6.3
Test sample positioning	2.8	N	1	1	1	2.8	2.8
Power scaling	4.5	R	$\sqrt{3}$	1	1	2.6	2.6
Drift of output power	5.0	R	$\sqrt{3}$	1	1	2.9	2.9
Phantom and set-up							
Phantom uncertainty (shape and thickness tolerances)	4.0	R	$\sqrt{3}$	1	1	2.3	2.3
Algorithm for correcting SAR for deviations in permittivity and conductivity	1.9	N	1	1	0.84	1.1	0.9
Liquid conductivity (meas.)	2.5	N	1	0.64	0.43	1.6	1.1
Liquid permittivity (meas.)	2.5	N	1	0.6	0.49	1.5	1.2
Temp. unc. - Conductivity	1.7	R	$\sqrt{3}$	0.78	0.71	0.8	0.7
Temp. unc. - Permittivity	0.3	R	$\sqrt{3}$	0.23	0.26	0.0	0.0
Combined standard uncertainty		RSS				12.2	12.1
Expanded uncertainty 95 % confidence interval)						24.5	24.2

APPENDIX B EUT TEST POSITION PHOTOS

Front(0mm)



Back(0mm)




Left (0mm)



Right Side (0mm)



Top (0mm)



APPENDIX C CALIBRATION CERTIFICATES

Please Refer to the Attachment.

***** END OF REPORT *****