TEST REPORT

Part 15 Subpart C 15.247

Equipment under test	Hair α-RAY
Model name	HA-M2192
derivative model	HA-M2142
FCC ID	2AUG3-HAM2192
Applicant	Cellreturn Co., Ltd.
Manufacturer	Cellreturn Co., Ltd.
Date of test(s)	2019.12.09~2019.12.20
Date of issue	2020.01.30

Issued to
Cellreturn Co., Ltd.
237, Namdongseo-ro, Namdong-gu, Inchon, Republic of Korea
Tel: +82-1688-1026 / Fax: +82-32-714-3895

Issued by
KES Co., Ltd.
3701, 40, Simin-daero 365beon-gil, Dongan-gu, Anyang-si,
Gyeonggi-do, 14057, Korea
473-21, Gayeo-ro, Yeoju-si, Gyeonggi-do, Korea
Tel: +82-31-425-6200 / Fax: +82-31-424-0450

Test and report completed by :	**Report approval by :**
Yeong-Jun Cho Test engineer	Hyeon-Su, Jang Technical manager

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact shchoi@kes.co.kr

Revision history

Revision	Date of issue	Test report No.	Description
-	2020.01.30	KES-RF-20T0019	Initial

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact shchoi@kes.co.kr

TABLE OF CONTENTS

1. General information 4
1.1. EUT description 4
1.2. Test configuration 4
1.3. Device modifications 5
1.4. Accessory information 5
1.5. Measurement results explanation example 5
1.6. Measurement Uncertainty 5
1.7. Frequency/channel operations 5
2. Summary of tests 6
3. Test results 7
3.1. 6 dB bandwidth 7
3.2. Output power 9
3.3. Power spectral density 11
3.4. Radiated restricted band and emissions 13
3.5. Conducted spurious emissions & band edge 27
3.6. AC conducted emissions 29
Appendix A. Measurement equipment 31
Appendix B. Test setup photos 32

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact shchoi@kes.co.kr

1. General information

Applicant:	Cellreturn Co., Ltd.
Applicant address:	237, Namdongseo-ro, Namdong-gu, Inchon, Republic of Korea
Test site:	KES Co., Ltd.
Test site address:	3701, 40, Simin-daero 365beon-gil, Dongan-gu, Anyang-si, Gyeonggi-do, 14057, Korea 473-21, Gayeo-ro, Yeoju-si, Gyeonggi-do, Korea
Test Facility	FCC Accreditation Designation No.: KR0100, Registration No.: 444148
FCC rule part(s):	15.247
FCC ID:	2AUG3-HAM2192
Test device serial No.:	☒ Production ☐ Pre-production ☐ Engineering

1.1. EUT description

Equipment under test	Hair α-RAY
Frequency range	2 402 ㎒ ~ 2 480 ㎒ (BLE)
Model:	HA-M2192
Modulation technique	GFSK
Number of channels	2 402 ㎒ ~ 2 480 ㎒ (BLE) : 40ch
Antenna specification	Antenna type : PCB Antenna // Peak gain: -0.84 ㏈i
Power source	DC 3.7 V (Battery)
S/W version	1.0.6
H/W version	Rev. 1.1

1.2. Test configuration

The **Cellreturn Co., Ltd. // Hair α-RAY // FCC ID: 2AUG3-HAM2192** was tested according to the specification of EUT, the EUT must comply with following standards and KDB documents.

FCC Part 15.247
KDB 558074 D01 v05 r02
ANSI C63.10-2013

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact shchoi@kes.co.kr

1.3. Device modifications

Model name	Near-infrared	α near-infrared	Red wavelengths
HA-M2192	240 ea	240 ea	240 ea
HA-M2142	150 ea	150 ea	150 ea

1.4. Accessory information

N/A

1.5. Measurement results explanation example

For all conducted test items :

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Offset(dB) = RF cable loss(dB) + attenuator factor(dB).
= 1.52 + 10 = 11.52 (dB)

1.6. Measurement Uncertainty

Test Item		Uncertainty
Uncertainty for Conduction emission test		2.62 dB
Uncertainty for Radiation emission test (include Fundamental emission)	9kHz - 30MHz	4.54 dB
	30MHz - 1GHz	4.36 dB
	Above 1GHz – 25GHz	5.00 dB
Note. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.		

1.7. Frequency/channel operations

Ch.	Frequency (MHz)	Rate(Mbps)
00	2 402	LE 1 Mbps
. .	. .	. .
20	2 442	LE 1 Mbps
. .	. .	. .
39	2 480	LE 1 Mbps

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact shchoi@kes.co.kr

2. Summary of tests

Section in FCC Part 15	Test description	Test results
15.247(a)(2)	6 dB bandwidth	Pass
15.247(b)(3)	Output power	Pass
15.247(e)	Power spectral density	Pass
15.205 15.209	Radiated restricted band and emission	Pass
15.247(d)	Conducted spurious emission and band edge	Pass
15.207(a)	AC Conducted emissions	Pass

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact shchoi@kes.co.kr

3. Test results

3.1. 6 dB bandwidth

Test procedure

ANSI C63.10-2013 - Section 11.8.2

Test setup



ANSI C63.10-2013 - Section 11.8.2

The automatic bandwidth measurement capability of an instrument may be employed using the X dB bandwidth mode with X set to 6 dB, if the functionality described above (i.e., RBW = 100 kHz, VBW ≥ 3 × RBW, peak detector with maximum hold) is implemented by the instrumentation function. When using this capability, care shall be taken so that the bandwidth measurement is not influenced by any intermediate power nulls in the fundamental emission that might be ≥ 6 dB.

Limit

According to §15.247(a)(2), systems using digital modulation techniques may operate 902 ~ 928 MHz, 2 400 ~ 2 483.5 MHz, and 5 725 ~ 5 850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact shchoi@kes.co.kr

Test results

Mode: LE 1 Mbps

Frequency(㎒)	6 dB bandwidth(㎒)	Limit(㎒)
2 402	0.678	0.500
2 442	0.662	
2 480	0.679	

LE







N/A

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact shchoi@kes.co.kr

3.2. Output power

Test procedure

ANSI C63.10-2013 - Section 11.9.1.3 and 11.9.2.3.2

Test setup



ANSI C63.10-2013 - Section 11.9.1.3

The maximum peak conducted output power may be measured using a broadband peak RF power meter. The power meter shall have a video bandwidth that is greater than or equal to the DTS ba ndwidth and shall use a fast-responding diode detector.

ANSI C63.10-2013 - Section 11.9.2.3.2

Alternatively, measurements may be performed using a wideband gated RF power meter provided that the gate parameters are adjusted such that the power is measured only when the EUT is transmitting at its maximum power control level. Because the measurement is made only during the ON time of the transmitter, no duty cycle correction is required.

Limit

According to §15.247(b)(3), For systems using digital modulation in the 902~928 ㎒, 2 400~2 483.5 ㎒, and 5 725~5 850 ㎒ bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted out-put power. Maximum Conducted Out-put Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact shchoi@kes.co.kr

Test results

Mode: LE 1 Mbps

Mode	2 402 ㎒		2 442 ㎒		2 480 ㎒	
	Peak (dBm)	Average (dBm)	Peak (dBm)	Average (dBm)	Peak (dBm)	Average (dBm)
LE	-2.41	-3.15	-4.86	-5.15	-5.37	-6.12

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact shchoi@kes.co.kr

3.3. Power spectral density

Test procedure

ANSI C63.10-2013 - Section 11.10.2

Test setup



Section 10.2 & ANSI C63.10-2013 - Section 11.10.2

a. Set analyzer center frequency to DTS channel center frequency.
b. Set the span to 1.5 times the DTS bandwidth.
c. Set the RBW to 3 ㎑ ≤ RBW ≤ 100 ㎑
d. Set the VBW ≥ [3 × RBW].
e. Detector = peak.
f. Sweep time = auto couple.
g. Trace mode = max hold.
h. Allow trace to fully stabilize.
i. Use the peak marker function to determine the maximum amplitude level within the RBW.
j. If measured value exceeds requirement, then reduce RBW (but no less than 3 kHz) and repeat.

Limit

According to §15.247(e), For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 ㏈m in any 3 ㎑ band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact shchoi@kes.co.kr

Results

Mode: LE 1 Mbps

Frequency(MHz)	PSD (dBm)	Limit(dBm)
2 402	-13.96	8.00
2 442	-14.78	
2 480	-17.33	

LE







Blank

3.4. Radiated restricted band and emissions

Test setup

The diagram below shows the test setup that is utilized to make the measurements for emission from 9 ㎑ to 30 ㎒ Emissions.



The diagram below shows the test setup that is utilized to make the measurements for emission from 30 ㎒ to 1 ㎓ emissions.



The diagram below shows the test setup that is utilized to make the measurements for emission from 1 ㎓ to the tenth harmonic of the highest fundamental frequency or to 40 ㎓ emissions, whichever is lower.



Test procedure

Radiated emissions from the EUT were measured according to the dictates in section 11.11 & 11.12 of ANSI C63.10-2013.

Test procedure below 30 ㎒

1. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter anechoic chamber test site. The table was rotated 360 degrees to determine the position of the highest radiation.
2. Then antenna is a loop antenna is fixed at one meter above the ground to determine the maximum value of the field strength. Both parallel, ground parallel and perpendicular of the antenna are set to make the measurement. It was determined that **parallel** was worst-case orientation; therefore, all final radiated testing was performed with the EUT in **parallel.**
3. For each suspected emission, the EUT was arranged to its worst case and then the table was turned from 0 degrees to 360 degrees to find the maximum reading.
4. The test-receiver system was set to average or quasi peak detect function and Specified Bandwidth with Maximum hold mode.

Test procedure above 30 ㎒

1. The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter anechoic chamber test site. The table was rotated 360 degrees to determine the position of the highest radiation.
2. The antenna is a bi-log antenna, a horn antenna ,and its height are varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
3. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the table was turned from 0 degrees to 360 degrees to find the maximum reading.
4. The test receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact shchoi@kes.co.kr

5. Spectrum analyzer settings for $f < 1$ ㎓:
   ① Span = wide enough to fully capture the emission being measured
   ② RBW = 100 ㎑
   ③ VBW ≥ RBW
   ④ Detector = quasi peak
   ⑤ Sweep time = auto
   ⑥ Trace = max hold
6. Spectrum analyzer settings for $f \geq 1$ ㎓: Peak
   ① Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
   ② RBW = 1 ㎒
   ③ VBW ≥ 3 ㎒
   ④ Detector = peak
   ⑤ Sweep time = auto
   ⑥ Trace = max hold
   ⑦ Trace was allowed to stabilize

7. Spectrum analyzer settings for $f \geq 1$ ㎓: Average
   ① Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
   ② RBW = 1 ㎒
   ③ VBW ≥ 3 × RBW
   ④ Detector = RMS, if span/(# of points in sweep) ≤ (RBW/2). Satisfying this condition may require increasing the number of points in the sweep or reducing the span. If this condition cannot be satisfied, then the detector mode shall be set to peak.
   ⑤ Averaging type = power(i.e., RMS)
      1) As an alternative, the detector and averaging type may be set for linear voltage averaging.
      2) Some instruments require linear display mode in order to use linear voltage averaging. Log or ㏈ averaging shall not be used.
   ⑥ Sweep = auto
   ⑦ Trace = max hold
   ⑧ Perform a trace average of at least 100 traces.
   ⑨ A correction factor shall be added to the measurement results prior to comparing to the emission limit in order to compute the emission level that would have been measured had the test been performed at 100 percent duty cycle. The correction factor is computed as follows:
      1) If power averaging (RMS) mode was used in step ⑤, then the applicable correction factor is 10 log(1/x), where x is the duty cycle.
      2) If linear voltage averaging mode was used in step ⑤, then the applicable correction factor is 20 log(1/x), where x is the duty cycle.
      3) If a specific emission is demonstrated to be continuous (≥ 98 percent duty cycle) rather than turning on and off with the transmit cycle, then no duty cycle correction is required for that emission.

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact shchoi@kes.co.kr

Note.

1. f<30 ㎒, extrapolation factor of 40 ㏈/decade of distance. $F_d = 40\log(D_m/Ds)$
   f ≥30 ㎒, extrapolation factor of 20 ㏈/decade of distance. $F_d = 20\log(D_m/Ds)$
   Where:
   F_d = Distance factor in ㏈
   D_m = Measurement distance in meters
   D_s = Specification distance in meters
2. Field strength(㏈㎶/m) = Level(㏈㎶) + CF (㏈) + or DCF(㏈)
3. Margin(㏈) = Limit(㏈㎶/m) - Field strength(㏈㎶/m)
4. Emissions below 18 ㎓ were measured at a 3 meter test distance while emissions above 18 ㎓ were measured at a 1 meter test distance with the application of a distance correction factor.
5. The fundamental of the EUT was investigated in three orthogonal orientations X, Y and Z, it was determined that **X orientation** was worst-case orientation; therefore, all final radiated testing was performed with the EUT in **X orientation.**
6. The worst-case emissions are reported however emissions whose levels were not within 20 ㏈ of respective limits were not reported.
7. According to exploratory test no any obvious emission were detected from 9 ㎑ to 30 ㎒. Although these tests were performed other than open field site, adequate comparison measurements were confirmed against 30 m open field site. Therefore sufficient tests were made to demonstrate that the alternative site produces results that correlate with the ones of tests made in an open field based on KDB 414788.

Limit

According to 15.209(a), for an intentional radiator devices, the general required of field strength of radiated emissions from unintentional radiators at a distance of 3 meters shall not exceed the following values：

Frequency (㎒)	Distance (Meters)	Radiated (㎶/m)
0.009 ~ 0.490	300	2400/F(㎑)
0.490 ~ 1.705	30	24000/F(㎑)
1.705 ~ 30.0	30	30
30 ~ 88	3	100**
88 ~ 216	3	150**
216 ~ 960	3	200**
Above 960	3	500

**Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54 ~ 72 ㎒, 76 ~ 88 ㎒, 174 ~ 216 ㎒ or 470 ~ 806 ㎒. However, operation within these frequency bands is permitted under other sections of this Part, e.g., Sections 15.231 and 15.241.

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact shchoi@kes.co.kr

Duty cycle

Regarding to KDB 558074 D01_v05 r02, 6. Measurements of duty cycle and transmission duration shall be performed using one of the following techniques:

a) A diode detector and an oscilloscope that together have sufficiently short response time to permit accurate measurements of the on- and off-times of the transmitted signal.

b) The zero-span mode on a spectrum analyzer or EMI receiver if the response time and spacing between bins on the sweep are sufficient to permit accurate measurements of the on- and off-times of the transmitted signal.

T_{on} time (㎳)	Period (㎳)	Duty cycle (Linear)	Duty cycle (%)	Duty cycle correction factor (㏈)
10.0	10.0	1	100	0

Duty cycle (Linear) = T_{on} time/Period

DCF(Duty cycle correction factor (㏈)) = 10log(1/duty cycle)

Middle channel



Test results (Below 30 ㎒)

Mode:	LE 1 Mbps
Distance of measurement:	3 meter
Channel:	0 (Worst case)

Parallel



Note.
No spurious emission were detected below 30 ㎒.

Test results (Below 1 000 ㎒)

Mode:	LE 1 Mbps
Distance of measurement:	3 meter
Channel:	0 (Worst case)

Horizontal // Vertical



Final Result

No.	Frequency [MHz]	(P)	Reading QP [dB(uV)]	c.f [dB(1/m)]	Result QP [dB(uV/m)]	Limit QP [dB(uV/m)]	Margin QP [dB]	Height [cm]	Angle [deg]	Remark
1	47.945	H	46.4	-22.1	24.3	40.0	15.7	388.0	82.0	
2	47.945	V	55.8	-22.1	33.7	40.0	6.3	135.0	107.0	
3	95.960	H	46.2	-24.0	22.2	43.5	21.3	400.0	268.0	
4	95.960	V	50.9	-24.0	26.9	43.5	16.6	211.0	322.0	
5	119.968	H	48.7	-24.9	23.8	43.5	19.7	330.0	109.0	
6	119.968	V	51.3	-24.9	26.4	43.5	17.1	157.0	227.0	

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact shchoi@kes.co.kr

Test results (Above 1 000 ㎒)

Mode: LE 1 Mbps

Distance of measurement: 3 meter

Channel: 0

- **Spurious**

Frequency (㎒)	Level (dBμV)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dBμV/m)	Limit (dBμV/m)	Margin (dB)
1 068.00	46.59	Peak	H	-8.70	-	37.89	74.00	36.11
1 704.80	45.27	Peak	H	-3.99	-	41.28	74.00	32.72
2 000.00	49.67	Peak	H	-0.97	-	48.70	74.00	25.30
3 771.00	48.25	Peak	H	3.02	-	51.27	74.00	22.73
1 218.50	46.66	Peak	V	-7.74	-	38.92	74.00	35.08
1 632.40	46.27	Peak	V	-4.68	-	41.59	74.00	32.41
2 839.40	44.12	Peak	V	1.23	-	45.35	74.00	28.65
3 944.00	47.06	Peak	V	3.88	-	50.94	74.00	23.06

- **Band edge**

Frequency (㎒)	Level (dBμV)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dBμV/m)	Limit (dBμV/m)	Margin (dB)
2 345.77	44.61	Peak	H	-0.30	-	44.31	74.00	29.69
2 367.89	43.97	Peak	V	-0.26	-	43.71	74.00	30.29

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact shchoi@kes.co.kr

Restricted band // Horizontal // Peak



Restricted band // Vertical // Peak



Horizontal // Peak for 1 GHz to 3 GHz



Vertical // Peak for 1 GHz to 3 GHz



Horizontal // Peak for 3 GHz to 18 GHz



Vertical // Peak for 3 GHz to 18 GHz



Note.
- Average test would be performed if the peak result were greater than the average limit.

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact shchoi@kes.co.kr

Mode: LE 1 Mbps

Distance of measurement: 3 meter

Channel: 20

- **Spurious**

Frequency (MHz)	Level (dBμV)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dBμV/m)	Limit (dBμV/m)	Margin (dB)
1 331.40	50.37	Peak	H	-7.02	-	43.35	74.00	30.65
1 496.40	47.75	Peak	H	-6.00	-	41.75	74.00	32.25
1 661.40	49.01	Peak	H	-4.40	-	44.61	74.00	29.39
3 705.00	47.03	Peak	H	2.69	-	49.72	74.00	24.28
1 140.40	46.01	Peak	V	-8.24	-	37.77	74.00	36.23
1 331.40	47.60	Peak	V	-7.02	-	40.58	74.00	33.42
1 835.00	44.29	Peak	V	-2.71	-	41.58	74.00	32.42
4 053.00	46.91	Peak	V	4.25	-	51.16	74.00	22.84

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact shchoi@kes.co.kr

Horizontal // Peak for 1 ㎓ to 3 ㎓



Vertical // Peak for 1 ㎓ to 3 ㎓



Horizontal // Peak for 3 ㎓ to 18 ㎓



Vertical // Peak for 3 ㎓ to 18 ㎓



Note.
- Average test would be performed if the peak result were greater than the average limit.

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact shchoi@kes.co.kr

Mode: LE 1 Mbps

Distance of measurement: 3 meter

Channel: 39

- **Spurious**

Frequency (MHz)	Level (dBμV)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dBμV/m)	Limit (dBμV/m)	Margin (dB)
1 117.20	45.50	Peak	H	-8.39	-	37.11	74.00	36.89
1 331.40	48.29	Peak	H	-7.02	-	41.27	74.00	32.73
1 997.10	45.50	Peak	H	-1.00	-	44.50	74.00	29.50
4 183.00	47.40	Peak	H	4.48	-	51.88	74.00	22.12
1 163.50	46.11	Peak	V	-8.09	-	38.02	74.00	35.98
1 331.40	46.34	Peak	V	-7.02	-	39.32	74.00	34.68
1 988.40	44.86	Peak	V	-1.09	-	43.77	74.00	30.23
3 054.00	48.55	Peak	V	1.79	-	50.34	74.00	23.66

- **Band edge**

Frequency (MHz)	Level (dBμV)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dBμV/m)	Limit (dBμV/m)	Margin (dB)
2 495.58	45.62	Peak	H	-0.02	-	45.60	74.00	28.40
2 494.09	45.44	Peak	V	-0.03	-	45.41	74.00	28.59

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact shchoi@kes.co.kr

Restricted band // Horizontal // Peak



Restricted band // Vertical // Peak



Horizontal // Peak for 1 GHz to 3 GHz



Vertical // Peak for 1 GHz to 3 GHz



Horizontal // Peak for 3 GHz to 18 GHz



Vertical // Peak for 3 GHz to 18 GHz



Note.
- Average test would be performed if the peak result were greater than the average limit.

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact shchoi@kes.co.kr

Test results (18 ㎓ to 30 ㎓) – Worst case

Mode:	LE 1 Mbps (Worst case)
Distance of measurement:	3 meter
Channel:	0 (Worst case)

Horizontal Peak	Vertical Peak
	

Note.
No spurious emission were detected above 18 ㎓.

3.5. Conducted spurious emissions & band edge

Test setup



Test procedure

Band edge

ANSI C63.10-2013 - Section 11.11

1. Start and stop frequency were set such that the band edge would be placed in the center of the plot
2. Span was set large enough so as to capture all out of band emissions near the band edge
3. Set the RBW = 100 ㎑
4. Set the VBW = [3 × RBW].
5. Detector = Peak
6. Sweep time = auto
7. Trace mode = max hold
8. Allow trace to fully stabilize.

Out of band emissions

ANSI C63.10-2013 - Section 11.11

1. Start frequency was set to 30 ㎒ and stop frequency was set to 25 ㎓ for 2.4 ㎓ frequencies and 40 ㎓ for 5 ㎓ frequencies
2. Set the RBW = 100 ㎑
3. Set the VBW = [3 × RBW].
4. Detector = Peak
5. Sweep time = auto
6. Trace mode = max hold
7. Allow trace to fully stabilize.

Limit

According to 15.247(d), in any 100 ㎑ bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 ㏈ below that in the 100 ㎑ bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval , as permitted under paragraph(b)(3) of this section , the attenuation required under this paragraph shall be 30 ㏈ instead of 20 ㏈. Attenuation below the general limits specified in section 15.209(a) is not required. In addition, radiated emission which in the restricted band, as define in section 15.205(a), must also comply the radiated emission limits specified in section 15.209(a) (see section 15.205(c))

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact shchoi@kes.co.kr

Test results

LE 1 Mbps













This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact shchoi@kes.co.kr

3.6. AC conducted emissions

Test setup



Limit

According to 15.207(a), for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 ㎑ to 30 ㎒, shall not exceed the limits in the following table, as measured using a 50uH/50 ohm line impedance stabilization network (LISN). Compliance with the provision of this paragraph shall on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower applies at the boundary between the frequencies ranges.

According to RSS-Gen Issue 5, 8.8, a radio apparatus that is designed to be connected to the public utility (AC) power line shall ensure that the radio frequency voltage, which is conducted back onto the AC power line on any frequency or frequencies, within the band 150 ㎑ to 30 ㎒, shall not exceed the limits in Table 3. Unless the requirements applicable to a given device state otherwise, for any radio apparatus equipped to operate from the public utility AC power supply either directly or indirectly (such as with a battery charger), the radio frequency voltage of emissions conducted back onto the AC power lines in the frequency range of 0.15 ㎒ to 30 ㎒ shall not exceed the limits shown in Table 3 below. The more stringent limit applies at the frequency range boundaries.
The conducted emissions shall be measured in accordance with the reference publication mentioned in Section 3.

Frequency of Emission (㎒)	Conducted limit (dBμV/m)	
	Quasi-peak	Average
0.15 – 0.50	66 - 56*	56 - 46*
0.50 – 5.00	56	46
5.00 – 30.0	60	50

Note:
1. All AC line conducted spurious emission are measured with a receiver connected to a grounded LISN while the EUT is operating at its maximum duty cycle, at maximum power, and the appropriate frequencies. All data rates and modes were investigated for conducted spurious emission. Only the conducted emissions of the configuration that produced the worst case emissions are reported in this section.
3. Both Cable loss and LISN factor are included in measurement level(QP Level or AV Level).

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact shchoi@kes.co.kr

Test results

Hot Line



Final_Result

Frequency (MHz)	QuasiPeak (dBµV)	CAverage (dBµV)	Limit (dBµV)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)
0.175000	---	40.90	54.72	13.82	1000.0	9.000	L1	9.9
0.175000	51.95	---	64.72	12.77	1000.0	9.000	L1	9.9
1.090000	---	25.01	46.00	20.99	1000.0	9.000	L1	11.1
1.090000	32.16	---	56.00	23.84	1000.0	9.000	L1	11.1
1.185000	---	29.09	46.00	16.91	1000.0	9.000	L1	10.9
1.185000	34.87	---	56.00	21.13	1000.0	9.000	L1	10.9
29.770000	---	20.20	50.00	29.80	1000.0	9.000	L1	11.1
29.770000	33.96	---	60.00	26.04	1000.0	9.000	L1	11.1
29.955000	---	20.51	50.00	29.49	1000.0	9.000	L1	11.1
29.955000	34.56	---	60.00	25.44	1000.0	9.000	L1	11.1

Neutral Line



Final_Result

Frequency (MHz)	QuasiPeak (dBµV)	CAverage (dBµV)	Limit (dBµV)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)
0.170000	---	37.35	54.96	17.61	1000.0	9.000	N	9.9
0.170000	49.21	---	64.96	15.75	1000.0	9.000	N	9.9
0.180000	---	36.66	54.49	17.83	1000.0	9.000	N	9.9
0.180000	48.29	---	64.49	16.20	1000.0	9.000	N	9.9
2.660000	---	27.84	46.00	18.16	1000.0	9.000	N	10.1
2.660000	33.40	---	56.00	22.60	1000.0	9.000	N	10.1
2.920000	---	26.14	46.00	19.86	1000.0	9.000	N	10.3
2.920000	31.98	---	56.00	24.02	1000.0	9.000	N	10.3
29.580000	---	24.25	50.00	25.75	1000.0	9.000	N	11.2
29.580000	35.22	---	60.00	24.78	1000.0	9.000	N	11.2
29.950000	---	20.62	50.00	29.38	1000.0	9.000	N	11.2
29.950000	34.63	---	60.00	25.37	1000.0	9.000	N	11.2

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact shchoi@kes.co.kr

Appendix A. Measurement equipment

Equipment	Manufacturer	Model	Serial No.	Cal. Day to next Cal. day
Spectrum Analyzer	R&S	FSV30	101389	2019.01.16 ~ 2020.01.16 2020.01.15 ~ 2021.01.15
Spectrum Analyzer	R&S	FSV40	101002	2019.06.24 ~ 2020.06.24
8360B Series Swept Signal Generator	HP	83630B	3844A00786	2019.01.15 ~ 2020.01.15 2020.01.15 ~ 2021.01.15
Power Meter	Anritsu	ML2495A	1438001	2019.01.15 ~ 2020.01.15 2020.01.15 ~ 2021.01.15
Pulse Power Sensor	Anritsu	MA2411B	1339205	2019.01.15 ~ 2020.01.15 2020.01.15 ~ 2021.01.15
Attenuator	HP	8494B	2630A12857	2019.01.15 ~ 2020.01.15 2020.01.15 ~ 2021.01.15
Loop Antenna	Schwarzbeck	FMZB1513	225	2019.02.15 ~ 2021.02.15
Trilog-broadband antenna	SCHWARZBECK	VULB 9163	715	2018.11.29 ~ 2020.11.29
Horn Antenna	A.H	SAS-571	414	2019.02.11 ~ 2021.02.11
Horn Antenna	SCHWARZBECK	BBHA9170	BBHA 9170550	2019.02.19 ~ 2021.02.19
High Pass Filter	Wainwright Instrument Gmbh	WHJS3000-10TT	1	2019.06.24 ~ 2020.06.24
Band Reject Filter	MICRO-TRONICS	BRM50702	G272	2019.01.16 ~ 2020.01.16 2020.01.15 ~ 2021.01.15
Low Pass Filter	Wainwright Instrument Gmbh	WLK1.0/18G-10TT	1	2019.06.24 ~ 2020.06.24
Broadband Amplifier	Schwarzbeck	BBV9721	PS9721-003	2019.01.16 ~ 2020.01.16 2020.01.15 ~ 2021.01.15
Preamplifier	AGILENT	8449B	3008A00538	2019.06.25 ~ 2020.06.25
Amplifier	R&S	SCU 01	100603	2019.11.25 ~ 2020.11.25
EMI Test Receiver	R&S	ESU26	100551	2019.04.09 ~ 2020.04.09
EMI Test Receiver	R&S	ESR3	101783	2019.04.22 ~ 2020.04.22
DC Power supply	Agilent	6632B	MY43004090	2019.06.25 ~ 2020.06.25
LISN	R&S	ENV216	101786	2019.01.25 ~ 2020.01.25 2020.01.20 ~ 2021.01.20
RF Cable 1	Woken	-	#B-1	2019.12.09 (Cal. date)
RF Cable 2	Woken	-	#B-2	2019.12.09 (Cal. date)

Peripheral devices

Device	Manufacturer	Model No.	Serial No.
Notebook computer	LG Electronics Inc.,	LGS53	306QCZP560949

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact shchoi@kes.co.kr