



EMC TEST REPORT

For

ARTIKA FOR LIVING INC.

28in Mirror Royce Rounded

Test Model: WMIRH-RYCH-D28-BL

Additional Model No.: WMIRH-RYCH-D28-BN, WMIRH-RYCH-D28-CH,
WMIRH-RYCH-D28-GD, WMIRH-RYCH-D28-XXXXXX("XXXXXX" can be A to
Z and/or 0 to 9 and/or blank (commercial code))

Prepared for : ARTIKA FOR LIVING INC.
Address : 800, boulevard Hymus, Saint-Laurent (Québec),
Canada H4S 0B5

Prepared by : Shenzhen LCS Compliance Testing Laboratory Ltd.
Address : Room 101, 201, Building A and Room 301, Building C,
Juji Industrial Park, Yabianxueziwei, Shajing Street,
Bao'an District, Shenzhen, Guangdong, China
Tel : +(86) 0755-82591330
Fax : +(86) 0755-82591332
Web : www.lcs-cert.com
Mail : webmaster@lcs-cert.com

Date of receipt of test sample : August 28, 2026
Number of tested samples : 1
Serial number : A260814028001
Date of Test : August 28, 2026-September 07, 2026
Date of Report : September 08, 2026

**TEST REPORT****Report No.** : LCSA08186081E**Date of Issue** : September 08, 2026**Testing Laboratory Name** : Shenzhen LCS Compliance Testing Laboratory Ltd.**Address** : Room 101, 201, Building A and Room 301, Building C, Juji Industrial Park, Yabianxueziwei, Shajing Street, Bao'an District, Shenzhen, Guangdong, China**Testing Location/ Procedure** : Full application of Harmonised standards ■
Partial application of Harmonised standards □
Other standard testing method □**Applicant's Name** : ARTIKA FOR LIVING INC.**Address** : 800, boulevard Hymus, Saint-Laurent (Québec), Canada H4S 0B5**Test Specification****Standard** : FCC Rules and Regulations Part 15 Subpart B
ANSI C63.4:2014
ANSI C63.4a-2017**TRF Originator** : Shenzhen LCS Compliance Testing Laboratory Ltd.**Master TRF** : Dated 2011-03**Shenzhen LCS Compliance Testing Laboratory Ltd. All rights reserved.**

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen LCS Compliance Testing Laboratory Ltd. is acknowledged as copyright owner and source of the material. Shenzhen LCS Compliance Testing Laboratory Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

Test Item Description : 28in Mirror Royce Rounded**Trade Mark** : ARTIKA**Test Model** : WMIRH-RYCH-D28-BL**Result** : Pass**Compiled by:****Supervised by:****Approved by:**

Emma Wang / File Administrator

Jelly Li / Technique principal

Gavin Liang / Manager

TRF-4-E-010 A/0

Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: Room 101, 201, Building A and Room 301, Building C, Juji Industrial Park, Yabianxueziwei, Shajing Street, Bao'an District, Shenzhen, Guangdong, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



TEST REPORT

Test Report No.: LCSA08186081E**September 08, 2026**
Date of issue**Test Model..... : WMIRH-RYCH-D28-BL****EUT..... : 28in Mirror Royce Rounded****Applicant..... : ARTIKA FOR LIVING INC.****Address..... : 800, boulevard Hymus, Saint-Laurent (Québec),
Canada H4S 0B5****Telephone..... : /****Fax..... : /****Manufacturer..... : HIFLY ILLUMINATION CO.,LIMITED****Address..... : No.2-2, Nanfeng Second Street, Guzhen Town,
Zhongshan City, Guangdong Province.****Telephone..... : /****Fax..... : /****Factory 1..... : HIFLY ILLUMINATION CO.,LIMITED****Address..... : No.2-2, Nanfeng Second Street, Guzhen Town,
Zhongshan City, Guangdong Province.****Factory 2..... : THE LIGHTNING COMPANY****Address..... : Lot D17-18-19, Road 9, Hai Son Industrial Zone, Duc Hoa
District, HO CHI MINH CITY Long An****Telephone..... : /****Fax..... : /****Test Result****Pass**

The test report merely corresponds to the test sample.

It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

TRF-4-E-010 A/0

Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: Room 101, 201, Building A and Room 301, Building C, Juji Industrial Park, Yabianxueziwei, Shajing Street, Bao'an District, Shenzhen, Guangdong, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



Revision History

Report Version	Issue Date	Revision Content	Revised By
000	September 08, 2026	Initial Issue	/



TABLE OF CONTENTS

Test Report Description	Page
1. SUMMARY OF STANDARDS AND RESULTS	6
1.1 Description of Standards and Results	6
1.2 Description of Test Modes	7
2. GENERAL INFORMATION	8
2.1 Description of Device (EUT)	8
2.2 Support equipment List	8
2.3 Description of Test Facility	8
2.4 Measurement Uncertainty	8
3. MEASURING DEVICES AND TEST EQUIPMENT	9
4. EMISSION TEST RESULTS (EMI)	10
4.1 AC Power Port Conducted Emission	10
4.2 Radiated Emissions Test(30-1000MHz)	16
5. TEST SETUP PHOTOS	22
6. EUT CONSTRUCTIONAL DETAILS (EUT PHOTOS)	22



1. SUMMARY OF STANDARDS AND RESULTS

1.1 Description of Standards and Results

Description of Test Item	Standard	Result	Memo
AC Power Port Conducted Emission	FCC Rules and Regulations Part 15 Subpart B,ANSI C63.4:2014,ANSI C63.4a-2017	PASS	/
Radiated Emissions Test(30-1000MHz)	FCC Rules and Regulations Part 15 Subpart B,ANSI C63.4:2014,ANSI C63.4a-2017	PASS	/



1.2 Description of Test Modes

No	Title	Description
Mode 1	Working(AC 120V/60Hz)	/



2. GENERAL INFORMATION

2.1 Description of Device (EUT)

EUT	: 28in Mirror Royce Rounded
Test Model	: WMIRH-RYCH-D28-BL
Power Supply	: AC 120V 60Hz 37W
Highest Internal Frequency	: ≤108MHz
Classification of Equipment	: Class B
Additional Model	: WMIRH-RYCH-D28-BN, WMIRH-RYCH-D28-CH, WMIRH-RYCH-D28-GD, WMIRH-RYCH-D28-XXXXXX("XXXXXX" can be A to Z and/or 0 to 9 and/or blank (commercial code))
Model Declaration	: PCB board, structure and internal of these model(s) are the same, So no additional models were tested.

2.2 Support equipment List

Equipment	Manufacturer	Model	Serial Number	Description
/	/	/	/	/

2.3 Description of Test Facility

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. To CISPR 16 – 4 “Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC Measurements” and is documented in the LCS quality system acc. To DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

NVLAP Accreditation Code is 600167-0.

FCC Designation Number is CN5024.

CAB identifier is CN0071.

CNAS Registration Number is L4595.

2.4 Measurement Uncertainty

Test Item	Measurement Uncertainty
Conducted Emission (150kHz to 30MHz)	± 2.35 dB
Radiated Emission (30MHz to 1000MHz)	± 3.48 dB
Radiated Emission (above 1000MHz)	± 3.90 dB
Note: This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.	



3. MEASURING DEVICES AND TEST EQUIPMENT

Conducted emissions

Equipment	Manufacturer	Model No	Serial No.	Cal Date	Due Date
EMI Test Receiver	R&S	ESR3	102312	2025-12-22	2026-12-21
Artificial Mains	R&S	ENV216	101288	2026-05-06	2027-05-05
Pulse Limiter	R&S	ESH3-Z2	102750-NB	2026-05-06	2027-05-05
EMI Test Software	Farad	EZ	/	/	/

Radiated Emissions (below 1GHz)

Equipment	Manufacturer	Model No	Serial No.	Cal Date	Due Date
EMI Test Software	Farad	EZ	/	N/A	N/A
By-log Antenna	SCHWARZBECK	VULB9163	01143	2024-07-20	2027-07-19
Broadband Preamplifier	/	BBV9745	00317	2025-11-26	2026-11-25
EMI Test Receiver	R&S	ESR7	102311	2026-05-06	2027-05-05



4. EMISSION TEST RESULTS (EMI)

4.1 AC Power Port Conducted Emission

4.1.1 Limits

Class A		
Frequency	Quasi-Peak Level dB(μV)	Average Level dB(μV)
150 kHz~500 kHz	79	66
500 kHz~30 MHz	73	60
Class B		
Frequency	Quasi-Peak Level dB(μV)	Average Level dB(μV)
150 kHz~500 kHz	66 ~ 56*	56 ~ 46*
500 kHz~5 MHz	56	46
5 MHz~30 MHz	60	50
Notes:		
1. * Decreasing linearly with logarithm of frequency.		
2. The lower limit shall apply at the transition frequencies.		

4.1.2 Test procedure

The EUT and Support equipment placement requires reference to the test block diagram and is placed on a non-metallic table.

All I/O cables were positioned to simulate typical actual usage as per ANSI C63.4.

All support equipment power received from a second LISN.

Emissions were measured on each current carrying line of the EUT using an EMI Test Receiver connected to the LISN powering the EUT.

The Receiver scanned from 150 kHz to 30MHz for emissions in each of the test modes.

During the above scans, the emissions were maximized by cable manipulation.

After the preliminary scan, we found the test mode producing the highest emission level.

The EUT configuration and worse cable configuration of the above highest emission levels were recorded for reference of the final test.

EUT and support equipment were set up on the test bench as per the configuration with highest emission level in the preliminary test.

A scan was taken on both power lines, Neutral and Line, recording at least the six highest emissions.

Emission frequency and amplitude were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit.

The test data of the worst-case condition(s) was recorded.

The bandwidth of test receiver is set at 9 kHz.

Note: 1) Pre-scan all modes and recorded the worst case results in this report.

2) Margin= Reading level + Correct factor-Limit


TRF-4-E-010 A/0




Correct Factor=Lisn Factor+Cable Factor+Insertion loss of Pulse Limiter

4.1.3 Test Setup Diagram

For floor standing equipment




For combinations equipment





For table-top equipment






4.1.4 E.U.T. Operation

Operating Environment:			
Temperature:	22.5° C	Humidity:	60.0%RH
Test Engineer	Xing Jin Mo		
Mode 1	Working	Voltage	AC 120V/60Hz



4.1.5 Test data

Mode 1 / Line: Line



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Margin dB	Detector	Comment
1		0.2983	25.33	20.35	45.68	50.29	-4.61	AVG	
2		0.3209	33.74	20.34	54.08	59.68	-5.60	QP	
3		0.3390	23.36	20.31	43.67	49.23	-5.56	AVG	
4		0.3613	32.88	20.28	53.16	58.70	-5.54	QP	
5		0.5010	18.84	20.12	38.96	46.00	-7.04	AVG	
6		0.5143	32.13	20.13	52.26	56.00	-3.74	QP	
7		0.8205	31.87	20.47	52.34	56.00	-3.66	QP	
8		0.8205	21.99	20.47	42.46	46.00	-3.54	AVG	
9		1.0410	31.39	20.48	51.87	56.00	-4.13	QP	
10	*	1.0410	22.05	20.48	42.53	46.00	-3.47	AVG	
11		1.3605	31.59	20.46	52.05	56.00	-3.95	QP	
12		1.3605	22.06	20.46	42.52	46.00	-3.48	AVG	

TRF-4-E-010 A/O

Shenzhen LCS Compliance Testing Laboratory Ltd.


Add: Room 101, 201, Building A and Room 301, Building C, Juji Industrial Park, Yabianxueziwei, Shajing Street, Bao'an District, Shenzhen, Guangdong, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



Mode 1 / Line: Neutral



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Margin dB	Detector	Comment
1		0.4200	29.41	20.21	49.62	57.45	-7.83	QP	
2		0.4380	18.44	20.19	38.63	47.10	-8.47	AVG	
3		0.4783	31.77	20.14	51.91	56.37	-4.46	QP	
4		0.4783	19.12	20.14	39.26	46.37	-7.11	AVG	
5		0.5010	19.22	20.12	39.34	46.00	-6.66	AVG	
6	*	0.5233	32.10	20.14	52.24	56.00	-3.76	QP	
7		0.6403	28.05	20.27	48.32	56.00	-7.68	QP	
8		0.6809	18.32	20.30	38.62	46.00	-7.38	AVG	
9		0.8205	17.14	20.43	37.57	46.00	-8.43	AVG	
10		0.8385	27.33	20.43	47.76	56.00	-8.24	QP	
11		3.4394	18.54	20.53	39.07	46.00	-6.93	AVG	
12		3.8220	28.62	20.53	49.15	56.00	-6.85	QP	

TRF-4-E-010 A/0

Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: Room 101, 201, Building A and Room 301, Building C, Juji Industrial Park, Yabianxueziwei, Shajing Street, Bao'an District, Shenzhen, Guangdong, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



4.2 Radiated Emissions Test(30-1000MHz)

4.2.1 Limits

Limits:				
Frequency (MHz)	Class A Field Strengths Limits at 10m measuring distance dB(μ V)/m	Class A Field Strengths Limits at 3m measuring distance dB(μ V)/m	Class B Field Strengths Limits at 10m measuring distance dB(μ V)/m	Class B Field Strengths Limits at 3m measuring distance dB(μ V)/m
30--88	39.0	49.5	29.5	40.0
88--216	43.5	54.0	33.0	43.5
216--960	46.4	57.0	35.5	46.0
960--1000	49.5	60.0	43.5	54.0
Above 1000	/	80.0 (Peak), 60.0 (Average)	/	74.0 (Peak), 54.0 (Average)

4.2.2 Test procedure

Procedure of Preliminary Test

The EUT and Support equipment, if needed, were put placed on a non-metallic table, 0.8m (table-top device)/0.1m (floor stand device) above the ground plane.

Configuration EUT to simulate typical usage as described in as shown above block diagram and equipment list of this report.

All I/O cables were positioned to simulate typical actual usage as per ANSI C63.4.

Mains cables, telephone lines or other connections to auxiliary equipment located outside the test are shall drape to the floor, be fitted with ferrite clamps or ferrite tubes placed on the floor at the point where the cable reaches the floor and then routed to the place where they leave the turntable. No extension cords shall be used to mains receptacle.

The antenna was placed at 3 meter away from the EUT as stated in ANSI C63.4. The antenna connected to the Spectrum Analyzer via a cable and at times a pre-amplifier would be used.

The Analyzer / Receiver quickly scanned from 30 MHz to 1 GHz. The EUT test program was started.

Emissions were scanned and measured rotating the EUT to 360 degrees and positioning the antenna 1 to 4 meters above the ground plane, in both the vertical and the horizontal polarization, to maximize the emission reading level.

After the preliminary scan, we found the test mode producing the highest emission level. The EUT and cable configuration, antenna position, polarization and turntable position of the above highest emission level were recorded for the final test.

Procedure of Final Test

EUT and support equipment were set up on the turntable as per the configuration with highest emission level in the preliminary test.



The Analyzer / Receiver scanned from 30 MHz to 1 GHz. Emissions were scanned and measured rotating the EUT to 360 degrees, varying cable placement and positioning the antenna 1 to 4 meters above the ground plane, in both the vertical and the horizontal polarization, to maximize the emission reading level. Recorded at least the six highest emissions. Emission frequency, amplitude, antenna position, polarization and turntable position were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit and only Q.P. reading is presented.

For emissions from 30 MHz to 1 GHz, Quasi-Peak values were measured with EMI Receiver and the bandwidth of Receiver is 120 kHz.

Note:1).Pre-Scan all mode, Thus record worse case mode result in this report.


2) Margin= Reading level + Correct factor – Limit

Correct Factor=Antenna Factor+Cable Factor- Pre-amplifier Factor

4.2.3 Test Setup Diagram


Below 1 GHz

For table-top equipment






For floor standing equipment



For combinations equipment



TRF-4-E-010 A/0

Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: Room 101, 201, Building A and Room 301, Building C, Juji Industrial Park, Yabianxueziwei, Shajing Street, Bao'an District, Shenzhen, Guangdong, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity




4.2.4 E.U.T. Operation

Operating Environment:			
Temperature:	26° C	Humidity:	54%RH
Test Engineer	Xing Jin Mo		
Mode 1	Working	Voltage	AC 120V/60Hz



4.2.5 Test data

Mode 1 / Polarization: Vertical



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1 *	51.1209	47.69	-16.05	31.64	40.00	-8.36	QP	P	
2	72.0843	43.26	-20.34	22.92	40.00	-17.08	QP	P	
3	107.8877	33.24	-17.11	16.13	43.50	-27.37	QP	P	
4	135.9822	41.98	-21.53	20.45	43.50	-23.05	QP	P	
5	152.1297	41.74	-20.91	20.83	43.50	-22.67	QP	P	
6	184.4898	36.17	-19.42	16.75	43.50	-26.75	QP	P	

TRF-4-E-010 A/0

Shenzhen LCS Compliance Testing Laboratory Ltd.


Add: Room 101, 201, Building A and Room 301, Building C, Juji Industrial Park, Yabianxueziwei, Shajing Street, Bao'an District, Shenzhen, Guangdong, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



Mode 1 / Polarization: Horizontal



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1	53.8818	33.19	-15.95	17.24	40.00	-22.76	QP	P	
2 *	56.0007	36.13	-16.87	19.26	40.00	-20.74	QP	P	
3	72.0843	30.47	-20.34	10.13	40.00	-29.87	QP	P	
4	152.1297	40.46	-20.91	19.55	43.50	-23.95	QP	P	
5	168.4138	34.71	-20.02	14.69	43.50	-28.81	QP	P	
6	184.4898	37.22	-19.42	17.80	43.50	-25.70	QP	P	

TRF-4-E-010 A/0

Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: Room 101, 201, Building A and Room 301, Building C, Juji Industrial Park, Yabianxueziwei, Shajing Street, Bao'an District, Shenzhen, Guangdong, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



5. TEST SETUP PHOTOS

Refer to Appendix - Test Setup Photos for LCSA08186081E.docx

6. EUT CONSTRUCTIONAL DETAILS (EUT PHOTOS)

Refer to Appendix - EUT Photos for LCSA08186081E.docx

-----End Report-----