FCC Test Report

Report No.: AGC01618190902FE03

FCC ID	:	2AUHRF-393
APPLICATION PURPOSE	:	Original Equipment
PRODUCT DESIGNATION	:	Play family remote control car series
BRAND NAME	:	N/A
MODEL NAME	:	F-393
SERIES MODEL		See Page 5
APPLICANT	:	HONG CHUAN SHENG TOYS FACTORY
DATE OF ISSUE	:	Sep. 17, 2019
STANDARD(S) **TEST PROCEDURE(S)**	:	FCC Part 15 Rules
REPORT VERSION	:	V1.0

Attestation of Global Compliance (Shenzhen) Co., Ltd

CAUTION:
This report shall not be reproduced except in full without the written permission of the test laboratory and shall not be quoted out of context.

REPORT REVISE RECORD

Report Version	Revise Time	Issued Date	Valid Version	Notes
V1.0	/	Sep. 17, 2019	Valid	Initial Release

TABLE OF CONTENTS

1. VERIFICATION OF CONFORMITY 4
2. GENERAL INFORMATION 5
2.1. PRODUCT DESCRIPTION 5
2.2. TABLE OF CARRIER FREQUENCY 5
3. MEASUREMENT UNCERTAINTY 6
4. DESCRIPTION OF TEST MODES 7
5. SYSTEM TEST CONFIGURATION 8
5.1. CONFIGURATION OF EUT SYSTEM 8
5.2 EQUIPMENT USED IN TESTED SYSTEM 8
5.3. SUMMARY OF TEST RESULTS 8
6. TEST FACILITY 9
7. RADIATED EMISSION 10
7.1TEST LIMIT 10
7.2. MEASUREMENT PROCEDURE 11
7.3. TEST SETUP 13
7.4. TEST RESULT 14
8. BAND EDGE EMISSION 20
8.1. MEASUREMENT PROCEDURE 20
8.2 TEST SETUP 20
8.3 RADIATED TEST RESULT 20
9. 20DB BANDWIDTH 25
9.1. MEASUREMENT PROCEDURE 25
9.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION) 25
9.3. MEASUREMENT RESULTS 26
APPENDIX A: PHOTOGRAPHS OF TEST SETUP 28
APPENDIX B: PHOTOGRAPHS OF THE EUT 29

1. VERIFICATION OF CONFORMITY

Applicant	HONG CHUAN SHENG TOYS FACTORY
Address	CHENGHAI DISTRICI, SHANTOU CITY, GUANGDONG PROVINCE, CHINA
Manufacturer	HONG CHUAN SHENG TOYS FACTORY
Address	CHENGHAI DISTRICI, SHANTOU CITY, GUANGDONG PROVINCE, CHINA
Product Designation	Play family remote control car series
Brand Name	N/A
Test Model	F-393
Series Model	See Page 5
Difference Description	All the same except for the model name and packaging
Date of test	Sep. 05, 2019 to Sep. 16, 2019
Deviation	None
Condition of Test Sample	Normal
Test Result	Pass
Report Template	AGCRT-US-BR/RF

We hereby certify that:

The above equipment was tested by Attestation of Global Compliance (Shenzhen) Co., Ltd. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.10 (2013) and the energy emitted by the sample EUT tested as described in this report is in compliance with radiated emission limits of FCC Rules Part 15.249.

Prepared By	Draven Li (Project Engineer)	Sep. 16, 2019
Reviewed By	Max Zhang (Reviewer)	Sep. 17, 2019
Approved By	Forrest Lei (Authorized Officer)	Sep. 17, 2019

2. GENERAL INFORMATION

2.1. PRODUCT DESCRIPTION

A major technical description of EUT is described as following

Operation Frequency	2.408 GHz to 2.468GHz
Maximum field strength	75.69dBuV/m(Average)@3m
Modulation	GFSK
Number of channels	13
Antenna Gain	0dBi
Antenna Designation	Wired Antenna (Met 15.203 Antenna requirement)
Hardware Version	QF-1688T-75-2.4G
Software Version	V1.0
Power Supply	DC 3V by Battery

Series Model:

698-9, 698-10, 698-11, 698-12, 698-13, 698-14, 698-15, 698-16, 698-17, 698-18, 698-19, 698-20, 698-21, 698-22, 698-23, 698-24, 698-25, 698-26, 698-27, 698-28, 698-29, 698-30, 698-31, 698-32, 698-33, 698-34, 698-35, 698-36, 698-37, 698-38, 689-12, 689-13, 689-14, 689-15, 689-16, 689-17, 689-18, 689-19, 689-20, 689-21, 689-22, 689-23, 689-24, 689-25, 689-26, 689-27, 689-28, 689-29, 689-30, 689-31, 689-32, 689-33, 689-34, 689-35, 689-36, 689-37, 689-38, 36778-146, 36778-147, 36778-148, 36778-149, 36778-150, 36778-151, 36778-152, 36778-153, 36778-154, 36778-155, 36778-151A, F-393-07269

2.2. TABLE OF CARRIER FREQUENCY

Frequency Band	Channel Number	Frequency
2400~2483.5MHZ	1	2408MHZ
	2	2413MHZ
	3	2418MHZ
	4	2423MHZ
	5	2428MHZ
	6	2433MHZ
	7	2438MHZ
	8	2443MHZ
	9	2448MHZ
	10	2453MHZ
	11	2458MHZ
	12	2463MHZ
	13	2468MHZ

3. MEASUREMENT UNCERTAINTY

The uncertainty is calculated using the methods suggested in the “Guide to the Expression of Uncertainty in measurement” (GUM) published by CISPR and ANSI.

- Uncertainty of Conducted Emission, Uc = ±3.2 dB
- Uncertainty of Radiated Emission below 1GHz, Uc = ±3.9 dB
- Uncertainty of Radiated Emission above 1GHz, Uc = ±4.8 dB

4. DESCRIPTION OF TEST MODES

NO.	TEST MODE DESCRIPTION
1	Low channel GFSK
2	Middle channel GFSK
3	High channel GFSK

Note:
1. All the test modes can be supply by battery, only the result of the worst case was recorded in the report, if no other cases.
2. For Radiated Emission, 3axis were chosen for testing for each applicable mode.

5. SYSTEM TEST CONFIGURATION

5.1. CONFIGURATION OF EUT SYSTEM

EUT

5.2 EQUIPMENT USED IN TESTED SYSTEM

Item	Equipment	Model No.	ID or Specification	Remark
1	Play family remote control car series	F-393	2AUHRF-393	EUT

5.3. SUMMARY OF TEST RESULTS

FCC RULES	DESCRIPTION OF TEST	RESULT
§15.249&15.209	Radiated Emission	Compliant
§15.249	Band Edges	Compliant
§15.215	20dB bandwidth	Compliant
§15.207	Conducted Emission	N/A

Note: The conducted limits are not required for devices which only employ battery power for operation.

6. TEST FACILITY

Test Site	Attestation of Global Compliance (Shenzhen) Co., Ltd
Location	1-2/F, Building 19, Junfeng Industrial Park, Chongqing Road, Heping Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China
Designation Number	CN1259
FCC Test Firm Registration Number	975832
A2LA Cert. No.	5054.02
Description	Attestation of Global Compliance(Shenzhen) Co., Ltd is accredited by A2LA

TEST EQUIPMENT OF RADIATED EMISSION TEST

Equipment	Manufacturer	Model	S/N	Cal. Date	Cal. Due
TEST RECEIVER	R&S	ESCI	10096	Jun. 10, 2019	Jun. 09, 2020
EXA Signal Analyzer	Aglient	N9010A	MY53470504	Dec. 20, 2018	Dec. 19, 2019
2.4GHz Fliter	Micro-tronics	087	N/A	Jun. 10, 2019	Jun. 09, 2020
Attenuator	Weinachel Corp	58-30-33	N/A	Jun. 10, 2019	Jun. 09, 2020
Horn antenna	SCHWARZBECK	BBHA 9170	#768	Sep. 21, 2017	Sep. 20, 2020
Active loop antenna (9K-30MHz)	ZHINAN	ZN30900C	18051	Jun. 14, 2018	Jun. 13, 2020
Double-Ridged Waveguide Horn	ETS LINDGREN	3117	00034609	May. 26, 2018	May. 25, 2020
Broadband Preamplifier	ETS LINDGREN	3117PA	00225134	Oct. 25, 2018	Oct. 24, 2019
ANTENNA	SCHWARZBECK	VULB9168	D69250	Sep. 28, 2017	Sep. 27, 2019

7. RADIATED EMISSION

7.1TEST LIMIT

Standard FCC15.249

Fundamental Frequency	Field Strength of Fundamental (millivolts/meter)	Field Strength of Harmonics (microvolts/meter)
900-928MHz	50	500
2400-2483.5MHz	50	500
5725-5875MHz	50	500
24.0-24.25GHz	250	2500

Standard FCC 15.209

Frequency (MHz)	Distance Meters	Field Strengths Limit	
		μ V/m	dB(μV)/m
0.009 ~ 0.490	300	2400/F(kHz)	---
0.490 ~ 1.705	30	24000/F(kHz)	---
1.705 ~ 30	30	30	---
30 ~ 88	3	100	40.0
88 ~ 216	3	150	43.5
216 ~ 960	3	200	46.0
960 ~ 1000	3	500	54.0
Above 1000	3	Other:74.0 dB(μV)/m (Peak) 54.0 dB(μV)/m (Average)	

Remark: (1) Emission level dB μ V = 20 log Emission level μ V/m

(2) The smaller limit shall apply at the cross point between two frequency bands.

(3) Distance is the distance in meters between the measuring instrument, antenna and the closest point of any part of the device or system.

7.2. MEASUREMENT PROCEDURE

1. The EUT was placed on the top of the turntable 0.8 or 1.5 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
4. For each suspected emissions, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
6. For emissions above 1GHz, use minimum resolution bandwidth of 1 MHz. Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.
7. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum values.
8. If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
9. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
10. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High - Low scan is not required in this case.

The following table is the setting of spectrum analyzer and receiver.

Spectrum Parameter	Setting
Start ~Stop Frequency	9KHz~150KHz/RB 200Hz for QP
Start ~Stop Frequency	150KHz~30MHz/RB 9KHz for QP
Start ~Stop Frequency	30MHz~1000MHz/RB 120KHz for QP
Start ~Stop Frequency	1GHz~26.5GHz RBW 2.4MHz/ VBW 8MHz for Peak, RBW 2.4MHz/10Hz for Average

Receiver Parameter	Setting
Start ~Stop Frequency	9KHz~150KHz/RB 200Hz for QP
Start ~Stop Frequency	150KHz~30MHz/RB 9KHz for QP
Start ~Stop Frequency	30MHz~1000MHz/RB 120KHz for QP

7.3. TEST SETUP

Radiated Emission Test-Setup Frequency Below 30MHz



RADIATED EMISSION TEST SETUP 30MHz-1000MHz



RADIATED EMISSION TEST SETUP ABOVE 1000MHz



7.4. TEST RESULT

RADIATED EMISSION BELOW 30MHZ

No emission found between lowest internal used/generated frequencies to 30MHz.

RADIATED EMISSION 30MHz- 1GHZ

EUT：	Play family remote control car series	Model Name. ：	F-393
Temperature：	20 ℃	Relative Humidtity：	48%
Pressure：	1010 hPa	Test Voltage ：	DC 3V
Test Mode ：	Mode 1	Polarization :	Horizontal



No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
	.	MHz	dBuV	dBuV/m	dBuV/m	dBuV/m	dB		cm	degree	
1		44.5500	-0.89	19.93	19.04	40.00	-20.96	peak			
2		156.1000	0.64	19.20	19.84	43.50	-23.66	peak			
3		477.8167	0.43	24.54	24.97	46.00	-21.03	peak			
4		616.8500	1.72	27.15	28.87	46.00	-17.13	peak			
5		806.0000	2.08	30.49	32.57	46.00	-13.43	peak			
6	*	924.0167	2.42	31.91	34.33	46.00	-11.67	peak			

EUT：	Play family remote control car series	Model Name. ：	F-393
Temperature：	20 ℃	Relative Humidtity：	48%
Pressure：	1010 hPa	Test Voltage ：	DC 3V
Test Mode ：	Mode 1	Polarization :	Vertical



No.	Mk.	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dBuV/m	dBuV/m	dBuV/m	dB		cm	degree	
1		46.1667	-0.11	19.87	19.76	40.00	-20.24	peak			
2		143.1667	0.07	19.22	19.29	43.50	-24.21	peak			
3		359.8000	2.78	21.57	24.35	46.00	-21.65	peak			
4		681.5167	0.46	27.93	28.39	46.00	-17.61	peak			
5		804.3833	1.20	30.47	31.67	46.00	-14.33	peak			
6	*	904.6167	2.46	31.74	34.20	46.00	-11.80	peak			

RESULT: PASS

Note:

Factor=Antenna Factor + Cable loss, Margin=Result-Limit.

The “Factor” value can be calculated automatically by software of measurement system.

The mode 1 is the worst case, and only the data of the worst case recorded in this test report.

FIELD STRENGTH OF FUNDAMENTAL

EUT：	Play family remote control car series	Model Name. ：	F-393
Temperature：	20 ℃	Relative Humidtity：	48%
Pressure：	1010 hPa	Test Voltage ：	DC 3V
Test Modulation ：	GFSK	Polarization :	Horizontal

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Value Type
2408.013	31.02	49.05	80.07	114.00	-33.93	peak
2408.013	26.63	49.05	75.68	94.00	-18.32	AVG
2438.013	30.74	49.12	79.86	114.00	-34.14	peak
2438.013	25.22	49.12	74.34	94.00	-19.66	AVG
2468.013	31.22	49.25	80.47	114.00	-33.53	peak
2468.013	26.44	49.25	75.69	94.00	-18.31	AVG

Remark:
Factor = Antenna Factor + Cable Loss – Pre-amplifier.

EUT：	Play family remote control car series	Model Name. ：	F-393
Temperature：	20 ℃	Relative Humidtity：	48%
Pressure：	1010 hPa	Test Voltage ：	DC 3V
Test Modulation ：	GFSK	Polarization :	Vertical

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Value Type
2408.013	29.06	49.05	78.11	114.00	-35.89	peak
2408.013	23.59	49.05	72.64	94.00	-21.36	AVG
2438.013	28.82	49.12	77.94	114.00	-36.06	peak
2438.013	22.93	49.12	72.05	94.00	-21.95	AVG
2468.013	29.41	49.25	78.66	114.00	-35.34	peak
2468.013	22.80	49.25	72.05	94.00	-21.95	AVG

Remark:
Factor = Antenna Factor + Cable Loss – Pre-amplifier.

RADIATED EMISSION ABOVE 1GHZ

EUT：	Play family remote control car series	Model Name. ：	F-393
Temperature：	20 ℃	Relative Humidtity：	48%
Pressure：	1010 hPa	Test Voltage ：	DC 3V
Test Mode ：	Mode 1	Polarization :	Horizontal

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Value Type
4816.026	50.36	0.08	50.44	74.00	-23.56	peak
4816.026	48.53	0.08	48.61	54.00	-5.39	AVG
7224.039	42.84	2.21	45.05	74.00	-28.95	peak
7224.039	38.79	2.21	41.00	54.00	-13.00	AVG

Remark:
Factor = Antenna Factor + Cable Loss – Pre-amplifier.

EUT：	Play family remote control car series	Model Name. ：	F-393
Temperature：	20 ℃	Relative Humidtity：	48%
Pressure：	1010 hPa	Test Voltage ：	DC 3V
Test Mode ：	Mode 1	Polarization :	Vertical

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Value Type
4816.026	53.63	0.08	53.71	74.00	-20.29	peak
4816.026	47.53	0.08	47.61	54.00	-6.39	AVG
7224.039	42.85	2.21	45.06	74.00	-28.94	peak
7224.039	40.73	2.21	42.94	54.00	-11.06	AVG

Remark:
Factor = Antenna Factor + Cable Loss – Pre-amplifier.

EUT：	Play family remote control car series	Model Name. ：	F-393
Temperature：	20 ℃	Relative Humidtity：	48%
Pressure：	1010 hPa	Test Voltage ：	DC 3V
Test Mode ：	Mode 2	Polarization :	Horizontal

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Value Type
4876.026	51.57	0.14	51.71	74.00	-22.29	peak
4876.026	46.36	0.14	46.50	54.00	-7.50	AVG
7314.039	45.70	2.36	48.06	74.00	-25.94	peak
7314.039	43.28	2.36	45.64	54.00	-8.36	AVG

Remark:
Factor = Antenna Factor + Cable Loss – Pre-amplifier.

EUT：	Play family remote control car series	Model Name. ：	F-393
Temperature：	20 ℃	Relative Humidtity：	48%
Pressure：	1010 hPa	Test Voltage ：	DC 3V
Test Mode ：	Mode 2	Polarization :	Vertical

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Value Type
4876.026	51.58	0.14	51.72	74.00	-22.28	peak
4876.026	48.47	0.14	48.61	54.00	-5.39	AVG
7314.039	45.70	2.36	48.06	74.00	-25.94	peak
7314.039	43.28	2.36	45.64	54.00	-8.36	AVG

Remark:
Factor = Antenna Factor + Cable Loss – Pre-amplifier.

EUT：	Play family remote control car series	Model Name. ：	F-393
Temperature：	20 ℃	Relative Humidtity：	48%
Pressure：	1010 hPa	Test Voltage ：	DC 3V
Test Mode ：	Mode 3	Polarization :	Horizontal

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Value Type
4936.026	50.50	0.22	50.72	74.00	-23.28	peak
4936.026	48.39	0.22	48.61	54.00	-5.39	AVG
7404.039	44.44	2.64	47.08	74.00	-26.92	peak
7404.039	41.97	2.64	44.61	54.00	-9.39	AVG
Remark:						
Factor = Antenna Factor + Cable Loss – Pre-amplifier.						

EUT：	Play family remote control car series	Model Name. ：	F-393
Temperature：	20 ℃	Relative Humidtity：	48%
Pressure：	1010 hPa	Test Voltage ：	DC 3V
Test Mode ：	Mode 3	Polarization :	Vertical

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Value Type
4936.026	51.72	0.22	51.94	74.00	-22.06	peak
4936.026	48.39	0.22	48.61	54.00	-5.39	AVG
7404.039	45.05	2.64	47.69	74.00	-26.31	peak
7404.039	42.44	2.64	45.08	54.00	-8.92	AVG
Remark:						
Factor = Antenna Factor + Cable Loss – Pre-amplifier.						

Note: Other emissions from 8G to 25 GHz are considered as ambient noise. No recording in the test report.
Factor=Antenna Factor + Cable loss - Amplifier gain, Margin=Measurement-Limit.
The “Factor” value can be calculated automatically by software of measurement system.
The GFSK modulation was the worst case and only the data of worst recorded in this report.

8. BAND EDGE EMISSION

8.1. MEASUREMENT PROCEDURE

1. The EUT operates at transmitting mode. The operate channel is tested to verify the largest transmission and spurious emissions power at the continuous transmission mode.

2. Set the spectrum analyzer in the following setting in order to capture the lower and upper band-edges of the emission: (a) PEAK: RBW=1MHz, VBW=3MHz / Sweep=AUTO

(b) AVERAGE: RBW=1MHz ; VBW=1/on time(1KHz) / Sweep=AUTO

3. Other procedures refer to clause 7.2.

8.2 TEST SETUP

RADIATED EMISSION TEST SETUP



8.3 RADIATED TEST RESULT

Note:

1. Factor=Antenna Factor + Cable loss - Amplifier gain. Field Strength=Factor + Reading level
2. The factor had been edited in the “Input Correction” of the Spectrum Analyzer. So the Amplitude of test plots is equal to Reading level plus the Factor in dB. Use the A dB(μV) to represent the Amplitude. Use the F dB(μV/m) to represent the Field Strength. So A=F.

EUT：	Play family remote control car series	Model Name. ：	F-393
Temperature：	20 ℃	Relative Humidtity：	48%
Pressure：	1010 hPa	Test Voltage ：	DC 3V
Test Mode ：	Mode 1	Polarization :	Horizontal

Peak Value

Average Value



EUT：	Play family remote control car series	Model Name. ：	F-393
Temperature：	20 ℃	Relative Humidtity：	48%
Pressure：	1010 hPa	Test Voltage ：	DC 3V
Test Mode ：	Mode 1	Polarization :	Vertical

Peak Value

Average Value



EUT：	Play family remote control car series	Model Name. ：	F-393
Temperature：	20 ℃	Relative Humidtity：	48%
Pressure：	1010 hPa	Test Voltage ：	DC 3V
Test Mode ：	Mode 3	Polarization :	Horizontal

Peak Value

Average Value

EUT：	Play family remote control car series	Model Name. ：	F-393
Temperature：	20 ℃	Relative Humidtity：	48%
Pressure：	1010 hPa	Test Voltage ：	DC 3V
Test Mode ：	Mode 3	Polarization :	Vertical

Peak Value

Average Value



9. 20DB BANDWIDTH

9.1. MEASUREMENT PROCEDURE

1. Set the EUT Work on the top, the middle and the bottom operation frequency individually.
2. Set SPA Centre Frequency = Operation Frequency, RBW= 30 KHz, VBW⩾3×RBW.
3. Set SPA Trace 1 Max hold, then View.

9.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)



9.3. MEASUREMENT RESULTS

TEST ITEM	20DB BANDWIDTH
TEST MODULATION	GFSK

Test Data (MHz)		Criteria
Low Channel	0.6806	PASS
Middle Channel	0.6701	PASS
High Channel	0.6851	PASS

TEST PLOT OF BANDWIDTH FOR LOW CHANNEL



TEST PLOT OF BANDWIDTH FOR MIDDLE CHANNEL



TEST PLOT OF BANDWIDTH FOR HIGH CHANNEL



APPENDIX A: PHOTOGRAPHS OF TEST SETUP

FCC RADIATED EMISSION TEST SETUP BELOW 1GHZ



FCC RADIATED EMISSION TEST SETUP ABOVE 1GHZ

APPENDIX B: PHOTOGRAPHS OF THE EUT

ALL VIEW OF EUT



TOP VIEW OF EUT

BOTTOM VIEW OF EUT



FRONT VIEW OF EUT

BACK VIEW OF EUT



LEFT VIEW OF EUT



RIGHT VIEW OF EUT



OPEN VIEW OF EUT-1



OPEN VIEW OF EUT-2



INTERNAL VIEW OF EUT-1



INTERNAL VIEW OF EUT-2



----END OF REPORT----