TEST REPORT

CTK Co., Ltd.
(Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si, Gyeonggi-do, Korea
Tel: +82-31-339-9970
Fax: +82-31-624-9501

Report No.: CTK-2019-03542

1. Client

◦ Name : CnR Tech. Co., Ltd.

◦ Address : #713, 11-41 simin-daero 327beon-gil, Dongan-gu, Anyang-si, Gyeonggi-do, Korea

◦ Date of Receipt : 2019-08-23

2. Manufacturer

◦ Name : CnR Tech. Co., Ltd.

◦ Address : #713, 11-41 simin-daero 327beon-gil, Dongan-gu, Anyang-si, Gyeonggi-do, Korea

3. Use of Report : For FCC Certification

4. Test Sample / Model: Code-Play Block / CR-CPB-v001

5. Date of Test : 2019-09-02 to 2019-09-05

6. Test Standard(method) used : FCC 47 CFR part 15 subpart C 15.247

7. Testing Environment: Temp.: (25 ± 1) ℃, Humidity: (51 ± 3) % R.H.

8. Test Results : Compliance

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This Test Report cannot be reproduced, except in full.

Affirmation	Tested by Ji-Hye Kim: (Signature)	Technical Manager Won-Jae, Hwang: (Signature)

2019-09-09

Republic of KOREA **CTK Co., Ltd.**

REPORT REVISION HISTORY

Date	Revision	Page No
2019-09-09	Issued (CTK-2019-03542)	all

This report shall not be reproduced except in full, without the written approval of CTK Co., Ltd. This document may be altered or revised by CTK Co., Ltd. personnel only, and shall be noted in the revision section of the document. Any alteration of this document not carried out by CTK Co., Ltd. will constitute fraud and shall nullify the document.

CONTENTS

1. General Product Description 4
1.1 Client Information 4
1.2 Product Information 4
1.3 Peripheral Devices 4
2. Facility and Accreditations 5
2.1 Test Facility 5
2.2 Laboratory Accreditations and Listings 5
2.3 Calibration Details of Equipment Used for Measurement 5
3. Test Specifications 6
3.1 Standards 6
3.2 Mode of operation during the test 7
3.3 Device Modifications 7
3.4 Maximum Measurement Uncertainty 7
3.5 Test Software 7
4. Technical Characteristic Test 8
4.1 6dB Bandwidth 8
4.2 Maximum peak Conducted Output Power 12
4.3 Transmitter Power Spectral Density 15
4.4 Conducted Spurious emission 18
4.5 Radiated Emission 20
4.6 AC Conducted Emissions 29
APPENDIX A – Test Equipment Used For Tests 32

1. General Product Description

1.1 Client Information

Company	CnR Tech. Co., Ltd.
Contact Point	#713, 11-41 simin-daero 327beon-gil, Dongan-gu, Anyang-si, Gyeonggi-do, Korea
Contact Person	Name : Deoksoo Han E-mail : cnr@candr.co.kr Tel : +82-70-4821-4328 Fax : +82-31-422-4328

1.2 Product Information

FCC ID	2AUIN-CR-CPB-V001
Product Description	Code-Play Block
Model name	CR-CPB-v001
Variant Model name	-
Operating Frequency	2 402 MHz – 2 480 MHz
RF Output Power	-11.560 dBm (0.07 mW)
Antenna Specification	Antenna type : PCB Antenna Peak Gain : -1.13 dBi
Type of Modulation	GFSK (Bluetooth LE)
Power Source	DC 3.7 V (Li-ion Battery)
Hardware Rev	0.4
Software Rev	7.2

1.3 Peripheral Devices

Device	Manufacturer	Model No.	Serial No.
Note Computer	HP	15-bs563TU	CND7253R6N
AC/DC Adapter	HP	HSTNN-CA40	-

2. Facility and Accreditations

2.1 Test Facility

The measurement facility is located at (Ho-dong), 113, Yejik-ro, Cheoin-gu, Yong-in-si, Gyeonggi-do, Korea.

2.2 Laboratory Accreditations and Listings

Country	Agency	Registration Number
USA	FCC	805871
CANADA	ISED	8737A-2
KOREA	NRRA	KR0025

2.3 Calibration Details of Equipment Used for Measurement

Test equipment and test accessories are calibrated on regular basis. The maximum time between calibrations is one year or what is recommended by the manufacturer, whichever is less. All test equipment calibrations are traceable to the Korea Research Institute of Standards and Science (KRISS), therefore, all test data recorded in this report is traceable to KRISS.

3. Test Specifications

3.1 Standards

FCC Part Section(s)	Requirement(s)	Status (Note 1)	Test Condition
15.247(a)	6 dB Bandwidth	C	Conducted
15.247(b)	Maximum Output Power	C	
15.247(d)	Conducted Spurious emission	C	
15.247(d)	Unwanted Emission(Conducted)	C	
15.247(e)	Transmitter Power Spectral Density	C	
15.209	Radiated Emissions	C	Radiated
15.207	AC Conducted Emissions	C	Line Conducted
Note 1: C=Complies NC=Not Complies NT=Not Tested NA=Not Applicable			
Note 2: The data in this test report are traceable to the national or international standards.			
Note 3: The sample was tested according to the following specification: FCC Part 15.247			
Note 4: The tests were performed according to the method of measurements prescribed in KDB No.558074, ANSI C63.10-2013			

3.2 Mode of operation during the test

The EUT is operated in a manner representative of the typical of the equipments.
During at testing, system components were manipulated within the confines of typical usage to maximize each emission. All modulation modes were tests.
The results are only attached worst cases.

Test Frequency

Lowest channel	Middle channel	Highest channel
2 402 MHz	2 440 MHz	2 480 MHz

Test mode

Modulation	Duty Cycle	Duty Cycle Factor
GFSK	17.5%	7.58 dB

3.3 Device Modifications

The following modifications were necessary for compliance:

Not applicable

3.4 Maximum Measurement Uncertainty

The value of the measurement uncertainty for the measurement of each parameter.
Coverage factor k = 2, Confidence levels of 95 %

Description	Uncertainty
Conducted RF Output Power	± 1.5 dB
Power Spectral Density	± 1.5 dB
Occupied Bandwidth	± 0.1 MHz
Unwanted Emission(conducted)	± 3.0 dB
Radiated Emissions (f ≤ 1 GHz)	± 4.0 dB
Radiated Emissions (f > 1 GHz)	± 5.0 dB

3.5 Test Software

Conducted Test	Ics Pro Ver. 6.0.3
Radiated Test	TOYO EMI software EP5RE Ver. 5.1.0 TOYO EMI software EP5RE Ver. 6.0.1
Line Conducted Test	ESCI7, ESCI3 : EMC32 Ver. 8.50.0 ESR7 : EMC32 Ver. 8.53.0

4. Technical Characteristic Test

4.1 6dB Bandwidth

Test Procedures

KDB 558074 - Section 8.2
ANSI C63.10-2013 - Section 11.8.2

Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

Test Procedures

ANSI C63.10-2013 - Section 6.9

The occupied bandwidth is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers are each equal to 0.5% of the total mean power of the given emission.
Use the 99% power bandwidth function of the instrument and report the measured bandwidth.

Test Settings :

Center frequency = the highest, middle and the lowest channels

a) RBW = 100 kHz
b) VBW ≥ 3 x RBW
c) Detector = peak
d) Trace mode = Max hold
e) Sweep = auto couple
f) Allow trace to fully stabilize
g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

Minimum Standard :

6 dB Bandwidth	>	500kHz

Test Data :

Frequency (MHz)	6dB Bandwidth (MHz)	99% Bandwidth (MHz)	Result
2 402	0.693	1.065	Complies
2 440	0.690	1.067	Complies
2 480	0.684	1.068	Complies

See next pages for actual measured spectrum plots.

6 dB bandwidth & 99% Bandwidth
Low channel (2 402 MHz)



Middle channel (2 440MHz)



High channel (2 480 MHz)



4.2 Maximum peak Conducted Output Power

Test Procedures

KDB 558074 - Section 8.3.1.1
ANSI C63.10-2013 - Section 11.9.1.1

This procedure shall be used when the measurement instrument has available a resolution bandwidth that is greater than the DTS bandwidth.

Test Settings:

Center frequency = the highest, middle and the lowest channels

a) RBW ≥ DTS bandwidth
b) VBW ≥ 3 x RBW
c) span ≥ 3 x RBW
d) Sweep time = auto couple
e) Detector = peak
f) Trace mode= max hold
g) Allow trace to fully stabilize
h) Use peak marker function to determine the peak amplitude level.

Limit :

Maximum Output Power < 1 W (30 dBm)

Test Data :

Frequency (MHz)	Maximum peak Conducted Output Power		
	Output power (dBm)	Output power (mW)	Result
2 402	-12.581	0.055	Complies
2 440	-12.066	0.062	Complies
2 480	-11.560	0.070	Complies

See next pages for actual measured spectrum plots.

Low channel (2 402 MHz)



Middle channel (2 440 MHz)



High channel (2 480 MHz)



4.3 Transmitter Power Spectral Density

Test Procedures

KDB 558074 - Section 8.4
ANSI C63.10-2013 - Section 11.10.2

This procedure shall be used if maximum peak conducted output power was used to demonstrate compliance.

Test Settings:

Center frequency = the highest, middle and the lowest channels

a) RBW : 3 kHz ≤ RBW ≤ 100 kHz

b) VBW ≥ 3 x RBW

c) span ≥ 1.5 x DTS bandwidth

d) Sweep time = auto couple

e) Detector = peak

f) Trace mode= max hold

g) Allow trace to fully stabilize

h) Use the peak marker function to determine the maximum amplitude level within the RBW.

Limit :

Power Spectral Density < 8dBm @ 3 kHz BW

Test Data :

Frequency (MHz)	Power Spectral Density	
	dBm/3kHz	Result
2 402	-30.114	Complies
2 440	-29.664	Complies
2 480	-29.184	Complies

See next pages for actual measured spectrum plots.

Low channel (2 402 MHz)



Middle channel (2 440 MHz)



High channel (2 480 MHz)



4.4 Conducted Spurious emission

Test Procedures

KDB 558074 - Section 8.5
ANSI C63.10-2013 - Section 11.11.3

The Unwanted emission from the EUT were measured according to the dictates PKPSD measurement procedure in section 11.11 of ANSI C63.10-2013.

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated device is operating, the RF power that is produced shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided that the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of root-mean-square averaging over a time interval, as permitted under Section 5.4(4), the attenuation required shall be 30 dB instead of 20 dB. Attenuation below the general field strength limits specified in RSS-Gen is not required.

Test Settings:

Center frequency = the highest, middle and the lowest channels

a) RBW = 100 kHz
b) VBW ≥ 3 x RBW
c) Detector = peak
d) Sweep time = auto couple
e) Trace mode= max hold
f) Allow trace to fully stabilize
g) Use the peak marker function to determine the maximum amplitude level.

Limit :

Emission level	<	20 dBc

Test results: Complies

- All conducted emission in any 100kHz bandwidth outside of the spread spectrum band was at least 20dB lower than the highest in-band spectral density. Therefore the applying equipment meets the requirement.

See next pages for actual measured spectrum plots.


Agilent Spectrum Analyzer - Swept SA
Center Freq 2.400000000 GHz
PNO: Wide
IFGain:Low
Trig: Free Run
#Atten: 10 dB
Avg Type: Log-Pwr
Avg|Hold:>30/30
Ext Gain: -0.86 dB
02:43:34 PM Sep 02, 2019
Mkr1 2.401 97 GHz
-12.526 dBm
10 dB/div
Ref 0.00 dBm
Center 2.400000 GHz
#Res BW 100 kHz
#VBW 300 kHz
Span 10.00 MHz
Sweep 1.000 ms (1001 pts)
Frequency
Auto Tune
Center Freq
2.400000000 GHz
Start Freq
2.395000000 GHz
Stop Freq
2.405000000 GHz
CF Step
1.000000 MHz
Auto
Man
Freq Offset
0 Hz


Agilent Spectrum Analyzer - Swept SA
Center Freq 2.483500000 GHz
PNO: Wide
IFGain:Low
Trig: Free Run
#Atten: 10 dB
Avg Type: Log-Pwr
Avg|Hold:>30/30
Ext Gain: -0.86 dB
02:48:15 PM Sep 02, 2019
Mkr1 2.479 96 GHz
-11.510 dBm
10 dB/div
Ref 0.00 dBm
Center 2.483500 GHz
#Res BW 100 kHz
#VBW 300 kHz
Span 10.00 MHz
Sweep 1.000 ms (1001 pts)
Frequency
Auto Tune
Center Freq
2.483500000 GHz
Start Freq
2.478500000 GHz
Stop Freq
2.488500000 GHz
CF Step
1.000000 MHz
Auto
Man
Freq Offset
0 Hz


Agilent Spectrum Analyzer - Swept SA
Start Freq 30.000000 MHz
PNO: Fast
IFGain:Low
Trig: Free Run
#Atten: 10 dB
Avg Type: Log-Pwr
Avg|Hold:>30/30
Ext Gain: -0.86 dB
02:43:19 PM Sep 02, 2019
Mkr1 7.196 GHz
-55.408 dBm
10 dB/div
Ref 0.00 dBm
Start 30 MHz
#Res BW 100 kHz
#VBW 300 kHz
Stop 25.00 GHz
Sweep 2.386 s (1001 pts)
Frequency
Auto Tune
Center Freq
12.515000000 GHz
Start Freq
30.000000 MHz
Stop Freq
25.000000000 GHz
CF Step
2.497000000 GHz
Auto
Man
Freq Offset
0 Hz


Agilent Spectrum Analyzer - Swept SA
Center Freq 12.515000000 GHz
PNO: Fast
IFGain:Low
Trig: Free Run
#Atten: 10 dB
Avg Type: Log-Pwr
Avg|Hold:>30/30
Ext Gain: -0.86 dB
02:45:47 PM Sep 02, 2019
Mkr1 7.321 GHz
-54.153 dBm
10 dB/div
Ref 0.00 dBm
Start 30 MHz
#Res BW 100 kHz
#VBW 300 kHz
Stop 25.00 GHz
Sweep 2.386 s (1001 pts)
Frequency
Auto Tune
Center Freq
12.515000000 GHz
Start Freq
30.000000 MHz
Stop Freq
25.000000000 GHz
CF Step
2.497000000 GHz
Auto
Man
Freq Offset
0 Hz


Agilent Spectrum Analyzer - Swept SA
Center Freq 12.515000000 GHz
PNO: Fast
IFGain:Low
Trig: Free Run
#Atten: 10 dB
Avg Type: Log-Pwr
Avg|Hold:>30/30
Ext Gain: -0.86 dB
02:48:00 PM Sep 02, 2019
Mkr1 4.949 GHz
-55.645 dBm
10 dB/div
Ref 0.00 dBm
Start 30 MHz
#Res BW 100 kHz
#VBW 300 kHz
Stop 25.00 GHz
Sweep 2.386 s (1001 pts)
Frequency
Auto Tune
Center Freq
12.515000000 GHz
Start Freq
30.000000 MHz
Stop Freq
25.000000000 GHz
CF Step
2.497000000 GHz
Auto
Man
Freq Offset
0 Hz

4.5 Radiated Emission

Test Location

☒ 10 m SAC (test distance : ☐ 10 m, ☒ 3 m)
☒ 3 m SAC (test distance : 3 m)

Test Procedures

KDB 558074 - Section 8.5, 8.6
ANSI C63.10-2013 - Section 11.11, 11.12

1) In the frequency range of 9 kHz to 30 MHz, magnetic field is measured with Loop Antenna. The Test Antenna is positioned with its plane vertical at 1m distance from the EUT. The center of the Loop Test Antenna is 1m above the ground. During the measurement the Loop Test Antenna rotates about its vertical axis for maximum response at each azimuth about the EUT.
2) In the frequency rage above 30 MHz, Bi-Log Test Antenna(30 MHz to 1 GHz) and Horn Test Antenna(above 1 GHz) are used. Test Antenna is 3m away from the EUT. Test Antenna height is carried from 1m to 4m above the ground to determine the maximum value of the field strength. The emissions levels at both horizontal and vertical polarizations should be tested.

Test Settings:

Frequency Range = 9 kHz ~ 1 GHz

a) RBW = 200 Hz(9 kHz ~150 kHz), 9 kHz(150 kHz ~ 30 MHz), 120 kHz(30 MHz ~ 1GHz)

b) VBW ≥ RBW

c) Detector = CISPR Quasi-peak

d) Sweep time = auto couple

- Peak

Frequency Range = 1 GHz ~ 25 GHz (2.4 GHz 10th harmonic)

a) RBW = 1 MHz

b) VBW ≥ 3 x RBW

c) Detector = Peak

d) Sweep time = auto

e) Trace mode = max hold

- Average (duty cycle ≥ 98%)

Frequency Range = 1 GHz ~ 25 GHz (2.4 GHz 10th harmonic)

a) RBW = 1 MHz

b) VBW ≥ 3 x RBW

c) Detector = RMS

d) Sweep time = auto

e) Averaging type = power (i.e., RMS)

f) Trace mode = average (at least 100 traces)

- Average (duty cycle < 98%, duty cycle variations are less than ±2%)

Frequency Range = 1 GHz ~ 25 GHz (2.4 GHz 10th harmonic)

a) RBW = 1 MHz

b) VBW ≥ 3 x RBW

c) Detector = RMS

d) Sweep time = auto

e) Averaging type = power (i.e., RMS)

f) Trace mode = average (at least 100 traces)

A correction factor shall be added to the measurement results prior to comparing to the emission limit in order to compute the emission level that would have been measured had the test been performed at 100 % duty cycle.
If power averaging (RMS) mode, then the applicable correction factor is
10 log(1/x), where x is the duty cycle.
Duty Cycle Fator : 7.58 dB

Limit :

FCC Part 15 § 15.205 (a) Except as shown in paragraph (d) of this section, only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	MHz	MHz	GHz
0.09-0.11	8.37626-8.38675	73-74.6	399.9-410	2690-2900	10.6-12.7
[1]0.495-0.505	8.41425-8.41475	74.8-75.2	608-614	3260-3267	13.25-13.4
2.1735-2.1905	12.29-12.293	108-121.94	960-1240	3332-3339	14.47-14.5
4.125-4.128	12.51975-12.52025	123-138	1300-1427	3345.8-3358	15.35-16.2
4.17725-4.17775	12.57675-12.57725	149.9-150.05	1435-1626.5	3600-4400	17.7-21.4
4.20725-4.20775	13.36-13.41	156.52475-156.52525	1645.5-1646.5	4500-5150	22.01-23.12
6.215-6.218	16.42-16.423	156.7-156.9	1660-1710	5350-5460	23.6-24
6.26775-6.26825	16.69475-16.69525	162.0125-167.17	1718.8-1722.2	7250-7750	31.2-31.8
6.31175-6.31225	16.80425-16.80475	167.72-173.2	2200-2300	8025-8500	36.43-36.5
8.291-8.294	25.5-25.67	240-285	2310-2390	9000-9200	[2]Above 38.6
8.362-8.366	37.5-38.25	322-335.4	2483.5-2500	9300-9500	

[1] Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz.

[2] Above 38.6

§ 15.205 (b) Except as provided in paragraphs (d) and (e), the field strength of emissions appearing within these frequency bands shall not exceed the limits shown is Section 15.209. At frequencies equal to or less than 1000 MHz, compliance with the limits in Section 15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasi-peak detector. Above 1000 MHz, compliance with the emission limits in Section 15.209 shall be demonstrated based on the average value of the measured emissions. The provisions in Section 15.35 apply to these measurements.

FCC Part 15 § 15.209 (a) Except as provided elsewhere in this Subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table :

Frequency(MHz)	Field Strength uV/m@3m	Field Strength dBuV/m@3m	Deasurement Distance (meters)
0.009-0.490	2400/F(kHz)	-	300
0.490-1.705	24000/F(kHz)	-	30
1.705-30	30	-	30
30-88	100**	40	3
88-216	150**	43.5	3
216-960	200**	46	3
Above 960	500	54	3

** Except as provided in 15.209(g).fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54-72MHz, 76-88MHz, 174-216MHz, 470-806MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g.15.231 and 15.241.

Note :

1) For above 1 GHz, the emission limit in this paragraph is based on measurement instrumentation employing an average detector, measurement using instrumentation with a peak detector function, corresponding to 20 dB above the maximum permitted average limit.
2) For above 1 GHz, limit field strength of harmonics : 54 dBuV/m@3m (AV) and 74 dBuV/m@3m (PK)

Test Setup:

1) For field strength of emissions from 9 kHz to 30 MHz



2) For field strength of emissions from 30 MHz to 1 GHz



3) For field strength of emissions above 1 GHz



Test results

1) 9 kHz to 30 MHz

Test mode : Transmitter

The requirements are:
☒ Complies

Test Data

Test Model : CR-CPB-v001
Test Mode : 9k-30M
Tester : Kim Ji Hye



Frequency [MHz]	(P)	Reading QP [dBuV]	dB [1/m]	Result QP [dBuV/m]	Limit QP [dBuV/m]	Margin QP [dB]
The emissions 9 kHz to 30MHz were 20 dB lower than the limit.						

Remark :
1. The Unwanted emission was measured in the following position: EUT stand-up position(Z axis), lie-down position(X,Y axis). The worst emission was found in lie-down position(X axis) and the worst case was recorded.
2. Distance extrapolation factor = 40 log (specific distance / test distance) (dB)

2) 30 MHz to 1 GHz

Test mode : Transmitter (Worst Case)

The requirements are:
☒ Complies

Test Data

Test Model : CR-CPB-v001
Test Mode : 30M-1G
Tester : Kim Ji Hye



Final Result

No.	Frequency [MHz]	(P)	Reading QP [dB(uV)]	c.f [dB(1/m)]	Result QP [dB(uV/m)]	Limit QP [dB(uV/m)]	Margin QP [dB]	Height [cm]	Angle [deg]
1	49.158	V	31.1	-15.1	16.0	40.0	24.0	291.0	42.0

Remark :
1. The Unwanted emission was measured in the following position: EUT stand-up position(Z axis), lie-down position(X,Y axis). The worst emission was found in lie-down position(X axis) and the worst case was recorded.
2. Result = Reading + c.f(Correction factor)
3. Correction factor = Antenna factor + Cable loss + 6 dB attenuator - Amp Gain

3) above 1 GHz

Test mode : Transmitter

The requirements are:
☒ Complies

Test Data

Model Name : CR-CPB-v001
Manufacturer :
Mode : 1G-18G
Model Type :





Low (2 402 MHz)

Frequency [MHz]	(P)	Limit AV [dBuV/m]	Limit PK [dBuV/m]	Result AV [dBuV/m]	Result PK [dBuV/m]	Margin AV [dB]	Margin PK [dB]
The emissions above 1GHz were 20 dB lower than the limit.							

Mid (2 440 MHz)

Frequency [MHz]	(P)	Limit AV [dBuV/m]	Limit PK [dBuV/m]	Result AV [dBuV/m]	Result PK [dBuV/m]	Margin AV [dB]	Margin PK [dB]
The emissions above 1GHz were 20 dB lower than the limit.							

High (2 480 MHz)

Frequency [MHz]	(P)	Limit AV [dBuV/m]	Limit PK [dBuV/m]	Result AV [dBuV/m]	Result PK [dBuV/m]	Margin AV [dB]	Margin PK [dB]
The emissions above 1GHz were 20 dB lower than the limit.							

Remarks

1. The Unwanted emission was measured in the following position: EUT stand-up position(Z axis), lie-down position(X,Y axis). The worst emission was found in lie-down position(X axis) and the worst case was recorded.
2. Result = Reading + c.f(correction factor)
3. Correction factor = Antenna factor + Cable loss - Amp Gain

4.6 AC Conducted Emissions

Frequency Range of Measurement
150 kHz to 30 MHz

Instrument Settings
IF Band Width: 9 kHz

Test Procedures

ANSI C63.10-2013 - Section 6.2

The EUT was placed on a non-metallic table 0.8m above the metallic, grounded floor and 0.4m from the reference ground plane wall. The distance to other metallic surfaces was at least 0.8m.
Amplitude measurements were performed with a quasi-peak detector and an average detector.

Limit
- **15.207(a)**

Frequency (MHz)	Conducted Limit (dBuV)	
	Quasi-peak	Average**
0.15 ~ 0.5	66 to 56*	56 to 46*
0.5 ~ 5	56	46
5 ~ 30	60	50

* The level decreases linearly with the logarithm of the frequency.
** A linear average detector is required.

Test Results

The requirements are:
☒ Complies

Test Data

[LINE]

3CE_Class B_L1



Final Result 1

Frequency (MHz)	QuasiPeak (dBµV)	Meas. Time (ms)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.150000	48.8	1000.0	9.000	On	L1	9.8	17.2	66.0
0.190500	44.1	1000.0	9.000	On	L1	10.0	19.9	64.0
0.231000	39.1	1000.0	9.000	On	L1	9.8	23.3	62.4
0.289500	35.7	1000.0	9.000	On	L1	9.8	24.8	60.5
0.532500	42.7	1000.0	9.000	On	L1	10.0	13.3	56.0
0.537000	43.1	1000.0	9.000	On	L1	10.0	12.9	56.0

Final Result 2

Frequency (MHz)	CAverage (dBµV)	Meas. Time (ms)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.159000	36.6	1000.0	9.000	On	L1	10.0	18.9	55.5
0.429000	31.6	1000.0	9.000	On	L1	10.0	15.7	47.3
0.532500	38.2	1000.0	9.000	On	L1	10.0	7.8	46.0
0.537000	38.6	1000.0	9.000	On	L1	10.0	7.4	46.0
0.694500	26.6	1000.0	9.000	On	L1	10.0	19.4	46.0
0.951000	26.1	1000.0	9.000	On	L1	9.9	19.9	46.0

[NEUTRAL]

3CE_Class B_N



Final Result 1

Frequency (MHz)	QuasiPeak (dBµV)	Meas. Time (ms)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.172500	45.9	1000.0	9.000	On	N	10.1	18.9	64.8
0.186000	44.4	1000.0	9.000	On	N	10.0	19.8	64.2
0.262500	35.9	1000.0	9.000	On	N	9.8	25.5	61.4
0.411000	35.2	1000.0	9.000	On	N	10.0	22.4	57.6
0.532500	43.1	1000.0	9.000	On	N	10.0	12.9	56.0
0.537000	43.4	1000.0	9.000	On	N	10.0	12.6	56.0

Final Result 2

Frequency (MHz)	CAverage (dBµV)	Meas. Time (ms)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.159000	36.4	1000.0	9.000	On	N	10.0	19.2	55.5
0.429000	31.1	1000.0	9.000	On	N	10.0	16.2	47.3
0.532500	38.6	1000.0	9.000	On	N	10.0	7.4	46.0
0.537000	38.8	1000.0	9.000	On	N	10.0	7.2	46.0
0.703500	26.2	1000.0	9.000	On	N	9.9	19.8	46.0
0.888000	24.1	1000.0	9.000	On	N	9.9	21.9	46.0

APPENDIX A – Test Equipment Used For Tests

	Name of Equipment	Manufacturer	Model No.	Serial No.	Date of Calibration	Due Date
1	MXA Signal Analyzer	AGILENT	N9020A	MY50200512	2019-04-23	2020-04-23
2	Signal Generator	Rohde & Schwarz	SMB100A	175528	2018-10-24	2019-10-24
3	EMI Test Receiver	Rohde & Schwarz	ESCI7	100814	2018-10-25	2019-10-25
4	Bilog Antenna	Schaffner	CBL6111C	2551	2018-05-10	2020-05-10
5	Active Loop Antenna	SCHWARZBECK	FMZB 1513	1513-126	2018-05-27	2020-05-27
6	6dB Attenuator	R&S	DNF	272.4110.50-2	2018-10-25	2019-10-25
7	AMPLIFIER	SONOMA	310	291721	2019-01-28	2020-01-28
8	EMI Test Receiver	Rohde & Schwarz	ESU40	100336	2019-01-29	2020-01-29
9	Preamplifier	Agilent	8449B	3008A02011	2018-12-03	2019-12-03
10	Horn Antenna	ETS-Lindgren	3117	00154525	2017-09-14	2019-09-14
11	Horn Antenna	ETS-Lindgren	3116	00062916	2019-04-22	2021-04-22
12	Band Reject Filter	Micro Tronics	BRM50702	G233	2019-01-28	2020-01-28
13	EMI Test Receiver	Rohde & Schwarz	ESCI3	100032	2019-01-29	2020-01-29
14	LISN	Rohde & Schwarz	ENV216	101235	2019-01-29	2020-01-29

	Cable	Manufacturer	Model No.	Serial No.	Check Date
1	RF Cable	Junkosha Inc.	MWX221	1512S148	2019-09-02
2	RF Cable	HUBER+SUHNER	SUCOFLEX 102	MY073/2	2018-12-19
3	RF Cable	HUBER+SUHNER	SUCOFLEX 102	MY4728/2	2018-12-19
4	RF Cable	HUBER+SUHNER	SUCOFLEX 104	MY27558/4	2018-12-19
5	RF Cable	HUBER+SUHNER	SUCOFLEX 104	N/A	2018-12-19
6	RF Cable	HUBER+SUHNER	SUCOFLEX 104	MY27573/4	2018-12-19
7	RF Cable	HUBER+SUHNER	SUCOFLEX 106	N/A	2018-12-19
8	RF Cable	Canare Corporation	L-5D2W	N/A	2018-12-19