

TEST REPORT

Application No.: SZCR2507003306AT
Applicant: Wyze Labs, Inc.
Address of Applicant: 5808 Lake Washington Blvd NE Ste 300 Kirkland Washington 98033 United States
Manufacturer: Wyze Labs, Inc.
Address of Manufacturer: 5808 Lake Washington Blvd NE Ste 300 Kirkland Washington 98033 United States
Equipment Under Test (EUT):
EUT Name: Wyze Scale Ultra BodyScan
Model No.: WL_SCLUBB, WL_SCLUBW ♣
 ♣ Please refer to section 2 of this report which indicates which model was actually tested and which were electrically identical.
Trade Mark: WYZE
FCC ID: 2AUIUWLSCLUB
Standard(s) : 47 CFR Part 15, Subpart C 15.247
Date of Receipt: 2025-07-28
Date of Test: 2025-08-06 to 2025-08-08
Date of Issue: 2025-08-29

Test Result:	Pass*
---------------------	--------------

* In the configuration tested, the EUT complied with the standards specified above.

Keny Xu

Keny Xu
EMC Laboratory Manager




SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/1

Report No.: SZCR250700330603

Page: 2 of 124

Revision Record				
Version	Chapter	Date	Modifier	Remark
01		2025-08-29		Original

Authorized for issue by:				
				
		Charlie Dai/Project Engineer		
				
		Eric Fu/Reviewer		



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch Testing & Calibration Laboratory

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

2 Test Summary

Radio Spectrum Technical Requirement				
Item	Standard	Method	Requirement	Result
Antenna Requirement	47 CFR Part 15, Subpart C 15.247	N/A	47 CFR Part 15, Subpart C 15.203 & 15.247(b)(4)	Pass

Radio Spectrum Matter Part				
Item	Standard	Method	Requirement	Result
Radiated Emissions which fall in the restricted bands	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2020) Section 6.10.5	47 CFR Part 15, Subpart C 15.205 & 15.209	Pass
Radiated Spurious Emissions Below 1GHz		ANSI C63.10 (2020) Section 6.4,6.5	47 CFR Part 15, Subpart C 15.205 & 15.209	Pass
Radiated Spurious Emissions Above 1GHz		ANSI C63.10 (2020) Section 6.6	47 CFR Part 15, Subpart C 15.205 & 15.209	Pass
Conducted Peak Output Power		ANSI C63.10 (2020) Section 11.9.2	47 CFR Part 15, Subpart C 15.247(b)(3)	Pass
Minimum 6dB Bandwidth		ANSI C63.10 (2020) Section 11.8.1	47 CFR Part 15, Subpart C 15.247a(2)	Pass
Power Spectrum Density		ANSI C63.10 (2020) Section 11.10.2	47 CFR Part 15, Subpart C 15.247(e)	Pass
Conducted Band Edges Measurement		ANSI C63.10 (2020) Section 6.10.4	47 CFR Part 15, Subpart C 15.247(d)	Pass
Conducted Spurious Emissions		ANSI C63.10 (2020) Section 11.11	47 CFR Part 15, Subpart C 15.247(d)	Pass

Declaration of EUT Family Grouping:

Model No.: WL_SCLUBB, WL_SCLUBW

Only the model WL_SCLUBB was tested, since according to the declaration from the applicant, the electrical circuit design, PCB layout, components used and internal wiring and functions were identical for the above models, with only difference on color.



3 Contents

	Page
1 Cover Page	1
2 Test Summary	3
3 Contents	4
4 General Information	6
4.1 Details of E.U.T.	6
4.2 Description of Support Units	6
4.3 Measurement Uncertainty	7
4.4 Test Location	8
4.5 Test Facility	8
4.6 Deviation from Standards	8
4.7 Abnormalities from Standard Conditions	8
5 Equipment List	9
6 Radio Spectrum Technical Requirement	11
6.1 Antenna Requirement	11
6.1.1 Test Requirement:	11
6.1.2 Conclusion	11
7 Radio Spectrum Matter Test Results	12
7.1 Radiated Emissions which fall in the restricted bands	12
7.1.1 E.U.T. Operation	12
7.1.2 Test Mode Description	12
7.1.3 Test Setup Diagram	13
7.1.4 Measurement Procedure and Data	14
7.2 Radiated Spurious Emissions Below 1GHz	39
7.2.1 E.U.T. Operation	39
7.2.2 Test Mode Description	39
7.2.3 Test Setup Diagram	39
7.2.4 Measurement Procedure and Data	40
7.3 Radiated Spurious Emissions Above 1GHz	43
7.3.1 E.U.T. Operation	43
7.3.2 Test Mode Description	43
7.3.3 Test Setup Diagram	43
7.3.4 Measurement Procedure and Data	44
7.4 Conducted Peak Output Power	81
7.4.1 E.U.T. Operation	81
7.4.2 Test Setup Diagram	81
7.4.3 Measurement Procedure and Data	81
7.5 Minimum 6dB Bandwidth	82
7.5.1 E.U.T. Operation	82
7.5.2 Test Setup Diagram	82



SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/1

Report No.: SZCR250700330603

Page: 5 of 124

7.5.3	Measurement Procedure and Data.....	82
7.6	Power Spectrum Density.....	83
7.6.1	E.U.T. Operation.....	83
7.6.2	Test Setup Diagram.....	83
7.6.3	Measurement Procedure and Data.....	83
7.7	Conducted Band Edges Measurement.....	84
7.7.1	E.U.T. Operation.....	84
7.7.2	Test Setup Diagram.....	84
7.7.3	Measurement Procedure and Data.....	84
7.8	Conducted Spurious Emissions.....	85
7.8.1	E.U.T. Operation.....	85
7.8.2	Test Setup Diagram.....	85
7.8.3	Measurement Procedure and Data.....	85
8	Test Setup Photo.....	86
9	EUT Constructional Details (EUT Photos).....	86
10	Appendix.....	87



SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch Testing & Calibration Laboratory

Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

4 General Information

4.1 Details of E.U.T.

Power supply:	DC 6V For Battery Alkaline AA,1.5V*4
Operation Frequency:	802.11b/g/n(HT20): 2412MHz to 2462MHz
Modulation Type:	802.11b: DSSS (DBPSK, DQPSK, CCK); 802.11g/n: OFDM (BPSK, QPSK, 16QAM, 64QAM)
Number of Channels:	802.11b/g/n(HT20):11
Channel Spacing:	5MHz
Antenna Type:	IPEX Antenna
Antenna Gain:	2.49 dBi

Remark:The information in this section is provided by the applicant or manufacturer, SGS is not liable to the accuracy, suitability, reliability or/and integrity of the information.

4.2 Description of Support Units

Description	Manufacturer	Model No.	Serial No.
--	--	--	--
The EUT has been tested as an independent unit.			



4.3 Measurement Uncertainty

Test Item	Measurement Uncertainty
Radiated Emissions which fall in the restricted bands	$\pm 6.0\text{dB}$ (Below 1GHz); $\pm 4.6\text{dB}$ (Above 1GHz)
Radiated Spurious Emissions Below 1GHz	$\pm 6.0\text{dB}$ for 3m; $\pm 5.0\text{dB}$ for 10m
Radiated Spurious Emissions Above 1GHz	$\pm 4.6\text{dB}$ (1-18GHz); $\pm 4.8\text{dB}$ (18-40GHz)
Conducted Peak Output Power	$\pm 0.75\text{dB}$
Minimum 6dB Bandwidth	$\pm 3\%$
Power Spectrum Density	$\pm 2.84\text{dB}$
Conducted Band Edges Measurement	$\pm 0.75\text{dB}$
Conducted Spurious Emissions	$\pm 0.75\text{dB}$

Remark:

The U_{lab} (lab Uncertainty) is less than $U_{\text{CISPR/ETSI}}$ (CISPR/ETSI Uncertainty), so the test results

- compliance is deemed to occur if no measured disturbance level exceeds the disturbance limit;
- non-compliance is deemed to occur if any measured disturbance level exceeds the disturbance limit.



SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/1

Report No.: SZCR250700330603

Page: 8 of 124

4.4 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen Branch

No. 1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China. 518057.

Tel: +86 755 2601 2053 Fax: +86 755 2671 0594

No tests were sub-contracted.

4.5 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

• A2LA (Certificate No. 3816.01)

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 3816.01.

• VCCI (Member No. 1937)

The 3m Fully-anechoic chamber for above 1GHz, 10m Semi-anechoic chamber for below 1GHz, Shielded Room for Mains Port Conducted Interference Measurement and Telecommunication Port Conducted Interference Measurement of SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen EMC laboratory have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: G-20026, R-14188, C-12383 and T-11153 respectively.

• FCC –Designation Number: CN1336

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been recognized as an accredited testing laboratory.

Designation Number: CN1336. Test Firm Registration Number: 787754.

• Innovation, Science and Economic Development Canada

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been recognized by ISED as an accredited testing laboratory.

CAB identifier: CN0006.

IC#: 4620C.

4.6 Deviation from Standards

None

4.7 Abnormalities from Standard Conditions

None



SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch EMC Laboratory

Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

5 Equipment List

Radiated Emissions which fall in the restricted bands					
Equipment	Manufacturer	Model No.	Inventory No.	Cal Date	Cal Due Date
3m Fully-Anechoic Chamber	AUDIX	N/A	SEM001-02	2025-05-07	2028-05-06
Signal Analyzer	Rohde & Schwarz	FSV40	SEM008-04	2025-03-04	2026-03-03
Horn Antenna	Rohde&Schwarz	HF907	SEM003-07	2025-07-22	2026-07-21
Microwave system amplifier	Agilent	83017A	SEM005-25	2024-09-14	2025-09-13
Measurement Software	AUDIX	e3 V8.2014-6-27	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM026-01	2025-07-05	2026-07-04
Broad-Band Horn Antenna	Schwarzbeck	BBHA 9170	SEM003-15	2025-07-22	2027-07-21
Pre-Amplifier	Compliance Directions Systems Inc.	PAP-2640-50	SEM005-08	2025-03-21	2026-03-20

Radiated Spurious Emissions Below 1GHz					
Equipment	Manufacturer	Model No.	Inventory No.	Cal Date	Cal Due Date
Loop Antenna	ETS-Lindgren	6502	SEM003-08	2023-11-20	2025-11-19
3m Semi-Anechoic Chamber	ETS-LINDGREN	N/A	SEM001-01	2023-06-19	2026-06-18
MXE EMI Receiver	Agilent Technologies	N9038A	SEM004-15	2025-07-25	2026-07-24
BiConiLog Antenna	ETS-LINDGREN	3142C	SEM003-01	2023-09-16	2025-09-15
Pre-Amplifier	Agilent Technologies	8447D	SEM005-01	2025-03-04	2026-03-03
Measurement Software	AUDIX	e3 V8.2014-6-27	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM025-01	2025-07-05	2026-07-04



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch Testing & Calibration Laboratory

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/1

Report No.: SZCR250700330603

Page: 10 of 124

Radiated Spurious Emissions Above 1GHz					
Equipment	Manufacturer	Model No.	Inventory No.	Cal Date	Cal Due Date
3m Fully-Anechoic Chamber	AUDIX	N/A	SEM001-02	2025-05-07	2028-05-06
Signal Analyzer	Rohde & Schwarz	FSV40	SEM008-04	2025-03-04	2026-03-03
Horn Antenna	Rohde&Schwarz	HF907	SEM003-07	2025-07-22	2026-07-21
Microwave system amplifier	Agilent	83017A	SEM005-25	2024-09-14	2025-09-13
Measurement Software	AUDIX	e3 V8.2014-6-27	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM026-01	2025-07-05	2026-07-04
Broad-Band Horn Antenna	Schwarzbeck	BBHA 9170	SEM003-15	2025-07-22	2027-07-21
Pre-Amplifier	Compliance Directions Systems Inc.	PAP-2640-50	SEM005-08	2025-03-21	2026-03-20

General used equipment					
Equipment	Manufacturer	Model No.	Inventory No.	Cal Date	Cal Due Date
Humidity/ Temperature Indicator	deli	8838	SEM002-32	2025-07-23	2026-07-22
Humidity/ Temperature Indicator	deli	8838	SEM002-33	2025-07-23	2026-07-22
Barometer	Changchun Meteorological Industry Factory	DYM3	SEM002-01	2025-03-03	2026-03-02



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch
 No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
 中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

6 Radio Spectrum Technical Requirement

6.1 Antenna Requirement

6.1.1 Test Requirement:

47 CFR Part 15, Subpart C 15.203 & 15.247(b)(4)

6.1.2 Conclusion

Standard Requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

15.247(b) (4) requirement:

The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

EUT Antenna:

The antenna is integrated on the main PCB and no consideration of replacement. The best case gain of the antenna is 2.7 dBi.

Antenna location: Refer to internal photo.



7 Radio Spectrum Matter Test Results

7.1 Radiated Emissions which fall in the restricted bands

Test Requirement 47 CFR Part 15, Subpart C 15.205 & 15.209

Test Method: ANSI C63.10 (2020) Section 6.10.5

Measurement Distance: 3m

Limit:

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

7.1.1 E.U.T. Operation

Operating Environment:

Temperature: 23.5 °C

Humidity: 56.3 % RH


Atmospheric Pressure: 1020 mbar

7.1.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	00	TX mode_Keep the EUT in continuously transmitting mode with all modulation types. Only the data of worst case is recorded in the report.



7.1.3 Test Setup Diagram



30MHz-1GHz

Above 1GHz



7.1.4 Measurement Procedure and Data

- a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- d. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- e. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- f. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- g. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- h. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- j. Repeat above procedures until all frequencies measured was complete.

Remark 1: Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor


Remark 2: For frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.

Remark 3: The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 3MHz for Peak detection (PK) and Average detection (AV) at frequency above 1GHz.

Remark 4: For fundamental and harmonic signal measurement, the resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is $\geq 1/T$ (Duty cycle $< 98\%$) or 10Hz (Duty cycle $\geq 98\%$) for Average detection (AV) at frequency above 1GHz.



Test Mode: 00; Polarity: Horizontal; Modulation:802.11b; Bandwidth:20MHz; Channel:Low




Site : chamber
Condition: 3m HORIZONTAL
Job No : 03306AT\03307AT
Mode : 2412 Band edge
: 2.4G WIFI 11B

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2385.494	16.13	29.10	32.78	43.82	56.27	74.00	-17.73	peak
2	2390.000	16.13	29.10	32.78	41.39	53.84	74.00	-20.16	peak
3 p	2412.000	16.17	29.05	32.77	96.25	108.70	74.00	34.70	peak



Test Mode: 00; Polarity: Horizontal; Modulation:802.11b; Bandwidth:20MHz; Channel:Low




Site : chamber
Condition: 3m HORIZONTAL
Job No : 03306AT\03307AT
Mode : 2412 Band edge
: 2.4G WIFI 11B

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2386.219	16.13	29.10	32.78	33.06	45.51	54.00	-8.49	Average
2	2390.000	16.13	29.10	32.78	31.63	44.08	54.00	-9.92	Average
3 q	2412.000	16.17	29.05	32.77	88.01	100.46	54.00	46.46	Average



Test Mode: 00; Polarity: Vertical; Modulation:802.11b; Bandwidth:20MHz; Channel:Low




Site : chamber
Condition: 3m VERTICAL
Job No : 03306AT\03307AT
Mode : 2412 Band edge
: 2.4G WIFI 11B

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2386.098	16.13	29.10	32.78	41.69	54.14	74.00	-19.86	Peak
2	2390.000	16.13	29.10	32.78	40.03	52.48	74.00	-21.52	Peak
3 p	2412.000	16.17	29.05	32.77	91.51	103.96	74.00	29.96	Peak



Test Mode: 00; Polarity: Vertical; Modulation:802.11b; Bandwidth:20MHz; Channel:Low




Site : chamber
Condition: 3m VERTICAL
Job No : 03306AT\03307AT
Mode : 2412 Band edge
: 2.4G WIFI 11B

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2385.615	16.13	29.10	32.78	29.64	42.09	54.00	-11.91	Average
2	2390.000	16.13	29.10	32.78	28.70	41.15	54.00	-12.85	Average
3 q	2412.000	16.17	29.05	32.77	83.39	95.84	54.00	41.84	Average



Test Mode: 00; Polarity: Horizontal; Modulation:802.11b; Bandwidth:20MHz; Channel:High




Site : chamber
 Condition: 3m HORIZONTAL
 Job No : 03306AT\03307AT
 Mode : 2462 Band edge
 : 2.4G WIFI 11B

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 p	2462.000	16.24	28.90	32.74	95.54	107.94	74.00	33.94	peak
2	2483.500	16.28	28.90	32.73	41.68	54.13	74.00	-19.87	peak
3	2488.461	16.28	28.90	32.73	43.48	55.93	74.00	-18.07	peak



Test Mode: 00; Polarity: Horizontal; Modulation:802.11b; Bandwidth:20MHz; Channel:High




Site : chamber
Condition: 3m HORIZONTAL
Job No : 03306AT\03307AT
Mode : 2462 Band edge
: 2.4G WIFI 11B

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 q	2462.000	16.24	28.90	32.74	87.32	99.72	54.00	45.72 Average
2	2483.500	16.28	28.90	32.73	31.01	43.46	54.00	-10.54 Average
3	2487.254	16.28	28.90	32.73	31.89	44.34	54.00	-9.66 Average



Test Mode: 00; Polarity: Vertical; Modulation:802.11b; Bandwidth:20MHz; Channel:High




Site : chamber
Condition: 3m VERTICAL
Job No : 03306AT\03307AT
Mode : 2462 Band edge
: 2.4G WIFI 11B

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 p	2462.000	16.24	28.90	32.74	92.00	104.40	74.00	30.40	Peak
2	2483.500	16.28	28.90	32.73	39.98	52.43	74.00	-21.57	Peak
3	2487.606	16.28	28.90	32.73	42.53	54.98	74.00	-19.02	Peak



Test Mode: 00; Polarity: Vertical; Modulation:802.11b; Bandwidth:20MHz; Channel:High




Site : chamber
Condition: 3m VERTICAL
Job No : 03306AT\03307AT
Mode : 2462 Band edge
: 2.4G WIFI 11B

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 q	2462.000	16.24	28.90	32.74	83.54	95.94	54.00	41.94 Average
2	2483.500	16.28	28.90	32.73	29.50	41.95	54.00	-12.05 Average
3	2487.707	16.28	28.90	32.73	30.20	42.65	54.00	-11.35 Average



Test Mode: 00; Polarity: Horizontal; Modulation:802.11g; Bandwidth:20MHz; Channel:Low




Site : chamber
Condition: 3m HORIZONTAL
Job No : 03306AT\03307AT
Mode : 2412 Band edge
: 2.4G WIFI 11G

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2389.726	16.13	29.10	32.78	57.30	69.75	74.00	-4.25	peak
2	2390.000	16.13	29.10	32.78	55.08	67.53	74.00	-6.47	peak
3 p	2412.000	16.17	29.05	32.77	94.83	107.28	74.00	33.28	peak



Test Mode: 00; Polarity: Horizontal; Modulation:802.11g; Bandwidth:20MHz; Channel:Low




Site : chamber
Condition: 3m HORIZONTAL
Job No : 03306AT\03307AT
Mode : 2412 Band edge
: 2.4G WIFI 11G

		Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2389.847	16.13	29.10	32.78	38.35	50.80	54.00	-3.20 Average
2	2390.000	16.13	29.10	32.78	38.34	50.79	54.00	-3.21 Average
3 q	2412.000	16.17	29.05	32.77	84.76	97.21	54.00	43.21 Average



Test Mode: 00; Polarity: Vertical; Modulation:802.11g; Bandwidth:20MHz; Channel:Low




Site : chamber
Condition: 3m VERTICAL
Job No : 03306AT\03307AT
Mode : 2412 Band edge
: 2.4G WIFI 11G

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2389.605	16.13	29.10	32.78	52.71	65.16	74.00	-8.84	Peak
2	2390.000	16.13	29.10	32.78	50.62	63.07	74.00	-10.93	Peak
3 p	2412.000	16.17	29.05	32.77	91.07	103.52	74.00	29.52	Peak



Test Mode: 00; Polarity: Vertical; Modulation:802.11g; Bandwidth:20MHz; Channel:Low




Site : chamber
Condition: 3m VERTICAL
Job No : 03306AT\03307AT
Mode : 2412 Band edge
: 2.4G WIFI 11G

		Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2389.968	16.13	29.10	32.78	34.39	46.84	54.00	-7.16 Average
2	2390.000	16.13	29.10	32.78	34.39	46.84	54.00	-7.16 Average
3 q	2412.000	16.17	29.05	32.77	81.62	94.07	54.00	40.07 Average



Test Mode: 00; Polarity: Horizontal; Modulation:802.11g; Bandwidth:20MHz; Channel:High




Site : chamber
Condition: 3m HORIZONTAL
Job No : 03306AT\03307AT
Mode : 2462 Band edge
: 2.4G WIFI 11G

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 p	2462.000	16.24	28.90	32.74	93.95	106.35	74.00	32.35 peak
2	2483.500	16.28	28.90	32.73	56.87	69.32	74.00	-4.68 peak
3	2483.790	16.28	28.90	32.73	57.58	70.03	74.00	-3.97 peak



Test Mode: 00; Polarity: Horizontal; Modulation:802.11g; Bandwidth:20MHz; Channel:High




Site : chamber
Condition: 3m HORIZONTAL
Job No : 03306AT\03307AT
Mode : 2462 Band edge
: 2.4G WIFI 11G

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 q	2462.000	16.24	28.90	32.74	83.49	95.89	54.00	41.89 Average
2	2483.500	16.28	28.90	32.73	37.58	50.03	54.00	-3.97 Average
3	2483.790	16.28	28.90	32.73	37.01	49.46	54.00	-4.54 Average



Test Mode: 00; Polarity: Vertical; Modulation:802.11g; Bandwidth:20MHz; Channel:High




Site : chamber
Condition: 3m VERTICAL
Job No : 03306AT\03307AT
Mode : 2462 Band edge
: 2.4G WIFI 11G

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 p	2462.000	16.24	28.90	32.74	90.95	103.35	74.00	29.35 Peak
2	2483.500	16.28	28.90	32.73	55.94	68.39	74.00	-5.61 Peak
3	2483.890	16.28	28.90	32.73	53.93	66.38	74.00	-7.62 Peak



Test Mode: 00; Polarity: Vertical; Modulation:802.11g; Bandwidth:20MHz; Channel:High




Site : chamber
Condition: 3m VERTICAL
Job No : 03306AT\03307AT
Mode : 2462 Band edge
: 2.4G WIFI 11G

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 q	2462.000	16.24	28.90	32.74	81.13	93.53	54.00	39.53 Average
2	2483.500	16.28	28.90	32.73	34.75	47.20	54.00	-6.80 Average
3	2483.790	16.28	28.90	32.73	34.47	46.92	54.00	-7.08 Average



Test Mode: 00; Polarity: Horizontal; Modulation:802.11n; Bandwidth:20MHz; Channel:Low




Site : chamber
Condition: 3m HORIZONTAL
Job No : 03306AT\03307AT
Mode : 2412 Band edge
: 2.4G WIFI 11N20

	Cable	Ant	Preamp	Read		Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
2389.726	16.13	29.10	32.78	55.42	67.87	74.00	-6.13	peak
2390.000	16.13	29.10	32.78	54.23	66.68	74.00	-7.32	peak
2412.000	16.17	29.05	32.77	92.90	105.35	74.00	31.35	peak



Test Mode: 00; Polarity: Horizontal; Modulation:802.11n; Bandwidth:20MHz; Channel:Low




Site : chamber
Condition: 3m HORIZONTAL
Job No : 03306AT\03307AT
Mode : 2412 Band edge
: 2.4G WIFI 11N20

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2389.847	16.13	29.10	32.78	36.94	49.39	54.00	-4.61	Average
2	2390.000	16.13	29.10	32.78	36.67	49.12	54.00	-4.88	Average
3 q	2412.000	16.17	29.05	32.77	83.41	95.86	54.00	41.86	Average



Test Mode: 00; Polarity: Vertical; Modulation:802.11n; Bandwidth:20MHz; Channel:Low




Site : chamber
 Condition: 3m VERTICAL
 Job No : 03306AT\03307AT
 Mode : 2412 Band edge
 : 2.4G WIFI 11N20

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2389.847	16.13	29.10	32.78	49.88	62.33	74.00	-11.67	Peak
2	2390.000	16.13	29.10	32.78	49.28	61.73	74.00	-12.27	Peak
3 p	2412.000	16.17	29.05	32.77	89.84	102.29	74.00	28.29	Peak



Test Mode: 00; Polarity: Vertical; Modulation:802.11n; Bandwidth:20MHz; Channel:Low




Site : chamber
Condition: 3m VERTICAL
Job No : 03306AT\03307AT
Mode : 2412 Band edge
: 2.4G WIFI 11N20

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2389.968	16.13	29.10	32.78	33.37	45.82	54.00	-8.18	Average
2	2390.000	16.13	29.10	32.78	33.37	45.82	54.00	-8.18	Average
3 q	2412.000	16.17	29.05	32.77	80.41	92.86	54.00	38.86	Average



Test Mode: 00; Polarity: Horizontal; Modulation:802.11n; Bandwidth:20MHz; Channel:High




Site : chamber
Condition: 3m HORIZONTAL
Job No : 03306AT\03307AT
Mode : 2462 Band edge
: 2.4G WIFI 11N20

		Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 p 2462.000	16.24	28.90	32.74	92.34	104.74	74.00	30.74	peak
2 2483.500	16.28	28.90	32.73	56.18	68.63	74.00	-5.37	peak
3 2484.091	16.28	28.90	32.73	56.60	69.05	74.00	-4.95	peak



Test Mode: 00; Polarity: Horizontal; Modulation:802.11n; Bandwidth:20MHz; Channel:High




Site : chamber
Condition: 3m HORIZONTAL
Job No : 03306AT\03307AT
Mode : 2462 Band edge
: 2.4G WIFI 11N20

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 q	2462.000	16.24	28.90	32.74	82.89	95.29	54.00	41.29 Average
2	2483.500	16.28	28.90	32.73	37.30	49.75	54.00	-4.25 Average
3	2483.790	16.28	28.90	32.73	37.17	49.62	54.00	-4.38 Average



Test Mode: 00; Polarity: Vertical; Modulation:802.11n; Bandwidth:20MHz; Channel:High




Site : chamber
Condition: 3m VERTICAL
Job No : 03306AT\03307AT
Mode : 2462 Band edge
: 2.4G WIFI 11N20

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 p	2462.000	16.24	28.90	32.74	89.90	102.30	74.00	28.30 Peak
2	2483.500	16.28	28.90	32.73	53.46	65.91	74.00	-8.09 Peak
3	2484.041	16.28	28.90	32.73	53.26	65.71	74.00	-8.29 Peak



Test Mode: 00; Polarity: Vertical; Modulation:802.11n; Bandwidth:20MHz; Channel:High



Site : chamber
Condition: 3m VERTICAL
Job No : 03306AT\03307AT
Mode : 2462 Band edge
: 2.4G WIFI 11N20

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 q	2462.000	16.24	28.90	32.74	80.49	92.89	54.00	38.89 Average
2	2483.500	16.28	28.90	32.73	35.15	47.60	54.00	-6.40 Average
3	2483.840	16.28	28.90	32.73	34.43	46.88	54.00	-7.12 Average



7.2 Radiated Spurious Emissions Below 1GHz

Test Requirement 47 CFR Part 15, Subpart C 15.205 & 15.209

Test Method: ANSI C63.10 (2020) Section 6.4,6.5

Measurement Distance: 3m

Limit:

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
960-1000	500	3

7.2.1 E.U.T. Operation

Operating Environment:

Temperature: 23.4 °C


Humidity: 42.5 % RH

Atmospheric Pressure: 1020 mbar

7.2.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	00	TX mode_Keep the EUT in continuously transmitting mode with all modulation types. Only the data of worst case is recorded in the report.

7.2.3 Test Setup Diagram



7.2.4 Measurement Procedure and Data


- a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using quasi-peak method as specified and then reported in a data sheet.
- g. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- h. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- i. Repeat above procedures until all frequencies measured was complete.

Remark:

1. Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor
2. Scan from 9kHz to 30MHz, the disturbance below 30MHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.



Test Mode: 00; Polarity: Horizontal




Site : chamber
Condition: 3m HORIZONTAL
Job No. : 03306AT/03307AT
Test Mode: 00

	Ant	Cable	Preamp	Read		Limit	Over	
	Freq	Factor	Loss	Factor	Level	Level	Line	Limit Remark
	MHz	dB/m	dB	dB	dBuV	dBuV/m	dBuV/m	dB
1	30.317	21.05	0.74	27.65	24.53	18.67	40.00	-21.33 QP
2	66.266	10.90	0.96	27.62	29.75	13.99	40.00	-26.01 QP
3	152.664	13.34	1.51	27.72	27.58	14.71	43.50	-28.79 QP
4	390.723	20.75	2.46	27.73	24.97	20.45	46.00	-25.55 QP
5	691.987	25.74	3.39	27.85	26.90	28.18	46.00	-17.82 QP
6 q	942.131	28.19	4.06	26.72	25.23	30.76	46.00	-15.24 QP



Test Mode: 00; Polarity: Vertical



Site : chamber

Condition: 3m VERTICAL

Job No. : 03306AT/03307AT

Test Mode: 00

	Ant	Cable	Preamp	Read		Limit	Over	
Freq	Factor	Loss	Factor	Level	Level	Line	Limit	Remark
MHz	dB/m	dB	dB	dBuV	dBuV/m	dBuV/m	dB	
1	30.211	21.10	0.74	27.65	24.93	19.12	40.00	-20.88 QP
2	52.025	12.46	0.90	27.63	25.28	11.01	40.00	-28.99 QP
3	104.170	12.22	1.25	27.61	36.27	22.13	43.50	-21.37 QP
4	393.472	20.72	2.47	27.73	25.70	21.16	46.00	-24.84 QP
5	672.845	25.64	3.33	27.90	26.04	27.11	46.00	-18.89 QP
6 q	760.704	26.47	3.58	27.69	30.95	33.31	46.00	-12.69 QP



7.3 Radiated Spurious Emissions Above 1GHz

Test Requirement 47 CFR Part 15, Subpart C 15.205 & 15.209

Test Method: ANSI C63.10 (2020) Section 6.6

Measurement Distance: 3m

Limit:

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
Above 1000	500	3

7.3.1 E.U.T. Operation

Operating Environment:

Temperature: 23.5 °C


Humidity: 56.3 % RH

Atmospheric Pressure: 1020 mbar

7.3.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	00	TX mode_Keep the EUT in continuously transmitting mode with all modulation types. Only the data of worst case is recorded in the report.

7.3.3 Test Setup Diagram



7.3.4 Measurement Procedure and Data


- a. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak or average method as specified and then reported in a data sheet.
- g. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- h. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- i. Repeat above procedures until all frequencies measured was complete.

Remark:

1. Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor
2. Scan from 1GHz to 25GHz, the disturbance above 18GHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.
3. As shown in this section, for frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 3MHz for Peak detection (PK) and Average detection (AV) at frequency above 1GHz.
- 5:For fundamental and harmonic signal measurement, the resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is $\geq 1/T$ (Duty cycle $\leq 98\%$) or 10Hz (Duty cycle $\geq 98\%$) for Average detection (AV) at frequency above 1GHz.



Test Mode: 00; Polarity: Horizontal; Modulation:802.11b; Bandwidth:20MHz; Channel:Low




Site : chamber
Condition: 3m HORIZONTAL
Job No : 03306AT\03307AT
Mode : 2412 TX RSE
: 2.4G WIFI 11B

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	4145.664	6.98	33.73	54.28	55.23	41.66	74.00	-32.34	peak
2	4824.000	7.43	34.40	54.22	65.11	52.72	74.00	-21.28	peak
3	5949.811	8.86	34.70	53.15	53.49	43.90	74.00	-30.10	Peak
4	7236.000	8.49	35.70	53.18	51.85	42.86	74.00	-31.14	peak
5	9648.000	10.72	37.50	53.34	54.33	49.21	74.00	-24.79	peak
6	17793.090	11.38	43.89	52.50	49.44	52.21	74.00	-21.79	peak



Test Mode: 00; Polarity: Horizontal; Modulation:802.11b; Bandwidth:20MHz; Channel:Low




Site : chamber
Condition: 3m HORIZONTAL
Job No : 03306AT\03307AT
Mode : 2412 TX RSE
: 2.4G WIFI 11B

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	4417.841	7.13	34.59	54.26	43.88	31.34	54.00	-22.66	Average
2	4824.000	7.43	34.40	54.22	60.10	47.71	54.00	-6.29	Average
3	6071.417	8.92	35.04	53.11	42.23	33.08	54.00	-20.92	Average
4	7236.000	8.49	35.70	53.18	41.83	32.84	54.00	-21.16	Average
5	9648.000	10.72	37.50	53.34	41.44	36.32	54.00	-17.68	Average
6	17793.090	11.38	43.89	52.50	37.40	40.17	54.00	-13.83	Average



Test Mode: 00; Polarity: Vertical; Modulation:802.11b; Bandwidth:20MHz; Channel:Low




Site : chamber
Condition: 3m VERTICAL
Job No : 03306AT\03307AT
Mode : 2412 TX RSE
: 2.4G WIFI 11B

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	4291.977	7.06	33.97	54.27	54.54	41.30	74.00	-32.70	peak
2 p	4824.000	7.43	34.40	54.22	65.95	53.56	74.00	-20.44	peak
3	6995.172	8.56	35.71	53.20	52.60	43.67	74.00	-30.33	Peak
4	7236.000	8.49	35.70	53.18	52.10	43.11	74.00	-30.89	peak
5	9648.000	10.72	37.50	53.34	53.03	47.91	74.00	-26.09	peak
6	17793.090	11.38	43.89	52.50	48.70	51.47	74.00	-22.53	peak



Test Mode: 00; Polarity: Vertical; Modulation:802.11b; Bandwidth:20MHz; Channel:Low




Site : chamber
 Condition: 3m VERTICAL
 Job No : 03306AT\03307AT
 Mode : 2412 TX RSE
 : 2.4G WIFI 11B

	Cable	Ant	Preamp	Read		Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	4417.841	7.13	34.59	54.26	43.72	31.18	54.00	-22.82 Average
2	q 4824.000	7.43	34.40	54.22	60.20	47.81	54.00	-6.19 Average
3	6106.616	8.92	35.07	53.11	42.32	33.20	54.00	-20.80 Average
4	7236.000	8.49	35.70	53.18	41.76	32.77	54.00	-21.23 Average
5	9648.000	10.72	37.50	53.34	41.70	36.58	54.00	-17.42 Average
6	17741.740	11.35	43.84	52.53	37.38	40.04	54.00	-13.96 Average



Test Mode: 00; Polarity: Horizontal; Modulation:802.11b; Bandwidth:20MHz; Channel:middle




Site : chamber
Condition: 3m HORIZONTAL
Job No : 03306AT\03307AT
Mode : 2437 TX RSE
: 2.4G WIFI 11B

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	4316.859	7.07	34.13	54.27	55.13	42.06	74.00	-31.94	peak
2 p	4874.000	7.47	34.60	54.21	65.19	53.05	74.00	-20.95	peak
3	6737.207	8.73	35.20	53.18	53.27	44.02	74.00	-29.98	Peak
4	7311.000	8.47	35.70	53.17	53.44	44.44	74.00	-29.56	peak
5	9748.000	10.69	37.40	53.30	52.53	47.32	74.00	-26.68	peak
6	17793.090	11.38	43.89	52.50	49.07	51.84	74.00	-22.16	peak



Test Mode: 00; Polarity: Horizontal; Modulation:802.11b; Bandwidth:20MHz; Channel:middle




Site : chamber
Condition: 3m HORIZONTAL
Job No : 03306AT\03307AT
Mode : 2437 TX RSE
: 2.4G WIFI 11B

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	4354.454	7.09	34.44	54.26	43.91	31.18	54.00	-22.82	Average
2	4874.000	7.47	34.60	54.21	60.86	48.72	54.00	-5.28	Average
3	6053.894	8.92	35.01	53.11	42.02	32.84	54.00	-21.16	Average
4	7311.000	8.47	35.70	53.17	42.20	33.20	54.00	-20.80	Average
5	9748.000	10.69	37.40	53.30	40.58	35.37	54.00	-18.63	Average
6	17844.590	11.41	43.90	52.48	37.32	40.15	54.00	-13.85	Average



Test Mode: 00; Polarity: Vertical; Modulation:802.11b; Bandwidth:20MHz; Channel:middle




Site : chamber
Condition: 3m VERTICAL
Job No : 03306AT\03307AT
Mode : 2437 TX RSE
: 2.4G WIFI 11B

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	4379.699	7.11	34.64	54.26	54.01	41.50	74.00	-32.50	peak
2 p	4874.000	7.47	34.60	54.21	67.70	55.56	74.00	-18.44	peak
3	6071.417	8.92	35.04	53.11	52.51	43.36	74.00	-30.64	Peak
4	7311.000	8.47	35.70	53.17	53.54	44.54	74.00	-29.46	peak
5	9748.000	10.69	37.40	53.30	50.69	45.48	74.00	-28.52	peak
6	17844.590	11.41	43.90	52.48	49.61	52.44	74.00	-21.56	peak



Test Mode: 00; Polarity: Vertical; Modulation:802.11b; Bandwidth:20MHz; Channel:middle




Site : chamber
Condition: 3m VERTICAL
Job No : 03306AT\03307AT
Mode : 2437 TX RSE
: 2.4G WIFI 11B

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	4392.376	7.11	34.74	54.26	43.82	31.41	54.00	-22.59	Average
2	4874.000	7.47	34.60	54.21	62.97	50.83	54.00	-3.17	Average
3	6071.417	8.92	35.04	53.11	42.25	33.10	54.00	-20.90	Average
4	7311.000	8.47	35.70	53.17	42.25	33.25	54.00	-20.75	Average
5	9748.000	10.69	37.40	53.30	40.70	35.49	54.00	-18.51	Average
6	17537.800	11.22	43.48	52.63	37.96	40.03	54.00	-13.97	Average



Test Mode: 00; Polarity: Horizontal; Modulation:802.11b; Bandwidth:20MHz; Channel:High




Site : chamber
 Condition: 3m HORIZONTAL
 Job No : 03306AT\03307AT
 Mode : 2462 TX RSE
 : 2.4G WIFI 11B

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	4430.628	7.13	34.43	54.25	54.31	41.62	74.00	-32.38	peak
2	4924.000	7.50	34.65	54.21	65.14	53.08	74.00	-20.92	peak
3	6322.136	8.90	34.96	53.13	53.22	43.95	74.00	-30.05	Peak
4	7386.000	8.44	35.77	53.16	52.69	43.74	74.00	-30.26	peak
5	9848.000	10.66	37.20	53.26	50.86	45.46	74.00	-28.54	peak
6	17844.590	11.41	43.90	52.48	49.51	52.34	74.00	-21.66	peak



Test Mode: 00; Polarity: Horizontal; Modulation:802.11b; Bandwidth:20MHz; Channel:High




Site : chamber
Condition: 3m HORIZONTAL
Job No : 03306AT\03307AT
Mode : 2462 TX RSE
: 2.4G WIFI 11B

		Cable	Ant	Preamp	Read		Limit	Over	
Freq		Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	4379.699	7.11	34.64	54.26	43.95	31.44	54.00	-22.56	Average
2	4924.000	7.50	34.65	54.21	59.14	47.08	54.00	-6.92	Average
3	6071.417	8.92	35.04	53.11	41.99	32.84	54.00	-21.16	Average
4	7386.000	8.44	35.77	53.16	42.89	33.94	54.00	-20.06	Average
5	9848.000	10.66	37.20	53.26	41.20	35.80	54.00	-18.20	Average
6	17844.590	11.41	43.90	52.48	37.15	39.98	54.00	-14.02	Average



Test Mode: 00; Polarity: Vertical; Modulation:802.11b; Bandwidth:20MHz; Channel:High




Site : chamber
Condition: 3m VERTICAL
Job No : 03306AT\03307AT
Mode : 2462 TX RSE
: 2.4G WIFI 11B

		Cable	Ant	Preamp	Read	Limit	Over	
Freq		Loss	Factor	Factor	Level	Line	Limit	Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	4379.699	7.11	34.64	54.26	54.18	41.67	74.00	-32.33 peak
2	4924.000	7.50	34.65	54.21	64.68	52.62	74.00	-21.38 peak
3	6526.373	8.86	35.55	53.15	52.66	43.92	74.00	-30.08 Peak
4	7386.000	8.44	35.77	53.16	51.98	43.03	74.00	-30.97 peak
5	9848.000	10.66	37.20	53.26	51.80	46.40	74.00	-27.60 peak
6	17793.090	11.38	43.89	52.50	48.98	51.75	74.00	-22.25 peak



Test Mode: 00; Polarity: Vertical; Modulation:802.11b; Bandwidth:20MHz; Channel:High




Site : chamber
 Condition: 3m VERTICAL
 Job No : 03306AT\03307AT
 Mode : 2462 TX RSE
 : 2.4G WIFI 11B

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	4329.354	7.08	34.23	54.26	44.22	31.27	54.00	-22.73	Average
2	4924.000	7.50	34.65	54.21	60.19	48.13	54.00	-5.87	Average
3	6053.894	8.92	35.01	53.11	42.03	32.85	54.00	-21.15	Average
4	7386.000	8.44	35.77	53.16	42.96	34.01	54.00	-19.99	Average
5	9848.000	10.66	37.20	53.26	41.09	35.69	54.00	-18.31	Average
6	18000.000	11.50	44.30	52.40	36.53	39.93	54.00	-14.07	Average



Test Mode: 00; Polarity: Horizontal; Modulation:802.11g; Bandwidth:20MHz; Channel:Low




Site : chamber
Condition: 3m HORIZONTAL
Job No : 03306AT\03307AT
Mode : 2412 TX RSE
: 2.4G WIFI 11G

	Cable	Ant	Preamp	Read		Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	4341.886	7.09	34.34	54.26	54.52	41.69	74.00	-32.31 peak
2	4824.000	7.43	34.40	54.22	65.16	52.77	74.00	-21.23 peak
3	6106.616	8.92	35.07	53.11	52.82	43.70	74.00	-30.30 Peak
4	7236.000	8.49	35.70	53.18	53.05	44.06	74.00	-29.94 peak
5	9648.000	10.72	37.50	53.34	52.14	47.02	74.00	-26.98 peak
6	17741.740	11.35	43.84	52.53	48.59	51.25	74.00	-22.75 peak



Test Mode: 00; Polarity: Horizontal; Modulation:802.11g; Bandwidth:20MHz; Channel:Low




Site : chamber
Condition: 3m HORIZONTAL
Job No : 03306AT\03307AT
Mode : 2412 TX RSE
: 2.4G WIFI 11G

	Cable	Ant	Preamp	Read		Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	4417.841	7.13	34.59	54.26	43.68	31.14	54.00	-22.86 Average
2	q 4824.000	7.43	34.40	54.22	60.46	48.07	54.00	-5.93 Average
3	6053.894	8.92	35.01	53.11	42.10	32.92	54.00	-21.08 Average
4	7236.000	8.49	35.70	53.18	41.96	32.97	54.00	-21.03 Average
5	9648.000	10.72	37.50	53.34	41.71	36.59	54.00	-17.41 Average
6	17844.590	11.41	43.90	52.48	37.21	40.04	54.00	-13.96 Average



Test Mode: 00; Polarity: Vertical; Modulation:802.11g; Bandwidth:20MHz; Channel:Low




Site : chamber
Condition: 3m VERTICAL
Job No : 03306AT\03307AT
Mode : 2412 TX RSE
: 2.4G WIFI 11G

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	4354.454	7.09	34.44	54.26	54.12	41.39	74.00	-32.61	peak
2	4824.000	7.43	34.40	54.22	65.07	52.68	74.00	-21.32	peak
3	6071.417	8.92	35.04	53.11	52.79	43.64	74.00	-30.36	Peak
4	7236.000	8.49	35.70	53.18	52.59	43.60	74.00	-30.40	peak
5	9648.000	10.72	37.50	53.34	51.38	46.26	74.00	-27.74	peak
6	17741.740	11.35	43.84	52.53	49.12	51.78	74.00	-22.22	peak



Test Mode: 00; Polarity: Vertical; Modulation:802.11g; Bandwidth:20MHz; Channel:Low




Site : chamber
Condition: 3m VERTICAL
Job No : 03306AT\03307AT
Mode : 2412 TX RSE
: 2.4G WIFI 11G

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	4379.699	7.11	34.64	54.26	43.71	31.20	54.00	-22.80	Average
2	4824.000	7.43	34.40	54.22	60.26	47.87	54.00	-6.13	Average
3	6488.754	8.88	35.58	53.15	41.78	33.09	54.00	-20.91	Average
4	7236.000	8.49	35.70	53.18	42.04	33.05	54.00	-20.95	Average
5	9648.000	10.72	37.50	53.34	41.65	36.53	54.00	-17.47	Average
6	17537.800	11.22	43.48	52.63	38.11	40.18	54.00	-13.82	Average



Test Mode: 00; Polarity: Horizontal; Modulation:802.11g; Bandwidth:20MHz; Channel:middle




Site : chamber
Condition: 3m HORIZONTAL
Job No : 03306AT\03307AT
Mode : 2437 TX RSE
: 2.4G WIFI 11G

		Cable	Ant	Preamp	Read		Limit	Over	
Freq		Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	4329.354	7.08	34.23	54.26	54.58	41.63	74.00	-32.37	peak
2	4874.000	7.47	34.60	54.21	64.48	52.34	74.00	-21.66	peak
3	6106.616	8.92	35.07	53.11	52.69	43.57	74.00	-30.43	Peak
4	7311.000	8.47	35.70	53.17	53.39	44.39	74.00	-29.61	peak
5	9748.000	10.69	37.40	53.30	50.82	45.61	74.00	-28.39	peak
6	17793.090	11.38	43.89	52.50	49.20	51.97	74.00	-22.03	peak



Test Mode: 00; Polarity: Horizontal; Modulation:802.11g; Bandwidth:20MHz; Channel:middle




Site : chamber
 Condition: 3m HORIZONTAL
 Job No : 03306AT\03307AT
 Mode : 2437 TX RSE
 : 2.4G WIFI 11G

		Cable	Ant	Preamp	Read	Limit	Over	
Freq		Loss	Factor	Factor	Level	Line	Limit	Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	4392.376	7.11	34.74	54.26	43.84	31.43	54.00	-22.57 Average
2	4874.000	7.47	34.60	54.21	59.01	46.87	54.00	-7.13 Average
3	6995.172	8.56	35.71	53.20	41.91	32.98	54.00	-21.02 Average
4	7311.000	8.47	35.70	53.17	42.32	33.32	54.00	-20.68 Average
5	9748.000	10.69	37.40	53.30	40.74	35.53	54.00	-18.47 Average
6	17948.050	11.47	44.09	52.43	37.05	40.18	54.00	-13.82 Average



Test Mode: 00; Polarity: Vertical; Modulation:802.11g; Bandwidth:20MHz; Channel:middle




Site : chamber
Condition: 3m VERTICAL
Job No : 03306AT\03307AT
Mode : 2437 TX RSE
: 2.4G WIFI 11G

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	4329.354	7.08	34.23	54.26	54.98	42.03	74.00	-31.97	peak
2 p	4874.000	7.47	34.60	54.21	64.94	52.80	74.00	-21.20	peak
3	6303.890	8.90	34.99	53.13	53.73	44.49	74.00	-29.51	Peak
4	7311.000	8.47	35.70	53.17	52.65	43.65	74.00	-30.35	peak
5	9748.000	10.69	37.40	53.30	51.97	46.76	74.00	-27.24	peak
6	17741.740	11.35	43.84	52.53	48.89	51.55	74.00	-22.45	peak



Test Mode: 00; Polarity: Vertical; Modulation:802.11g; Bandwidth:20MHz; Channel:middle




Site : chamber
Condition: 3m VERTICAL
Job No : 03306AT\03307AT
Mode : 2437 TX RSE
: 2.4G WIFI 11G

	Cable	Ant	Preamp	Read		Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	4379.699	7.11	34.64	54.26	44.23	31.72	54.00	-22.28 Average
2	q 4874.000	7.47	34.60	54.21	60.72	48.58	54.00	-5.42 Average
3	6088.991	8.92	35.08	53.11	42.09	32.98	54.00	-21.02 Average
4	7311.000	8.47	35.70	53.17	42.12	33.12	54.00	-20.88 Average
5	9748.000	10.69	37.40	53.30	40.75	35.54	54.00	-18.46 Average
6	17948.050	11.47	44.09	52.43	37.13	40.26	54.00	-13.74 Average



Test Mode: 00; Polarity: Horizontal; Modulation:802.11g; Bandwidth:20MHz; Channel:High




Site : chamber
 Condition: 3m HORIZONTAL
 Job No : 03306AT\03307AT
 Mode : 2462 TX RSE
 : 2.4G WIFI 11G

	Cable	Ant	Preamp	Read		Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	4341.886	7.09	34.34	54.26	54.43	41.60	74.00	-32.40 peak
2	4924.000	7.50	34.65	54.21	65.00	52.94	74.00	-21.06 peak
3	5932.638	8.83	34.67	53.17	54.43	44.76	74.00	-29.24 Peak
4	7386.000	8.44	35.77	53.16	52.69	43.74	74.00	-30.26 peak
5	9848.000	10.66	37.20	53.26	50.65	45.25	74.00	-28.75 peak
6	17844.590	11.41	43.90	52.48	48.98	51.81	74.00	-22.19 peak



Test Mode: 00; Polarity: Horizontal; Modulation:802.11g; Bandwidth:20MHz; Channel:High




Site : chamber
Condition: 3m HORIZONTAL
Job No : 03306AT\03307AT
Mode : 2462 TX RSE
: 2.4G WIFI 11G

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	4354.454	7.09	34.44	54.26	44.03	31.30	54.00	-22.70	Average
2	4924.000	7.50	34.65	54.21	60.18	48.12	54.00	-5.88	Average
3	6071.417	8.92	35.04	53.11	42.29	33.14	54.00	-20.86	Average
4	7386.000	8.44	35.77	53.16	42.92	33.97	54.00	-20.03	Average
5	9848.000	10.66	37.20	53.26	41.16	35.76	54.00	-18.24	Average
6	17948.050	11.47	44.09	52.43	36.93	40.06	54.00	-13.94	Average



Test Mode: 00; Polarity: Vertical; Modulation:802.11g; Bandwidth:20MHz; Channel:High




Site : chamber
Condition: 3m VERTICAL
Job No : 03306AT\03307AT
Mode : 2462 TX RSE
: 2.4G WIFI 11G

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	4379.699	7.11	34.64	54.26	55.41	42.90	74.00	-31.10	peak
2	4924.000	7.50	34.65	54.21	64.12	52.06	74.00	-21.94	peak
3	5932.638	8.83	34.67	53.17	53.30	43.63	74.00	-30.37	Peak
4	7386.000	8.44	35.77	53.16	53.35	44.40	74.00	-29.60	peak
5	9848.000	10.66	37.20	53.26	50.83	45.43	74.00	-28.57	peak
6	p17793.090	11.38	43.89	52.50	49.43	52.20	74.00	-21.80	peak



Test Mode: 00; Polarity: Vertical; Modulation:802.11g; Bandwidth:20MHz; Channel:High




Site : chamber
Condition: 3m VERTICAL
Job No : 03306AT\03307AT
Mode : 2462 TX RSE
: 2.4G WIFI 11G

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	4367.058	7.10	34.54	54.26	44.09	31.47	54.00	-22.53	Average
2	4924.000	7.50	34.65	54.21	60.39	48.33	54.00	-5.67	Average
3	6053.894	8.92	35.01	53.11	42.17	32.99	54.00	-21.01	Average
4	7386.000	8.44	35.77	53.16	43.11	34.16	54.00	-19.84	Average
5	9848.000	10.66	37.20	53.26	41.07	35.67	54.00	-18.33	Average
6	17948.050	11.47	44.09	52.43	36.82	39.95	54.00	-14.05	Average



Test Mode: 00; Polarity: Horizontal; Modulation:802.11n; Bandwidth:20MHz; Channel:Low




Site : chamber
Condition: 3m HORIZONTAL
Job No : 03306AT\03307AT
Mode : 2412 TX RSE
: 2.4G WIFI 11N20

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	4379.699	7.11	34.64	54.26	54.58	42.07	74.00	-31.93	peak
2 p	4824.000	7.43	34.40	54.22	65.02	52.63	74.00	-21.37	peak
3	5949.811	8.86	34.70	53.15	53.33	43.74	74.00	-30.26	Peak
4	7236.000	8.49	35.70	53.18	52.97	43.98	74.00	-30.02	peak
5	9648.000	10.72	37.50	53.34	50.95	45.83	74.00	-28.17	peak
6	18000.000	11.50	44.30	52.40	48.99	52.39	74.00	-21.61	peak



Test Mode: 00; Polarity: Horizontal; Modulation:802.11n; Bandwidth:20MHz; Channel:Low




Site : chamber
Condition: 3m HORIZONTAL
Job No : 03306AT\03307AT
Mode : 2412 TX RSE
: 2.4G WIFI 11N20

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	4405.090	7.12	34.74	54.26	43.69	31.29	54.00	-22.71	Average
2	4824.000	7.43	34.40	54.22	60.01	47.62	54.00	-6.38	Average
3	6106.616	8.92	35.07	53.11	42.29	33.17	54.00	-20.83	Average
4	7236.000	8.49	35.70	53.18	42.06	33.07	54.00	-20.93	Average
5	9648.000	10.72	37.50	53.34	41.40	36.28	54.00	-17.72	Average
6	17896.250	11.44	43.90	52.45	37.08	39.97	54.00	-14.03	Average



Test Mode: 00; Polarity: Vertical; Modulation:802.11n; Bandwidth:20MHz; Channel:Low




Site : chamber
 Condition: 3m VERTICAL
 Job No : 03306AT\03307AT
 Mode : 2412 TX RSE
 : 2.4G WIFI 11N20

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	4367.058	7.10	34.54	54.26	54.59	41.97	74.00	-32.03	peak
2	4824.000	7.43	34.40	54.22	65.12	52.73	74.00	-21.27	peak
3	6583.209	8.83	35.37	53.16	52.86	43.90	74.00	-30.10	Peak
4	7236.000	8.49	35.70	53.18	51.80	42.81	74.00	-31.19	peak
5	9648.000	10.72	37.50	53.34	51.33	46.21	74.00	-27.79	peak
6	p17844.590	11.41	43.90	52.48	51.01	53.84	74.00	-20.16	peak



Test Mode: 00; Polarity: Vertical; Modulation:802.11n; Bandwidth:20MHz; Channel:Low




Site : chamber
 Condition: 3m VERTICAL
 Job No : 03306AT\03307AT
 Mode : 2412 TX RSE
 : 2.4G WIFI 11N20

	Cable	Ant	Preamp	Read		Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	4417.841	7.13	34.59	54.26	43.73	31.19	54.00	-22.81 Average
2	q 4824.000	7.43	34.40	54.22	60.09	47.70	54.00	-6.30 Average
3	6053.894	8.92	35.01	53.11	42.23	33.05	54.00	-20.95 Average
4	7236.000	8.49	35.70	53.18	41.90	32.91	54.00	-21.09 Average
5	9648.000	10.72	37.50	53.34	41.54	36.42	54.00	-17.58 Average
6	17948.050	11.47	44.09	52.43	37.11	40.24	54.00	-13.76 Average



Test Mode: 00; Polarity: Horizontal; Modulation:802.11n; Bandwidth:20MHz; Channel:middle




Site : chamber
Condition: 3m HORIZONTAL
Job No : 03306AT\03307AT
Mode : 2437 TX RSE
: 2.4G WIFI 11N20

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	4341.886	7.09	34.34	54.26	54.54	41.71	74.00	-32.29	peak
2 p	4874.000	7.47	34.60	54.21	64.95	52.81	74.00	-21.19	peak
3	6088.991	8.92	35.08	53.11	52.51	43.40	74.00	-30.60	Peak
4	7311.000	8.47	35.70	53.17	52.42	43.42	74.00	-30.58	peak
5	9748.000	10.69	37.40	53.30	51.08	45.87	74.00	-28.13	peak
6	17896.250	11.44	43.90	52.45	48.44	51.33	74.00	-22.67	peak



Test Mode: 00; Polarity: Horizontal; Modulation:802.11n; Bandwidth:20MHz; Channel:middle




Site : chamber
Condition: 3m HORIZONTAL
Job No : 03306AT\03307AT
Mode : 2437 TX RSE
: 2.4G WIFI 11N20

	Cable	Ant	Preamp	Read		Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	4430.628	7.13	34.43	54.25	43.94	31.25	54.00	-22.75 Average
2	q 4874.000	7.47	34.60	54.21	60.68	48.54	54.00	-5.46 Average
3	6088.991	8.92	35.08	53.11	42.08	32.97	54.00	-21.03 Average
4	7311.000	8.47	35.70	53.17	42.44	33.44	54.00	-20.56 Average
5	9748.000	10.69	37.40	53.30	40.41	35.20	54.00	-18.80 Average
6	17948.050	11.47	44.09	52.43	37.09	40.22	54.00	-13.78 Average



Test Mode: 00; Polarity: Vertical; Modulation:802.11n; Bandwidth:20MHz; Channel:middle




Site : chamber
Condition: 3m VERTICAL
Job No : 03306AT\03307AT
Mode : 2437 TX RSE
: 2.4G WIFI 11N20

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	4367.058	7.10	34.54	54.26	55.25	42.63	74.00	-31.37	peak
2	4874.000	7.47	34.60	54.21	64.13	51.99	74.00	-22.01	peak
3	6995.172	8.56	35.71	53.20	52.87	43.94	74.00	-30.06	Peak
4	7311.000	8.47	35.70	53.17	53.19	44.19	74.00	-29.81	peak
5	9748.000	10.69	37.40	53.30	51.82	46.61	74.00	-27.39	peak
6	p17793.090	11.38	43.89	52.50	49.29	52.06	74.00	-21.94	peak



Test Mode: 00; Polarity: Vertical; Modulation:802.11n; Bandwidth:20MHz; Channel:middle




Site : chamber
Condition: 3m VERTICAL
Job No : 03306AT\03307AT
Mode : 2437 TX RSE
: 2.4G WIFI 11N20

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	4379.699	7.11	34.64	54.26	44.22	31.71	54.00	-22.29	Average
2	4874.000	7.47	34.60	54.21	59.76	47.62	54.00	-6.38	Average
3	6071.417	8.92	35.04	53.11	42.13	32.98	54.00	-21.02	Average
4	7311.000	8.47	35.70	53.17	42.22	33.22	54.00	-20.78	Average
5	9748.000	10.69	37.40	53.30	40.31	35.10	54.00	-18.90	Average
6	17487.180	11.19	43.40	52.65	38.07	40.01	54.00	-13.99	Average



Test Mode: 00; Polarity: Horizontal; Modulation:802.11n; Bandwidth:20MHz; Channel:High




Site : chamber
Condition: 3m HORIZONTAL
Job No : 03306AT\03307AT
Mode : 2462 TX RSE
: 2.4G WIFI 11N20

		Cable	Ant	Preamp	Read	Limit	Over	
Freq		Loss	Factor	Factor	Level	Line	Limit	Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	4354.454	7.09	34.44	54.26	53.73	41.00	74.00	-33.00 peak
2	4924.000	7.50	34.65	54.21	64.40	52.34	74.00	-21.66 peak
3	6036.421	8.93	34.97	53.10	52.78	43.58	74.00	-30.42 Peak
4	7386.000	8.44	35.77	53.16	54.24	45.29	74.00	-28.71 peak
5	9848.000	10.66	37.20	53.26	52.00	46.60	74.00	-27.40 peak
6	17793.090	11.38	43.89	52.50	49.26	52.03	74.00	-21.97 peak



Test Mode: 00; Polarity: Horizontal; Modulation:802.11n; Bandwidth:20MHz; Channel:High




Site : chamber
Condition: 3m HORIZONTAL
Job No : 03306AT\03307AT
Mode : 2462 TX RSE
: 2.4G WIFI 11N20

		Cable	Ant	Preamp	Read	Limit	Over	
Freq		Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	4367.058	7.10	34.54	54.26	43.79	31.17	54.00	-22.83 Average
2	4924.000	7.50	34.65	54.21	59.12	47.06	54.00	-6.94 Average
3	6545.263	8.85	35.51	53.16	41.73	32.93	54.00	-21.07 Average
4	7386.000	8.44	35.77	53.16	42.85	33.90	54.00	-20.10 Average
5	9848.000	10.66	37.20	53.26	41.10	35.70	54.00	-18.30 Average
6	18000.000	11.50	44.30	52.40	36.80	40.20	54.00	-13.80 Average



Test Mode: 00; Polarity: Vertical; Modulation:802.11n; Bandwidth:20MHz; Channel:High




Site : chamber
Condition: 3m VERTICAL
Job No : 03306AT\03307AT
Mode : 2462 TX RSE
: 2.4G WIFI 11N20

	Cable	Ant	Preamp	Read		Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	4354.454	7.09	34.44	54.26	54.42	41.69	74.00	-32.31 peak
2	4924.000	7.50	34.65	54.21	64.87	52.81	74.00	-21.19 peak
3	6001.626	8.93	34.90	53.10	53.54	44.27	74.00	-29.73 Peak
4	7386.000	8.44	35.77	53.16	53.10	44.15	74.00	-29.85 peak
5	9848.000	10.66	37.20	53.26	51.18	45.78	74.00	-28.22 peak
6	18000.000	11.50	44.30	52.40	48.28	51.68	74.00	-22.32 peak



Test Mode: 00; Polarity: Vertical; Modulation:802.11n; Bandwidth:20MHz; Channel:High



Site : chamber
 Condition: 3m VERTICAL
 Job No : 03306AT\03307AT
 Mode : 2462 TX RSE
 : 2.4G WIFI 11N20

	Cable	Ant	Preamp	Read		Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	7.09	34.34	54.26	44.21	31.38	54.00	-22.62	Average
2	7.50	34.65	54.21	59.02	46.96	54.00	-7.04	Average
3	8.92	35.01	53.11	41.99	32.81	54.00	-21.19	Average
4	8.44	35.77	53.16	42.79	33.84	54.00	-20.16	Average
5	10.66	37.20	53.26	41.34	35.94	54.00	-18.06	Average
6	11.41	43.90	52.48	37.21	40.04	54.00	-13.96	Average



7.4 Conducted Peak Output Power

Test Requirement 47 CFR Part 15, Subpart C 15.247(b)(3)

Test Method: ANSI C63.10 (2020) Section 11.9.2

Limit:

Frequency range(MHz)	Output power of the intentional radiator(watt)
902-928	1 for ≥ 50 hopping channels
	0.25 for $25 \leq$ hopping channels < 50
	1 for digital modulation
2400-2483.5	1 for ≥ 75 non-overlapping hopping channels
	0.125 for all other frequency hopping systems
	1 for digital modulation
5725-5850	1 for frequency hopping systems and digital modulation

7.4.1 E.U.T. Operation


Operating Environment:

Temperature: 23.5 °C

Humidity: 56.3 % RH

Atmospheric Pressure: 1020 mbar

7.4.2 Test Setup Diagram



7.4.3 Measurement Procedure and Data

Note: Since the verify power the same operating range bandwidth and smaller power can be covered by the higher power.

Please Refer to Appendix for Details



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch Testing & Calibration Laboratory

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

7.5 Minimum 6dB Bandwidth

Test Requirement 47 CFR Part 15, Subpart C 15.247a(2)

Test Method: ANSI C63.10 (2020) Section 11.8.1

Limit:

≥500 kHz

7.5.1 E.U.T. Operation


Operating Environment:

Temperature: 23.5 °C

Humidity: 56.3 % RH

Atmospheric Pressure: 1020 mbar

7.5.2 Test Setup Diagram



7.5.3 Measurement Procedure and Data

Please Refer to Appendix for Details



7.6 Power Spectrum Density

Test Requirement 47 CFR Part 15, Subpart C 15.247(e)

Test Method: ANSI C63.10 (2020) Section 11.10.2

Limit:

≤8dBm in any 3 kHz band during any time interval of continuous transmission

7.6.1 E.U.T. Operation


Operating Environment:

Temperature: 23.5 °C

Humidity: 56.3 % RH

Atmospheric Pressure: 1020 mbar

7.6.2 Test Setup Diagram



7.6.3 Measurement Procedure and Data

Please Refer to Appendix for Details



7.7 Conducted Band Edges Measurement

Test Requirement 47 CFR Part 15, Subpart C 15.247(d)

Test Method: ANSI C63.10 (2020) Section 6.10.4

Limit:

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

7.7.1 E.U.T. Operation


Operating Environment:

Temperature: 23.5 °C

Humidity: 56.3 % RH

Atmospheric Pressure: 1020 mbar

7.7.2 Test Setup Diagram



7.7.3 Measurement Procedure and Data

Please Refer to Appendix for Details

7.8 Conducted Spurious Emissions

Test Requirement 47 CFR Part 15, Subpart C 15.247(d)

Test Method: ANSI C63.10 (2020) Section 11.11

Limit:

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

7.8.1 E.U.T. Operation


Operating Environment:

Temperature: 23.5 °C

Humidity: 56.3 % RH

Atmospheric Pressure: 1020 mbar

7.8.2 Test Setup Diagram



7.8.3 Measurement Procedure and Data

Please Refer to Appendix for Details



8 Test Setup Photo

Refer to Setup Photo for SZCR2507003306AT

9 EUT Constructional Details (EUT Photos)

Refer to External and Internal Photos for SZCR2507003306AT



10 Appendix

1. Duty Cycle

1.1 Test Result


1.1.1 Ant1

Ant1							
Mode	TX Type	Frequency (MHz)	T_on (ms)	Period (ms)	Duty Cycle (%)	Duty Cycle Correction Factor (dB)	Max. DC Variation (%)
802.11b	SISO	2412	32.953	32.973	99.94	0.00	0.01
		2437	32.950	32.970	99.94	0.00	0.00
		2462	32.954	32.970	99.95	0.00	0.00
802.11g	SISO	2412	5.484	5.509	99.55	0.02	0.00
		2437	5.484	5.508	99.56	0.02	0.03
		2462	5.484	5.508	99.56	0.02	0.00
802.11n (HT20)	SISO	2412	5.079	5.104	99.51	0.02	0.00
		2437	5.079	5.104	99.51	0.02	0.04
		2462	5.079	5.104	99.51	0.02	0.00




1.2 Test Graph


1.2.1 Ant1




802.11b_HCH_2462MHz_Ant1 (SISO)_NTNV




802.11g_LCH_2412MHz_Ant1 (SISO)_NTNV




802.11g_MCH_2437MHz_Ant1 (SISO)_NTNV




802.11g_HCH_2462MHz_Ant1 (SISO)_NTNV




802.11n(HT20)_LCH_2412MHz_Ant1 (SISO)_NTNV



802.11n(HT20)_MCH_2437MHz_Ant1 (SISO)_NTNV



802.11n(HT20)_HCH_2462MHz_Ant1 (SISO)_NTNV



2. Bandwidth

2.1 Test Result

2.1.1 OBW


Mode	TX Type	Frequency (MHz)	ANT	99% Occupied Bandwidth (MHz)		Verdict
				Result	Limit	
802.11b	SISO	2412	1	12.848	/	Pass
		2437	1	12.821	/	Pass
		2462	1	12.837	/	Pass
802.11g	SISO	2412	1	17.050	/	Pass
		2437	1	18.395	/	Pass
		2462	1	16.967	/	Pass
802.11n (HT20)	SISO	2412	1	17.598	/	Pass
		2437	1	17.683	/	Pass
		2462	1	17.596	/	Pass

2.1.2 6dB BW


Mode	TX Type	Frequency (MHz)	ANT	6dB Bandwidth (MHz)		Verdict
				Result	Limit	
802.11b	SISO	2412	1	8.919	≥ 0.5	Pass
		2437	1	8.838	≥ 0.5	Pass
		2462	1	8.845	≥ 0.5	Pass
802.11g	SISO	2412	1	16.280	≥ 0.5	Pass
		2437	1	16.159	≥ 0.5	Pass
		2462	1	16.263	≥ 0.5	Pass
802.11n (HT20)	SISO	2412	1	17.136	≥ 0.5	Pass
		2437	1	17.025	≥ 0.5	Pass
		2462	1	17.137	≥ 0.5	Pass

2.2 Test Graph


2.2.1 OBW




802.11b_HCH_2462MHz_Ant1 (SISO)_NTNV




802.11g_LCH_2412MHz_Ant1 (SISO)_NTNV




802.11g_MCH_2437MHz_Ant1 (SISO)_NTNV




802.11g_HCH_2462MHz_Ant1 (SISO)_NTNV




802.11n(HT20)_LCH_2412MHz_Ant1 (SISO)_NTNV



802.11n(HT20)_MCH_2437MHz_Ant1 (SISO)_NTNV



802.11n(HT20)_HCH_2462MHz_Ant1 (SISO)_NTNV




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.


Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

2.2.2 6dB BW


802.11b_LCH_2412MHz_Ant1 (SISO)_NTNV




802.11b_MCH_2437MHz_Ant1 (SISO)_NTNV




802.11b_HCH_2462MHz_Ant1 (SISO)_NTNV




802.11g_LCH_2412MHz_Ant1 (SISO)_NTNV




802.11g_MCH_2437MHz_Ant1 (SISO)_NTNV




802.11g_HCH_2462MHz_Ant1 (SISO)_NTNV




802.11n(HT20)_LCH_2412MHz_Ant1 (SISO)_NTNV



802.11n(HT20)_MCH_2437MHz_Ant1 (SISO)_NTNV



802.11n(HT20)_HCH_2462MHz_Ant1 (SISO)_NTNV



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

3. Maximum Conducted Output Power

3.1 Test Result

3.1.1 Power

Mode	TX Type	Frequency (MHz)	Maximum Average Conducted Output Power (dBm)		Verdict
			ANT1	Limit	
802.11b	SISO	2412	16.75	≤ 30	Pass
		2437	16.12	≤ 30	Pass
		2462	15.26	≤ 30	Pass
802.11g	SISO	2412	15.99	≤ 30	Pass
		2437	17.95	≤ 30	Pass
		2462	15.60	≤ 30	Pass
802.11n (HT20)	SISO	2412	15.45	≤ 30	Pass
		2437	16.85	≤ 30	Pass
		2462	14.94	≤ 30	Pass

Note1: Antenna Gain: Ant1: 2.49dBi;

4. Maximum Power Spectral Density

4.1 Test Result


4.1.1 PSD

Mode	TX Type	Frequency (MHz)	Maximum PSD (dBm/3kHz)		Verdict
			ANT1	Limit	
802.11b	SISO	2412	-14.59	≤ 8	Pass
		2437	-15.09	≤ 8	Pass
		2462	-15.88	≤ 8	Pass
802.11g	SISO	2412	-15.87	≤ 8	Pass
		2437	-14.06	≤ 8	Pass
		2462	-16.31	≤ 8	Pass
802.11n (HT20)	SISO	2412	-16.85	≤ 8	Pass
		2437	-15.37	≤ 8	Pass
		2462	-17.22	≤ 8	Pass


Note1: Antenna Gain: Ant1: 2.49dBi;

4.2 Test Graph


4.2.1 PSD



802.11b_HCH_2462MHz_Ant1 (SISO)_NTNV



802.11g_LCH_2412MHz_Ant1 (SISO)_NTNV




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com


SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch Testing & Calibration Laboratory

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

802.11g_MCH_2437MHz_Ant1 (SISO)_NTNV




802.11g_HCH_2462MHz_Ant1 (SISO)_NTNV




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com


802.11n(HT20)_LCH_2412MHz_Ant1 (SISO)_NTNV



802.11n(HT20)_MCH_2437MHz_Ant1 (SISO)_NTNV



802.11n(HT20)_HCH_2462MHz_Ant1 (SISO)_NTNV



5. Unwanted Emissions In Non-restricted Frequency Bands

5.1 Test Result

5.1.1 Ref

Mode	TX Type	Frequency (MHz)	ANT	Level of Reference (dBm)
802.11b	SISO	2412	1	8.42
		2437	1	7.41
		2462	1	6.61
802.11g	SISO	2412	1	4.77
		2437	1	7.97
		2462	1	4.10
802.11n (HT20)	SISO	2412	1	4.02
		2437	1	5.91
		2462	1	3.93

Note1: Refer to FCC Part 15.247 (d) and ANSI C63.10-2020, the channel contains the maximum PSD level was used to establish the reference level.


5.1.2 CSE

Mode	TX Type	Frequency (MHz)	ANT	Level of Reference (dBm)	Limit (dBm)	Verdict
802.11b	SISO	2412	1	8.42	-21.58	Pass
		2437	1	8.42	-21.58	Pass
		2462	1	8.42	-21.58	Pass
802.11g	SISO	2412	1	7.97	-22.03	Pass
		2437	1	7.97	-22.03	Pass
		2462	1	7.97	-22.03	Pass
802.11n (HT20)	SISO	2412	1	5.91	-24.09	Pass
		2437	1	5.91	-24.09	Pass
		2462	1	5.91	-24.09	Pass


Note1: Refer to FCC Part 15.247 (d) and ANSI C63.10-2020, the channel contains the maximum PSD level was used to establish the reference level.

5.2 Test Graph


5.2.1 Ref




802.11b_HCH_2462MHz_Ant1 (SISO)_NTNV




802.11g_LCH_2412MHz_Ant1 (SISO)_NTNV




802.11g_MCH_2437MHz_Ant1 (SISO)_NTNV




802.11g_HCH_2462MHz_Ant1 (SISO)_NTNV




802.11n(HT20)_LCH_2412MHz_Ant1 (SISO)_NTNV



802.11n(HT20)_MCH_2437MHz_Ant1 (SISO)_NTNV




802.11n(HT20)_HCH_2462MHz_Ant1 (SISO)_NTNV




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com


5.2.2 CSE




802.11b_MCH_2437MHz_Ant1 (SISO)_NTNV




802.11b_HCH_2462MHz_Ant1 (SISO)_NTNV




802.11b_HCH_2462MHz_Ant1 (SISO)_NTNV




802.11g_LCH_2412MHz_Ant1 (SISO)_NTNV




802.11g_LCH_2412MHz_Ant1 (SISO)_NTNV




802.11g_MCH_2437MHz_Ant1 (SISO)_NTNV




802.11g_HCH_2462MHz_Ant1 (SISO)_NTNV




802.11g_HCH_2462MHz_Ant1 (SISO)_NTNV




802.11n(HT20)_LCH_2412MHz_Ant1 (SISO)_NTNV




802.11n(HT20)_LCH_2412MHz_Ant1 (SISO)_NTNV




802.11n(HT20)_MCH_2437MHz_Ant1 (SISO)_NTNV



802.11n(HT20)_HCH_2462MHz_Ant1 (SISO)_NTNV



802.11n(HT20)_HCH_2462MHz_Ant1 (SISO)_NTNV



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

6. Form731

6.1 Test Result

6.1.1 Form731

Lower Freq (MHz)	High Freq (MHz)	MAX Power (W)	MAX Power (dBm)
2412	2462	0.0624	17.95

- End of the Report -