

Gao chang electronic technology co. LTD

Room 101, 201, 301, 401, Building A14, 98 Industrial City, Wanfeng Community,
Xinqiao Sub-district, Bao 'an District, Shenzhen City

SPECIFICATION FOR APPROVAL

20111101

File No. _____

1.0

Rev ision _____

CUSTOMER: _____

CUSTOMER NO: _____

2.4G Antenna L=28MM

PART NAME: _____

01.026.000003

SUPPLIER NO: _____

Date:

Q'TY: PCS

CUSTOMER APPROVED BY		
APPROVAL	CHIEF	SUPERVISOR

SUPPLIER SIGNATURE		
APPROVAL	CHECK	DESIGN

SH-RD-F04-A

The project table

NO.	(Contents)	(Number of Page)	(Page Code)
1	(Spec Cover)	1	1
2	(Spec Item)	1	2
3	(Drawing)	1	3
4	(Test Reports)	1	4
5	(S Parameter)	1	5
6	(Gain Test)	1	6
7			
8			
9			
10	-	-	-
11	-	-	-
12	-	-	-





线长: 28mm

Test Reports

Electrical Properties	
Frequency	2.4GHz
Impedance	50 Ohm Nominal
V.S.W.R	1.92 : 1 Max
Return Loss	-10 dB Max
Radiation	Omni-directional
Gain (Peak)	1.94dBi
Cable Loss	1.5 dB / m Max @ 2450 MHz
Polarization	Linear, Vertical
Admitted Power	1 W
Connector	
Physical Properties	
Antenna Material	TUBE
Cable Type	The wire// L= 32mm
Operating Temp.	-10 ~ +60 °C
Storage Temp.	-10 ~ +70 °C
Cable Color	BLACK



S Parameter Test

Agilent E5071C



Gain Test

*Antenna
Radiation
Pattern
VS
Gain*



Efficiency

Passive Test For 2.4								
Freq (MHz)	Effi (%)	Effi (dB)	Gain (dBi)	Gain (dBd)	UHS (%)	DHS (%)	Max (dB)	Min (dB)
2400	59.52	-2.25	1.74	2.59	17.404	42.116	1.74	-15.98
2410	57.06	-2.44	1.61	2.46	16.988	40.071	1.61	-16.43
2420	58.9	-2.3	1.82	2.67	17.853	41.047	1.82	-14.86
2430	60.98	-2.15	1.94	2.79	19.046	41.929	1.94	-15.28
2440	60.05	-2.22	0.5	2.89	18.929	41.118	0.5	-16.06
2450	57.65	-2.39	1.92	2.77	18.834	38.812	1.92	-16.28
2460	51.21	-2.91	1.49	2.34	17.497	33.715	1.49	-16.08
2470	49.05	-3.09	1.23	2.08	17.954	31.101	1.23	-15.57
2480	48.59	-3.13	1.16	2.01	18.701	29.889	1.16	-15.69
2490	49.17	-3.08	1.09	1.94	19.826	29.349	1.09	-15.38
2500	43.12	-3.65	1.47	1.32	17.831	25.29	1.47	-15.29