


$$\begin{array}{c} \text{W!} \\ \text{S} \end{array} + \begin{array}{c} \text{Q} \\ \text{Q} \end{array}$$

The diagram shows the back of the HP iPAQ 190 with the following components labeled:

- MICRO USB charging port
- 3.5mm audio cable
- LED indicator light
- microphone
- SD card

Headphoning mode	LED Status
power on	White LED flashes 2 times
power off	Red LED is off
BT pairing	Red LED & White LED flashes alternately
BT Connected	Blue light 7 s clock ticks once
Low Battery	Red LED flashes 2 times every 2 seconds
Charging in Progress	Red LED keep lighting during charging

Diagram of the rear of the device showing the 'Colorful lights on' and 'Colorful lights off' buttons.

- premm 32mm dynamic driver
- frequency response:20HZ-20KHZ
- support:BT5.0 A2DP V1.2 AVRCP V1.5 HFPV1.5 HSPV1.2
- bluetooth transmitter frequency range: 2.402-2.480GHZ
- bluetooth transmitter power<4dBm
- bluetooth transmitter modulation: GFSK /4 DQPSK 8DPSK
- battery type lithium-ion polymer (3.7V,500 mAh)
- battery charge time <2hrs
- music play time 20hrs
- weight 0.11kg

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.