

RF Exposure Evaluation Report

Product : MAXDRIVE
Trade mark : MATCO TOOLS
Model/Type reference : MAXDRIVE
Serial Number : N/A
Report Number : EED32M00031202
FCC ID : 2AUKMMAXDRIVE
Date of Issue : Mar. 20, 2020
Test Standards : IEEE C95.1 2005
KDB 447498 D03
47 C.F.R. Part 1, Subpart I, Section 1.1310
47 C.F.R. Part 2, Subpart J, Section 2.1091
Test result : PASS

Prepared for:

Matco Tools

4403 Allen Rd. Stow, OH 44224 USA

Prepared by:

Centre Testing International Group Co., Ltd.
Hongwei Industrial Zone, Bao'an 70 District,
Shenzhen, Guangdong, China

TEL: +86-755-3368 3668

FAX: +86-755-3368 3385

Compiled by:

Smile Zhong

Smile Zhong

Reviewed by:

Ware Xin

Ware Xin

Approved by:

Sam Chuang

Sam Chuang

Date:

Mar. 20, 2020



Check No.: 3096320629

2 Version

Version No.	Date	Description
00	Mar. 20, 2020	Original

3 Contents

	Page
1 COVER PAGE.....	1
2 VERSION.....	2
3 CONTENTS.....	3
4 GENERAL INFORMATION.....	4
4.1 CLIENT INFORMATION.....	4
4.2 GENERAL DESCRIPTION OF EUT.....	4
4.3 PRODUCT SPECIFICATION SUBJECTIVE TO THIS STANDARD.....	4
4.4 TEST LOCATION.....	5
4.5 DEVIATION FROM STANDARDS.....	5
4.6 ABNORMALITIES FROM STANDARD CONDITIONS.....	5
4.7 OTHER INFORMATION REQUESTED BY THE CUSTOMER.....	5
5 RF EXPOSURE EVALUATION.....	6
5.1 RF EXPOSURE COMPLIANCE REQUIREMENT.....	6
5.2 MAXIMUM PERMISSIBLE EXPOSURE.....	7
PHOTOGRAPHS OF EUT CONSTRUCTIONAL DETAILS.....	8

4 General Information

4.1 Client Information

Applicant:	Matco Tools
Address of Applicant:	4403 Allen Rd. Stow, OH 44224 USA
Manufacturer:	Matco Tools
Address of Manufacturer:	4403 Allen Rd. Stow, OH 44224 USA

4.2 General Description of EUT

Product Name:	MAXDRIVE
Model No.(EUT):	MAXDRIVE
Trade Mark:	MATCO TOOLS
EUT Supports Radios application	5.0.1 BT Single mode

4.3 Product Specification subjective to this standard

Frequency Range:	2402MHz~2480MHz
Modulation Type:	GFSK
Number of Channels:	40
Test Power Grade:	Default
Test Software of EUT:	DTM Tester
Antenna Type:	Chip antenna
Antenna Gain:	2.08 dBi
Power Supply:	DC 12V
Max Conducted Peak Output Power:	-1.67dBm
	The Max Conducted Peak Output Power data refer to the report EED32L00200301
Sample Received Date:	Jul. 25, 2019
Sample tested Date:	Jul. 25, 2019 to Aug. 29, 2019
The tested sample(s) and the sample information are provided by the client. This report only change the product name, model name, Trade mark, Applicant's name & address, Manufacturer's name & address and color of the enclosure, All test data come from the report of No. EED32L00200302.	

4.4 Test Location

All tests were performed at:

Centre Testing International Group Co., Ltd

Building C, Hongwei Industrial Park Block 70, Bao'an District, Shenzhen, China

Telephone: +86 (0) 755 33683668 Fax: +86 (0) 755 33683385

No tests were sub-contracted.

FCC Designation No.: CN1164

4.5 Deviation from Standards

None.

4.6 Abnormalities from Standard Conditions

None.

4.7 Other Information Requested by the Customer

None.

5 RF Exposure Evaluation

5.1 RF Exposure Compliance Requirement

Given $E = \frac{\sqrt{30 \times P \times G}}{d}$ & $S = \frac{E^2}{377}$

Where E = Field strength in Volts / meter

P = Power in Watts

G = Numeric antenna gain

d = Distance in meters

S = Power density in milliwatts / square centimeter

Combining equations and re-arranging the terms to express the distance as a function of the remaining variables yields:

$$S = \frac{30 \times P \times G}{377 d^2}$$

Changing to units of mW and cm, using:

$$P \text{ (mW)} = P \text{ (W)} / 1000 \text{ and}$$

$$d \text{ (cm)} = d \text{ (m)} / 100$$

Yields

$$S = \frac{30 \times (P/1000) \times G}{377 \times (d/100)^2} = 0.0796 \times \frac{P \times G}{d^2} \quad \text{Equation 1}$$

Where d = Distance in cm

P = Power in mW

G = Numeric antenna gain

S = Power density in mW / cm²

5.2 Maximum Permissible Exposure

Substituting the MPE safe distance using $d = 20$ cm into Equation 1:

$$S = 0.000199 \times P \times G$$

Where P = Power in mW

G = Numeric antenna gain

S = Power density in mW / cm²

Bluetooth:

Ch.	Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm ²	Limit (mW/cm2)
19	2440	0.68	1.61	20	0.0002	1

PHOTOGRAPHS OF EUT Constructional Details

Refer to Report No. EED32M00031201 or EUT external and internal photos.

*** End of Report ***

The test report is effective only with both signature and specialized stamp, The result(s) shown in this report refer only to the sample(s) tested. Without written approval of CTI, this report can't be reproduced except in full.