APPLICATION CERTIFICATION FCC Part 15C
On Behalf of
SKY SINCERITY INTERNATIONAL CO., LTD.

Bluetooth Headphone

Model No.: BHOBTAM, SS-BH032

FCC ID: 2AUOS-BHOBTAM

Prepared for	:	SKY SINCERITY INTERNATIONAL CO., LTD.
Address	:	FLAT C, 9/F WINNING HOUSE, NO. 72-74 WING LOK STREET, HONGKONG, China
Prepared by	:	Shenzhen Accurate Technology Co., Ltd.
Address	:	1/F., Building A, Changyuan New Material Port, Science & Industry Park, Nanshan District, Shenzhen, Guangdong, P.R. China
		Tel: (0755) 26503290 Fax: (0755) 26503396

Report No.	:	ATE20191412
Date of Test	:	September 27-29, 2019
Date of Report	:	September 30, 2019

TABLE OF CONTENTS

Description Page

Test Report Certification
TABLE OF CONTENTS **2**
1. GENERAL INFORMATION **5**
1.1. Description of Device (EUT) 5
1.2. Accessory and Auxiliary Equipment 5
1.3. Description of Test Facility 6
1.4. Measurement Uncertainty 6
2. MEASURING DEVICE AND TEST EQUIPMENT **7**
3. OPERATION OF EUT DURING TESTING **8**
3.1. Operating Mode 8
3.2. Configuration and peripherals 8
4. TEST PROCEDURES AND RESULTS **9**
5. 20DB BANDWIDTH TEST **10**
5.1. Block Diagram of Test Setup 10
5.2. The Requirement For Section 15.247(a)(1) 10
5.3. EUT Configuration on Measurement 10
5.4. Operating Condition of EUT 10
5.5. Test Procedure 10
5.6. Test Result 11
6. CARRIER FREQUENCY SEPARATION TEST **16**
6.1. Block Diagram of Test Setup 16
6.2. The Requirement For Section 15.247(a)(1) 16
6.3. EUT Configuration on Measurement 16
6.4. Operating Condition of EUT 16
6.5. Test Procedure 17
6.6. Test Result 17
7. NUMBER OF HOPPING FREQUENCY TEST **23**
7.1. Block Diagram of Test Setup 23
7.2. The Requirement For Section 15.247(a)(1)(iii) 23
7.3. EUT Configuration on Measurement 23
7.4. Operating Condition of EUT 23
7.5. Test Procedure 23
7.6. Test Result 24
8. DWELL TIME TEST **26**
8.1. Block Diagram of Test Setup 26
8.2. The Requirement For Section 15.247(a)(1)(iii) 26
8.3. EUT Configuration on Measurement 26
8.4. Operating Condition of EUT 26
8.5. Test Procedure 26
8.6. Test Result 27
9. MAXIMUM PEAK OUTPUT POWER TEST **33**
9.1. Block Diagram of Test Setup 33

9.2. The Requirement For Section 15.247(b)(1) 33
9.3. EUT Configuration on Measurement 33
9.4. Operating Condition of EUT 33
9.5. Test Procedure 33
9.6. Test Result 34
10. RADIATED EMISSION TEST 40
10.1. Block Diagram of Test Setup 40
10.2. The Limit For Section 15.247(d) 41
10.3. Restricted bands of operation 43
10.4. Configuration of EUT on Measurement 43
10.5. Operating Condition of EUT 44
10.6. Test Procedure 44
10.7. Data Sample 45
10.8. Tetst Results 45
11. BAND EDGE COMPLIANCE TEST 58
11.1. Block Diagram of Test Setup 58
11.2. The Requirement For Section 15.247(d) 58
11.3. EUT Configuration on Measurement 58
11.4. Operating Condition of EUT 58
11.5. Test Procedure 59
11.6. Test Result 59
12. AC POWER LINE CONDUCTED EMISSION TEST 70
12.1. Block Diagram of Test Setup 70
12.2. Power Line Conducted Emission Measurement Limits 71
12.3. Configuration of EUT on Measurement 71
12.4. Operating Condition of EUT 71
12.5. Test Procedure 71
12.6. Data Sample 72
12.7. Test Results 72
13. ANTENNA REQUIREMENT 75
13.1. The Requirement 75
13.2. Antenna Construction 75

Test Report Certification

Applicant	:	SKY SINCERITY INTERNATIONAL CO., LTD.
Manufacturer	:	SKY SINCERITY INTERNATIONAL CO., LTD.
EUT	:	Bluetooth Headphone
Model No.	:	BHOBTAM, SS-BH032

Measurement Procedure Used:

FCC Rules and Regulations Part 15 Subpart C Section 15.247
ANSI C63.10: 2013

The device described above is tested by Shenzhen Accurate Technology Co., Ltd. to determine the maximum emission levels emanating from the device. The maximum emission levels are compared to the FCC Part 15 Subpart C Section 15.247 limits. The measurement results are contained in this test report and Shenzhen Accurate Technology Co., Ltd. is assumed full responsibility for the accuracy and completeness of these measurements. Also, this report shows that the Equipment Under Test (EUT) is to be technically compliant with the FCC requirements.

This report applies to above tested sample only. This report shall not be reproduced in part without written approval of Shenzhen Accurate Technology Co., Ltd.

Date of Test :	September 27-29, 2019
Date of Report :	September 30, 2019
Prepared by :	(Bob Wang, Engineer)
Approved & Authorized Signer :	(Sean Liu, Manager)

1. GENERAL INFORMATION

1.1.Description of Device (EUT)

Model Number	:	BHOBTAM, SS-BH032 (Note: These samples are same except their appearance is different. So we prepare BHOBTAM for test only.)
Bluetooth version	:	V5.0
Frequency Range	:	2402MHz-2480MHz
Number of Channels	:	79
Antenna Gain(Max)	:	-0.5dBi
Antenna type	:	PCB Antenna
Modulation mode	:	GFSK, π/4 DQPSK, 8DPSK
Power Supply	:	DC 3.7V (Powered by Lithium battery) or DC 5.0V (Powered by USB port)
Applicant	:	SKY SINCERITY INTERNATIONAL CO., LTD.
Address	:	FLAT C, 9/F WINNING HOUSE, NO. 72-74 WING LOK STREET, HONGKONG, China
Manufacturer	:	SKY SINCERITY INTERNATIONAL CO., LTD.
Address	:	FLAT C, 9/F WINNING HOUSE, NO. 72-74 WING LOK STREET, HONGKONG, China

1.2.Accessory and Auxiliary Equipment

AC/DC Power Adapter (provided by laboratory)	:	Model:TEKA006-0501000UKU
		Input: 120V~60Hz 0.3A
		Output: DC 5V/1A

1.3.Description of Test Facility

EMC Lab	:	Recognition of accreditation by Federal Communications Commission (FCC) The Designation Number is CN1189 The Registration Number is 708358 Listed by Innovation, Science and Economic Development Canada (ISEDC) The Registration Number is 5077A-2 Accredited by China National Accreditation Service for Conformity Assessment (CNAS) The Registration Number is CNAS L3193 Accredited by American Association for Laboratory Accreditation (A2LA) The Certificate Number is 4297.01
Name of Firm	:	Shenzhen Accurate Technology Co., Ltd.
Site Location	:	1/F., Building A, Changyuan New Material Port, Science & Industry Park, Nanshan District, Shenzhen, Guangdong, P.R. China

1.4.Measurement Uncertainty

Radiated emission expanded uncertainty (9kHz-30MHz)	:	U=2.66dB, k=2
Radiated emission expanded uncertainty (30MHz-1000MHz)	:	U=4.28dB, k=2
Radiated emission expanded uncertainty (1G-18GHz)	:	U=4.98dB, k=2
Radiated emission expanded uncertainty (18G-26.5GHz)	:	U=5.06dB, k=2
Conduction Emission Expanded Uncertainty (Mains ports, 9kHz-30MHz)	:	U=2.72dB, k=2
Conduction Emission Expanded Uncertainty (Telecommunication ports, 150kHz-30MHz)	:	U=2.94dB, k=2
Power disturbance Expanded Uncertainty	:	U=2.92dB, k=2
Harmonic current expanded uncertainty	:	U=0.512%, k=2

2. MEASURING DEVICE AND TEST EQUIPMENT

Table 1: List of Test and Measurement Equipment

Kind of equipment	Manufacturer	Type	S/N	Calibrated dates	Calibrated until
EMI Test Receiver	Rohde&Schwarz	ESCS30	100307	Jan. 05, 2019	1 Year
EMI Test Receiver	Rohde& Schwarz	ESR	101817	Jan. 05, 2019	1 Year
Spectrum Analyzer	Rohde&Schwarz	FSV40	101495	Jan. 05, 2019	1 Year
Pre-Amplifier	Rohde&Schwarz	CBLU1183540-01	3791	Jan. 05, 2019	1 Year
Loop Antenna	Schwarzbeck	FMZB1516	1516131	Jan. 05, 2019	1 Year
Bilog Antenna	Schwarzbeck	VULB9163	9163-323	Jan. 05, 2019	1 Year
Horn Antenna	Schwarzbeck	BBHA9120D	9120D-655	Jan. 05, 2019	1 Year
Horn Antenna	Schwarzbeck	BBHA9170	9170-359	Jan. 05, 2019	1 Year
LISN	Schwarzbeck	NSLK8126	8126431	Jan. 05, 2019	1 Year
Highpass Filter	Wainwright Instruments	WHKX3.6/18G-10SS	N/A	Jan. 05, 2019	1 Year
Band Reject Filter	Wainwright Instruments	WRCG2400/2485-2375/2510-60/11SS	N/A	Jan. 05, 2019	1 Year
RF COAXIAL CABLE	SUHNER	N-5m(Frequency range:9KHz-26.5GHz)	NO.3	Jan. 05, 2019	1 Year
RF COAXIAL CABLE	SUHNER	N-5m(Frequency range:9KHz-26.5GHz)	NO.4	Jan. 05, 2019	1 Year
RF COAXIAL CABLE	SUHNER	N-1m(Frequency range:9KHz-26.5GHz)	NO.5	Jan. 05, 2019	1 Year
RF COAXIAL CABLE	SUHNER	N-1m(Frequency range:9KHz-26.5GHz)	NO.6	Jan. 05, 2019	1 Year
Temporary antenna connector	NTGS	14AE	N/A	Jan. 21, 2019	N/A

Note: The temporary antenna connector is soldered on the PCB board in order to perform conducted tests and this temporary antenna connector is listed in the equipment list.

3. OPERATION OF EUT DURING TESTING

3.1.Operating Mode

The mode is used: Transmitting mode
Low Channel: 2402MHz
Middle Channel: 2441MHz
High Channel: 2480MHz
Hopping

3.2.Configuration and peripherals



Figure 1 Setup: Transmitting mode



Figure 2 Setup: for radiated emission

4. TEST PROCEDURES AND RESULTS

FCC Rules	Description of Test	Result
Section 15.247(a)(1)	20dB Bandwidth Test	Compliant
Section 15.247(a)(1)	Carrier Frequency Separation Test	Compliant
Section 15.247(a)(1)(iii)	Number Of Hopping Frequency Test	Compliant
Section 15.247(a)(1)(iii)	Dwell Time Test	Compliant
Section 15.247(b)(1)	Maximum Peak Output Power Test	Compliant
Section 15.247(d) Section 15.209	Radiated Emission Test	Compliant
Section 15.247(d)	Band Edge Compliance Test	Compliant
Section 15.207	AC Power Line Conducted Emissions Test	Compliant
Section 15.203	Antenna Requirement	Compliant

5. 20DB BANDWIDTH TEST

5.1.Block Diagram of Test Setup



5.2.The Requirement For Section 15.247(a)(1)

Section 15.247(a)(1): Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater.

5.3.EUT Configuration on Measurement

The equipment are installed on the emission measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

5.4.Operating Condition of EUT

5.4.1.Setup the EUT and simulator as shown as Section 5.1.

5.4.2.Turn on the power of all equipment.

5.4.3.Let the EUT work in TX (Hopping off) modes measure it. The transmit frequency are 2402-2480MHz. We select 2402MHz, 2441MHz, and 2480MHz TX frequency to transmit.

5.5.Test Procedure

5.5.1.The transmitter output was connected to the spectrum analyzer through a low loss cable.

5.5.2.Set RBW of spectrum analyzer to 30 kHz and VBW to 100 kHz.

5.5.3.The 20dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 20dB.

5.6.Test Result

Test Lab: Shielding room

Channel	Frequency (MHz)	GFSK 20dB Bandwidth (MHz)	Π/4-DQPSK 20dB Bandwidth (MHz)	8DPSK 20dB Bandwidth (MHz)	Result
Low	2402	0.990	1.356	1.344	Pass
Middle	2441	0.987	1.362	1.350	Pass
High	2480	0.978	1.362	1.350	Pass

The spectrum analyzer plots are attached as below.

GFSK Mode

Low channel



Middle channel



High channel



Π/4-DQPSK Mode

Low channel



Middle channel



High channel



8DPSK Mode

Low channel



Middle channel



High channel



6. CARRIER FREQUENCY SEPARATION TEST

6.1.Block Diagram of Test Setup



6.2.The Requirement For Section 15.247(a)(1)

Section 15.247(a)(1): Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW. The system shall hop to channel frequencies that are selected at the system hopping rate from a pseudo randomly ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

6.3.EUT Configuration on Measurement

The equipment are installed on the emission measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

6.4.Operating Condition of EUT

6.4.1.Setup the EUT and simulator as shown as Section 6.1.

6.4.2.Turn on the power of all equipment.

6.4.3.Let the EUT work in TX (Hopping on) modes measure it. The transmit frequency are 2402-2480MHz. We select 2402MHz, 2441MHz, and 2480MHz TX frequency to transmit.

6.5.Test Procedure

6.5.1.The transmitter output was connected to the spectrum analyzer through a low loss cable.

6.5.2.Set RBW of spectrum analyzer to 30 kHz and VBW to 100 kHz. Adjust Span to 3 MHz.

6.5.3.Set the adjacent channel of the EUT Maxhold another trace.

6.5.4.Measurement the channel separation

6.6.Test Result

Test Lab: Shielding room

GFSK

Channel	Frequency (MHz)	Channel Separation(MHz)	Limit (MHz)	Result
Low	2402	1.080	25KHz or 2/3*20dB bandwidth	Pass
	2403			
Middle	2440	1.002	25KHz or 2/3*20dB bandwidth	Pass
	2441			
High	2479	1.002	25KHz or 2/3*20dB bandwidth	Pass
	2480			

Π/4-DQPSK

Channel	Frequency (MHz)	Channel Separation(MHz)	Limit (MHz)	Result
Low	2402	1.002	25KHz or 2/3*20dB bandwidth	Pass
	2403			
Middle	2440	1.008	25KHz or 2/3*20dB bandwidth	Pass
	2441			
High	2479	0.996	25KHz or 2/3*20dB bandwidth	Pass
	2480			

8DPSK

Channel	Frequency (MHz)	Channel Separation(MHz)	Limit (MHz)	Result
Low	2402	1.002	25KHz or 2/3*20dB bandwidth	Pass
	2403			
Middle	2440	1.026	25KHz or 2/3*20dB bandwidth	Pass
	2441			
High	2479	0.996	25KHz or 2/3*20dB bandwidth	Pass
	2480			

GFSK Mode

Low channel



Middle channel



High channel



Π/4-DQPSK Mode

Low channel



Middle channel



High channel



8DPSK Mode

Low channel



Middle channel



High channel



7. NUMBER OF HOPPING FREQUENCY TEST

7.1.Block Diagram of Test Setup



7.2.The Requirement For Section 15.247(a)(1)(iii)

Section 15.247(a)(1)(iii): Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels.

7.3.EUT Configuration on Measurement

The equipment are installed on the emission measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

7.4.Operating Condition of EUT

7.4.1.Setup the EUT and simulator as shown as Section 7.1.

7.4.2.Turn on the power of all equipment.

7.4.3.Let the EUT work in TX (Hopping on) modes measure it.

7.5.Test Procedure

7.5.1.The transmitter output was connected to the spectrum analyzer through a low loss cable.

7.5.2.Set the spectrum analyzer as RBW=100 kHz, VBW=300 kHz.

7.5.3.Max hold, view and count how many channel in the band.

7.6.Test Result

Test Lab: Shielding room

Total number of hopping channel	Measurement result(CH)	Limit(CH)	Result
	79	⩾15	Pass

The spectrum analyzer plots are attached as below.

Number of hopping channels (GFSK Mode)



Number of hopping channels (Π/4-DQPSK Mode)



Number of hopping channels (8DPSK Mode)



8. DWELL TIME TEST

8.1.Block Diagram of Test Setup



8.2.The Requirement For Section 15.247(a)(1)(iii)

Section 15.247(a)(1)(iii): Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

8.3.EUT Configuration on Measurement

The equipment are installed on the emission measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

8.4.Operating Condition of EUT

8.4.1.Setup the EUT and simulator as shown as Section 8.1.

8.4.2.Turn on the power of all equipment.

8.4.3.Let the EUT work in TX (Hopping on) modes measure it. The transmit frequency are 2402-2480MHz. We select 2402MHz, 2441MHz, and 2480MHz TX frequency to transmit.

8.5.Test Procedure

8.5.1.The transmitter output was connected to the spectrum analyzer through a low loss cable.

8.5.2.Set center frequency of spectrum analyzer = operating frequency.

8.5.3.Set the spectrum analyzer as RBW=1MHz, VBW=3MHz, Span=0Hz, Adjust Sweep=5ms, 10ms, 15ms. Get the pulse time.

8.5.4.Repeat above procedures until all frequency measured were complete.

8.6.Test Result

Test Lab: Shielding room

GFSK Mode (Worse case)

Mode	Channel Frequency (MHz)	Pulse Time (ms)	Dwell Time (ms)	Limit (ms)
DH1	2441	0.40	128.0	400
A period transmit time = 0.4 × 79 = 31.6 Dwell time = pulse time × (1600/(2*79))×31.6				
DH3	2441	1.70	272.0	400
A period transmit time = 0.4 × 79 = 31.6 Dwell time = pulse time × (1600/(4*79))×31.6				
DH5	2441	3.00	320.0	400
A period transmit time = 0.4 × 79 = 31.6 Dwell time = pulse time × (1600/(6*79))×31.6				

Π/4-DQPSK (Worse case)

Mode	Channel Frequency (MHz)	Pulse Time (ms)	Dwell Time (ms)	Limit (ms)
DH1	2441	0.42	134.4	400
A period transmit time = 0.4 × 79 = 31.6 Dwell time = pulse time × (1600/(2*79))×31.6				
DH3	2441	1.70	272.0	400
A period transmit time = 0.4 × 79 = 31.6 Dwell time = pulse time × (1600/(4*79))×31.6				
DH5	2441	2.99	318.9	400
A period transmit time = 0.4 × 79 = 31.6 Dwell time = pulse time × (1600/(6*79))×31.6				

8DPSK Mode (Worse case)

Mode	Channel Frequency (MHz)	Pulse Time (ms)	Dwell Time (ms)	Limit (ms)
DH1	2441	0.40	128.0	400
A period transmit time = 0.4 × 79 = 31.6 Dwell time = pulse time × (1600/(2*79))×31.6				
DH3	2441	1.70	272.0	400
A period transmit time = 0.4 × 79 = 31.6 Dwell time = pulse time × (1600/(4*79))×31.6				
DH5	2441	2.99	318.9	400
A period transmit time = 0.4 × 79 = 31.6 Dwell time = pulse time × (1600/(6*79))×31.6				

Note: We tested GFSK mode and Π/4-DQPSK & 8DPSK mode the low, middle and high channel and recorded the Worse case data for all test mode.

The spectrum analyzer plots are attached as below.

GFSK Mode

DH1 Middle channel



DH3 Middle channel



DH5 Middle channel



Π/4-DQPSK Mode

2DH1 Middle channel



2DH3 Middle channel



2DH5 Middle channel



8DPSK Mode

3DH1 Middle channel



3DH3 Middle channel



3DH5 Middle channel



9. MAXIMUM PEAK OUTPUT POWER TEST

9.1.Block Diagram of Test Setup



9.2.The Requirement For Section 15.247(b)(1)

Section 15.247(b)(1): For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 watts.

9.3.EUT Configuration on Measurement

The equipment are installed on the emission Measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

9.4.Operating Condition of EUT

9.4.1.Setup the EUT and simulator as shown as Section 9.1.

9.4.2.Turn on the power of all equipment.

9.4.3.Let the EUT work in TX (Hopping off) modes measure it. The transmit frequency are 2402-2480MHz. We select 2402MHz, 2441MHz, and 2480MHz TX frequency to transmit.

9.5.Test Procedure

9.5.1.The transmitter output was connected to the spectrum analyzer through a low loss cable.

9.5.2.Set RBW of spectrum analyzer to 3MHz and VBW to 10MHz.

9.5.3.Measurement the maximum peak output power.

9.6.Test Result

Test Lab: Shielding room

GFSK Mode

Channel	Frequency (MHz)	Peak Output Power (dBm/W)	Limits dBm / W
Low	2402	0.90/0.0012	21 / 0.125
Middle	2441	0.69/0.0012	21 / 0.125
High	2480	0.43/0.0011	21 / 0.125

Π/4-DQPSK Mode

Channel	Frequency (MHz)	Peak Output Power (dBm/W)	Limits dBm / W
Low	2402	3.42/0.0022	21 / 0.125
Middle	2441	3.12/0.0021	21 / 0.125
High	2480	3.00/0.0020	21 / 0.125

8DPSK Mode

Channel	Frequency (MHz)	Peak Output Power (dBm/W)	Limits dBm / W
Low	2402	3.79/0.0024	21 / 0.125
Middle	2441	3.45/0.0022	21 / 0.125
High	2480	3.36/0.0022	21 / 0.125

The spectrum analyzer plots are attached as below.

GFSK Mode

Low channel



Middle channel



High channel



Π/4-DQPSK Mode

Low channel



Middle channel



High channel



8DPSK Mode

Low channel



Middle channel



High channel



10. RADIATED EMISSION TEST

10.1. Block Diagram of Test Setup

10.1.1. Block diagram of connection between the EUT and peripherals

EUT

Figure 1 Setup: Transmitting mode

10.1.2. Semi-Anechoic Chamber Test Setup Diagram

(A)Radiated Emission Test Set-Up, Frequency below 30MHz



(B)Radiated Emission Test Set-Up, Frequency 30MHz-1GHz



(C) Radiated Emission Test Set-Up, Frequency above 1GHz



10.2.The Limit For Section 15.247(d)

Section 15.247(d): In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the

general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a).

10.3.Restricted bands of operation

10.3.1.FCC Part 15.205 Restricted bands of operation

(a) Except as shown in paragraph (d) of this section, Only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
[1]0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	([2])
13.36-13.41			

[1]Until February 1, 1999, this restricted band shall be 0.490-0.510
[2]Above 38.6

(b) Except as provided in paragraphs (d) and (e), the field strength of emission appearing within these frequency bands shall not exceed the limits shown in Section 15.209. At frequencies equal to or less than 1000MHz, Compliance with the limits in Section 15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasi-peak detector. Above 1000MHz, compliance with the emission limits in Section15.209 shall be demonstrated based on the average value of the measured emissions. The provisions in Section 15.35 apply to these measurements.

10.4.Configuration of EUT on Measurement

The equipment is installed on Radiated Emission Measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

10.5. Operating Condition of EUT

10.5.1. Setup the EUT and simulator as shown as Section 10.1.

10.5.2. Turn on the power of all equipment.

10.5.3. Let the EUT work in TX modes measure it. The transmit frequency are 2402-2480MHz. We select 2402MHz, 2441MHz, and 2480MHz TX frequency to transmit.

10.6. Test Procedure

The EUT and its simulators are placed on a turntable, which is 0.8 meter high above ground(Below 1GHz). The EUT and its simulators are placed on a turntable, which is 1.5 meter high above ground(Above 1GHz). The turntable can rotate 360 degrees to determine the position of the maximum emission level. EUT is set 3.0 meters away from the receiving antenna, which is mounted on an antenna tower. The antenna can be moved up and down between 1.0 meter and 4 meters to find out the maximum emission level. Broadband antenna (calibrated bi-log antenna) is used as receiving antenna. Both horizontal and vertical polarizations of the antenna are set on measurement. In order to find the maximum emission levels, all of the EUT location must be manipulated according to ANSI C63.10:2013 on radiated emission measurement. This EUT was tested in 3 orthogonal positions and the Worse case position data was reported.

During the radiated emission test, the spectrum analyzer was set with the following configurations:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for peak measurement with peak detector at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average measurement with peak detection at frequency above 1GHz.
4. All modes of operation were investigated and the worst-case emissions are reported.

10.7.Data Sample

Frequency (MHz)	Reading (dBμv)	Factor (dB/m)	Result (dBμv/m)	Limit (dBμv/m)	Margin (dB)	Remark
X.XX	28.66	-15.19	13.47	40.0	-26.53	QP

Frequency(MHz) = Emission frequency in MHz
Reading(dBμv) = Uncorrected Analyzer/Receiver reading
Factor (dB/m) = Antenna factor + Cable Loss – Amplifier gain
Result(dBμv/m) = Reading(dBμv) + Factor(dB/m)
Limit (dBμv/m) = Limit stated in standard
Margin (dB) = Result(dBμv/m) - Limit (dBμv/m)
QP = Quasi-peak Reading

Calculation Formula:
Margin(dB) = Result (dBμV/m)–Limit(dBμV/m)
Result(dBμV/m)= Reading(dBμV)+ Factor(dB/m)

The “Margin” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of -7dB means the emission is 7dB below the limit.

10.8.Tetst Results

Pass.
Test Lab: 3m Anechoic chamber

Note: 1.We tested GFSK mode, Π/4-DQPSK Mode & 8DPSK mode and recorded the Worse case data (GFSK mode) for all test mode.

2. Testing is carried out with frequency rang 9kHz to the tenth harmonics, which above 3th Harmonics are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

The measurements greater than 20dB below the limit from 9kHz to 30MHz and 18 to 26.5GHz.

The spectrum analyzer plots are attached as below.

Below 1GHz

ACCURATE TECHNOLOGY CO., LTD.
F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China
Site: 1# Chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: FRANK2019-BT #369	Polarization: Horizontal
Standard: FCC Class B 3M Radiated	Power Source: DC 3.7V
Test item: Radiation Test	Date: 2019/09/27
Temp.(C)/Hum.(%) 25 C / 55 %	Time: 16:35:03
EUT: Bluetooth Headphone	Engineer Signature:
Mode: TX2402MHz	Distance: 3m
Model: BHOBTAM	
Manufacturer: SKY SINCERITY INTERNATIONAL CO.,LTD	

Note: Report NO.:ATE20191412



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	164.8908	58.18	-26.55	31.63	43.50	-11.87	QP	200	332	
2	170.7878	59.96	-26.08	33.88	43.50	-9.62	QP	200	210	
3	182.5783	57.04	-25.78	31.26	43.50	-12.24	QP	200	85	
4	216.1194	54.97	-24.05	30.92	46.00	-15.08	QP	200	221	
5	236.7924	54.46	-23.78	30.68	46.00	-15.32	QP	200	63	
6	328.3068	55.35	-20.25	35.10	46.00	-10.90	QP	200	175	

ACCURATE TECHNOLOGY CO., LTD.
F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China
Site: 1# Chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: FRANK2019-BT #370	Polarization: Vertical
Standard: FCC Class B 3M Radiated	Power Source: DC 3.7V
Test item: Radiation Test	Date: 2019/09/27
Temp.(C)/Hum.(%) 25 C / 55 %	Time: 16:37:56
EUT: Bluetooth Headphone	Engineer Signature:
Mode: TX2402MHz	Distance: 3m
Model: BHOBTAM	
Manufacturer: SKY SINCERITY INTERNATIONAL CO.,LTD	

Note: Report NO.:ATE20191412



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	130.3048	43.29	-27.72	15.57	43.50	-27.93	QP	100	93	
2	154.2427	43.13	-27.68	15.45	43.50	-28.05	QP	100	201	
3	164.8909	45.63	-26.55	19.08	43.50	-24.42	QP	100	23	
4	170.7878	49.28	-26.08	23.20	43.50	-20.30	QP	100	221	
5	328.3068	47.80	-20.25	27.55	46.00	-18.45	QP	100	63	
6	498.7302	44.90	-16.34	28.56	46.00	-17.44	QP	100	149	

ACCURATE TECHNOLOGY CO., LTD.
F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China
Site: 1# Chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: FRANK2019-BT #371	Polarization: Vertical
Standard: FCC Class B 3M Radiated	Power Source: DC 3.7V
Test item: Radiation Test	Date: 2019/09/27
Temp.(C)/Hum.(%) 25 C / 55 %	Time: 16:39:03
EUT: Bluetooth Headphone	Engineer Signature:
Mode: TX2441MHz	Distance: 3m
Model: BHOBTAM	
Manufacturer: SKY SINCERITY INTERNATIONAL CO.,LTD	

Note: Report NO.:ATE20191412



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	130.3048	43.29	-27.72	15.57	43.50	-27.93	QP	100	66	
2	170.7878	49.28	-26.08	23.20	43.50	-20.30	QP	100	218	
3	216.1195	43.24	-24.05	19.19	46.00	-26.81	QP	100	96	
4	328.3068	47.80	-20.25	27.55	46.00	-18.45	QP	100	116	
5	377.8480	43.78	-18.66	25.12	46.00	-20.88	QP	100	22	
6	488.3263	48.04	-16.48	31.56	46.00	-14.44	QP	100	163	

ACCURATE TECHNOLOGY CO., LTD.
F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China
Site: 1# Chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: FRANK2019-BT #372	Polarization: Horizontal
Standard: FCC Class B 3M Radiated	Power Source: DC 3.7V
Test item: Radiation Test	Date: 2019/09/27
Temp.(C)/Hum.(%) 25 C / 55 %	Time: 16:41:45
EUT: Bluetooth Headphone	Engineer Signature:
Mode: TX2441MHz	Distance: 3m
Model: BHOBTAM	
Manufacturer: SKY SINCERITY INTERNATIONAL CO.,LTD	

Note: Report NO.:ATE20191412



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	154.2427	54.32	-27.68	26.64	43.50	-16.86	QP	200	312	
2	164.8910	59.08	-26.55	32.53	43.50	-10.97	QP	200	66	
3	170.7878	59.82	-26.08	33.74	43.50	-9.76	QP	200	50	
4	216.1195	56.23	-24.05	32.18	46.00	-13.82	QP	200	221	
5	328.3068	57.93	-20.25	37.68	46.00	-8.32	QP	200	33	
6	354.6911	52.55	-19.14	33.41	46.00	-12.59	QP	200	146	

ACCURATE TECHNOLOGY CO., LTD.
F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China
Site: 1# Chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: FRANK2019-BT #373	Polarization: Horizontal
Standard: FCC Class B 3M Radiated	Power Source: DC 3.7V
Test item: Radiation Test	Date: 2019/09/27
Temp.(C)/Hum.(%) 25 C / 55 %	Time: 16:43:51
EUT: Bluetooth Headphone	Engineer Signature:
Mode: TX2480MHz	Distance: 3m
Model: BHOBTAM	
Manufacturer: SKY SINCERITY INTERNATIONAL CO.,LTD	

Note: Report NO.:ATE20191412



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	154.2427	54.32	-27.68	26.64	43.50	-16.86	QP	200	133	
2	170.7878	59.82	-26.08	33.74	43.50	-9.76	QP	200	231	
3	182.5783	57.32	-25.78	31.54	43.50	-11.96	QP	200	69	
4	216.1195	56.23	-24.05	32.18	46.00	-13.82	QP	200	223	
5	271.5686	55.77	-22.52	33.25	46.00	-12.75	QP	200	302	
6	328.3068	57.93	-20.25	37.68	46.00	-8.32	QP	200	149	

ACCURATE TECHNOLOGY CO., LTD.
F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China
Site: 1# Chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: FRANK2019-BT #374	Polarization: Vertical
Standard: FCC Class B 3M Radiated	Power Source: DC 3.7V
Test item: Radiation Test	Date: 2019/09/27
Temp.(C)/Hum.(%) 25 C / 55 %	Time: 16:45:20
EUT: Bluetooth Headphone	Engineer Signature:
Mode: TX2480MHz	Distance: 3m
Model: BHOBTAM	
Manufacturer: SKY SINCERITY INTERNATIONAL CO.,LTD	

Note: Report NO.:ATE20191412



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	72.4651	42.92	-27.59	15.33	40.00	-24.67	QP	100	100	
2	154.2427	43.13	-27.68	15.45	43.50	-28.05	QP	100	63	
3	170.7878	47.19	-26.08	21.11	43.50	-22.39	QP	100	26	
4	202.8745	43.39	-24.25	19.14	43.50	-24.36	QP	100	101	
5	328.3068	44.74	-20.25	24.49	46.00	-21.51	QP	100	332	
6	478.1394	45.90	-16.65	29.25	46.00	-16.75	QP	100	146	

Above 1GHz

ACCURATE TECHNOLOGY CO., LTD.
F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China
Site: 1# Chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: FRANK2019-BT #383	Polarization: Vertical
Standard: FCC PK	Power Source: DC 3.7V
Test item: Radiation Test	Date: 19/09/29/
Temp.(C)/Hum.(%) 25 C / 55 %	Time: 13/31/15
EUT: Bluetooth Headphone	Engineer Signature:
Mode: TX2402MHz	Distance: 3m
Model: BHOBTAM	
Manufacturer: SKY SINCERITY INTERNATIONAL CO.,LTD	

Note: Report NO.:ATE20191412



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2402.000	92.27	-6.37	85.90			peak	150	136	
2	4804.000	45.46	1.13	46.59	74.00	-27.41	peak	150	211	

ACCURATE TECHNOLOGY CO., LTD.
F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China
Site: 1# Chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: FRANK2019-BT #384	Polarization: Horizontal
Standard: FCC PK	Power Source: DC 3.7V
Test item: Radiation Test	Date: 19/09/29/
Temp.(C)/Hum.(%) 25 C / 55 %	Time: 13/34/12
EUT: Bluetooth Headphone	Engineer Signature:
Mode: TX2402MHz	Distance: 3m
Model: BHOBTAM	
Manufacturer: SKY SINCERITY INTERNATIONAL CO.,LTD	

Note: Report NO.:ATE20191412



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2402.000	90.18	-6.37	83.81			peak	200	93	
2	4804.000	43.35	1.13	44.48	74.00	-29.52	peak	200	149	

ACCURATE TECHNOLOGY CO., LTD.
F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China
Site: 1# Chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: FRANK2019-BT #385	Polarization: Horizontal
Standard: FCC PK	Power Source: DC 3.7V
Test item: Radiation Test	Date: 19/09/29/
Temp.(C)/Hum.(%) 25 C / 55 %	Time: 13/37/10
EUT: Bluetooth Headphone	Engineer Signature:
Mode: TX2441MHz	Distance: 3m
Model: BHOBTAM	
Manufacturer: SKY SINCERITY INTERNATIONAL CO.,LTD	

Note: Report NO.:ATE20191412



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2441.000	90.15	-6.08	84.07			peak	200	138	
2	4882.000	42.42	1.25	43.67	74.00	-30.33	peak	200	109	

ACCURATE TECHNOLOGY CO., LTD.
F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China
Site: 1# Chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: FRANK2019-BT #386	Polarization: Vertical
Standard: FCC PK	Power Source: DC 3.7V
Test item: Radiation Test	Date: 19/09/29/
Temp.(C)/Hum.(%) 25 C / 55 %	Time: 13/41/12
EUT: Bluetooth Headphone	Engineer Signature:
Mode: TX2441MHz	Distance: 3m
Model: BHOBTAM	
Manufacturer: SKY SINCERITY INTERNATIONAL CO.,LTD	

Note: Report NO.:ATE20191412



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2441.000	91.19	-6.08	85.11			peak	150		
2	4882.000	44.67	1.36	46.03	74.00	-27.97	peak	150	63	

ACCURATE TECHNOLOGY CO., LTD.
F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China
Site: 1# Chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: FRANK2019-BT #387	Polarization: Vertical
Standard: FCC PK	Power Source: DC 3.7V
Test item: Radiation Test	Date: 19/09/29/
Temp.(C)/Hum.(%) 25 C / 55 %	Time: 13/47/13
EUT: Bluetooth Headphone	Engineer Signature:
Mode: TX2480MHz	Distance: 3m
Model: BHOBTAM	
Manufacturer: SKY SINCERITY INTERNATIONAL CO.,LTD	

Note: Report NO.:ATE20191412



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2480.000	93.33	-5.87	87.46			peak	150	320	
2	4960.000	44.61	1.62	46.23	74.00	-27.77	peak	150	196	

ACCURATE TECHNOLOGY CO., LTD.
F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China
Site: 1# Chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: FRANK2019-BT #388
Standard: FCC PK
Test item: Radiation Test
Temp.(C)/Hum.(%) 25 C / 55 %
EUT: Bluetooth Headphone
Mode: TX2480MHz
Model: BHOBTAM
Manufacturer: SKY SINCERITY INTERNATIONAL CO.,LTD

Polarization: Horizontal
Power Source: DC 3.7V
Date: 19/09/29/
Time: 13/51/13
Engineer Signature:
Distance: 3m

Note: Report NO.:ATE20191412



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2480.000	92.01	-5.87	86.14			peak	200	135	
2	4960.000	42.93	1.62	44.55	74.00	-29.45	peak	200	196	

11.BAND EDGE COMPLIANCE TEST

11.1.Block Diagram of Test Setup



11.2.The Requirement For Section 15.247(d)

Section 15.247(d): In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a).

11.3.EUT Configuration on Measurement

The equipment are installed on the emission Measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

11.4.Operating Condition of EUT

11.4.1.Setup the EUT and simulator as shown as Section 11.1.

11.4.2.Turn on the power of all equipment.

11.4.3.Let the EUT work in TX (Hopping off, Hopping on) modes measure it. The transmit frequency are 2402-2480MHz. We select 2402MHz, 2480MHz TX frequency to transmit.

11.5.Test Procedure

11.5.1.The transmitter output was connected to the spectrum analyzer via a low loss cable.

11.5.2.Set RBW of spectrum analyzer to 100 kHz and VBW to 300 kHz with convenient frequency span including 100 kHz bandwidth from band edge.

11.5.3.The band edges was measured and recorded.

11.6.Test Result

Test Lab: Shielding room

Note: Both hopping-on mode and hopping-off mode had been pre-tested, and only the Worse case was recorded in the test report.

Conducted Band Edge Result

Non-hopping mode

Frequency (MHz)	Result of Band Edge (dBc)	Limit of Band Edge (dBc)	Result
GFSK Mode			
2400.00	38.26	> 20dBc	Pass
2483.50	42.67	> 20dBc	Pass
Π/4-DQPSK Mode			
2400.00	39.11	> 20dBc	Pass
2483.50	42.95	> 20dBc	Pass
8DPSK Mode			
2400.00	38.31	> 20dBc	Pass
2483.50	42.65	> 20dBc	Pass

The spectrum analyzer plots are attached as below.

GFSK Mode


RBW 100 kHz
VBW 300 kHz
SWT 10 ms
Marker 1 [T1]
0.87 dBm
2.402040000 GHz
Ref 20 dBm
Att 40 dB
20 Offset 10 dB
Marker 2 [T1]
-42.43 dBm
2.390000000 GHz
Marker 3 [T1]
-39.13 dBm
2.400000000 GHz
1 PK
MAXH
D1 -19.13 dBm
A
LVL
3DB
Center 2.4 GHz
6 MHz/
Span 60 MHz


RBW 100 kHz
VBW 300 kHz
SWT 10 ms
Marker 3 [T1]
-43.71 dBm
2.500000000 GHz
Ref 20 dBm
Att 40 dB
20 Offset 10 dB
Marker 1 [T1]
0.44 dBm
2.480020000 GHz
Marker 2 [T1]
-43.11 dBm
2.483500000 GHz
1 PK
MAXH
D1 -19.56 dBm
A
LVL
3DB
Center 2.4835 GHz
6 MHz/
Span 60 MHz

Π/4-DQPSK Mode





8DPSK Mode


RBW 100 kHz
VBW 300 kHz
SWT 10 ms
Ref 20 dBm
Att 40 dB
Marker 1 [T1]
-0.60 dBm
2.402160000 GHz
Marker 2 [T1]
-42.27 dBm
2.390000000 GHz
Marker 3 [T1]
-38.91 dBm
2.400000000 GHz
1 PK
MAXH
D1 -20.6 dBm
3DB
Center 2.4 GHz
6 MHz/
Span 60 MHz


RBW 100 kHz
VBW 300 kHz
SWT 10 ms
Ref 20 dBm
Att 40 dB
Marker 3 [T1]
-44.47 dBm
2.500000000 GHz
Marker 1 [T1]
-1.33 dBm
2.480140000 GHz
Marker 2 [T1]
-43.98 dBm
2.483500000 GHz
1 PK
MAXH
D1 -21.33 dBm
3DB
Center 2.4835 GHz
6 MHz/
Span 60 MHz

Radiated Band Edge Result

Note:

1. Emissions attenuated more than 20 dB below the permissible value are not reported.
2. The field strength is calculated by adding the antenna factor, high pass filter loss(if used) and cable loss, and subtracting the amplifier gain(if any)from the measured reading. The basic equation calculation is as follows:

   Result = Reading + Corrected Factor
3. Display the measurement of peak values.

Test Procedure:

The EUT and its simulators are placed on a turntable, which is 1.5 meter high above ground(Above 1GHz). The turntable can rotate 360 degrees to determine the position of the maximum emission level. EUT is set 3.0 meters away from the receiving antenna, which is mounted on an antenna tower. The antenna can be moved up and down between 1.0 meter and 4 meters to find out the maximum emission level. Broadband antenna (calibrated bi-log antenna) is used as receiving antenna. Both horizontal and vertical polarizations of the antenna are set on measurement. In order to find the maximum emission levels, all of the EUT location must be manipulated according to ANSI C63.10:2013 on radiated emission measurement. The EUT was tested in 3 orthogonal planes.

Let the EUT work in TX (Hopping off, Hopping on) modes measure it.
We select 2402MHz, 2480MHz TX frequency to transmit(Hopping off mode).
We select 2402-2480MHz TX frequency to transmit(Hopping on mode).

During the radiated emission test, the spectrum analyzer was set with the following configurations:
1.The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for peak measurement with peak detector at frequency above 1GHz.
2.The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average measurement with peak detection at frequency above 1GHz.
3.All modes of operation were investigated and the worse case (GFSK Mode) emissions are reported.

Test Lab: 3m Anechoic chamber

The spectrum analyzer plots are attached as below.

Non-hopping mode

ACCURATE TECHNOLOGY CO., LTD.
F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China
Site: 1# Chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: FRANK2019-BT #389	Polarization: Horizontal
Standard: FCC PK	Power Source: DC 3.7V
Test item: Radiation Test	Date: 19/09/29/
Temp.(C)/Hum.(%) 25 C / 55 %	Time: 13/56/12
EUT: Bluetooth Headphone	Engineer Signature:
Mode: TX2402MHz(GSFK)	Distance: 3m
Model: BHOBTAM	
Manufacturer: SKY SINCERITY INTERNATIONAL CO.,LTD	

Note: Report NO.:ATE20191412



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2390.000	41.02	-6.32	34.70	74.00	-39.30	peak	200	196	
2	2390.000	31.42	-6.32	25.10	54.00	-28.90	AVG	200	33	
3	2400.000	47.16	-6.27	40.89	74.00	-33.11	peak	200	211	
4	2400.000	37.42	-6.27	31.15	54.00	-22.85	AVG	200	204	

Note: Average measurement with peak detection at No.2&4

ACCURATE TECHNOLOGY CO., LTD.
F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China
Site: 1# Chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: FRANK2019-BT #390	Polarization: Vertical
Standard: FCC PK	Power Source: DC 3.7V
Test item: Radiation Test	Date: 19/09/29/
Temp.(C)/Hum.(%) 25 C / 55 %	Time: 14/01/45
EUT: Bluetooth Headphone	Engineer Signature:
Mode: TX2402MHz(GSFK)	Distance: 3m
Model: BHOBTAM	
Manufacturer: SKY SINCERITY INTERNATIONAL CO.,LTD	

Note: Report NO.:ATE20191412



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2390.000	43.25	-6.32	36.93	74.00	-37.07	peak	150	109	
2	2390.000	33.16	-6.32	26.84	54.00	-27.16	AVG	150	63	
3	2400.000	46.65	-6.27	40.38	74.00	-33.62	peak	150	331	
4	2400.000	36.42	-6.27	30.15	54.00	-23.85	AVG	150	201	

Note: Average measurement with peak detection at No.2&4

ACCURATE TECHNOLOGY CO., LTD.
F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China
Site: 1# Chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: FRANK2019-BT #395	Polarization: Vertical
Standard: FCC PK	Power Source: DC 3.7V
Test item: Radiation Test	Date: 19/09/29/
Temp.(C)/Hum.(%) 25 C / 55 %	Time: 14/24/41
EUT: Bluetooth Headphone	Engineer Signature:
Mode: TX2480MHz(GFSK)	Distance: 3m
Model: BHOBTAM	
Manufacturer: Topalong Lean Supply (H.K) Ltd	

Note: Report NO.:ATE20191412



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2483.500	39.24	-5.89	33.35	74.00	-40.65	peak	150	201	
2	2483.500	30.21	-5.89	24.32	54.00	-29.68	AVG	150	331	
3	2500.000	38.75	-5.81	32.94	74.00	-41.06	peak	150	66	
4	2500.000	28.90	-5.81	23.09	54.00	-30.91	AVG	150	196	

Note: Average measurement with peak detection at No.2&4

ACCURATE TECHNOLOGY CO., LTD.
F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China
Site: 1# Chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: FRANK2019-BT #396	Polarization: Horizontal
Standard: FCC PK	Power Source: DC 3.7V
Test item: Radiation Test	Date: 19/09/29/
Temp.(C)/Hum.(%) 25 C / 55 %	Time: 14/28/42
EUT: Bluetooth Headphone	Engineer Signature:
Mode: TX2480MHz(GFSK)	Distance: 3m
Model: BHOBTAM	
Manufacturer: Topalong Lean Supply (H.K) Ltd	

Note: Report NO.:ATE20191412



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2483.500	40.74	-5.89	34.85	74.00	-39.15	peak	200	196	
2	2483.500	30.30	-5.89	24.41	54.00	-29.59	AVG	200	302	
3	2500.000	39.96	-5.81	34.15	74.00	-39.85	peak	200	115	
4	2500.000	29.49	-5.81	23.68	54.00	-30.32	AVG	200	93	

Note: Average measurement with peak detection at No.2&4

Hopping mode

ACCURATE TECHNOLOGY CO., LTD.
F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China
Site: 1# Chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: FRANK2019-BT #405	Polarization: Horizontal
Standard: FCC PK	Power Source: DC 3.7V
Test item: Radiation Test	Date: 19/09/29/
Temp.(C)/Hum.(%) 25 C / 55 %	Time: 15/20/15
EUT: Bluetooth Headphone	Engineer Signature:
Mode: HOPPING(GFSK)	Distance: 3m
Model: BHOBTAM	
Manufacturer: Topalong Lean Supply (H.K) Ltd	

Note: Report NO.:ATE20191412



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2390.000	41.23	-6.32	34.91	74.00	-39.09	peak	200	103	
2	2390.000	31.85	-6.32	25.53	54.00	-28.47	AVG	200	52	
3	2400.000	46.22	-6.27	39.95	74.00	-34.05	peak	200	215	
4	2400.000	36.46	-6.27	30.19	54.00	-23.81	AVG	200	93	
5	2483.500	42.01	-5.89	36.12	74.00	-37.88	peak	200	321	
6	2483.500	32.50	-5.89	26.61	54.00	-27.39	AVG	200	201	
7	2500.000	41.61	-5.81	35.80	74.00	-38.20	peak	200	82	
8	2500.000	31.42	-5.81	25.61	54.00	-28.39	AVG	200	216	

Note: Average measurement with peak detection at No.2&4&6&8

ACCURATE TECHNOLOGY CO., LTD.
F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China
Site: 1# Chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: FRANK2019-BT #406	Polarization: Vertical
Standard: FCC PK	Power Source: DC 3.7V
Test item: Radiation Test	Date: 19/09/29/
Temp.(C)/Hum.(%) 25 C / 55 %	Time: 15/32/18
EUT: Bluetooth Headphone	Engineer Signature:
Mode: HOPPING(GFSK)	Distance: 3m
Model: BHOBTAM	
Manufacturer: Topalong Lean Supply (H.K) Ltd	

Note: Report NO.:ATE20191412



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2390.000	41.73	-6.32	35.41	74.00	-38.59	peak	150	196	
2	2390.000	31.45	-6.32	25.13	54.00	-28.87	AVG	150	312	
3	2400.000	44.72	-6.27	38.45	74.00	-35.55	peak	150	221	
4	2400.000	34.00	-6.27	27.73	54.00	-26.27	AVG	150	82	
5	2483.000	42.94	-5.89	37.05	74.00	-36.95	peak	150	220	
6	2483.500	32.55	-5.89	26.66	54.00	-27.34	AVG	150	33	
7	2500.000	42.11	-5.81	36.30	74.00	-37.70	peak	150	159	
8	2500.000	32.12	-5.81	26.31	54.00	-27.69	AVG	150	93	

Note: Average measurement with peak detection at No.2&4&6&8

12. AC POWER LINE CONDUCTED EMISSION TEST

12.1. Block Diagram of Test Setup

12.1.1. Block diagram of connection between the EUT and simulators



12.1.2. Test System Setup



Note: 1. Support units were connected to second LISN.
2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

12.2.Power Line Conducted Emission Measurement Limits

Frequency (MHz)	Limit dB(μV)	
	Quasi-peak Level	Average Level
0.15 - 0.50	66.0 – 56.0 *	56.0 – 46.0 *
0.50 - 5.00	56.0	46.0
5.00 - 30.00	60.0	50.0
NOTE1: The lower limit shall apply at the transition frequencies. NOTE2: The limit decreases linearly with the logarithm of the frequency in the range 0.15MHz to 0.50MHz.		

12.3.Configuration of EUT on Measurement

The equipments are installed on Power Line Conducted Emission Measurement to meet the commission requirement and operating regulations in a manner, which tends to maximize its emission characteristics in a normal application.

12.4.Operating Condition of EUT

12.4.1.Setup the EUT and simulator as shown as Section 12.1.

12.4.2.Turn on the power of all equipment.

12.4.3.Let the EUT work in test mode and measure it.

12.5.Test Procedure

The EUT is put on the plane 0.8m high above the ground by insulating support and is connected to the power mains through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm coupling impedance for the EUT system. Please refer the block diagram of the test setup and photographs. Both sides of AC lines are checked to find out the maximum conducted emission. In order to find the maximum emission levels, the relative positions of equipment and all of the interface cables shall be changed according to ANSI C63.10: 2013 on Conducted Emission Measurement.

The bandwidth of test receiver is set at 9kHz.

The frequency range from 150kHz to 30MHz is checked.

12.6.Data Sample

Frequency (MHz)	Transducer value (dB)	QuasiPeak Level (dBμV)	Average Level (dBμV)	QuasiPeak Limit (dBμV)	Average Limit (dBμV)	QuasiPeak Margin (dB)	Average Margin (dB)	Remark (Pass/Fail)
X.XX	10.6	25.3	17.0	59.0	49.0	33.4	31.7	Pass

Frequency(MHz) = Emission frequency in MHz
Transducer value(dB) = Insertion loss of LISN + Cable Loss
Level(dBμV) = Quasi-peak Reading/Average Reading + Transducer value
Limit (dBμV) = Limit stated in standard
Margin = Limit (dBμV) - Level (dBμV)

Calculation Formula:
Margin = Limit (dBμV) - Level (dBμV)

12.7.Test Results

Pass.
Test Lab: 3m Anechoic chamber

The frequency range from 150kHz to 30MHz is checked.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.
Emissions attenuated more than 20 dB below the permissible value are not reported.

All data was recorded in the Quasi-peak and average detection mode.

The spectral diagrams are attached as below.

ACCURATE TECHNOLOGY CO.,LTD

CONDUCTED EMISSION STANDARD FCC PART 15B

```
EUT:                  Bluetooth Headphone M/N:SS-BH032
Manufacturer:         SKY SINCERITY INTERNATIONAL CO.,LTD
Operating Condition:  BT Communication
Test Site:            2#Shielding Room
Operator:             Frank
Test Specification:   N   120V 60Hz
Comment:              Report NO.:ATE20191412
Start of Test:        2019-9-27 / 11:24:18
```

SCAN TABLE: "V 150K-30MHz fin"

```
Short Description:            _SUB_STD_VTERM2 1.70
Start      Stop       Step       Detector  Meas.     IF       Transducer
Frequency  Frequency  Width                Time      Bandw.
150.0 kHz  30.0 MHz   4.5 kHz    QuasiPeak 1.0 s     9 kHz    NSLK8126 2008
                                 Average
```



MEASUREMENT RESULT: "F-1412-2_fin"

2019-9-27 11:26

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line	PE
0.150000	41.80	10.8	66	24.2	QP	N	GND
0.442000	28.50	11.0	57	28.5	QP	N	GND
1.310000	23.10	11.2	56	32.9	QP	N	GND
4.850000	20.10	11.4	56	35.9	QP	N	GND
5.620000	19.20	11.5	60	40.8	QP	N	GND
15.050000	19.00	11.6	60	41.0	QP	N	GND

MEASUREMENT RESULT: "F-1412-2_fin2"

2019-9-27 11:26

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line	PE
0.150000	36.30	10.8	56	19.7	AV	N	GND
0.440000	22.70	11.0	47	24.4	AV	N	GND
1.800000	18.00	11.2	46	28.0	AV	N	GND
2.530000	14.70	11.3	46	31.3	AV	N	GND
5.625000	11.40	11.5	50	38.6	AV	N	GND
14.800000	8.50	11.6	50	41.5	AV	N	GND

ACCURATE TECHNOLOGY CO.,LTD

CONDUCTED EMISSION STANDARD FCC PART 15B

EUT: Bluetooth Headphone M/N:SS-BH032
Manufacturer: SKY SINCERITY INTERNATIONAL CO.,LTD
Operating Condition: BT Communication
Test Site: 2#Shielding Room
Operator: Frank
Test Specification: L 120V 60Hz
Comment: Report NO.:ATE20191412
Start of Test: 2019-9-27 / 11:21:50

SCAN TABLE: "V 150K-30MHz fin"

Short Description: _SUB_STD_VTERM2 1.70

Start Frequency	Stop Frequency	Step Width	Detector	Meas. Time	IF Bandw.	Transducer
150.0 kHz	30.0 MHz	4.5 kHz	QuasiPeak	1.0 s	9 kHz	NSLK8126 2008
			Average			



MEASUREMENT RESULT: "F-1412-1_fin"

2019-9-27 11:23

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line	PE
0.150000	51.10	10.8	66	14.9	QP	L1	GND
0.446000	34.30	11.0	57	22.6	QP	L1	GND
1.782000	28.30	11.2	56	27.7	QP	L1	GND
2.480000	27.80	11.3	56	28.2	QP	L1	GND
5.510000	25.90	11.5	60	34.1	QP	L1	GND
14.895000	23.50	11.6	60	36.5	QP	L1	GND

MEASUREMENT RESULT: "F-1412-1_fin2"

2019-9-27 11:23

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line	PE
0.150000	46.10	10.8	56	9.9	AV	L1	GND
0.444000	27.10	11.0	47	19.9	AV	L1	GND
1.056000	21.10	11.1	46	24.9	AV	L1	GND
4.035000	18.00	11.4	46	28.0	AV	L1	GND
5.510000	16.40	11.5	50	33.6	AV	L1	GND
14.895000	15.60	11.6	50	34.4	AV	L1	GND

13. ANTENNA REQUIREMENT

13.1. The Requirement

According to Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

13.2. Antenna Construction

Device is equipped with permanent attached antenna, which isn't displaced by other antenna. The Max Antenna gain of EUT is -0.5dBi. Therefore, the equipment complies with the antenna requirement of Section 15.203.



Antenna

******* End of Test Report *******