



FCC ID: 2AUS4-NFA18822CS5
Report No.: TMWK2108000372KR

Page 1 / 11
Rev.: 01

KDB 447498 D03
47 C.F.R. Part 1, Subpart I, Section 1.1310
47 C.F.R. Part 2, Subpart J, Section 2.1091

RF EXPOSURE REPORT

For

Neat Pad

Model: A1

Trade Name: neat.

Issued to

Neatframe AS
Martin Linges Vei 25 Fornebu 1364 Norway

Issued by

Compliance Certification Services Inc.
Wugu Laboratory
No.11, Wugong 6th Rd., Wugu Dist.,
New Taipei City, Taiwan. (R.O.C.)
Issue Date: September 14, 2021

Note: This document may be altered or revised by Compliance Certification Services Inc. personnel only, and shall be noted in the revision section of the document. The client should not use it to claim product endorsement by TAF, NIST or any government agencies. The test results in the report only apply to the tested sample.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com.tw/Terms-and-Conditions> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com.tw/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of client's instruction, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced, except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.



Report No.: TMWK2108000372KR

Page 2 / 11
Rev.: 01

Revision History

Rev.	Issue Date	Revisions	Effect Page	Revised By
00	September 14, 2021	Initial Issue	ALL	Doris Chu



Report No.: TMWK2108000372KR

Page 3 / 11
Rev.: 01

TABLE OF CONTENTS

1. TEST RESULT CERTIFICATION 4

2. LIMIT 5

3. EUT SPECIFICATION 6

4. TEST RESULTS 9

5. MAXIMUM PERMISSIBLE EXPOSURE.....10

6. SIMULTANEOUS TRANSMISSION SAR ANALYSIS.....11

1. TEST RESULT CERTIFICATION

We hereby certify that:

The above equipment was tested by Compliance Certification Services Inc. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.10: 2013 and the energy emitted by the sample EUT tested as described in this report is in compliance with the requirements of FCC Rules Part 15.207, 15.209, 15.247.

The test results of this report relate only to the tested sample EUT identified in this report.

APPLICABLE STANDARDS	
STANDARD	TEST RESULT
KDB 447498 D03 47 C.F.R. Part 1, Subpart I, Section 1.1310 47 C.F.R. Part 2, Subpart J, Section 2.1091	No non-compliance noted
Statements of Conformity	
Determination of compliance is based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.	

Approved by:



Kevin Tsai
Deputy Manager
Compliance Certification Services Inc.

2. LIMIT

According to §15.247(i), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess of the Commission's guidelines. See § 1.1307(b)(1) of this chapter.

§1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in §1.1307(b), except in the case of portable devices which shall be evaluated according to the provisions of FCC part 2.1093 of the chapter.

TABLE 1 - LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposure				
0.3-3.0	614	1.63	* 100	6
3.0-30	1842/f	4.89/f	* 900/f ²	6
30-300	61.4	0.163	1.0	6
300-1,500			f/300	6
1,500-100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	* 100	30
1.34-30	824/f	2.19/f	* 180/f ²	30
30-300	27.5	0.073	0.2	30
300-1,500			f/1500	30
<u>1,500-100,000</u>			1.0	30

f = frequency in MHz

* = Plane-wave equivalent power density

Note 1 to Table 1: Occupational/controlled exposure limits apply in situations in which persons are exposed as a consequence of their employment provided those persons are fully aware of the potential for exposure and can exercise control over their exposure. Limits for occupational/controlled exposure also apply in situations when a person is transient through a location where occupational/controlled limits apply provided he or she is made aware of the potential for exposure.

Note 2 to Table 2: General population/uncontrolled exposure limits apply in situations in which the general public may be exposed, or in which persons who are exposed as a consequence of their employment may not be fully aware of the potential for exposure or cannot exercise control over their exposure.



Report No.: TMWK2108000372KR

Page 6 / 11

Rev.: 01

3. EUT SPECIFICATION

EUT	Neat Pad
Model	A1
Trade Name	neat.
Model Discrepancy	N/A
Received Date	August 13, 2021
Frequency band (Operating)	☒ Bluetooth: 2402MHz-2480MHz ☒ 802.11b/g/n HT20: 2412MHz ~ 2462 MHz ☒ 802.11a/n HT20: 5180MHz ~ 5240MHz / 5260 ~ 5320MHz / 5500 ~ 5700MHz / 5745MHz ~ 5825MHz ☒ 802.11n HT40: 5190MHz ~ 5230MHz / 5270 ~ 5310MHz / 5510 ~ 5670MHz / 5755MHz ~ 5795MHz ☒ 802.11ac VHT80: 5210MHz / 5290MHz / 5530 MHz~5610MHz / 5775MHz ☐ Others
Device category	☐ Portable (<20cm separation) ☒ Mobile (>20cm separation) ☐ Others
Exposure classification	☐ Occupational/Controlled exposure ($S = 5\text{mW/cm}^2$) ☒ General Population/Uncontrolled exposure ($S=1\text{mW/cm}^2$)

Report No.: TMWK2108000372KR

Antenna Specification	FPC Antenna				
	BT: FPA2927-2A: Gain :0.89 dBi				
	WIFI 2.4GHz: FPA2927-1A: Gain :0.85 dBi FPA2927-2A: Gain :0.89 dBi Power Directional Gain: 3.88 dBi				
	WIFI 5GHz: FPA2927-1A: 5150~5250: Gain: 2.63 dBi 5250~5350: Gain: 2.63 dBi 5470~5725: Gain: 1.89 dBi 5725~5850: Gain: 3.11 dBi FPA2927-2A: 5150~5250: Gain: 1.60 dBi 5250~5350: Gain: 1.60 dBi 5470~5725: Gain: 2.42 dBi 5725~5850: Gain: 2.92 dBi Power Directional Gain: 5150~5250: Gain: 5.14 dBi 5250~5350: Gain: 5.14 dBi 5470~5725: Gain: 5.17 dBi 5725~5850: Gain: 6.03 dBi				
	BT:	Gain :	0.89 dBi	(Numeric gain:	1.23) Worst
	2.4GHz:	Directional Gain :	3.88 dBi	(Numeric gain:	2.44) Worst
	5GHz:	Directional Gain :			
		5150~5250: Gain:	5.14 dBi	(Numeric gain:	3.27) Worst
		5250~5350: Gain:	5.14 dBi	(Numeric gain:	3.27) Worst
		5470~5725: Gain:	5.17 dBi	(Numeric gain:	3.29) Worst
		5725~5850: Gain:	6.03 dBi	(Numeric gain:	4.01) Worst

Report No.: TMWK2108000372KR

Maximum Measurement Average Power	BT	9.13 dBm	(8.185 mW)
	2.4GHz		
	IEEE 802.11b Mode:	19.29 dBm	(84.918 mW)
	IEEE 802.11g Mode:	19.15 dBm	(82.224 mW)
	IEEE 802.11n HT 20 Mode:	18.64 dBm	(73.114 mW)
	IEEE 802.11n HT 40 Mode:	18.87 dBm	(77.090 mW)
	5GHz		
	IEEE 802.11a Mode:	20.20 dBm	(104.713 mW)
	IEEE 802.11n HT 20 Mode:	20.47 dBm	(111.429 mW)
	IEEE 802.11n HT 40 Mode:	19.47 dBm	(88.512 mW)
	IEEE 802.11ac VHT 80 Mode:	17.41 dBm	(55.081 mW)
Maximum tune up power	BT	9.50 dBm	(8.913 mW)
	2.4GHz		
	IEEE 802.11b Mode:	20.00 dBm	(100.000 mW)
	IEEE 802.11g Mode:	19.50 dBm	(89.125 mW)
	IEEE 802.11n HT 20 Mode:	19.00 dBm	(79.433 mW)
	IEEE 802.11n HT 40 Mode:	19.50 dBm	(89.125 mW)
	5GHz		
	IEEE 802.11a Mode:	21.00 dBm	(125.893 mW)
	IEEE 802.11n HT 20 Mode:	21.00 dBm	(125.893 mW)
	IEEE 802.11n HT 40 Mode:	20.00 dBm	(100.000 mW)
	IEEE 802.11ac VHT 80 Mode:	18.00 dBm	(63.096 mW)
Evaluation applied	☒ MPE Evaluation* ☐ SAR Evaluation ☐ N/A		

Remark:

- For more details, please refer to the User's manual of the EUT.
- Disclaimer: Antenna information is provided by the applicant, test results of this report are applicable to the sample EUT received.
- The tune up power referred the AVG power of the test report TMWK2108000370KR, TMWK2108000371KR, TMWK2109000513KR and TMWK2109000514KR for RF Exposure assessment purpose.

4. TEST RESULTS

No non-compliance noted.

Calculation

Given $E = \frac{\sqrt{30 \times P \times G}}{d}$ & $S = \frac{E^2}{377}$

Where E = Field strength in Volts / meter

P = Power in Watts

G = Numeric antenna gain

d = Distance in meters

S = Power density in milliwatts / square centimeter

Combining equations and re-arranging the terms to express the distance as a function of the remaining variables yields:

$$S = \frac{30 \times P \times G}{377 d^2}$$

Changing to units of mW and cm, using:

P (mW) = P (W) / 1000 and

d (cm) = d(m) / 100

Yields

$$S = \frac{30 \times (P/1000) \times G}{377 \times (d/100)^2} = 0.0796 \times \frac{P \times G}{d^2} \text{Equation 1}$$

Where d = Distance in cm

P = Power in mW

G = Numeric antenna gain

S = Power density in mW / cm²

5. MAXIMUM PERMISSIBLE EXPOSURE

Substituting the MPE safe distance using $d = 20$ cm into Equation 1:

$$S = 0.000199 \times P \times G$$

Where P = Power in mW

G = Numeric antenna gain

S = Power density in mW / cm²

BT:

Ch.	Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm ²	Limit (mW/cm2)
0	2402	8.913	1.23	20	0.0022	1

IEEE 802.11b mode:

Ch.	Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm ²	Limit (mW/cm2)
11	2462	100.000	2.44	20	0.0486	1

IEEE 802.11g mode:

Ch.	Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm ²	Limit (mW/cm2)
11	2462	89.125	2.44	20	0.0433	1

IEEE 802.11n HT20 mode:

Ch.	Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm ²	Limit (mW/cm2)
6	2437	79.433	2.44	20	0.0386	1

IEEE 802.11n HT40 mode:

Ch.	Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm ²	Limit (mW/cm2)
6	2437	89.125	2.44	20	0.0433	1

IEEE 802.11a mode:

Ch.	Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm ²	Limit (mW/cm2)
52	5260	125.893	3.27	20	0.0819	1

IEEE 802.11n HT20 mode:

Ch.	Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm ²	Limit (mW/cm2)
64	5320	125.893	3.27	20	0.0819	1

IEEE 802.11n HT40 mode:

Ch.	Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm ²	Limit (mW/cm2)
62	5310	100.000	3.27	20	0.0651	1

IEEE 802.11ac VHT80 mode:

Ch.	Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm ²	Limit (mW/cm2)
42	5210	63.096	3.27	20	0.0411	1

6. SIMULTANEOUS TRANSMISSION SAR ANALYSIS

Both of the WiFi and Bluetooth can transmit simultaneously, the formula of calculated the MPE is:

$$\text{CPD1} / \text{LPD1} + \text{CPD2} / \text{LPD2} + \dots \text{etc.} < 1$$

CPD = Calculation power density

LPD = Limit of power density

WiFi + Bluetooth

Therefore, the worst-case situation is $0.0022 / 1 + 0.0819 / 1 = 0.0841$, which is less than “1”.

--End of Report--