

FCC RF EXPOSURE REPORT

FCC ID: 2AUTE-2TS25L

Project No. : 2510C254

Equipment : 1) Portable Photo Printer
2) Mini Photo Printer
3) Dye-Sublimation Photo Printer
4) Photo Printer

Brand Name :  Hanin or  HPRT or  iDPRT, PRT

Test Model : HCP-2TS25L

Model Name : HCP-2TS25L, CP2200, CP2201, CP2200 Pro, CP2200-L, D2200, DD20, PIX2200, PIX22, PIX22L, PIX22 Pro, Zeva 2200, W2200, W22

Hardware Version : Z5S-MBC

Software Version : CP2200_V1.01.05

Applicant : Xiamen Hanin Co., Ltd.

Address : Room 305A, Angye Building, Pioneering Park, Torch High-tech Zone, Xiamen, China

Manufacturer : Xiamen Hanin Co., Ltd.

Address : Room 305A, Angye Building, Pioneering Park, Torch High-tech Zone, Xiamen, China

Factory : Xiamen Hanin Co., Ltd.

Address : No.96, RongYuan Road, Tong'an District, Xiamen City, Fujian Province, P.R. China

Date of Receipt : Oct. 28, 2025

Date of Test : Nov. 01, 2025 ~ Nov. 22, 2025


Issued Date : Dec. 26, 2025

Test Sample : Engineering Sample No.: DG92025102818

Standard(s) : FCC Guidelines for Human Exposure IEEE C95.1 & KDB447498 D01 v06

The above equipment has been tested and found compliance with the requirement of the relative standards by BTL Inc. (Dongguan)

Prepared by : 
Chella Zheng

Approved by : 
Chay Cai

REVISION HISTORY

Report No.	Version	Description	Issued Date	Note
BTL-FCCP-3-2510C254	R00	Original Report.	Dec. 26, 2025	Valid

1. GENERAL CONCLUSION

According to FCC KDB447498 D01, Appendix A, SAR Test Exclusion Thresholds for 100 MHz – 6 GHz and ≤ 50 mm, the 1-g and 10-g SAR test exclusion thresholds are determined by the following:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}]$
 ≤ 3.0 for 1-g SAR, and ≤ 7.5 for 10-g extremity SAR, where

- $f(\text{GHz})$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

Appendix A - SAR Test Exclusion Thresholds for 100 MHz - 6 GHz and ≤ 50 mm											
MHz	5	10	15	20	25	30	35	40	45	50	mm
150	39	77	116	155	194	232	271	310	349	387	SAR Test Exclusion Thresholds (mW)
300	27	55	82	110	137	164	192	219	246	274	
450	22	45	67	89	112	134	157	179	201	224	
835	16	33	49	66	82	98	115	131	148	164	
900	16	32	47	63	79	95	111	126	142	158	
1500	12	24	37	49	61	73	86	98	110	122	
1900	11	22	33	44	54	65	76	87	98	109	
2450	10	19	29	38	48	57	67	77	86	96	
3600	8	16	24	32	40	47	55	63	71	79	
5200	7	13	20	26	33	39	46	53	59	66	
5400	6	13	19	26	32	39	45	52	58	65	
5800	6	12	19	25	31	37	44	50	56	62	

2. TABLE FOR FILED ANTENNA

Ant.	Manufacturer	Model Name	Antenna Type	Connector	Gain (dBi)
1	Xiamen Hanin Co.,Ltd.	HCP-2TS25F	PCB	N/A	-5.89

Note:

The antenna gain is provided by the manufacturer.

3. TEST RESULTS

Function	Frequency (MHz)	Max. Output Power (dBm)	Max. Tune-up Power (dBm)	Max. Tune-up Power (mW)	Exclusion Thresholds	Limit	Result
BT	2440	5.37	5.37	3.4435	1.0758	3	SAR Test Exclusion
BLE	2402	5.30	5.30	3.3884	1.0503	3	SAR Test Exclusion

Note: No SAR evaluation required since transmitter power is below FCC threshold.

End of Test Report