

RF EVALUATION TEST REPORT

Applicant/ Manufacturer..... : Xiamen Hanin Co.,Ltd.

Address..... : Room 305A, Angye Building, Pioneering Park Torch High-tech, Zone Xiamen
China

Factory..... : Xiamen Hanin Co.,Ltd.

Address..... : No.96, Rongyuan Road, Tong'an District, Xiamen City,Fujian Province, P.R.
China

Product Name..... : Thermal Receipt Printer

Brand Name..... : N/A

Model No. : TP805, TP806, P35, FFSP5000+, FFSP5U01+, FFSP5U02+, FFSP5U03+,
FFSP5U04+, FFSP5U05+, FFSP5X01+, FFSP5X02+, FFSP5X03+,
FFSP5X04+, FFSP5X05+, POS80B, P36, FFSP6000+, FFSP6U01+,
FFSP6U02+, FFSP6U03+, FFSP6U04+, FFSP6U05+, FFSP6X01+,
FFSP6X02+, FFSP6X03+, FFSP6X04+, FFSP6X05+, POS80C, HDR3D1400,
HDR3D1401 (For model difference refer to section 2)

FCC ID..... : 2AUTE-P322


Measurement Standard..... : 47 CFR PART 2, Section 2.1091

Receipt Date of Samples.... : January 02, 2024

Date of Tested..... : January 02, 2024 to August 20, 2025

Date of Report..... : December 30, 2025

This report shows that above equipment is technically compliant with the requirements of the standards above.
All test results in this report apply only to the tested sample(s). Without prior written approval of Dongguan Nore
Testing Center Co., Ltd, this report shall not be reproduced except in full.



Prepared by

Jenny Liu / Project Engineer



Approved by

Iori Fan / Authorized Signatory

Table of Contents

1. General Description of EUT	4
2. Test Facility and Location	6
3. Applicable Standards and References.....	7
4. Maximum Permissible Exposure Limit	8
5. RF Exposure Evaluation Results	11

[illegible]

1. General Description of EUT

Product Information	
Product Name:	Thermal Receipt Printer
Main Model Name:	TP806
Additional Model Name:	TP805, P35, FFSP5000+, FFSP5U01+, FFSP5U02+, FFSP5U03+, FFSP5U04+, FFSP5U05+, FFSP5X01+, FFSP5X02+, FFSP5X03+, FFSP5X04+, FFSP5X05+, POS80B, P36, FFSP6000+, FFSP6U01+, FFSP6U02+, FFSP6U03+, FFSP6U04+, FFSP6U05+, FFSP6X01+, FFSP6X02+, FFSP6X03+, FFSP6X04+, FFSP6X05+, POS80C, HDR3D1400, HDR3D1401
Model difference:	These models have the same circuitry, electrical mechanical, PCB Layout and physical construction. The difference is model name due to marketing purpose.
S/N:	TP806021440801
Brand Name:	N/A
Hardware Version:	TP803MB
Software Version:	TP803MB_V1
Rating:	DC 24V 2A come from adapter
Typical Arrangement:	Tabletop
I/O Port:	Refer to the user manual
Accessories Information	
Adapter 1:	Manufacturer: ShenZhen KunXing Technology Co., Ltd. Model: AP152G-240200 Input: AC 100-240V 50/60Hz 2.0A Output: DC 24.0V 2.0A 48.0W
Adapter 2:	Manufacturer: FOSHAN SHUNDE GUANYUDA POWER SUPPLY CO., LTD Model: GM53-240200-F Input: AC 100-240V 50/60Hz 2.0A Output: DC 24.0V 2.0A 48.0W
Cable:	Power cord: 1m, unshielded, detachable DC line (Adapter): 1.50m, unshielded, undetachable USB line: 1.50m, unshielded, detachable
Other:	N/A

Additional Information	
Note:	According to the model differences and the manufacturer's requirement, all tests were performed on model TP806.
Remark:	All the information above are provided by the manufacturer. More detailed feature of the EUT please refers to the user manual
Technical Specification (BDR EDR)	
Bluetooth Version:	V5.2
Frequency Range:	2402-2480MHz
Modulation Type:	GFSK, $\pi/4$ -DQPSK, 8DPSK
Number of Channel:	79
Channel Space:	1MHz
Antenna Type:	PCB Antenna
Number of Antenna	1
Antenna Gain:	-1.08 dBi (Declared by the manufacturer)
Technical Specification (BLE)	
Bluetooth Version:	V5.2
Frequency Range:	2402-2480MHz
Modulation Type:	GFSK
Number of Channel:	40
Channel Space:	2MHz
Antenna Type:	PCB antenna
Number of Antenna	1
Antenna Gain:	-1.08 dBi (Declared by the manufacturer)
RF PHY Support:	1Mbps

2. Test Facility and Location

Test Site	:	Dongguan Nore Testing Center Co., Ltd. (Dongguan NTC Co., Ltd.)
Accreditations and Authorizations	:	The Laboratory has been assessed and proved to be in compliance with CNAS/CL01 Listed by CNAS, August 13, 2018 The Certificate Registration Number is L5795. The Certificate is valid until August 13, 2030 The Laboratory has been assessed and proved to be in compliance with ISO17025 Listed by A2LA, November 01, 2017 The Certificate Registration Number is 4429.01 The Certificate is valid until December 31, 2027 Listed by FCC, November 06, 2017 Test Firm Registration Number: 907417 Listed by Industry Canada, June 08, 2017 The Certificate Registration Number. Is 46405-9743A
Test Site Location	:	Building D, Gaosheng Science and Technology Park, Hongtu Road, Nancheng District, Dongguan City, Guangdong Province, China
Test Site Location	:	Room 101, 1101, Building 2, No. 61, Hongmei Section, Wangsha Road, Hongmei Town, Dongguan, Guangdong, People's Republic of China

3. Applicable Standards and References

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

Test Standards:

47 CFR Part 1, 1.1307

47 CFR Part 2, 2.1091

KDB 447498 D04 v01

4. Maximum Permissible Exposure Limit

According to 47 CFR Part 1, 1.1307, for single RF sources (i.e., any single fixed RF source, mobile device, or portable device, as defined in paragraph (b)(2) of this section): A single RF source is exempt if: 47 CFR Part 1, 1.1307

(A) The available maximum time- averaged power is no more than 1 mW, regardless of separation distance. This exemption may not be used in conjunction with other exemption criteria other than those in paragraph (b)(3)(ii)(A) of this section. Medical implant devices may only use this exemption and that in paragraph (b)(3)(ii)(A);

(B) Or the available maximum time- averaged power or effective radiated power (ERP), whichever is greater, is less than or equal to the threshold P_{th} (mW) described in the following formula. This method shall only be used at separation distances (cm) from 0.5 centimeters to 40 centimeters and at frequencies from 0.3 GHz to 6 GHz (inclusive). P_{th} is given by:

$$P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}} (d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases}$$

Where,

$$x = -\log_{10} \left(\frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right) \text{ and } f \text{ is in GHz;}$$

And,

$$ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases}$$

d = the minimum separation distance (cm) in any direction from any part of the device antenna(s) or radiating structure(s) to the body of the device user.

For multiple RF sources: Multiple RF sources are exempt if:

(A) The available maximum time- averaged power of each source is no more than 1 mW and there is a separation distance of two centimeters between any portion of a radiating structure operating and the nearest portion of any other radiating structure in the same device, except if the sum of multiple sources is less than 1 mW during the time-averaging period, in which case they may be treated as a single source (separation is not required). This exemption may not be used in conjunction with other exemption criteria other than those in paragraph (b)(3)(i)(A) of this section. Medical implant devices may only use this exemption and that in paragraph (b)(3)(i)(A).

(B) in the case of fixed RF sources operating in the same time-averaging period, or of multiple mobile or portable RF sources within a device operating in the same time averaging period, if the sum of the fractional contributions to the applicable thresholds is less than or equal to 1 as indicated in the following equation.

$$\sum_{i=1}^a \frac{P_i}{P_{th,i}} + \sum_{j=1}^b \frac{ERP_j}{ERP_{th,j}} + \sum_{k=1}^c \frac{Evaluated_k}{Exposure Limit_k} \leq 1$$

Where,

a = number of fixed, mobile, or portable RF sources claiming exemption using paragraph (b)(3)(i)(B) of this section for P_{th} , including existing exempt transmitters and those being added.

b = number of fixed, mobile, or portable RF sources claiming exemption using paragraph (b)(3)(i)(C) of this section for Threshold ERP, including existing exempt transmitters and those being added.

c = number of existing fixed, mobile, or portable RF sources with known evaluation for the specified minimum distance including existing evaluated transmitters.

P_i = the available maximum time-averaged power or the ERP, whichever is greater, for fixed, mobile, or portable RF source i at a distance between 0.5 cm and 40 cm (inclusive).

$P_{th,i}$ = the exemption threshold power (P_{th}) according to paragraph (b)(3)(i)(B) of this section for fixed, mobile, or portable RF source i .

ERP_j = the ERP of fixed, mobile, or portable RF source j .

$ERP_{th,j}$ = exemption threshold ERP for fixed, mobile, or portable RF source j , at a distance of at least $\lambda/2\pi$ according to the applicable formula of paragraph (b)(3)(i)(C) of this section.

Evaluated_k= the maximum reported SAR or MPE of fixed, mobile, or portable RF source k either in the device or at the transmitter site from an existing evaluation at the location of exposure.

Exposure Limit_k= either the general population/uncontrolled maximum permissible exposure (MPE) or specific absorption rate (SAR) limit for each fixed, mobile, or portable RF source k, as applicable from §1.1310 of this chapter.

5. RF Exposure Evaluation Results

Single RF Source								
Mode	Frequency (MHz)	Max. Conducted Power (dBm)	Antenna Gain (dBi)	Max. EIRP (dBm)	Max. ERP (dBm)	Max. Conducted Power (mW)	Separation Distance (cm)	Part 1.1307 Option (B) P _{th} (mW)
GFSK	2402	2.02	-1.08	0.940	-1.210	1.592	20	3060
	2441	4.31	-1.08	3.23	1.080	2.698	20	3060
	2480	6.06	-1.08	4.98	2.830	4.036	20	3060
Π4/-DQPSK	2402	2.06	-1.08	0.98	-1.170	1.607	20	3060
	2441	4.39	-1.08	3.310	1.160	2.748	20	3060
	2480	5.84	-1.08	4.76	2.610	3.837	20	3060
8DPSK	2402	1.95	-1.08	0.87	-1.280	1.567	20	3060
	2441	4.24	-1.08	3.16	1.010	2.655	20	3060
	2480	5.90	-1.08	4.82	2.670	3.890	20	3060
BLE	2402	-6.857	-1.08	-7.937	-10.087	0.206	20	3060
	2440	-4.005	-1.08	-5.085	-7.235	0.398	20	3060
	2480	-3.305	-1.08	-4.385	-6.535	0.467	20	3060

Conclusion:

According to 47 CFR §1.1307 (b)(3)(i)(B), the RF exposure analysis concludes that the product is compliant with the FCC RF exposure requirements in mobile exposure condition.

---End---