

Test Report

Product	Tool Recognition HUB with Bluetooth LE Transceiver		
Name and address of the applicant	SVAB Hydraulik AB Ulvsättersgatan 2 69491 Hallsberg, Sweden		
Name and address of the manufacturer	SVAB Hydraulik AB Ulvsättersgatan 2 69491 Hallsberg, Sweden		
Model	Quantum HUB		
Rating	12V/24V DC (100mA/55mA, 1.32W)		
Trademark	SVAB		
Serial number	/		
Additional information	Bluetooth Low Energy		
Tested according to	FCC Part 15.247 Frequency Hopping Transmitters / Digital Transmission Systems Industry Canada RSS-247, Issue 2 Digital Transmission Systems (DTSS), Frequency Hopping Systems (FHSs) and Licence-Exempt Local Area Network (LE-LAN) Devices		
Order number	371810		
Tested in period	2019-07-23 to 2019-07-23		
Issue date	2020-12-18		
Name and address of the testing laboratory	 Instituttveien 6 Kjeller, Norway CAB Number: FCC: NO0001 ISED: NO0470   An accredited technical test executed under the Norwegian accreditation scheme		
 Prepared by [Frode Sveinsen]  Approved by [G.Suhanthakumar]			
This report shall not be reproduced except in full without the written approval of Nemko. Opinions and interpretations expressed within this report are not part of the current accreditation. This report was originally distributed electronically with digital signatures. For more information contact Nemko.			

CONTENTS

1	INFORMATION	3
1.1	Test Item.....	3
1.2	Normal test condition	4
1.3	Test Engineer	4
1.4	Antenna Requirement.....	4
1.5	Test configuration	4
1.6	Comments	4
2	TEST REPORT SUMMARY	5
2.1	General.....	5
2.2	Test Summary	6
3	TEST RESULTS.....	7
3.1	Occupied Bandwidth (99% BW).....	7
3.2	DTS Bandwidth.....	10
3.3	Peak Power Output.....	13
3.4	Power Spectral Density (PSD).....	17
3.5	Conducted Emissions at Antenna Connector	20
3.6	Restricted Bands of operation.....	27
3.7	Radiated Emissions, Band Edge	28
3.8	Radiated Emissions, 30 – 1000 MHz.....	30
3.9	Radiated Emissions, 1 – 26 GHz	32
4	Measurement Uncertainty.....	48
5	LIST OF TEST EQUIPMENT.....	49
6	BLOCK DIAGRAM.....	50
6.1	Conducted Tests.....	50
6.2	Test Site Radiated Emission.....	50

1 INFORMATION

1.1 Test Item

Name	SVAB
FCC ID	2AUTR-963
ISED ID	25895-963
Model/version	Quantum HUB
Serial number	N/A
Hardware identity and/or version	V.3.55
Software identity and/or version	V.3.2.5
Frequency Range	2402–2480 MHz
Number of Channels	40
Operating Modes	Bluetooth Low Energy
Type of Modulation	Digital (Gaussian Frequency Shift Keying)
Conducted Output Power	9.1 mW (Peak)
Antenna Connector	None
Number of Antennas	1
Antenna Diversity Supported	No
Power Supply	12/24 V _{DC} , 100 mA / 55 mA, 1.32W
Connections	4x M8 connectors, CAN1, CAN2, I/O and DC Power input
Highest Clock Frequency	120 MHz

Description of Test Item

The tested device is a BT Low Energy Hub.

Description	Brand	Model	Regulatory Information
Bluetooth Controller	Texas Instruments	Dual-Mode Bluetooth Controller	N/A
CPU	ST Microelectronics	High-performance ARM Cortex-M3 CPU	N/A

1.2 Normal test condition

Temperature:	20–25 °C
Relative humidity	20–50 %
Normal test voltage	14 V _{DC} (Nominal Voltage)

All tests were performed with the EUT powered from a regulated power supply.

Values above are the limit registered during the test period.

1.3 Test Engineer

Frode Sveinsen

1.4 Antenna Requirement

Does the EUT have detachable antenna(s)?	☐ YES	☒ NO
If detachable, is the antenna connector(s) non-standard?	☐ YES	☐ NO
The tested equipment has only integral antennas. Conducted tests with a temporary antenna connector.		

Requirement: FCC 15.203, 15.204

1.5 Test configuration

The EUT was programmed from a computer with the Texas Instruments SmartRF Studio software via a USB interface and the TI test-jig.

The EUT was programmed to transmit continuously with GFSK modulation on the selected channel during all tests.

All tests were performed with Maximum Output Power selected.

1.6 Comments

All tested parameters are passed.

2 TEST REPORT SUMMARY

2.1 General

All measurements are traceable to national standards.

The tests were conducted for demonstrating compliance with FCC CFR 47 Part 15, paragraph 15.247 and Industry Canada RSS-247 Issue 2 and RSS-GEN Issue 5.

Tests were performed in accordance with ANSI C63.4-2014 and ANSI C63.10-2013.

Radiated tests were made in a semi-anechoic chamber at measuring distance of 3m.

A description of the test facility is on file with FCC and ISSED.

☒ New Submission

☒ Production Unit

☐ Class II Permissive Change

☐ Pre-production Unit

DTS Equipment Code

☐ Family Listing



THIS TEST REPORT APPLIES ONLY TO THE ITEM(S) AND CONFIGURATIONS TESTED.

Deviations from, additions to, or exclusions from the test specifications are described in "Summary of Test Data".

Nemko Group authorizes the above named entity to reproduce this report provided it is reproduced in its entirety and for use by the entity's employees only. Any reproduction of parts of this report requires approval in writing from Nemko Group.

Any use that a third party makes of this report, or any reliance on or decisions to be made based on it, are the responsibility of such third parties. Nemko Group accepts no responsibility for damages suffered by any third party caused by decisions made or actions based on this report.

2.2 Test Summary

Name of test	FCC Part 15 reference	RSS-247 Issue 2, RSS-GEN Issue 5 reference	Test Method ANSI C63.10-2013 Reference	Result
Supply Voltage Variations	15.31(e)	6.11 (RSS-GEN)	5.13	Complies
Antenna Requirement	15.203	6.8 (RSS-GEN)	5.8	Complies
Power Line Conducted Emission	15.107(a) 15.207(a)	7.2 / 8.8 (RSS-GEN)	N/A	N/A ¹
Occupied Bandwidth (99% BW)	N/A	6.7 (RSS-GEN)	6.9.2	Complies
DTS Bandwidth	15.247(a)(2)	5.2 (1) (RSS-247)	11.8	Complies
Peak Power Output	15.247(b)	5.4 (RSS-247)	11.9.1.2	Complies
Power Spectral Density	15.247(d)	5.2 (2) (RSS-247)	11.10	Complies
Spurious Emissions (Antenna Conducted)	15.247(c)	5.5 (RSS-247)	11.11	Complies
Spurious Emissions (Radiated)	15.247(c) 15.109(a) 15.209(a)	5.5 (RSS-247) 7.3 (RSS-GEN) 8.9 (RSS-GEN)	11.12	Complies

¹ The EUT is not intended for connection to the mains

Revision history

Revision	Date	Comment	Sign
00	2020-08-21	First edition	FS
01	2020-11-16	Added info about test configuration Updated duty cycle correction factor	FS
02	2020-12-18	Updated info about test configuration.	FS

3 TEST RESULTS

3.1 Occupied Bandwidth (99% BW)

RSS-GEN Issue 5, Clause 6.7

Test Results: Complies


Measurement Data:

Carrier Frequency	Occupied Bandwidth (99% BW)
2402 MHz	1.03 MHz
2440 MHz	1.03 MHz
2480 MHz	1.03 MHz

See attached plots.

Requirements:


No limit specified.



Occupied Bandwidth, 99%, 2402 MHz



Occupied Bandwidth, 99%, 2440 MHz



Occupied Bandwidth, 99%, 2480 MHz

3.2 DTS Bandwidth

FCC Part 15.247 (a)(2)

RSS-247 Issue 2, Clause 5.2 (a)


Test Results: Complies

Measurement Data:


Modulation type and bitrate	Measured DTS Bandwidth (kHz)
2402 MHz	759
2440 MHz	749
2480 MHz	753

Requirements:


For Digital Transmission Systems in the 2400–2483.5 MHz band the minimum 6 dB bandwidth (DTS BW) shall be at least 500 kHz.



DTS Bandwidth, 2402 MHz



DTS Bandwidth, 2440 MHz



DTS Bandwidth, 2480 MHz

3.3 Peak Power Output

FCC 15.247 (b)

RSS-247 Issue 2, Clause 5.4 (d)

Test Results: Complies

Measurement Data:

Maximum Peak Power, Max Power			
	2402 MHz	2440 MHz	2480 MHz
Peak Conducted Power (dBm)	8.9	9.6	9.1
Peak Conducted Power (mW)	7.7	9.1	8.2
Peak Field Strength (dBμV/m @3m)	102.3	102.9	103.6
Peak Radiated power (calculated e.i.r.p.) (dBm)	7.1	7.6	8.4
Calculated Antenna Gain (dBi)	-1.8	-1.9	-0.8

Output Power reported is Maximum Peak Power.


See attached plots.

Requirements:


The maximum peak output power shall not exceed the following limits:

For Digital Transmission Systems in the 2400–2483.5 MHz band: 1 Watt

If transmitting antennas of directional gain greater than 6 dBi are used, the peak output power limit shall be reduced below the stated value above by the amount in dB that the directional gain of the antenna exceeds 6 dBi.




Conducted Power, 2402 MHz




Date: 22.JUL.2019 10:28:07

Maximum Field Strength, 2402 MHz




Conducted Power, 2440 MHz




Date: 22.JUL.2019 10:50:42

Maximum Field Strength, 2440 MHz



Conducted Power, 2480 MHz



Date: 22.JUL.2019 10:06:43

Maximum Field Strength, 2480 MHz

3.4 Power Spectral Density (PSD)

Para. No.: 15.247 (d)

Test Results: Passed

Measured and Calculated Data:

The measurement procedures PKPSD described in ANSI C63.10-2013 was used.


Carrier Frequency (MHz)	Power Spectral Density (dBm/3 kHz)
2402	-8.3
2440	-7.4
2480	-8.1

The measured values with 30 kHz RBW are corrected by a Bandwidth Correction Factor of -10 dB.


Values above have been corrected with 0.9 dB for cable loss.

Requirements:


The Power Spectral Density of a Digital Transmission System shall be no greater than +8 dBm in any 3 kHz band.



Power Spectral Density, 2402 MHz



Power Spectral Density, 2440 MHz



Power Spectral Density, 2480 MHz

3.5 Conducted Emissions at Antenna Connector

Para. No.: 15.247 (d)

Carrier Frequency	Highest Value (dBc)	Margin (dB)	Verdict
2402 MHz	> 45	> 25	Pass
2440 MHz	> 45	> 25	Pass
2480 MHz	> 45	> 25	Pass

Measured with Peak Detector


RF conducted power to 25 GHz: see attached plots.

Limit


Peak measurement	RMS averaging
20 dBc or more in 100 kHz bandwidth	30 dBc or more in 100 kHz bandwidth

Detector type shall be the same as used for measuring Output Power.


Attenuation below the general limits specified in part 15.209(a) is not required.




Conducted Emissions, 10–2350 MHz, 2402MHz




Conducted Emissions, 2350–2450 MHz, 2402MHz




Conducted Emissions, 2450–3000 MHz, 2402MHz




Conducted Emissions, 3000–25000 MHz, 2402MHz




Conducted Emissions, 10–2400 MHz, 2440MHz




Conducted Emissions, 2340–2540 MHz, 2440MHz




Conducted Emissions, 2500–25000 MHz, 2440MHz



Conducted Emissions, 10–2450 MHz, 2480MHz



Conducted Emissions, 2433.5–2533.5 MHz, 2480MHz



Conducted Emissions, 2500–25000 MHz, 2480MHz

3.6 Restricted Bands of operation

Restricted Bands of operation for FCC and ISSED are defined in FCC Part 15.205 and ISSED RSS-GEN, Issue 4 clause 8.10.

Generally, no fundamentals are allowed in the restricted bands and all emissions must comply with the limits in FCC 15.209 or RSS-GEN, Issue 5, clause 8.9.

FCC (MHz)	ISSED (MHz)	FCC (GHz)	ISSED (GHz)
0.090-0.110		0.96-1.24 1.3-1.427	0.96-1.427
0.495-0.505		1.435-1.6265	
2.1735-2.1905		1.6455-1.6465	
	3.020-3.026	1.660-1.710	
4.125-4.128		1.7188-1.7222	
4.17725-4.17775		2.2-2.3	
4.20725-4.20775		2.31-2.39	
	5.677-5.683	2.4835-2.5	
6.215-6.218		2.69-2.9	2.655-2.9
6.26775-6.26825		3.26-3.267	
6.31175-6.31225		3.332-3.339	
8.291-8.294		3.3458-3.358	
8.362-8.366		3.6-4.4	3.5-4.4
8.37625-8.38675		4.5-5.15	
8.41425-8.41475		5.35-5.46	
12.29-12.293		7.25-7.75	
12.51975-12.52025		8.025-8.5	
12.57675-12.57725		9.0-9.2	
13.36-13.41		9.3-9.5	
16.42-16.423		10.6-12.7	
16.69475-16.69525		13.25-13.4	
16.80425-16.80475		14.47-14.5	
25.5-25.67		15.35-16.2	
37.5-38.25		17.7-21.4	
73-74.6		22.01-23.12	
74.8-75.2		23.6-24.0	
108-121.94 123-138	108-138	31.2-31.8	
149.9-150.05		36.43-36.5	
156.52475-156.52525		Above 38.6	
156.7-156.9			
162.0125-167.17			
167.72-173.2			
240-285			
322-335.4			
399.9-410			
608-614			

Frequencies in **Bold** text are specific for FCC or ISSED, all other frequencies are common.

3.7 Radiated Emissions, Band Edge

FCC Part 15.209

Test Results: Complies

Measurement Data:

	Measured field strength (dBµV/m)		Limit	Margin	
	2390 MHz	2483.5 MHz	(dBµV/m)	(dB)	
Peak Detector	45.2	61.6	74	28.8	12.4
Average Detector	30.3	46.7	54	23.7	7.3

Band Edge is measured with the EUT transmitting on 2402 and 2480 MHz


Average values are calculated from Peak Values using the Duty Cycle correction factor.

See attached plots.

Duty Cycle Correction Factors


Maximum Duty Cycle: 17.92%

Duty Cycle Correction Factor: $-20 \cdot \log_{10}(17.92\%) = 14.9 \text{ dB}$



Date: 22.JUL.2019 10:29:59

Band Edge, Lower, Peak, 2402 MHz, Max Power



Date: 22.JUL.2019 10:05:41

Band Edge, Upper, Peak, 2480 MHz, Max Power

3.8 Radiated Emissions, 30 – 1000 MHz

FCC 15.205, 15.209

ISED RSS-GEN, Issue 5, Clause 8.9

Test Results: Complies

Measuring distance: 3m


Detector: Peak

Tested in test mode with EUT transmitting on channel 19.

See attached plots.


Requirements/Limit

FCC	Part 15.209 @ frequencies defined in §15.205	
ISED	RSS-GEN Issue 5, clause 8.9 @ frequencies defined in clause 8.10	
	Radiated emission limit @3 meters	
Frequency (MHz)	Quasi Peak (µV/m)	Quasi Peak (dBµV/m)
30 – 88	100	40.0
88 – 216	150	43.5
216 – 960	200	46.0
960 - 1000	500	54.0



Date: 22.JUL.2019 09:01:02

Radiated Emissions, 30 – 1000 MHz, 2440 MHz, EUT V, VP



Date: 22.JUL.2019 09:03:53

Radiated Emissions, 30 – 1000 MHz, 2440 MHz, EUT V, HP

3.9 Radiated Emissions, 1 – 26 GHz

FCC 15.205, 15.209

ISED RSS-GEN, Issue 5, Clause 8.9

Test Results: Complies

Measurement Data:

Measuring distance: 3 m (1–18 GHz)
1 m (18-26 GHz)

Bandwidths: RBW=1MHz / VBW=3MHz

Measured values:

Frequency (MHz)	Channel	Polarization	Peak (dBμV/m)	Average (dBμV/m)	Peak Margin (dB)	Av Margin (dB)
4804	0	V	64.0	44.0	10.0	10.0
4880	19	V	60.6	40.6	13.4	13.4
4960	39	V	65.3	45.3	8.7	8.7
7206	0	V	63.8	43.8	10.2	10.2
7320	19	V	60.0	40.0	14.0	14.0
7440	39	V	62.1	42.1	11.9	11.9
9608	0	V	55.7	35.7	18.3	18.3
9760	19	V	61.5	41.5	12.5	12.5
9920	39	V	53.8	33.8	20.2	20.2
12010	0	V	60.6	40.6	13.4	13.4
12200	19	V	53.5	33.5	20.5	20.5
12400	39	V	58.6	38.6	15.4	15.4


All measurements were performed with the EUT transmitting on a fixed channel.

Antenna factor, amplifier gain and cable loss are included in spectrum analyzer "Transducer factor".

See plots.


Requirements/Limit

FCC	Part 15.209 @ frequencies defined in §15.205	
ISED	RSS-GEN Issue 5, clause 8.9 @ frequencies defined in clause 8.10	
	Radiated emission limit @3 meters	
Frequency (MHz)	Average Detector (dBμV/m)	Peak Detector (dBμV/m)
1 – 26 GHz	54.0	74.0




Date: 22.JUL.2019 10:33:54

Radiated Emissions, 1000 – 4000 MHz, 2402 MHz, EUT V, VP




Date: 22.JUL.2019 10:35:49

Radiated Emissions, 1000 – 4000 MHz, 2402 MHz, EUT V, HP




Date: 22.JUL.2019 10:54:20

Radiated Emissions, 1000 – 4000 MHz, 2440 MHz, EUT V, VP




Date: 22.JUL.2019 10:56:15

Radiated Emissions, 1000 – 4000 MHz, 2440 MHz, EUT V, HP




Date: 22.JUL.2019 10:11:06

Radiated Emissions, 1000 – 4000 MHz, 2480 MHz, EUT V, VP




Date: 22.JUL.2019 10:13:01

Radiated Emissions, 1000 – 4000 MHz, 2480 MHz, EUT V, HP




Date: 22.JUL.2019 14:03:30

Radiated Emissions, 3000 – 18000 MHz, 2402 MHz, EUT V, VP




Date: 22.JUL.2019 14:05:26

Radiated Emissions, 3000 – 18000 MHz, 2402 MHz, EUT V, HP




Date: 22.JUL.2019 14:59:28

Radiated Emissions, 3000 – 18000 MHz, 2440 MHz, EUT V, VP




Date: 22.JUL.2019 15:01:24

Radiated Emissions, 3000 – 18000 MHz, 2440 MHz, HP




Date: 22.JUL.2019 15:25:50

Radiated Emissions, 3000 – 18000 MHz, 2480 MHz, EUT V, VP




Date: 22.JUL.2019 15:27:45

Radiated Emissions, 3000 – 18000 MHz, 2480 MHz, HP




Date: 22.JUL.2019 14:15:18

Radiated Emissions, 4804 MHz, 2402 MHz (Max: VP)




Date: 22.JUL.2019 14:27:37

Radiated Emissions, 7206 MHz, 2402 MHz (Max: VP)




Date: 22.JUL.2019 14:36:01

Radiated Emissions, 9608 MHz, 2402 MHz (Max: VP)




Date: 22.JUL.2019 14:51:32

Radiated Emissions, 12010 MHz, 2402 MHz (Max: VP)




Date: 22.JUL.2019 15:11:05

Radiated Emissions, 4880 MHz, 2440 MHz (Max: VP)




Date: 22.JUL.2019 15:14:10

Radiated Emissions, 7320 MHz, 2440 MHz (Max: VP)




Date: 22.JUL.2019 15:16:25

Radiated Emissions, 9760 MHz, 2440 MHz (Max: VP)




Date: 22.JUL.2019 15:19:30

Radiated Emissions, 12200 MHz, 2440 MHz (Max: VP)




Date: 22.JUL.2019 15:31:28

Radiated Emissions, 4960 MHz, 2480 MHz (Max: VP)




Date: 22.JUL.2019 15:35:04

Radiated Emissions, 7440 MHz, 2480 MHz (Max: VP)




Date: 22.JUL.2019 15:39:09

Radiated Emissions, 9920 MHz, 2480 MHz (Max: VP)




Date: 22.JUL.2019 15:43:34

Radiated Emissions, 12400 MHz, 2480 MHz (Max: VP)




Date: 23.JUL.2019 09:25:57

Radiated Emissions, 18 – 26 GHz, 2402 MHz, VP, @1m




Date: 23.JUL.2019 09:24:26

Radiated Emissions, 18 – 26 GHz, 2402 MHz, HP, @1m




Date: 23.JUL.2019 09:29:02

Radiated Emissions, 18 – 26 GHz, 2440 MHz, VP, @1m




Date: 23.JUL.2019 09:31:05

Radiated Emissions, 18 – 26 GHz, 2440 MHz, HP, @1m



Date: 23.JUL.2019 09:35:01

Radiated Emissions, 18 – 26 GHz, 2480 MHz, VP, @1m



Date: 23.JUL.2019 09:36:33

Radiated Emissions, 18 – 26 GHz, 2480 MHz, HP, @1m

4 Measurement Uncertainty

Measurement Uncertainty Values		
Test Item		Uncertainty
Output Power		±0.5 dB
Power Spectral Density		±0.5 dB
Out of Band Emissions, Conducted	< 3.6 GHz	±0.6 dB
	> 3.6 GHz	±0.9 dB
Spurious Emissions, Radiated	< 1 GHz	±2.5 dB
	> 1 GHz	±2.2 dB
Emission Bandwidth		±4 %
Power Line Conducted Emissions		+2.9 / -4.1 dB
Spectrum Mask Measurements	Frequency	±5 %
	Amplitude	±1.0 dB
Frequency Error		±0.6 ppm
Temperature Uncertainty		±1 °C

All uncertainty values are expanded standard uncertainty to give a confidence level of 95%, based on coverage factor k=2

5 LIST OF TEST EQUIPMENT

To facilitate inclusion on each page of the test equipment used for related tests, each item of test equipment and ancillaries are identified (numbered) by the Test Laboratory.

No.	Model number	Description	Manufacturer	Ref. no.	Cal. date	Cal. Due
1	FSW43	Spectrum Analyzer	Rohde & Schwarz	LR 1690	2019-01 2020-01	2020-01 2021-01
2	ESU40	Measuring Receiver	Rohde & Schwarz	LR 1639	2019-03 2020-01	2020-03 2021-01
3	6810.17B	Attenuator	Suhner	LR 1669	2019-07	2020-07
4	6HC3000/18000	Highpass Filter	Trilithic	LR 1614	COU	
5	JB3	BiLog Antenna	Sunol Sciences	N-4525	2017-11	2020-11
6	317	Preamplifier	Sonoma Inst.	LR 1687	2019-07	2020-07
7	3115	Horn Antenna	EMCO	LR 1330	2016-10	2021-10
8	3117-PA	Horn Antenna with Preamp	EMCO	LR 1717	2017-12	2020-12
9	8449A	Pre-amplifier	Hewlett Packard	LR 1322	2019-07	2020-07
10	638	Horn Antenna	Narda	LR 1480	2010-06	2030-06
11	WRCG2400/2483.5	Band Reject Filter	Wainwright Inst.	LR 1530	COU	
12	Model 45	Dual Display Multimeter	Fluke	LT 5218	2018-11	2020-11
13	CPX400S	DC Power Supply	AimTTi	LR 1713	COU	
14	ST18/SMA/N/36	RF Cable	Suhner	LR 1627	COU	
15	SF102/1000MM	RF Cable	Suhner	SN 50113/2	COU	
16	SF102/2000MM	RF Cable	Suhner	SN 500100/2	COU	


COU - Calibrate ON Use; N/A – Not Applicable

The software listed below has been used for one or more tests.

No.	Manufacturer	Name	Version	Comment
1	Rohde & Schwarz	EMC32	10.50.10	Radiated Emission test software
2	Rohde & Schwarz	GPBShot	2.7	Screenshots from R&S Spectrum Analyzers


6 BLOCK DIAGRAM

6.1 Conducted Tests



This test set-up is used for all Conducted tests.

6.2 Test Site Radiated Emission



This test setup is used for all radiated emissions tests. Measuring distance is 3m for all frequencies up to 18 GHz. Above 18 GHz measuring distance is 1m.

Emissions above 1 GHz are measured with a Spectrum Analyzer and Horn Antenna.

All measurements at 1 GHz and above were performed with turntable height 1.5m and with the ground plane covered by absorbers.

A pre-amplifier is used for all measurements, and High-Pass filter is used for all harmonics.

Above 18 GHz the test receiver is moved inside the anechoic chamber and located next to the antenna to minimize the cable loss.