

Calian Agriculture Ltd.

RF Exposure Exhibit

SCOPE OF WORK

EMC TESTING – Binsense Live Master, Model: BMU-106103_STD_V

REPORT NUMBER

106033026MPK-003

ISSUE DATE

February 13, 2025

REVISED DATE

May 5, 2026

July 27, 2026

PAGES

12

DOCUMENT CONTROL NUMBER

Non-Specific Radio Report Shell Rev. December 2017 MPK

© 2017 INTERTEK



RF Exposure Exhibit (Mobile Devices)

Report Number: 106033026MPK-003
Project Number: G106033026, G106562063

Report Issue Date: February 13, 2025
Report Revision Date: May 5, 2026; July 27, 2026

Testing performed on the
Binsense Live Master
Model Tested: BMU-106103_STD_V

FCC ID: 2AUTY-106103-V3
IC: 27173-106103V3
HVIN: V3

to

47CFR 2.1091
RSS-102 Issue 5

for

Calian Agriculture Ltd.

Tested by:
Intertek
1365 Adams Court
Menlo Park, CA 94025 USA

Client:
Calian Agriculture Ltd.
118 Husum Road
RM of Sherwood, SK S4K0A4 Canada

Report prepared by:



Arjun Mukherjea / EMC Engineer

Report reviewed by:



Aaron Chang / EMC Team Leader


This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program. This report must not be used to claim product endorsement by A2LA, NIST nor any other agency of the U.S. Government.

Report No. 106033026MPK-003	
Equipment Under Test:	Binsense Live Master
Model Number:	BMU-106103_STD_V / SN: FACA7F0
Applicant:	Calian Agriculture Ltd.
Contact:	Simon Lee
Address:	118 Husum Road RM of Sherwood, SK S4K0A4
Country:	Canada
Tel. Number:	(306) 550-1369
Email:	simon.lee@calian.com
Applicable Regulation:	47CFR 2.1091 RSS-102 Issue 5

We attest to the accuracy of this report:



Arjun Mukherjee
EMC Engineer



Aaron Chang
EMC Team Leader

TABLE OF CONTENTS

<i>Mizuho Orthopedic Systems Inc.</i>	<i>1</i>
<i>1.0 RF Exposure Summary.....</i>	<i>5</i>
<i>2.0 RF Exposure Limits</i>	<i>5</i>
<i>3.0 Test Results.....</i>	<i>7</i>
<i>4.0 Variant Models.....</i>	<i>9</i>
<i>5.0 Document History</i>	<i>10</i>
<i>Appendix A: Power Density Calculation.....</i>	<i>11</i>

1.0 RF Exposure Summary

Test	Reference FCC	Reference Industry Canada	Result
Radio frequency Radiation Exposure Evaluation	47 CFR§2.1091	RSS-102 Issue 5	Complies

2.0 RF Exposure Limits

In this document, we evaluate the RF Exposure to human body due the intentional transmission from the transmitter (EUT). The limits for Maximum Permissible Exposure (MPE) specified in FCC 1.1310 and RSS-102 are followed.

2.1 FCC Limits

According to FCC 1.1310 table 1: The criteria listed in the following table shall be used to evaluate the environmental impact of human exposure to radio-frequency (RF) radiation as specified in 1.1307(b)

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (minutes)
(A)Limits For Occupational / Control Exposures				
0.3 – 3.0	614	1.63	*100	6
3.0 – 30	1842/f	4.89/f	*900/f ²	6
30-300	61.4	0.163	1.0	6
300 - 1500	...	...	F/300	6
1500 - 100,000	...	...	5	6
(B)Limits For General Population / Uncontrolled Exposure				
0.3 – 1.34	614	1.63	*100	30
1.34 – 30	824/f	2.19/f	*180/f ²	30
30 – 300	27.5	0.073	0.2	30
300 - 1500	...	...	F/1500	30
1500 - 100,000	...	...	1.0	30

F = Frequency in MHz

* = plane wave equivalent density

2.2 Industry Canada Limits

According to RSS-102, Industry Canada has adopted the SAR and RF field strength limits established in Health Canada's RF exposure guideline, Safety Code 6.

Table 4: RF Field Strength Limits for Devices Used by the General Public (Uncontrolled Environment)				
Frequency Range	Electric Field	Magnetic Field	Power Density	Reference Period
(MHz)	(V/m rms)	(A/m rms)	(W/m ²)	(minutes)
0.003-10	83	90	-	Instantaneous*
0.1-10	-	0.73/ f	-	6**
1.1-10	87/ f ^{0.5}	-	-	6**
10-20	27.46	0.0728	2	6
20-48	58.07/ f ^{0.25}	0.1540/ f ^{0.25}	8.944/ f ^{0.5}	6
48-300	22.06	0.05852	1.291	6
300-6000	3.142 f ^{0.3417}	0.008335 f ^{0.3417}	0.02619 f ^{0.6834}	6
6000-15000	61.4	0.163	10	6
15000-150000	61.4	0.163	10	616000/ f ^{1.2}
150000-300000	0.158 f ^{0.5}	4.21 x 10 ⁻⁴ f ^{0.5}	6.67 x 10 ⁻⁵ f	616000/ f ^{1.2}
Note: f is frequency in MHz. * Based on nerve stimulation (NS). ** Based on specific absorption rate (SAR).				

3.0 Test Results

3.1 Classification

Radio is installed inside a mobile host device. The antenna of the product, under normal use condition, is at least 20 cm away from the body of the user and accessible to the end user. Warning statement to the user for keeping at least 20 cm or more separation distance with the antenna should be included in user's manual.

3.2 EIRP calculations

The table in the Binsense Live Master, Model: BMU-106103_STD_V consists of one radio: 2.4GHz Zigbee.

3.3 Maximum RF Power

Specification of Radio on the BMU-106103_STD_V	
Type	Zigbee
Frequency Range	2405 – 2470 MHz
Antenna 1 Rated RF Output Power	20.5 dBm
Antenna 2 Rated RF Output Power	19.39 dBm
Internal Antenna 1 Gain ¹	1.5 dBi
External Antenna 2 Gain ¹	7 dBi

¹As provided by the client. Intertek takes no responsibility for the accuracy of this information.

Specification of Cellular Module (FCC ID: XPY1EIQ24NN) ² on the BMU-106103_STD_V	
Type ¹	LTE
Frequency Range ¹	698 – 716 MHz, 824 – 849 MHz, 1710 – 1755 MHz, 1850 – 1910 MHz
Maximum Conducted RF Output Power ¹	23.55 dBm
Peak Antenna Gain ²	824 – 960 MHz: 0.5 dBi, 1710 – 2170 MHz: 2.5 dBi

¹Information taken from Assessment Reference: MDE_UBLOX_1712_MPEb

²As provided by the client. Intertek takes no responsibility for the accuracy of this information.

3.4 RF Exposure Calculation

3.4.1 RF Exposure calculation for 2.4GHz range

FCC

Zigbee Antenna 1

Radio	Frequency Range (MHz)	EIRP ¹ (dBm)	EIRP ¹ (mW)	Power Density (mW/cm ²) @20 cm	FCC Limit (mW/cm ²)
Zigbee	2405 - 2470	22	158.489	0.03153	1

Zigbee Antenna 2

Radio	Frequency Range (MHz)	EIRP ¹ (dBm)	EIRP ¹ (mW)	Power Density (mW/cm ²) @20 cm	FCC Limit (mW/cm ²)
Zigbee	2405 - 2470	26.39	435.512	0.08664	1

LTE

Radio	Frequency Range (MHz)	EIRP ¹ (dBm)	EIRP ¹ (mW)	Power Density (mW/cm ²) @20 cm	FCC Limit (mW/cm ²)
LTE	1710 – 1755	26.05	402.717	0.08012	1

RSS

Zigbee Antenna 1

Radio	Frequency Range (MHz)	EIRP ¹ (dBm)	EIRP ¹ (mW)	Power Density (W/m ²) @20 cm	RSS Limit (W/m ²)
Zigbee	2405 - 2470	22	158.489	0.31530	5.469

Zigbee Antenna 2

Radio	Frequency Range (MHz)	EIRP ¹ (dBm)	EIRP ¹ (mW)	Power Density (W/m ²) @20 cm	RSS Limit (W/m ²)
Zigbee	2405 - 2470	26.39	435.512	0.86642	5.469

Cellular

Radio	Frequency Range (MHz)	EIRP ¹ (dBm)	EIRP ¹ (mW)	Power Density (W/m ²) @20 cm	RSS Limit (W/m ²)
LTE	1710 – 1755	26.05	402.717	0.80118	4.280

4.0 Variant Models

Not applicable.

5.0 Document History

Revision/ Job Number	Writer Initials	Reviewers Initials	Date	Change
0 / G106033026	AM	AC	February 13, 2025	Original Document
1 / G106562063	AM	AC	May 5, 2026	Performed a technical review of report to ensure standard is up to date.
2 / G106562063	AM <i>Adrian Mubijar</i>	AC <i>Adam Chang</i>	July 27, 2026	Added Cellular Module calculations

Appendix A: Power Density Calculation

The Power Density can be calculated using the formula

$$S = \text{EIRP} / 4\pi D^2$$

Where: S is Power Density in mW/cm²

D is the distance from the antenna in cm.

END OF TEST REPORT