

RF Exposure

Test Requirement: FCC 47CFR 15.247(i)
FCC ID: 2AUVM-CIR415
Test Date: 2025-08-14
Mode of Operation: BT Tx mode / NFC Tx mode

Requirements:

In 15.247(i), an equipment shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess of the limits in §§ 1.1310 and 2.1093 of this chapter.

Applications to the Commission for construction permits, licenses to transmit or renewals thereof, equipment authorizations or modifications in existing facilities must contain a statement confirming compliance with the limits unless the facility, operation, or transmitter is categorically excluded, as discussed below. Technical information showing the basis for this statement must be submitted to the Commission upon request.

According to KDB447498 D04 General RF Exposure Guidance v01, Appendix B

B.2 Blanket 1 mW Blanket Exemption

The 1 mW Blanket Exemption of § 1.1307(b)(3)(i)(A) applies for single fixed, mobile, and portable RF sources with available maximum time-averaged power of no more than 1mW, regardless of separation distance.

Result: Pass

BT Tx mode

The Maximum ERP = 0.760mW (at frequency = 2.402GHz) < 1mW

NFC Tx mode

The Maximum EIRP = 0.000016mW (at frequency = 13.56MHz) < 1mW

Remark:

test result Field Strength of Fundamental Emissions is 47.45dBuV/m (at frequency = 13.56MHz)

$$\text{EIRP (dBm)} = E(\text{dB}\mu\text{V/m}) - 95.3$$

$$\text{EIRP} = -47.85\text{dBm} = 0.000016\text{mW}$$