



FCC Part 15C Test Report

FCC ID: 2AUVM-CIR415

Applicant: AB Circle Limited

Address: Shimbashi Place 7F, 1-12-9, Shimbashi, Minato-ku, Tokyo, 105-0004 Japan

Manufacturer: AB Circle Limited

Address: Shimbashi Place 7F, 1-12-9, Shimbashi, Minato-ku, Tokyo, 105-0004 Japan

Product Name: Bluetooth Contactless Smart Card Reader

Trade Mark: AB Circle Limited

Model Number: CIR415A

Date of Receipt: Aug. 08, 2025

Test Date: Aug. 08, 2025 - Aug. 14, 2025

Date of Report: Sep. 18, 2025

Prepared By: Shenzhen DL Testing Technology Co., Ltd.

Address: 101-201, Comprehensive Building, Tongzhou Electronics Longgang Factory Area, No.1 Baolong Fifth Road, Baolong Community, Baolong Street, Longgang District, Shenzhen, China

Applicable Standards: FCC PART 15 C 15.247
ANSI C63.10:2020

Test Result: Pass

Report Number: DLE-250919003

Prepared by(Engineer): Ken Tan

Reviewer(Supervisor): Jack Bu

Approved(Manager): Jade Yang



This test report is based on a single evaluation of one sample of above mentioned products. It is not permitted to be duplicated in extracts without written approval of Shenzhen DL Testing Technology Co., Ltd.



Table of Contents	Page
1 . SUMMARY OF TEST RESULTS	4
1.1 MEASUREMENT UNCERTAINTY	4
2 . GENERAL INFORMATION	5
2.1 GENERAL DESCRIPTION OF EUT	5
2.2 DESCRIPTION OF TEST MODES	6
2.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED	6
2.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)	7
2.5 TABLE OF PARAMETERS OF TEST SOFTWARE SETTING	7
2.6 EQUIPMENTS LIST FOR ALL TEST ITEMS	8
3 . EMC EMISSION TEST	9
3.1 CONDUCTED EMISSION MEASUREMENT	9
3.1.1 POWER LINE CONDUCTED EMISSION LIMITS	9
3.1.2 TEST PROCEDURE	9
3.1.3 DEVIATION FROM TEST STANDARD	9
3.1.4 TEST SETUP	10
3.1.5 EUT OPERATING CONDITIONS	10
3.1.6 TEST RESULTS	11
3.2 RADIATED EMISSION MEASUREMENT	13
3.2.1 RADIATED EMISSION LIMITS	13
3.2.2 TEST PROCEDURE	14
3.2.3 DEVIATION FROM TEST STANDARD	14
3.2.4 TEST SETUP	14
3.2.5 EUT OPERATING CONDITIONS	15
3.2.6 TEST RESULTS (BETWEEN 9KHZ – 30 MHZ)	16
3.2.7 TEST RESULTS (BETWEEN 30MHZ – 1GHZ)	17
3.2.8 TEST RESULTS (1GHZ~25GHZ)	19
3.3 RADIATED BAND EMISSION MEASUREMENT	22
3.3.1 TEST REQUIREMENT:	22
3.3.2 TEST PROCEDURE	22
3.3.3 DEVIATION FROM TEST STANDARD	22
3.3.4 TEST SETUP	23
3.3.5 EUT OPERATING CONDITIONS	23
4 . PEAK OUTPUT POWER	25
4.1 APPLIED PROCEDURES / LIMIT	25
4.1.1 TEST PROCEDURE	25
4.1.2 DEVIATION FROM STANDARD	25



Table of Contents	Page
4.1.3 TEST SETUP	25
4.1.4 EUT OPERATION CONDITIONS	25
4.1.5 TEST RESULTS	26
5 . POWER SPECTRAL DENSITY TEST	30
5.1 APPLIED PROCEDURES / LIMIT	30
5.1.1 TEST PROCEDURE	30
5.1.2 DEVIATION FROM STANDARD	30
5.1.3 TEST SETUP	30
5.1.4 EUT OPERATION CONDITIONS	30
5.1.5 TEST RESULTS	30
6 . 6DB BANDWIDTH TEST	34
6.1 APPLIED PROCEDURES / LIMIT	34
6.1.1 TEST PROCEDURE	34
6.1.2 DEVIATION FROM STANDARD	34
6.1.3 TEST SETUP	34
6.1.4 EUT OPERATION CONDITIONS	34
6.1.5 TEST RESULTS	34
7 . CONDUCTED BAND EMISSION MEASUREMENT	39
7.1 APPLIED PROCEDURES / LIMIT	39
7.1.1 TEST PROCEDURE	39
7.1.2 DEVIATION FROM STANDARD	39
7.1.3 TEST SETUP	39
7.1.4 EUT OPERATION CONDITIONS	39
7.1.5 TEST RESULTS	40
8 . ANTENNA REQUIREMENT	46
8.1 STANDARD REQUIREMENT	46
8.2 EUT ANTENNA	46
9 . TEST SEUUP PHOTO	47
10 . EUT PHOTO	49



1. SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:

FCC Part15 (15.247) , Subpart C			
Standard Section	Test Item	Judgment	Remark
15.207	Conducted Emission	PASS	
15.209 15.205	Radiated Spurious Emission	PASS	
15.205 15.247(d)	Band Edge Emission	PASS	
15.247(b)(3)	Peak Output Power	PASS	
15.247(a)(2)	6dB Bandwidth	PASS	
15.247(e)	Power Spectral Density	PASS	
15.203	Antenna Requirement	PASS	

NOTE:

(1)" N/A" denotes test is not applicable in this Test Report

Test lab: Shenzhen DL Testing Technology Co., Ltd.

101-201, Comprehensive Building, Tongzhou Electronics Longgang Factory Area, No.1

Address: Baolong Fifth Road, Baolong Community, Baolong Street, Longgang District, Shenzhen, China

FCC Test Firm Registration Number: 854456

Designation Number: CN1307

IC Registered No.: 27485

CAB ID.: CN0118

1.1 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $y \pm U$, where expanded uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$ providing a level of confidence of approximately 95 %.

No.	Item	Uncertainty
1	Conducted Emission Test	$\pm 2.56\text{dB}$
2	RF power,conducted	$\pm 0.42\text{dB}$
3	Spurious emissions,conducted	$\pm 2.76\text{dB}$
4	All emissions,radiated(<1G)	$\pm 3.65\text{dB}$
5	All emissions,radiated(>1G)	$\pm 4.89\text{dB}$
6	Temperature	$\pm 0.5^{\circ}\text{C}$
7	Humidity	$\pm 2\%$
8	6dB Bandwidth	$\pm 0.2\text{MHz}$
9	Power Spectral Density	$\pm 0.3\text{dBm}$



2. GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF EUT

Product Name:	Bluetooth Contactless Smart Card Reader
Trade Mark:	AB Circle Limited
Model Number:	CIR415A
Model Difference	N/A
BT Version:	Bluetooth 5.2 BLE
Operation Frequency:	2402~2480MHz
Channel numbers:	40 Channels
Channel separation:	2MHz
Data Rates:	1Mbps; 2Mbps
Modulation technology:	GFSK
Antenna Type:	Internal Antenna
Antenna gain:	-1.61dBi
Power supply:	3.7Vd.c. (lithium battery x1) 5Vd.c. by USB port

Note:

- 1.For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.
- 2.The EUT's all information provided by client.

2. Channel List

Channel List					
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
00	2402	14	2430	28	2458
01	2404	15	2432	29	2460
02	2406	16	2434	30	2462
03	2408	17	2436	31	2464
04	2410	18	2438	32	2466
05	2412	19	2440	33	2468
06	2414	20	2442	34	2470
07	2416	21	2444	35	2472
08	2418	22	2446	36	2474
09	2420	23	2448	37	2476
10	2422	24	2450	38	2478
11	2424	25	2452	39	2480
12	2426	26	2454		
13	2428	27	2456		



2.2 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.


Pretest Mode	Modulation	Channel
Mode 1	GFSK 1Mbps; GFSK 2Mbps;	CH00
Mode 2		CH19
Mode 3		CH39

Note: (1) The measurements are performed at the highest, middle, lowest available channels.


(2) For the two items of conducted disturbance at the power supply end and space radiation below 1GHz, all modes have undergone pre-tests. The report only shows the worst test results of mode 3.

2.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED

Radiated Spurious Emission Test



Power Line Conducted Emission Test





2.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Model/Type No.	Series No.	Note
E-1	(LENOVO)Notebook PC	310S-14AST	N/A	I/P: AC 100-240V 50/60Hz O/P: DC 19V 1A

Item	Shielded Type	Ferrite Core	Length	Note


Note:

- (1) For detachable type I/O cable should be specified the length in cm in 『Length』 column.

2.5 TABLE OF PARAMETERS OF TEST SOFTWARE SETTING

During testing, channel & power controlling software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the end product.

Test software Version	Direct Test Mode v2.1.0		
Frequency	2402 MHz	2440MHz	2480 MHz
Power Setting of Software	0	0	0





2.6 EQUIPMENTS LIST FOR ALL TEST ITEMS

Radiation test, Band-edge test and 6db bandwidth test equipment

Item	Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
1	Spectrum Analyzer (9kHz-26.5GHz)	Agilent	E4408B	MY50140780	Nov. 01, 2024	Oct. 31, 2025
2	Test Receiver (9kHz-7GHz)	R&S	ESRP7	101393	Nov. 01, 2024	Oct. 31, 2025
3	Bilog Antenna (30MHz-1GHz)	R&S	VULB9162	00306	Nov. 02, 2024	Nov. 01, 2025
4	Horn Antenna (1GHz-18GHz)	Schwarzbeck	BBHA9120D	02139	Nov. 02, 2024	Nov. 01, 2025
5	Horn Antenna (18GHz-40GHz)	A.H. Systems	SAS-574	588	Nov. 01, 2024	Oct. 31, 2025
6	Amplifier (9KHz-6GHz)	Schwarzbeck	BBV9743B	00153	Nov. 01, 2024	Oct. 31, 2025
7	Amplifier (1GHz-18GHz)	EMEC	EM01G8GA	00270	Nov. 01, 2024	Oct. 31, 2025
8	Amplifier (18GHz-40GHz)	Quanjuda	DLE-161	97	Nov. 01, 2024	Oct. 31, 2025
9	Loop Antenna (9KHz-30MHz)	Schwarzbeck	FMZB1519B	00014	Nov. 01, 2024	Oct. 31, 2025
10	RF cables1 (9kHz-1GHz)	ChengYu	966	004	Nov. 01, 2024	Oct. 31, 2025
11	RF cables2 (1GHz-40GHz)	ChengYu	966	003	Nov. 01, 2024	Oct. 31, 2025
12	Antenna connector	Florida RF Labs	N/A	RF 01#	Nov. 01, 2024	Oct. 31, 2025
13	Power probe	KEYSIGHT	U2021XA	MY55210018	Nov. 01, 2024	Oct. 31, 2025
14	Signal Analyzer 9kHz-26.5GHz	Agilent	N9020A	MY55370280	Nov. 01, 2024	Oct. 31, 2025
15	Test Receiver 20kHz-40GHz	R&S	ESU 40	100376	Nov. 01, 2024	Oct. 31, 2025
16	D.C. Power Supply	LongWei	PS-305D	010964729	Nov. 01, 2024	Oct. 31, 2025

Conduction Test equipment

Item	Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
1	843 Shielded Room	ChengYu	843 Room	843	Nov. 05, 2023	Nov. 04, 2026
2	EMI Receiver	R&S	ESR	101421	Nov. 01, 2024	Oct. 31, 2025
3	LISN	R&S	ENV216	102417	Nov. 01, 2024	Oct. 31, 2025
4	843 Cable 1#	ChengYu	CE Cable	001	Nov. 01, 2024	Oct. 31, 2025

Other

Item	Name	Manufacturer	Model	Software version
1	EMC Conduction Test System	FALA	EZ_EMCC	EMC-CON 3A1.1
2	EMC radiation test system	FALA	EZ_EMCC	FA-03A2
3	RF test system	MAIWEI	MTS8310	2.0.0.0
4	RF communication test system	MAIWEI	MTS8200	2.0.0.0



3. EMC EMISSION TEST

3.1 CONDUCTED EMISSION MEASUREMENT

3.1.1 POWER LINE CONDUCTED EMISSION Limits (Frequency Range 150KHz-30MHz)

FREQUENCY (MHz)	Limit (dBuV)		Standard
	Quasi-peak	Average	
0.15 -0.5	66 - 56 *	56 - 46 *	FCC
0.50 -5.0	56.00	46.00	FCC
5.0 -30.0	60.00	50.00	FCC

Note:

- (1) The tighter limit applies at the band edges.
- (2) The limit of " * " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.

The following table is the setting of the receiver

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz

3.1.2 TEST PROCEDURE


- The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- LISN at least 80 cm from nearest part of EUT chassis.
- For the actual test configuration, please refer to the related Item –EUT Test Photos.

3.1.3 DEVIATION FROM TEST STANDARD

No deviation



3.1.4 TEST SETUP



Note: 1. Support units were connected to second LISN.


2. Both of LISNs (AMN) are 80 cm from EUT and at least 80 cm from other units and other metal planes

3.1.5 EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.

**3.1.6 TEST RESULTS**

Temperature:	25 °C	Relative Humidity:	54%
Pressure:	1010 hPa	Phase :	L
Test Voltage :	AC 120V/60Hz	Test Mode:	Mode 1 (GFSK 1Mbps)

**MEASUREMENT RESULT: "vol_0001_fin QP"**


Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Line	PE
0.260000	46.00	9.6	61.40	15.40	L1	GND
0.785000	45.70	9.7	56.00	10.30	L1	GND
0.880000	42.10	9.7	56.00	13.90	L1	GND
4.330000	34.80	9.7	56.00	21.20	L1	GND
11.920000	30.30	10.0	60.00	29.70	L1	GND
14.000000	34.70	10.1	60.00	25.30	L1	GND

MEASUREMENT RESULT: "vol_0001_fin AV"

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Line	PE
0.260000	28.40	9.6	51.40	23.00	L1	GND
0.790000	25.00	9.7	46.00	21.00	L1	GND
0.905000	25.00	9.7	46.00	21.00	L1	GND
4.295000	27.60	9.7	46.00	18.40	L1	GND
6.545000	23.60	9.8	50.00	26.40	L1	GND
14.075000	23.90	10.1	50.00	26.10	L1	GND



Temperature:	25 °C	Relative Humidity:	54%
Pressure:	1010 hPa	Phase :	N
Test Voltage :	AC 120V/60Hz	Test Mode:	Mode 1 (GFSK 1Mbps)

**MEASUREMENT RESULT: "vol_0001_fin QP"**

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Line	PE
0.240000	52.00	9.6	62.10	10.10	N	GND
0.820000	49.20	9.7	56.00	6.80	N	GND
0.880000	43.50	9.7	56.00	12.50	N	GND
4.215000	35.30	9.7	56.00	20.70	N	GND
8.150000	28.50	9.9	60.00	31.50	N	GND
14.290000	30.20	10.2	60.00	29.80	N	GND

MEASUREMENT RESULT: "vol_0001_fin AV"

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Line	PE
0.240000	41.70	9.6	52.10	10.40	N	GND
0.815000	31.20	9.7	46.00	14.80	N	GND
1.660000	24.80	9.7	46.00	21.20	N	GND
4.215000	27.60	9.7	46.00	18.40	N	GND
6.975000	21.40	9.8	50.00	28.60	N	GND
14.045000	20.80	10.1	50.00	29.20	N	GND



3.2 RADIATED EMISSION MEASUREMENT

3.2.1 RADIATED EMISSION LIMITS (Frequency Range 9kHz-1000MHz)

In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (microvolt/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

FREQUENCY (MHz)	Limit (dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15C.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	25GHz
RB / VB (emission in restricted band)	1 MHz / 1 MHz for Peak, 1 MHz / 10Hz for Average

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP



3.2.2 TEST PROCEDURE

Below 1GHz test procedure as below:

- The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

Above 1GHz test procedure as below:

- Different between above is the test site, change from Semi- Anechoic Chamber to fully Anechoic Chamber and change form table 0.8 metre to 1.5 metre.
- Test the EUT in the lowest channel, the middle channel, the Highest channel

Note:


The horizontal and vertical polarities of the antenna were tested, and a pre-test was conducted on the EUT placement as three orthogonal axes X,Y,Z. The worst display of the test results was the Y-axis. The worst case emissions were reported.

3.2.3 DEVIATION FROM TEST STANDARD


No deviation

3.2.4 TEST SETUP


(A) Radiated Emission Test-Up Frequency Below 30MHz



(B) Radiated Emission Test-Up Frequency 30MHz~1GHz



(C) Radiated Emission Test-Up Frequency Above 1GHz



3.2.5 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.

**3.2.6 TEST RESULTS (BETWEEN 9KHZ – 30 MHZ)**

Temperature:	20°C	Relative Humidity:	48%
Pressure:	1010 hPa	Test Voltage :	DC 3.7V
Test Mode :	Mode 3	Polarization :	--

Freq.	Reading	Limit	Margin	State
(MHz)	(dBuV/m)	(dBuV/m)	(dB)	P/F
--	--	--	--	PASS
--	--	--	--	PASS

NOTE:


The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

Distance extrapolation factor = $40 \log (\text{specific distance/test distance})$ (dB);

Limit line = specific limits(dBuV) + distance extrapolation factor.

**3.2.7 TEST RESULTS (BETWEEN 30MHZ – 1GHZ)**

Temperature:	26°C	Relative Humidity:	54%
Pressure:	1010 hPa	Polarization :	Horizontal
Test Voltage :	DC 3.7V		
Test Mode :	Mode 1 (GFSK 1Mbps)		




Ambient Temperature: 25.1 °C
Relative Humidity : 53.8%
Air Pressure : 100.8kPa

	Freq	Level	Limit	Over	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB		
1	111.347	21.34	43.50	-22.16	QP	Horizontal
2	200.688	28.72	43.50	-14.78	QP	Horizontal
3	256.521	28.66	46.00	-17.34	QP	Horizontal
4	531.964	32.41	46.00	-13.59	QP	Horizontal
5	704.226	36.17	46.00	-9.83	QP	Horizontal
6	919.287	39.48	46.00	-6.52	QP	Horizontal



Temperature:	26°C	Relative Humidity:	54%
Pressure:	1010 hPa	Polarization :	Vertical
Test Voltage :	DC 3.7V		
Test Mode :	Mode 1 (GFSK 1Mbps)		



Ambient Temperature: 25.1 °C
Relative Humidity : 53.8%
Air Pressure : 100.8kPa

	Freq	Level	Limit	Over	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB		
1	37.812	25.97	40.00	-14.03	QP	Vertical
2	235.816	26.18	46.00	-19.82	QP	Vertical
3	401.839	30.98	46.00	-15.02	QP	Vertical
4	714.173	35.99	46.00	-10.01	QP	Vertical
5	810.265	37.76	46.00	-8.24	QP	Vertical
6	919.287	40.56	46.00	-5.44	QP	Vertical

**3.2.8 TEST RESULTS (1GHZ~25GHZ)**

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre- amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB/m)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
Operation frequency:2402 GFSK 1Mbps									
V	4804.00	69.68	50.65	6.88	31.29	57.2	74	-16.8	PK
V	4804.00	54.38	50.65	6.88	31.29	41.9	54	-12.1	AV
V	7206.00	62.39	49.98	7.16	36.63	56.2	74	-17.8	PK
V	7206.00	48.29	49.98	7.16	36.63	42.1	54	-11.9	AV
V	9608.00	53.27	51.53	11.34	41.52	54.6	74	-19.4	PK
V	9608.00	39.27	51.53	11.34	41.52	40.6	54	-13.4	AV
V	12010.00	51.98	52.31	12.89	43.24	55.8	74	-18.2	PK
V	12010.00	37.48	52.31	12.89	43.24	41.3	54	-12.7	AV
H	4804.00	70.22	50.65	6.88	31.15	57.6	74	-16.4	PK
H	4804.00	54.32	50.65	6.88	31.15	41.7	54	-12.3	AV
H	7236.00	62.96	49.98	7.16	36.46	56.6	74	-17.4	PK
H	7236.00	47.86	49.98	7.16	36.46	41.5	54	-12.5	AV
H	9608.00	53.91	51.53	11.34	41.68	55.4	74	-18.6	PK
H	9608.00	39.21	51.53	11.34	41.68	40.7	54	-13.3	AV
H	12010.00	52.12	52.31	12.89	43.2	55.9	74	-18.1	PK
H	12010.00	37.02	52.31	12.89	43.2	40.8	54	-13.2	AV
Operation frequency:2440 GFSK 1Mbps									
V	4880.00	69.58	50.67	6.91	31.38	57.2	74	-16.8	PK
V	4880.00	54.28	50.67	6.91	31.38	41.9	54	-12.1	AV
V	7320.00	63.11	50.02	7.26	36.65	57.0	74	-17.0	PK
V	7320.00	47.31	50.02	7.26	36.65	41.2	54	-12.8	AV
V	9760.00	54.07	51.53	11.39	41.57	55.5	74	-18.5	PK
V	9760.00	39.27	51.53	11.39	41.57	40.7	54	-13.3	AV
V	12200.00	52.08	52.34	12.95	43.31	56	74	-18.0	PK
V	12200.00	37.08	52.34	12.95	43.31	41.0	54	-13.0	AV
H	4880.00	69.08	50.67	6.91	31.38	56.7	74	-17.3	PK
H	4880.00	53.98	50.67	6.91	31.38	41.6	54	-12.4	AV
H	7311.00	62.66	50.02	7.26	36.7	56.6	74	-17.4	PK
H	7311.00	47.36	50.02	7.26	36.7	41.3	54	-12.7	AV
H	9760.00	54.2	51.53	11.39	41.64	55.7	74	-18.3	PK
H	9760.00	39.8	51.53	11.39	41.64	41.3	54	-12.7	AV
H	12200.00	51.83	52.34	12.95	43.26	55.7	74	-18.3	PK
H	12200.00	37.23	52.34	12.95	43.26	41.1	54	-12.9	AV
Operation frequency:2480 GFSK 1Mbps									
V	4960.00	69.67	50.7	6.93	31.4	57.3	74	-16.7	PK
V	4960.00	54.27	50.7	6.93	31.4	41.9	54	-12.1	AV
V	7440.00	62.75	50.08	7.29	36.74	56.7	74	-17.3	PK
V	7440.00	47.55	50.08	7.29	36.74	41.5	54	-12.5	AV
V	9760.00	53.29	51.59	11.47	41.63	54.8	74	-19.2	PK
V	9760.00	40.29	51.59	11.47	41.63	41.8	54	-12.2	AV



V	12200.00	51.4	52.42	13.08	43.34	55.4	74	-18.6	PK
V	12200.00	36.9	52.42	13.08	43.34	40.9	54	-13.1	AV
H	4960.00	69.88	50.7	6.93	31.39	57.5	74	-16.5	PK
H	4960.00	54.08	50.7	6.93	31.39	41.7	54	-12.3	AV
H	7440.00	63.01	50.08	7.29	36.68	56.9	74	-17.1	PK
H	7440.00	47.31	50.08	7.29	36.68	41.2	54	-12.8	AV
H	9760.00	53.8	51.59	11.47	41.62	55.3	74	-18.7	PK
H	9760.00	39.7	51.59	11.47	41.62	41.2	54	-12.8	AV
H	12200.00	51.81	52.42	13.08	43.33	55.8	74	-18.2	PK
H	12200.00	37.21	52.42	13.08	43.33	41.2	54	-12.8	AV

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB/m)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
Operation frequency:2402 GFSK 2Mbps									
V	4804.00	69.28	50.65	6.88	31.29	56.8	74	-17.2	PK
V	4804.00	54.28	50.65	6.88	31.29	41.8	54	-12.2	AV
V	7206.00	62.29	49.98	7.16	36.63	56.1	74	-17.9	PK
V	7206.00	47.99	49.98	7.16	36.63	41.8	54	-12.2	AV
V	9608.00	53.47	51.53	11.34	41.52	54.8	74	-19.2	PK
V	9608.00	39.17	51.53	11.34	41.52	40.5	54	-13.5	AV
V	12010.00	52.08	52.31	12.89	43.24	55.9	74	-18.1	PK
V	12010.00	37.58	52.31	12.89	43.24	41.4	54	-12.6	AV
H	4804.00	69.32	50.65	6.88	31.15	56.7	74	-17.3	PK
H	4804.00	54.02	50.65	6.88	31.15	41.4	54	-12.6	AV
H	7236.00	62.36	49.98	7.16	36.46	56	74	-18.0	PK
H	7236.00	47.96	49.98	7.16	36.46	41.6	54	-12.4	AV
H	9608.00	53.81	51.53	11.34	41.68	55.3	74	-18.7	PK
H	9608.00	39.01	51.53	11.34	41.68	40.5	54	-13.5	AV
H	12010.00	52.22	52.31	12.89	43.2	56	74	-18	PK
H	12010.00	37.32	52.31	12.89	43.2	41.1	54	-12.9	AV
Operation frequency:2440 GFSK 2Mbps									
V	4880.00	69.28	50.67	6.91	31.38	56.9	74	-17.1	PK
V	4880.00	54.08	50.67	6.91	31.38	41.7	54	-12.3	AV
V	7320.00	62.91	50.02	7.26	36.65	56.8	74	-17.2	PK
V	7320.00	47.41	50.02	7.26	36.65	41.3	54	-12.7	AV
V	9760.00	55.17	51.53	11.39	41.57	56.6	74	-17.4	PK
V	9760.00	39.47	51.53	11.39	41.57	40.9	54	-13.1	AV
V	12200.00	51.98	52.34	12.95	43.31	55.9	74	-18.1	PK
V	12200.00	37.28	52.34	12.95	43.31	41.2	54	-12.8	AV
H	4880.00	69.18	50.67	6.91	31.38	56.8	74	-17.2	PK
H	4880.00	53.68	50.67	6.91	31.38	41.3	54	-12.7	AV
H	7311.00	62.26	50.02	7.26	36.7	56.2	74	-17.8	PK
H	7311.00	47.56	50.02	7.26	36.7	41.5	54	-12.5	AV
H	9760.00	55	51.53	11.39	41.64	56.5	74	-17.5	PK



H	9760.00	39.3	51.53	11.39	41.64	40.8	54	-13.2	AV
H	12200.00	52.03	52.34	12.95	43.26	55.9	74	-18.1	PK
H	12200.00	37.23	52.34	12.95	43.26	41.1	54	-12.9	AV
Operation frequency:2480 GFSK 2Mbps									
V	4960.00	69.37	50.7	6.93	31.4	57	74	-17.0	PK
V	4960.00	53.97	50.7	6.93	31.4	41.6	54	-12.4	AV
V	7440.00	62.45	50.08	7.29	36.74	56.4	74	-17.6	PK
V	7440.00	47.65	50.08	7.29	36.74	41.6	54	-12.4	AV
V	9760.00	53.79	51.59	11.47	41.63	55.3	74	-18.7	PK
V	9760.00	39.99	51.59	11.47	41.63	41.5	54	-12.5	AV
V	12200.00	51.6	52.42	13.08	43.34	55.6	74	-18.4	PK
V	12200.00	37.3	52.42	13.08	43.34	41.3	54	-12.7	AV
H	4960.00	68.98	50.7	6.93	31.39	56.6	74	-17.4	PK
H	4960.00	53.48	50.7	6.93	31.39	41.1	54	-12.9	AV
H	7440.00	62.71	50.08	7.29	36.68	56.6	74	-17.4	PK
H	7440.00	46.81	50.08	7.29	36.68	40.7	54	-13.3	AV
H	9760.00	53.7	51.59	11.47	41.62	55.2	74	-18.8	PK
H	9760.00	39.9	51.59	11.47	41.62	41.4	54	-12.6	AV
H	12200.00	51.91	52.42	13.08	43.33	55.9	74	-18.1	PK
H	12200.00	37.41	52.42	13.08	43.33	41.4	54	-12.6	AV

Remark:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier, Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.



3.3 RADIATED BAND EMISSION MEASUREMENT

3.3.1 TEST REQUIREMENT:

FCC Part15 C Section 15.209 and 15.205

LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

FREQUENCY (MHz)	Limit (dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15C.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	2300MHz
Stop Frequency	2520
RB / VB (emission in restricted band)	1 MHz / 1 MHz for Peak, 1 MHz / 10Hz for Average

3.3.2 TEST PROCEDURE

Above 1GHz test procedure as below:

1. The EUT was placed on the top of a rotating table 0.1 meters above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation.
2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading.
5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
6. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
7. Test the EUT in the lowest channel,the Highest channel

Note:

The horizontal and vertical polarities of the antenna were tested, and a pre-test was conducted on the EUT placement as three orthogonal axes X,Y,Z. The worst display of the test results was the Y-axis. The worst case emissions were reported.


3.3.3 DEVIATION FROM TEST STANDARD

No deviation



3.3.4 TEST SETUP

Radiated Emission Test-Up Frequency Above 1GHz



3.3.5 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.

**3.3.6 TEST RESULT**

Polar (H/V)	Frequency	Meter Reading	Pre- amplifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
Operation frequency:2402 GFSK 1Mbps									
V	2400.00	65.85	52.13	2.52	27.46	43.7	74	-30.3	PK
V	2400.00	59.55	52.13	2.52	27.46	37.4	54	-16.6	AV
H	2400.00	65.95	52.13	2.52	27.46	43.8	74	-30.2	PK
H	2400.00	59.55	52.13	2.52	27.46	37.4	54	-16.6	AV

Polar (H/V)	Frequency	Meter Reading	Pre- amplifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
Operation frequency:2480 GFSK 1Mbps									
V	2483.50	79.23	52.23	2.86	27.44	57.3	74	-16.7	PK
V	2483.50	61.33	52.23	2.86	27.44	39.4	54	-14.6	AV
H	2483.50	78.93	52.23	2.86	27.44	57	74	-17	PK
H	2483.50	61.33	52.23	2.86	27.44	39.4	54	-14.6	AV

Polar (H/V)	Frequency	Meter Reading	Pre- amplifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
Operation frequency: 2402 GFSK 2Mbps									
V	2400.00	65.75	52.13	2.52	27.46	43.6	74	-30.4	PK
V	2400.00	59.95	52.13	2.52	27.46	37.8	54	-16.2	AV
H	2400.00	65.45	52.13	2.52	27.46	43.3	74	-30.7	PK
H	2400.00	59.75	52.13	2.52	27.46	37.6	54	-16.4	AV
Polar (H/V)	Frequency	Meter Reading	Pre- amplifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
Operation frequency:2480 GFSK 2Mbps									
V	2483.50	80.23	52.23	2.86	27.44	58.3	74	-15.7	PK
V	2483.50	62.33	52.23	2.86	27.44	40.4	54	-13.6	AV
H	2483.50	81.03	52.23	2.86	27.44	59.1	74	-14.9	PK
H	2483.50	62.63	52.23	2.86	27.44	40.7	54	-13.3	AV

Remark:

1. Emission Level = Meter Reading + Factor, Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.



4. PEAK OUTPUT POWER

4.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247 (b)(3)	Peak Output Power	1 watt or 30dBm	2400-2483.5	PASS

4.1.1 TEST PROCEDURE

The testing follows Subclause 11.9.1.1 of ANSI C63.10

The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator.

The path loss was compensated to the results for each measurement.

Set to the maximum power setting and enable the EUT transmit continuously.

The EUT was operating in controlled its channel.

Use the following spectrum analyzer settings:

Set the RBW $\geq$ DTS bandwidth.

Set VBW = 3*RBW.

Set the span $\geq$ 3*RBW

Set Sweep time = auto couple.

Set Detector = peak.

Set Trace mode = max hold.

Allow trace to fully stabilize.

Use peak marker function to determine the peak amplitude level.

4.1.2 DEVIATION FROM STANDARD

No deviation.

4.1.3 TEST SETUP



4.1.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.




4.1.5 TEST RESULTS

Results of BT DTS Tx Mode (2402MHz to 2480MHz) : Pass (TX Unit) (GFSK 1Mbps)


Channel	Frequency(MHz)	Conducted power(dBm)	Antenna Gain(dBi)	E.I.R.P.(dBm)	E.I.R.P (Watt)
0	2402	-1.19	-1.61	-2.80	0.000525
19	2440	-1.57	-1.61	-3.18	0.000481
39	2480	-1.69	-1.61	-3.30	0.000468

Test plot of Maximum Peak Conducted Output Power :
Bluetooth Communication mode (2402MHz)






Bluetooth Communication mode (2440MHz)




Bluetooth Communication mode (2480MHz)






Results of BT DTS Tx Mode (2402MHz to 2480MHz) : Pass (TX Unit) (GFSK 2Mbps)					
Channel	Frequency(MHz)	Conducted power(dBm)	Antenna Gain(dBi)	E.I.R.P(dBm)	E.I.R.P (Watt)
0	2402	-2.58	-1.61	-4.19	0.000381
19	2440	-2.47	-1.61	-4.08	0.000391
39	2480	-2.45	-1.61	-4.06	0.000393

Test plot of Maximum Peak Conducted Output Power :
Bluetooth Communication mode (2402MHz)






Bluetooth Communication mode (2440MHz)



Bluetooth Communication mode (2480MHz)





5. POWER SPECTRAL DENSITY TEST

5.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247	Power Spectral Density	8 dBm (in any 3KHz)	2400-2483.5	PASS

Spectrum Parameters	Setting
Attenuation	Auto
Span Frequency	= the frequency band of operation
RB	RBW $\geq$ 3kHz
VB	VBW $\geq$ 3RBW
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

5.1.1 TEST PROCEDURE

- a. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,

5.1.2 DEVIATION FROM STANDARD

No deviation.

5.1.3 TEST SETUP






5.1.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.


5.1.5 TEST RESULTS



Transmitter Frequency (MHz)	Maximum Power spectral density level / 3kHz band (dBm)	Maximum Power spectral density / 3kHz band limit
2402.0	-16.78	8dBm
2440.0	-17.18	8dBm
2480.0	-17.33	8dBm

**CH 0 (2402.0 MHz) (GFSK 1Mbps)****CH 19 (2440.0 MHz) (GFSK 1Mbps)**

**CH 39 (2480.0 MHz) (GFSK 1Mbps)**

Transmitter Frequency (MHz)	Maximum Power spectral density level / 3kHz band (dBm)	Maximum Power spectral density / 3kHz band limit
2402.0	-18.804	8dBm
2440.0	-19.365	8dBm
2480.0	-19.543	8dBm

CH 0 (2402.0 MHz) (GFSK 2Mbps)

**CH 19 (2440.0 MHz) (GFSK 2Mbps)****CH 39 (2480.0 MHz) (GFSK 2Mbps)**



6. 6DB BANDWIDTH TEST

6.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range(MHz)	Result
15.247(a)(2)	Bandwidth	$\geq 500\text{KHz}$ (6dB bandwidth)	2400-2483.5	PASS


6.1.1 TEST PROCEDURE

1. Set RBW = 100 kHz.
2. Set the video bandwidth (VBW) $\geq 3\text{RBW}$.
3. Detector = Peak.
4. Trace mode = max hold.
5. Sweep = auto couple.
6. Allow the trace to stabilize.
7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 20 dB relative to the maximum level measured in the fundamental emission.

6.1.2 DEVIATION FROM STANDARD

No deviation.

6.1.3 TEST SETUP




6.1.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.


6.1.5 TEST RESULTS

(GFSK 1Mbps)

Frequency Range [MHz]	6dB Bandwidth [KHz]	FCC Limits [kHz]
2402.0	707.7	> 500


**(GFSK 1Mbps)**

Frequency Range [MHz]	6dB Bandwidth [KHz]	FCC Limits [kHz]
2440.0	707.7	> 500



**(GFSK 1Mbps)**

Frequency Range [MHz]	6dB Bandwidth [KHz]	FCC Limits [kHz]
2480.0	703.3	> 500



**(GFSK 2Mbps)**

Frequency Range [MHz]	6dB Bandwidth [KHz]	FCC Limits [kHz]
2402.0	1149	> 500

Ref Value 25.00 dBm

Center Freq: 2.402000000 GHz

Radio Std: None


Trig: Free Run

Avg|Hold:> 10/10

#IFGain:Low

#Atten: 10 dB

Radio Device: BTS



Occupied Bandwidth

Total Power

6.23 dBm

2.0897 MHz

Transmit Freq Error

30.867 kHz

OBW Power

99.00 %

x dB Bandwidth

1.149 MHz

x dB

-6.00 dB

(GFSK 2Mbps)

Frequency Range [MHz]	6dB Bandwidth [KHz]	FCC Limits [kHz]
2440.0	1146	> 500

Center Freq 2.440000000 GHz

Center Freq: 2.440000000 GHz

Radio Std: None


Trig: Free Run

Avg|Hold:> 10/10

#IFGain:Low

#Atten: 10 dB

Radio Device: BTS



Occupied Bandwidth

Total Power

5.66 dBm

2.0896 MHz

Transmit Freq Error

31.295 kHz

OBW Power

99.00 %

x dB Bandwidth

1.146 MHz

x dB

-6.00 dB

**(GFSK 2Mbps)**

Frequency Range [MHz]	6dB Bandwidth [KHz]	FCC Limits [kHz]
2480.0	1144	> 500

Center Freq 2.480000000 GHz

Center Freq: 2.480000000 GHz

Radio Std: None

Trig: Free Run

Avg|Hold> 10/10

Radio Device: BTS


#IFGain:Low

#Atten: 10 dB

10 dB/div

Ref 25.00 dBm

Log



Center 2.48 GHz

#Res BW 100 kHz

#VBW 300 kHz

Span 5 MHz

Sweep 1 ms

Occupied Bandwidth

Total Power

5.28 dBm

2.0933 MHz

Transmit Freq Error

31.698 kHz

OBW Power

99.00 %

x dB Bandwidth

1.144 MHz

x dB

-6.00 dB



7. CONDUCTED BAND EMISSION MEASUREMENT

7.1 APPLIED PROCEDURES / LIMIT

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in Section 15.209(a) is not required.

Remark: Emissions under the fixed frequency mode and hopping mode have been investigated, the worst-case measurement results were recorded in the test report


7.1.1 TEST PROCEDURE

1. Set RBW = 100 kHz.
2. Set the video bandwidth (VBW) $\geq$ RBW.
3. Detector = Peak.
4. Trace mode = max hold.
5. Sweep = auto couple.
6. Allow the trace to stabilize.

7.1.2 DEVIATION FROM STANDARD

No deviation.

7.1.3 TEST SETUP



7.1.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.




7.1.5 TEST RESULTS

BAND-EDGE COMPLIANCE OF RF CONDUCTED EMISSIONS MEASUREMENT:


Frequency Range	Reference level	Limit	The highest conducted band edge emission	Result
[MHz]	[dBm]	[dBm]	[dBm]	
2400 – Lowest Fundamental (2402)	-1.49	-21.49	-49.57	PASS

Band-edge Compliance of RF Emissions – Lowest (GFSK 1Mbps)




**BAND-EDGE COMPLIANCE OF RF CONDUCTED EMISSIONS MEASUREMENT:**

Frequency Range [MHz]	Reference level [dBm]	Limit [dBm]	The highest conducted band edge emission [dBm]	Result
2483.5 - Highest Fundamental (2480)	-1.97	-21.97	-51.53	PASS

Band-edge Compliance of RF Emissions – Highest (GFSK 1Mbps)


**BAND-EDGE COMPLIANCE OF RF CONDUCTED EMISSIONS MEASUREMENT:**

Frequency Range [MHz]	Reference level [dBm]	Limit [dBm]	The highest conducted band edge emission [dBm]	Result
2400 – Lowest Fundamental (2402)	-2.70	-22.70	-34.65	PASS

Band-edge Compliance of RF Emissions – Lowest (GFSK 2Mbps)

**BAND-EDGE COMPLIANCE OF RF CONDUCTED EMISSIONS MEASUREMENT:**


Frequency Range [MHz]	Reference level [dBm]	Limit [dBm]	The highest conducted band edge emission [dBm]	Result
2483.5 - Highest Fundamental (2480)	-2.67	-22.67	-53.16	PASS


Band-edge Compliance of RF Emissions – Highest (GFSK 2Mbps)

**COMPLIANCE OF RF EMISSIONS MEASUREMENT (30MHZ-25GHZ) :****Limit :**

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in Section 15.209(a) is not required.

Remark: Emissions under the fixed frequency mode and hopping mode have been investigated, the worst-case measurement results were recorded in the test report

Compliance of RF Emissions – (GFSK 1Mbps 2402MHz) (the worst case)

**Compliance of RF Emissions – (GFSK 2Mbps 2402MHz) (the worst case)**



8. ANTENNA REQUIREMENT

8.1 STANDARD REQUIREMENT

15.203 requirement: For intentional device, according to 15.203: an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.


8.2 EUT ANTENNA

The EUT antenna is Internal Antenna, It comply with the standard requirement.




9. TEST SEUUP PHOTO

Radiated Measurement Photos (9KHz-30MHz)




Radiated Measurement Photos (30MHz-1000MHz)





Radiated Measurement Photos (Above 1000MHz)







Conducted Emission Measurement Photos





10. EUT PHOTO



***** END OF REPORT *****