



## RF EXPOSURE EVALUATION

### Maximal Permissible Exposure [MPE]

**Applicant Name:**  
Pivotal Commware  
10801 120th Ave NE #200,  
Kirkland, WA 98033  
United States

**Date of Testing:**  
9/17/2020-10/16/2020  
**Test Site/Location:**  
PCTEST Lab. Columbia, MD, USA  
**Test Report Serial No.:**  
1M2010120161-06.2AUVU

|                   |                         |
|-------------------|-------------------------|
| <b>FCC ID:</b>    | <b>2AUVU-UBR410M</b>    |
| <b>APPLICANT:</b> | <b>Pivotal Commware</b> |

|                             |                                           |
|-----------------------------|-------------------------------------------|
| <b>Application Type:</b>    | Class II Permissive Change                |
| <b>Model:</b>               | UBR410M                                   |
| <b>EUT Type:</b>            | Multi-Band Cat. M1 LTE Module             |
| <b>FCC Classifications:</b> | PCS Licensed Transmitter (PCB)            |
| <b>FCC Rule Parts:</b>      | FCC Part 1 (§1.1310) and Part 2 (§2.1091) |
| <b>Test Procedure(s):</b>   | KDB 447498 D01 v06                        |

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in FCC KDB 447498 D01 v06. Test results reported herein relate only to the item(s) tested.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

  
Randy Ortanez  
President



|                                           |                                                                                                                    |                                                |                                                                                       |                                          |
|-------------------------------------------|--------------------------------------------------------------------------------------------------------------------|------------------------------------------------|---------------------------------------------------------------------------------------|------------------------------------------|
| FCC ID: 2AUVU-UBR410M                     | <br>Proud to be part of element | <b>MAXIMUM PERMISSIBLE EXPOSURE<br/>REPORT</b> |  | <b>Approved by:</b><br>Technical Manager |
| Test Report S/N:<br>1M2010120161-06.2AUVU | Test Dates:<br>9/17/2020-10/16/2020                                                                                | EUT Type:<br>Multi-Band Cat. M1 LTE Module     |                                                                                       | Page 1 of 2                              |

## 1.1 Procedure

The procedure used to determine the RF power density was based upon a calculation for determining compliance with the MPE requirements. The radiated power (EIRP) generated by 5G mmWave antennas are measured for both the horizontal and vertical components using a spectrum analyzer. The LTE and WiFi powers used for the MPE evaluation were taken from the power levels shown on the respective Grants of Authorization.

Through use of the Friis transmission formula and knowledge of the maximum antenna gain to be used, the power density level is calculated at the minimum distance required to show compliance to the MPE limit.

### Friis Transmission Formula

Friis transmission formula:  $P_d = (P_{out} * G) / (4\pi r^2)$

Where,

$P_d$  = Power Density (mW/cm<sup>2</sup>)

$\pi$  = 3.1416

$P_{out}$  = output power to antenna (mW)

$r$  = distance between observation point and center of the radiator (cm)

$G$  = gain of antenna in linear scale

### Calculated MPE

The power density limit for General Population/Uncontrolled Exposure at each frequency is determined based on the limits found in FCC Part 1 (§1.1310).

| SU (Horizontal-DL+ Vertical-DL + LTE + WiFi) |                 |                              |                    |                |                               |                           |                                      |                                 |
|----------------------------------------------|-----------------|------------------------------|--------------------|----------------|-------------------------------|---------------------------|--------------------------------------|---------------------------------|
| Radio                                        | Frequency (GHz) | Conducted Output Power (dBm) | Antenna Gain (dBi) | Tolerance (dB) | Tolerance Maximum Power (dBm) | Measurement Distance (cm) | Calculated MPE (mW/cm <sup>2</sup> ) | MPE Limit (mW/cm <sup>2</sup> ) |
| Horizontal-DL                                | 27.5 - 28.35    | 20.00                        | 11.50              | 1.50           | 33.00                         | 21                        | 0.360                                | 1.0                             |
| Vertical-DL                                  | 27.5 - 28.35    | 20.00                        | 11.50              | 1.50           | 33.00                         | 21                        | 0.360                                | 1.0                             |
| WiFi                                         | 2.4             | 18.72                        | 1.00               | -              | 19.72                         | 21                        | 0.017                                | 1.0                             |
| LTE                                          | 0.777 - 0.787   | 25.00                        | 2.50               | -              | 27.50                         | 21                        | 0.101                                | 0.518                           |
| Total:                                       |                 |                              |                    |                |                               |                           | 0.933                                | 1.0                             |

**Table 1. Calculated MPE Data for Simultaneous Transmissions**

|                                           |                                                                                                                                                                                                              |                                                |                                                                                       |                                   |
|-------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------|---------------------------------------------------------------------------------------|-----------------------------------|
| FCC ID: 2AUVU-UBR410M                     |  <b>PCTEST</b><br>Proud to be part of  | <b>MAXIMUM PERMISSIBLE EXPOSURE<br/>REPORT</b> |  | Approved by:<br>Technical Manager |
| Test Report S/N:<br>1M2010120161-06.2AUVU | Test Dates:<br>9/17/2020-10/16/2020                                                                                                                                                                          | EUT Type:<br>Multi-Band Cat. M1 LTE Module     | Page 2 of 2                                                                           |                                   |