FCC TEST REPORT

FCC ID: 2AUVWPB700

On Behalf of

Pocketbook International SA

eBook Reader

Model No.: PB700

Prepared for	:	Pocketbook International SA
Address	:	Crocicchio Cortogna, 6, 6900, Lugano, Switzerland

Prepared By	:	Shenzhen Alpha Product Testing Co., Ltd.
Address	:	Building i, No.2, Lixin Road, Fuyong Street, Bao'an District, 518103, Shenzhen, Guangdong, China

Report Number	:	A2204211-C01-R06
Date of Receipt	:	April 27, 2022
Date of Test	:	April 27, 2022- May 19, 2022
Date of Report	:	May 19, 2022
Version Number	:	V0

ALPHA's reports is using a digital certificate that is trusted on Adobe's official server. If there is no digital certificate or the digital certificate shows damaged in your report. Please do not accept the report.

TABLE OF CONTENTS

Description Page

1. Summary of Standards And Results 6
1.1. Description of Standards and Results 6
2. General Information 7
2.1. Description of Device (EUT) 7
2.2. Accessories of Device (EUT) 8
2.3. Tested Supporting System Details 8
2.4. Block Diagram of connection between EUT and simulators 8
2.5. Test Mode Description 9
2.6. Test Conditions 10
2.7. Test Facility 10
2.8. Measurement Uncertainty 10
2.9. Test Equipment List 11
3. Maximum Peak Output power 12
3.1. Limit 12
3.2. Test Procedure 12
3.3. Test Setup 12
3.4. Test Result 12
4. Bandwidth 13
4.1. Limit 13
4.2. Test Procedure 13
4.3. Test Result 13
5. Carrier Frequency Separation 23
5.1. Limit 23
5.2. Test Procedure 23
5.3. Test Result 23
6. Number Of Hopping Channel 25
6.1. Limit 25
6.2. Test Procedure 25
6.3. Test Result 25
7. Dwell Time 27
7.1. Test limit 27
7.2. Test Procedure 27
7.3. Test Result 27
8. Radiated emissions 44
8.1. Limit 44
8.2. Block Diagram of Test setup 45
8.3. Test Procedure 46
8.4. Test Result 46
9. Band Edge Compliance 57

9.1. Block Diagram of Test Setup 57
9.2. Limit 57
9.3. Test Procedure 57
9.4. Test Result 57
10. Power Line Conducted Emissions 67
10.1. Block Diagram of Test Setup 67
10.2. Limit 67
10.3. Test Procedure 67
10.4. Test Result 68
12. Antenna Requirements 71
12.1. Limit 71
12.2. Result 71
13. Test Setup Photo 72
13.1. Photos of Radiated emission 72
13.2. Photos of Conducted Emission test 73
14. EUT photo 74

TEST REPORT DECLARATION

Applicant	:	Pocketbook International SA
Address	:	Crocicchio Cortogna, 6, 6900, Lugano, Switzerland
Manufacturer	:	JIU ZHOU GROUP (HONG KONG) HOLDINGS LIMITED
Address	:	Jinzhou Industrial Park, Gongming, Guangming New District, Shenzhen
EUT Description	:	eBook Reader
		(A) Model No. : PB700
		(B) Trademark : PocketBook

Measurement Standard Used:

FCC Rules and Regulations Part 15 Subpart C Section 15.247,

ANSI C63.10-2013

The device described above is tested by Shenzhen Alpha Product Testing Co., Ltd. to determine the maximum emission levels emanating from the device. The test results are contained in this test report and Shenzhen Alpha Product Testing Co., Ltd. is assumed of full responsibility for the accuracy and completeness of these tests.

After the test, our opinion is that EUT compliance with the requirement of the above standards.

This report applies to above tested sample only. This report shall not be reproduced in parts without written approval of Shenzhen Alpha Product Testing Co., Ltd.

Tested by (name + signature).....…..:	Yannis Wen Project Engineer	Yannis Wen
Approved by (name + signature)…....:	Simple Guan Project Manager	
Date of issue…… ……..:	May 19, 2022	

Revision History

Revision	Issue Date	Revisions	Revised By
V0	May 19, 2022	Initial released Issue	Yannis Wen

1. Summary Of Standards And Results

1.1. Description of Standards and Results

The EUT have been tested according to the applicable standards as referenced below:

Test Item	Standards Paragraph	Result
Maximum Peak Output Power	FCC Part 15: 15.247(b)(1)	P
Bandwidth	FCC Part 15: 15.215	P
Carrier Frequency Separation	FCC Part 15: 15.247(a)(1)	P
Number Of Hopping Channel	FCC Part 15: 15.247(a)(1)	P
Dwell Time	FCC Part 15: 15.247(a)(1)	P
Radiated Emission	FCC Part 15: 15.209 FCC Part 15: 15.247(d)	P
Band Edge Compliance	FCC Part 15: 15.247(d)	P
Power Line Conducted Emissions	FCC Part 15: 15.207	P
Antenna requirement	FCC Part 15: 15.203	P
Note:	1. P is an abbreviation for Pass. 2. F is an abbreviation for Fail. 3. N/A is an abbreviation for Not Applicable.	

2. General Information

2.1. Description of Device (EUT)

Description/PMN	:	eBook Reader
Model Number/HVIN(s)	:	PB700
Diff.	:	The device optional memory capacity is 16GB and 64GB. There is no difference except for appearance color and memory capacity. So all the tests were performed on a device with a capacity of 64GB
Trademark	:	PocketBook
Test Voltage	:	DC 5V from adapter with AC 120V/60Hz DC 3.7V from battery
Radio Technology	:	Bluetooth EDR
Operation frequency	:	2402MHz-2480MHz
Modulation	:	GFSK, π/4-DQPSK, 8DPSK
Channel No.	:	79 Channels
Channel Separation	:	1MHz
Antenna Type	:	Internal Antenna, max gain 2dBi. Antenna information is provided by applicant.
Software version	:	U700.6.7.xxx
Hardware version	:	V1.0

Remark:

1. The worst-case simultaneous transmission configuration was evaluated with no non-compliance found. Results in this report are only for Bluetooth EDR function, and there is no other transmitter involved.

2.2. Accessories of Device (EUT)

Accessories	:	Type-c USB cable
Manufacturer	:	Shenzhen K-star Precise Technology CO.,Ltd
Model	:	K004-00A-024
Input	:	0.5A
Output	:	2A

2.3. Tested Supporting System Details

No.	Description	Manufacturer	Model	Serial Number	Certification or SDOC
1.	Notebook PC	Lenovo	ThinkPad E14	N/A	**SDOC**
2	AC ADAPTER	Shenzhen HUONIU Technology Co., Ltd.	HNFCQC3024UU	N/A	N/A

2.4. Block Diagram of connection between EUT and simulators



2.5. Test Mode Description

The test software “RFTestTool.app” was used to control EUT work in Continuous TX mode, and select test channel, wireless mode

Tested mode, channel, and data rate information		
Mode	Channel	Frequency (MHz)
Carrier Tx Mode	CH0	2402
	CH39	2441
	CH78	2480
GFSK / Pi/4-DQPSK/8DPSK hopping on Tx Mode	CH0 to CH78	2402 to 2480
GFSK / Pi/4-DQPSK/8DPSK hopping off Tx Mode	CH0	2402
	CH39	2441
	CH78	2480

Setting output power (Max)		
GFSK	4-DQPSK	8DPSK
2.5±1dBm	2.5±1dBm	2.5±1dBm

2.6. Test Conditions

Items	Required	Actual
Temperature range:	15-35℃	25℃
Humidity range:	25-75%	56%
Pressure range:	86-106kPa	98kPa

2.7. Test Facility

Shenzhen Alpha Product Testing Co., Ltd
Building i, No.2, Lixin Road, Fuyong Street, Bao'an District, 518103,
Shenzhen, Guangdong, China

June 21, 2018 File on Federal Communication Commission
Registration Number: 293961
Designation Number: CN1236
July 15, 2019 Certificated by IC
Registration Number: CN0085

2.8. Measurement Uncertainty

(95% confidence levels, k=2)

Item	**Uncertainty**
Uncertainty for Power point Conducted Emissions Test	1.63dB
Uncertainty for Radiation Emission test in 3m chamber (below 30MHz)	3.5dB
Uncertainty for Radiation Emission test in 3m chamber (30MHz to 1GHz)	3.74dB(Polarize: V)
	3.76dB(Polarize: H)
Uncertainty for Radiation Emission test in 3m chamber (1GHz to 25GHz)	3.77dB(Polarize: V)
	3.80dB(Polarize: H)
Uncertainty for radio frequency	5.06×10^{-8}GHz
Uncertainty for conducted RF Power	0.40dB
Uncertainty for temperature	0.2℃
Uncertainty for humidity	1%
Uncertainty for DC and low frequency voltages	0.06%

2.9. Test Equipment List

Equipment	Manufacture	Model No.	Serial No.	Last cal.	Cal Interval
9*6*6 anechoic chamber	CHENYU	9*6*6	N/A	2020.09.02	3Year
Spectrum analyzer	ROHDE&SCHWARZ	FSV40-N	102137	2021.08.25	1Year
Spectrum analyzer	Agilent	N9020A	MY499100060	2021.08.25	1Year
Receiver	ROHDE&SCHWARZ	ESR	1316.3003K03-102082-Wa	2021.08.25	1Year
Receiver	R&S	ESCI	101165	2021.08.25	1Year
Bilog Antenna	Schwarzbeck	VULB 9168	VULB 9168#627	2021.08.30	2Year
Horn Antenna	SCHWARZBECK	BBHA 9120 D	2106	2021.08.30	2Year
Active Loop Antenna	SCHWARZBECK	FMZB 1519B	00059	2021.08.30	2Year
RF Cable	Resenberger	Cable 1	RE1	2021.08.25	1Year
RF Cable	Resenberger	Cable 2	RE2	2021.08.25	1Year
RF Cable	Resenberger	Cable 3	CE1	2021.08.25	1Year
Pre-amplifier	HP	HP8347A	2834A00455	2021.08.25	1Year
Pre-amplifier	Agilent	8449B	3008A02664	2021.08.25	1Year
L.I.S.N.#1	Schwarzbeck	NSLK8126	8126-466	2021.08.25	1Year
L.I.S.N.#2	ROHDE&SCHWARZ	ENV216	101043	2021.08.25	1 Year
Horn Antenna	SCHWARZBECK	BBHA9170	00946	2021.08.30	2 Year
Preamplifier	SKET	LNPA_1840-50	SK2018101801	2021.08.25	1 Year
Power Meter	Agilent	E9300A	MY41496628	2021.08.25	1 Year
Power Sensor	DARE	RPR3006W	15100041SNO91	2021.08.25	1 Year
Temp. & Humid. Chamber	Weihuang	WHTH-1000-40-880	100631	2022.04.21	1 Year
Switching Mode Power Supply	JUNKE	JK12010S	20140927-6	2021.08.25	1 Year

3. Maximum Peak Output Power

3.1. Limit

Please refer FCC part 15.247 & RSS-247..

For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 watts, the e.i.r.p shall not exceed 4W

3.2. Test Procedure

The transmitter output is connected to the RF Power meter. The Power meter is set to the peak power detection.

3.3. Test Setup



3.4. Test Result

Mode	Freq (MHz)	PK Output Power (dBm)	Limit (dBm)	Result
GFSK	2402	2.369	21	Pass
	2441	3.46	21	Pass
	2480	3.047	21	Pass
π/4 DQPSK	2402	3.412	21	Pass
	2441	2.758	21	Pass
	2480	2.679	21	Pass
8DPSK	2402	3.416	21	Pass
	2441	3.286	21	Pass
	2480	3.089	21	Pass
Conclusion: PASS				

4. Bandwidth

4.1. Limit

Intentional radiators operating under the alternative provisions to the general emission limits, as contained in RSS-GEN, FCC Section 15.247(a)(1), must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated.

4.2. Test Procedure

The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The bandwidth of the fundamental frequency was measured by spectrum analyzer with 30kHz RBW and 100kHz VBW. The 20dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 20dB.

4.3. Test Result

Condition	Mode	Frequency (MHz)	Antenna	99% OBW (MHz)	-20 dB Bandwidth (MHz)	Limit -20 dB Bandwidth (MHz)	Verdict
NVNT	1-DH1	2402	Ant 1	0.933	1.03	/	Pass
NVNT	1-DH1	2441	Ant 1	0.925	1.042	/	Pass
NVNT	1-DH1	2480	Ant 1	0.957	1.034	/	Pass
NVNT	2-DH1	2402	Ant 1	1.173	1.282	/	Pass
NVNT	2-DH1	2441	Ant 1	1.169	1.3	/	Pass
NVNT	2-DH1	2480	Ant 1	1.175	1.296	/	Pass
NVNT	3-DH1	2402	Ant1	1.155	1.274	/	Pass
NVNT	3-DH1	2441	Ant1	1.153	1.272	/	Pass
NVNT	3-DH1	2480	Ant1	1.147	1.288	/	Pass

OBW NVNT 1-DH1 2402MHz Ant1



Date: 5.MAY.2022 11:01:33

-20 dB BW NVNT 1-DH1 2402MHz Ant1



Date: 5.MAY.2022 11:01:41

OBW NVNT 1-DH1 2441MHz Ant1



Date: 5.MAY.2022 11:03:09

-20 dB BW NVNT 1-DH1 2441MHz Ant1



Date: 5.MAY.2022 11:03:17

OBW NVNT 1-DH1 2480MHz Ant1



Date: 5.MAY.2022 11:08:20

-20 dB BW NVNT 1-DH1 2480MHz Ant1

Date: 5.MAY.2022 11:08:29

OBW NVNT 2-DH1 2402MHz Ant1



Date: 5.MAY.2022 11:32:04

-20 dB BW NVNT 2-DH1 2402MHz Ant1



Date: 5.MAY.2022 11:32:14

OBW NVNT 2-DH1 2441MHz Ant1



Date: 5.MAY.2022 11:16:11

-20 dB BW NVNT 2-DH1 2441MHz Ant1



Date: 5.MAY.2022 11:16:21

OBW NVNT 2-DH1 2480MHz Ant1



Date: 5.MAY.2022 11:45:32

-20 dB BW NVNT 2-DH1 2480MHz Ant1



Date: 5.MAY.2022 11:45:44

OBW NVNT 3-DH1 2402MHz Ant1



Date: 5.MAY.2022 11:34:24

-20 dB BW NVNT 3-DH1 2402MHz Ant1



Date: 5.MAY.2022 11:34:35

OBW NVNT 3-DH1 2441MHz Ant1



Date: 5.MAY.2022 11:29:53

-20 dB BW NVNT 3-DH1 2441MHz Ant1



Date: 5.MAY.2022 11:30:03

OBW NVNT 3-DH1 2480MHz Ant1



Date: 5.MAY.2022 11:36:12

-20 dB BW NVNT 3-DH1 2480MHz Ant1



Date: 5.MAY.2022 11:36:24

5. Carrier Frequency Separation

5.1. Limit

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW

5.2. Test Procedure

The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The carrier frequency was measured by spectrum analyzer with 30kHz RBW and 100kHz VBW.

5.3. Test Result

Condition	Mode	Hopping Freq1 (MHz)	Hopping Freq2 (MHz)	HFS (MHz)	Limit (MHz)	Verdict
NVNT	1-DH1	2441.024	2442.031	1.007	1	Pass
NVNT	2-DH1	2440.854	2441.858	1.004	0.025	Pass
NVNT	3-DH1	2440.856	2441.856	1	0.848	Pass

CFS NVNT 1-DH1 2441MHz Ant1



CFS NVNT 2-DH1 2441MHz Ant1



Date: 5.MAY.2022 12:14:48

CFS NVNT 3-DH1 2441MHz Ant1



Date: 5.MAY.2022 12:40:24

6. Number Of Hopping Channel

6.1. Limit

Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels

6.2. Test Procedure

The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The number of hopping channel was measured by spectrum analyzer with 100kHz RBW and 300KHz VBW.

6.3. Test Result

Condition	Mode	Hopping Number	Limit	Verdict
NVNT	1-DH1	79	15	Pass
NVNT	2-DH1	79	15	Pass
NVNT	3-DH1	79	15	Pass

Hopping No. NVNT 1-DH1 2441MHz Ant1



Hopping No. NVNT 2-DH1 2441MHz Ant1



Date: 5.MAY.2022 12:15:39

Hopping No. NVNT 3-DH1 2441MHz Ant1



Date: 5.MAY.2022 12:43:39

7. Dwell Time

7.1. Test limit

Please refer FCC part 15.247 & RSS-247.

Frequency hopping systems operating in the 2400MHz-2483.5 MHz. The average time of occupancy on any frequency shall not greater than 0.4 s within period of 0.4 sec- onds multiplied by the number of hopping channel employed.

7.2. Test Procedure

7.2.1. Place the EUT on the table and set it in transmitting mode.

7.2.2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.

7.2.3. Set center frequency of spectrum analyzer = operating frequency.

7.2.4. Set the spectrum analyzer as RBW, VBW=1MHz, Span = 0Hz, Sweep = auto.

7.2.5. Repeat above procedures until all frequency measured were complete.

7.3. Test Result

PASS.

Detailed information please see the following page.

Condition	Mode	Frequency (MHz)	Antenna	Pulse Time (ms)	Total Dwell Time (ms)	Burst Count	Period Time (ms)	Limit (ms)	Verdict
NVNT	1-DH1	2402	Ant1	0.395	126.400	319	31600	400	Pass
NVNT	1-DH1	2441	Ant1	0.395	126.400	318	31600	400	Pass
NVNT	1-DH1	2480	Ant1	0.394	126.080	318	31600	400	Pass
NVNT	1-DH3	2441	Ant1	1.65	264.000	165	31600	400	Pass
NVNT	1-DH5	2441	Ant1	2.899	309.227	106	31600	400	Pass
NVNT	2-DH1	2402	Ant1	0.405	129.600	317	31600	400	Pass
NVNT	2-DH1	2441	Ant1	0.404	129.280	319	31600	400	Pass
NVNT	2-DH1	2480	Ant1	0.405	129.600	320	31600	400	Pass
NVNT	2-DH3	2441	Ant1	1.656	264.960	158	31600	400	Pass
NVNT	2-DH5	2441	Ant1	2.904	309.760	101	31600	400	Pass
NVNT	3-DH1	2402	Ant1	0.405	129.600	318	31600	400	Pass
NVNT	3-DH1	2441	Ant1	0.404	129.280	318	31600	400	Pass
NVNT	3-DH1	2480	Ant1	0.404	129.280	318	31600	400	Pass
NVNT	3-DH3	2441	Ant1	1.655	264.800	158	31600	400	Pass
NVNT	3-DH5	2441	Ant1	2.906	309.973	112	31600	400	Pass

Remark: Dwell Time = Pulse Time * Burst Count

Dwell NVNT 1-DH1 2402MHz Ant1 One Burst



Dwell NVNT 1-DH1 2402MHz Ant1 Accumulated



Date: 5.MAY.2022 11:49:35

Dwell NVNT 1-DH1 2441MHz Ant1 One Burst



Date: 5.MAY.2022 11:57:38

Dwell NVNT 1-DH1 2441MHz Ant1 Accumulated



Date: 5.MAY.2022 11:58:12

Dwell NVNT 1-DH1 2480MHz Ant1 One Burst



Date: 5.MAY.2022 11:58:36

Dwell NVNT 1-DH1 2480MHz Ant1 Accumulated



Date: 5.MAY.2022 11:59:10

Dwell NVNT 1-DH3 2441MHz Ant1 One Burst



Date: 5.MAY.2022 12:08:05

Dwell NVNT 1-DH3 2441MHz Ant1 Accumulated



Date: 5.MAY.2022 12:08:39

Dwell NVNT 1-DH5 2441MHz Ant1 One Burst



Date: 5.MAY.2022 12:09:03

Dwell NVNT 1-DH5 2441MHz Ant1 Accumulated



Date: 5.MAY.2022 12:09:38

Dwell NVNT 2-DH1 2402MHz Ant1 One Burst



Date: 5.MAY.2022 12:12:09

Dwell NVNT 2-DH1 2402MHz Ant1 Accumulated



Date: 5.MAY.2022 12:12:44

Dwell NVNT 2-DH1 2441MHz Ant1 One Burst



Date: 5.MAY.2022 12:29:26

Dwell NVNT 2-DH1 2441MHz Ant1 Accumulated



Date: 5.MAY.2022 12:30:01

Dwell NVNT 2-DH1 2480MHz Ant1 One Burst



Date: 5.MAY.2022 12:30:26

Dwell NVNT 2-DH1 2480MHz Ant1 Accumulated



Date: 5.MAY.2022 12:31:01

Dwell NVNT 2-DH3 2441MHz Ant1 One Burst



Date: 5.MAY.2022 12:33:00

Dwell NVNT 2-DH3 2441MHz Ant1 Accumulated



Date: 5.MAY.2022 12:33:34

Dwell NVNT 2-DH5 2441MHz Ant1 One Burst



Date: 5.MAY.2022 12:34:38

Dwell NVNT 2-DH5 2441MHz Ant1 Accumulated



Date: 5.MAY.2022 12:35:13

Dwell NVNT 3-DH1 2402MHz Ant1 One Burst



Date: 5.MAY.2022 12:35:58

Dwell NVNT 3-DH1 2402MHz Ant1 Accumulated



Date: 5.MAY.2022 12:36:33

Dwell NVNT 3-DH1 2441MHz Ant1 One Burst



Date: 5.MAY.2022 12:43:57

Dwell NVNT 3-DH1 2441MHz Ant1 Accumulated



Date: 5.MAY.2022 12:44:31

Dwell NVNT 3-DH1 2480MHz Ant1 One Burst



Date: 5.MAY.2022 12:44:46

Dwell NVNT 3-DH1 2480MHz Ant1 Accumulated



Date: 5.MAY.2022 12:45:21

Dwell NVNT 3-DH3 2441MHz Ant1 One Burst



Date: 5.MAY.2022 12:48:25

Dwell NVNT 3-DH3 2441MHz Ant1 Accumulated



Date: 5.MAY.2022 12:48:59

Dwell NVNT 3-DH5 2441MHz Ant1 One Burst



Date: 5.MAY.2022 12:54:27

Dwell NVNT 3-DH5 2441MHz Ant1 Accumulated



Date: 5.MAY.2022 12:55:02

8. Radiated Emissions

8.1. Limit

All the emissions appearing within 15.205 restricted frequency bands shall not exceed the limits shown in 15.209, all the other emissions shall be at least 20dB below the fundamental emissions, or comply with 15.209 limits.

15.205 Restricted frequency band

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
[1]0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 - 156.52525	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.7 - 156.9	2690 - 2900	22.01 - 23.12
8.41425 - 8.41475	162.0125 - 167.17	3260 - 3267	23.6 - 24.0
12.29 - 12.293	167.72 - 173.2	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	240 - 285	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	322 - 335.4	3600 - 4400	([2])

15.209 Limit

FREQUENCY MHz	DISTANCE Meters	FIELD STRENGTHS LIMIT	
		μV/m	dB(μV)/m
0.009-0.490	300	2400/F(KHz)	/
0.490-1.705	30	24000/F(KHz)	/
1.705-30	30	30	29.5
30 ~ 88	3	100	40.0
88 ~ 216	3	150	43.5
216 ~ 960	3	200	46.0
960 ~ 1000	3	500	54.0
Above 1000	3	74.0 dB(μV)/m (Peak) 54.0 dB(μV)/m (Average)	

Note: The peak limit is 20 dB higher than the average limit

8.2. Block Diagram of Test setup

8.2.1 In 3m Anechoic Chamber Test Setup Diagram for below 30MHz



8.2.1 In 3m Anechoic Chamber Test Setup Diagram for below 1GHz



8.2.2 In 3m Anechoic Chamber Test Setup Diagram for frequency above 1GHz



Note: For harmonic emissions test a appropriate high pass filter was inserted in the input port of AMP.

8.3. Test Procedure

(1) EUT was placed on a non-metallic table, 80 cm above the ground plane inside a semi-anechoic chamber.

(2) Setup EUT and simulator

(3) Test antenna was located 3m from the EUT on an adjustable mast. Below pre-scan procedure was first performed in order to find prominent radiated emissions.

(a) Change work frequency or channel of device if practicable.

(b) Change modulation type of device if practicable.

(c) Rotated EUT though three orthogonal axes to determine the attitude of EUT arrangement produces highest emissions

(4) Spectrum frequency from 9KHz to 25GHz (tenth harmonic of fundamental frequency) was investigated

(5) For final emissions measurements at each frequency of interest, the EUT were rotated and the antenna height was varied between 1m and 4m in order to maximize the emission. Measurements in both horizontal and vertical polarities were made and the data was recorded. In order to find the maximum emission, the relative positions of equipments and all of the interface cables were changed according to ANSI C63.10 :2013on Radiated Emission test.

(6) For emissions above 1GHz, both Peak and Average level were measured with Spectrum Analyzer, and the RBW is set at 1MHz, VBW is set at 3MHz for Peak measure; RBW is set at 1MHz, VBW is set at 10Hz for Average measure.

8.4. Test Result

We have scanned from 9kHz to the 10th harmonic of the EUT's highest frequency.
Detailed information please see the following page.

From 9KHz to 30MHz: Conclusion: PASS

Note: The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

From 30MHz to 1000MHz: Conclusion: PASS

Vertical:



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Margin		Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1		31.8390	10.56	13.60	24.16	40.00	-15.84	peak			
2	*	46.8138	12.44	14.08	26.52	40.00	-13.48	peak			
3		126.4172	9.88	13.39	23.27	43.50	-20.23	peak			
4		159.7284	10.30	15.04	25.34	43.50	-18.16	peak			
5		391.3625	9.80	16.10	25.90	46.00	-20.10	peak			
6		568.7456	11.23	19.52	30.75	46.00	-15.25	peak			

Note:1. *:Maximum data; x:Over limit; !:over margin.
2.Measurement=Reading Level+Correct Factor; Correct Factor=Antenna Factor+Cable Loss.

Horizontal:



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Margin		Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1		39.5665	9.31	14.47	23.78	40.00	-16.22	peak			
2		47.8148	9.54	14.08	23.62	40.00	-16.38	peak			
3		151.7213	9.87	15.06	24.93	43.50	-18.57	peak			
4		297.1545	9.94	14.04	23.98	46.00	-22.02	peak			
5		557.8817	10.48	19.33	29.81	46.00	-16.19	peak			
6	*	786.1035	10.87	22.82	33.69	46.00	-12.31	peak			

Note:1. *:Maximum data; x:Over limit; !:over margin.
2.Measurement=Reading Level+Correct Factor; Correct Factor=Antenna Factor+Cable Loss.

Remark: All modes have been tested, and only worst data of GFSK mode, Channel 2441MHz (AC 120V/ 60Hz) was listed in this report.

From 1G-25GHz

Test Mode: GFSK TX Low									
Freq (MHz)	Read Level (dBuV/m)	Polar (H/V)	Antenna Factor (dB/m)	Cable loss(dB)	Amp Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
4804	46.26	V	33.95	10.18	34.26	56.13	74	-17.87	PK
4804	35.34	V	33.95	10.18	34.26	45.21	54	-8.79	AV
7206	/	/	/	/	/	/	/	/	/
9608	/	/	/	/	/	/	/	/	/
4804	45.76	H	33.95	10.18	34.26	55.63	74	-18.37	PK
4804	37.16	H	33.95	10.18	34.26	47.03	54	-6.97	AV
7206	/	/	/	/	/	/	/	/	/
9608	/	/	/	/	/	/	/	/	/
Test Mode: GFSK TX Mid									
4882	42.19	V	33.93	10.2	34.29	52.03	74	-21.97	PK
4882	36.23	V	33.93	10.2	34.29	46.07	54	-7.93	AV
7323	/	/	/	/	/	/	/	/	/
9764	/	/	/	/	/	/	/	/	/
4882	43.87	H	33.93	10.2	34.29	53.71	74	-20.29	PK
4882	35.27	H	33.93	10.2	34.29	45.11	54	-8.89	AV
7323	/	/	/	/	/	/	/	/	/
9764	/	/	/	/	/	/	/	/	/
Test Mode: GFSK TX High									
4960	45.30	V	33.98	10.22	34.25	55.25	74	-18.75	PK
4960	33.93	V	33.98	10.22	34.25	43.88	54	-10.12	AV
7440	/	/	/	/	/	/	/	/	/
9920	/	/	/	/	/	/	/	/	/
4960	41.99	H	33.98	10.22	34.25	51.94	74	-22.06	PK
4960	33.49	H	33.98	10.22	34.25	43.44	54	-10.56	AV
7440	/	/	/	/	/	/	/	/	/
9920	/	/	/	/	/	/	/	/	/

Note:
1, Result = Read level + Antenna factor + cable loss-Amp factor
2, All the other emissions not reported were too low to read and deemed to comply with FCC limit.

From 1G-25GHz

Test Mode: π/4 DQPSK TX Low									
Freq (MHz)	Read Level (dBuV/m)	Polar (H/V)	Antenna Factor (dB/m)	Cable loss(dB)	Amp Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
4804	45.82	V	33.95	10.18	34.26	55.69	74	-18.31	PK
4804	35.26	V	33.95	10.18	34.26	45.13	54	-8.87	AV
7206	/	/	/	/	/	/	/	/	/
9608	/	/	/	/	/	/	/	/	/
4804	47.65	H	33.95	10.18	34.26	57.52	74	-16.48	PK
4804	37.97	H	33.95	10.18	34.26	47.84	54	-6.16	AV
7206	/	/	/	/	/	/	/	/	/
9608	/	/	/	/	/	/	/	/	/
Test Mode: π/4 DQPSK TX Mid									
4882	44.59	V	33.93	10.2	34.29	54.43	74	-19.57	PK
4882	33.77	V	33.93	10.2	34.29	43.61	54	-10.39	AV
7323	/	/	/	/	/	/	/	/	/
9764	/	/	/	/	/	/	/	/	/
4882	44.41	H	33.93	10.2	34.29	54.25	74	-19.75	PK
4882	36.60	H	33.93	10.2	34.29	46.44	54	-7.56	AV
7323	/	/	/	/	/	/	/	/	/
9764	/	/	/	/	/	/	/	/	/
Test Mode: π/4 DQPSK TX High									
4960	46.25	V	33.98	10.22	34.25	56.20	74	-17.80	PK
4960	35.45	V	33.98	10.22	34.25	45.40	54	-8.60	AV
7440	/	/	/	/	/	/	/	/	/
9920	/	/	/	/	/	/	/	/	/
4960	44.90	H	33.98	10.22	34.25	54.85	74	-19.15	PK
4960	35.09	H	33.98	10.22	34.25	45.04	54	-8.96	AV
7440	/	/	/	/	/	/	/	/	/
9920	/	/	/	/	/	/	/	/	/

Note:
1, Result = Read level + Antenna factor + cable loss-Amp factor
2, All the other emissions not reported were too low to read and deemed to comply with FCC limit.

From 1G-25GHz

Test Mode: π/4 DQPSK TX Low									
Freq (MHz)	Read Level (dBuV/m)	Polar (H/V)	Antenna Factor (dB/m)	Cable loss(dB)	Amp Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
4804	44.35	V	33.95	10.18	34.26	54.22	74	-19.78	PK
4804	34.70	V	33.95	10.18	34.26	44.57	54	-9.43	AV
7206	/	/	/	/	/	/	/	/	/
9608	/	/	/	/	/	/	/	/	/
4804	46.02	H	33.95	10.18	34.26	55.89	74	-18.11	PK
4804	34.70	H	33.95	10.18	34.26	44.57	54	-9.43	AV
7206	/	/	/	/	/	/	/	/	/
9608	/	/	/	/	/	/	/	/	/
Test Mode: π/4 DQPSK TX Mid									
4882	43.05	V	33.93	10.2	34.29	52.89	74	-21.11	PK
4882	33.33	V	33.93	10.2	34.29	43.17	54	-10.83	AV
7323	/	/	/	/	/	/	/	/	/
9764	/	/	/	/	/	/	/	/	/
4882	44.99	H	33.93	10.2	34.29	54.83	74	-19.17	PK
4882	34.44	H	33.93	10.2	34.29	44.28	54	-9.72	AV
7323	/	/	/	/	/	/	/	/	/
9764	/	/	/	/	/	/	/	/	/
Test Mode: π/4 DQPSK TX High									
4960	45.22	V	33.98	10.22	34.25	55.17	74	-18.83	PK
4960	35.91	V	33.98	10.22	34.25	45.86	54	-8.14	AV
7440	/	/	/	/	/	/	/	/	/
9920	/	/	/	/	/	/	/	/	/
4960	43.30	H	33.98	10.22	34.25	53.25	74	-20.75	PK
4960	33.30	H	33.98	10.22	34.25	43.25	54	-10.75	AV
7440	/	/	/	/	/	/	/	/	/
9920	/	/	/	/	/	/	/	/	/

Note:
1, Result = Read level + Antenna factor + cable loss-Amp factor
2, All the other emissions not reported were too low to read and deemed to comply with FCC limit.

Conducted RF Spurious Emission

Tx. Spurious NVNT 1-DH1 2402MHz Ant1 Emission



Date: 5.MAY.2022 11:02:16

Tx. Spurious NVNT 1-DH1 2441MHz Ant1 Emission



Date: 5.MAY.2022 11:03:42

Tx. Spurious NVNT 1-DH1 2480MHz Ant1 Emission



Date: 5.MAY.2022 11:09:06

Tx. Spurious NVNT 2-DH1 2402MHz Ant1 Emission



Date: 5.MAY.2022 11:32:56

Tx. Spurious NVNT 2-DH1 2441MHz Ant1 Emission



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	2.4409 GHz	-0.32 dBm		
M2		1	17.140208 GHz	-37.64 dBm		
M3		1	4.70372 GHz	-40.75 dBm		
M4		1	7.236899 GHz	-42.65 dBm		
M5		1	9.875075 GHz	-40.29 dBm		

Date: 5.MAY.2022 11:16:45

Tx. Spurious NVNT 2-DH1 2480MHz Ant1 Emission



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	2.4806 GHz	-0.32 dBm		
M2		1	16.954918 GHz	-38.20 dBm		
M3		1	5.048712 GHz	-41.41 dBm		
M4		1	7.586303 GHz	-42.37 dBm		
M5		1	10.016249 GHz	-40.96 dBm		

Date: 5.MAY.2022 11:46:29

Tx. Spurious NVNT 3-DH1 2402MHz Ant1 Emission



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	2.40207 GHz	1.43 dBm		
M2		1	16.952271 GHz	-37.98 dBm		
M3		1	4.973714 GHz	-41.31 dBm		
M4		1	7.015433 GHz	-42.52 dBm		
M5		1	9.654492 GHz	-40.58 dBm		

Date: 5.MAY.2022 11:35:18

Tx. Spurious NVNT 3-DH1 2441MHz Ant1 Emission



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	2.4409 GHz	0.03 dBm		
M2		1	22.640674 GHz	-37.11 dBm		
M3		1	5.009889 GHz	-41.24 dBm		
M4		1	7.467188 GHz	-40.92 dBm		
M5		1	9.776254 GHz	-40.80 dBm		

Date: 5.MAY.2022 11:30:28

Tx. Spurious NVNT 3-DH1 2480MHz Ant1 Emission



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	2.47972 GHz	-4.05 dBm		
M2		1	16.947859 GHz	-37.46 dBm		
M3		1	5.0593 GHz	-40.64 dBm		
M4		1	7.27131 GHz	-41.98 dBm		
M5		1	9.97125 GHz	-41.14 dBm		

Date: 5.MAY.2022 11:37:08

9. Band Edge Compliance

9.1. Block Diagram of Test Setup



9.2. Limit

All the lower and upper band-edges emissions appearing within restricted frequency bands shall not exceed the limits shown in FCC part 15.209 and RSS-GEN, all the other emissions outside operation shall be at least 20dB below the fundamental emissions, or comply with FCC part 15.209 and RSS-GEN limits.

9.3. Test Procedure

Refer to ANSI C 63.10, Clause 6.10.

All restriction band and non- restriction band have been tested, only worse case is reported.

9.4. Test Result

PASS. (See below detailed test data)

Radiated Method:

Test Mode: GFSK-Low



hopping-off



hopping-on

Test Mode: GFSK-High



hopping-off



hopping-on

Test Mode: π/4 DQPSK-Low



hopping-off



hopping-on

Test Mode: π/4 DQPSK-High



hopping-off



hopping-on

Test Mode: 8DPSK-Low



hopping-off



hopping-on

Test Mode: 8DPSK-High



hopping-off



hopping-on

Note: 1. *:Maximum data; x:Over limit; !:over margin.

2.Measurement=Reading Level+Correct Factor; Correct Factor=Antenna Factor+Cable Loss.

Conducted Method

GFSK Mode:

Test channel:	Lowest channel
	
No-hopping mode	Hopping mode

Test channel:	Highest channel
	
No-hopping mode	Hopping mode

Pi/4QPSK Mode:

Test channel:	Lowest channel
	
No-hopping mode	Hopping mode

Test channel:	Highest channel
	
No-hopping mode	Hopping mode

8DPSK Mode:

Test channel:	Lowest channel
	
No-hopping mode	Hopping mode

Test channel:	Highest channel
	
No-hopping mode	Hopping mode

10. Power Line Conducted Emissions

10.1.Block Diagram of Test Setup



10.2.Limit

Frequency	Maximum RF Line Voltage	
	Quasi-Peak Level dB(μV)	Average Level dB(μV)
150kHz ~ 500kHz	66 ~ 56*	56 ~ 46*
500kHz ~ 5MHz	56	46
5MHz ~ 30MHz	60	50

Notes: 1. * Decreasing linearly with logarithm of frequency.

2. The lower limit shall apply at the transition frequencies.

10.3.Test Procedure

(1) The EUT was placed on a non-metallic table, 80cm above the ground plane.

(2) Setup the EUT and simulator as shown in 10.1

(3) The EUT Power connected to the power mains through a power adapter and a line impedance stabilization network (L.I.S.N1). The other peripheral devices power cord connected to the power mains through a line impedance stabilization network (L.I.S.N2), this provided a 50-ohm coupling impedance for the EUT (Please refer to the block diagram of the test setup and photographs). Both sides of power line were checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipments and all of the interface cables were changed according to ANSI C63.10:2013on conducted Emission test.

(4) The bandwidth of test receiver is set at 10KHz.

(5) The frequency range from 150 KHz to 30MHz is checked.

10.4.Test Result

PASS. (See below detailed test data)

Note: If peak Result comply with AV limit, QP and AV Result is deemed to comply with AV limit

Line:



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Margin		
		MHz	dBuV	dB	dBuV	dBuV	dB	Detector	Comment
1		0.6120	14.99	9.92	24.91	56.00	-31.09	peak	
2	*	1.3530	25.44	9.89	35.33	56.00	-20.67	peak	
3		2.4090	23.67	9.90	33.57	56.00	-22.43	peak	
4		6.3869	28.47	10.10	38.57	60.00	-21.43	peak	
5		9.6630	25.77	10.20	35.97	60.00	-24.03	peak	
6		18.1470	23.14	10.42	33.56	60.00	-26.44	peak	

*:Maximum data x:Over limit !:over margin 〈Reference Only

Note: Measurement=Reading Level+Correc Factor. Factor=(LISN or ISN or PLC or Current Probe)Factor+Cable

Neutral:



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Margin		
		MHz	dBuV	dB	dBuV	dBuV	dB	Detector	Comment
1		0.5610	17.06	9.94	27.00	56.00	-29.00	peak	
2		0.9510	25.69	9.94	35.63	56.00	-20.37	peak	
3		2.0369	23.91	9.88	33.79	56.00	-22.21	peak	
4	*	6.4560	31.35	10.10	41.45	60.00	-18.55	peak	
5		10.1760	30.59	10.21	40.80	60.00	-19.20	peak	
6		22.0230	26.48	10.46	36.94	60.00	-23.06	peak	

*:Maximum data x:Over limit !:over margin 〈Reference Only

Note: Measurement=Reading Level+Correc Factor. Factor=(LISN or ISN or PLC or Current Probe)Factor+Cable

Remark: All modes have been tested, and only worst data of GFSK mode, Channel 2441MHz (AC 120V/ 60Hz) was listed in this report.

11. Antenna Requirements

11.1.Limit

For intentional device, according to FCC 47 CFR Section 15.203 and RSS-GEN, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

11.2.Result

The EUT antenna is internal antenna. It complies with the standard requirement.

12. Test Setup Photo

12.1. Photos of Radiated emission



12.2.Photos of Conducted Emission test

13. EUT Photo


PocketBook Era
Latest generation 7-inch E Ink Carta™ 1200 screen
Enhanced anti-scratch screen protection and IP68 waterproof
Glare-free screen with 1264 × 1680 and 300 dpi
Built-in speaker, Bluetooth and Text-to-Speech function
PocketBook


LOW BATTERY!
Please connect device to a compatible power source.
PocketBook Era
Latest generation 7-inch E Ink Carta™ 1200 screen
Enhanced anti-scratch screen protection and IP68 waterproof
Glare-free screen with 1264 × 1680 and 300 dpi
Built-in speaker, Bluetooth and Text-to-Speech function
PocketBook


PocketBook


PocketBook Era
7"
Glare-free screen with 1264 × 1680 and 300 dpi
Built-in speaker, Bluetooth and Text-to-Speech function
PocketBook

PocketBook Era
PocketBook


PocketBook Era

PocketBook Era

Rechargeable Li-Ion Battery:
Model No: JL2545134PL
Batch No: JL22-F24
Date of production: WK09, 2022
Manufacturer: DongGuan JinLu Battery Technology Co., Ltd.
Wires polarity: Red (+) / White (thermal sensor) / Black (-)
Made in China

Rechargeable Li-Ion Battery
Model No: JL2545134PL
Batch No: JL22-F24
Date of production: WK09, 2022
Manufacturer: DongGuan JinLu Battery Technology Co., Ltd.
Made in China

Rechargeable Li-Ion Battery: 1700mAh, 3.7V, 6.29Wh
Model No: JL2545134PL
Batch No: JL22-F24
Date of production: WK09, 2022
Manufacturer: DongGuan JinLu Battery Technology Co., Ltd.
Wires polarity: Red (+) / White (thermal sensor) / Black (-)
Cautions: Do not expose to high temperature (140F/60°C). Do not disassemble. Do not allow metal objects to contact or short circuit the battery terminals. Do not dispose of in fire or water. Do not extrude the battery. Charge only with specified charger. Deliver to recycle station.
Made in China












B288


B288


B288









---------THE END OF REPORT-------