TEST REPORT

Product Name	:	Android Tv Box
Brand Mark	:	Eon Samrt Box
FCC ID	:	2AUWA-ATV4K85198
Model No.	:	SDOTT0202
Report Number	:	BLA-EMC-202107-A7503
Date of Sample Receipt	:	2021/7/19
Date of Test	:	2021/7/19 to 2021/8/18
Date of Issue	:	2021/8/18
Test Standard	:	47 CFR Part 15, Subpart C 15.247
Test Result	:	Pass

Prepared for:

Shenzhen SDMC Technology Co.,Ltd.
7/F, W2-A, Hi-Tech, Industrial Park, Nanshan District

Prepared by:

BlueAsia of Technical Services(Shenzhen) Co.,Ltd.
Building C, No. 107, Shihuan Road, Shiyan Sub-District, Baoan District, Shenzhen, Guangdong Province, China
TEL: +86-755-23059481

Compiled by: Sven

Review by: Sweely

Approved by: Blue Zhong

Date: 2021/8/18

BlueAsia of Technical Services(Shenzhen) Co., Ltd. BLA

REPORT REVISE RECORD

Version No.	Date	Description
00	2021/8/18	Original

BlueAsia

TABLE OF CONTENTS

1 TEST SUMMARY....5
2 GENERAL INFORMATION....6
3 GENERAL DESCRIPTION OF E.U.T....6
4 TEST ENVIRONMENT....7
5 TEST MODE....7
6 MEASUREMENT UNCERTAINTY....7
7 DESCRIPTION OF SUPPORT UNIT....8
8 LABORATORY LOCATION....8
9 TEST INSTRUMENTS LIST....9
10 CONDUCTED PEAK OUTPUT POWER....13
10.1 LIMITS....13
10.2 BLOCK DIAGRAM OF TEST SETUP....13
10.3 TEST DATA....14
11 MINIMUM 6DB BANDWIDTH....15
11.1 LIMITS....15
11.2 BLOCK DIAGRAM OF TEST SETUP....15
11.3 TEST DATA....15
12 CONDUCTED EMISSIONS AT AC POWER LINE (150KHZ-30MHZ)....16
12.1 LIMITS....16
12.2 BLOCK DIAGRAM OF TEST SETUP....16
12.3 PROCEDURE....16
12.4 TEST DATA....18
13 ANTENNA REQUIREMENT....20
13.1 CONCLUSION....20
14 CONDUCTED BAND EDGES MEASUREMENT....21
14.1 LIMITS....21
14.2 BLOCK DIAGRAM OF TEST SETUP....21
14.3 TEST DATA....22
15 RADIATED SPURIOUS EMISSIONS....23

BlueAsia

15.1 LIMITS 23
15.2 BLOCK DIAGRAM OF TEST SETUP 24
15.3 PROCEDURE 24
15.4 TEST DATA 26

16 POWER SPECTRUM DENSITY 34

16.1 LIMITS 34
16.2 BLOCK DIAGRAM OF TEST SETUP 34
16.3 TEST DATA 34

17 RADIATED EMISSIONS WHICH FALL IN THE RESTRICTED BANDS 35

17.1 LIMITS 35
17.2 BLOCK DIAGRAM OF TEST SETUP 36
17.3 PROCEDURE 36
17.4 TEST DATA 38

18 CONDUCTED SPURIOUS EMISSIONS 42

18.1 LIMITS 42
18.2 BLOCK DIAGRAM OF TEST SETUP 42
18.3 TEST DATA 43

19 APPENDIX 44

APPENDIX A: PHOTOGRAPHS OF EUT 59

BlueAsia

1 TEST SUMMARY

Test item	Test Requirement	Test Method	Class/Severity	Result
Conducted Peak Output Power	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 7.8.5 & Section 11.9.1	47 CFR Part 15, Subpart C 15.247(b)(1) & 15.247(b)(3)	Pass
Minimum 6dB Bandwidth	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 11.8.1	47 CFR Part 15, Subpart C 15.247a(2)	Pass
Conducted Emissions at AC Power Line (150kHz-30MHz)	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 6.2	47 CFR Part 15, Subpart C 15.207	Pass
Antenna Requirement	47 CFR Part 15, Subpart C 15.247	N/A	47 CFR Part 15, Subpart C 15.203 & 15.247(c)	Pass
Conducted Band Edges Measurement	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 7.8.8 & Section 11.13.3.2	47 CFR Part 15, Subpart C 15.247(d)	Pass
Radiated Spurious Emissions	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 6.4,6.5,6.6	47 CFR Part 15, Subpart C 15.209 & 15.247(d)	
Power Spectrum Density	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 11.10.2	47 CFR Part 15, Subpart C 15.247(e)	Pass
Radiated Emissions which fall in the restricted bands	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 6.10.5	47 CFR Part 15, Subpart C 15.209 & 15.247(d)	Pass
Conducted Spurious Emissions	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 7.8.6 & Section 11.11	47 CFR Part 15, Subpart C 15.247(d)	Pass

BlueAsia

2 GENERAL INFORMATION

Applicant	Shenzhen SDMC Technology Co.,Ltd.
Address	7/F, W2-A, Hi-Tech, Industrial Park, Nanshan District
Manufacturer	Shenzhen SDMC Technology Co.,Ltd.
Address	7/F, W2-A, Hi-Tech, Industrial Park, Nanshan District
Factory	NA
Address	NA
Product Name	Android Tv Box
Test Model No.	SDOTT0202

3 GENERAL DESCRIPTION OF E.U.T.

Hardware Version	V2
Software Version	9.3.68 & 9.3.69

Operation Frequency:	2402MHz-2480MHz
Modulation Type:	GFSK
Channel Spacing:	2MHz
Number of Channels:	40
Antenna Type:	PCB Antenna
Antenna Gain:	3.04(provided by the applicant)

BlueAsia

4 TEST ENVIRONMENT

Environment	Temperature	Voltage
Normal	25°C	DC12V

5 TEST MODE

TEST MODE	TEST MODE DESCRIPTION
TX	Keep the EUT in transmitting mode
Remark:Only the data of the worst mode would be recorded in this report.	

6 MEASUREMENT UNCERTAINTY

Parameter	Expanded Uncertainty (Confidence of 95%)
Radiated Emission(9kHz-30MHz)	±4.34dB
Radiated Emission(30Mz-1000MHz)	±4.24dB
Radiated Emission(1GHz-18GHz)	±4.68dB
AC Power Line Conducted Emission(150kHz-30MHz)	±3.45dB

BlueAsia

7 DESCRIPTION OF SUPPORT UNIT

Device Type	Manufacturer	Model Name	Serial No.	Remark
AC/DC ADAPTOR	Zhuzhou Dachuan Electronic Technology Co., Ltd.	DCT12W120100US-A0	PPPPPPPYYMMDDXXXXXX	100~240Vac 50/60Hz 0.3A Max. Output12V1A
Power adapter	Dongguan Sunun Power Co., Ltd	SA12BV-120100U	340-500-283	100~240Vac 50/60Hz 0.4A Max. Output12V1A
MONITOR	DELL	S2817Q	N/A	N/A
HDMI Cable	Shenzhen Xinhongya Electronics Co. , Ltd.	HDMI cable	D6243-X Y-H053	L=1500MM

8 LABORATORY LOCATION

All tests were performed at:
BlueAsia of Technical Services(Shenzhen) Co., Ltd.
Building C, No. 107, Shihuan Road, Shiyan Sub-District, Baoan District, Shenzhen, Guangdong Province, China
Telephone: TEL: +86-755-28682673 FAX: +86-755-28682673
No tests were sub-contracted.

BlueAsia

9 TEST INSTRUMENTS LIST

Test Equipment Of Conducted Peak Output Power					
Equipment	**Manufacturer**	**Model**	**S/N**	**Cal.Date**	**Cal.Due**
Spectrum	R&S	FSP40	100817	2020/10/12	2021/10/11
Spectrum	Agilent	N9020A	MY49100060	2020/10/12	2021/10/11
Signal Generator	Agilent	N5182A	MY49060650	2020/10/12	2021/10/11
Signal Generator	Agilent	E8257D	MY44320250	2020/10/12	2021/10/11

Test Equipment Of Minimum 6dB Bandwidth					
Equipment	**Manufacturer**	**Model**	**S/N**	**Cal.Date**	**Cal.Due**
Spectrum	R&S	FSP40	100817	2020/10/12	2021/10/11
Spectrum	Agilent	N9020A	MY49100060	2020/10/12	2021/10/11
Signal Generator	Agilent	N5182A	MY49060650	2020/10/12	2021/10/11
Signal Generator	Agilent	E8257D	MY44320250	2020/10/12	2021/10/11

Test Equipment Of Conducted Emissions at AC Power Line (150kHz-30MHz)					
Equipment	**Manufacturer**	**Model**	**S/N**	**Cal.Date**	**Cal.Due**
Shield room	SKET	833	N/A	2020/11/25	2023/11/24
Receiver	R&S	ESPI3	101082	2020/10/12	2021/10/11
LISN	R&S	ENV216	3560.6550.15	2020/10/12	2021/10/11
LISN	AT	AT166-2	AKK1806000003	2020/10/12	2021/10/11
EMI software	EZ	EZ-EMC	EEMC-3A1	N/A	N/A

BlueAsia

Test Equipment Of Conducted Band Edges Measurement					
Equipment	**Manufacturer**	**Model**	**S/N**	**Cal.Date**	**Cal.Due**
Spectrum	R&S	FSP40	100817	2020/10/12	2021/10/11
Spectrum	Agilent	N9020A	MY49100060	2020/10/12	2021/10/11
Signal Generator	Agilent	N5182A	MY49060650	2020/10/12	2021/10/11
Signal Generator	Agilent	E8257D	MY44320250	2020/10/12	2021/10/11

Test Equipment Of Radiated Spurious Emissions					
Equipment	**Manufacturer**	**Model**	**S/N**	**Cal.Date**	**Cal.Due**
Chamber	SKET	966	N/A	2020/11/10	2023/11/9
Spectrum	R&S	FSP40	100817	2020/10/12	2021/10/11
Receiver	R&S	ESR7	101199	2020/10/12	2021/10/11
broadband Antenna	Schwarzbeck	VULB9168	00836 P:00227	2020/9/26	2022/9/25
Horn Antenna	Schwarzbeck	9120D	01892 P:00331	2020/9/26	2022/9/25
Amplifier	SKET	PA-000318G-45	N/A	2020/10/16	2021/10/15
EMI software	EZ	EZ-EMC	EEMC-3A1	N/A	N/A
Loop antenna	SCHNARZBECK	FMZB1519B	00102	2020/9/26	2022/9/25
Controller	SKET	N/A	N/A	N/A	N/A
Coaxial Cable	BlueAsia	BLA-XC-02	N/A	N/A	N/A
Coaxial Cable	BlueAsia	BLA-XC-03	N/A	N/A	N/A
Coaxial Cable	BlueAsia	BLA-XC-01	N/A	N/A	N/A

Test Equipment Of Power Spectrum Density					
Equipment	**Manufacturer**	**Model**	**S/N**	**Cal.Date**	**Cal.Due**

BlueAsia

Spectrum	R&S	FSP40	100817	2020/10/12	2021/10/11
Spectrum	Agilent	N9020A	MY49100060	2020/10/12	2021/10/11
Signal Generator	Agilent	N5182A	MY49060650	2020/10/12	2021/10/11
Signal Generator	Agilent	E8257D	MY44320250	2020/10/12	2021/10/11

Test Equipment Of Radiated Emissions which fall in the restricted bands

Equipment	Manufacturer	Model	S/N	Cal.Date	Cal.Due
Chamber	SKET	966	N/A	2020/11/10	2023/11/9
Spectrum	R&S	FSP40	100817	2020/10/12	2021/10/11
Receiver	R&S	ESR7	101199	2020/10/12	2021/10/11
broadband Antenna	Schwarzbeck	VULB9168	00836 P:00227	2020/9/26	2022/9/25
Horn Antenna	Schwarzbeck	9120D	01892 P:00331	2020/9/26	2022/9/25
Amplifier	SKET	PA-000318G-45	N/A	2020/10/16	2021/10/15
EMI software	EZ	EZ-EMC	EEMC-3A1	N/A	N/A
Loop antenna	SCHNARZBECK	FMZB1519B	00102	2020/9/26	2022/9/25
Controller	SKET	N/A	N/A	N/A	N/A
Coaxial Cable	BlueAsia	BLA-XC-02	N/A	N/A	N/A
Coaxial Cable	BlueAsia	BLA-XC-03	N/A	N/A	N/A
Coaxial Cable	BlueAsia	BLA-XC-01	N/A	N/A	N/A

Test Equipment Of Conducted Spurious Emissions

Equipment	Manufacturer	Model	S/N	Cal.Date	Cal.Due
Spectrum	R&S	FSP40	100817	2020/10/12	2021/10/11

BlueAsia

Spectrum	Agilent	N9020A	MY49100060	2020/10/12	2021/10/11
Signal Generator	Agilent	N5182A	MY49060650	2020/10/12	2021/10/11
Signal Generator	Agilent	E8257D	MY44320250	2020/10/12	2021/10/11

BlueAsia

10 CONDUCTED PEAK OUTPUT POWER

Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 7.8.5 & Section 11.9.1
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX
Tester	Sven
Temperature	25℃
Humidity	52%

10.1 LIMITS

Frequency range(MHz)	Output power of the intentional radiator(watt)
902-928	1 for ≥50 hopping channels
	0.25 for 25≤ hopping channels <50
	1 for digital modulation
2400-2483.5	1 for ≥75 non-overlapping hopping channels
	0.125 for all other frequency hopping systems
	1 for digital modulation
5725-5850	1 for frequency hopping systems and digital modulation

10.2 BLOCK DIAGRAM OF TEST SETUP



10.3 TEST DATA

Pass: Please Refer To Appendix: For Details

BlueAsia

11 MINIMUM 6DB BANDWIDTH

Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 11.8.1
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX
Tester	Sven
Temperature	25℃
Humidity	52%

11.1 LIMITS

Limit:	≥500 kHz

11.2 BLOCK DIAGRAM OF TEST SETUP



11.3 TEST DATA

Pass: Please Refer To Appendix: For Details

12 CONDUCTED EMISSIONS AT AC POWER LINE (150KHZ-30MHZ)

Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 6.2
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX
Tester	Sven
Temperature	25℃
Humidity	52%

12.1 LIMITS

Frequency of emission(MHz)	Conducted limit(dBμV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50
*Decreases with the logarithm of the frequency.		

12.2 BLOCK DIAGRAM OF TEST SETUP



12.3 PROCEDURE

1) The mains terminal disturbance voltage test was conducted in a shielded room.
2) The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a 50ohm/50H + 5ohm linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded.

3) The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane,
4) The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0.4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0.8 m from the LISN 2.
5) In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10 on conducted measurement.
Remark: LISN=Read Level+ Cable Loss+ LISN Factor

BlueAsia

12.4 TEST DATA

[TestMode: TX]; [Line: Line] [Power:120V/60Hz]



Site
Phase: *L1*
Temperature:
Limit: FCC Class B Conduction(QP)
Power:
Humidity: %
EUT: Android Tv Box
M/N: SDOTT0202
Mode: TX
Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV	dBuV	dB	Detector	Comment
1		0.4980	39.75	9.87	49.62	56.03	-6.41	QP	
2	*	0.4980	33.43	9.87	43.30	46.03	-2.73	AVG	
3		0.5340	37.75	9.87	47.62	56.00	-8.38	QP	
4		0.5340	30.03	9.87	39.90	46.00	-6.10	AVG	
5		0.8540	32.31	9.91	42.22	56.00	-13.78	QP	
6		0.8540	23.36	9.91	33.27	46.00	-12.73	AVG	
7		1.1660	30.47	9.92	40.39	56.00	-15.61	QP	
8		1.1660	20.14	9.92	30.06	46.00	-15.94	AVG	
9		1.5620	32.08	9.93	42.01	56.00	-13.99	QP	
10		1.5620	20.53	9.93	30.46	46.00	-15.54	AVG	
11		2.6099	29.54	9.96	39.50	56.00	-16.50	QP	
12		2.6099	18.42	9.96	28.38	46.00	-17.62	AVG	

*:Maximum data x:Over limit !:over margin (Reference Only

Test Result: Pass

[TestMode: TX]; [Line: Neutral] [Power:120V/60Hz]



Site
Phase: N
Temperature:
Limit: FCC Class B Conduction(QP)
Power:
Humidity: %
EUT: Android Tv Box
M/N: SDOTT0202
Mode: TX
Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV	dBuV	dB	Detector	Comment
1		0.1940	26.57	9.75	36.32	63.86	-27.54	QP	
2		0.1940	19.56	9.75	29.31	53.86	-24.55	AVG	
3		0.5340	39.44	9.79	49.23	56.00	-6.77	QP	
4	*	0.5340	30.64	9.79	40.43	46.00	-5.57	AVG	
5		0.5820	29.87	9.80	39.67	56.00	-16.33	QP	
6		0.5820	20.36	9.80	30.16	46.00	-15.84	AVG	
7		0.9260	32.33	9.83	42.16	56.00	-13.84	QP	
8		0.9260	22.91	9.83	32.74	46.00	-13.26	AVG	
9		1.1260	27.35	9.84	37.19	56.00	-18.81	QP	
10		1.1260	16.98	9.84	26.82	46.00	-19.18	AVG	
11		2.0540	30.58	9.86	40.44	56.00	-15.56	QP	
12		2.0540	18.18	9.86	28.04	46.00	-17.96	AVG	

*:Maximum data x:Over limit !:over margin (Reference Only

Test Result: Pass

13 ANTENNA REQUIREMENT

Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	N/A

13.1 CONCLUSION

Standard Requirement:
An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit permanently attached antenna or of an so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

EUT Antenna:
The antenna is integrated on the main PCB and no consideration of replacement. The best case gain of the antenna is 3.04 dBi.

BlueAsia

14 CONDUCTED BAND EDGES MEASUREMENT

Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 7.8.8 & Section 11.13.3.2
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX
Tester	Sven
Temperature	25℃
Humidity	52%

14.1 LIMITS

Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

14.2 BLOCK DIAGRAM OF TEST SETUP



14.3 TEST DATA

Pass: Please Refer To Appendix: For Details

BlueAsia

15 RADIATED SPURIOUS EMISSIONS

Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 6.4,6.5,6.6
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX
Tester	Sven
Temperature	25℃
Humidity	52%

15.1 LIMITS

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

BlueAsia

15.2 BLOCK DIAGRAM OF TEST SETUP







15.3 PROCEDURE

a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
b. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
c. The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
d. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
e. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
f. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
g. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

h. Test the EUT in the lowest channel, the middle channel, the Highest channel.
i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
j. Repeat above procedures until all frequencies measured was complete.

Remark:
1) For emission below 1GHz, through pre-scan found the worst case is the lowest channel. Only the worst case is recorded in the report.
2) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:
Final Test Level =Receiver Reading + Antenna Factor + Cable Factor - Preamplifier Factor
3) Scan from 9kHz to 25GHz, the disturbance above 12.75GHz and below 30MHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported. Fundamental frequency is blocked by filter, and only spurious emission is shown.
4) For frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.

BlueAsia

15.4 TEST DATA

[TestMode: TX]; [Polarity: Horizontal]

Test Lab: BlueAsia EMC Lab（RE #1）	Project: BLA-EMC-202107-A75-1
EUT: Android Tv Box	Test Engineer:
M/N: SDOTT0202	Temperature:
S/N:	Humidity:
Test Mode: TX mode	Test Voltage:
Note:	Test Data: 2021-08-04 09:37:14



No.	Frequency	Limit dBuV/m	Level dBuV/m	Delta dB	Reading dBuV	Factor dB/m	Detector	Polar	Height cm	Angle deg
1*	42.368MHz	40.0	24.2	-15.8	0.2	24.0	QP	Hor		
2*	109.176MHz	43.5	26.4	-17.1	4.8	21.6	QP	Hor		
3*	157.313MHz	43.5	26.7	-16.8	3.4	23.3	QP	Hor		
4*	262.436MHz	46.0	28.4	-17.6	5.7	22.7	QP	Hor		
5*	412.180MHz	46.0	33.3	-12.7	5.9	27.4	QP	Hor		
6*	948.711MHz	46.0	37.2	-8.8	1.6	35.6	QP	Hor		

Test Result: Pass

[TestMode: TX]; [Polarity: Vertical]

Test Lab: BlueAsia EMC Lab（RE #1）	Project: BLA-EMC-202107-A75-1
EUT: Android TV Box	Test Engineer:
M/N: SDOTT0202	Temperature:
S/N:	Humidity:
Test Mode: TX mode	Test Voltage:
Note:	Test Data: 2021-08-10 10:00:55



No.	Frequency	Limit dBuV/m	Level dBuV/m	Delta dB	Reading dBuV	Factor dB/m	Detector	Polar	Height cm	Angle deg
1*	104.205MHz	43.5	27.0	-16.5	5.9	21.1	QP	Ver		
2*	199.265MHz	43.5	26.9	-16.6	6.3	20.6	QP	Ver		
3*	262.558MHz	46.0	30.6	-15.4	7.8	22.8	QP	Ver		
4*	411.210MHz	46.0	34.0	-12.0	6.6	27.4	QP	Ver		
5*	651.770MHz	46.0	35.7	-10.3	4.1	31.6	QP	Ver		
6*	899.241MHz	46.0	39.7	-6.3	4.7	35.0	QP	Ver		

Test Result: Pass

[TestMode: TX Low channel]; [Polarity: Horizontal]



Site
Limit: FCC Part15 (PK)
EUT: Android Tv Box
M/N: SDOTT0202
Mode: TX-L
Note:

Polarization: *Horizontal*
Power:
Distance:

Temperature:
Humidity: %

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1		4804.000	42.24	3.71	45.95	74.00	-28.05	peak			
2		7206.000	41.76	5.96	47.72	74.00	-26.28	peak			
3	*	9608.000	40.06	9.29	49.35	74.00	-24.65	peak			

*:Maximum data x:Over limit !:over margin (Reference Only

Test Result: Pass

[TestMode: TX Low channel]; [Polarity: Vertical]



Site
Limit: FCC Part15 (PK)
EUT: Android Tv Box
M/N: SDOTT0202
Mode: TX-L
Note:

Polarization: *Vertical*
Power:
Distance:

Temperature:
Humidity: %

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1		4804.000	41.97	3.71	45.68	74.00	-28.32	peak			
2		7206.000	43.02	5.96	48.98	74.00	-25.02	peak			
3	*	9608.000	39.71	9.29	49.00	74.00	-25.00	peak			

*:Maximum data x:Over limit !:over margin (Reference Only

Test Result: Pass

[TestMode: TX middle channel]; [Polarity: Horizontal]



Site
Limit: FCC Part15 (PK)
EUT: Android Tv Box
M/N: SDOTT0202
Mode: TX-M
Note:

Polarization: *Horizontal*
Power:
Distance:

Temperature:
Humidity: %

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1		4884.000	43.13	3.34	46.47	74.00	-27.53	peak			
2		7324.000	40.63	6.44	47.07	74.00	-26.93	peak			
3	*	9768.000	39.46	9.63	49.09	74.00	-24.91	peak			

*:Maximum data x:Over limit !:over margin (Reference Only

Test Result: Pass

[TestMode: TX middle channel]; [Polarity: Vertical]



Site
Limit: FCC Part15 (PK)
EUT: Android Tv Box
M/N: SDOTT0202
Mode: TX-M
Note:

Polarization: *Vertical*
Power:
Distance:

Temperature:
Humidity: %

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1		4884.000	42.98	3.34	46.32	74.00	-27.68	peak			
2		7326.000	41.25	6.44	47.69	74.00	-26.31	peak			
3	*	9768.000	40.00	9.63	49.63	74.00	-24.37	peak			

*:Maximum data x:Over limit !:over margin (Reference Only

Test Result: Pass

[TestMode: TX high channel]; [Polarity: Horizontal]



Site
Limit: FCC Part15 (PK)
EUT: Android Tv Box
M/N: SDOTT0202
Mode: TX-H
Note:

Polarization: *Horizontal*
Power:
Distance:

Temperature:
Humidity: %

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1		4882.000	42.50	3.36	45.86	74.00	-28.14	peak			
2		7324.000	40.75	6.44	47.19	74.00	-26.81	peak			
3	*	9768.000	40.09	9.63	49.72	74.00	-24.28	peak			

*:Maximum data x:Over limit !:over margin (Reference Only

Test Result: Pass

[TestMode: TX high channel]; [Polarity: Vertical]



Site
Limit: FCC Part15 (PK)
EUT: Android Tv Box
M/N: SDOTT0202
Mode: TX-H
Note:

Polarization: *Vertical*
Power:
Distance:

Temperature:
Humidity: %

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1		4884.000	42.45	3.34	45.79	74.00	-28.21	peak			
2		7326.000	42.13	6.44	48.57	74.00	-25.43	peak			
3	*	9768.000	41.29	9.63	50.92	74.00	-23.08	peak			

*:Maximum data x:Over limit !:over margin (Reference Only

Test Result: Pass

16 POWER SPECTRUM DENSITY

Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 11.10.2
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX
Tester	Sven
Temperature	25℃
Humidity	52%

16.1 LIMITS

Limit:	≤8dBm in any 3 kHz band during any time interval of continuous transmission

16.2 BLOCK DIAGRAM OF TEST SETUP



16.3 TEST DATA

Pass: Please Refer To Appendix: For Details

17 RADIATED EMISSIONS WHICH FALL IN THE RESTRICTED BANDS

Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 6.10.5
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX
Tester	Sven
Temperature	25℃
Humidity	52%

17.1 LIMITS

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

BlueAsia

17.2 BLOCK DIAGRAM OF TEST SETUP







17.3 PROCEDURE

a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
b. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
c. The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
d. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
e. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
f. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
g. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

h. Test the EUT in the lowest channel, the middle channel, the Highest channel.
i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
j. Repeat above procedures until all frequencies measured was complete.
Remark 1: Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor
Remark 2: For frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.

BlueAsia

17.4 TEST DATA

[TestMode: TX low channel]; [Polarity: Horizontal]



Site	Polarization: ***Horizontal***	Temperature:
Limit: FCC Part15 (PK)	Power:	Humidity: %
EUT: Android Tv Box	Distance:	
M/N: SDOTT0202		
Mode: TX-L		
Note:		

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1	*	2310.000	45.72	-4.61	41.11	74.00	-32.89	peak			
2		2390.000	45.36	-4.27	41.09	74.00	-32.91	peak			

*:Maximum data x:Over limit !:over margin 〈Reference Only

Test Result: Pass

[TestMode: TX low channel]; [Polarity: Vertical]



Site
Limit: FCC Part15 (PK)
EUT: Android Tv Box
M/N: SDOTT0202
Mode: TX-L
Note:

Polarization: *Vertical*
Power:
Distance:

Temperature:
Humidity: %

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1	*	2310.000	45.60	-4.61	40.99	74.00	-33.01	peak			
2		2390.000	44.93	-4.27	40.66	74.00	-33.34	peak			

*:Maximum data x:Over limit !:over margin 〈Reference Only

Test Result: Pass

[TestMode: TX high channel]; [Polarity: Horizontal]



Site
Limit: FCC Part15 (PK)
EUT: Android Tv Box
M/N: SDOTT0202
Mode: TX-H
Note:

Polarization: ***Horizontal***
Power:
Distance:

Temperature:
Humidity: %

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1		2483.500	64.29	-3.84	60.45	74.00	-13.55	peak			
2	*	2483.500	57.00	-3.84	53.16	54.00	-0.84	AVG			
3		2500.000	45.81	-3.78	42.03	74.00	-31.97	peak			

*:Maximum data x:Over limit !:over margin 〈Reference Only

Test Result: Pass

[TestMode: TX high channel]; [Polarity: Vertical]



Site
Limit: FCC Part15 (PK)
EUT: Android Tv Box
M/N: SDOTT0202
Mode: TX-H
Note:

Polarization: *Vertical*
Power:
Distance:

Temperature:
Humidity: %

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1		2483.500	60.99	-3.84	57.15	74.00	-16.85	peak			
2	*	2483.500	52.15	-3.84	48.31	54.00	-5.69	AVG			
3		2500.000	47.89	-3.78	44.11	74.00	-29.89	peak			

*:Maximum data x:Over limit !:over margin 〈Reference Only

Test Result: Pass

18 CONDUCTED SPURIOUS EMISSIONS

Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 7.8.6 & Section 11.11
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX
Tester	Sven
Temperature	25℃
Humidity	52%

18.1 LIMITS

Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

18.2 BLOCK DIAGRAM OF TEST SETUP



18.3 TEST DATA

Pass: Please Refer To Appendix: For Details

BlueAsia

19 APPENDIX

Maximum Conducted Output Power

Condition	Mode	Frequency (MHz)	Antenna	Conducted Power (dBm)	Limit (dBm)	Verdict
NVNT	BLE 1M	2402	Ant1	4.128	30	Pass
NVNT	BLE 1M	2442	Ant1	4.683	30	Pass
NVNT	BLE 1M	2480	Ant1	5.434	30	Pass

Power NVNT BLE 1M 2402MHz Ant1



Power NVNT BLE 1M 2442MHz Ant1



Power NVNT BLE 1M 2480MHz Ant1



-6dB Bandwidth

Condition	Mode	Frequency (MHz)	Antenna	-6 dB Bandwidth (MHz)	Limit -6 dB Bandwidth (MHz)	Verdict
NVNT	BLE 1M	2402	Ant1	0.681	0.5	Pass
NVNT	BLE 1M	2442	Ant1	0.684	0.5	Pass
NVNT	BLE 1M	2480	Ant1	0.682	0.5	Pass

-6dB Bandwidth NVNT BLE 1M 2402MHz Ant1



-6dB Bandwidth NVNT BLE 1M 2442MHz Ant1



-6dB Bandwidth NVNT BLE 1M 2480MHz Ant1



Occupied Channel Bandwidth

Condition	Mode	Frequency (MHz)	Antenna	99% OBW (MHz)
NVNT	BLE 1M	2402	Ant1	1.051819362
NVNT	BLE 1M	2442	Ant1	1.053953235
NVNT	BLE 1M	2480	Ant1	1.053126337

OBW NVNT BLE 1M 2402MHz Ant1



OBW NVNT BLE 1M 2442MHz Ant1



OBW NVNT BLE 1M 2480MHz Ant1



Maximum Power Spectral Density Level

Condition	Mode	Frequency (MHz)	Antenna	Max PSD (dBm)	Limit (dBm)	Verdict
NVNT	BLE 1M	2402	Ant1	-6.814	8	Pass
NVNT	BLE 1M	2442	Ant1	-6.249	8	Pass
NVNT	BLE 1M	2480	Ant1	-5.502	8	Pass

PSD NVNT BLE 1M 2402MHz Ant1



PSD NVNT BLE 1M 2442MHz Ant1

PSD NVNT BLE 1M 2480MHz Ant1

Band Edge

Condition	Mode	Frequency (MHz)	Antenna	Max Value (dBc)	Limit (dBc)	Verdict
NVNT	BLE 1M	2402	Ant1	-58.25	-30	Pass
NVNT	BLE 1M	2480	Ant1	-59.5	-30	Pass

Band Edge NVNT BLE 1M 2402MHz Ant1 Ref



Band Edge NVNT BLE 1M 2402MHz Ant1 Emission



Band Edge NVNT BLE 1M 2480MHz Ant1 Ref

Band Edge NVNT BLE 1M 2480MHz Ant1 Emission

Conducted RF Spurious Emission

Condition	Mode	Frequency (MHz)	Antenna	Max Value (dBc)	Limit (dBc)	Verdict
NVNT	BLE 1M	2402	Ant1	-48.18	-30	Pass
NVNT	BLE 1M	2442	Ant1	-49.37	-30	Pass
NVNT	BLE 1M	2480	Ant1	-49.66	-30	Pass

Tx. Spurious NVNT BLE 1M 2402MHz Ant1 Ref



Tx. Spurious NVNT BLE 1M 2402MHz Ant1 Emission



Tx. Spurious NVNT BLE 1M 2442MHz Ant1 Ref



Tx. Spurious NVNT BLE 1M 2442MHz Ant1 Emission

Tx. Spurious NVNT BLE 1M 2480MHz Ant1 Ref



Tx. Spurious NVNT BLE 1M 2480MHz Ant1 Emission

APPENDIX A: PHOTOGRAPHS OF EUT

(Reference to the report NO.BLA-EMC-202107-A7501)

----END OF REPORT----

The test report is effective only with both signature and specialized stamp, The result(s) shown in this report refer only to the sample(s) tested. Without written approval of BlueAsia, this report can't be reproduced except in full.

BlueAsia